

Indexes

- **Alphanumeric**
- **Functional/Selection Guide**

1

ALPHANUMERIC INDEX

TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE	TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†
SN5400	SN7400	6-2	5-6	SN54LS14	SN74LS14	6-14	5-9
SN54H00	SN74H00	6-2	5-6	SN54H15	SN74H15	6-12	5-10
SN54L00	SN74L00	6-2	5-6	SN54LS15	SN74LS15	6-12	5-10
SN54LS00	SN74LS00	6-2	5-6	SN54S15	SN74S15	6-12	5-10
SN54S00	SN74S00	6-2	5-6	SN5416	SN7416	6-24	5-10
SN5401	SN7401	6-4	5-6	SN5417	SN7417	6-24	5-10
SN54H01	SN74H01	6-4	5-6	SN5420	SN7420	6-2	5-10
SN54L01		6-4	5-6	SN54H20	SN74H20	6-2	5-10
SN54LS01	SN74LS01	6-4	5-6	SN54L20	SN74L20	6-2	5-10
SN5402	SN7402	6-8	5-6	SN54LS20	SN74LS20	6-2	5-10
SN54L02	SN74L02	6-8	5-6	SN54S20	SN74S20	6-2	5-10
SN54LS02	SN74LS02	6-8	5-6	SN54H21	SN74H21	6-10	5-11
SN54S02	SN74S02	6-8	5-6	SN54LS21	SN74LS21	6-10	5-11
SN5403	SN7403	6-4	5-7	SN5422	SN7422	6-4	5-11
SN54L03	SN74L03	6-4	5-7	SN54H22	SN74H22	6-4	5-11
SN54LS03	SN74LS03	6-4	5-7	SN54LS22	SN74LS22	6-4	5-11
SN54S03	SN74S03	6-4	5-7	SN54S22	SN74S22	6-4	5-11
SN5404	SN7404	6-2	5-7	SN5423	SN7423	6-39	5-11
SN54H04	SN74H04	6-2	5-7	SN5425	SN7425	6-8	5-11
SN54L04	SN74L04	6-2	5-7	SN5426	SN7426	6-24	5-12
SN54LS04	SN74LS04	6-2	5-7	SN54LS26	SN74LS26	6-26	5-12
SN54S04	SN74S04	6-2	5-7	SN5427	SN7427	6-8	5-12
SN5405	SN7405	6-4	5-7	SN54LS27	SN74LS27	6-8	5-12
SN54H05	SN74H05	6-4	5-7	SN5428	SN7428	6-20	5-12
SN54LS05	SN74LS05	6-4	5-7	SN54LS28	SN74LS28	6-20	5-12
SN54S05	SN74S05	6-4	5-7	SN5430	SN7430	6-2	5-12
SN5406	SN7406	6-24	5-7	SN54H30	SN74H30	6-2	5-12
SN5407	SN7407	6-24	5-8	SN54L30	SN74L30	6-2	5-12
SN5408	SN7408	6-10	5-8	SN54LS30	SN74LS30	6-2	5-12
SN54LS08	SN74LS08	6-10	5-8	SN54S30	SN74S30	6-2	5-12
SN54S08	SN74S08	6-10	5-8	SN5432	SN7432	6-28	5-13
SN5409	SN7409	6-12	5-8	SN54LS32	SN74LS32	6-28	5-13
SN54LS09	SN74LS09	6-12	5-8	SN54S32	SN74S32	6-28	5-13
SN54S09	SN74S09	6-12	5-8	SN5433	SN7433	6-24	5-13
SN5410	SN7410	6-2	5-8	SN54LS33	SN74LS33	6-26	5-13
SN54H10	SN74H10	6-2	5-8	SN5437	SN7437	6-20	5-13
SN54L10	SN74L10	6-2	5-8	SN54LS37	SN74LS37	6-20	5-13
SN54LS10	SN74LS10	6-2	5-8	SN54S37	SN74S37	6-20	5-13
SN54S10	SN74S10	6-2	5-8	SN5438	SN7438	6-24	5-13
SN54H11	SN74H11	6-10	5-9	SN54LS38	SN74LS38	6-26	5-13
SN54LS11	SN74LS11	6-10	5-9	SN54S38	SN74S38	6-26	5-13
SN54S11	SN74S11	6-10	5-9	SN5440	SN7440	6-20	5-14
SN5412	SN7412	6-4	5-9	SN54H40	SN74H40	6-20	5-14
SN54LS12	SN74LS12	6-4	5-9	SN54LS40	SN74LS40	6-20	5-14
SN5413	SN7413	6-14	5-9	SN54S40	SN74S40	6-20	5-14
SN54LS13	SN74LS13	6-14	5-9	SN5442A	SN7442A	7-15	7-15
SN5414	SN7414	6-14	5-9	SN54L42	SN74L42	7-15	7-15

1

†See Bipolar Microcomputer Components Data Book, LCC4270.

ALPHANUMERIC INDEX

1

TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†	TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†
SN54LS42	SN74LS42	7-15	7-15	SN54L73	SN74L73	6-54	5-22
SN5443A	SN7443A	7-15	7-15	SN54LS73	SN74LS73	6-56	5-22
SN54L43	SN74L43	7-15	7-15	SN5474	SN7474	6-46	5-22
SN5444A	SN7444A	7-15	7-15	SN54H74	SN74H74	6-60	5-22
SN54L44	SN74L44	7-15	7-15	SN54L74	SN74L74	6-54	5-22
SN5445	SN7445	7-20	7-20	SN54LS74A	SN74LS74A	6-56	5-22
SN5446A	SN7446A	7-22	7-22	SN54S74	SN74S74	6-58	5-22
SN54L46	SN74L46	7-22	7-22	SN5475	SN7475	7-35	7-35
SN5447A	SN7447A	7-22	7-22	SN54L75	SN74L75	7-35	7-35
SN54L47	SN74L47	7-22	7-22	SN54LS75	SN74LS75	7-35	7-35
SN54LS47	SN74LS47	7-22	7-22	SN5476	SN7476	6-46	5-23
SN5448	SN7448	7-22	7-22	SN54H76	SN74H76	6-60	5-23
SN54LS48	SN74LS48	7-22	7-22	SN54LS76	SN74LS76	6-56	5-23
SN5449		7-22	7-22	SN5477		7-35	7-35
SN54LS49	SN74LS49	7-22	7-22	SN54L77		7-35	7-35
SN5450	SN7450	6-39	5-16	SN54LS77		7-35	7-35
SN54H50	SN74H50	6-39	5-16	SN54H78	SN74H78	6-50	5-24
SN5451	SN7451	6-30	5-16	SN54L78	SN74L78	6-54	5-24
SN54H51	SN74H51	6-30	5-16	SN54LS78	SN74LS78	6-56	5-24
SN54L51	SN74L51	6-30	5-16	SN5480	SN7480	7-41	7-41
SN54LS51	SN74LS51	6-30	5-16	SN5481A	SN7481A	7-44	7-44
SN54S51	SN74S51	6-30	5-16	SN5482	SN7482	7-49	7-49
SN54H52	SN74H52	6-39	5-17	SN5483A	SN7483A	7-53	7-53
SN5453	SN7453	6-39	5-17	SN54LS83A	SN74LS83A	7-53	7-53
SN54H53	SN74H53	6-39	5-17	SN5484A	SN7484A	7-44	7-44
SN5454	SN7454	6-30	5-18	SN5485	SN7485	7-57	7-57
SN54H54	SN74H54	6-30	5-18	SN54L85	SN74L85	7-57	7-57
SN54L54	SN74L54	6-30	5-18	SN54LS85	SN74LS85	7-57	7-57
SN54LS54	SN74LS54	6-30	5-18	SN54S85	SN74S85	7-57	7-57
SN54H55	SN74H55	6-39	5-19	SN5486	SN7486	7-65	7-65
SN54L55	SN74L55	6-30	5-19	SN54L86	SN74L86	7-65	7-65
SN54LS55	SN74LS55	6-30	5-19	SN54LS86	SN74LS86	7-65	7-65
SN5460	SN7460	6-43	5-19	SN54S86	SN74S86	7-65	7-65
SN54H60	SN74H60	6-44	5-19	SN54H87	SN74H87	7-70	7-70
SN54H61	SN74H61	6-45	5-19	SN5488A	SN7488A	†	5-27
SN54H62	SN74H62	6-44	5-20		SN7489	†	5-27
SN54LS63	SN74LS63	6-62	5-20	SN5490A	SN7490A	7-72	7-72
SN54S64	SN74S64	6-30	5-20	SN54L90	SN74L90	7-72	7-72
SN54S65	SN74S65	6-32	5-20	SN54LS90	SN74LS90	7-72	7-72
SN5470	SN7470	6-46	5-21	SN5491A	SN7491A	7-81	7-81
SN54H71	SN74H71	6-50	5-21	SN54L91	SN74L91	7-81	7-81
SN54L71	SN74L71	6-54	5-21	SN54LS91	SN74LS91	7-81	7-81
SN5472	SN7472	6-46	5-22	SN5492A	SN7492A	7-72	7-72
SN54H72	SN74H72	6-50	5-22	SN54LS92	SN74LS92	7-72	7-72
SN54L72	SN74L72	6-54	5-22	SN5493A	SN7493A	7-72	7-72
SN5473	SN7473	6-46	5-22	SN54L93	SN74L93	7-72	7-72
SN54H73	SN74H73	6-50	5-22	SN54LS93	SN74LS93	7-72	7-72

†See Bipolar Microcomputer Components Data Book, LCC4270.

ALPHANUMERIC INDEX

TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†	TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†
SN5494	SN7494	7-86	7-86	SN54S132	SN74S132	6-14	5-32
SN5495A	SN7495A	7-89	7-89	SN54S133	SN74S133	6-2	5-38
SN54L95	SN74L95	7-89	7-89	SN54S134	SN74S134	6-33	5-38
SN54LS95B	SN74LS95B	7-89	7-89	SN54S135	SN74S135	7-129	7-129
SN5496	SN7496	7-95	7-95	SN54136	SN74136	7-131	7-131
SN54L96	SN74L96	7-95	7-95	SN54LS136	SN74LS136	7-131	7-131
SN54LS96	SN74LS96	7-95	7-95	SN54LS138	SN74LS138	7-134	7-134
SN5497	SN7497	7-102	7-102	SN54S138	SN74S138	7-134	7-134
SN54L98	SN74L98	7-107	7-107	SN54LS139	SN74LS139	7-134	7-134
SN54L99	SN74L99	7-109	7-109	SN54S139	SN74S139	7-134	7-134
SN54100	SN74100	7-113	7-113	SN54S140	SN74S140	6-22	5-39
SN54H101	SN74H101	6-52	5-31		SN74141	7-138	7-138
SN54H102	SN74H102	6-52	5-31		SN74142	7-140	7-140
SN54H103	SN74H103	6-52	5-31	SN54143	SN74143	7-143	7-143
SN54H106	SN74H106	6-52	5-32	SN54144	SN74144	7-143	7-143
SN54107	SN74107	6-46	5-32	SN54145	SN74145	7-148	7-148
SN54LS107	SN74LS107	6-56	5-32	SN54LS145	SN74LS145	7-148	7-148
SN54H108	SN74H108	6-52	5-32	SN54147	SN74147	7-151	7-151
SN54109	SN74109	6-46	5-33	SN54LS147	SN74LS147	7-151	7-151
SN54LS109A	SN74LS109A	6-56	5-33	SN54148	SN74148	7-151	7-151
SN54110	SN74110	6-46	5-33	SN54LS148	SN74LS148	7-151	7-151
SN54111	SN74111	6-46	5-33	SN54150	SN74150	7-157	7-157
SN54LS112	SN74LS112	6-56	5-34	SN54151A	SN74151A	7-157	7-157
SN54S112	SN74S112	6-58	5-34	SN54LS151	SN74LS151	7-157	7-157
SN54LS113	SN74LS113	6-56	5-34	SN54S151	SN74S151	7-157	7-157
SN54S113	SN74S113	6-58	5-34	SN54152A		7-157	7-157
SN54LS114	SN74LS114	6-56	5-34	SN54LS152		7-157	7-157
SN54S114	SN74S114	6-56	5-34	SN54153	SN74153	7-165	7-165
SN54116	SN74116	7-115	7-115	SN54L153	SN74L153	7-165	7-165
SN54120	SN74120	7-118	7-118	SN54LS153	SN74LS153	7-165	7-165
SN54121	SN74121	6-64	5-35	SN54S153	SN74S153	7-165	7-165
SN54L121	SN74L121	6-64	5-35	SN54154	SN74154	7-171	7-171
SN54122	SN74122	6-76	5-36	SN54L154	SN74L154	7-171	7-171
SN54L122	SN74L122	6-76	5-36	SN54155	SN74155	7-175	7-175
SN54LS122	SN74LS122	6-76	5-36	SN54LS155	SN74LS155	7-175	7-175
SN54123	SN74123	6-76	5-36	SN54156	SN74156	7-175	7-175
SN54L123	SN74L123	6-76	5-36	SN54LS156	SN74LS156	7-175	7-175
SN54LS123	SN74LS123	6-76	5-36	SN54157	SN74157	7-181	7-181
SN54LS124	SN74LS124	7-123	7-123	SN54L157	SN74L157	7-181	7-181
SN54S124	SN74S124	7-123	7-123	SN54LS157	SN74LS157	7-181	7-181
SN54125	SN74125	6-33	5-37	SN54S157	SN74S157	7-181	7-181
SN54LS125	SN74LS125	6-33	5-37	SN54LS158	SN74LS158	7-181	7-181
SN54126	SN74126	6-33	5-37	SN54S158	SN74S158	7-181	7-181
SN54LS126	SN74LS126	6-33	5-37	SN54159	SN74159	7-188	7-188
SN54128	SN74128	6-22	5-37	SN54160	SN74160	7-190	7-190
SN54132	SN74132	6-14	5-37	SN54LS160A	SN74LS160A	7-190	7-190
SN54LS132	SN74LS132	6-14	5-37	SN54161	SN74161	7-190	7-190

†See Bipolar Microcomputer Components Data Book, LCC4270.

ALPHANUMERIC INDEX

1

TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†	TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†
SN54LS161A	SN74LS161A	7-190	7-190	SN54S188	SN74S188	†	5-49
SN54162	SN74162	7-190	7-190	SN54S189	SN74S189	†	5-49
SN54LS162A	SN74LS162A	7-190	7-190	SN54190	SN74190	7-296	7-296
SN54S162	SN74S162	7-190	7-190	SN54LS190	SN74LS190	7-296	7-296
SN54163	SN74163	7-190	7-190	SN54191	SN74191	7-296	7-296
SN54LS163A	SN74LS163A	7-190	7-190	SN54LS191	SN74LS191	7-296	7-296
SN54S163	SN74S163	7-190	7-190	SN54192	SN74192	7-306	7-306
SN54164	SN74164	7-206	7-206	SN54L192	SN74L192	7-306	7-306
SN54LS164	SN74LS164	7-206	7-206	SN54LS192	SN74LS192	7-306	7-306
SN54165	SN74165	7-212	7-212	SN54193	SN74193	7-306	7-306
SN54LS165	SN74LS165	7-212	7-212	SN54L193	SN74L193	7-306	7-306
SN54166	SN74166	7-217	7-217	SN54LS193	SN74LS193	7-306	7-306
SN54LS166	SN74LS166	7-217	7-217	SN54194	SN74194	7-316	7-316
SN54167	SN74167	7-222	7-222	SN54LS194A	SN74LS194A	7-316	7-316
SN54LS168A	SN74LS168A	7-226	7-226	SN54S194	SN74S194	7-316	7-316
SN54S168	SN74S168	7-226	7-226	SN54195	SN74195	7-324	7-324
SN54LS169A	SN74LS169A	7-226	7-226	SN54LS195A	SN74LS195A	7-324	7-324
SN54S169	SN74S169	7-226	7-226	SN54S195	SN74S195	7-324	7-324
SN54170	SN74170	7-237	7-237	SN54196	SN74196	7-331	7-331
SN54LS170	SN74LS170	7-237	7-237	SN54LS196	SN74LS196	7-331	7-331
	SN74172	7-245	7-245	SN54S196	SN74S196	7-331	7-331
SN54173	SN74173	7-249	7-249	SN54197	SN74197	7-331	7-331
SN54LS173	SN74LS173	7-249	7-249	SN54LS197	SN74LS197	7-331	7-331
SN54174	SN74174	7-253	7-253	SN54S197	SN74S197	7-331	7-331
SN54LS174	SN74LS174	7-253	7-253	SN54198	SN74198	7-338	7-338
SN54S174	SN74S174	7-253	7-253	SN54199	SN74199	7-338	7-339
SN54175	SN74175	7-253	7-253	SN54LS200A	SN74LS200A	†	5-52
SN54LS175	SN74LS175	7-253	7-253	SN54S200A	SN74S200A	†	5-52
SN54S175	SN74S175	7-253	7-253	SN54S201	SN74S201	†	5-52
SN54176	SN74176	7-259	7-259	SN54LS202	SN74LS202	†	5-52
SN54177	SN74177	7-259	7-259	SN54LS207	SN74LS207	†	5-52
SN54178	SN74178	7-265	7-265	SN54S207	SN74S207	†	5-53
SN54179	SN74179	7-265	7-265	SN54LS208	SN74LS208	†	5-53
SN54180	SN74180	7-269	7-269	SN54S208	SN74S208	†	5-53
SN54181	SN74181	7-271	7-271	SN54LS214	SN74LS214	†	5-53
SN54LS181	SN74LS181	7-271	7-271	SN54S214	SN74S214	†	5-53
SN54S181	SN74S181	7-271	7-271	SN54LS215	SN74LS215	†	5-53
SN54182	SN74182	7-282	7-282	SN54221	SN74221	6-68	5-54
SN54S182	SN74S182	7-282	7-282	SN54LS221	SN74LS221	6-68	5-54
SN54LS183	SN74LS183	7-282	7-282		SN74S225	†	5-54
SN54H183	SN74H183	7-287	7-287	SN54S226	SN74S226	7-345	7-345
SN54184	SN74184	7-290	7-290	SN54LS240	SN74LS240	6-83	5-54
SN54185A	SN74185A	7-290	7-290	SN54S240	SN74S240	6-83	5-54
SN54186	SN74186	†	5-49	SN54LS241	SN74LS241	6-83	5-55
SN54187	SN74187	†	5-49	SN54S241	SN74S241	6-83	5-55
SN54188A	SN74188A	†	5-49	SN54LS242	SN74LS242	6-87	5-55
				SN54LS243	SN74LS243	6-87	5-55

†See Bipolar Microcomputer Components Data Book, LCC4270.

ALPHANUMERIC INDEX

TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†	TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†
SN54LS244	SN74LS244	6-83	5-55	SN54293	SN74293	7-423	7-423
SN54LS245	SN74LS245	7-349	7-349	SN54LS293	SN74LS293	7-423	7-423
SN54246	SN74246	7-351	7-351	SN54LS295B	SN74LS295B	7-429	7-429
SN54247	SN74247	7-351	7-351	SN54298	SN74298	7-432	7-432
SN54LS247	SN74LS247	7-351	7-351	SN54LS298	SN74LS298	7-432	7-432
SN54248	SN74248	7-351	7-351	SN54LS299	SN74S299	7-437	7-437
SN54LS248	SN74LS248	7-351	7-351	SN54S299	SN74S299	7-437	7-437
SN54249	SN74249	7-351	7-351	SN54LS300A	SN74LS300A	†	5-64
SN54LS249	SN74LS249	7-351	7-351	SN54S300A	SN74S300A	†	5-64
SN54251	SN74251	7-362	7-362	SN54S301	SN74S301	†	5-64
SN54LS251	SN74LS251	7-362	7-362	SN54LS302	SN74LS302	†	5-64
SN54S251	SN74S251	7-362	7-362	SN54LS314	SN74LS314	†	5-64
SN54LS253	SN74LS253	7-369	7-369	SN54S314	SN74S314	†	5-65
SN54LS257A	SN74LS257A	7-372	7-372	SN54LS315	SN74LS315	†	5-65
SN54S257	SN74S257	7-372	7-372	SN54LS323	SN74LS323	7-443	7-443
SN54LS258A	SN74LS258A	7-372	7-372	SN54LS324	SN74LS324	7-445	7-445
SN54S258	SN74S258	7-372	7-372	SN54LS325	SN74LS325	7-445	7-445
SN54259	SN74259	7-376	7-376	SN54LS326	SN74LS326	7-445	7-445
SN54LS259	SN74LS259	7-376	7-376	SN54LS327	SN74LS327	7-445	7-445
SN54S260	SN74S260	6-8	5-58	SN54LS348	SN74LS348	7-448	7-448
SN54LS261	SN74LS261	7-380	7-380		SN74351	7-451	7-451
SN54265	SN74265	6-89	5-58	SN54LS352	SN74LS352	7-454	7-454
SN54LS266	SN74LS266	7-386	7-386	SN54LS353	SN74LS353	7-457	7-457
SN54S270	SN74S270	†	5-59		SN74LS362	7-460	7-460
SN54S271	SN74S271	†	5-59	SN54LS363	SN74LS363	7-467	7-467
SN54273	SN74273	7-388	7-388	SN54LS364	SN74LS364	7-467	7-467
SN54LS273	SN74LS273	7-388	7-388	SN54365A	SN74365A	6-36	5-68
SN54S274	SN74S274	7-388	7-391	SN54LS365	SN74LS365	6-36	5-68
SN54LS275	SN74LS275	7-391	7-391	SN54366A	SN74366A	6-36	5-68
SN54S275	SN74S275	7-391	7-391	SN54LS366	SN74LS366	6-36	5-68
SN54276	SN74276	7-401	7-401	SN54367A	SN74367A	6-36	5-69
SN54278	SN74278	7-403	7-403	SN54LS367	SN74LS367	6-36	5-69
SN54279	SN74279	6-60	5-60	SN54368A	SN74368A	6-36	5-69
SN54LS279	SN74LS279	6-60	5-60	SN54LS368	SN74LS368	6-36	5-69
SN54LS280	SN74LS280	7-406	7-406	SN54S370	SN74S370	†	5-69
SN54S280	SN74S280	7-406	7-406	SN54S371	SN74S371	†	5-69
SN54S281	SN74S281	7-410	7-410	SN54LS373	SN74LS373	7-471	7-471
SN54283	SN74283	7-415	7-415	SN54S373	SN74S373	7-471	7-471
SN54LS283	SN74LS283	7-415	7-415	SN54LS374	SN74LS374	7-471	7-471
SN54S283	SN74S283	7-415	7-415	SN54S374	SN74S374	7-471	7-471
SN54284	SN74284	7-420	7-420	SN54LS375	SN74LS375	7-478	7-478
SN54285	SN74285	7-420	7-420	SN54376	SN74376	7-479	7-479
SN54S287	SN74S287	†	5-62	SN54LS377	SN74LS377	7-481	7-481
SN54S288	SN74S288	†	5-62	SN54LS378	SN74LS378	7-481	7-481
SN54S289	SN74S289	†	5-62	SN54LS379	SN74LS379	7-481	7-481
SN54290	SN74290	7-423	7-423	SN54S381	SN74S381	7-484	7-484
SN54LS290	SN74LS290	7-423	7-423	SN54LS386	SN74LS386	7-487	7-487

†See Bipolar Microcomputer Components Data Book, LCC4270.

ALPHANUMERIC INDEX

1

TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE†	TYPE NUMBERS		ELECTRICAL PAGE†	PIN ASSIGNMENTS PAGE
SN54S387	SN74S387	†	5-72	SN54S472	SN74S472	†	5-76
SN54390	SN74390	7-489	7-489	SN54S473	SN74S473	†	5-76
SN54LS390	SN74LS390	7-489	7-489	SN54S474	SN74S474	†	5-76
SN54393	SN74393	7-489	7-489	SN54S475	SN74S475	†	5-76
SN54LS393	SN74LS393	7-489	7-489	SN54S481	SN74S481	†	5-76
SN54LS395A	SN74LS395A	7-496	7-496	SN54S482	SN74S482	†	5-77
SN54LS398	SN74LS398	7-499	7-499	SN54490	SN74490	7-520	7-520
SN54LS399	SN74LS399	7-499	7-499	SN54LS490	SN74LS490	7-520	7-520
SN54S412	SN74S412	7-502	7-502	SN54LS670	SN74LS670	7-526	7-526
	SN74LS424	7-507	7-507	TIM8224		7-507	7-507
SN54425	SN74425	6-33	5-74	TIM8228		7-514	7-514
SN54426	SN74426	6-33	5-75	TIM8238		7-514	7-514
	SN74S428	7-514	7-514	TIM9904		7-460	7-460
	SN74S438	7-514	7-514	TIM9905		7-362	7-362
SN54S470	SN74S470	†	5-75	TIM9906		7-376	7-376
SN54S471	SN74S471	†	5-75	TIM9907		7-151	7-151

†See Bipolar Microcomputer Components Data Book, LCC4270.

FUNCTIONAL INDEX/SELECTION GUIDE

The following pages contain functional indexes and selection guides designed to simplify the choice of a particular function to fit a specific application. Essential characteristics of similar or like functions are grouped for comparative analysis, and the electrical specifications are referenced by page number. The following categories of functions are covered:

SSI FUNCTIONS	Page
Positive-NAND gates and inverters with totem-pole outputs	1-10
Positive-NAND gates and inverters with open-collector outputs	1-10
Positive-NOR gates with totem-pole outputs	1-11
Positive-AND gates with totem-pole outputs	1-11
Positive-AND gates with open-collector outputs	1-11
Schmitt-trigger positive-NAND gates and inverters with totem-pole outputs	1-11
Buffers/clock drivers with totem-pole outputs	1-12
50-ohm/75-ohm line drivers	1-12
Buffer and interface gates with open-collector outputs	1-12
Gates, buffers, drivers and bus transceivers with 3-state outputs	1-13
Positive-OR gates with totem-pole outputs	1-14
AND-OR-INVERT gates with totem-pole outputs	1-14
AND-OR-INVERT gates with open-collector outputs	1-14
Expandable gates	1-14
Expanders	1-14
Dual J-K edge-triggered flip-flops	1-15
Single J-K edge-triggered flip-flops	1-15
Pulse-triggered dual flip-flops	1-16
Pulse-triggered single flip-flops	1-16
Dual J-K flip-flops with data lockout	1-16
Single J-K flip-flops with data lockout	1-16
Dual D-type flip-flops	1-16
S-R latches	1-17
Current-sensing gates	1-17
Monostable multivibrators with Schmitt-trigger inputs	1-17
Retriggerable monostable multivibrators	1-17
Clock generator circuits	1-17
MSI/LSI FUNCTIONS	
Adders	1-18
Accumulators, arithmetic logic units, look-ahead carry generators	1-18
Multipliers	1-18
Comparators	1-18
Parity generators/checkers	1-19
Other arithmetic operators	1-19
Quad, hex, and octal flip-flops	1-19
Register files	1-19
Shift registers	1-20
Other registers	1-20
Latches	1-21
Clock generator circuits	1-21
Code converters	1-21
Priority encoders/registers	1-22
Data selectors/multiplexers	1-22
Decoders/demultiplexers	1-23
Open-collector display decoders/drivers with counters/latches	1-23
Open-collector display decoders/drivers	1-24
Bus transceivers and drivers	1-25
Asynchronous counters (ripple clock)—negative-edge triggered	1-25
Synchronous counters—Positive-edge triggered	1-26
Bipolar bit-slice processor elements	1-26
First-in first-out memories (FIFO's)	1-26
Random-access read/write memories (RAM's)	1-27
Read-only memories (ROM's)	1-27
Programmable-read-only memories (PROM's)	1-28
Microprocessor controllers and support functions	1-28

1

SSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

POSITIVE-NAND GATES AND INVERTERS WITH TOTEM-POLE OUTPUTS
ELECTRICAL TABLES – PAGE 6-2

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
HEX INVERTERS	3 ns	19 mW	SN54S04	J, W	SN74S04	J, N	5-7
	6 ns	22 mW	SN54H04	J, W	SN74H04	J, N	
	9.5 ns	2 mW	SN54LS04	J, W	SN74LS04	J, N	
	10 ns	10 mW	SN5404	J, W	SN7404	J, N	
	33 ns	1 mW	SN54L04	J, T	SN74L04	J, N	
QUADRUPLE 2-INPUT POSITIVE-NAND GATES	3 ns	19 mW	SN54S00	J, W	SN74S00	J, N	5-6
	6 ns	22 mW	SN54H00	J, W	SN74H00	J, N	
	9.5 ns	2 mW	SN54LS00	J, W	SN74LS00	J, N	
	10 ns	10 mW	SN5400	J, W	SN7400	J, N	
	33 ns	1 mW	SN54L00	J, T	SN74L00	J, N	
TRIPLE 3-INPUT POSITIVE-NAND GATES	3 ns	19 mW	SN54S10	J, W	SN74S10	J, N	
	6 ns	22 mW	SN54H10	J, W	SN74H10	J, N	
	9.5 ns	2 mW	SN54LS10	J, W	SN74LS10	J, N	
	10 ns	10 mW	SN5410	J, W	SN7410	J, N	
	33 ns	1 mW	SN54L10	J, T	SN74L10	J, N	
DUAL 4-INPUT POSITIVE-NAND GATES	3 ns	19 mW	SN54S20	J, W	SN74S20	J, N	5-10
	6 ns	22 mW	SN54H20	J, W	SN74H20	J, N	
	9.5 ns	2 mW	SN54LS20	J, W	SN74LS20	J, N	
	10 ns	10 mW	SN5420	J, W	SN7420	J, N	
	33 ns	1 mW	SN54L20	J, T	SN74L20	J, N	
8-INPUT POSITIVE-NAND GATES	3 ns	19 mW	SN54S30	J, W	SN74S30	J, N	5-12
	6 ns	22 mW	SN54H30	J, W	SN74H30	J, N	
	17 ns	2.4 mW	SN54LS30	J, W	SN74LS30	J, N	
	10 ns	10 mW	SN5430	J, W	SN7430	J, N	
	33 ns	1 mW	SN54L30	J, T	SN74L30	J, N	
13-INPUT POSITIVE-NAND GATES	3 ns	19 mW	SN54S133	J, W	SN74S133	J, N	5-38

POSITIVE-NAND GATES AND INVERTERS WITH OPEN-COLLECTOR OUTPUTS
ELECTRICAL TABLES – PAGE 6-4

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
HEX INVERTERS	5 ns	17.5 mW	SN54S05	J, W	SN74S05	J, N	5-7
	8 ns	22 mW	SN54H05	J, W	SN74H05	J, N	
	16 ns	2 mW	SN54LS05	J, W	SN74LS05	J, N	
	24 ns	10 mW	SN5405	J, W	SN7405	J, N	
QUADRUPLE 2-INPUT POSITIVE-NAND GATES	5 ns	17.5 mW	SN54S03	J, W	SN74S03	J, N	5-7
	8 ns	22 mW	SN54H01	J, W	SN74H01	J, N	5-6
	16 ns	2 mW	SN54LS01	J, W	SN74LS01	J, N	5-6
	16 ns	2 mW	SN54LS03	J, W	SN74LS03	J, N	5-7
	22 ns	10 mW	SN5401	J, W	SN7401	J, N	5-6
	22 ns	10 mW	SN5403	J	SN7403	J, N	5-7
	46 ns	1 mW	SN54L01	T			5-6
	46 ns	1 mW	SN54L03	J	SN74L03	J, N	5-7
TRIPLE 3-INPUT POSITIVE-NAND GATES	16 ns	2 mW	SN54LS12	J, W	SN74LS12	J, N	5-9
	22 ns	10 mW	SN5412	J, W	SN7412	J, N	
DUAL 4-INPUT POSITIVE-NAND GATES	5 ns	17.5 mW	SN54S22	J, W	SN74S22	J, N	5-11
	8 ns	22 mW	SN54H22	J, W	SN74H22	J, N	
	16 ns	2 mW	SN54LS22	J, W	SN74LS22	J, N	
	22 ns	10 mW	SN5422	J, W	SN7422	J, N	

SSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

POSITIVE-NOR GATES WITH TOTEM-POLE OUTPUTS
ELECTRICAL TABLES – PAGE 6-8

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
QUADRUPLE 2-INPUT POSITIVE-NOR GATES	3.5 ns	29 mW	SN54S02	J, W	SN74S02	J, N	5-6
	10 ns	2.75 mW	SN54LS02	J, W	SN74LS02	J, N	
	10 ns	14 mW	SN5402	J, W	SN7402	J, N	
	33 ns	1.5 mW	SN54L02	J, T	SN74L02	J, N	
TRIPLE 3-INPUT POSITIVE-NOR GATES	8.5 ns	22 mW	SN5427	J, W	SN7427	J, N	5-12
	10 ns	4.5 mW	SN54LS27	J, W	SN74LS27	J, N	
DUAL 4-INPUT POSITIVE-NOR GATES WITH STROBE	10.5 ns	23 mW	SN5425	J, W	SN7425	J, N	5-11
DUAL 5-INPUT POSITIVE-NOR GATES	4 ns	54 mW	SN54S260	J, W	SN74S260	J, N	5-58

POSITIVE-AND GATES WITH TOTEM-POLE OUTPUTS
ELECTRICAL TABLES – PAGE 6-10

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
QUADRUPLE 2-INPUT POSITIVE-AND GATES	4.75 ns	32 mW	SN54S08	J, W	SN74S08	J, N	5-8
	12 ns	4.25 mW	SN54LS08	J, W	SN74LS08	J, N	
	15 ns	19 mW	SN5408	J, W	SN7408	J, N	
TRIPLE 3-INPUT POSITIVE-AND GATES	4.75 ns	31 mW	SN54S11	J, W	SN74S11	J, N	5-9
	8.2 ns	40 mW	SN54H11	J, W	SN74H11	J, N	
	12 ns	4.25 mW	SN54LS11	J, W	SN74LS11	J, N	
DUAL 4-INPUT POSITIVE-AND GATES	8.2 ns	40 mW	SN54H21	J, W	SN74H21	J, N	5-11
	12 ns	4.25 mW	SN54LS21	J, W	SN74LS21	J, N	

POSITIVE-AND GATES WITH OPEN-COLLECTOR OUTPUTS
ELECTRICAL TABLES – PAGE 6-12

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
QUADRUPLE 2-INPUT POSITIVE-AND GATES	6.5 ns	32 mW	SN54S09	J, W	SN74S09	J, N	5-8
	18.5 ns	19.4 mW	SN5409	J, W	SN7409	J, N	
	20 ns	4.25 mW	SN54LS09	J, W	SN74LS09	J, N	
TRIPLE 3-INPUT POSITIVE-AND GATES	6 ns	28 mW	SN54S15	J, W	SN74S15	J, N	5-10
	10.5 ns	38 mW	SN54H15	J, W	SN74H15	J, N	
	20 ns	4.25 mW	SN54LS15	J, W	SN74LS15	J, N	

SCHMITT-TRIGGER POSITIVE-NAND GATES AND INVERTERS WITH TOTEM-POLE OUTPUTS
ELECTRICAL TABLES – PAGE 6-14

DESCRIPTION	TYPICAL HYSTERESIS	TYPICAL DELAY TIME	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
HEX SCHMITT TRIGGER INVERTERS	0.8 V	15 ns	SN5414	J, W	SN7414	J, N	5-9
	0.8 V	15 ns	SN54LS14	J, W	SN74LS14	J, N	
QUADRUPLE 2-INPUT POSITIVE-NAND SCHMITT TRIGGERS	0.55 V	8 ns	SN54S132	J, W	SN74S132	J, N	5-37
	0.8 V	15 ns	SN54132	J, W	SN74132	J, N	
	0.8 V	15 ns	SN54LS132	J, W	SN74LS132	J, N	
DUAL 4-INPUT POSITIVE-NAND SCHMITT TRIGGERS	0.8 V	16.5 ns	SN5413	J, W	SN7413	J, N	5-9
	0.8 V	16.5 ns	SN54LS13	J, W	SN74LS13	J, N	

SSI FUNCTIONS

FUNCTIONAL INDEX/SELECTION GUIDE

BUFFERS/CLOCK DRIVERS WITH TOTEM-POLE OUTPUTS (ALSO SEE 3-STATE BUFFERS AND DRIVERS ON PAGE 1-13)

ELECTRICAL TABLES – PAGE 6-20

DESCRIPTION	LOW-LEVEL OUTPUT CURRENT	HIGH-LEVEL OUTPUT CURRENT	TYPICAL DELAY TIME	TYP POWER PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
					-55°C to 125°C		0°C to 70°C		
QUADRUPLE 2-INPUT POSITIVE-NOR BUFFERS	48 mA	-2.4 mA	7 ns	28 mW	SN5428	J, W	SN7428	J, N	5-12
	24 mA	-1.2 mA	12 ns	5.5 mW			SN74LS28	J, N	
	12 mA	-1.2 mA	12 ns	5.5 mW	SN54LS28	J, W			
QUADRUPLE 2-INPUT POSITIVE-NAND BUFFERS	60 mA	-3 mA	4 ns	41 mW	SN54S37	J, W	SN74S37	J, N	5-13
	48 mA	-1.2 mA	10.5 ns	27 mW	SN5437	J, W	SN7437	J, N	
	24 mA	-1.2 mA	12 ns	4.3 mW			SN74LS37	J, N	
	12 mA	-1.2 mA	12 ns	4.3 mW	SN54LS37	J, W			
DUAL 4-INPUT POSITIVE-NAND BUFFERS	60 mA	-3 mA	4 ns	44 mW	SN54S40	J, W	SN74S40	J, N	5-14
	60 mA	-1.5 mA	7.5 ns	44 mW	SN54H40	J, W	SN74H40	J, N	
	48 mA	-1.2 mA	10.5 ns	26 mW	SN5440	J, W	SN7440	J, N	
	24 mA	-1.2 mA	12 ns	4.3 mW			SN74LS40	J, N	
	12 mA	-1.2 mA	12 ns	4.3 mW	SN54LS40	J, W			

50-OHM/75-OHM LINE DRIVERS

ELECTRICAL TABLES – PAGE 6-22

DESCRIPTION	LOW-LEVEL OUTPUT CURRENT	HIGH-LEVEL OUTPUT CURRENT	TYPICAL DELAY TIME	TYP POWER PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
					-55°C to 125°C		0°C to 70°C		
DUAL 4-INPUT POSITIVE-NAND LINE DRIVERS	60 mA	-40 mA	4 ns	44 mW	SN54S140	J, W	SN74S140	J, N	5-39
QUADRUPLE 2-INPUT POSITIVE-NOR LINE DRIVERS	48 mA	-42.4 mA	7 ns	28 mW			SN74128	J, N	5-37
	48 mA	-29 mA	7 ns	28 mW	SN54128	J, W			

BUFFER AND INTERFACE GATES WITH OPEN-COLLECTOR OUTPUTS

ELECTRICAL TABLES – PAGES 6-24 AND 6-26

DESCRIPTION	HIGH-LEVEL OUTPUT VOLTAGE	LOW-LEVEL OUTPUT CURRENT	TYPICAL DELAY TIME	TYP POWER PER GATE	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.
					-55°C to 125°C		0°C to 70°C		
HEX BUFFERS/DRIVERS	30 V	40 mA	13 ns	21 mW			SN7407	J, N	5-8
	30 V	30 mA	13 ns	21 mW	SN5407	J, W			5-8
	15 V	40 mA	13 ns	21 mW			SN7417	J, N	5-10
HEX INVERTER BUFFERS/DRIVERS	15 V	30 mA	13 ns	21 mW	SN5417	J, W			5-10
	30 V	40 mA	12.5 ns	26 mW			SN7406	J, N	5-7
	30 V	30 mA	12.5 ns	26 mW	SN5406	J, W			5-7
QUADRUPLE 2-INPUT POSITIVE-NAND BUFFERS	15 V	40 mA	12.5 ns	26 mW			SN7416	J, N	5-10
	15 V	30 mA	12.5 ns	26 mW	SN5416	J, W			5-10
	15 V	16 mA	13.5 ns	10 mW	SN5426	J	SN7426	J, N	5-12
QUADRUPLE 2-INPUT POSITIVE-NAND BUFFERS	15 V	8 mA	16 ns	2 mW			SN74LS26	J, N	5-12
	15 V	4 mA	16 ns	2 mW	SN54LS26	J, W			5-12
	5.5 V	60 mA	6.5 ns	41 mW	SN54S38	J, W	SN74S38	J, N	5-13
	5.5 V	48 mA	12.5 ns	24.4 mW	SN5438	J, W	SN7438	J, N	5-13
	5.5 V	24 mA	19 ns	4.3 mW			SN74LS38	J, N	5-13
	5.5 V	12 mA	19 ns	4.3 mW	SN54LS38	J, W			5-13
QUADRUPLE 2-INPUT POSITIVE- NOR BUFFERS	5.5 V	48 mA	11 ns	28 mW	SN5433	J, W	SN7433	J, N	5-13
	5.5 V	24 mA	19 ns	5.45 mW			SN74LS33	J, N	
	5.5 V	12 mA	19 ns	5.45 mW	SN54LS33	J, W			

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

GATES, BUFFERS, DRIVERS, AND BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	MAXIMUM SOURCE CURRENT	MAXIMUM SINK CURRENT	DEVICE TYPE AND PACKAGE				PIN ASSIGNMENTS PAGE NO.	ELECTRICAL CHARACTERISTICS PAGE NO.
				-55°C to 125°C		0°C to 70°C			
				Part No.	Package	Part No.	Package		
12-INPUT NAND GATE	4.5 ns 4.5 ns	-6.5 mA -2 mA	20 mA 20 mA	SN54S134	J, W	SN74S134	J, N	5-38	6-33
QUADRUPLE BUS BUFFERS/DRIVERS WITH INDEPENDENT OUTPUT CONTROLS	8 ns	-2.6 mA	16 mA	SN54LS125	J, W	SN74LS125	J, N	5-37	6-33
	8 ns	-1 mA	8 mA	SN54LS125	J, W	SN74LS125	J, N	5-37	
	8.5 ns	-2.6 mA	16 mA	SN54LS126	J, W	SN74LS126	J, N	5-37	
	8.5 ns	-1 mA	8 mA	SN54LS126	J, W	SN74LS126	J, N	5-37	
	10 ns	-5.2 mA	16 mA	SN54125	J, W	SN74125	J, N	5-37	
	10 ns	-2 mA	16 mA	SN54125	J, W	SN74125	J, N	5-37	
	10 ns	-5.2 mA	16 mA	SN54126	J, W	SN74126	J, N	5-37	
	10 ns	-2 mA	16 mA	SN54126	J, W	SN74126	J, N	5-37	
	10 ns	-5.2 mA	16 mA	SN54425	J, W	SN74425	J, N	5-74	
	10 ns	-2 mA	16 mA	SN54425	J, W	SN74425	J, N	5-74	
HEX BUS BUFFERS/DRIVERS	9.5 ns	-2.6 mA	16 mA	SN54LS365	J, W	SN74LS365	J, N	5-68	6-36
	9.5 ns	-1 mA	8 mA	SN54LS365	J, W	SN74LS365	J, N	5-68	
	9.5 ns	-2.6 mA	16 mA	SN54LS366	J, W	SN74LS366	J, N	5-68	
	9.5 ns	-1 mA	8 mA	SN54LS366	J, W	SN74LS366	J, N	5-68	
	9.5 ns	-2.6 mA	16 mA	SN54LS367	J, W	SN74LS367	J, N	5-69	
	9.5 ns	-1 mA	8 mA	SN54LS367	J, W	SN74LS367	J, N	5-69	
	9.5 ns	-2.6 mA	16 mA	SN54LS368	J, W	SN74LS368	J, N	5-69	
	9.5 ns	-1 mA	8 mA	SN54LS368	J, W	SN74LS368	J, N	5-69	
	11 ns	-5.2 mA	32 mA	SN54366A	J, W	SN74366A	J, N	5-68	
	11 ns	-2 mA	32 mA	SN54366A	J, W	SN74366A	J, N	5-68	
	11 ns	-5.2 mA	32 mA	SN54368A	J, W	SN74368A	J, N	5-69	
	11 ns	-2 mA	32 mA	SN54368A	J, W	SN74368A	J, N	5-69	
	12 ns	-5.2 mA	32 mA	SN54365A	J, W	SN74365A	J, N	5-68	
	12 ns	-2 mA	32 mA	SN54365A	J, W	SN74365A	J, N	5-68	
12 ns	-5.2 mA	32 mA	SN54367A	J, W	SN74367A	J, N	5-69		
12 ns	-2 mA	32 mA	SN54367A	J, W	SN74367A	J, N	5-69		
OCTAL BUS BUFFERS/DRIVERS	5 ns	-15 mA	64 mA	SN54S240	J	SN74S240	J, N	5-54	6-83
	5 ns	-12 mA	48 mA	SN54S240	J	SN74S240	J, N	5-54	
	5 ns	-15 mA	64 mA	SN54S241	J	SN74S241	J, N	5-55	
	5 ns	-12 mA	48 mA	SN54S241	J	SN74S241	J, N	5-55	
	10 ns	-15 mA	24 mA	SN54LS240	J	SN74LS240	J, N	5-54	
	10 ns	-12 mA	12 mA	SN54LS240	J	SN74LS240	J, N	5-54	
	10 ns	-15 mA	24 mA	SN54LS241	J	SN74LS241	J, N	5-55	
	10 ns	-12 mA	12 mA	SN54LS241	J	SN74LS241	J, N	5-55	
	10 ns	-15 mA	24 mA	SN54LS244	J	SN74LS244	J, N	5-55	
	10 ns	-12 mA	12 mA	SN54LS244	J	SN74LS244	J, N	5-55	
CONTROLLER AND BUS DRIVER FOR 8080A SYSTEMS (MSI)		-1 mA -1 mA	10 mA 10 mA			SN74S428 SN74S438	N N	7-514	7-514
QUADRUPLE TRANSCEIVERS	11 ns	-15 mA	24 mA	SN54LS242	J, W	SN74LS242	J, N	5-55	6-87
	11 ns	-12 mA	12 mA	SN54LS242	J, W	SN74LS242	J, N		
	12 ns	-15 mA	24 mA	SN54LS243	J, W	SN74LS243	J, N		
QUADRUPLE TRANSCEIVERS WITH STORAGE (MSI)	10 ns	-10.3 mA	20 mA	SN54S226	J, W	SN74S226	J, N	7-345	7-345
	10 ns	-6.5 mA	20 mA	SN54S226	J, W	SN74S226	J, N	7-345	7-345
OCTAL TRANSCEIVERS (MSI)	12 ns	-15 mA	24 mA	SN54LS245	J	SN74LS245	J, N	7-349	7-349
	12 ns	-12 mA	12 mA	SN54LS245	J	SN74LS245	J, N	7-349	7-349

1

SSI FUNCTIONS

FUNCTIONAL INDEX/SELECTION GUIDE

POSITIVE-OR GATES WITH TOTEM-POLE OUTPUTS

ELECTRICAL TABLES – PAGE 6-28

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
			–55° C to 125° C		0° C to 70° C	
QUADRUPLE 2-INPUT POSITIVE-OR GATES	4 ns	35 mW	SN54S32	J, W	SN74S32	J, N
	12 ns	24 mW	SN5432	J, W	SN7432	J, N
	12 ns	5 mW	SN54LS32	J, W	SN74LS32	J, N

AND-OR-INVERT GATES WITH TOTEM-POLE OUTPUTS

ELECTRICAL TABLES – PAGE 6-30

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
			–55° C to 125° C		0° C to 70° C	
2-WIDE 4-INPUT	12.5 ns	2.75 mW	SN54LS55	J, W	SN74LS55	J, N
	43 ns	1.5 mW	SN54L55	J, T	SN74L55	J, N
4-WIDE 4-2-3-2-INPUT	3.5 ns	29 mW	SN54S64	J, W	SN74S64	J, N
4-WIDE 2-2-3-2-INPUT	6.6 ns	41 mW	SN54H54	J, W	SN74H54	J, N
4-WIDE 2-INPUT	10.5 ns	23 mW	SN5454	J, W	SN7454	J, N
4-WIDE 2-3-3-2-INPUT	12.5 ns	4.5 mW	SN54LS54	J, W	SN74LS54	J, N
4-WIDE 2-3-3-2-INPUT	43 ns	1.5 mW	SN54L54	J, T	SN74L54	J, N
DUAL 2-WIDE 2-INPUT	3.5 ns	28 mW	SN54S51	J, W	SN74S51	J, N
	6.5 ns	29 mW	SN54H51	J, W	SN74H51	J, N
	10.5 ns	14 mW	SN5451	J, W	SN7451	J, N
	12.5 ns	2.75 mW	SN54LS51	J, W	SN74LS51	J, N
	43 ns	1.5 mW	SN54L51	J, T	SN74L51	J, N

AND-OR-INVERT GATES WITH OPEN-COLLECTOR OUTPUTS

ELECTRICAL TABLES – PAGE 6-32

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
			–55° C to 125° C		0° C to 70° C	
4-WIDE 4-2-3-2-INPUT	5.5 ns	36 mW	SN54S65	J, W	SN74S65	J, N

EXPANDABLE GATES

ELECTRICAL TABLE – PAGE 6-39

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
			–55° C to 125° C		0° C to 70° C	
DUAL 4-INPUT POSITIVE-NOR GATES WITH STROBE	10.5 ns	23 mW	SN5423	J, W	SN7423	J, N
4-WIDE AND-OR GATES	9.9 ns	88 mW	SN54H52	J, W	SN74H52	J, N
4-WIDE AND-OR-INVERT GATES	6.6 ns	41 mW	SN54H53	J, W	SN74H53	J, N
4-WIDE AND-OR-INVERT GATES	10.5 ns	23 mW	SN5453	J, W	SN7453	J, N
2-WIDE AND-OR-INVERT GATES	6.8 ns	30 mW	SN54H55	J, W	SN74H55	J, N
DUAL 2-WIDE AND-OR-INVERT GATES	6.5 ns	29 mW	SN54H50	J, W	SN74H50	J, N
	10.5 ns	14 mW	SN5450	J, W	SN7450	J, N


EXPANDERS

ELECTRICAL TABLES – PAGES 6-43, 6-44, AND 6-45

DESCRIPTION	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
		–55° C to 125° C		0° C to 70° C	
DUAL 4-INPUT EXPANDERS	4 mW	SN5460	J, W	SN7460	J, N
TRIPLE 3-INPUT EXPANDERS	6 mW	SN54H60	J, W	SN74H60	J, N
	13 mW	SN54H61	J, W	SN74H61	J, N
3-2-2-3-INPUT AND-OR EXPANDERS	25 mW	SN54H62	J, W	SN74H62	J, N


SSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

DUAL J-K EDGE-TRIGGERED FLIP-FLOPS



1

SINGLE J-K EDGE-TRIGGERED FLIP-FLOPS




DWG REF.	TYPICAL CHARACTERISTICS		DATA TIMES		DEVICE TYPE AND PACKAGE				PAGE REFERENCES	
	f _{max} (MHz)	P _{wr/F-F} (mW)	SETUP (ns)	HOLD (ns)	-55°C to 125°C		0°C to 70°C		PIN ASSIGNMENTS	ELECTRICAL
					Part No.	Package	Part No.	Package		
A	125	75	3↓	0↓	SN54S112	J, W	SN74S112	J, N	5-34	6-58
	50	100	13↓	0↓	SN54H106	J, W	SN74H106	J, N	5-32	6-52
	45	10	20↓	0↓	SN54LS76	J, W	SN74S76	J, N	5-23	6-58
	45	10	20↓	0↓	SN54LS112	J, W	SN74LS112	J, N	5-34	6-56
B	125	75	3↓	0↓	SN54S114	J, W	SN74S114	J, N	5-34	6-58
	50	100	13↓	0↓	SN54H108	J, W	SN74H108	J, N	5-32	6-52
	45	10	20↓	0↓	SN54LS78	J, W	SN74LS78	J, N	5-24	6-56
	45	10	20↓	0↓	SN54LS114	J, W	SN74LS114	J, N	5-34	6-56
C	125	75	3↓	0↓	SN54S113	J, W	SN74S113	J, N	5-34	6-58
	45	10	20↓	0↓	SN54LS113	J, W	SN74LS113	J, N	5-34	6-56
D	50	100	13↓	0↓	SN54H103	J, W	SN74H103	J, N	5-31	6-52
	45	10	20↓	0↓	SN54LS73	J, W	SN74LS73	J, N	5-22	6-56
	45	10	20↓	0↓	SN54LS107	J	SN74LS107	J, N	5-32	6-56
E	33	10	20↑	5↑	SN54LS109A	J, W	SN74LS109A	J, N	5-33	6-56
	33	45	10↑	6↑	SN54109	J, W	SN74109	J, N	5-33	6-46
F	50	100	13↓	0↓	SN54H101	J, W	SN74H101	J, N	5-31	6-52
G	50	100	13↓	0↓	SN54H102	J, W	SN74H102	J, N	5-31	6-52
H	35	65	20↑	5↑	SN5470	J, W	SN7470	J, N	5-21	6-46

↑↓ The arrow indicates the edge of the clock pulse used for reference: ↑ for the rising edge, ↓ for the falling edge.


SSI FUNCTIONS

FUNCTIONAL INDEX/SELECTION GUIDE

PULSE-TRIGGERED DUAL FLIP-FLOPS




PULSE-TRIGGERED SINGLE FLIP-FLOPS



DWG. REF.	TYPICAL CHARACTERISTICS		DATA TIMES		DEVICE TYPE AND PACKAGE				PAGE REFERENCES	
	f _{max} (MHz)	Pwr/F-F (mW)	SETUP (ns)	HOLD (ns)	-55°C to 125°C		0°C to 70°C		PIN ASSIGNMENTS	ELECTRICAL
					J, W	J, N	J, N	J, N		
I	30	80	0†	0‡	SN54H73	J, W	SN74H73	J, N	5-22	6-50
	20	50	0†	0‡	SN5473	J, W	SN7473	J, N	5-22	6-46
	20	50	0†	0‡	SN54107	J	SN74107	J, N	5-32	6-46
	3	3.8	0†	0‡	SN54L73	J, T	SN74L73	J, N	5-22	6-54
J	30	80	0†	0‡	SN54H76	J, W	SN74H76	J, N	5-23	6-50
	20	50	0†	0‡	SN5476	J, W	SN7476	J, N	5-23	6-46
K	30	80	0†	0‡	SN54H78	J, W	SN74H78	J, N	5-24	6-50
	3	3.8	0†	0‡	SN54L78	J, T	SN74L78	J, N	5-24	6-54
L	30	80	0†	0‡	SN54H71	J, W	SN74H71	J, N	5-21	6-50
M	30	80	0†	0‡	SN54H72	J, W	SN74H72	J, N	5-22	6-50
	20	50	0†	0‡	SN5472	J, W	SN7472	J, N	5-22	6-46
	3	3.8	0†	0‡	SN54L72	J, T	SN74L72	J, N	5-22	6-54
N	3	3.8	0†	0‡	SN54L71	J, T	SN74L71	J, N	5-21	6-54

J-K FLIP-FLOPS WITH DATA LOCKOUT



DWG. REF.	TYPICAL CHARACTERISTICS		DATA TIMES		DEVICE TYPE AND PACKAGE				PAGE REFERENCES	
	f _{max} (MHz)	Pwr/F-F (mW)	SETUP (ns)	HOLD (ns)	-55°C to 125°C		0°C to 70°C		PIN ASSIGNMENTS	ELECTRICAL
					J, W	J, N	J, N	J, N		
O	25	70	0†	30†	SN54111	J, W	SN74111	J, N	5-33	6-46
P	25	100	20†	5†	SN54110	J, W	SN74110	J, N	5-33	6-46
Q	110	75	3†	2†	SN54S74	J, W	SN74S74	J, N	5-22	6-58
	43	75	15†	5†	SN54H74	J, W	SN74H74	J, N	5-22	6-50
	33	10	25†	5†	SN54LS74A	J, W	SN74LS74A	J, N	5-22	6-56
	25	43	20†	5†	SN5474	J, W	SN7474	J, N	5-22	6-46
	3	4	50†	15†	SN54L74	J, T	SN74L74	J, N	5-22	6-54

†‡The arrow indicates the edge of the clock pulse used for reference: † for the rising edge, ‡ for the falling edge.

SSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

S-R LATCHES

ELECTRICAL TABLES – PAGE 6-60

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
			–55° C to 125° C		0° C to 70° C	
QUADRUPLE S-R LATCHES	12 ns	19 mW	SN54LS279	J, W	SN74LS279	J, N
	12 ns	90 mW	SN54279	J, W	SN74279	J, N

CURRENT-SENSING-GATES

ELECTRICAL TABLES – PAGE 6-62

DESCRIPTION	TYPICAL PROPAGATION DELAY TIME	TYP POWER DISSIPATION PER GATE	DEVICE TYPE AND PACKAGES			PIN ASSIGNMENTS PAGE NO.
			–55° C to 125° C		0° C to 70° C	
HEX	21 ns	3.3 mW	SN54LS63	J, W	SN74LS63	J, N

MONOSTABLE MULTIVIBRATORS WITH SCHMITT-TRIGGER INPUTS

ELECTRICAL TABLES – PAGES 6-64 AND 6-68

DESCRIPTION	NO. OF INPUTS		OUTPUT PULSE RANGE	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
	POSITIVE	NEGATIVE			–55° C to 125° C		0° C to 70° C	
SINGLE	1	2	40 ns–28 s	90 mW	SN54121	J, W	SN74121	J, N
	1	2	40 ns–28 s	40 mW	SN54L121	J, T	SN74L121	J, N
DUAL	1	1	20 ns–70 s	23 mW	SN54LS221	J, W	SN74LS221	J, N
	1	1	20 ns–49 s	23 mW				
	1	1	20 ns–28 s	130 mW	SN74221	J, W	J, N	
	1	1	20 ns–21 s	130 mW				SN54221

RETRIGGERABLE MONOSTABLE MULTIVIBRATORS

ELECTRICAL TABLES – PAGE 6-76

DESCRIPTION	NO. OF INPUTS		DIRECT CLEAR	OUTPUT PULSE RANGE	TYP TOTAL POWER	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
	POSITIVE	NEGATIVE				–55° C to 125° C		0° C to 70° C	
SINGLE	2	2	Yes	45 ns–∞	115 mW	SN54122	J, W	SN74122	J, N
	2	2	Yes	90 ns–∞	55 mW	SN54L122	J, T	SN74L122	J, N
	2	2	Yes	45 ns–∞	30 mW	SN54LS122	J, W	SN74LS122	J, N
DUAL	1	1	Yes	45 ns–∞	230 mW	SN54123	J, W	SN74123	J, N
	1	1	Yes	90 ns–∞	115 mW	SN54L123	J	SN74L123	J, N
	1	1	Yes	45 ns–∞	60 mW	SN54LS123	J, W	SN74LS123	J, N

CLOCK GENERATOR CIRCUITS

ELECTRICAL TABLES – PAGES 6-89 AND 7-123

DESCRIPTION	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE			PIN ASSIGNMENTS PAGE NO.
		–55° C to 125° C		0° C to 70° C	
QUADRUPLE COMPLEMENTARY-OUTPUT LOGIC ELEMENTS	125 mW	SN54265	J, W	SN74265	J, N
DUAL VOLTAGE-CONTROLLED OSCILLATORS (MSI)	90 mW	SN54LS124	J, W	SN74LS124	J, N
	525 mW	SN54S124	J, W	SN74S124	J, N

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

ADDERS

DESCRIPTION	TYPICAL CARRY TIME	TYPICAL ADD TIME	TYP POWER DISSIPATION PER BIT	DEVICE TYPE AND PACKAGE				PAGE NO.
				-55°C to 125°C		0°C to 70°C		
				Device	Package	Device	Package	
SINGLE 1-BIT GATED FULL ADDERS	10.5 ns	52 ns	105 mW	SN5480	J, W	SN7480	J, N	7-41
SINGLE 2-BIT FULL ADDERS	14.5 ns	25 ns	87 mW	SN5482	J, W	SN7482	J, N	7-49
SINGLE 4-BIT FULL ADDERS	10 ns	15 ns	24 mW	SN54LS83A	J, W	SN74LS83A	J, N	7-53
	10 ns	15 ns	24 mW	SN54LS283	J, W	SN74LS283	J, N	7-415
	11 ns	7 ns	124 mW	SN54S283	J	SN74S283	J, N	7-415
	10 ns	16 ns	76 mW	SN5483A	J, W	SN7483A	J, N	7-53
	10 ns	16 ns	76 mW	SN54283	J, W	SN74283	J, N	7-415
DUAL 1-BIT CARRY-SAVE FULL ADDERS	11 ns	11 ns	110 mW	SN54H183	J, W	SN74H183	J, N	7-287
	15 ns	15 ns	23 mW	SN54LS183*	J, W	SN74LS183*	J, N	7-287

ACCUMULATORS, ARITHMETIC LOGIC UNITS, LOOK-AHEAD CARRY GENERATORS

DESCRIPTION	TYPICAL CARRY TIME	TYPICAL ADD TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
				-55°C to 125°C		0°C to 70°C		
				Device	Package	Device	Package	
4-BIT PARALLEL BINARY ACCUMULATORS	10 ns	20 ns	720 mW	SN54S281	J, W	SN74S281	J, N	7-410
4-BIT ARITHMETIC LOGIC UNITS/ FUNCTION GENERATORS	11 ns	20 ns	525 mW			SN74S381	N	7-484
	7 ns	11 ns	600 mW	SN54S181	J, W	SN74S181	J, N	7-271
	12.5 ns	24 ns	455 mW	SN54181	J, W	SN74181	J, N	7-271
LOOK-AHEAD CARRY GENERATORS	16 ns	24 ns	102 mW	SN54LS181	J, W	SN74LS181	J, N	7-271
	7 ns		260 mW	SN54S182	J, W	SN74S182	J, N	7-282
	13 ns		180 mW	SN54182	J, W	SN74182	J, N	7-282

MULTIPLIERS

DESCRIPTION	DEVICE TYPE AND PACKAGE				PAGE NO.
	-55°C to 125°C		0°C to 70°C		
	Device	Package	Device	Package	
2-BIT-BY-4-BIT PARALLEL BINARY MULTIPLIERS	SN54LS261	J, W	SN74LS261	J, N	7-380
4-BIT-BY-4-BIT PARALLEL BINARY MULTIPLIERS	SN54284, SN54285	J, W	SN74284, SN74285	J, N	7-420
	SN54S274	J	SN74S274	J, N	7-391
7-BIT-SLICE WALLACE TREES	SN54LS275	J	SN74LS275	J, N	7-391
	SN54S275	J	SN74S275	J, N	
25-MHz 6-BIT-BINARY RATE MULTIPLIERS	SN5497	J, W	SN7497	J, N	7-102
25-MHz DECADE RATE MULTIPLIERS	SN54167	J, W	SN74167	J, N	7-222

COMPARATORS

DESCRIPTION	TYPICAL COMPARE TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Device	Package	Device	Package	
4-BIT MAGNITUDE COMPARATORS	11.5 ns	365 mW	SN54S85	J, W	SN74S85	J, N	7-57
	21 ns	275 mW	SN5485	J, W	SN7485	J, N	
	23.5 ns	52 mW	SN54LS85	J, W	SN74LS85	J, N	
	82 ns	20 mW	SN54L85	J	SN74L85	J, N	

* New product in development as of October 1976.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

PARITY GENERATORS/CHECKERS

DESCRIPTION	TYPICAL DELAY TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE				PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
9-BIT ODD/EVEN PARITY GENERATORS/CHECKERS	31 ns	80 mW	SN54LS280	J, W	SN74LS280	J, N	7-406
	13 ns	335 mW	SN54S280	J, W	SN74S280	J, N	
8-BIT ODD/EVEN PARITY GENERATORS/CHECKERS	35 ns	170 mW	SN54180	J, W	SN74180	J, N	7-269

OTHER ARITHMETIC OPERATORS

DESCRIPTION	TYPICAL DELAY TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
QUADRUPLE 2-INPUT EXCLUSIVE-OR GATES WITH TOTEM-POLE OUTPUTS	7 ns	250 mW	SN54S86	J, W	SN74S86	J, N	7-65
	10 ns	30 mW	SN54LS86	J, W	SN74LS86	J, N	7-65
	10 ns	30 mW	SN54LS386	J, W	SN74LS386	J, N	7-487
	14 ns	150 mW	SN5486	J, W	SN7486	J, N	7-65
	55 ns	15 mW	SN54L86	J, T	SN74L86	J, N	7-65
QUADRUPLE 2-INPUT EXCLUSIVE-OR GATES WITH OPEN-COLLECTOR OUTPUTS	18 ns	30 mW	SN54LS136	J, W	SN74LS136	J, N	7-131
	27 ns	150 mW	SN54136	J, W	SN74136	J, N	
QUADRUPLE 2-INPUT EXCLUSIVE-NOR GATES	18 ns	40 mW	SN54LS266	J, W	SN74LS266	J, N	7-386
QUADRUPLE EXCLUSIVE OR/NOR GATES	8 ns	325 mW	SN54S135	J, W	SN74S135	J, N	7-129
4-BIT TRUE/COMPLEMENT, ZERO/ONE ELEMENT	14 ns	270 mW	SN54H87	J, W	SN74H87	J, N	7-70

QUAD, HEX, AND OCTAL FLIP-FLOPS

DESCRIPTION	F-F PER PKG	FREQ	POWER PER FLIP-FLOP	DATA TIMES		DEVICE TYPE AND PACKAGE				PAGE NO.
				SETUP ns	HOLD ns	-55°C to 125°C		0°C to 70°C		
						Part No.	Package	Part No.	Package	
D TYPE 3-STATE WITH ENABLE	8	50 MHz	26 mW	20†	0†	SN54LS364*	J	SN74LS364*	J, N	7-467
		50 MHz	17 mW	20†	0†	SN54LS374*	J	SN74LS374*	J, N	7-471
		100 MHz	56 mW	5†	2†	SN54S374	J	SN74S374	J, N	7-471
D TYPE WITH ENABLE	8	40 MHz	10.6 mW	20†	5†	SN54LS377	J	SN74LS377	J, N	7-481
	6	40 MHz	10.6 mW	20†	5†	SN54LS378	J, W	SN74LS378	J, N	7-481
	4	40 MHz	10.6 mW	20†	5†	SN54LS379	J	SN74LS379	J, N	7-481
D TYPE WITH CLEAR	8	40 MHz	39 mW	20†	5†	SN54273	J	SN74273	J, N	7-388
		40 MHz	10.6 mW	20†	5†	SN54LS273	J	SN74LS273	J, N	
	6	35 MHz	38 mW	20†	5†	SN54174	J, W	SN74174	J, N	7-253
		40 MHz	10.6 mW	20†	5†	SN54LS174	J, W	SN74LS174	J, N	
		110 MHz	75 mW	5†	3†	SN54S174	J, W	SN74S174	J, N	
	4	35 MHz	38 mW	20†	5†	SN54175	J, W	SN74175	J, N	7-253
40 MHz		10.6 mW	20†	5†	SN54LS175	J, W	SN74LS175	J, N		
110 MHz	75 mW	5†	3†	SN54S175	J, W	SN74S175	J, N			
J-K TYPE WITH SEPARATE CLOCK	4	50 MHz	75 mW	3↓	10↓	SN54276	J	SN74276	J, N	7-401
J-K TYPE WITH COMMON CLOCK	4	45 MHz	65 mW	0†	20†	SN54376	J, W	SN74376	J, N	7-479

REGISTER FILES

DESCRIPTION	TYPICAL ADDRESS TIME	TYP READ ENABLE TIME	DATA INPUT RATE	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
					-55°C to 125°C		0°C to 70°C		
					Part No.	Package	Part No.	Package	
EIGHT WORDS OF TWO BITS	33 ns	15 ns	20 MHz	560 mW			SN74172	J, N	7-245
FOUR WORDS OF FOUR BITS	27 ns	15 ns	20 MHz	125 mW	SN54LS170	J, W	SN74LS170	J, N	7-237
	30 ns	15 ns	20 MHz	635 mW	SN54170	J, W	SN74170	J, N	
FOUR WORDS OF FOUR BITS (3-STATE OUTPUTS)	24 ns	19 ns	20 MHz	135 mW	SN54LS670	J, W	SN74LS670	J, N	7-526

*New product in development as of October 1976.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

SHIFT REGISTERS

DESCRIPTION	NO. OF BITS	SHIFT FREQ	SERIAL DATA INPUT	ASYNC CLEAR	MODES				TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.	
					S-R†	S-L†	LOAD	HOLD		-55°C to 125°C		0°C to 70°C			
PARALLEL-IN, PARALLEL-OUT (BIDIRECTIONAL)	8	50 MHz	D	Low	X	X	X	X	750 mW	SN54S299	J, W	SN74S299	J, N	7-437	
		35 MHz	D	Low	X	X	X	X	175 mW	SN54LS299*	J	SN74LS299*	J, N	7-437	
		35 MHz	D	Sync L	X	X	X	X	175 mW	SN54LS323*	J	SN74LS323*	J, N	7-443	
		25 MHz	D	Low	X	X	X	X	360 mW	SN54198	J, W	SN74198	J, N	7-338	
	4	70 MHz	D	Low	X	X	X	X	450 mW	SN54S194	J, W	SN74S194	J, N	7-316	
		25 MHz	D	Low	X	X	X	X	75 mW	SN54LS194A	J, W	SN74LS194A	J, N		
		25 MHz	D	Low	X	X	X	X	195 mW	SN54194	J, W	SN74194	J, N		
	PARALLEL-IN, PARALLEL-OUT	8	25 MHz	J-K̄	Low	X	X	X	360 mW	SN54199	J, W	SN74199	J, N	7-338	
			5	10 MHz	D	Low	X	X		60 mW	SN54LS96	J, W	SN74LS96	J, N	7-95
				10 MHz	D	Low	X	X		240 mW	SN5496	J, W	SN7496	J, N	
5 MHz		D		Low	X	X		120 mW	SN54L96	J	SN74L96	J, N			
4		70 MHz	J-K̄	Low	X	X		375 mW	SN54S195	J, W	SN74S195	J, N	7-324		
		30 MHz	J-K̄	Low	X	X		195 mW	SN54195	J, W	SN74195	J, N	7-324		
		25 MHz	D	Low	X	X		75 mW	SN54LS395A*	J, W	SN74LS395A*	J, N	7-496		
		25 MHz	D	None	X	X		195 mW	SN5495A	J, W	SN7495A	J, N	7-89		
		25 MHz	D	Low	X	X	X	230 mW	SN54179	J, W	SN74179	J, N	7-265		
		25 MHz	D	None	X	X	X	230 mW	SN54178	J, W	SN74178	J, N	7-265		
		30 MHz	J-K̄	Low	X	X		70 mW	SN54LS195A	J, W	SN74LS195A	J, N	7-324		
		25 MHz	D	None	X	X		65 mW	SN54LS95B	J, W	SN74LS95B	J, N	7-89		
		25 MHz	D	None	X	X		70 mW	SN54LS295B*	J, W	SN74LS295B*	J, N	7-429		
		3 MHz	J-K̄	None	X	X		19 mW	SN54L99	J	SN74L99	J, N	7-109		
		3 MHz	D	None	X	X		19 mW	SN54L95	J, T	SN74L95	J, N	7-89		
SERIAL-IN, PARALLEL-OUT		8	25 MHz	Gated D	Low	X			80 mW	SN54LS164	J, W	SN74LS164	J, N	7-206	
			25 MHz	Gated D	Low	X			167 mW	SN54164	J, W	SN74164	J, N		
	12 MHz		Gated D	Low	X			84 mW	SN54L164	J, T	SN74L164	J, N			
PARALLEL-IN, SERIAL-OUT	8	25 MHz	D	None	X	X	X	210 mW	SN54165	J, W	SN74165	J, N	7-212		
		35 MHz	D	None	X	X	X	105 mW	SN54LS165	J, W	SN74LS165	J, N	7-212		
		20 MHz	D	Low	X	X	X	360 mW	SN54166	J, W	SN74166	J, N	7-217		
		35 MHz	D	Low	X	X	X	110 mW	SN54LS166	J, W	SN74LS166	J, N	7-217		
SERIAL-IN, SERIAL-OUT	4	10 MHz	D	High	X	X		175 mW	SN5494	J, W	SN7494	J, N	7-86		
		8	25 MHz	Gated D	None	X			60 mW	SN54LS91	J, W	SN74LS91	J, N	7-81	
			10 MHz	Gated D	None	X			175 mW	SN5491A	J, W	SN7491A	J, N		
		3 MHz	Gated D	None	X			17.5 mW	SN54L91	J, T	SN74L91	J, N			

*S-R ≡ shift right, S-L ≡ shift left

OTHER REGISTERS

DESCRIPTION	FREQ	ASYNC CLEAR	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
				-55°C to 125°C		0°C to 70°C		
QUADRUPLE MULTIPLEXERS WITH STORAGE	30 MHz	None	36.5 mW	SN54LS398	J	SN74LS398	J, N	7-499
	30 MHz	None	36.5 mW	SN54LS399	J, W	SN74LS399	J, N	7-499
	25 MHz	None	65 mW	SN54LS298	J, W	SN74LS298	J, N	7-432
	25 MHz	None	195 mW	SN54298	J, W	SN74298	J, N	7-432
	3 MHz	None	25 mW	SN54L98	J	SN74L98	J, N	7-107
8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS	35 MHz	Low	175 mW	SN54LS299*	J	SN74LS299*	J, N	7-437
	50 MHz	Low	750 mW	SN54S299	J, W	SN74S299	J, N	
QUADRUPLE BUS-BUFFER REGISTERS	25 MHz	High	250 mW	SN54173	J, W	SN74173	J, N	7-249
	50 MHz	High	85 mW	SN54LS173*	J, W	SN74LS173*	J, N	

*New product in development as of October 1976.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

LATCHES

DESCRIPTION	NO. OF BITS	CLEAR	OUTPUTS	TYPICAL DELAY TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
						-55°C to 125°C		0°C to 70°C		
						Part No.	Package	Part No.	Package	
MULTI-MODE BUFFERED	8	Low	Q	11 ns	410 mW	SN54S412	J	SN74S412	J, N	7-502
ADDRESSABLE	8	Low	Q	12 ns	300 mW	SN54259	J, W	SN74259	J, N	7-376
		Low	Q	17 ns	110 mW	SN54LS259	J, W	SN74LS259	J, N	
TRANSPARENT	8	None	Q	17 ns	210 mW	SN54LS363*	J	SN74LS363*	J, N	7-467
		None	Q	19 ns	120 mW	SN54LS373*	J	SN74LS373*	J, N	7-471
		None	Q	7 ns	525 mW	SN54S373	J	SN74S373	J, N	7-471
DUAL 4-BIT WITH INDEPENDENT ENABLE	8	Low	Q	11 ns	250 mW	SN54116	J, W	SN74116	J, N	7-115
		None	Q	15 ns	320 mW	SN54100	J, W	SN74100	J, N	7-113
DUAL 2-BIT WITH INDEPENDENT ENABLE	4	None	Q, \bar{Q}	15 ns	160 mW	SN5475	J, W	SN7475	J, N	7-35
		None	Q, \bar{Q}	30 ns	80 mW	SN54L75	J	SN74L75	J, N	7-35
		None	Q, \bar{Q}	11 ns	32 mW	SN54LS75	J, W	SN74LS75	J, N	7-35
		None	Q	15 ns	160 mW	SN5477	W			7-35
		None	Q	30 ns	80 mW	SN54L77	T			7-35
		None	Q	10 ns	35 mW	SN54LS77	W			7-35
QUAD \bar{S} - \bar{R} (SSI)	4	None	Q	12 ns	90 mW	SN54279	J, W	SN74279	J, N	6-60
		None	Q	12 ns	19 mW	SN54LS279	J, W	SN74LS279	J, N	

CLOCK GENERATOR CIRCUITS

DESCRIPTION	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
		-55°C to 125°C		0°C to 70°C		
		Part No.	Package	Part No.	Package	
CLOCK GENERATOR/DRIVERS (FOR TMS 9900) (FOR TMS 8080A)	669 mW			SN74LS362*	J, N	7-460
	719 mW			SN74LS424	J, N	7-507
DUAL VOLTAGE-CONTROLLED OSCILLATOR WITH ENABLE	90 mW	SN54LS124	J, W	SN74LS124	J, N	7-123
	525 mW	SN54S124	J, W	SN74S124	J, N	7-123
	90 mW	SN54LS326	J, W	SN74LS326	J, N	7-445
DUAL VOLTAGE-CONTROLLED OSCILLATOR	150 mW	SN54LS325	J, W	SN74LS325	J, N	7-445
	150 mW	SN54LS327	J, W	SN74LS327	J, N	
VOLTAGE-CONTROLLED OSCILLATOR WITH ENABLE	90 mW	SN54LS324	J, W	SN74LS324	J, N	7-445
DUAL 30-MHz PULSE SYNCHRONIZERS/DRIVERS	255 mW	SN54120	J, W	SN74120	J, N	7-118
QUAD COMPLIMENTARY GATES (CLOCK/CLOCK) [SSI]	125 mW	SN54265	J, W	SN74265	J, N	6-89

CODE CONVERTERS

DESCRIPTION	TYPICAL DELAY TIME PER PACKAGE LEVEL	TYPICAL TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
6-LINE-BCD TO 6-LINE BINARY, OR 4-LINE TO 4-LINE BCD 9's/BCD 10's CONVERTERS	25 ns	280 mW	SN54184	J, W	SN74184	J, N	7-290
6-BIT-BINARY TO 6-BIT-BCD CONVERTERS	25 ns	280 mW	SN54185A	J, W	SN74185A	J, N	7-290

*New product in development as of October 1976.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

PRIORITY ENCODERS/REGISTERS

DESCRIPTION	TYPICAL DELAY TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
			-55°C to 125°C		0°C to 70°C		
			Part No.	Package	Part No.	Package	
FULL BCD PRIORITY ENCODERS	10 ns	225 mW	SN54147	J, W	SN74147	J, N	7-151
	15 ns	60 mW	SN54LS147*	J, W	SN74LS147*	J, N	
CASCADABLE OCTAL PRIORITY ENCODERS	12 ns	190 mW	SN54148	J, W	SN74148	J, N	7-151
	15 ns	60 mW	SN54LS148*	J, W	SN74LS148*	J, N	
CASCADABLE OCTAL PRIORITY ENCODERS WITH 3-STATE OUTPUTS	16 ns	63 mW	SN54LS348*	J, W	SN74LS348*	J, N	7-448
4-BIT CASCADABLE PRIORITY REGISTERS	35 ns	275 mW	SN54278	J, W	SN74278	J, N	7-403

DATA SELECTORS/MULTIPLEXERS

DESCRIPTION	TYPE OF OUTPUT	TYPICAL DELAY TIMES			TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
		DATA TO INV OUTPUT	DATA TO NON-INV OUTPUT	FROM ENABLE		-55°C to 125°C		0°C to 70°C		
						Part No.	Package	Part No.	Package	
16-LINE-TO-1-LINE	2-State	11 ns		18 ns	200 mW	SN54150	J, W	SN74150	J, N	7-157
DUAL 8-LINE-TO-1-LINE	3-State	10 ns		17 ns	220 mW			SN74351	N	7-451
8-LINE-TO-1-LINE	3-State	4.5 ns	8 ns	14 ns	275 mW	SN54S251	J, W	SN74S251	J, N	7-362
	3-State	17 ns	21 ns	21 ns	250 mW	SN54251	J, W	SN74251	J, N	7-362
	3-State	17 ns	21 ns	21 ns	35 mW	SN54LS251	J, W	SN74LS251	J, N	7-362
	2-State	4.5 ns	8 ns	9 ns	225 mW	SN54S151	J, W	SN74S151	J, N	7-157
	2-State	8 ns	16 ns	22 ns	145 mW	SN54151A	J, W	SN74151A	J, N	7-157
	2-State	8 ns			130 mW	SN54152A	W			7-157
	2-State	11 ns	18 ns	27 ns	30 mW	SN54LS151	J, W	SN74LS151	J, N	7-157
	2-State	11 ns	18 ns	18 ns	28 mW	SN54LS152	W			7-157
DUAL 4-LINE-TO-1-LINE	3-State		12 ns	16 ns	35 mW	SN54LS253	J, W	SN74LS253	J, N	7-369
	2-State	15 ns		22 ns	31 mW	SN54LS352	J, W	SN74LS352	J, N	7-454
	3-State	12 ns		21 ns	43 mW	SN54LS353	J, W	SN74LS353	J, N	7-457
	2-State		6 ns	9.5 ns	225 mW	SN54S153	J, W	SN74S153	J, N	7-165
	2-State		14 ns	17 ns	180 mW	SN54153	J, W	SN74153	J, N	7-165
	2-State		14 ns	17 ns	31 mW	SN54LS153	J, W	SN74LS153	J, N	7-165
	2-State		27 ns	34 ns	90 mW	SN54L153	J	SN74L153	J, N	7-165
QUADRUPLE 2-LINE-TO-1-LINE WITH STORAGE	2-State		20 ns [†]		65 mW	SN54LS298	J, W	SN74LS298	J, N	7-432
	2-State		20 ns [†]		195 mW	SN54298	J, W	SN74298	J, N	7-432
	2-State		20 ns [†]		32 mW	SN54LS398	J	SN74LS398	J, N	7-499
	2-State	20 ns [†]	20 ns [†]		37 mW	SN54LS399	J, W	SN74LS399	J, N	7-499
	2-State		120 ns [†]		25 mW	SN54L98	J	SN74L98	J, N	7-107
QUADRUPLE 2-LINE-TO-1-LINE	3-State	4 ns		14 ns	280 mW	SN54S258	J, W	SN74S258	J, N	7-372
	3-State		5 ns	14 ns	320 mW	SN54S257	J, W	SN74S257	J, N	7-372
	2-State	4 ns		7 ns	195 mW	SN54S158	J, W	SN74S158	J, N	7-181
	2-State		5 ns	8 ns	250 mW	SN54S157	J, W	SN74S157	J, N	7-181
	3-State	12 ns		20 ns	60 mW	SN54LS258A*	J, W	SN74LS258A*	J, N	7-372
	3-State		12 ns	20 ns	60 mW	SN54LS257A*	J, W	SN74LS257A*	J, N	7-372
	2-State	7 ns		12 ns	24 mW	SN54LS158	J, W	SN74LS158	J, N	7-181
	2-State		9 ns	14 ns	49 mW	SN54LS157	J, W	SN74LS157	J, N	7-181
	2-State		9 ns	14 ns	150 mW	SN54157	J, W	SN74157	J, N	7-181
	2-State		18 ns	27 ns	75 mW	SN54L157	J	SN74L157	J, N	7-181

[†]From clock.

*New product in development as of October 1976.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE


DECODERS/DEMULPLEXERS

DESCRIPTION	TYPE OF OUTPUT	TYPICAL SELECT TIME	TYPICAL ENABLE TIME	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
					-55°C to 125°C		0°C to 70°C		
					Part No.	Package	Part No.	Package	
4-LINE-TO-16-LINE	Totem-Pole	23 ns	19 ns	170 mW	SN54154	J, W	SN74154	J, N	7-171
	Totem-Pole	46 ns	38 ns	85 mW	SN54L154	J	SN74L154	J, N	7-171
	Open-Collector	24 ns	19 ns	170 mW	SN54159	J, W	SN74159	J, N	7-188
4-LINE-TO-10-LINE, BCD-TO-DECIMAL	Totem-Pole	17 ns		35 mW	SN54LS42	J, W	SN54LS42	J, N	7-15
	Totem-Pole	17 ns		140 mW	SN5442A	J, W	SN7442A	J, N	
	Totem-Pole	34 ns		70 mW	SN54L42	J	SN74L42	J, N	
4-LINE-TO-10-LINE, EXCESS-3-TO-DECIMAL	Totem-Pole	17 ns		140 mW	SN5443A	J, W	SN7443A	J, N	7-15
	Totem-Pole	34 ns		70 mW	SN54L43	J	SN74L43	J, N	
4-LINE-TO-10-LINE EXCESS-3-GRAY-TO-DECIMAL	Totem-Pole	17 ns		140 mW	SN5444A	J, W	SN7444A	J, N	7-15
	Totem-Pole	34 ns		70 mW	SN54L44	J	SN74L44	J, N	
3-LINE-TO-8-LINE	Totem-Pole	8 ns	7 ns	245 mW	SN54S138	J, W	SN74S138	J, N	7-134
	Totem-Pole	22 ns	21 ns	31 mW	SN54LS138	J, W	SN74LS138	J, N	7-134
DUAL 2-LINE-TO-4-LINE	Totem-Pole	7.5 ns	6 ns	300 mW	SN54S139	J, W	SN74S139	J, N	7-134
	Totem-Pole	22 ns	19 ns	34 mW	SN54LS139	J, W	SN74LS139	J, N	7-134
	Totem-Pole	18 ns	15 ns	30 mW	SN54LS155	J, W	SN74LS155	J, N	7-175
	Totem-Pole	21 ns	16 ns	125 mW	SN54155	J, W	SN74155	J, N	7-175
	Open-Collector	23 ns	18 ns	125 mW	SN54156	J, W	SN74156	J, N	7-175
	Open-Collector	33 ns	26 ns	31 mW	SN54LS156	J, W	SN74LS156	J, N	7-175

OPEN-COLLECTOR DISPLAY DECODERS/DRIVERS WITH COUNTERS/LATCHES

DESCRIPTION	OUTPUT SINK CURRENT	OFF-STATE OUTPUT VOLTAGE	TYP TOTAL POWER DISSIPATION	BLANKING	DEVICE TYPE AND PACKAGE				PAGE NO.
					-55°C to 125°C		0°C to 70°C		
					Part No.	Package	Part No.	Package	
BCD COUNTER/ 4-BIT LATCH/ BCD-TO-DECIMAL DECODER/DRIVER	7 mA	55 V	340 mW				SN74142	J, N	7-140
BCD COUNTER/ 4-BIT LATCH/ BCD-TO-SEVEN- SEGMENT DECODER/ LED DRIVER	Constant Current 15 mA	7 V	280 mW	Ripple	SN54143	J, W	SN74143	J, N	7-143
BCD COUNTER/ 4-BIT LATCH/ BCD-TO-SEVEN- SEGMENT DECODER/ LAMP DRIVER	20 mA 25 mA	15 V 15 V	280 mW 280 mW	Ripple Ripple	SN54144	J, W	SN74144	J, N	7-143

RESULTANT DISPLAYS USING '143, '144



MSI/LSI FUNCTIONS

FUNCTIONAL INDEX/SELECTION GUIDE


OPEN-COLLECTOR DISPLAY DECODERS/DRIVERS

DESCRIPTION	OUTPUT SINK CURRENT	OFF-STATE OUTPUT VOLTAGE	TYP TOTAL POWER DISSIPATION	BLANKING	DEVICE TYPE AND PACKAGE				PAGE NO.
					-55°C to 125°C		0°C to 70°C		
BCD-TO-DECIMAL DECODERS/DRIVERS	80 mA	30 V	215 mW	Invalid Codes	SN5445	J, W	SN7445	J, N	7-20
	80 mA	15 V	35 mW	Invalid Codes			SN74LS145	J, N	7-148
	12 mA	15 V	35 mW	Invalid Codes	SN54LS145	J, W			7-148
	80 mA	15 V	215 mW	Invalid Codes	SN54145	J, W	SN74145	J, N	7-148
	7 mA	60 V	80 mW	Invalid Codes			SN74141	J, N	7-138
BCD-TO- SEVEN-SEGMENT DECODERS/DRIVERS	40 mA	30 V	320 mW	Ripple	SN5446A	J, W	SN7446A	J, N	7-22
	40 mA	30 V	320 mW	Ripple	SN54246	J, W	SN74246	J, N	7-22
	40 mA	15 V	320 mW	Ripple	SN5447A	J, W	SN7447A	J, N	7-22
	40 mA	15 V	320 mW	Ripple	SN54247	J, W	SN74247	J, N	7-351
	24 mA	15 V	35 mW	Ripple			SN74LS47	J, N	7-22
	24 mA	15 V	35 mW	Ripple			SN74LS247	J, N	7-351
	12 mA	15 V	35 mW	Ripple	SN54LS47	J, W			7-22
	12 mA	15 V	35 mW	Ripple	SN54LS247	J, W			7-351
	20 mA	30 V	133 mW	Ripple	SN54L46	J	SN74L46	J, N	7-22
	20 mA	15 V	133 mW	Ripple	SN54L47	J	SN74L47	J, N	7-22
	6.4 mA	5.5 V	265 mW	Ripple	SN5448	J, W	SN7448	J, N	7-22
	6.4 mA	5.5 V	265 mW	Ripple	SN54248	J, W	SN74248	J, N	7-351
	6 mA	5.5 V	125 mW	Ripple			SN74LS48	J, N	7-22
	6 mA	5.5 V	125 mW	Ripple			SN74LS248	J, N	7-351
	2 mA	5.5 V	125 mW	Ripple	SN54LS48	J, W			7-22
	2 mA	5.5 V	125 mW	Ripple	SN54LS248	J, W			7-351
	10 mA	5.5 V	165 mW	Direct	SN5449	W			7-22
	10 mA	5.5 V	265 mW	Direct	SN54249	J, W	SN74249	J, N	7-351
	8 mA	5.5 V	40 mW	Direct			SN74LS249	J, N	7-351
	8 mA	5.5 V	40 mW	Direct			SN74LS49	J, N	7-22
	4 mA	5.5 V	40 mW	Direct		SN54LS49	J, W		7-22
	4 mA	5.5 V	40 mW	Direct		SN54LS249	J, W		7-351

RESULTANT DISPLAYS USING '46A, '47A, '48, '49, 'L46, 'L47, 'LS47, 'LS48, 'LS49



RESULTANT DISPLAYS USING '246, '247, '248, '249, 'LS247, 'LS248, 'LS249



MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

BUS TRANSCEIVERS AND DRIVERS

DESCRIPTION	TYPICAL PROPAGATION DELAY TIMES	MAXIMUM SOURCE CURRENT	MAXIMUM SINK CURRENT	DEVICE TYPE AND PACKAGE				PAGE NO.
				-55°C to 125°C		0°C to 70°C		
CONTROLLER AND BUS DRIVER FOR 8080A SYSTEMS		-1 mA	10 mA			SN74S428	N	7-514
		-1 mA	10 mA			SN74S438	N	
OCTAL BUS TRANSCEIVERS	12 ns	-12 mA	12 mA	SN54LS245*	J	SN74LS245*	J, N	7-349
4-BIT BUS TRANSCEIVERS WITH STORAGE	10 ns	-6.5 mA	20 mA	SN54S226*	J, W	SN74S226*	J, N	7-345

ASYNCHRONOUS COUNTERS (RIPPLE CLOCK)—NEGATIVE-EDGE TRIGGERED

1

DESCRIPTION	COUNT FREQ	PARALLEL LOAD	CLEAR	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
					-55°C to 125°C		0°C to 70°C		
DECADE	50 MHz	Yes	Low	240 mW	SN54196	J, W	SN74196	J, N	7-331
	100 MHz	Yes	Low	375 mW	SN54S196	J, W	SN74S196	J, N	7-331
	35 MHz	Yes	Low	150 mW	SN54176	J, W	SN74176	J, N	7-259
	32 MHz	Set-to-9	High	40 mW	SN54LS90	J, W	SN74LS90	J, N	7-72
	32 MHz	Set-to-9	High	40 mW	SN54LS290	J, W	SN74LS290	J, N	7-423
	32 MHz	Set-to-9	High	160 mW	SN5490A	J, W	SN7490A	J, N	7-72
	32 MHz	Set-to-9	High	160 mW	SN54290	J, W	SN74290	J, N	7-423
	30 MHz	Yes	Low	60 mW	SN54LS196	J, W	SN74LS196	J, N	7-331
	3 MHz	Set-to-9	High	20 mW	SN54L90	J, T	SN74L90	J, N	7-72
4-BIT BINARY	50 MHz	Yes	Low	240 mW	SN54197	J, W	SN74197	J, N	7-331
	100 MHz	Yes	Low	375 mW	SN54S197	J, W	SN74S197	J, N	7-331
	35 MHz	Yes	Low	150 mW	SN54177	J, W	SN74177	J, N	7-259
	32 MHz	None	High	39 mW	SN54LS93	J, W	SN74LS93	J, N	7-72
	32 MHz	None	High	39 mW	SN54LS293	J, W	SN74LS293	J, N	7-423
	32 MHz	None	High	160 mW	SN5493A	J, W	SN7493A	J, N	7-72
	32 MHz	None	High	160 mW	SN54293	J, W	SN74293	J, N	7-423
	30 MHz	Yes	Low	60 mW	SN54LS197	J, W	SN74LS197	J, N	7-331
	3 MHz	None	High	20 mW	SN54L93	J, T	SN74L93	J, N	7-72
DIVIDE-BY-12	32 MHz	None	High	39 mW	SN54LS92	J, W	SN74LS92	J, N	7-72
	32 MHz	None	High	160 mW	SN5492A	J, W	SN7492A	J, N	
DUAL DECADE	25 MHz	None	High	210 mW	SN54390	J, W	SN74390	J, N	7-489
	35 MHz	None	High	75 mW	SN54LS390	J, W	SN74LS390	J, N	7-489
	25 MHz	Set-to-9	High	225 mW	SN54490	J, W	SN74490	J, N	7-520
	35 MHz	Set-to-9	High	75 mW	SN54LS490	J, W	SN74LS490	J, N	7-520
DUAL 4-BIT BINARY	25 MHz	None	High	190 mW	SN54393	J, W	SN74393	J, N	7-489
	35 MHz	None	High	75 mW	SN54LS393	J, W	SN74LS393	J, N	7-489

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

SYNCHRONOUS COUNTERS—POSITIVE-EDGE TRIGGERED

DESCRIPTION	COUNT FREQ	PARALLEL LOAD	CLEAR	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
					-55°C to 125°C		0°C to 70°C		
					Part No.	Package	Part No.	Package	
DECADE	40 MHz	Sync	Sync-L	475 mW	SN54S162	J, W	SN74S162	J, N	7-190
	25 MHz	Sync	Sync-L	93 mW	SN54LS162A	J, W	SN74LS162A	J, N	
	25 MHz	Sync	Async-L	93 mW	SN54LS160A	J, W	SN74LS160A	J, N	
	25 MHz	Sync	Sync-L	305 mW	SN54162	J, W	SN74162	J, N	
	25 MHz	Sync	Async-L	305 mW	SN54160	J, W	SN74160	J, N	
DECADE UP/DOWN	40 MHz	Sync	None	500 mW	SN54S168	J, W	SN74S168	J, N	7-226
	25 MHz	Sync	None	100 mW	SN54LS168A	J, W	SN74LS168A	J, N	7-226
	25 MHz	Async	Async-H	85 mW	SN54LS192	J, W	SN74LS192	J, N	7-306
	25 MHz	Async	Async-H	325 mW	SN54192	J, W	SN74192	J, N	7-306
	20 MHz	Async	None	100 mW	SN54LS190	J, W	SN74LS190	J, N	7-296
	20 MHz	Async	None	325 mW	SN54190	J, W	SN74190	J, N	7-296
	3 MHz	Async	Async-H	42 mW	SN54L192	J	SN74L192	J, N	7-306
DECADE RATE MULTIPLIER, $\frac{1}{N_{10}}$	25 MHz	Set-to-9	Async-H	270 mW	SN54167	J, W	SN74167	J, N	7-222
4-BIT BINARY	40 MHz	Sync	Sync-L	475 mW	SN54S163	J, W	SN74S163	J, N	7-190
	25 MHz	Sync	Sync-L	93 mW	SN54LS163A	J, W	SN74LS163A	J, N	
	25 MHz	Sync	Async-L	93 mW	SN54LS161A	J, W	SN74LS161A	J, N	
	25 MHz	Sync	Sync-L	305 mW	SN54163	J, W	SN74163	J, N	
	25 MHz	Sync	Async-L	305 mW	SN54161	J, W	SN74161	J, N	
4-BIT BINARY UP/DOWN	40 MHz	Sync	None	500 mW	SN54S169	J, W	SN74S169	J, N	7-226
	25 MHz	Sync	None	100 mW	SN54LS169A	J, W	SN74LS169A	J, N	7-226
	25 MHz	Async	Async-H	85 mW	SN54LS193	J, W	SN74LS193	J, N	7-306
	25 MHz	Async	Async-H	325 mW	SN54193	J, W	SN74193	J, N	7-306
	20 MHz	Async	None	90 mW	SN54LS191	J, W	SN74LS191	J, N	7-296
	20 MHz	Async	None	325 mW	SN54191	J, W	SN74191	J, N	7-296
	3 MHz	Async	Async-H	42 mW	SN54L193	J	SN74L193	J, N	7-306
6-BIT BINARY RATE MULTIPLIER, $\frac{1}{N_2}$	25 MHz		Async-H	345 mW	SN5497	J, W	SN7497	J, N	7-102

BIPOLAR BIT-SLICE PROCESSOR ELEMENTS†

DESCRIPTION	CASCADABLE TO N-BITS	TYPICAL μ -OPERATION TIME	TECHNOLOGY	DEVICE TYPE AND PACKAGE			
				-55°C to 125°C		0°C to 70°C	
				Part No.	Package	Part No.	Package
4-BIT SLICE	Yes	100 ns	STTL	SN54S481	J	SN74S481	J, N
	Yes	230 ns	I ² L	SBP0400AM	J	SBP0400AC	J, N
	Yes	230 ns	I ² L	SBP0401AM	J	SBP0401AC	J, N

FIRST-IN FIRST-OUT MEMORIES (FIFO'S)†

DESCRIPTION	TYPE OF OUTPUT	DELAY TIME FROM CLOCK	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE			
				-55°C to 125°C		0°C to 70°C	
				Part No.	Package	Part No.	
ASYNCHRONOUS 16 X 5	3-State	50 ns	400 mW			SN74S225	J

†See Bipolar Microcomputer Components Data Book, LCC4270.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

RANDOM-ACCESS READ-WRITE MEMORIES (RAM'S)

DESCRIPTION	ORGANI- ZATION	TYPE OF OUTPUT	TYPICAL ADDRESS TIME	TYPICAL ENABLE TIME	TYP POWER DISSIPATION PER BIT	DEVICE TYPE AND PACKAGE				PAGE NO.
						-55°C to 125°C		0°C to 70°C		
						Device	Package	Device	Package	
1024-BIT ARRAYS WITH POWER-DOWN	1024 X 1	3-State	65 ns	20 ns	0.2/0.07 mW	SN54LS215	JD	SN74LS215	JD, N	†
	1024 X 1	O-C	65 ns	20 ns	0.2/0.07 mW	SN54LS315	JD	SN74LS315	JD, N	†
1024-BIT ARRAYS	1024 X 1	3-State	65 ns	20 ns	0.2 mW	SN54LS214	JD	SN74LS214	JD, N	†
	1024 X 1	3-State	30 ns	15 ns	0.51 mW	SN54S214	JD	SN74S214	JD, N	†
	1024 X 1	O-C	65 ns	20 ns	0.2 mW	SN54LS314	JD	SN74LS314	JD, N	†
	1024 X 1	O-C	30 ns	15 ns	0.51 mW	SN54S314	JD	SN74S314	JD, N	†
	256 X 4	3-State	60 ns	20 ns	0.3 mW	SN54LS207	J	SN74LS207	J, N	†
	256 X 4	3-State	40 ns	15 ns	0.59 mW	SN54S207	J	SN74S207	J, N	†
	256 X 4	3-State	60 ns	20 ns	0.3 mW	SN54LS208	J	SN74LS208	J, N	†
	256 X 4	3-State	40 ns	15 ns	0.59 mW	SN54S208	J	SN74S208	J, N	†
256-BIT ARRAYS WITH POWER-DOWN	256 X 1	3-State	35 ns	15 ns	1.1/0.39 mW	SN54LS202	J, W	SN74LS202	J, N	†
	256 X 1	O-C	35 ns	15 ns	1.1/0.39 mW	SN54LS302	J, W	SN74LS302	J, N	†
256-BIT ARRAYS	256 X 1	3-State	35 ns	15 ns	1.1 mW	SN54LS200A	J, W	SN74LS200A	J, N	†
	256 X 1	3-State	25 ns	15 ns	1.9 mW	SN54S200A	J, W	SN74S200A	J, N	†
	256 X 1	3-State	42 ns	17 ns	1.9 mW	SN54S201	J, W	SN74S201	J, N	†
	256 X 1	O-C	35 ns	15 ns	1.1 mW	SN54LS300A	J, W	SN74LS300A	J, N	†
	256 X 1	O-C	25 ns	15 ns	1.9 mW	SN54S300A	J, W	SN74S300A	J, N	†
	256 X 1	O-C	42 ns	13 ns	1.9 mW	SN54S301	J, W	SN74S301	J, N	†
64-BIT ARRAYS	16 X 4	3-State	25 ns	12 ns	5.9 mW	SN54S189	J, W	SN74S189	J, N	†
	16 X 4	O-C	25 ns	12 ns	5.9 mW	SN54S289	J, W	SN74S289	J, N	†
	16 X 4	O-C	32 ns	30 ns	5.9 mW			SN7489	J, N	†
16-BIT ARRAYS	16 X 1	O-C	15 ns	15 ns	14 mW	SN5481A	J, W	SN7481A	J, N	†
	16 X 1	O-C	15 ns	15 ns	14 mW	SN5484A	J, W	SN7484A	J, N	†
16-BIT MULTIPLE-PORT REGISTER FILE	8 X 2	3-State	33 ns	15 ns	35 mW			SN74172	J, N	7-245
16-BIT REGISTER FILE	4 X 4	O-C	27 ns	15 ns	7.8 mW	SN54LS170	J, W	SN74LS170	J, N	7-237
	4 X 4	O-C	30 ns	15 ns	40 mW	SN54170	J, W	SN74170	J, N	7-237
	4 X 4	3-State	24 ns	19 ns	9.3 mW	SN54LS670	J, W	SN74LS670	J, N	7-526

READ-ONLY MEMORIES (ROM'S)†

DESCRIPTION	ORGANI- ZATION	TYPE OF OUTPUT	TYPICAL ADDRESS TIME	TYPICAL ENABLE TIME	TYP POWER DISSIPATION PER BIT	DEVICE TYPE AND PACKAGE			
						-55°C to 125°C		0°C to 70°C	
						Device	Package	Device	Package
2048-BIT ARRAYS	512 X 4	O-C	45 ns	15 ns	0.26 mW	SN54S270	J	SN74S270	J, N
	256 X 8	O-C	45 ns	15 ns	0.26 mW	SN54S271	J	SN74S271	J, N
	512 X 4	3-State	45 ns	15 ns	0.26 mW	SN54S370	J	SN74S370	J, N
	256 X 8	3-State	45 ns	15 ns	0.26 mW	SN54S371	J	SN74S371	J, N
1024-BIT ARRAYS	256 X 4	O-C	40 ns	20 ns	0.46 mW	SN54187	J, W	SN74187	J, N
256-BIT ARRAYS	32 X 8	O-C	26 ns	22 ns	1.1 mW	SN5488A	J, W	SN7488A	J, N

†See Bipolar Microcomputer Components Data Book, LCC4270.

MSI/LSI FUNCTIONS FUNCTIONAL INDEX/SELECTION GUIDE

PROGRAMMABLE READ-ONLY MEMORIES (PROM'S)†

DESCRIPTION	ORGANIZATION	TYPE OF OUTPUT	TYPICAL ADDRESS TIME	TYPICAL ENABLE TIME	TYP POWER DISSIPATION PER BIT	DEVICE TYPE AND PACKAGE			
						-55°C to 125°C		0°C to 70°C	
4096-BIT ARRAYS	512 X 8	3-State	55 ns	20 ns	0.14 mW	SN54S472	J	SN74S472	J, N
	512 X 8	O-C	55 ns	20 ns	0.14 mW	SN54S473	J	SN74S473	J, N
	512 X 8	3-State	55 ns	20 ns	0.14 mW	SN54S474	J, W	SN74S474	J, N
	512 X 8	O-C	55 ns	20 ns	0.14 mW	SN54S475	J, W	SN74S475	J, N
2048-BIT ARRAYS	256 X 8	O-C	50 ns	20 ns	0.24 mW	SN54S470	J	SN74S470	J, N
	256 X 8	3-State	50 ns	20 ns	0.27 mW	SN54S471	J	SN74S471	J, N
1024-BIT ARRAYS	256 X 4	3-State	40 ns	15 ns	0.49 mW	SN54S287	J, W	SN74S287	J, N
	256 X 4	O-C	40 ns	15 ns	0.49 mW	SN54S387	J, W	SN74S387	J, N
512-BIT ARRAYS	64 X 8	O-C	50 ns	47 ns	0.6 mW	SN54186	J, W	SN74186	J, N
256-BIT ARRAYS	32 X 8	O-C	29 ns	28 ns	1.3 mW	SN54188A	J, W	SN74188A	J, N
	32 X 8	O-C	25 ns	12 ns	1.56 mW	SN54S188	J, W	SN74S188	J, N
	32 X 8	3-State	25 ns	12 ns	1.56 mW	SN54S288	J, W	SN74S288	J, N

MICROPROCESSOR CONTROLLERS AND SUPPORT FUNCTIONS

DESCRIPTION	SYSTEM APPLICATION	TYP TOTAL POWER DISSIPATION	DEVICE TYPE AND PACKAGE				PAGE NO.
			-55°C to 125°C		0°C to 70°C		
SYSTEM CONTROLLERS	8080A	700 mW			SN74S428 (TIM8228)	N	7-514
	8080A	700 mW			SN74S438 (TIM8238)	N	7-514
	Universal	450 mW	SN54S482	J	SN74S482	J, N	†
REGISTERS	TMS 9900	110 mW	SN54LS259	J, W	SN74LS259 (TIM9906)	J, N	7-376
	MOS	210 mW	SN54LS363*	J	SN74LS363*	J, N	7-467
		210 mW	SN54LS364*	J	SN74LS364*	J, N	7-467
MULTI-MODE LATCHES	8080A	410 mW	SN54S412	J, W	SN74S412 (TIM8212)	J, N	7-502
TRANSCEIVERS AND BUS DRIVERS		625 mW	SN54S226*	J, W	SN74S226*	J, N	7-345
		207 mW	SN54LS245*	J	SN74LS245*	J, N	7-349
TRANSCEIVERS AND BUS DRIVERS (SSI)		98 mW	SN54LS240	J	SN74LS240	J, N	6-83
		450 mW	SN54S240	J	SN74S240	J, N	6-83
		100 mW	SN54LS241	J	SN74LS241	J, N	6-83
		538 mW	SN54S241	J	SN74S241	J, N	6-83
		128 mW	SN54LS242	J, W	SN74LS242	J, N	6-87
		128 mW	SN54LS243	J, W	SN74LS243	J, N	6-87
	100 mW	SN54LS244	J	SN74LS244	J, N	6-83	
CLOCK ELEMENTS	TMS 9900	669 mW			SN74LS362 (TIM9904)*	J, N	7-460
	8080A	719 mW			SN74LS424 (TIM8224)	J, N	7-507
LOGIC ELEMENTS	TMS 9900	190 mW	SN54148	J, W	SN74148 (TIM9907)	J, N	7-151
	TMS 9900	35 mW	SN54LS251	J, W	SN74LS251 (TIM9905)	J, N	7-362
	TMS 9900	63 mW	SN54LS348*	J, W	SN74LS348 (TIM9908)*	J, N	7-448

*New product in development as of October 1976.

†See Bipolar Microcomputer Components Data Book, LCC4270.