

Model			FCU - 4 C / FCU - 4	FCU - 6 C / FCU - 6	FCU - 8 C / FCU - 8	FCU - 10 C / FCU - 10	FCU - 12 C / FCU - 12	FCU - 14 C / FCU - 14
Nominal Cooling Capacity		KCal/hr	3000	4500	6000	7500	9000	10500
		Tons	1.0 TR	1.5 TR	2.0 TR	2.5 TR	3.0 TR	3.5 TR
Power Supply		V/Ph/Hz	230/1/50					
Dimensions	Height	mm	266	266	266	266	266	266
	Width	mm	1110	1110	1400	1600	1790	2000
	Depth	mm	513	513	513	513	513	513
Fan	Type		Centrifugal Forward Curve, DIDW					
	Qty	Nos	2	2	2	3	4	4
Motor	Power	HP	1/12	1/12	1/10	1/10 & 1/12	1/10	1/10
	Speed	Rpm	920	920	1050	1050 & 920	1050	1050
	Qty	Nos	1	1	1	2	2	2
Coil	Tube Material		Inner Grooved Copper Tube					
	Tube O.D.	mm	9.5					
	Fin Material		Aluminium					
	Rows Deep	Nos	3					
	Fins/cm		4					
	Face Area	Sq.M.	0.14	0.17	0.23	0.27	0.31	0.35
Condensate Drainage	O.D.	mm	20					
Air Filter			Woven high density polyethylene, washable					
Piping	Inlet	mm	20	20	25	25	25	25
	Outlet	mm	20	20	25	25	25	25
Control Valve*	Make		Siemens					
	Type		3 way spring return type					
Thermostat*			Heating/Cooling with 3 speed regulating switch					
Ball Valve*	Size	mm	20	20	20	25	25	25
Operating Weight		kg	35	37	44	48	66	69