

Isabelle/HOL — Higher-Order Logic

October 1, 2005

Contents

1	HOL: The basis of Higher-Order Logic	15
1.1	Primitive logic	15
1.1.1	Core syntax	15
1.1.2	Additional concrete syntax	16
1.1.3	Axioms and basic definitions	17
1.1.4	Generic algebraic operations	18
1.2	Equality	19
1.3	Congruence rules for application	19
1.4	Equality of booleans – iff	19
1.5	True	20
1.6	Universal quantifier	20
1.7	False	20
1.8	Negation	21
1.9	Implication	21
1.10	Existential quantifier	22
1.11	Conjunction	22
1.12	Disjunction	22
1.13	Classical logic	23
1.14	Unique existence	23
1.15	THE: definite description operator	24
1.16	Classical intro rules for disjunction and existential quantifiers	24
1.17	Theory and package setup	25
1.17.1	Intuitionistic Reasoning	25
1.17.2	Atomizing meta-level connectives	26
1.17.3	Classical Reasoner setup	26
1.17.4	Simplifier setup	26
1.17.5	Code generator setup	31
1.18	Other simple lemmas	31
1.19	Generic cases and induction	32
1.19.1	Tags, for the ATP Linkup	33

2	Lattice-Locales: Lattices via Locales	33
2.1	Lattices	33
2.2	Distributive lattices	35
3	Orderings: Type classes for \leq	36
3.1	Order signatures and orders	36
3.2	Monotonicity	37
3.3	Orders	37
3.4	Transitivity rules for calculational reasoning	39
3.5	Least value operator	39
3.6	Linear / total orders	40
3.7	Setup of transitivity reasoner as Solver	41
3.8	Min and max on (linear) orders	41
3.9	Bounded quantifiers	42
3.10	Extra transitivity rules	43
4	LOrder: Lattice Orders	45
5	Set: Set theory for higher-order logic	48
5.1	Basic syntax	49
5.2	Additional concrete syntax	49
5.2.1	Bounded quantifiers	51
5.3	Rules and definitions	52
5.4	Lemmas and proof tool setup	53
5.4.1	Relating predicates and sets	53
5.4.2	Bounded quantifiers	53
5.4.3	Congruence rules	54
5.4.4	Subsets	55
5.4.5	Equality	56
5.4.6	The universal set – UNIV	57
5.4.7	The empty set	57
5.4.8	The Powerset operator – Pow	58
5.4.9	Set complement	58
5.4.10	Binary union – Un	58
5.4.11	Binary intersection – Int	59
5.4.12	Set difference	59
5.4.13	Augmenting a set – insert	59
5.4.14	Singletons, using insert	60
5.4.15	Unions of families	61
5.4.16	Intersections of families	61
5.4.17	Union	61
5.4.18	Inter	62
5.4.19	Set reasoning tools	63
5.4.20	The “proper subset” relation	64

5.5	Further set-theory lemmas	65
5.5.1	Derived rules involving subsets.	65
5.5.2	Equalities involving union, intersection, inclusion, etc.	66
5.5.3	Monotonicity of various operations	82
5.6	Inverse image of a function	83
5.6.1	Basic rules	84
5.6.2	Equations	84
5.7	Getting the Contents of a Singleton Set	85
5.8	Transitivity rules for calculational reasoning	85
6	Typedef: HOL type definitions	87
6.1	The Composition Operator: $f \circ g$	90
6.2	The Injectivity Predicate, <i>inj</i>	91
6.3	The Predicate <i>inj-on</i> : Injectivity On A Restricted Domain	91
6.4	The Predicate <i>surj</i> : Surjectivity	92
6.5	The Predicate <i>bij</i> : Bijection	92
6.6	Facts About the Identity Function	93
6.7	Function Updating	94
6.8	<i>override-on</i>	95
6.9	<i>swap</i>	95
7	Product-Type: Cartesian products	96
7.1	Unit	96
7.2	Pairs	97
7.2.1	Type definition	97
7.2.2	Abstract constants and syntax	97
7.2.3	Definitions	98
7.2.4	Lemmas and proof tool setup	99
7.3	Code generator setup	106
8	FixedPoint: Fixed Points and the Knaster-Tarski Theorem	107
8.1	Proof of Knaster-Tarski Theorem using <i>lfp</i>	107
8.2	General induction rules for greatest fixed points	107
8.3	Proof of Knaster-Tarski Theorem using <i>gfp</i>	108
8.4	Coinduction rules for greatest fixed points	108
8.5	Even Stronger Coinduction Rule, by Martin Coen	109
9	Sum-Type: The Disjoint Sum of Two Types	110
9.1	Freeness Properties for <i>Inl</i> and <i>Inr</i>	111
9.2	The Disjoint Sum of Sets	112
9.3	The <i>Part</i> Primitive	112

10 Relation: Relations	113
10.1 Definitions	113
10.2 The identity relation	114
10.3 Diagonal: identity over a set	115
10.4 Composition of two relations	115
10.5 Reflexivity	116
10.6 Antisymmetry	116
10.7 Symmetry and Transitivity	116
10.8 Converse	116
10.9 Domain	117
10.10 Range	118
10.11 Image of a set under a relation	118
10.12 Single valued relations	120
10.13 Graphs given by <i>Collect</i>	120
10.14 Inverse image	120
10.15 Concrete record syntax	121
11 Inductive: Support for inductive sets and types	122
11.1 Inductive sets	122
11.2 Inductive datatypes and primitive recursion	122
12 Transitive-Closure: Reflexive and Transitive closure of a relation	123
12.1 Reflexive-transitive closure	124
12.2 Transitive closure	126
12.3 Setup of transitivity reasoner	129
13 Wellfounded-Recursion: Well-founded Recursion	129
13.0.1 Minimal-element characterization of well-foundedness	131
13.0.2 Other simple well-foundedness results	131
13.0.3 Well-Foundedness Results for Unions	131
13.0.4 acyclic	132
13.1 Well-Founded Recursion	132
13.2 Code generator setup	133
13.3 Variants for TFL: the Recdef Package	133
13.4 LEAST and wellorderings	133
14 OrderedGroup: Ordered Groups	134
14.1 Semigroups, Groups	134
14.2 (Partially) Ordered Groups	136
14.3 Ordering Rules for Unary Minus	138
14.4 Support for reasoning about signs	140
14.5 Lemmas for the <i>cancel-numerals</i> simproc	141
14.6 Lattice Ordered (Abelian) Groups	141

14.7 Positive Part, Negative Part, Absolute Value	142
15 Ring-and-Field: (Ordered) Rings and Fields	148
15.1 Distribution rules	150
15.2 Ordering Rules for Multiplication	152
15.3 Products of Signs	153
15.4 More Monotonicity	155
15.5 Cancellation Laws for Relationships With a Common Factor	156
15.5.1 Special Cancellation Simprules for Multiplication . . .	157
15.6 Fields	158
15.7 Basic Properties of <i>inverse</i>	160
15.8 Calculations with fractions	161
15.8.1 Special Cancellation Simprules for Division	162
15.9 Division and Unary Minus	163
15.10 Ordered Fields	164
15.11 Anti-Monotonicity of <i>inverse</i>	165
15.12 Inverses and the Number One	166
15.13 Simplification of Inequalities Involving Literal Divisors . . .	166
15.14 Division and Signs	168
15.15 Cancellation Laws for Division	169
15.16 Division and the Number One	169
15.17 Ordering Rules for Division	170
15.18 Conditional Simplification Rules: No Case Splits	171
15.19 Reasoning about inequalities with division	172
15.20 Ordered Fields are Dense	173
15.21 Absolute Value	173
15.22 Miscellaneous	174
16 Nat: Natural numbers	175
16.1 Type <i>ind</i>	176
16.2 Type <i>nat</i>	176
16.3 Basic properties of "less than"	178
16.3.1 Introduction properties	178
16.3.2 Elimination properties	178
16.3.3 Inductive (?) properties	179
16.4 Properties of "less than or equal"	180
16.5 Arithmetic operators	183
16.6 <i>LEAST</i> theorems for type <i>nat</i>	184
16.7 <i>min</i> and <i>max</i>	184
16.8 Basic rewrite rules for the arithmetic operators	184
16.9 Addition	185
16.10 Multiplication	186
16.11 Monotonicity of Addition	187
16.12 Additional theorems about "less than"	187

16.13	Difference	188
16.14	More results about difference	189
16.15	Monotonicity of Multiplication	190
17	NatArith: Further Arithmetic Facts Concerning the Natural Numbers	192
17.1	Embedding of the Naturals into any <i>comm-semiring-1-cancel</i> : <i>of-nat</i>	194
18	Datatype-Universe: Analogues of the Cartesian Product and Disjoint Sum for Datatypes	196
18.1	Freeness: Distinctness of Constructors	198
18.2	Set Constructions	201
19	Datatype: Datatypes	205
19.1	Representing primitive types	206
19.2	Finishing the datatype package setup	207
19.3	Further cases/induct rules for tuples	207
19.4	The option type	208
19.4.1	Operations	208
19.5	Initial Lemmas	210
19.6	Remainder	210
19.7	Quotient	211
19.8	Simproc for Cancelling Div and Mod	212
19.9	Proving facts about Quotient and Remainder	212
19.10	Proving $a \text{ div } (b * c) = a \text{ div } b \text{ div } c$	213
19.11	Cancellation of Common Factors in Division	214
19.12	Further Facts about Quotient and Remainder	214
19.13	The Divides Relation	215
19.14	An “induction” law for modulus arithmetic.	218
20	Power: Exponentiation	218
20.1	Powers for Arbitrary Semirings	218
20.2	Exponentiation for the Natural Numbers	222
21	Finite-Set: Finite sets	223
21.1	Definition and basic properties	223
21.1.1	Finiteness and set theoretic constructions	224
21.2	A fold functional for finite sets	227
21.2.1	Commutative monoids	227
21.2.2	From <i>foldSet</i> to <i>fold</i>	228
21.2.3	Lemmas about <i>fold</i>	229
21.3	Generalized summation over a set	231
21.3.1	Properties in more restricted classes of structures	233

21.4	Generalized product over a set	236
21.4.1	Properties in more restricted classes of structures . . .	238
21.5	Finite cardinality	239
21.5.1	Cardinality of unions	241
21.5.2	Cardinality of image	242
21.5.3	Cardinality of products	242
21.5.4	Cardinality of the Powerset	243
21.6	A fold functional for non-empty sets	243
21.6.1	Determinacy for <i>fold1Set</i>	244
21.6.2	Semi-Lattices	245
21.6.3	Lemmas about <i>fold1</i>	245
21.6.4	Lattices	246
21.6.5	Fold laws in lattices	246
21.7	Min and Max	247
21.8	Properties of axclass <i>finite</i>	249
22	Wellfounded-Relations: Well-founded Relations	249
22.1	Measure Functions make Wellfounded Relations	250
22.1.1	‘Less than’ on the natural numbers	250
22.1.2	The Inverse Image into a Wellfounded Relation is Well- founded.	250
22.1.3	Finally, All Measures are Wellfounded.	251
22.2	Other Ways of Constructing Wellfounded Relations	251
22.2.1	Wellfoundedness of proper subset on finite sets.	251
22.2.2	Wellfoundedness of finite acyclic relations	251
22.2.3	Wellfoundedness of <i>samefst</i>	251
22.3	Weakly decreasing sequences (w.r.t. some well-founded order) stabilize.	252
23	Equiv-Relations: Equivalence Relations in Higher-Order Set Theory	252
23.1	Equivalence relations	252
23.2	Equivalence classes	253
23.3	Quotients	254
23.4	Defining unary operations upon equivalence classes	255
23.5	Defining binary operations upon equivalence classes	255
23.6	Cardinality results	257
24	IntDef: The Integers as Equivalence Classes over Pairs of Natural Numbers	257
24.1	Construction of the Integers	258
24.1.1	Preliminary Lemmas about the Equivalence Relation	258
24.1.2	<i>int</i> : Embedding the Naturals into the Integers	259
24.1.3	Integer Unary Negation	259

24.2 Integer Addition	259
24.3 Integer Multiplication	260
24.4 The \leq Ordering	261
24.5 Monotonicity results	262
24.6 Strict Monotonicity of Multiplication	263
24.7 Magnitude of an Integer, as a Natural Number: <i>nat</i>	263
24.8 Lemmas about the Function <i>int</i> and Orderings	265
24.9 The Constants <i>neg</i> and <i>iszero</i>	265
24.10 To simplify inequalities when Numeral1 can get simplified to 1	266
24.11 The Set of Natural Numbers	266
24.12 Embedding of the Integers into any <i>comm-ring-1</i> : <i>of-int</i>	267
24.13 The Set of Integers	268
24.14 More Properties of <i>setsum</i> and <i>setprod</i>	269
24.15 Configuration of the code generator	270
25 Numeral: Arithmetic on Binary Integers	271
25.1 The Functions <i>bin-succ</i> , <i>bin-pred</i> and <i>bin-minus</i>	274
25.2 Binary Addition and Multiplication: <i>bin-add</i> and <i>bin-mult</i>	274
25.3 Converting Numerals to Rings: <i>number-of</i>	275
25.4 Equality of Binary Numbers	277
25.5 Comparisons, for Ordered Rings	277
25.6 The Less-Than Relation	278
25.7 Simplification of arithmetic operations on integer constants.	279
25.8 Simplification of arithmetic when nested to the right	280
26 IntArith: Integer arithmetic	280
26.1 Instantiating Binary Arithmetic for the Integers	280
26.2 Inequality Reasoning for the Arithmetic Simproc	281
26.3 Special Arithmetic Rules for Abstract 0 and 1	281
26.4 Lemmas About Small Numerals	282
26.5 More Inequality Reasoning	283
26.6 The Functions <i>nat</i> and <i>int</i>	283
26.7 Induction principles for int	284
26.8 Intermediate value theorems	284
26.9 Products and 1, by T. M. Rasmussen	285
27 SetInterval: Set intervals	285
27.1 Various equivalences	287
27.2 Logical Equivalences for Set Inclusion and Equality	287
27.3 Two-sided intervals	288
27.3.1 Emptiness and singletons	288
27.4 Intervals of natural numbers	289
27.4.1 The Constant <i>lessThan</i>	289
27.4.2 The Constant <i>greaterThan</i>	289


27.4.3	The Constant <i>atLeast</i>	289
27.4.4	The Constant <i>atMost</i>	290
27.4.5	The Constant <i>atLeastLessThan</i>	290
27.4.6	Intervals of nats with <i>Suc</i>	290
27.4.7	Image	290
27.4.8	Finiteness	291
27.4.9	Cardinality	291
27.5	Intervals of integers	292
27.5.1	Finiteness	292
27.5.2	Cardinality	293
27.6	Lemmas useful with the summation operator <i>setsum</i>	293
27.6.1	Disjoint Unions	293
27.6.2	Disjoint Intersections	294
27.6.3	Some Differences	295
27.6.4	Some Subset Conditions	295
27.7	Summation indexed over intervals	295
27.8	Shifting bounds	297
27.9	The formula for geometric sums	297
28	Recdef: TFL: recursive function definitions	297
29	IntDiv: The Division Operators <i>div</i> and <i>mod</i>; the Divides Relation <i>dvd</i>	299
29.1	Uniqueness and Monotonicity of Quotients and Remainders	301
29.2	Correctness of <i>posDivAlg</i> , the Algorithm for Non-Negative Dividends	301
29.3	Correctness of <i>negDivAlg</i> , the Algorithm for Negative Dividends	302
29.4	Existence Shown by Proving the Division Algorithm to be Correct	302
29.5	General Properties of <i>div</i> and <i>mod</i>	303
29.6	Laws for <i>div</i> and <i>mod</i> with Unary Minus	304
29.7	Division of a Number by Itself	305
29.8	Computation of Division and Remainder	305
29.9	Monotonicity in the First Argument (Dividend)	308
29.10	Monotonicity in the Second Argument (Divisor)	308
29.11	More Algebraic Laws for <i>div</i> and <i>mod</i>	308
29.12	Proving $a \text{ div } (b * c) = a \text{ div } b \text{ div } c$	310
29.13	Cancellation of Common Factors in <i>div</i>	311
29.14	Distribution of Factors over <i>mod</i>	311
29.15	Splitting Rules for <i>div</i> and <i>mod</i>	311
29.16	Speeding up the Division Algorithm with Shifting	312
29.17	Computing <i>mod</i> by Shifting (proofs resemble those for <i>div</i>)	312
29.18	Quotients of Signs	313
29.19	The Divides Relation	313

29.20	Integer Powers	315
30	NatBin: Binary arithmetic for the natural numbers	316
30.1	Function <i>nat</i> : Coercion from Type <i>int</i> to <i>nat</i>	316
30.2	Function <i>int</i> : Coercion from Type <i>nat</i> to <i>int</i>	317
30.2.1	Successor	317
30.2.2	Addition	318
30.2.3	Subtraction	318
30.2.4	Multiplication	318
30.2.5	Quotient	318
30.2.6	Remainder	318
30.3	Comparisons	319
30.3.1	Equals (=)	319
30.3.2	Less-than (i)	319
30.4	Powers with Numeric Exponents	319
30.4.1	Nat	321
30.4.2	Arith	321
30.5	Comparisons involving (0::nat)	322
30.6	Comparisons involving Suc	322
30.7	Literal arithmetic involving powers	324
30.8	Literal arithmetic and <i>of-nat</i>	325
30.9	Lemmas for the Combination and Cancellation Simprocs . . .	326
30.9.1	For <i>combine-numerals</i>	326
30.9.2	For <i>cancel-numerals</i>	326
30.9.3	For <i>cancel-numeral-factors</i>	327
30.9.4	For <i>cancel-factor</i>	327
31	NatSimprocs: Simprocs for the Naturals	327
31.1	For simplifying $Suc\ m - K$ and $K - Suc\ m$	328
31.2	For <i>nat-case</i> and <i>nat-rec</i>	328
31.3	Various Other Lemmas	329
31.3.1	Evens and Odds, for Mutilated Chess Board	329
31.3.2	Removal of Small Numerals: 0, 1 and (in additive positions) 2	329
31.4	Special Simplification for Constants	330
31.5	Optional Simplification Rules Involving Constants	332
31.5.1	Division By -1	333
32	Presburger: Presburger Arithmetic: Cooper's Algorithm	333
33	Relation-Power: Powers of Relations and Functions	345

34 Parity: Even and Odd for ints and nats	347
34.1 Even and odd are mutually exclusive	348
34.2 Behavior under integer arithmetic operations	348
34.3 Equivalent definitions	349
34.4 even and odd for nats	349
34.5 Equivalent definitions	350
34.6 Parity and powers	351
34.7 An Equivalence for $0 \leq a^n$	353
34.8 Miscellaneous	353
35 GCD: The Greatest Common Divisor	353
36 Binomial: Binomial Coefficients	356
36.0.1 Theorems about <i>choose</i>	357
37 PreList: A Basis for Building the Theory of Lists	358
38 List: The datatype of finite lists	358
38.1 Basic list processing functions	359
38.1.1 <i>length</i>	364
38.1.2 <i>@</i> – append	364
38.1.3 <i>map</i>	366
38.1.4 <i>rev</i>	368
38.1.5 <i>set</i>	369
38.1.6 <i>filter</i>	370
38.1.7 <i>concat</i>	371
38.1.8 <i>nth</i>	372
38.1.9 <i>list-update</i>	372
38.1.10 <i>last</i> and <i>butlast</i>	374
38.1.11 <i>take</i> and <i>drop</i>	375
38.1.12 <i>takeWhile</i> and <i>dropWhile</i>	377
38.1.13 <i>zip</i>	378
38.1.14 <i>list-all2</i>	379
38.1.15 <i>foldl</i> and <i>foldr</i>	382
38.1.16 <i>upto</i>	382
38.1.17 <i>distinct</i> and <i>remdups</i>	384
38.1.18 <i>remove1</i>	385
38.1.19 <i>replicate</i>	385
38.1.20 <i>rotate1</i> and <i>rotate</i>	387
38.1.21 <i>sublist</i> — a generalization of <i>nth</i> to sets	388
38.1.22 Sets of Lists	389
38.1.23 <i>lists</i> : the list-forming operator over sets	389
38.1.24 For efficiency	390
38.1.25 Code generation	391

38.1.26	Inductive definition for membership	391
38.1.27	Lists as Cartesian products	391
38.2	Relations on Lists	392
38.2.1	Length Lexicographic Ordering	392
38.2.2	Lexicographic Ordering	393
38.2.3	Lifting a Relation on List Elements to the Lists	394
38.3	Miscellany	395
38.3.1	Characters and strings	395
38.3.2	Code generator setup	395
39	Map: Maps	396
39.1	<i>empty</i>	398
39.2	<i>map-upd</i>	398
39.3	<i>sum-case</i> and <i>empty/map-upd</i>	399
39.4	<i>chg-map</i>	399
39.5	<i>map-of</i>	399
39.6	<i>option-map</i> related	400
39.7	<i>map-comp</i> related	400
39.8	<i>++</i>	401
39.9	<i>restrict-map</i>	402
39.10	<i>map-upds</i>	402
39.11	<i>map-upd-s</i>	403
39.12	<i>dom</i>	404
39.13	<i>ran</i>	405
39.14	<i>map-le</i>	405
40	Refute: Refute	406
41	SAT: Reconstructing external resolution proofs for propositional logic	408
42	Hilbert-Choice: Hilbert's Epsilon-Operator and the Axiom of Choice	408
42.1	Hilbert's epsilon	409
42.2	Hilbert's Epsilon-operator	409
42.3	Axiom of Choice, Proved Using the Description Operator	410
42.4	Function Inverse	410
42.5	Inverse of a PI-function (restricted domain)	412
42.6	Other Consequences of Hilbert's Epsilon	412
42.7	Least value operator	413
42.8	Greatest value operator	414
42.9	The Meson proof procedure	415
42.9.1	Negation Normal Form	415
42.9.2	Pulling out the existential quantifiers	415

42.9.3	Generating clauses for the Meson Proof Procedure . .	416
42.10	Lemmas for Meson, the Model Elimination Procedure	416
42.10.1	Lemmas for Forward Proof	416
43	Infinite-Set: Infinte Sets and Related Concepts	417
43.1	Infinite Sets	417
43.2	Infinitely Many and Almost All	419
43.3	Miscellaneous	421
44	Extraction: Program extraction for HOL	421
44.1	Setup	421
44.2	Type of extracted program	421
44.3	Realizability	422
44.4	Computational content of basic inference rules	424
45	Reconstruction: Reconstructing external resolution proofs	429
46	Main: Main HOL	429



1 HOL: The basis of Higher-Order Logic

```
theory HOL
imports CPure
uses (cladata.ML) (blastdata.ML) (simpdata.ML) (eqrule-HOL-data.ML)
    (~~/src/Provers/eqsubst.ML)
```

```
begin
```

1.1 Primitive logic

1.1.1 Core syntax

```
classes type
defaultsort type
```

```
global
```

```
typedecl bool
```

```
arities
```

```
  bool :: type
  fun :: (type, type) type
```

```
judgment
```

```
  Trueprop      :: bool => prop          ((-) 5)
```

```
consts
```

```
  Not           :: bool => bool          (~ - [40] 40)
  True          :: bool
  False         :: bool
  arbitrary     :: 'a
```

```
  The          :: ('a => bool) => 'a
  All          :: ('a => bool) => bool      (binder ALL 10)
  Ex           :: ('a => bool) => bool      (binder EX 10)
  Ex1          :: ('a => bool) => bool      (binder EX! 10)
  Let          :: ['a, 'a => 'b] => 'b
```

```
  =            :: ['a, 'a] => bool         (infixl 50)
  &            :: [bool, bool] => bool      (infixr 35)
  |            :: [bool, bool] => bool      (infixr 30)
  -->         :: [bool, bool] => bool      (infixr 25)
```

```
local
```

```
consts
```

```
  If           :: [bool, 'a, 'a] => 'a      ((if (-)/ then (-)/ else (-)) 10)
```

1.1.2 Additional concrete syntax

nonterminals

letbinds letbind
case-syn cases-syn

syntax

-not-equal :: [*'a*, *'a*] => *bool* (infixl ~ = 50)
-The :: [*pttrn*, *bool*] => *'a* ((3THE -./ -) [0, 10] 10)

-bind :: [*pttrn*, *'a*] => *letbind* ((2- =/ -) 10)
 :: *letbind* => *letbinds* (-)
-binds :: [*letbind*, *letbinds*] => *letbinds* (-;/ -)
-Let :: [*letbinds*, *'a*] => *'a* ((let (-)/ in (-)) 10)

-case-syntax:: [*'a*, *cases-syn*] => *'b* ((case - of / -) 10)
-case1 :: [*'a*, *'b*] => *case-syn* ((2- =>/ -) 10)
 :: *case-syn* => *cases-syn* (-)
-case2 :: [*case-syn*, *cases-syn*] => *cases-syn* (-/ | -)

translations

x ~ = *y* == ~ (*x* = *y*)
THE x. P == *The* (%*x*. *P*)
-Let (-binds b bs) e == *-Let b (-Let bs e)*
let x = a in e == *Let a* (%*x*. *e*)

⟨ML⟩

syntax (output)

= :: [*'a*, *'a*] => *bool* (infix 50)
-not-equal :: [*'a*, *'a*] => *bool* (infix ~ = 50)

syntax (*xsymbols*)

Not :: *bool* => *bool* (¬ - [40] 40)
op & :: [*bool*, *bool*] => *bool* (infixr ∧ 35)
op | :: [*bool*, *bool*] => *bool* (infixr ∨ 30)
op --> :: [*bool*, *bool*] => *bool* (infixr → 25)
-not-equal :: [*'a*, *'a*] => *bool* (infix ≠ 50)
ALL :: [*idts*, *bool*] => *bool* ((3∀ -./ -) [0, 10] 10)
EX :: [*idts*, *bool*] => *bool* ((3∃ -./ -) [0, 10] 10)
EX! :: [*idts*, *bool*] => *bool* ((3∃! -./ -) [0, 10] 10)
-case1 :: [*'a*, *'b*] => *case-syn* ((2- ⇒/ -) 10)

syntax (*xsymbols* output)

-not-equal :: [*'a*, *'a*] => *bool* (infix ≠ 50)

syntax (HTML output)

-not-equal :: [*'a*, *'a*] => *bool* (infix ≠ 50)
Not :: *bool* => *bool* (¬ - [40] 40)

$op \ \&$	$:: [bool, bool] \Rightarrow bool$	$(\mathbf{infixr} \ \wedge \ 35)$
$op \ $	$:: [bool, bool] \Rightarrow bool$	$(\mathbf{infixr} \ \vee \ 30)$
-not-equal	$:: ['a, 'a] \Rightarrow bool$	$(\mathbf{infix} \ \neq \ 50)$
ALL	$:: [idts, bool] \Rightarrow bool$	$((\exists \forall \text{-./ -}) [0, 10] \ 10)$
EX	$:: [idts, bool] \Rightarrow bool$	$((\exists \exists \text{-./ -}) [0, 10] \ 10)$
$EX!$	$:: [idts, bool] \Rightarrow bool$	$((\exists \exists !\text{-./ -}) [0, 10] \ 10)$
syntax (<i>HOL</i>)		
ALL	$:: [idts, bool] \Rightarrow bool$	$((\exists ! \text{-./ -}) [0, 10] \ 10)$
EX	$:: [idts, bool] \Rightarrow bool$	$((\exists ? \text{-./ -}) [0, 10] \ 10)$
$EX!$	$:: [idts, bool] \Rightarrow bool$	$((\exists ? ! \text{-./ -}) [0, 10] \ 10)$

1.1.3 Axioms and basic definitions

axioms

eq-reflection: $(x=y) \Rightarrow (x==y)$

refl: $t = (t::'a)$

ext: $(!x::'a. (f \ x :: 'b) = g \ x) \Rightarrow (\%x. f \ x) = (\%x. g \ x)$

— Extensionality is built into the meta-logic, and this rule expresses a related property. It is an eta-expanded version of the traditional rule, and similar to the ABS rule of HOL

the-eq-trivial: $(THE \ x. \ x = a) = (a::'a)$

impI: $(P \Rightarrow Q) \Rightarrow P \multimap Q$

mp: $[P \multimap Q; \ P] \Rightarrow Q$

Thanks to Stephan Merz

theorem *subst*:

assumes *eq*: $s = t$ **and** $p: P(s)$

shows $P(t::'a)$

$\langle proof \rangle$

defs

True-def: $True == ((\%x::bool. \ x) = (\%x. \ x))$

All-def: $All(P) == (P = (\%x. \ True))$

Ex-def: $Ex(P) == !Q. (!x. \ P \ x \ \multimap \ Q) \ \multimap \ Q$

False-def: $False == (!P. \ P)$

not-def: $\sim P == P \multimap False$

and-def: $P \ \& \ Q == !R. (P \multimap Q \multimap R) \multimap R$

or-def: $P \ | \ Q == !R. (P \multimap R) \multimap (Q \multimap R) \multimap R$

Ex1-def: $Ex1(P) == ? \ x. \ P(x) \ \& \ (! \ y. \ P(y) \multimap y=x)$

axioms

iff: $(P \multimap Q) \multimap (Q \multimap P) \multimap (P=Q)$

True-or-False: $(P=True) \ | \ (P=False)$

defs

Let-def: *Let* $s\ f == f(s)$
if-def: *If* $P\ x\ y == \text{THE } z::'a. (P=\text{True} \dashrightarrow z=x) \ \& \ (P=\text{False} \dashrightarrow z=y)$

finalconsts

op =
op \dashrightarrow
The
arbitrary

1.1.4 Generic algebraic operations

axclass *zero* < *type*
axclass *one* < *type*
axclass *plus* < *type*
axclass *minus* < *type*
axclass *times* < *type*
axclass *inverse* < *type*

global**consts**

0 :: $'a::\text{zero}$ (0)
 1 :: $'a::\text{one}$ (1)
 $+$:: $['a::\text{plus}, 'a] ==> 'a$ (**infixl** 65)
 $-$:: $['a::\text{minus}, 'a] ==> 'a$ (**infixl** 65)
uminus :: $['a::\text{minus}] ==> 'a$ ($-$ - [81] 80)
 $*$:: $['a::\text{times}, 'a] ==> 'a$ (**infixl** 70)

syntax

$\text{-index1} :: \text{index} \quad (1)$

translations

$(\text{index})_1 ==> (\text{index})_\diamond$

local

$\langle ML \rangle$

consts

abs :: $'a::\text{minus} ==> 'a$
inverse :: $'a::\text{inverse} ==> 'a$
divide :: $['a::\text{inverse}, 'a] ==> 'a$ (**infixl** '/' 70)

syntax (*xsymbols*)

abs :: $'a::\text{minus} ==> 'a$ (|-|)

syntax (*HTML output*)

abs :: $'a::\text{minus} ==> 'a$ (|-|)

1.2 Equality

lemma *sym*: $s=t \implies t=s$
 $\langle proof \rangle$

lemmas *ssubst* = *sym* [THEN *subst*, *standard*]

lemma *trans*: $[| r=s; s=t |] \implies r=t$
 $\langle proof \rangle$

lemma *def-imp-eq*: **assumes** *meq*: $A == B$ **shows** $A = B$
 $\langle proof \rangle$

lemma *box-equals*: $[| a=b; a=c; b=d |] \implies c=d$
 $\langle proof \rangle$

For calculational reasoning:

lemma *forw-subst*: $a = b \implies P\ b \implies P\ a$
 $\langle proof \rangle$

lemma *back-subst*: $P\ a \implies a = b \implies P\ b$
 $\langle proof \rangle$

1.3 Congruence rules for application

lemma *fun-cong*: $(f::'a \Rightarrow 'b) = g \implies f(x)=g(x)$
 $\langle proof \rangle$

lemma *arg-cong*: $x=y \implies f(x)=f(y)$
 $\langle proof \rangle$

lemma *arg-cong2*: $[| a = b; c = d |] \implies f\ a\ c = f\ b\ d$
 $\langle proof \rangle$

lemma *cong*: $[| f = g; (x::'a) = y |] \implies f(x) = g(y)$
 $\langle proof \rangle$

1.4 Equality of booleans – iff

lemma *iffI*: **assumes** *prems*: $P \implies Q$ $Q \implies P$ **shows** $P=Q$
 $\langle proof \rangle$

lemma *iffD2*: $[| P=Q; Q |] \implies P$
 $\langle proof \rangle$

lemma *rev-iffD2*: $[| Q; P=Q |] \implies P$

$\langle proof \rangle$

lemmas *iffD1* = *sym* [*THEN iffD2, standard*]

lemmas *rev-iffD1* = *sym* [*THEN* [2] *rev-iffD2, standard*]

lemma *iffE*:

assumes *major*: $P=Q$

and *minor*: $[P \dashv\dashv Q; Q \dashv\dashv P] \implies R$

shows R

$\langle proof \rangle$

1.5 True

lemma *TrueI*: $True$

$\langle proof \rangle$

lemma *eqTrueI*: $P \implies P=True$

$\langle proof \rangle$

lemma *eqTrueE*: $P=True \implies P$

$\langle proof \rangle$

1.6 Universal quantifier

lemma *allI*: **assumes** $p: !!x::'a. P(x)$ **shows** $ALL\ x. P(x)$

$\langle proof \rangle$

lemma *spec*: $ALL\ x::'a. P(x) \implies P(x)$

$\langle proof \rangle$

lemma *allE*:

assumes *major*: $ALL\ x. P(x)$

and *minor*: $P(x) \implies R$

shows R

$\langle proof \rangle$

lemma *all-dupE*:

assumes *major*: $ALL\ x. P(x)$

and *minor*: $[P(x); ALL\ x. P(x)] \implies R$

shows R

$\langle proof \rangle$

1.7 False

lemma *FalseE*: $False \implies P$

$\langle proof \rangle$

lemma *False-neg-True*: $False=True \implies P$

$\langle proof \rangle$

1.8 Negation

lemma *notI*:
 assumes $p: P \implies False$
 shows $\sim P$
 $\langle proof \rangle$

lemma *False-not-True*: $False \sim = True$
 $\langle proof \rangle$

lemma *True-not-False*: $True \sim = False$
 $\langle proof \rangle$

lemma *notE*: $[\sim P; P] \implies R$
 $\langle proof \rangle$

lemmas *notI2* = *notE* [THEN *notI*, standard]

1.9 Implication

lemma *impE*:
 assumes $P \implies Q$ P $Q \implies R$
 shows R
 $\langle proof \rangle$

lemma *rev-mp*: $[P; P \implies Q] \implies Q$
 $\langle proof \rangle$

lemma *contrapos-nn*:
 assumes *major*: $\sim Q$
 and *minor*: $P \implies Q$
 shows $\sim P$
 $\langle proof \rangle$

lemma *contrapos-pn*:
 assumes *major*: Q
 and *minor*: $P \implies \sim Q$
 shows $\sim P$
 $\langle proof \rangle$

lemma *not-sym*: $t \sim = s \implies s \sim = t$
 $\langle proof \rangle$

lemma *rev-contrapos*:
 assumes *pq*: $P \implies Q$
 and *nq*: $\sim Q$

shows $\sim P$
 $\langle proof \rangle$

1.10 Existential quantifier

lemma *exI*: $P\ x \implies EX\ x::'a.\ P\ x$
 $\langle proof \rangle$

lemma *exE*:
 assumes *major*: $EX\ x::'a.\ P(x)$
 and *minor*: $!!x.\ P(x) \implies Q$
 shows Q
 $\langle proof \rangle$

1.11 Conjunction

lemma *conjI*: $[P;\ Q] \implies P \& Q$
 $\langle proof \rangle$

lemma *conjunct1*: $[P \& Q] \implies P$
 $\langle proof \rangle$

lemma *conjunct2*: $[P \& Q] \implies Q$
 $\langle proof \rangle$

lemma *conjE*:
 assumes *major*: $P \& Q$
 and *minor*: $[P;\ Q] \implies R$
 shows R
 $\langle proof \rangle$

lemma *context-conjI*:
 assumes *prems*: $P \implies Q$ shows $P \& Q$
 $\langle proof \rangle$

1.12 Disjunction

lemma *disjI1*: $P \implies P \mid Q$
 $\langle proof \rangle$

lemma *disjI2*: $Q \implies P \mid Q$
 $\langle proof \rangle$

lemma *disjE*:
 assumes *major*: $P \mid Q$
 and *minorP*: $P \implies R$
 and *minorQ*: $Q \implies R$
 shows R
 $\langle proof \rangle$

1.13 Classical logic

lemma *classical*:

assumes *prem*: $\sim P \implies P$

shows P

$\langle proof \rangle$

lemmas *ccontr* = *FalseE* [*THEN classical, standard*]

lemma *rev-notE*:

assumes *premp*: P

and *premnot*: $\sim R \implies \sim P$

shows R

$\langle proof \rangle$

lemma *notnotD*: $\sim\sim P \implies P$

$\langle proof \rangle$

lemma *contrapos-pp*:

assumes *p1*: Q

and *p2*: $\sim P \implies \sim Q$

shows P

$\langle proof \rangle$

1.14 Unique existence

lemma *ex1I*:

assumes *prems*: $P\ a \ \&!x. P(x) \implies x=a$

shows $EX! x. P(x)$

$\langle proof \rangle$

Sometimes easier to use: the premises have no shared variables. Safe!

lemma *ex-ex1I*:

assumes *ex-prem*: $EX\ x. P(x)$

and *eq*: $\&!x\ y. [P(x); P(y)] \implies x=y$

shows $EX! x. P(x)$

$\langle proof \rangle$

lemma *ex1E*:

assumes *major*: $EX! x. P(x)$

and *minor*: $\&!x. [P(x); \text{ALL } y. P(y) \longrightarrow y=x] \implies R$

shows R

$\langle proof \rangle$

lemma *ex1-implies-ex*: $EX! x. P\ x \implies EX\ x. P\ x$

$\langle proof \rangle$

1.15 THE: definite description operator

lemma *the-equality*:

assumes *prema*: $P\ a$
 and *premx*: $!!x. P\ x \implies x=a$
 shows $(THE\ x. P\ x) = a$

<proof>

lemma *theI*:

assumes $P\ a$ and $!!x. P\ x \implies x=a$
 shows $P\ (THE\ x. P\ x)$

<proof>

lemma *theI'*: $EX!\ x. P\ x \implies P\ (THE\ x. P\ x)$

<proof>

lemma *theI2*:

assumes $P\ a$ $!!x. P\ x \implies x=a$ $!!x. P\ x \implies Q\ x$
 shows $Q\ (THE\ x. P\ x)$

<proof>

lemma *the1-equality*: $[[EX!\ x. P\ x; P\ a]] \implies (THE\ x. P\ x) = a$

<proof>

lemma *the-sym-eq-trivial*: $(THE\ y. x=y) = x$

<proof>

1.16 Classical intro rules for disjunction and existential quantifiers

lemma *disjCI*:

assumes $\sim Q \implies P$ shows $P \mid Q$

<proof>

lemma *excluded-middle*: $\sim P \mid P$

<proof>

case distinction as a natural deduction rule. Note that $\neg P$ is the second case, not the first.

lemma *case-split-thm*:

assumes *prem1*: $P \implies Q$
 and *prem2*: $\sim P \implies Q$
 shows Q

<proof>

lemma *impCE*:

assumes *major*: $P \dashv\dashv Q$
 and *minor*: $\sim P \implies R$ $Q \implies R$

shows R
 $\langle proof \rangle$

lemma *impCE'*:
assumes *major*: $P \dashv\dashv Q$
and *minor*: $Q \implies R \sim P \implies R$
shows R
 $\langle proof \rangle$

lemma *iffCE*:
assumes *major*: $P = Q$
and *minor*: $[P; Q] \implies R \quad [\sim P; \sim Q] \implies R$
shows R
 $\langle proof \rangle$

lemma *exCI*:
assumes *ALL* $x. \sim P(x) \implies P(a)$
shows *EX* $x. P(x)$
 $\langle proof \rangle$

1.17 Theory and package setup

$\langle ML \rangle$

theorems *case-split* = *case-split-thm* [*case-names* *True False*]

1.17.1 Intuitionistic Reasoning

lemma *impE'*:
assumes *1*: $P \dashv\dashv Q$
and *2*: $Q \implies R$
and *3*: $P \dashv\dashv Q \implies P$
shows R
 $\langle proof \rangle$

lemma *allE'*:
assumes *1*: *ALL* $x. P x$
and *2*: $P x \implies \text{ALL } x. P x \implies Q$
shows Q
 $\langle proof \rangle$

lemma *notE'*:
assumes *1*: $\sim P$
and *2*: $\sim P \implies P$
shows R
 $\langle proof \rangle$

lemmas [*Pure.elim!*] = *disjE iffE FalseE conjE exE*

and $[Pure.intro!] = iffI\ conjI\ impI\ TrueI\ notI\ allI\ refl$
and $[Pure.elim\ 2] = allE\ notE'\ impE'$
and $[Pure.intro] = exI\ disjI2\ disjI1$

lemmas $[trans] = trans$
and $[sym] = sym\ not-sym$
and $[Pure.elim?] = iffD1\ iffD2\ impE$

1.17.2 Atomizing meta-level connectives

lemma *atomize-all* $[atomize]: (!x. P\ x) == Trueprop\ (ALL\ x. P\ x)$
 $\langle proof \rangle$

lemma *atomize-imp* $[atomize]: (A ==> B) == Trueprop\ (A --> B)$
 $\langle proof \rangle$

lemma *atomize-not*: $(A ==> False) == Trueprop\ (\sim A)$
 $\langle proof \rangle$

lemma *atomize-eq* $[atomize]: (x == y) == Trueprop\ (x = y)$
 $\langle proof \rangle$

lemma *atomize-conj* $[atomize]:$
 $(!C. (A ==> B ==> PROP\ C) ==> PROP\ C) == Trueprop\ (A \& B)$
 $\langle proof \rangle$

lemmas $[symmetric, rulify] = atomize-all\ atomize-imp$

1.17.3 Classical Reasoner setup

$\langle ML \rangle$

lemmas $[intro?] = ext$
and $[elim?] = ex1-implies-ex$

$\langle ML \rangle$

1.17.4 Simplifier setup

lemma *meta-eq-to-obj-eq*: $x == y ==> x = y$
 $\langle proof \rangle$

lemma *eta-contract-eq*: $(\%s. f\ s) = f\ \langle proof \rangle$

lemma *simp-thms*:
shows *not-not*: $(\sim \sim P) = P$
and *Not-eq-iff*: $((\sim P) = (\sim Q)) = (P = Q)$
and
 $(P \sim = Q) = (P = (\sim Q))$
 $(P \mid \sim P) = True \quad (\sim P \mid P) = True$

$(x = x) = \text{True}$
 $(\sim \text{True}) = \text{False} \quad (\sim \text{False}) = \text{True}$
 $(\sim P) \sim = P \quad P \sim = (\sim P)$
 $(\text{True} = P) = P \quad (P = \text{True}) = P \quad (\text{False} = P) = (\sim P) \quad (P = \text{False}) = (\sim P)$
 $(\text{True} \dashrightarrow P) = P \quad (\text{False} \dashrightarrow P) = \text{True}$
 $(P \dashrightarrow \text{True}) = \text{True} \quad (P \dashrightarrow P) = \text{True}$
 $(P \dashrightarrow \text{False}) = (\sim P) \quad (P \dashrightarrow \sim P) = (\sim P)$
 $(P \ \& \ \text{True}) = P \quad (\text{True} \ \& \ P) = P$
 $(P \ \& \ \text{False}) = \text{False} \quad (\text{False} \ \& \ P) = \text{False}$
 $(P \ \& \ P) = P \quad (P \ \& \ (P \ \& \ Q)) = (P \ \& \ Q)$
 $(P \ \& \ \sim P) = \text{False} \quad (\sim P \ \& \ P) = \text{False}$
 $(P \mid \text{True}) = \text{True} \quad (\text{True} \mid P) = \text{True}$
 $(P \mid \text{False}) = P \quad (\text{False} \mid P) = P$
 $(P \mid P) = P \quad (P \mid (P \mid Q)) = (P \mid Q) \text{ and}$
 $(\text{ALL } x. P) = P \quad (\text{EX } x. P) = P \quad \text{EX } x. x=t \quad \text{EX } x. t=x$
— needed for the one-point-rule quantifier simplification procs
— essential for termination!! and
 $!!P. (\text{EX } x. x=t \ \& \ P(x)) = P(t)$
 $!!P. (\text{EX } x. t=x \ \& \ P(x)) = P(t)$
 $!!P. (\text{ALL } x. x=t \dashrightarrow P(x)) = P(t)$
 $!!P. (\text{ALL } x. t=x \dashrightarrow P(x)) = P(t)$
 $\langle \text{proof} \rangle$

lemma *imp-cong*: $(P = P') \implies (P' \implies (Q = Q')) \implies ((P \dashrightarrow Q) = (P' \dashrightarrow Q'))$
 $\langle \text{proof} \rangle$

lemma *ex-simps*:

$!!P \ Q. (\text{EX } x. P \ x \ \& \ Q) = ((\text{EX } x. P \ x) \ \& \ Q)$
 $!!P \ Q. (\text{EX } x. P \ \& \ Q \ x) = (P \ \& \ (\text{EX } x. Q \ x))$
 $!!P \ Q. (\text{EX } x. P \ x \mid Q) = ((\text{EX } x. P \ x) \mid Q)$
 $!!P \ Q. (\text{EX } x. P \mid Q \ x) = (P \mid (\text{EX } x. Q \ x))$
 $!!P \ Q. (\text{EX } x. P \ x \dashrightarrow Q) = ((\text{ALL } x. P \ x) \dashrightarrow Q)$
 $!!P \ Q. (\text{EX } x. P \ dashrightarrow Q \ x) = (P \ dashrightarrow (\text{EX } x. Q \ x))$
— Miniscoping: pushing in existential quantifiers.
 $\langle \text{proof} \rangle$

lemma *all-simps*:

$!!P \ Q. (\text{ALL } x. P \ x \ \& \ Q) = ((\text{ALL } x. P \ x) \ \& \ Q)$
 $!!P \ Q. (\text{ALL } x. P \ \& \ Q \ x) = (P \ \& \ (\text{ALL } x. Q \ x))$
 $!!P \ Q. (\text{ALL } x. P \ x \mid Q) = ((\text{ALL } x. P \ x) \mid Q)$
 $!!P \ Q. (\text{ALL } x. P \mid Q \ x) = (P \mid (\text{ALL } x. Q \ x))$
 $!!P \ Q. (\text{ALL } x. P \ x \dashrightarrow Q) = ((\text{EX } x. P \ x) \dashrightarrow Q)$
 $!!P \ Q. (\text{ALL } x. P \ dashrightarrow Q \ x) = (P \ dashrightarrow (\text{ALL } x. Q \ x))$
— Miniscoping: pushing in universal quantifiers.
 $\langle \text{proof} \rangle$

lemma *disj-absorb*: $(A \mid A) = A$
 $\langle \text{proof} \rangle$

lemma *disj-left-absorb*: $(A \mid (A \mid B)) = (A \mid B)$
 $\langle proof \rangle$

lemma *conj-absorb*: $(A \ \& \ A) = A$
 $\langle proof \rangle$

lemma *conj-left-absorb*: $(A \ \& \ (A \ \& \ B)) = (A \ \& \ B)$
 $\langle proof \rangle$

lemma *eq-ac*:
shows *eq-commute*: $(a=b) = (b=a)$
and *eq-left-commute*: $(P=(Q=R)) = (Q=(P=R))$
and *eq-assoc*: $((P=Q)=R) = (P=(Q=R))$ $\langle proof \rangle$
lemma *neq-commute*: $(a \sim b) = (b \sim a)$ $\langle proof \rangle$

lemma *conj-comms*:
shows *conj-commute*: $(P \ \& \ Q) = (Q \ \& \ P)$
and *conj-left-commute*: $(P \ \& \ (Q \ \& \ R)) = (Q \ \& \ (P \ \& \ R))$ $\langle proof \rangle$
lemma *conj-assoc*: $((P \ \& \ Q) \ \& \ R) = (P \ \& \ (Q \ \& \ R))$ $\langle proof \rangle$

lemma *disj-comms*:
shows *disj-commute*: $(P \mid Q) = (Q \mid P)$
and *disj-left-commute*: $(P \mid (Q \mid R)) = (Q \mid (P \mid R))$ $\langle proof \rangle$
lemma *disj-assoc*: $((P \mid Q) \mid R) = (P \mid (Q \mid R))$ $\langle proof \rangle$

lemma *conj-disj-distribL*: $(P \ \& \ (Q \mid R)) = (P \ \& \ Q \mid P \ \& \ R)$ $\langle proof \rangle$
lemma *conj-disj-distribR*: $((P \mid Q) \ \& \ R) = (P \ \& \ R \mid Q \ \& \ R)$ $\langle proof \rangle$

lemma *disj-conj-distribL*: $(P \mid (Q \ \& \ R)) = ((P \mid Q) \ \& \ (P \mid R))$ $\langle proof \rangle$
lemma *disj-conj-distribR*: $((P \ \& \ Q) \mid R) = ((P \ \& \ R) \ \& \ (Q \ \& \ R))$ $\langle proof \rangle$

lemma *imp-conjR*: $(P \dashrightarrow (Q \ \& \ R)) = ((P \dashrightarrow Q) \ \& \ (P \dashrightarrow R))$ $\langle proof \rangle$
lemma *imp-conjL*: $((P \ \& \ Q) \dashrightarrow R) = (P \dashrightarrow (Q \dashrightarrow R))$ $\langle proof \rangle$
lemma *imp-disjL*: $((P \mid Q) \dashrightarrow R) = ((P \dashrightarrow R) \ \& \ (Q \dashrightarrow R))$ $\langle proof \rangle$

These two are specialized, but *imp-disj-not1* is useful in *Auth/Yahalom*.

lemma *imp-disj-not1*: $(P \dashrightarrow Q \mid R) = (\sim Q \dashrightarrow P \dashrightarrow R)$ $\langle proof \rangle$
lemma *imp-disj-not2*: $(P \dashrightarrow Q \mid R) = (\sim R \dashrightarrow P \dashrightarrow Q)$ $\langle proof \rangle$

lemma *imp-disj1*: $((P \dashrightarrow Q) \mid R) = (P \dashrightarrow Q \mid R)$ $\langle proof \rangle$
lemma *imp-disj2*: $(Q \mid (P \dashrightarrow R)) = (P \dashrightarrow Q \mid R)$ $\langle proof \rangle$

lemma *de-Morgan-disj*: $(\sim(P \mid Q)) = (\sim P \ \& \ \sim Q)$ $\langle proof \rangle$
lemma *de-Morgan-conj*: $(\sim(P \ \& \ Q)) = (\sim P \mid \sim Q)$ $\langle proof \rangle$
lemma *not-imp*: $(\sim(P \dashrightarrow Q)) = (P \ \& \ \sim Q)$ $\langle proof \rangle$
lemma *not-iff*: $(P \sim Q) = (P = (\sim Q))$ $\langle proof \rangle$
lemma *disj-not1*: $(\sim P \mid Q) = (P \dashrightarrow Q)$ $\langle proof \rangle$
lemma *disj-not2*: $(P \mid \sim Q) = (Q \dashrightarrow P)$ — changes orientation :-)

$\langle proof \rangle$

lemma *imp-conv-disj*: $(P \dashv\dashv Q) = ((\sim P) \mid Q) \langle proof \rangle$

lemma *iff-conv-conj-imp*: $(P = Q) = ((P \dashv\dashv Q) \& (Q \dashv\dashv P)) \langle proof \rangle$

lemma *cases-simp*: $((P \dashv\dashv Q) \& (\sim P \dashv\dashv Q)) = Q$

— Avoids duplication of subgoals after *split-if*, when the true and false cases boil down to the same thing.

$\langle proof \rangle$

lemma *not-all*: $(\sim (! x. P(x))) = (? x. \sim P(x)) \langle proof \rangle$

lemma *imp-all*: $((! x. P x) \dashv\dashv Q) = (? x. P x \dashv\dashv Q) \langle proof \rangle$

lemma *not-ex*: $(\sim (? x. P(x))) = (! x. \sim P(x)) \langle proof \rangle$

lemma *imp-ex*: $((? x. P x) \dashv\dashv Q) = (! x. P x \dashv\dashv Q) \langle proof \rangle$

lemma *ex-disj-distrib*: $(? x. P(x) \mid Q(x)) = ((? x. P(x)) \mid (? x. Q(x))) \langle proof \rangle$

lemma *all-conj-distrib*: $(! x. P(x) \& Q(x)) = ((! x. P(x)) \& (! x. Q(x))) \langle proof \rangle$

The $\&$ congruence rule: not included by default! May slow rewrite proofs down by as much as 50%

lemma *conj-cong*:

$(P = P') \implies (P' \implies (Q = Q')) \implies ((P \& Q) = (P' \& Q'))$

$\langle proof \rangle$

lemma *rev-conj-cong*:

$(Q = Q') \implies (Q' \implies (P = P')) \implies ((P \& Q) = (P' \& Q'))$

$\langle proof \rangle$

The \mid congruence rule: not included by default!

lemma *disj-cong*:

$(P = P') \implies (\sim P' \implies (Q = Q')) \implies ((P \mid Q) = (P' \mid Q'))$

$\langle proof \rangle$

lemma *eq-sym-conv*: $(x = y) = (y = x)$

$\langle proof \rangle$

if-then-else rules

lemma *if-True*: $(if\ True\ then\ x\ else\ y) = x$

$\langle proof \rangle$

lemma *if-False*: $(if\ False\ then\ x\ else\ y) = y$

$\langle proof \rangle$

lemma *if-P*: $P \implies (if\ P\ then\ x\ else\ y) = x$

$\langle proof \rangle$

lemma *if-not-P*: $\sim P \implies (if\ P\ then\ x\ else\ y) = y$

$\langle proof \rangle$

lemma *split-if*: $P \text{ (if } Q \text{ then } x \text{ else } y) = ((Q \text{ --> } P(x)) \ \& \ (\sim Q \text{ --> } P(y)))$
 $\langle proof \rangle$

lemma *split-if-asm*: $P \text{ (if } Q \text{ then } x \text{ else } y) = (\sim((Q \ \& \ \sim P \ x) \mid (\sim Q \ \& \ \sim P \ y)))$
 $\langle proof \rangle$

lemmas *if-splits* = *split-if split-if-asm*

lemma *if-def2*: $(\text{if } Q \text{ then } x \text{ else } y) = ((Q \text{ --> } x) \ \& \ (\sim Q \text{ --> } y))$
 $\langle proof \rangle$

lemma *if-cancel*: $(\text{if } c \text{ then } x \text{ else } x) = x$
 $\langle proof \rangle$

lemma *if-eq-cancel*: $(\text{if } x = y \text{ then } y \text{ else } x) = x$
 $\langle proof \rangle$

lemma *if-bool-eq-conj*: $(\text{if } P \text{ then } Q \text{ else } R) = ((P \text{ --> } Q) \ \& \ (\sim P \text{ --> } R))$
 — This form is useful for expanding *ifs* on the RIGHT of the ==> symbol.
 $\langle proof \rangle$

lemma *if-bool-eq-disj*: $(\text{if } P \text{ then } Q \text{ else } R) = ((P \ \& \ Q) \mid (\sim P \ \& \ R))$
 — And this form is useful for expanding *ifs* on the LEFT.
 $\langle proof \rangle$

lemma *Eq-TrueI*: $P \text{ ==> } P \text{ == True}$ $\langle proof \rangle$

lemma *Eq-FalseI*: $\sim P \text{ ==> } P \text{ == False}$ $\langle proof \rangle$

let rules for *simproc*

lemma *Let-folded*: $f \ x \equiv g \ x \implies \text{Let } x \ f \equiv \text{Let } x \ g$
 $\langle proof \rangle$

lemma *Let-unfold*: $f \ x \equiv g \implies \text{Let } x \ f \equiv g$
 $\langle proof \rangle$

The following copy of the implication operator is useful for fine-tuning congruence rules. It instructs the simplifier to simplify its premise.

constdefs

simp-implies :: $[prop, prop] \text{ ==> } prop$ (**infixr** ==simp==> 1)
simp-implies $\equiv op \text{ ==>}$

lemma *simp-impliesI*:

assumes *PQ*: $(PROP \ P \implies PROP \ Q)$

shows $PROP \ P \text{ ==simp==> } PROP \ Q$

$\langle proof \rangle$

lemma *simp-impliesE*:
assumes $PQ:PROP\ P =_{simp}=> PROP\ Q$
and $P: PROP\ P$
and $QR: PROP\ Q \implies PROP\ R$
shows $PROP\ R$
 $\langle proof \rangle$

lemma *simp-implies-cong*:
assumes $PP':PROP\ P == PROP\ P'$
and $P'QQ': PROP\ P' ==> (PROP\ Q == PROP\ Q')$
shows $(PROP\ P =_{simp}=> PROP\ Q) == (PROP\ P' =_{simp}=> PROP\ Q')$
 $\langle proof \rangle$

Actual Installation of the Simplifier.

$\langle ML \rangle$

Lucas Dixon’s eqstep tactic.

$\langle ML \rangle$

1.17.5 Code generator setup

types-code
 $bool\ (bool)$
attach (*term-of*) $\langle\langle$
 $fun\ term-of-bool\ b = if\ b\ then\ HLogic.true-const\ else\ HLogic.false-const;$
 $\rangle\rangle$
attach (*test*) $\langle\langle$
 $fun\ gen-bool\ i = one-of\ [false,\ true];$
 $\rangle\rangle$

consts-code
 $True\ (true)$
 $False\ (false)$
 $Not\ (not)$
 $op\ |\ ((- \ orelse\ -))$
 $op\ \&\ ((- \ andalso\ -))$
 $HOL.If\ ((if\ -/\ then\ -/\ else\ -))$

$\langle ML \rangle$

1.18 Other simple lemmas

declare *disj-absorb* [*simp*] *conj-absorb* [*simp*]

lemma *ex1-eq[iff]*: $EX!\ x.\ x = t\ EX!\ x.\ t = x$
 $\langle proof \rangle$

theorem *choice-eq*: $(ALL\ x.\ EX!\ y.\ P\ x\ y) = (EX!\ f.\ ALL\ x.\ P\ x\ (f\ x))$

$\langle \text{proof} \rangle$

Needs only HOL-lemmas:

lemma *mk-left-commute*:

assumes a : $\bigwedge x y z. f (f x y) z = f x (f y z)$ **and**

c : $\bigwedge x y. f x y = f y x$

shows $f x (f y z) = f y (f x z)$

$\langle \text{proof} \rangle$

1.19 Generic cases and induction

constdefs

induct-forall :: $('a \Rightarrow \text{bool}) \Rightarrow \text{bool}$

induct-forall $P == \forall x. P x$

induct-implies :: $\text{bool} \Rightarrow \text{bool} \Rightarrow \text{bool}$

induct-implies $A B == A \longrightarrow B$

induct-equal :: $'a \Rightarrow 'a \Rightarrow \text{bool}$

induct-equal $x y == x = y$

induct-conj :: $\text{bool} \Rightarrow \text{bool} \Rightarrow \text{bool}$

induct-conj $A B == A \ \& \ B$

lemma *induct-forall-eq*: $(!!x. P x) == \text{Trueprop } (\text{induct-forall } (\lambda x. P x))$

$\langle \text{proof} \rangle$

lemma *induct-implies-eq*: $(A \Longrightarrow B) == \text{Trueprop } (\text{induct-implies } A B)$

$\langle \text{proof} \rangle$

lemma *induct-equal-eq*: $(x == y) == \text{Trueprop } (\text{induct-equal } x y)$

$\langle \text{proof} \rangle$

lemma *induct-forall-conj*: $\text{induct-forall } (\lambda x. \text{induct-conj } (A x) (B x)) =$

$\text{induct-conj } (\text{induct-forall } A) (\text{induct-forall } B)$

$\langle \text{proof} \rangle$

lemma *induct-implies-conj*: $\text{induct-implies } C (\text{induct-conj } A B) =$

$\text{induct-conj } (\text{induct-implies } C A) (\text{induct-implies } C B)$

$\langle \text{proof} \rangle$

lemma *induct-conj-curry*: $(\text{induct-conj } A B \Longrightarrow \text{PROP } C) == (A \Longrightarrow B \Longrightarrow$

$\text{PROP } C)$

$\langle \text{proof} \rangle$

lemma *induct-impliesI*: $(A \Longrightarrow B) \Longrightarrow \text{induct-implies } A B$

$\langle \text{proof} \rangle$

lemmas *induct-atomize* = *atomize-conj* *induct-forall-eq* *induct-implies-eq* *induct-equal-eq*

lemmas *induct-rulify1* [*symmetric*, *standard*] = *induct-forall-eq* *induct-implies-eq*

induct-equal-eq

lemmas *induct-rulify2* = *induct-forall-def* *induct-implies-def* *induct-equal-def* *induct-conj-def*

lemmas *induct-conj* = *induct-forall-conj* *induct-implies-conj* *induct-conj-curry*

hide *const* *induct-forall* *induct-implies* *induct-equal* *induct-conj*

Method setup.

$\langle ML \rangle$

1.19.1 Tags, for the ATP Linkup

constdefs

tag :: *bool* ==> *bool*

tag *P* == *P*

These label the distinguished literals of introduction and elimination rules.

lemma *tagI*: *P* ==> *tag P*

$\langle proof \rangle$

lemma *tagD*: *tag P* ==> *P*

$\langle proof \rangle$

Applications of “tag” to True and False must go!

lemma *tag-True*: *tag True* = *True*

$\langle proof \rangle$

lemma *tag-False*: *tag False* = *False*

$\langle proof \rangle$

end

2 Lattice-Locales: Lattices via Locales

theory *Lattice-Locales*

imports *HOL*

begin

2.1 Lattices

This theory of lattice locales only defines binary sup and inf operations. The extension to finite sets is done in theory *Finite-Set*. In the longer term it may be better to define arbitrary sups and infs via *THE*.

locale *partial-order* =

fixes *below* :: '*a* \Rightarrow '*a* \Rightarrow *bool* (**infixl** \sqsubseteq 50)

assumes *refl*[*iff*]: *x* \sqsubseteq *x*

and *trans*: *x* \sqsubseteq *y* \Longrightarrow *y* \sqsubseteq *z* \Longrightarrow *x* \sqsubseteq *z*

and *antisym*: *x* \sqsubseteq *y* \Longrightarrow *y* \sqsubseteq *x* \Longrightarrow *x* = *y*

locale *lower-semilattice* = *partial-order* +
fixes *inf* :: 'a \Rightarrow 'a \Rightarrow 'a (**infixl** \sqcap 70)
assumes *inf-le1*: $x \sqcap y \sqsubseteq x$ **and** *inf-le2*: $x \sqcap y \sqsubseteq y$
and *inf-least*: $x \sqsubseteq y \Longrightarrow x \sqsubseteq z \Longrightarrow x \sqsubseteq y \sqcap z$

locale *upper-semilattice* = *partial-order* +
fixes *sup* :: 'a \Rightarrow 'a \Rightarrow 'a (**infixl** \sqcup 65)
assumes *sup-ge1*: $x \sqsubseteq x \sqcup y$ **and** *sup-ge2*: $y \sqsubseteq x \sqcup y$
and *sup-greatest*: $y \sqsubseteq x \Longrightarrow z \sqsubseteq x \Longrightarrow y \sqcup z \sqsubseteq x$

locale *lattice* = *lower-semilattice* + *upper-semilattice*

lemma (**in** *lower-semilattice*) *inf-commute*: $(x \sqcap y) = (y \sqcap x)$
 \langle *proof* \rangle

lemma (**in** *upper-semilattice*) *sup-commute*: $(x \sqcup y) = (y \sqcup x)$
 \langle *proof* \rangle

lemma (**in** *lower-semilattice*) *inf-assoc*: $(x \sqcap y) \sqcap z = x \sqcap (y \sqcap z)$
 \langle *proof* \rangle

lemma (**in** *upper-semilattice*) *sup-assoc*: $(x \sqcup y) \sqcup z = x \sqcup (y \sqcup z)$
 \langle *proof* \rangle

lemma (**in** *lower-semilattice*) *inf-idem[simp]*: $x \sqcap x = x$
 \langle *proof* \rangle

lemma (**in** *upper-semilattice*) *sup-idem[simp]*: $x \sqcup x = x$
 \langle *proof* \rangle

lemma (**in** *lower-semilattice*) *inf-left-idem[simp]*: $x \sqcap (x \sqcap y) = x \sqcap y$
 \langle *proof* \rangle

lemma (**in** *upper-semilattice*) *sup-left-idem[simp]*: $x \sqcup (x \sqcup y) = x \sqcup y$
 \langle *proof* \rangle

lemma (**in** *lattice*) *inf-sup-absorb*: $x \sqcap (x \sqcup y) = x$
 \langle *proof* \rangle

lemma (**in** *lattice*) *sup-inf-absorb*: $x \sqcup (x \sqcap y) = x$
 \langle *proof* \rangle

lemma (**in** *lower-semilattice*) *inf-absorb*: $x \sqsubseteq y \Longrightarrow x \sqcap y = x$
 \langle *proof* \rangle

lemma (**in** *upper-semilattice*) *sup-absorb*: $x \sqsubseteq y \Longrightarrow x \sqcup y = y$
 \langle *proof* \rangle

lemma (in *lower-semilattice*) *below-inf-conv*[*simp*]:
 $x \sqsubseteq y \sqcap z = (x \sqsubseteq y \wedge x \sqsubseteq z)$
 ⟨*proof*⟩

lemma (in *upper-semilattice*) *above-sup-conv*[*simp*]:
 $x \sqcup y \sqsubseteq z = (x \sqsubseteq z \wedge y \sqsubseteq z)$
 ⟨*proof*⟩

Towards distributivity: if you have one of them, you have them all.

lemma (in *lattice*) *distrib-imp1*:
assumes $D: !!x\ y\ z. x \sqcap (y \sqcup z) = (x \sqcap y) \sqcup (x \sqcap z)$
shows $x \sqcup (y \sqcap z) = (x \sqcup y) \sqcap (x \sqcup z)$
 ⟨*proof*⟩

lemma (in *lattice*) *distrib-imp2*:
assumes $D: !!x\ y\ z. x \sqcup (y \sqcap z) = (x \sqcup y) \sqcap (x \sqcup z)$
shows $x \sqcap (y \sqcup z) = (x \sqcap y) \sqcup (x \sqcap z)$
 ⟨*proof*⟩

A package of rewrite rules for deciding equivalence wrt ACI:

lemma (in *lower-semilattice*) *inf-left-commute*: $x \sqcap (y \sqcap z) = y \sqcap (x \sqcap z)$
 ⟨*proof*⟩

lemma (in *upper-semilattice*) *sup-left-commute*: $x \sqcup (y \sqcup z) = y \sqcup (x \sqcup z)$
 ⟨*proof*⟩

lemma (in *lower-semilattice*) *inf-left-idem*: $x \sqcap (x \sqcap y) = x \sqcap y$
 ⟨*proof*⟩

lemma (in *upper-semilattice*) *sup-left-idem*: $x \sqcup (x \sqcup y) = x \sqcup y$
 ⟨*proof*⟩

lemmas (in *lower-semilattice*) *inf-ACI* =
inf-commute inf-assoc inf-left-commute inf-left-idem

lemmas (in *upper-semilattice*) *sup-ACI* =
sup-commute sup-assoc sup-left-commute sup-left-idem

lemmas (in *lattice*) *ACI* = *inf-ACI sup-ACI*

2.2 Distributive lattices

locale *distrib-lattice* = *lattice* +
assumes *sup-inf-distrib1*: $x \sqcup (y \sqcap z) = (x \sqcup y) \sqcap (x \sqcup z)$

lemma (in *distrib-lattice*) *sup-inf-distrib2*:
 $(y \sqcap z) \sqcup x = (y \sqcup x) \sqcap (z \sqcup x)$

<proof>

lemma (in *distrib-lattice*) *inf-sup-distrib1*:

$x \sqcap (y \sqcup z) = (x \sqcap y) \sqcup (x \sqcap z)$

<proof>

lemma (in *distrib-lattice*) *inf-sup-distrib2*:

$(y \sqcup z) \sqcap x = (y \sqcap x) \sqcup (z \sqcap x)$

<proof>

lemmas (in *distrib-lattice*) *distrib* =

sup-inf-distrib1 sup-inf-distrib2 inf-sup-distrib1 inf-sup-distrib2

end

3 Orderings: Type classes for \leq

theory *Orderings*

imports *Lattice-Locales*

uses (*antisym-setup.ML*)

begin

3.1 Order signatures and orders

axclass

ord < *type*

syntax

op < :: [*a*::*ord*, '*a*] => *bool* (*op* <)

op <= :: [*a*::*ord*, '*a*] => *bool* (*op* <=)

global

consts

op < :: [*a*::*ord*, '*a*] => *bool* ((-/ < -) [50, 51] 50)

op <= :: [*a*::*ord*, '*a*] => *bool* ((-/ <= -) [50, 51] 50)

local

syntax (*xsymbols*)

op <= :: [*a*::*ord*, '*a*] => *bool* (*op* ≤)

op <= :: [*a*::*ord*, '*a*] => *bool* ((-/ ≤ -) [50, 51] 50)

syntax (*HTML output*)

op <= :: [*a*::*ord*, '*a*] => *bool* (*op* ≤)

op <= :: [*a*::*ord*, '*a*] => *bool* ((-/ ≤ -) [50, 51] 50)

Syntactic sugar:

syntax

$-gt :: 'a::ord \Rightarrow 'a \Rightarrow bool$ (infixl > 50)
 $-ge :: 'a::ord \Rightarrow 'a \Rightarrow bool$ (infixl >= 50)

translations

$x > y \Rightarrow y < x$
 $x \geq y \Rightarrow y \leq x$

syntax (*xsymbols*)

$-ge :: 'a::ord \Rightarrow 'a \Rightarrow bool$ (infixl \geq 50)

syntax (*HTML output*)

$-ge :: ['a::ord, 'a] \Rightarrow bool$ (infixl \geq 50)

3.2 Monotonicity

locale *mono* =

fixes *f*

assumes *mono*: $A \leq B \Rightarrow f A \leq f B$

lemmas *monoI* [*intro?*] = *mono.intro*

and *monoD* [*dest?*] = *mono.mono*

constdefs

$min :: ['a::ord, 'a] \Rightarrow 'a$
 $min\ a\ b == (if\ a \leq b\ then\ a\ else\ b)$
 $max :: ['a::ord, 'a] \Rightarrow 'a$
 $max\ a\ b == (if\ a \leq b\ then\ b\ else\ a)$

lemma *min-leastL*: $(!!x. least \leq x) \Rightarrow min\ least\ x = least$

<proof>

lemma *min-of-mono*:

$ALL\ x\ y. (f\ x \leq f\ y) = (x \leq y) \Rightarrow min\ (f\ m)\ (f\ n) = f\ (min\ m\ n)$
<proof>

lemma *max-leastL*: $(!!x. least \leq x) \Rightarrow max\ least\ x = x$

<proof>

lemma *max-of-mono*:

$ALL\ x\ y. (f\ x \leq f\ y) = (x \leq y) \Rightarrow max\ (f\ m)\ (f\ n) = f\ (max\ m\ n)$
<proof>

3.3 Orders

axclass *order* < *ord*

order-refl [*iff*]: $x \leq x$

order-trans: $x \leq y \Rightarrow y \leq z \Rightarrow x \leq z$

order-antisym: $x \leq y \Rightarrow y \leq x \Rightarrow x = y$

order-less-le: $(x < y) = (x \leq y \ \& \ x \sim y)$

Connection to locale:

interpretation *order*:

partial-order $[op \leq :: 'a::order \Rightarrow 'a \Rightarrow bool]$
 $\langle proof \rangle$

Reflexivity.

lemma *order-eq-refl*: $!!x::'a::order. x = y \implies x \leq y$

— This form is useful with the classical reasoner.

$\langle proof \rangle$

lemma *order-less-irrefl* $[iff]$: $\sim x < (x::'a::order)$

$\langle proof \rangle$

lemma *order-le-less*: $((x::'a::order) \leq y) = (x < y \mid x = y)$

— NOT suitable for iff, since it can cause PROOF FAILED.

$\langle proof \rangle$

lemmas *order-le-imp-less-or-eq* = *order-le-less* $[THEN \text{ iffD1, standard}]$

lemma *order-less-imp-le*: $!!x::'a::order. x < y \implies x \leq y$

$\langle proof \rangle$

Asymmetry.

lemma *order-less-not-sym*: $(x::'a::order) < y \implies \sim (y < x)$

$\langle proof \rangle$

lemma *order-less-asymp*: $x < (y::'a::order) \implies (\sim P \implies y < x) \implies P$

$\langle proof \rangle$

lemma *order-eq-iff*: $!!x::'a::order. (x = y) = (x \leq y \ \& \ y \leq x)$

$\langle proof \rangle$

lemma *order-antisym-conv*: $(y::'a::order) \leq x \implies (x \leq y) = (x = y)$

$\langle proof \rangle$

Transitivity.

lemma *order-less-trans*: $!!x::'a::order. [| x < y; y < z |] \implies x < z$

$\langle proof \rangle$

lemma *order-le-less-trans*: $!!x::'a::order. [| x \leq y; y < z |] \implies x < z$

$\langle proof \rangle$

lemma *order-less-le-trans*: $!!x::'a::order. [| x < y; y \leq z |] \implies x < z$

$\langle proof \rangle$

Useful for simplification, but too risky to include by default.

lemma *order-less-imp-not-less*: $(x::'a::order) < y ==> (\sim y < x) = True$
 $\langle proof \rangle$

lemma *order-less-imp-triv*: $(x::'a::order) < y ==> (y < x \dashv\vdash P) = True$
 $\langle proof \rangle$

lemma *order-less-imp-not-eq*: $(x::'a::order) < y ==> (x = y) = False$
 $\langle proof \rangle$

lemma *order-less-imp-not-eq2*: $(x::'a::order) < y ==> (y = x) = False$
 $\langle proof \rangle$

Other operators.

lemma *min-leastR*: $(!!x::'a::order. least \leq x) ==> min\ x\ least = least$
 $\langle proof \rangle$

lemma *max-leastR*: $(!!x::'a::order. least \leq x) ==> max\ x\ least = x$
 $\langle proof \rangle$

3.4 Transitivity rules for calculational reasoning

lemma *order-neq-le-trans*: $a \sim b ==> (a::'a::order) \leq b ==> a < b$
 $\langle proof \rangle$

lemma *order-le-neq-trans*: $(a::'a::order) \leq b ==> a \sim b ==> a < b$
 $\langle proof \rangle$

lemma *order-less-asym'*: $(a::'a::order) < b ==> b < a ==> P$
 $\langle proof \rangle$

3.5 Least value operator

constdefs

$Least :: ('a::ord ==> bool) ==> 'a$ (binder *LEAST* 10)
 $Least\ P == THE\ x. P\ x \ \& \ (ALL\ y. P\ y \dashv\vdash x \leq y)$
 — We can no longer use *LeastM* because the latter requires Hilbert-AC.

lemma *LeastI2-order*:

$[| P\ (x::'a::order);$
 $\quad !!y. P\ y ==> x \leq y;$
 $\quad !!x. [| P\ x; ALL\ y. P\ y \dashv\vdash x \leq y |] ==> Q\ x |]$
 $==> Q\ (Least\ P)$
 $\langle proof \rangle$

lemma *Least-equality*:

$[| P\ (k::'a::order); !!x. P\ x ==> k \leq x |] ==> (LEAST\ x. P\ x) = k$
 $\langle proof \rangle$

3.6 Linear / total orders

axclass *linorder* < *order*

linorder-linear: $x \leq y \mid y \leq x$

lemma *linorder-less-linear*: $!!x::'a::linorder. x < y \mid x = y \mid y < x$
 $\langle proof \rangle$

lemma *linorder-le-less-linear*: $!!x::'a::linorder. x \leq y \mid y < x$
 $\langle proof \rangle$

lemma *linorder-le-cases* [*case-names le ge*]:
 $((x::'a::linorder) \leq y \implies P) \implies (y \leq x \implies P) \implies P$
 $\langle proof \rangle$

lemma *linorder-cases* [*case-names less equal greater*]:
 $((x::'a::linorder) < y \implies P) \implies (x = y \implies P) \implies (y < x \implies P) \implies P$
 $\langle proof \rangle$

lemma *linorder-not-less*: $!!x::'a::linorder. (\sim x < y) = (y \leq x)$
 $\langle proof \rangle$

lemma *linorder-not-le*: $!!x::'a::linorder. (\sim x \leq y) = (y < x)$
 $\langle proof \rangle$

lemma *linorder-neq-iff*: $!!x::'a::linorder. (x \sim y) = (x < y \mid y < x)$
 $\langle proof \rangle$

lemma *linorder-neqE*: $x \sim (y::'a::linorder) \implies (x < y \implies R) \implies (y < x \implies R) \implies R$
 $\langle proof \rangle$

lemma *linorder-antisym-conv1*: $\sim (x::'a::linorder) < y \implies (x \leq y) = (x = y)$
 $\langle proof \rangle$

lemma *linorder-antisym-conv2*: $(x::'a::linorder) \leq y \implies (\sim x < y) = (x = y)$
 $\langle proof \rangle$

lemma *linorder-antisym-conv3*: $\sim (y::'a::linorder) < x \implies (\sim x < y) = (x = y)$
 $\langle proof \rangle$

Replacing the old Nat.leI

lemma *leI*: $\sim x < y \implies y \leq (x::'a::linorder)$
 $\langle proof \rangle$

lemma *leD*: $y \leq (x::'a::linorder) \implies \sim x < y$
 $\langle proof \rangle$

lemma *not-leE*: $\sim y \leq (x :: 'a :: \text{linorder}) \implies x < y$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

3.7 Setup of transitivity reasoner as Solver

lemma *less-imp-neq*: $[(x :: 'a :: \text{order}) < y] \implies x \sim = y$
 $\langle \text{proof} \rangle$

lemma *eq-neq-eq-imp-neq*: $[x = a ; a \sim = b ; b = y] \implies x \sim = y$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

3.8 Min and max on (linear) orders

Instantiate locales:

interpretation *min-max*:
 $\text{lower-semilattice}[op \leq \text{min} :: 'a :: \text{linorder} \Rightarrow 'a \Rightarrow 'a]$
 $\langle \text{proof} \rangle$

interpretation *min-max*:
 $\text{upper-semilattice}[op \leq \text{max} :: 'a :: \text{linorder} \Rightarrow 'a \Rightarrow 'a]$
 $\langle \text{proof} \rangle$

interpretation *min-max*:
 $\text{lattice}[op \leq \text{min} :: 'a :: \text{linorder} \Rightarrow 'a \Rightarrow 'a \text{ max}]$
 $\langle \text{proof} \rangle$

interpretation *min-max*:
 $\text{distrib-lattice}[op \leq \text{min} :: 'a :: \text{linorder} \Rightarrow 'a \Rightarrow 'a \text{ max}]$
 $\langle \text{proof} \rangle$

lemma *le-max-iff-disj*: $!!z :: 'a :: \text{linorder}. (z \leq \text{max } x \ y) = (z \leq x \mid z \leq y)$
 $\langle \text{proof} \rangle$

lemmas *le-maxI1* = *min-max.sup-ge1*

lemmas *le-maxI2* = *min-max.sup-ge2*

lemma *less-max-iff-disj*: $!!z :: 'a :: \text{linorder}. (z < \text{max } x \ y) = (z < x \mid z < y)$
 $\langle \text{proof} \rangle$

lemma *max-less-iff-conj* [simp]:
 $!!z :: 'a :: \text{linorder}. (\text{max } x \ y < z) = (x < z \ \& \ y < z)$
 $\langle \text{proof} \rangle$

lemma *min-less-iff-conj* [simp]:

$!!z::'a::linorder. (z < \min x y) = (z < x \ \& \ z < y)$
 $\langle proof \rangle$

lemma *min-le-iff-disj*: $!!z::'a::linorder. (\min x y \leq z) = (x \leq z \mid y \leq z)$
 $\langle proof \rangle$

lemma *min-less-iff-disj*: $!!z::'a::linorder. (\min x y < z) = (x < z \mid y < z)$
 $\langle proof \rangle$

lemmas *max-ac = min-max.sup-assoc min-max.sup-commute*
mk-left-commute[of max, OF min-max.sup-assoc min-max.sup-commute]

lemmas *min-ac = min-max.inf-assoc min-max.inf-commute*
mk-left-commute[of min, OF min-max.inf-assoc min-max.inf-commute]

lemma *split-min*:
 $P (\min (i::'a::linorder) j) = ((i \leq j \dashv\rightarrow P(i)) \ \& \ (\sim i \leq j \dashv\rightarrow P(j)))$
 $\langle proof \rangle$

lemma *split-max*:
 $P (\max (i::'a::linorder) j) = ((i \leq j \dashv\rightarrow P(j)) \ \& \ (\sim i \leq j \dashv\rightarrow P(i)))$
 $\langle proof \rangle$

3.9 Bounded quantifiers

syntax

-lessAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists ALL \ -<./ \ -) \ [0, 0, 10] \ 10)$
-lessEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists EX \ -<./ \ -) \ [0, 0, 10] \ 10)$
-leAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists ALL \ -<=./ \ -) \ [0, 0, 10] \ 10)$
-leEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists EX \ -<=./ \ -) \ [0, 0, 10] \ 10)$

-gtAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists ALL \ ->./ \ -) \ [0, 0, 10] \ 10)$
-gtEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists EX \ ->./ \ -) \ [0, 0, 10] \ 10)$
-geAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists ALL \ ->=./ \ -) \ [0, 0, 10] \ 10)$
-geEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists EX \ ->=./ \ -) \ [0, 0, 10] \ 10)$

syntax (*xsymbols*)

-lessAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \ -<./ \ -) \ [0, 0, 10] \ 10)$
-lessEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \ -<./ \ -) \ [0, 0, 10] \ 10)$
-leAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \ -<=./ \ -) \ [0, 0, 10] \ 10)$
-leEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \ -<=./ \ -) \ [0, 0, 10] \ 10)$

-gtAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \ ->./ \ -) \ [0, 0, 10] \ 10)$
-gtEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \ ->./ \ -) \ [0, 0, 10] \ 10)$
-geAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \ ->=./ \ -) \ [0, 0, 10] \ 10)$
-geEx :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \ ->=./ \ -) \ [0, 0, 10] \ 10)$

syntax (*HOL*)

-lessAll :: $[idt, 'a, bool] \Rightarrow bool \quad ((\exists! \ -<./ \ -) \ [0, 0, 10] \ 10)$

$-lessEx :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists? \text{-<-./ -}) [0, 0, 10] 10)$
 $-leAll :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists! \text{-<=.-./ -}) [0, 0, 10] 10)$
 $-leEx :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists? \text{-<=.-./ -}) [0, 0, 10] 10)$

syntax (HTML output)

$-lessAll :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \text{-<-./ -}) [0, 0, 10] 10)$
 $-lessEx :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \text{-<-./ -}) [0, 0, 10] 10)$
 $-leAll :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \text{-<=.-./ -}) [0, 0, 10] 10)$
 $-leEx :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \text{-<=.-./ -}) [0, 0, 10] 10)$

$-gtAll :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \text{->-./ -}) [0, 0, 10] 10)$
 $-gtEx :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \text{->-./ -}) [0, 0, 10] 10)$
 $-geAll :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \forall \text{->=.-./ -}) [0, 0, 10] 10)$
 $-geEx :: [idt, 'a, bool] \Rightarrow bool \quad ((\exists \exists \text{->=.-./ -}) [0, 0, 10] 10)$

translations

$ALL\ x < y. P \Rightarrow ALL\ x. x < y \dashrightarrow P$
 $EX\ x < y. P \Rightarrow EX\ x. x < y \ \& \ P$
 $ALL\ x \leq y. P \Rightarrow ALL\ x. x \leq y \dashrightarrow P$
 $EX\ x \leq y. P \Rightarrow EX\ x. x \leq y \ \& \ P$
 $ALL\ x > y. P \Rightarrow ALL\ x. x > y \dashrightarrow P$
 $EX\ x > y. P \Rightarrow EX\ x. x > y \ \& \ P$
 $ALL\ x \geq y. P \Rightarrow ALL\ x. x \geq y \dashrightarrow P$
 $EX\ x \geq y. P \Rightarrow EX\ x. x \geq y \ \& \ P$

$\langle ML \rangle$

3.10 Extra transitivity rules

These support proving chains of decreasing inequalities $a \leq b \leq c \dots$ in Isar proofs.

lemma *xt1*: $a = b \implies b > c \implies a > c$
 $\langle proof \rangle$

lemma *xt2*: $a > b \implies b = c \implies a > c$
 $\langle proof \rangle$

lemma *xt3*: $a = b \implies b \geq c \implies a \geq c$
 $\langle proof \rangle$

lemma *xt4*: $a \geq b \implies b = c \implies a \geq c$
 $\langle proof \rangle$

lemma *xt5*: $(x::'a::order) \geq y \implies y \geq x \implies x = y$
 $\langle proof \rangle$

lemma *xt6*: $(x::'a::order) \geq y \implies y \geq z \implies x \geq z$
 $\langle proof \rangle$

lemma *xt7*: $(x::'a::order) > y ==> y >= z ==> x > z$
 $\langle proof \rangle$

lemma *xt8*: $(x::'a::order) >= y ==> y > z ==> x > z$
 $\langle proof \rangle$

lemma *xt9*: $(a::'a::order) > b ==> b > a ==> ?P$
 $\langle proof \rangle$

lemma *xt10*: $(x::'a::order) > y ==> y > z ==> x > z$
 $\langle proof \rangle$

lemma *xt11*: $(a::'a::order) >= b ==> a \sim b ==> a > b$
 $\langle proof \rangle$

lemma *xt12*: $(a::'a::order) \sim b ==> a >= b ==> a > b$
 $\langle proof \rangle$

lemma *xt13*: $a = f b ==> b > c ==> (!x y. x > y ==> f x > f y) ==>$
 $a > f c$
 $\langle proof \rangle$

lemma *xt14*: $a > b ==> f b = c ==> (!x y. x > y ==> f x > f y) ==>$
 $f a > c$
 $\langle proof \rangle$

lemma *xt15*: $a = f b ==> b >= c ==> (!x y. x >= y ==> f x >= f y) ==>$
 $a >= f c$
 $\langle proof \rangle$

lemma *xt16*: $a >= b ==> f b = c ==> (!x y. x >= y ==> f x >= f y) ==>$
 $f a >= c$
 $\langle proof \rangle$

lemma *xt17*: $(a::'a::order) >= f b ==> b >= c ==>$
 $(!x y. x >= y ==> f x >= f y) ==> a >= f c$
 $\langle proof \rangle$

lemma *xt18*: $(a::'a::order) >= b ==> (f b::'b::order) >= c ==>$
 $(!x y. x >= y ==> f x >= f y) ==> f a >= c$
 $\langle proof \rangle$

lemma *xt19*: $(a::'a::order) > f b ==> (b::'b::order) >= c ==>$
 $(!x y. x >= y ==> f x >= f y) ==> a > f c$
 $\langle proof \rangle$

lemma *xt20*: $(a::'a::order) > b ==> (f b::'b::order) >= c ==>$
 $(!x y. x > y ==> f x > f y) ==> f a > c$
 $\langle proof \rangle$

lemma *xt21*: $(a::'a::order) \geq f\ b \implies b \geq c \implies$
 $(!!x\ y. x \geq y \implies f\ x \geq f\ y) \implies a \geq f\ c$
 $\langle proof \rangle$

lemma *xt22*: $(a::'a::order) \geq b \implies (f\ b::'b::order) \geq c \implies$
 $(!!x\ y. x \geq y \implies f\ x \geq f\ y) \implies f\ a \geq c$
 $\langle proof \rangle$

lemma *xt23*: $(a::'a::order) \geq f\ b \implies (b::'b::order) \geq c \implies$
 $(!!x\ y. x \geq y \implies f\ x \geq f\ y) \implies a \geq f\ c$
 $\langle proof \rangle$

lemma *xt24*: $(a::'a::order) \geq b \implies (f\ b::'b::order) \geq c \implies$
 $(!!x\ y. x \geq y \implies f\ x \geq f\ y) \implies f\ a \geq c$
 $\langle proof \rangle$

lemmas *xtrans* = *xt1 xt2 xt3 xt4 xt5 xt6 xt7 xt8 xt9 xt10 xt11 xt12*
xt13 xt14 xt15 xt15 xt17 xt18 xt19 xt20 xt21 xt22 xt23 xt24

end

4 LOrder: Lattice Orders

theory *LOrder*
imports *Orderings*
begin

The theory of lattices developed here is taken from the book:

- *Lattice Theory* by Garret Birkhoff, American Mathematical Society 1979.

constdefs

is-meet :: $((a::order) \Rightarrow 'a \Rightarrow 'a) \Rightarrow bool$
is-meet *m* == ! *a b x*. $m\ a\ b \leq a \wedge m\ a\ b \leq b \wedge (x \leq a \wedge x \leq b \longrightarrow x \leq m\ a\ b)$
is-join :: $((a::order) \Rightarrow 'a \Rightarrow 'a) \Rightarrow bool$
is-join *j* == ! *a b x*. $a \leq j\ a\ b \wedge b \leq j\ a\ b \wedge (a \leq x \wedge b \leq x \longrightarrow j\ a\ b \leq x)$

lemma *is-meet-unique*:

assumes *is-meet* *u is-meet v* **shows** $u = v$
 $\langle proof \rangle$

lemma *is-join-unique*:

assumes *is-join* *u* *is-join* *v* **shows** $u = v$
 $\langle \text{proof} \rangle$

axclass *join-semilorder* $<$ *order*
join-exists: ? *j*. *is-join* *j*

axclass *meet-semilorder* $<$ *order*
meet-exists: ? *m*. *is-meet* *m*

axclass *lorder* $<$ *join-semilorder*, *meet-semilorder*

constdefs
 $\text{meet} :: ('a::\text{meet-semilorder}) \Rightarrow 'a \Rightarrow 'a$
 $\text{meet} == \text{THE } m. \text{is-meet } m$
 $\text{join} :: ('a::\text{join-semilorder}) \Rightarrow 'a \Rightarrow 'a$
 $\text{join} == \text{THE } j. \text{is-join } j$

lemma *is-meet-meet*: *is-meet* ($\text{meet}::'a \Rightarrow 'a \Rightarrow ('a::\text{meet-semilorder})$)
 $\langle \text{proof} \rangle$

lemma *meet-unique*: (*is-meet* *m*) = (*m* = *meet*)
 $\langle \text{proof} \rangle$

lemma *is-join-join*: *is-join* ($\text{join}::'a \Rightarrow 'a \Rightarrow ('a::\text{join-semilorder})$)
 $\langle \text{proof} \rangle$

lemma *join-unique*: (*is-join* *j*) = (*j* = *join*)
 $\langle \text{proof} \rangle$

lemma *meet-left-le*: $\text{meet } a \ b \leq (a::'a::\text{meet-semilorder})$
 $\langle \text{proof} \rangle$

lemma *meet-right-le*: $\text{meet } a \ b \leq (b::'a::\text{meet-semilorder})$
 $\langle \text{proof} \rangle$

lemma *meet-imp-le*: $x \leq a \implies x \leq b \implies x \leq \text{meet } a \ (b::'a::\text{meet-semilorder})$
 $\langle \text{proof} \rangle$

lemma *join-left-le*: $a \leq \text{join } a \ (b::'a::\text{join-semilorder})$
 $\langle \text{proof} \rangle$

lemma *join-right-le*: $b \leq \text{join } a \ (b::'a::\text{join-semilorder})$
 $\langle \text{proof} \rangle$

lemma *join-imp-le*: $a \leq x \implies b \leq x \implies \text{join } a \ b \leq (x::'a::\text{join-semilorder})$
 $\langle \text{proof} \rangle$

lemmas *meet-join-le* = *meet-left-le* *meet-right-le* *join-left-le* *join-right-le*

lemma *is-meet-min*: *is-meet* (*min*::'a \Rightarrow 'a \Rightarrow ('a::linorder))
 ⟨proof⟩

lemma *is-join-max*: *is-join* (*max*::'a \Rightarrow 'a \Rightarrow ('a::linorder))
 ⟨proof⟩

instance *linorder* \subseteq *meet-semilorder*
 ⟨proof⟩

instance *linorder* \subseteq *join-semilorder*
 ⟨proof⟩

instance *linorder* \subseteq *lorder* ⟨proof⟩

lemma *meet-min*: *meet* = (*min* :: 'a \Rightarrow 'a \Rightarrow ('a::linorder))
 ⟨proof⟩

lemma *join-max*: *join* = (*max* :: 'a \Rightarrow 'a \Rightarrow ('a::linorder))
 ⟨proof⟩

lemma *meet-idempotent[simp]*: *meet* *x* *x* = *x*
 ⟨proof⟩

lemma *join-idempotent[simp]*: *join* *x* *x* = *x*
 ⟨proof⟩

lemma *meet-comm*: *meet* *x* *y* = *meet* *y* *x*
 ⟨proof⟩

lemma *join-comm*: *join* *x* *y* = *join* *y* *x*
 ⟨proof⟩

lemma *meet-assoc*: *meet* (*meet* *x* *y*) *z* = *meet* *x* (*meet* *y* *z*) (**is** ?l=?r)
 ⟨proof⟩

lemma *join-assoc*: *join* (*join* *x* *y*) *z* = *join* *x* (*join* *y* *z*) (**is** ?l=?r)
 ⟨proof⟩

lemma *meet-left-comm*: *meet* *a* (*meet* *b* *c*) = *meet* *b* (*meet* *a* *c*)
 ⟨proof⟩

lemma *meet-left-idempotent*: *meet* *y* (*meet* *y* *x*) = *meet* *y* *x*
 ⟨proof⟩

lemma *join-left-comm*: *join* *a* (*join* *b* *c*) = *join* *b* (*join* *a* *c*)
 ⟨proof⟩

lemma *join-left-idempotent*: *join* *y* (*join* *y* *x*) = *join* *y* *x*
 ⟨proof⟩

lemmas *meet-aci* = *meet-assoc meet-comm meet-left-comm meet-left-idempotent*

lemmas *join-aci* = *join-assoc join-comm join-left-comm join-left-idempotent*

lemma *le-def-meet*: $(x \leq y) = (\text{meet } x \ y = x)$
 $\langle \text{proof} \rangle$

lemma *le-def-join*: $(x \leq y) = (\text{join } x \ y = y)$
 $\langle \text{proof} \rangle$

lemma *meet-join-absorp*: $\text{meet } x \ (\text{join } x \ y) = x$
 $\langle \text{proof} \rangle$

lemma *join-meet-absorp*: $\text{join } x \ (\text{meet } x \ y) = x$
 $\langle \text{proof} \rangle$

lemma *meet-mono*: $y \leq z \implies \text{meet } x \ y \leq \text{meet } x \ z$
 $\langle \text{proof} \rangle$

lemma *join-mono*: $y \leq z \implies \text{join } x \ y \leq \text{join } x \ z$
 $\langle \text{proof} \rangle$

lemma *distrib-join-le*: $\text{join } x \ (\text{meet } y \ z) \leq \text{meet } (\text{join } x \ y) \ (\text{join } x \ z)$ (**is** - \leq ?*r*)
 $\langle \text{proof} \rangle$

lemma *distrib-meet-le*: $\text{join } (\text{meet } x \ y) \ (\text{meet } x \ z) \leq \text{meet } x \ (\text{join } y \ z)$ (**is** ?*l* \leq -)
 $\langle \text{proof} \rangle$

lemma *meet-join-eq-imp-le*: $a = c \vee a = d \vee b = c \vee b = d \implies \text{meet } a \ b \leq \text{join } c \ d$
 $\langle \text{proof} \rangle$

lemma *modular-le*: $x \leq z \implies \text{join } x \ (\text{meet } y \ z) \leq \text{meet } (\text{join } x \ y) \ z$ (**is** - \implies ?*t* \leq -)
 $\langle \text{proof} \rangle$

end

5 Set: Set theory for higher-order logic

theory *Set*
imports *LOrder*
begin

A set in HOL is simply a predicate.

5.1 Basic syntax

global

typeddecl 'a set

arities set :: (type) type

consts

{} :: 'a set ({})
 UNIV :: 'a set
 insert :: 'a => 'a set => 'a set
 Collect :: ('a => bool) => 'a set — comprehension
 Int :: 'a set => 'a set => 'a set (**infixl** 70)
 Un :: 'a set => 'a set => 'a set (**infixl** 65)
 UNION :: 'a set => ('a => 'b set) => 'b set — general union
 INTER :: 'a set => ('a => 'b set) => 'b set — general intersection
 Union :: 'a set set => 'a set — union of a set
 Inter :: 'a set set => 'a set — intersection of a set
 Pow :: 'a set => 'a set set — powerset
 Ball :: 'a set => ('a => bool) => bool — bounded universal quantifiers

 Bex :: 'a set => ('a => bool) => bool — bounded existential
 quantifiers
 image :: ('a => 'b) => 'a set => 'b set (**infixr** ' 90)

syntax

op : :: 'a => 'a set => bool (op :)

consts

op : :: 'a => 'a set => bool ((-/ : -) [50, 51] 50) — membership

local

instance set :: (type) {ord, minus} <proof>

5.2 Additional concrete syntax

syntax

range :: ('a => 'b) => 'b set — of function

 op ~: :: 'a => 'a set => bool (op ~:) — non-membership
 op ~: :: 'a => 'a set => bool ((-/ ~: -) [50, 51] 50)

 @Finset :: args => 'a set ({(-)})
 @Coll :: pptrn => bool => 'a set ((1{-./ -}))
 @SetCompr :: 'a => idts => bool => 'a set ((1{- |./ -}))
 @Collect :: idt => 'a set => bool => 'a set ((1{- :./ -}))
 @INTER1 :: pptrns => 'b set => 'b set ((3INT -./ -) 10)
 @UNION1 :: pptrns => 'b set => 'b set ((3UN -./ -) 10)
 @INTER :: pptrn => 'a set => 'b set => 'b set ((3INT -.: -) 10)

@UNION :: *pttrn* => 'a set => 'b set => 'b set ((3UN :-./ -) 10)

-Ball :: *pttrn* => 'a set => bool => bool ((3ALL :-./ -) [0, 0, 10] 10)

-Bex :: *pttrn* => 'a set => bool => bool ((3EX :-./ -) [0, 0, 10] 10)

syntax (HOL)

-Ball :: *pttrn* => 'a set => bool => bool ((3! :-./ -) [0, 0, 10] 10)

-Bex :: *pttrn* => 'a set => bool => bool ((3? :-./ -) [0, 0, 10] 10)

translations

range *f* == *f*‘UNIV

x ~: *y* == ~ (*x* : *y*)

{*x*, *xs*} == insert *x* {*xs*}

{*x*} == insert *x* {}

{*x*. *P*} == Collect (%*x*. *P*)

{*x*:*A*. *P*} => {*x*. *x*:*A* & *P*}

UN *x y*. *B* == UN *x*. UN *y*. *B*

UN *x*. *B* == UNION UNIV (%*x*. *B*)

UN *x*. *B* == UN *x*:UNIV. *B*

INT *x y*. *B* == INT *x*. INT *y*. *B*

INT *x*. *B* == INTER UNIV (%*x*. *B*)

INT *x*. *B* == INT *x*:UNIV. *B*

UN *x*:*A*. *B* == UNION *A* (%*x*. *B*)

INT *x*:*A*. *B* == INTER *A* (%*x*. *B*)

ALL *x*:*A*. *P* == Ball *A* (%*x*. *P*)

EX *x*:*A*. *P* == Bex *A* (%*x*. *P*)

syntax (output)

-setle :: 'a set => 'a set => bool (op <=)

-setle :: 'a set => 'a set => bool ((-/ <= -) [50, 51] 50)

-setless :: 'a set => 'a set => bool (op <)

-setless :: 'a set => 'a set => bool ((-/ < -) [50, 51] 50)

syntax (xsymbols)

-setle :: 'a set => 'a set => bool (op ⊆)

-setle :: 'a set => 'a set => bool ((-/ ⊆ -) [50, 51] 50)

-setless :: 'a set => 'a set => bool (op ⊂)

-setless :: 'a set => 'a set => bool ((-/ ⊂ -) [50, 51] 50)

op Int :: 'a set => 'a set => 'a set (infixl ∩ 70)

op Un :: 'a set => 'a set => 'a set (infixl ∪ 65)

op : :: 'a => 'a set => bool (op ∈)

op : :: 'a => 'a set => bool ((-/ ∈ -) [50, 51] 50)

op ~: :: 'a => 'a set => bool (op ∉)

op ~: :: 'a => 'a set => bool ((-/ ∉ -) [50, 51] 50)

Union :: 'a set set => 'a set (∪ - [90] 90)

Inter :: 'a set set => 'a set (∩ - [90] 90)

-Ball :: *pttrn* => 'a set => bool => bool ((3∀ -∈./ -) [0, 0, 10] 10)

-Bex :: *pttrn* => 'a set => bool => bool ((3∃ -∈./ -) [0, 0, 10] 10)

syntax (*HTML output*)

$\text{-setle} \quad :: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad (op \subseteq)$
 $\text{-setle} \quad :: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad ((-/ \subseteq -) [50, 51] 50)$
 $\text{-setless} \quad :: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad (op \subset)$
 $\text{-setless} \quad :: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad ((-/ \subset -) [50, 51] 50)$
 $\text{op Int} \quad :: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow 'a \text{ set} \quad (\text{infixl } \cap 70)$
 $\text{op Un} \quad :: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow 'a \text{ set} \quad (\text{infixl } \cup 65)$
 $\text{op } : \quad :: 'a \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad (op \in)$
 $\text{op } : \quad :: 'a \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad ((-/ \in -) [50, 51] 50)$
 $\text{op } \sim : \quad :: 'a \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad (op \notin)$
 $\text{op } \sim : \quad :: 'a \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \quad ((-/ \notin -) [50, 51] 50)$
 $\text{-Ball} \quad :: \text{pttrn} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \Rightarrow \text{bool} \quad ((\forall - \in -) [0, 0, 10] 10)$
 $\text{-Bex} \quad :: \text{pttrn} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \Rightarrow \text{bool} \quad ((\exists - \in -) [0, 0, 10] 10)$

syntax (*xsymbols*)

$\text{@Collect} \quad :: \text{idt} \Rightarrow 'a \text{ set} \Rightarrow \text{bool} \Rightarrow 'a \text{ set} \quad ((1\{- \in - / -\}))$
 $\text{@UNION1} \quad :: \text{pttrns} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcup - / -) 10)$
 $\text{@INTER1} \quad :: \text{pttrns} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcap - / -) 10)$
 $\text{@UNION} \quad :: \text{pttrn} \Rightarrow 'a \text{ set} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcup - \in - / -) 10)$
 $\text{@INTER} \quad :: \text{pttrn} \Rightarrow 'a \text{ set} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcap - \in - / -) 10)$

syntax (*latex output*)

$\text{@UNION1} \quad :: \text{pttrns} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcup (00-) / -) 10)$
 $\text{@INTER1} \quad :: \text{pttrns} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcap (00-) / -) 10)$
 $\text{@UNION} \quad :: \text{pttrn} \Rightarrow 'a \text{ set} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcup (00- \in -) / -) 10)$
 $\text{@INTER} \quad :: \text{pttrn} \Rightarrow 'a \text{ set} \Rightarrow 'b \text{ set} \Rightarrow 'b \text{ set} \quad ((3\bigcap (00- \in -) / -) 10)$

Note the difference between ordinary xsymbol syntax of indexed unions and intersections (e.g. $\bigcup_{a_1 \in A_1} B$) and their \LaTeX rendition: $\bigcup_{a_1 \in A_1} B$. The former does not make the index expression a subscript of the union/intersection symbol because this leads to problems with nested subscripts in Proof General.

translations

$\text{op } \subseteq \Rightarrow \text{op } \leq :: - \text{ set} \Rightarrow - \text{ set} \Rightarrow \text{bool}$
 $\text{op } \subset \Rightarrow \text{op } < :: - \text{ set} \Rightarrow - \text{ set} \Rightarrow \text{bool}$

$\langle ML \rangle$

5.2.1 Bounded quantifiers**syntax**

$\text{-setlessAll} \quad :: [\text{idt}, 'a, \text{bool}] \Rightarrow \text{bool} \quad ((3ALL -<- / -) [0, 0, 10] 10)$
 $\text{-setlessEx} \quad :: [\text{idt}, 'a, \text{bool}] \Rightarrow \text{bool} \quad ((3EX -<- / -) [0, 0, 10] 10)$
 $\text{-setleAll} \quad :: [\text{idt}, 'a, \text{bool}] \Rightarrow \text{bool} \quad ((3ALL -<= / -) [0, 0, 10] 10)$
 $\text{-setleEx} \quad :: [\text{idt}, 'a, \text{bool}] \Rightarrow \text{bool} \quad ((3EX -<= / -) [0, 0, 10] 10)$

syntax (*xsymbols*)

$\text{-setlessAll} \quad :: [\text{idt}, 'a, \text{bool}] \Rightarrow \text{bool} \quad ((3\forall - \subset - / -) [0, 0, 10] 10)$
 $\text{-setlessEx} \quad :: [\text{idt}, 'a, \text{bool}] \Rightarrow \text{bool} \quad ((3\exists - \subset - / -) [0, 0, 10] 10)$

-settleAll :: [idt, 'a, bool] => bool (($\exists \forall$ - \subseteq - / -) [0, 0, 10] 10)
 -settleEx :: [idt, 'a, bool] => bool (($\exists \exists$ - \subseteq - / -) [0, 0, 10] 10)

syntax (HOL)

-setlessAll :: [idt, 'a, bool] => bool (($\exists!$ - \subseteq - / -) [0, 0, 10] 10)
 -setlessEx :: [idt, 'a, bool] => bool (($\exists?$ - \subseteq - / -) [0, 0, 10] 10)
 -settleAll :: [idt, 'a, bool] => bool (($\exists!$ - \subseteq - / -) [0, 0, 10] 10)
 -settleEx :: [idt, 'a, bool] => bool (($\exists?$ - \subseteq - / -) [0, 0, 10] 10)

syntax (HTML output)

-setlessAll :: [idt, 'a, bool] => bool (($\exists \forall$ - \subset - / -) [0, 0, 10] 10)
 -setlessEx :: [idt, 'a, bool] => bool (($\exists \exists$ - \subset - / -) [0, 0, 10] 10)
 -settleAll :: [idt, 'a, bool] => bool (($\exists \forall$ - \subseteq - / -) [0, 0, 10] 10)
 -settleEx :: [idt, 'a, bool] => bool (($\exists \exists$ - \subseteq - / -) [0, 0, 10] 10)

translations

$\forall A \subseteq B. P \Rightarrow ALL A. A \subseteq B \dashrightarrow P$
 $\exists A \subseteq B. P \Rightarrow EX A. A \subseteq B \ \& \ P$
 $\forall A \subseteq B. P \Rightarrow ALL A. A \subseteq B \dashrightarrow P$
 $\exists A \subseteq B. P \Rightarrow EX A. A \subseteq B \ \& \ P$

$\langle ML \rangle$

Translate between $\{e \mid x1...xn. P\}$ and $\{u. EX x1..xn. u = e \ \& \ P\}; \{y. EX x1..xn. y = e \ \& \ P\}$ is only translated if $[0..n] \text{ subset } \text{bvs}(e)$.

$\langle ML \rangle$

5.3 Rules and definitions

Isomorphisms between predicates and sets.

axioms

mem-Collect-eq: $(a : \{x. P(x)\}) = P(a)$
 Collect-mem-eq: $\{x. x:A\} = A$

finalconsts

Collect
 op :

defs

Ball-def: $Ball \ A \ P \quad == \ ALL \ x. \ x:A \dashrightarrow P(x)$
 Bex-def: $Bex \ A \ P \quad == \ EX \ x. \ x:A \ \& \ P(x)$

defs (overloaded)

subset-def: $A \leq B \quad == \ ALL \ x:A. \ x:B$
 psubset-def: $A < B \quad == \ (A::'a \text{ set}) \leq B \ \& \ \sim A=B$
 Compl-def: $- \ A \quad == \ \{x. \ \sim x:A\}$
 set-diff-def: $A - B \quad == \ \{x. \ x:A \ \& \ \sim x:B\}$

defs

$Un\text{-}def: \quad A \text{ Un } B \quad == \{x. x:A \mid x:B\}$
 $Int\text{-}def: \quad A \text{ Int } B \quad == \{x. x:A \ \& \ x:B\}$
 $INTER\text{-}def: \quad INTER \ A \ B \quad == \{y. \ ALL \ x:A. \ y: \ B(x)\}$
 $UNION\text{-}def: \quad UNION \ A \ B \quad == \{y. \ EX \ x:A. \ y: \ B(x)\}$
 $Inter\text{-}def: \quad Inter \ S \quad == (INT \ x:S. \ x)$
 $Union\text{-}def: \quad Union \ S \quad == (UN \ x:S. \ x)$
 $Pow\text{-}def: \quad Pow \ A \quad == \{B. \ B \leq A\}$
 $empty\text{-}def: \quad \{\}$
 $UNIV\text{-}def: \quad UNIV \quad == \{x. \ True\}$
 $insert\text{-}def: \quad insert \ a \ B \quad == \{x. \ x=a\} \text{ Un } B$
 $image\text{-}def: \quad f^{\circ}A \quad == \{y. \ EX \ x:A. \ y = f(x)\}$

5.4 Lemmas and proof tool setup

5.4.1 Relating predicates and sets

declare *mem-Collect-eq* [*iff*] *Collect-mem-eq* [*simp*]

lemma *CollectI*: $P(a) ==> a : \{x. P(x)\}$
 $\langle proof \rangle$

lemma *CollectD*: $a : \{x. P(x)\} ==> P(a)$
 $\langle proof \rangle$

lemma *Collect-cong*: $(!!x. P \ x = Q \ x) ==> \{x. P(x)\} = \{x. Q(x)\}$
 $\langle proof \rangle$

lemmas *CollectE* = *CollectD* [*elim-format*]

5.4.2 Bounded quantifiers

lemma *ballI* [*intro!*]: $(!!x. x:A ==> P \ x) ==> \ ALL \ x:A. P \ x$
 $\langle proof \rangle$

lemmas *strip* = *impI* *allI* *ballI*

lemma *bspec* [*dest?*]: $\ ALL \ x:A. P \ x ==> x:A ==> P \ x$
 $\langle proof \rangle$

lemma *ballE* [*elim*]: $\ ALL \ x:A. P \ x ==> (P \ x ==> Q) ==> (x \sim: A ==> Q) ==> Q$
 $\langle proof \rangle$
 $\langle ML \rangle$

This tactic takes assumptions $\forall x \in A. P \ x$ and $a \in A$; creates assumption $P \ a$.

$\langle ML \rangle$

Gives better instantiation for bound:

$\langle ML \rangle$

lemma *bexI* [*intro*]: $P\ x \implies x:A \implies EX\ x:A.\ P\ x$
 — Normally the best argument order: $P\ x$ constrains the choice of $x \in A$.
 $\langle proof \rangle$

lemma *rev-bexI* [*intro?*]: $x:A \implies P\ x \implies EX\ x:A.\ P\ x$
 — The best argument order when there is only one $x \in A$.
 $\langle proof \rangle$

lemma *bexCI*: $(ALL\ x:A.\ \sim P\ x \implies P\ a) \implies a:A \implies EX\ x:A.\ P\ x$
 $\langle proof \rangle$

lemma *bexE* [*elim!*]: $EX\ x:A.\ P\ x \implies (!x.\ x:A \implies P\ x \implies Q) \implies Q$
 $\langle proof \rangle$

lemma *ball-triv* [*simp*]: $(ALL\ x:A.\ P) = ((EX\ x.\ x:A) \dashv\vdash P)$
 — Trivial rewrite rule.
 $\langle proof \rangle$

lemma *bex-triv* [*simp*]: $(EX\ x:A.\ P) = ((EX\ x.\ x:A) \& P)$
 — Dual form for existentials.
 $\langle proof \rangle$

lemma *bex-triv-one-point1* [*simp*]: $(EX\ x:A.\ x = a) = (a:A)$
 $\langle proof \rangle$

lemma *bex-triv-one-point2* [*simp*]: $(EX\ x:A.\ a = x) = (a:A)$
 $\langle proof \rangle$

lemma *bex-one-point1* [*simp*]: $(EX\ x:A.\ x = a \& P\ x) = (a:A \& P\ a)$
 $\langle proof \rangle$

lemma *bex-one-point2* [*simp*]: $(EX\ x:A.\ a = x \& P\ x) = (a:A \& P\ a)$
 $\langle proof \rangle$

lemma *ball-one-point1* [*simp*]: $(ALL\ x:A.\ x = a \dashv\vdash P\ x) = (a:A \dashv\vdash P\ a)$
 $\langle proof \rangle$

lemma *ball-one-point2* [*simp*]: $(ALL\ x:A.\ a = x \dashv\vdash P\ x) = (a:A \dashv\vdash P\ a)$
 $\langle proof \rangle$

$\langle ML \rangle$

5.4.3 Congruence rules

lemma *ball-cong*:
 $A = B \implies (!x.\ x:B \implies P\ x = Q\ x) \implies$
 $(ALL\ x:A.\ P\ x) = (ALL\ x:B.\ Q\ x)$
 $\langle proof \rangle$

lemma *strong-ball-cong* [*cong*]:

$A = B \implies (!x. x:B \implies P\ x = Q\ x) \implies$
 $(ALL\ x:A. P\ x) = (ALL\ x:B. Q\ x)$
 $\langle proof \rangle$

lemma *bex-cong*:

$A = B \implies (!x. x:B \implies P\ x = Q\ x) \implies$
 $(EX\ x:A. P\ x) = (EX\ x:B. Q\ x)$
 $\langle proof \rangle$

lemma *strong-bex-cong* [*cong*]:

$A = B \implies (!x. x:B \implies P\ x = Q\ x) \implies$
 $(EX\ x:A. P\ x) = (EX\ x:B. Q\ x)$
 $\langle proof \rangle$

5.4.4 Subsets

lemma *subsetI* [*intro!*]: $(!x. x:A \implies x:B) \implies A \subseteq B$
 $\langle proof \rangle$

Map the type '*a set* $\implies anything$ ' to just '*a*'; for overloading constants whose first argument has type '*a set*'.

lemma *subsetD* [*elim*]: $A \subseteq B \implies c \in A \implies c \in B$
 — Rule in Modus Ponens style.
 $\langle proof \rangle$

declare *subsetD* [*intro?*] — FIXME

lemma *rev-subsetD*: $c \in A \implies A \subseteq B \implies c \in B$
 — The same, with reversed premises for use with *erule* – cf *rev-mp*.
 $\langle proof \rangle$

declare *rev-subsetD* [*intro?*] — FIXME

Converts $A \subseteq B$ to $x \in A \implies x \in B$.

$\langle ML \rangle$

lemma *subsetCE* [*elim*]: $A \subseteq B \implies (c \notin A \implies P) \implies (c \in B \implies P)$
 $\implies P$
 — Classical elimination rule.
 $\langle proof \rangle$

Takes assumptions $A \subseteq B$; $c \in A$ and creates the assumption $c \in B$.

$\langle ML \rangle$

lemma *contra-subsetD*: $A \subseteq B \implies c \notin B \implies c \notin A$

$\langle proof \rangle$

lemma *subset-refl*: $A \subseteq A$
 $\langle proof \rangle$

lemma *subset-trans*: $A \subseteq B \implies B \subseteq C \implies A \subseteq C$
 $\langle proof \rangle$

5.4.5 Equality

lemma *set-ext*: **assumes** *prem*: $(!!x. (x:A) = (x:B))$ **shows** $A = B$
 $\langle proof \rangle$

lemma *expand-set-eq*: $(A = B) = (ALL\ x. (x:A) = (x:B))$
 $\langle proof \rangle$

lemma *subset-antisym* [*intro!*]: $A \subseteq B \implies B \subseteq A \implies A = B$
 — Anti-symmetry of the subset relation.
 $\langle proof \rangle$

lemmas *equalityI* [*intro!*] = *subset-antisym*

Equality rules from ZF set theory – are they appropriate here?

lemma *equalityD1*: $A = B \implies A \subseteq B$
 $\langle proof \rangle$

lemma *equalityD2*: $A = B \implies B \subseteq A$
 $\langle proof \rangle$

Be careful when adding this to the clasets as *subset-empty* is in the simpset:
 $A = \{\}$ goes to $\{\} \subseteq A$ and $A \subseteq \{\}$ and then back to $A = \{\}$!

lemma *equalityE*: $A = B \implies (A \subseteq B \implies B \subseteq A \implies P) \implies P$
 $\langle proof \rangle$

lemma *equalityCE* [*elim*]:
 $A = B \implies (c \in A \implies c \in B \implies P) \implies (c \notin A \implies c \notin B \implies P) \implies P$
 $\langle proof \rangle$

Lemma for creating induction formulae – for ”pattern matching” on p . To make the induction hypotheses usable, apply *spec* or *bspec* to put universal quantifiers over the free variables in p .

lemma *setup-induction*: $p:A \implies (!!z. z:A \implies p = z \dashrightarrow R) \implies R$
 $\langle proof \rangle$

lemma *eqset-imp-iff*: $A = B \implies (x : A) = (x : B)$

$\langle proof \rangle$

lemma *eqelem-imp-iff*: $x = y ==> (x : A) = (y : A)$
 $\langle proof \rangle$

5.4.6 The universal set – UNIV

lemma *UNIV-I* [*simp*]: $x : UNIV$
 $\langle proof \rangle$

declare *UNIV-I* [*intro*] — unsafe makes it less likely to cause problems

lemma *UNIV-witness* [*intro?*]: $EX\ x. x : UNIV$
 $\langle proof \rangle$

lemma *subset-UNIV*: $A \subseteq UNIV$
 $\langle proof \rangle$

Eta-contracting these two rules (to remove P) causes them to be ignored because of their interaction with congruence rules.

lemma *ball-UNIV* [*simp*]: $Ball\ UNIV\ P = All\ P$
 $\langle proof \rangle$

lemma *bex-UNIV* [*simp*]: $Bex\ UNIV\ P = Ex\ P$
 $\langle proof \rangle$

5.4.7 The empty set

lemma *empty-iff* [*simp*]: $(c : \{\}) = False$
 $\langle proof \rangle$

lemma *emptyE* [*elim!*]: $a : \{\} ==> P$
 $\langle proof \rangle$

lemma *empty-subsetI* [*iff*]: $\{\} \subseteq A$
 — One effect is to delete the ASSUMPTION $\{\} \subseteq A$
 $\langle proof \rangle$

lemma *equals0I*: $(!!y. y \in A ==> False) ==> A = \{\}$
 $\langle proof \rangle$

lemma *equals0D*: $A = \{\} ==> a \notin A$
 — Use for reasoning about disjointness: $A \cap B = \{\}$
 $\langle proof \rangle$

lemma *ball-empty* [*simp*]: $Ball\ \{\} P = True$
 $\langle proof \rangle$

lemma *bex-empty* [*simp*]: $Bex\ \{\} P = False$

$\langle proof \rangle$

lemma *UNIV-not-empty* [iff]: $UNIV \sim = \{\}$
 $\langle proof \rangle$

5.4.8 The Powerset operator – Pow

lemma *Pow-iff* [iff]: $(A \in Pow\ B) = (A \subseteq B)$
 $\langle proof \rangle$

lemma *PowI*: $A \subseteq B ==> A \in Pow\ B$
 $\langle proof \rangle$

lemma *PowD*: $A \in Pow\ B ==> A \subseteq B$
 $\langle proof \rangle$

lemma *Pow-bottom*: $\{\} \in Pow\ B$
 $\langle proof \rangle$

lemma *Pow-top*: $A \in Pow\ A$
 $\langle proof \rangle$

5.4.9 Set complement

lemma *Compl-iff* [simp]: $(c \in -A) = (c \notin A)$
 $\langle proof \rangle$

lemma *ComplI* [intro!]: $(c \in A ==> False) ==> c \in -A$
 $\langle proof \rangle$

This form, with negated conclusion, works well with the Classical prover. Negated assumptions behave like formulae on the right side of the notional turnstile ...

lemma *ComplD* [dest!]: $c : -A ==> c \sim : A$
 $\langle proof \rangle$

lemmas *ComplE* = *ComplD* [elim-format]

5.4.10 Binary union – Un

lemma *Un-iff* [simp]: $(c : A\ Un\ B) = (c:A \mid c:B)$
 $\langle proof \rangle$

lemma *UnI1* [elim?]: $c:A ==> c : A\ Un\ B$
 $\langle proof \rangle$

lemma *UnI2* [elim?]: $c:B ==> c : A\ Un\ B$
 $\langle proof \rangle$

Classical introduction rule: no commitment to A vs B .

lemma *UnCI* [*intro!*]: $(c \sim : B \implies c : A) \implies c : A \text{ Un } B$
 $\langle \text{proof} \rangle$

lemma *UnE* [*elim!*]: $c : A \text{ Un } B \implies (c : A \implies P) \implies (c : B \implies P) \implies P$
 $\langle \text{proof} \rangle$

5.4.11 Binary intersection – Int

lemma *Int-iff* [*simp*]: $(c : A \text{ Int } B) = (c : A \ \& \ c : B)$
 $\langle \text{proof} \rangle$

lemma *IntI* [*intro!*]: $c : A \implies c : B \implies c : A \text{ Int } B$
 $\langle \text{proof} \rangle$

lemma *IntD1*: $c : A \text{ Int } B \implies c : A$
 $\langle \text{proof} \rangle$

lemma *IntD2*: $c : A \text{ Int } B \implies c : B$
 $\langle \text{proof} \rangle$

lemma *IntE* [*elim!*]: $c : A \text{ Int } B \implies (c : A \implies c : B \implies P) \implies P$
 $\langle \text{proof} \rangle$

5.4.12 Set difference

lemma *Diff-iff* [*simp*]: $(c : A - B) = (c : A \ \& \ c \sim : B)$
 $\langle \text{proof} \rangle$

lemma *DiffI* [*intro!*]: $c : A \implies c \sim : B \implies c : A - B$
 $\langle \text{proof} \rangle$

lemma *DiffD1*: $c : A - B \implies c : A$
 $\langle \text{proof} \rangle$

lemma *DiffD2*: $c : A - B \implies c : B \implies P$
 $\langle \text{proof} \rangle$

lemma *DiffE* [*elim!*]: $c : A - B \implies (c : A \implies c \sim : B \implies P) \implies P$
 $\langle \text{proof} \rangle$

5.4.13 Augmenting a set – insert

lemma *insert-iff* [*simp*]: $(a : \text{insert } b \ A) = (a = b \mid a : A)$
 $\langle \text{proof} \rangle$

lemma *insertI1*: $a : \text{insert } a \ B$
 $\langle \text{proof} \rangle$

lemma *insertI2*: $a : B \implies a : \text{insert } b \ B$
 $\langle \text{proof} \rangle$

lemma *insertE* [*elim!*]: $a : \text{insert } b \ A \implies (a = b \implies P) \implies (a : A \implies P)$
 $\implies P$
 $\langle \text{proof} \rangle$

lemma *insertCI* [*intro!*]: $(a \sim B \implies a = b) \implies a : \text{insert } b \ B$
 — Classical introduction rule.
 $\langle \text{proof} \rangle$

lemma *subset-insert-iff*: $(A \subseteq \text{insert } x \ B) = (\text{if } x : A \text{ then } A - \{x\} \subseteq B \text{ else } A \subseteq B)$
 $\langle \text{proof} \rangle$

5.4.14 Singletons, using insert

lemma *singletonI* [*intro!*]: $a : \{a\}$
 — Redundant? But unlike *insertCI*, it proves the subgoal immediately!
 $\langle \text{proof} \rangle$

lemma *singletonD* [*dest!*]: $b : \{a\} \implies b = a$
 $\langle \text{proof} \rangle$

lemmas *singletonE* = *singletonD* [*elim-format*]

lemma *singleton-iff*: $(b : \{a\}) = (b = a)$
 $\langle \text{proof} \rangle$

lemma *singleton-inject* [*dest!*]: $\{a\} = \{b\} \implies a = b$
 $\langle \text{proof} \rangle$

lemma *singleton-insert-inj-eq* [*iff*]: $(\{b\} = \text{insert } a \ A) = (a = b \ \& \ A \subseteq \{b\})$
 $\langle \text{proof} \rangle$

lemma *singleton-insert-inj-eq'* [*iff*]: $(\text{insert } a \ A = \{b\}) = (a = b \ \& \ A \subseteq \{b\})$
 $\langle \text{proof} \rangle$

lemma *subset-singletonD*: $A \subseteq \{x\} \implies A = \{\} \mid A = \{x\}$
 $\langle \text{proof} \rangle$

lemma *singleton-conv* [*simp*]: $\{x. x = a\} = \{a\}$
 $\langle \text{proof} \rangle$

lemma *singleton-conv2* [*simp*]: $\{x. a = x\} = \{a\}$
 $\langle \text{proof} \rangle$

lemma *diff-single-insert*: $A - \{x\} \subseteq B \implies x \in A \implies A \subseteq \text{insert } x \ B$

$\langle proof \rangle$

5.4.15 Unions of families

$UN\ x:A. B\ x$ is $\bigcup B \text{ ‘ } A$.

lemma *UN-iff* [*simp*]: $(b: (UN\ x:A. B\ x)) = (EX\ x:A. b: B\ x)$
 $\langle proof \rangle$

lemma *UN-I* [*intro*]: $a:A \implies b: B\ a \implies b: (UN\ x:A. B\ x)$
 — The order of the premises presupposes that A is rigid; b may be flexible.
 $\langle proof \rangle$

lemma *UN-E* [*elim*!]: $b : (UN\ x:A. B\ x) \implies (!x. x:A \implies b: B\ x \implies R) \implies R$
 $\langle proof \rangle$

lemma *UN-cong* [*cong*]:
 $A = B \implies (!x. x:B \implies C\ x = D\ x) \implies (UN\ x:A. C\ x) = (UN\ x:B. D\ x)$
 $\langle proof \rangle$

5.4.16 Intersections of families

$INT\ x:A. B\ x$ is $\bigcap B \text{ ‘ } A$.

lemma *INT-iff* [*simp*]: $(b: (INT\ x:A. B\ x)) = (ALL\ x:A. b: B\ x)$
 $\langle proof \rangle$

lemma *INT-I* [*intro*!]: $(!x. x:A \implies b: B\ x) \implies b : (INT\ x:A. B\ x)$
 $\langle proof \rangle$

lemma *INT-D* [*elim*]: $b : (INT\ x:A. B\ x) \implies a:A \implies b: B\ a$
 $\langle proof \rangle$

lemma *INT-E* [*elim*]: $b : (INT\ x:A. B\ x) \implies (b: B\ a \implies R) \implies (a \sim : A \implies R) \implies R$
 — “Classical” elimination – by the Excluded Middle on $a \in A$.
 $\langle proof \rangle$

lemma *INT-cong* [*cong*]:
 $A = B \implies (!x. x:B \implies C\ x = D\ x) \implies (INT\ x:A. C\ x) = (INT\ x:B. D\ x)$
 $\langle proof \rangle$

5.4.17 Union

lemma *Union-iff* [*simp*]: $(A : Union\ C) = (EX\ X:C. A:X)$
 $\langle proof \rangle$

lemma *UnionI* [*intro*]: $X:C \implies A:X \implies A : \text{Union } C$

— The order of the premises presupposes that C is rigid; A may be flexible.

$\langle \text{proof} \rangle$

lemma *UnionE* [*elim!*]: $A : \text{Union } C \implies (!X. A:X \implies X:C \implies R) \implies R$

$\langle \text{proof} \rangle$

5.4.18 Inter

lemma *Inter-iff* [*simp*]: $(A : \text{Inter } C) = (\text{ALL } X:C. A:X)$

$\langle \text{proof} \rangle$

lemma *InterI* [*intro!*]: $(!X. X:C \implies A:X) \implies A : \text{Inter } C$

$\langle \text{proof} \rangle$

A “destruct” rule – every X in C contains A as an element, but $A \in X$ can hold when $X \in C$ does not! This rule is analogous to *spec*.

lemma *InterD* [*elim*]: $A : \text{Inter } C \implies X:C \implies A:X$

$\langle \text{proof} \rangle$

lemma *InterE* [*elim*]: $A : \text{Inter } C \implies (X\sim:C \implies R) \implies (A:X \implies R) \implies R$

— “Classical” elimination rule – does not require proving $X \in C$.

$\langle \text{proof} \rangle$

Image of a set under a function. Frequently b does not have the syntactic form of $f x$.

lemma *image-eqI* [*simp*, *intro*]: $b = f x \implies x:A \implies b : f'A$

$\langle \text{proof} \rangle$

lemma *imageI*: $x : A \implies f x : f' A$

$\langle \text{proof} \rangle$

lemma *rev-image-eqI*: $x:A \implies b = f x \implies b : f'A$

— This version’s more effective when we already have the required x .

$\langle \text{proof} \rangle$

lemma *imageE* [*elim!*]:

$b : (\%x. f x)'A \implies (!x. b = f x \implies x:A \implies P) \implies P$

— The eta-expansion gives variable-name preservation.

$\langle \text{proof} \rangle$

lemma *image-Un*: $f'(A \text{ Un } B) = f'A \text{ Un } f'B$

$\langle \text{proof} \rangle$

lemma *image-iff*: $(z : f'A) = (\text{EX } x:A. z = f x)$

$\langle \text{proof} \rangle$

lemma *image-subset-iff*: $(f^{\circ}A \subseteq B) = (\forall x \in A. f\ x \in B)$

— This rewrite rule would confuse users if made default.

<proof>

lemma *subset-image-iff*: $(B \subseteq f^{\circ}A) = (EX\ AA. AA \subseteq A \ \& \ B = f^{\circ}AA)$

<proof>

lemma *image-subsetI*: $(!!x. x \in A ==> f\ x \in B) ==> f^{\circ}A \subseteq B$

— Replaces the three steps *subsetI*, *imageE*, *hypsubst*, but breaks too many existing proofs.

<proof>

Range of a function – just a translation for image!

lemma *range-eqI*: $b = f\ x ==> b \in \text{range } f$

<proof>

lemma *rangeI*: $f\ x \in \text{range } f$

<proof>

lemma *rangeE* [*elim?*]: $b \in \text{range } (\lambda x. f\ x) ==> (!!x. b = f\ x ==> P) ==> P$

<proof>

5.4.19 Set reasoning tools

Rewrite rules for boolean case-splitting: faster than *split-if* [*split*].

lemma *split-if-eq1*: $((\text{if } Q \text{ then } x \text{ else } y) = b) = ((Q \longrightarrow x = b) \ \& \ (\sim Q \longrightarrow y = b))$

<proof>

lemma *split-if-eq2*: $(a = (\text{if } Q \text{ then } x \text{ else } y)) = ((Q \longrightarrow a = x) \ \& \ (\sim Q \longrightarrow a = y))$

<proof>

Split ifs on either side of the membership relation. Not for [*simp*] – can cause goals to blow up!

lemma *split-if-mem1*: $((\text{if } Q \text{ then } x \text{ else } y) : b) = ((Q \longrightarrow x : b) \ \& \ (\sim Q \longrightarrow y : b))$

<proof>

lemma *split-if-mem2*: $(a : (\text{if } Q \text{ then } x \text{ else } y)) = ((Q \longrightarrow a : x) \ \& \ (\sim Q \longrightarrow a : y))$

<proof>

lemmas *split-ifs* = *if-bool-eq-conj split-if-eq1 split-if-eq2 split-if-mem1 split-if-mem2*

lemmas *mem-simps* =

insert-iff empty-iff Un-iff Int-iff Compl-iff Diff-iff

mem-Collect-eq UN-iff Union-iff INT-iff Inter-iff
 — Each of these has ALREADY been added [simp] above.

$\langle ML \rangle$

declare *subset-UNIV* [simp] *subset-refl* [simp]

5.4.20 The “proper subset” relation

lemma *psubsetI* [intro!]: $A \subseteq B \implies A \neq B \implies A \subset B$
 $\langle proof \rangle$

lemma *psubsetE* [elim!]:
 $[| A \subset B; [| A \subseteq B; \sim (B \subseteq A) |] \implies R |] \implies R$
 $\langle proof \rangle$

lemma *psubset-insert-iff*:
 $(A \subset \text{insert } x \ B) = (\text{if } x \in B \text{ then } A \subset B \text{ else if } x \in A \text{ then } A - \{x\} \subset B \text{ else } A \subseteq B)$
 $\langle proof \rangle$

lemma *psubset-eq*: $(A \subset B) = (A \subseteq B \ \& \ A \neq B)$
 $\langle proof \rangle$

lemma *psubset-imp-subset*: $A \subset B \implies A \subseteq B$
 $\langle proof \rangle$

lemma *psubset-trans*: $[| A \subset B; B \subset C |] \implies A \subset C$
 $\langle proof \rangle$

lemma *psubsetD*: $[| A \subset B; c \in A |] \implies c \in B$
 $\langle proof \rangle$

lemma *psubset-subset-trans*: $A \subset B \implies B \subseteq C \implies A \subset C$
 $\langle proof \rangle$

lemma *subset-psubset-trans*: $A \subseteq B \implies B \subset C \implies A \subset C$
 $\langle proof \rangle$

lemma *psubset-imp-ex-mem*: $A \subset B \implies \exists b. b \in (B - A)$
 $\langle proof \rangle$

lemma *atomize-ball*:
 $(!!x. x \in A \implies P \ x) == \text{Trueprop } (\forall x \in A. P \ x)$
 $\langle proof \rangle$

declare *atomize-ball* [symmetric, rulify]

5.5 Further set-theory lemmas

5.5.1 Derived rules involving subsets.

insert.

lemma *subset-insertI*: $B \subseteq \text{insert } a \ B$
 $\langle \text{proof} \rangle$

lemma *subset-insertI2*: $A \subseteq B \implies A \subseteq \text{insert } b \ B$
 $\langle \text{proof} \rangle$

lemma *subset-insert*: $x \notin A \implies (A \subseteq \text{insert } x \ B) = (A \subseteq B)$
 $\langle \text{proof} \rangle$

Big Union – least upper bound of a set.

lemma *Union-upper*: $B \in A \implies B \subseteq \text{Union } A$
 $\langle \text{proof} \rangle$

lemma *Union-least*: $(!!X. X \in A \implies X \subseteq C) \implies \text{Union } A \subseteq C$
 $\langle \text{proof} \rangle$

General union.

lemma *UN-upper*: $a \in A \implies B \ a \subseteq (\bigcup_{x \in A. B \ x})$
 $\langle \text{proof} \rangle$

lemma *UN-least*: $(!!x. x \in A \implies B \ x \subseteq C) \implies (\bigcup_{x \in A. B \ x}) \subseteq C$
 $\langle \text{proof} \rangle$

Big Intersection – greatest lower bound of a set.

lemma *Inter-lower*: $B \in A \implies \text{Inter } A \subseteq B$
 $\langle \text{proof} \rangle$

lemma *Inter-subset*:
 $[! X. X \in A \implies X \subseteq B; A \sim \{\}] \implies \bigcap A \subseteq B$
 $\langle \text{proof} \rangle$

lemma *Inter-greatest*: $(!!X. X \in A \implies C \subseteq X) \implies C \subseteq \text{Inter } A$
 $\langle \text{proof} \rangle$

lemma *INT-lower*: $a \in A \implies (\bigcap_{x \in A. B \ x}) \subseteq B \ a$
 $\langle \text{proof} \rangle$

lemma *INT-greatest*: $(!!x. x \in A \implies C \subseteq B \ x) \implies C \subseteq (\bigcap_{x \in A. B \ x})$
 $\langle \text{proof} \rangle$

Finite Union – the least upper bound of two sets.

lemma *Un-upper1*: $A \subseteq A \cup B$

$\langle proof \rangle$

lemma *Un-upper2*: $B \subseteq A \cup B$
 $\langle proof \rangle$

lemma *Un-least*: $A \subseteq C \implies B \subseteq C \implies A \cup B \subseteq C$
 $\langle proof \rangle$

Finite Intersection – the greatest lower bound of two sets.

lemma *Int-lower1*: $A \cap B \subseteq A$
 $\langle proof \rangle$

lemma *Int-lower2*: $A \cap B \subseteq B$
 $\langle proof \rangle$

lemma *Int-greatest*: $C \subseteq A \implies C \subseteq B \implies C \subseteq A \cap B$
 $\langle proof \rangle$

Set difference.

lemma *Diff-subset*: $A - B \subseteq A$
 $\langle proof \rangle$

lemma *Diff-subset-conv*: $(A - B \subseteq C) = (A \subseteq B \cup C)$
 $\langle proof \rangle$

Monotonicity.

lemma *mono-Un*: $mono\ f \implies f\ A \cup f\ B \subseteq f\ (A \cup B)$
 $\langle proof \rangle$

lemma *mono-Int*: $mono\ f \implies f\ (A \cap B) \subseteq f\ A \cap f\ B$
 $\langle proof \rangle$

5.5.2 Equalities involving union, intersection, inclusion, etc.

$\{\}$.

lemma *Collect-const* [simp]: $\{s. P\} = (if\ P\ then\ UNIV\ else\ \{\})$
 — supersedes *Collect-False-empty*
 $\langle proof \rangle$

lemma *subset-empty* [simp]: $(A \subseteq \{\}) = (A = \{\})$
 $\langle proof \rangle$

lemma *not-psubset-empty* [iff]: $\neg (A < \{\})$
 $\langle proof \rangle$

lemma *Collect-empty-eq* [simp]: $(Collect\ P = \{\}) = (\forall x. \neg P\ x)$
 $\langle proof \rangle$

lemma *Collect-neg-eq*: $\{x. \neg P x\} = - \{x. P x\}$
 ⟨proof⟩

lemma *Collect-disj-eq*: $\{x. P x \mid Q x\} = \{x. P x\} \cup \{x. Q x\}$
 ⟨proof⟩

lemma *Collect-imp-eq*: $\{x. P x \longrightarrow Q x\} = -\{x. P x\} \cup \{x. Q x\}$
 ⟨proof⟩

lemma *Collect-conj-eq*: $\{x. P x \ \& \ Q x\} = \{x. P x\} \cap \{x. Q x\}$
 ⟨proof⟩

lemma *Collect-all-eq*: $\{x. \forall y. P x y\} = (\bigcap y. \{x. P x y\})$
 ⟨proof⟩

lemma *Collect-ball-eq*: $\{x. \forall y \in A. P x y\} = (\bigcap y \in A. \{x. P x y\})$
 ⟨proof⟩

lemma *Collect-ex-eq*: $\{x. \exists y. P x y\} = (\bigcup y. \{x. P x y\})$
 ⟨proof⟩

lemma *Collect-bex-eq*: $\{x. \exists y \in A. P x y\} = (\bigcup y \in A. \{x. P x y\})$
 ⟨proof⟩

insert.

lemma *insert-is-Un*: $\text{insert } a \ A = \{a\} \ \text{Un } A$
 — NOT SUITABLE FOR REWRITING since $\{a\} == \text{insert } a \ \{\}$
 ⟨proof⟩

lemma *insert-not-empty [simp]*: $\text{insert } a \ A \neq \{\}$
 ⟨proof⟩

lemmas *empty-not-insert* = *insert-not-empty* [*symmetric, standard*]
declare *empty-not-insert* [*simp*]

lemma *insert-absorb*: $a \in A ==> \text{insert } a \ A = A$
 — [*simp*] causes recursive calls when there are nested inserts
 — with *quadratic* running time
 ⟨proof⟩

lemma *insert-absorb2 [simp]*: $\text{insert } x \ (\text{insert } x \ A) = \text{insert } x \ A$
 ⟨proof⟩

lemma *insert-commute*: $\text{insert } x \ (\text{insert } y \ A) = \text{insert } y \ (\text{insert } x \ A)$
 ⟨proof⟩

lemma *insert-subset [simp]*: $(\text{insert } x \ A \subseteq B) = (x \in B \ \& \ A \subseteq B)$
 ⟨proof⟩

lemma *mk-disjoint-insert*: $a \in A \implies \exists B. A = \text{insert } a \ B \ \& \ a \notin B$
 — use new B rather than $A - \{a\}$ to avoid infinite unfolding
 $\langle \text{proof} \rangle$

lemma *insert-Collect*: $\text{insert } a \ (\text{Collect } P) = \{u. u \neq a \implies P \ u\}$
 $\langle \text{proof} \rangle$

lemma *UN-insert-distrib*: $u \in A \implies (\bigcup_{x \in A}. \text{insert } a \ (B \ x)) = \text{insert } a \ (\bigcup_{x \in A}. B \ x)$
 $\langle \text{proof} \rangle$

lemma *insert-inter-insert[simp]*: $\text{insert } a \ A \cap \text{insert } a \ B = \text{insert } a \ (A \cap B)$
 $\langle \text{proof} \rangle$

lemma *insert-disjoint[simp]*:
 $(\text{insert } a \ A \cap B = \{\}) = (a \notin B \wedge A \cap B = \{\})$
 $(\{\} = \text{insert } a \ A \cap B) = (a \notin B \wedge \{\} = A \cap B)$
 $\langle \text{proof} \rangle$

lemma *disjoint-insert[simp]*:
 $(B \cap \text{insert } a \ A = \{\}) = (a \notin B \wedge B \cap A = \{\})$
 $(\{\} = A \cap \text{insert } b \ B) = (b \notin A \wedge \{\} = A \cap B)$
 $\langle \text{proof} \rangle$

image.

lemma *image-empty [simp]*: $f' \{\} = \{\}$
 $\langle \text{proof} \rangle$

lemma *image-insert [simp]*: $f' \text{insert } a \ B = \text{insert } (f \ a) \ (f' B)$
 $\langle \text{proof} \rangle$

lemma *image-constant*: $x \in A \implies (\lambda x. c)' A = \{c\}$
 $\langle \text{proof} \rangle$

lemma *image-image*: $f' (g' A) = (\lambda x. f (g \ x))' A$
 $\langle \text{proof} \rangle$

lemma *insert-image [simp]*: $x \in A \implies \text{insert } (f \ x) \ (f' A) = f' A$
 $\langle \text{proof} \rangle$

lemma *image-is-empty [iff]*: $(f' A = \{\}) = (A = \{\})$
 $\langle \text{proof} \rangle$

lemma *image-Collect*: $f' \{x. P \ x\} = \{f \ x \mid x. P \ x\}$
 — NOT suitable as a default simp rule: the RHS isn't simpler than the LHS, with its implicit quantifier and conjunction. Also image enjoys better equational properties than does the RHS.

$\langle \text{proof} \rangle$

lemma *if-image-distrib* [simp]:

$(\lambda x. \text{if } P \ x \text{ then } f \ x \text{ else } g \ x) \text{ ` } S$
 $= (f \text{ ` } (S \cap \{x. P \ x\})) \cup (g \text{ ` } (S \cap \{x. \neg P \ x\}))$
 $\langle \text{proof} \rangle$

lemma *image-cong*: $M = N \implies (!x. x \in N \implies f \ x = g \ x) \implies f \text{ ` } M = g \text{ ` } N$
 $\langle \text{proof} \rangle$

range.

lemma *full-SetCompr-eq*: $\{u. \exists x. u = f \ x\} = \text{range } f$
 $\langle \text{proof} \rangle$

lemma *range-composition* [simp]: $\text{range } (\lambda x. f \ (g \ x)) = f \text{ ` } \text{range } g$
 $\langle \text{proof} \rangle$

Int

lemma *Int-absorb* [simp]: $A \cap A = A$
 $\langle \text{proof} \rangle$

lemma *Int-left-absorb*: $A \cap (A \cap B) = A \cap B$
 $\langle \text{proof} \rangle$

lemma *Int-commute*: $A \cap B = B \cap A$
 $\langle \text{proof} \rangle$

lemma *Int-left-commute*: $A \cap (B \cap C) = B \cap (A \cap C)$
 $\langle \text{proof} \rangle$

lemma *Int-assoc*: $(A \cap B) \cap C = A \cap (B \cap C)$
 $\langle \text{proof} \rangle$

lemmas *Int-ac* = *Int-assoc Int-left-absorb Int-commute Int-left-commute*
 — Intersection is an AC-operator

lemma *Int-absorb1*: $B \subseteq A \implies A \cap B = B$
 $\langle \text{proof} \rangle$

lemma *Int-absorb2*: $A \subseteq B \implies A \cap B = A$
 $\langle \text{proof} \rangle$

lemma *Int-empty-left* [simp]: $\{\} \cap B = \{\}$
 $\langle \text{proof} \rangle$

lemma *Int-empty-right* [simp]: $A \cap \{\} = \{\}$
 $\langle \text{proof} \rangle$

lemma *disjoint-eq-subset-Compl*: $(A \cap B = \{\}) = (A \subseteq -B)$
 $\langle \text{proof} \rangle$

lemma *disjoint-iff-not-equal*: $(A \cap B = \{\}) = (\forall x \in A. \forall y \in B. x \neq y)$
 $\langle \text{proof} \rangle$

lemma *Int-UNIV-left* [simp]: $UNIV \cap B = B$
 $\langle \text{proof} \rangle$

lemma *Int-UNIV-right* [simp]: $A \cap UNIV = A$
 $\langle \text{proof} \rangle$

lemma *Int-eq-Inter*: $A \cap B = \bigcap \{A, B\}$
 $\langle \text{proof} \rangle$

lemma *Int-Un-distrib*: $A \cap (B \cup C) = (A \cap B) \cup (A \cap C)$
 $\langle \text{proof} \rangle$

lemma *Int-Un-distrib2*: $(B \cup C) \cap A = (B \cap A) \cup (C \cap A)$
 $\langle \text{proof} \rangle$

lemma *Int-UNIV* [simp]: $(A \cap B = UNIV) = (A = UNIV \ \& \ B = UNIV)$
 $\langle \text{proof} \rangle$

lemma *Int-subset-iff* [simp]: $(C \subseteq A \cap B) = (C \subseteq A \ \& \ C \subseteq B)$
 $\langle \text{proof} \rangle$

lemma *Int-Collect*: $(x \in A \cap \{x. P \ x\}) = (x \in A \ \& \ P \ x)$
 $\langle \text{proof} \rangle$

Un.

lemma *Un-absorb* [simp]: $A \cup A = A$
 $\langle \text{proof} \rangle$

lemma *Un-left-absorb*: $A \cup (A \cup B) = A \cup B$
 $\langle \text{proof} \rangle$

lemma *Un-commute*: $A \cup B = B \cup A$
 $\langle \text{proof} \rangle$

lemma *Un-left-commute*: $A \cup (B \cup C) = B \cup (A \cup C)$
 $\langle \text{proof} \rangle$

lemma *Un-assoc*: $(A \cup B) \cup C = A \cup (B \cup C)$
 $\langle \text{proof} \rangle$

lemmas *Un-ac = Un-assoc Un-left-absorb Un-commute Un-left-commute*
 — Union is an AC-operator

lemma *Un-absorb1*: $A \subseteq B \implies A \cup B = B$
 $\langle proof \rangle$

lemma *Un-absorb2*: $B \subseteq A \implies A \cup B = A$
 $\langle proof \rangle$

lemma *Un-empty-left [simp]*: $\{\} \cup B = B$
 $\langle proof \rangle$

lemma *Un-empty-right [simp]*: $A \cup \{\} = A$
 $\langle proof \rangle$

lemma *Un-UNIV-left [simp]*: $UNIV \cup B = UNIV$
 $\langle proof \rangle$

lemma *Un-UNIV-right [simp]*: $A \cup UNIV = UNIV$
 $\langle proof \rangle$

lemma *Un-eq-Union*: $A \cup B = \bigcup \{A, B\}$
 $\langle proof \rangle$

lemma *Un-insert-left [simp]*: $(insert\ a\ B) \cup C = insert\ a\ (B \cup C)$
 $\langle proof \rangle$

lemma *Un-insert-right [simp]*: $A \cup (insert\ a\ B) = insert\ a\ (A \cup B)$
 $\langle proof \rangle$

lemma *Int-insert-left*:
 $(insert\ a\ B) \cap C = (if\ a \in C\ then\ insert\ a\ (B \cap C)\ else\ B \cap C)$
 $\langle proof \rangle$

lemma *Int-insert-right*:
 $A \cap (insert\ a\ B) = (if\ a \in A\ then\ insert\ a\ (A \cap B)\ else\ A \cap B)$
 $\langle proof \rangle$

lemma *Un-Int-distrib*: $A \cup (B \cap C) = (A \cup B) \cap (A \cup C)$
 $\langle proof \rangle$

lemma *Un-Int-distrib2*: $(B \cap C) \cup A = (B \cup A) \cap (C \cup A)$
 $\langle proof \rangle$

lemma *Un-Int-crazy*:
 $(A \cap B) \cup (B \cap C) \cup (C \cap A) = (A \cup B) \cap (B \cup C) \cap (C \cup A)$
 $\langle proof \rangle$

lemma *subset-Un-eq*: $(A \subseteq B) = (A \cup B = B)$
 $\langle proof \rangle$

lemma *Un-empty [iff]*: $(A \cup B = \{\}) = (A = \{\} \ \&\ B = \{\})$

$\langle proof \rangle$

lemma *Un-subset-iff* [simp]: $(A \cup B \subseteq C) = (A \subseteq C \ \& \ B \subseteq C)$
 $\langle proof \rangle$

lemma *Un-Diff-Int*: $(A - B) \cup (A \cap B) = A$
 $\langle proof \rangle$

Set complement

lemma *Compl-disjoint* [simp]: $A \cap -A = \{\}$
 $\langle proof \rangle$

lemma *Compl-disjoint2* [simp]: $-A \cap A = \{\}$
 $\langle proof \rangle$

lemma *Compl-partition*: $A \cup -A = UNIV$
 $\langle proof \rangle$

lemma *Compl-partition2*: $-A \cup A = UNIV$
 $\langle proof \rangle$

lemma *double-complement* [simp]: $-(-A) = (A::'a \text{ set})$
 $\langle proof \rangle$

lemma *Compl-Un* [simp]: $-(A \cup B) = (-A) \cap (-B)$
 $\langle proof \rangle$

lemma *Compl-Int* [simp]: $-(A \cap B) = (-A) \cup (-B)$
 $\langle proof \rangle$

lemma *Compl-UN* [simp]: $-(\bigcup x \in A. B \ x) = (\bigcap x \in A. -B \ x)$
 $\langle proof \rangle$

lemma *Compl-INT* [simp]: $-(\bigcap x \in A. B \ x) = (\bigcup x \in A. -B \ x)$
 $\langle proof \rangle$

lemma *subset-Compl-self-eq*: $(A \subseteq -A) = (A = \{\})$
 $\langle proof \rangle$

lemma *Un-Int-assoc-eq*: $((A \cap B) \cup C = A \cap (B \cup C)) = (C \subseteq A)$
 — Halmos, Naive Set Theory, page 16.
 $\langle proof \rangle$

lemma *Compl-UNIV-eq* [simp]: $-UNIV = \{\}$
 $\langle proof \rangle$

lemma *Compl-empty-eq* [simp]: $-\{\} = UNIV$
 $\langle proof \rangle$

lemma *Compl-subset-Compl-iff* [iff]: $(-A \subseteq -B) = (B \subseteq A)$
 ⟨proof⟩

lemma *Compl-eq-Compl-iff* [iff]: $(-A = -B) = (A = (B::'a \text{ set}))$
 ⟨proof⟩

Union.

lemma *Union-empty* [simp]: $\text{Union}(\{\}) = \{\}$
 ⟨proof⟩

lemma *Union-UNIV* [simp]: $\text{Union } UNIV = UNIV$
 ⟨proof⟩

lemma *Union-insert* [simp]: $\text{Union } (\text{insert } a \ B) = a \cup \bigcup B$
 ⟨proof⟩

lemma *Union-Un-distrib* [simp]: $\bigcup (A \ \text{Un} \ B) = \bigcup A \cup \bigcup B$
 ⟨proof⟩

lemma *Union-Int-subset*: $\bigcup (A \cap B) \subseteq \bigcup A \cap \bigcup B$
 ⟨proof⟩

lemma *Union-empty-conv* [iff]: $(\bigcup A = \{\}) = (\forall x \in A. \ x = \{\})$
 ⟨proof⟩

lemma *empty-Union-conv* [iff]: $(\{\} = \bigcup A) = (\forall x \in A. \ x = \{\})$
 ⟨proof⟩

lemma *Union-disjoint*: $(\bigcup C \cap A = \{\}) = (\forall B \in C. \ B \cap A = \{\})$
 ⟨proof⟩

Inter.

lemma *Inter-empty* [simp]: $\bigcap \{\} = UNIV$
 ⟨proof⟩

lemma *Inter-UNIV* [simp]: $\bigcap UNIV = \{\}$
 ⟨proof⟩

lemma *Inter-insert* [simp]: $\bigcap (\text{insert } a \ B) = a \cap \bigcap B$
 ⟨proof⟩

lemma *Inter-Un-subset*: $\bigcap A \cup \bigcap B \subseteq \bigcap (A \cap B)$
 ⟨proof⟩

lemma *Inter-Un-distrib*: $\bigcap (A \cup B) = \bigcap A \cap \bigcap B$
 ⟨proof⟩

lemma *Inter-UNIV-conv* [iff]:

$$\begin{aligned}
(\bigcap A = UNIV) &= (\forall x \in A. x = UNIV) \\
(UNIV = \bigcap A) &= (\forall x \in A. x = UNIV) \\
\langle proof \rangle
\end{aligned}$$

UN and *INT*.

Basic identities:

lemma *UN-empty* [simp]: $(\bigcup x \in \{\}. B\ x) = \{\}$
 $\langle proof \rangle$

lemma *UN-empty2* [simp]: $(\bigcup x \in A. \{\}) = \{\}$
 $\langle proof \rangle$

lemma *UN-singleton* [simp]: $(\bigcup x \in A. \{x\}) = A$
 $\langle proof \rangle$

lemma *UN-absorb*: $k \in I \implies A\ k \cup (\bigcup i \in I. A\ i) = (\bigcup i \in I. A\ i)$
 $\langle proof \rangle$

lemma *INT-empty* [simp]: $(\bigcap x \in \{\}. B\ x) = UNIV$
 $\langle proof \rangle$

lemma *INT-absorb*: $k \in I \implies A\ k \cap (\bigcap i \in I. A\ i) = (\bigcap i \in I. A\ i)$
 $\langle proof \rangle$

lemma *UN-insert* [simp]: $(\bigcup x \in insert\ a\ A. B\ x) = B\ a \cup UNION\ A\ B$
 $\langle proof \rangle$

lemma *UN-Un*: $(\bigcup i \in A \cup B. M\ i) = (\bigcup i \in A. M\ i) \cup (\bigcup i \in B. M\ i)$
 $\langle proof \rangle$

lemma *UN-UN-flatten*: $(\bigcup x \in (\bigcup y \in A. B\ y). C\ x) = (\bigcup y \in A. \bigcup x \in B\ y. C\ x)$
 $\langle proof \rangle$

lemma *UN-subset-iff*: $((\bigcup i \in I. A\ i) \subseteq B) = (\forall i \in I. A\ i \subseteq B)$
 $\langle proof \rangle$

lemma *INT-subset-iff*: $(B \subseteq (\bigcap i \in I. A\ i)) = (\forall i \in I. B \subseteq A\ i)$
 $\langle proof \rangle$

lemma *INT-insert* [simp]: $(\bigcap x \in insert\ a\ A. B\ x) = B\ a \cap INTER\ A\ B$
 $\langle proof \rangle$

lemma *INT-Un*: $(\bigcap i \in A \cup B. M\ i) = (\bigcap i \in A. M\ i) \cap (\bigcap i \in B. M\ i)$
 $\langle proof \rangle$

lemma *INT-insert-distrib*:

$$u \in A \implies (\bigcap x \in A. insert\ a\ (B\ x)) = insert\ a\ (\bigcap x \in A. B\ x)$$

$\langle proof \rangle$

lemma *Union-image-eq [simp]*: $\bigcup (B' A) = (\bigcup x \in A. B x)$
 ⟨proof⟩

lemma *image-Union*: $f' \bigcup S = (\bigcup x \in S. f' x)$
 ⟨proof⟩

lemma *Inter-image-eq [simp]*: $\bigcap (B' A) = (\bigcap x \in A. B x)$
 ⟨proof⟩

lemma *UN-constant [simp]*: $(\bigcup y \in A. c) = (\text{if } A = \{\} \text{ then } \{\} \text{ else } c)$
 ⟨proof⟩

lemma *INT-constant [simp]*: $(\bigcap y \in A. c) = (\text{if } A = \{\} \text{ then } UNIV \text{ else } c)$
 ⟨proof⟩

lemma *UN-eq*: $(\bigcup x \in A. B x) = \bigcup (\{Y. \exists x \in A. Y = B x\})$
 ⟨proof⟩

lemma *INT-eq*: $(\bigcap x \in A. B x) = \bigcap (\{Y. \exists x \in A. Y = B x\})$
 — Look: it has an *existential* quantifier
 ⟨proof⟩

lemma *UNION-empty-conv[iff]*:
 $(\{\} = (\bigcup x:A. B x)) = (\forall x \in A. B x = \{\})$
 $((\bigcup x:A. B x) = \{\}) = (\forall x \in A. B x = \{\})$
 ⟨proof⟩

lemma *INTER-UNIV-conv[iff]*:
 $(UNIV = (\bigcap x:A. B x)) = (\forall x \in A. B x = UNIV)$
 $((\bigcap x:A. B x) = UNIV) = (\forall x \in A. B x = UNIV)$
 ⟨proof⟩

Distributive laws:

lemma *Int-Union*: $A \cap \bigcup B = (\bigcup C \in B. A \cap C)$
 ⟨proof⟩

lemma *Int-Union2*: $\bigcup B \cap A = (\bigcup C \in B. C \cap A)$
 ⟨proof⟩

lemma *Un-Union-image*: $(\bigcup x \in C. A x \cup B x) = \bigcup (A' C) \cup \bigcup (B' C)$
 — Devlin, Fundamentals of Contemporary Set Theory, page 12, exercise 5:
 — Union of a family of unions
 ⟨proof⟩

lemma *UN-Un-distrib*: $(\bigcup i \in I. A i \cup B i) = (\bigcup i \in I. A i) \cup (\bigcup i \in I. B i)$
 — Equivalent version
 ⟨proof⟩

lemma *Un-Inter*: $A \cup \bigcap B = (\bigcap C \in B. A \cup C)$

$\langle proof \rangle$

lemma *Int-Inter-image*: $(\bigcap_{x \in C}. A \ x \cap B \ x) = \bigcap (A' C) \cap \bigcap (B' C)$
 $\langle proof \rangle$

lemma *INT-Int-distrib*: $(\bigcap_{i \in I}. A \ i \cap B \ i) = (\bigcap_{i \in I}. A \ i) \cap (\bigcap_{i \in I}. B \ i)$
 — Equivalent version
 $\langle proof \rangle$

lemma *Int-UN-distrib*: $B \cap (\bigcup_{i \in I}. A \ i) = (\bigcup_{i \in I}. B \cap A \ i)$
 — Halmos, Naive Set Theory, page 35.
 $\langle proof \rangle$

lemma *Un-INT-distrib*: $B \cup (\bigcap_{i \in I}. A \ i) = (\bigcap_{i \in I}. B \cup A \ i)$
 $\langle proof \rangle$

lemma *Int-UN-distrib2*: $(\bigcup_{i \in I}. A \ i) \cap (\bigcup_{j \in J}. B \ j) = (\bigcup_{i \in I}. \bigcup_{j \in J}. A \ i \cap B \ j)$
 $\langle proof \rangle$

lemma *Un-INT-distrib2*: $(\bigcap_{i \in I}. A \ i) \cup (\bigcap_{j \in J}. B \ j) = (\bigcap_{i \in I}. \bigcap_{j \in J}. A \ i \cup B \ j)$
 $\langle proof \rangle$

Bounded quantifiers.

The following are not added to the default simpset because (a) they duplicate the body and (b) there are no similar rules for *Int*.

lemma *ball-Un*: $(\forall x \in A \cup B. P \ x) = ((\forall x \in A. P \ x) \ \& \ (\forall x \in B. P \ x))$
 $\langle proof \rangle$

lemma *bex-Un*: $(\exists x \in A \cup B. P \ x) = ((\exists x \in A. P \ x) \ | \ (\exists x \in B. P \ x))$
 $\langle proof \rangle$

lemma *ball-UN*: $(\forall z \in \text{UNION } A \ B. P \ z) = (\forall x \in A. \forall z \in B \ x. P \ z)$
 $\langle proof \rangle$

lemma *bex-UN*: $(\exists z \in \text{UNION } A \ B. P \ z) = (\exists x \in A. \exists z \in B \ x. P \ z)$
 $\langle proof \rangle$

Set difference.

lemma *Diff-eq*: $A - B = A \cap (-B)$
 $\langle proof \rangle$

lemma *Diff-eq-empty-iff* [simp]: $(A - B = \{\}) = (A \subseteq B)$
 $\langle proof \rangle$

lemma *Diff-cancel* [simp]: $A - A = \{\}$
 $\langle proof \rangle$

lemma *Diff-idemp* [simp]: $(A - B) - B = A - (B::'a \text{ set})$
 ⟨proof⟩

lemma *Diff-triv*: $A \cap B = \{\} \implies A - B = A$
 ⟨proof⟩

lemma *empty-Diff* [simp]: $\{\} - A = \{\}$
 ⟨proof⟩

lemma *Diff-empty* [simp]: $A - \{\} = A$
 ⟨proof⟩

lemma *Diff-UNIV* [simp]: $A - \text{UNIV} = \{\}$
 ⟨proof⟩

lemma *Diff-insert0* [simp]: $x \notin A \implies A - \text{insert } x \ B = A - B$
 ⟨proof⟩

lemma *Diff-insert*: $A - \text{insert } a \ B = A - B - \{a\}$
 — NOT SUITABLE FOR REWRITING since $\{a\} == \text{insert } a \ 0$
 ⟨proof⟩

lemma *Diff-insert2*: $A - \text{insert } a \ B = A - \{a\} - B$
 — NOT SUITABLE FOR REWRITING since $\{a\} == \text{insert } a \ 0$
 ⟨proof⟩

lemma *insert-Diff-if*: $\text{insert } x \ A - B = (\text{if } x \in B \text{ then } A - B \text{ else } \text{insert } x \ (A - B))$
 ⟨proof⟩

lemma *insert-Diff1* [simp]: $x \in B \implies \text{insert } x \ A - B = A - B$
 ⟨proof⟩

lemma *insert-Diff-single*[simp]: $\text{insert } a \ (A - \{a\}) = \text{insert } a \ A$
 ⟨proof⟩

lemma *insert-Diff*: $a \in A \implies \text{insert } a \ (A - \{a\}) = A$
 ⟨proof⟩

lemma *Diff-insert-absorb*: $x \notin A \implies (\text{insert } x \ A) - \{x\} = A$
 ⟨proof⟩

lemma *Diff-disjoint* [simp]: $A \cap (B - A) = \{\}$
 ⟨proof⟩

lemma *Diff-partition*: $A \subseteq B \implies A \cup (B - A) = B$
 ⟨proof⟩

lemma *double-diff*: $A \subseteq B \implies B \subseteq C \implies B - (C - A) = A$
 $\langle \text{proof} \rangle$

lemma *Un-Diff-cancel* [*simp*]: $A \cup (B - A) = A \cup B$
 $\langle \text{proof} \rangle$

lemma *Un-Diff-cancel2* [*simp*]: $(B - A) \cup A = B \cup A$
 $\langle \text{proof} \rangle$

lemma *Diff-Un*: $A - (B \cup C) = (A - B) \cap (A - C)$
 $\langle \text{proof} \rangle$

lemma *Diff-Int*: $A - (B \cap C) = (A - B) \cup (A - C)$
 $\langle \text{proof} \rangle$

lemma *Un-Diff*: $(A \cup B) - C = (A - C) \cup (B - C)$
 $\langle \text{proof} \rangle$

lemma *Int-Diff*: $(A \cap B) - C = A \cap (B - C)$
 $\langle \text{proof} \rangle$

lemma *Diff-Int-distrib*: $C \cap (A - B) = (C \cap A) - (C \cap B)$
 $\langle \text{proof} \rangle$

lemma *Diff-Int-distrib2*: $(A - B) \cap C = (A \cap C) - (B \cap C)$
 $\langle \text{proof} \rangle$

lemma *Diff-Compl* [*simp*]: $A - (- B) = A \cap B$
 $\langle \text{proof} \rangle$

lemma *Compl-Diff-eq* [*simp*]: $-(A - B) = -A \cup B$
 $\langle \text{proof} \rangle$

Quantification over type *bool*.

lemma *all-bool-eq*: $(\forall b::\text{bool}. P b) = (P \text{ True} \ \& \ P \text{ False})$
 $\langle \text{proof} \rangle$

lemma *bool-induct*: $P \text{ True} \implies P \text{ False} \implies P x$
 $\langle \text{proof} \rangle$

lemma *ex-bool-eq*: $(\exists b::\text{bool}. P b) = (P \text{ True} \mid P \text{ False})$
 $\langle \text{proof} \rangle$

lemma *Un-eq-UN*: $A \cup B = (\bigcup b. \text{if } b \text{ then } A \text{ else } B)$
 $\langle \text{proof} \rangle$

lemma *UN-bool-eq*: $(\bigcup b::\text{bool}. A b) = (A \text{ True} \cup A \text{ False})$
 $\langle \text{proof} \rangle$

lemma *INT-bool-eq*: $(\bigcap b::\text{bool}. A \ b) = (A \ \text{True} \cap A \ \text{False})$
 $\langle \text{proof} \rangle$

Pow

lemma *Pow-empty* [simp]: $\text{Pow} \ \{\} = \{\{\}\}$
 $\langle \text{proof} \rangle$

lemma *Pow-insert*: $\text{Pow} \ (\text{insert } a \ A) = \text{Pow} \ A \cup (\text{insert } a \ ' \ \text{Pow} \ A)$
 $\langle \text{proof} \rangle$

lemma *Pow-Compl*: $\text{Pow} \ (\neg \ A) = \{-B \mid B. A \in \text{Pow} \ B\}$
 $\langle \text{proof} \rangle$

lemma *Pow-UNIV* [simp]: $\text{Pow} \ \text{UNIV} = \text{UNIV}$
 $\langle \text{proof} \rangle$

lemma *Un-Pow-subset*: $\text{Pow} \ A \cup \text{Pow} \ B \subseteq \text{Pow} \ (A \cup B)$
 $\langle \text{proof} \rangle$

lemma *UN-Pow-subset*: $(\bigcup x \in A. \text{Pow} \ (B \ x)) \subseteq \text{Pow} \ (\bigcup x \in A. B \ x)$
 $\langle \text{proof} \rangle$

lemma *subset-Pow-Union*: $A \subseteq \text{Pow} \ (\bigcup A)$
 $\langle \text{proof} \rangle$

lemma *Union-Pow-eq* [simp]: $\bigcup (\text{Pow} \ A) = A$
 $\langle \text{proof} \rangle$

lemma *Pow-Int-eq* [simp]: $\text{Pow} \ (A \cap B) = \text{Pow} \ A \cap \text{Pow} \ B$
 $\langle \text{proof} \rangle$

lemma *Pow-INT-eq*: $\text{Pow} \ (\bigcap x \in A. B \ x) = (\bigcap x \in A. \text{Pow} \ (B \ x))$
 $\langle \text{proof} \rangle$

Miscellany.

lemma *set-eq-subset*: $(A = B) = (A \subseteq B \ \& \ B \subseteq A)$
 $\langle \text{proof} \rangle$

lemma *subset-iff*: $(A \subseteq B) = (\forall t. t \in A \longrightarrow t \in B)$
 $\langle \text{proof} \rangle$

lemma *subset-iff-psubset-eq*: $(A \subseteq B) = ((A \subset B) \mid (A = B))$
 $\langle \text{proof} \rangle$

lemma *all-not-in-conv* [iff]: $(\forall x. x \notin A) = (A = \{\})$
 $\langle \text{proof} \rangle$

lemma *ex-in-conv*: $(\exists x. x \in A) = (A \neq \{\})$

$\langle proof \rangle$

lemma *distinct-lemma*: $f\ x \neq f\ y \implies x \neq y$

$\langle proof \rangle$

Miniscoping: pushing in quantifiers and big Unions and Intersections.

lemma *UN-simps* [simp]:

$!!a\ B\ C. (UN\ x:C. insert\ a\ (B\ x)) = (if\ C=\{\} \ then\ \{\} \ else\ insert\ a\ (UN\ x:C. B\ x))$
 $!!A\ B\ C. (UN\ x:C. A\ x\ Un\ B) = ((if\ C=\{\} \ then\ \{\} \ else\ (UN\ x:C. A\ x)\ Un\ B))$
 $!!A\ B\ C. (UN\ x:C. A\ Un\ B\ x) = ((if\ C=\{\} \ then\ \{\} \ else\ A\ Un\ (UN\ x:C. B\ x)))$
 $!!A\ B\ C. (UN\ x:C. A\ x\ Int\ B) = ((UN\ x:C. A\ x)\ Int\ B)$
 $!!A\ B\ C. (UN\ x:C. A\ Int\ B\ x) = (A\ Int\ (UN\ x:C. B\ x))$
 $!!A\ B\ C. (UN\ x:C. A\ x - B) = ((UN\ x:C. A\ x) - B)$
 $!!A\ B\ C. (UN\ x:C. A - B\ x) = (A - (INT\ x:C. B\ x))$
 $!!A\ B. (UN\ x: Union\ A. B\ x) = (UN\ y:A. UN\ x:y. B\ x)$
 $!!A\ B\ C. (UN\ z: UNION\ A\ B. C\ z) = (UN\ x:A. UN\ z: B(x). C\ z)$
 $!!A\ B\ f. (UN\ x:f'A. B\ x) = (UN\ a:A. B\ (f\ a))$
 $\langle proof \rangle$

lemma *INT-simps* [simp]:

$!!A\ B\ C. (INT\ x:C. A\ x\ Int\ B) = (if\ C=\{\} \ then\ UNIV\ else\ (INT\ x:C. A\ x)\ Int\ B)$
 $!!A\ B\ C. (INT\ x:C. A\ Int\ B\ x) = (if\ C=\{\} \ then\ UNIV\ else\ A\ Int\ (INT\ x:C. B\ x))$
 $!!A\ B\ C. (INT\ x:C. A\ x - B) = (if\ C=\{\} \ then\ UNIV\ else\ (INT\ x:C. A\ x) - B)$
 $!!A\ B\ C. (INT\ x:C. A - B\ x) = (if\ C=\{\} \ then\ UNIV\ else\ A - (UN\ x:C. B\ x))$
 $!!a\ B\ C. (INT\ x:C. insert\ a\ (B\ x)) = insert\ a\ (INT\ x:C. B\ x)$
 $!!A\ B\ C. (INT\ x:C. A\ x\ Un\ B) = ((INT\ x:C. A\ x)\ Un\ B)$
 $!!A\ B\ C. (INT\ x:C. A\ Un\ B\ x) = (A\ Un\ (INT\ x:C. B\ x))$
 $!!A\ B. (INT\ x: Union\ A. B\ x) = (INT\ y:A. INT\ x:y. B\ x)$
 $!!A\ B\ C. (INT\ z: UNION\ A\ B. C\ z) = (INT\ x:A. INT\ z: B(x). C\ z)$
 $!!A\ B\ f. (INT\ x:f'A. B\ x) = (INT\ a:A. B\ (f\ a))$
 $\langle proof \rangle$

lemma *ball-simps* [simp]:

$!!A\ P\ Q. (ALL\ x:A. P\ x \mid Q) = ((ALL\ x:A. P\ x) \mid Q)$
 $!!A\ P\ Q. (ALL\ x:A. P \mid Q\ x) = (P \mid (ALL\ x:A. Q\ x))$
 $!!A\ P\ Q. (ALL\ x:A. P \dashv\rightarrow Q\ x) = (P \dashv\rightarrow (ALL\ x:A. Q\ x))$
 $!!A\ P\ Q. (ALL\ x:A. P\ x \dashv\rightarrow Q) = ((EX\ x:A. P\ x) \dashv\rightarrow Q)$
 $!!P. (ALL\ x:\{\}. P\ x) = True$
 $!!P. (ALL\ x:UNIV. P\ x) = (ALL\ x. P\ x)$
 $!!a\ B\ P. (ALL\ x:insert\ a\ B. P\ x) = (P\ a \ \& \ (ALL\ x:B. P\ x))$
 $!!A\ P. (ALL\ x:Union\ A. P\ x) = (ALL\ y:A. ALL\ x:y. P\ x)$
 $!!A\ B\ P. (ALL\ x: UNION\ A\ B. P\ x) = (ALL\ a:A. ALL\ x: B\ a. P\ x)$

$!!P Q. (ALL x:Collect Q. P x) = (ALL x. Q x \multimap P x)$
 $!!A P f. (ALL x:f'A. P x) = (ALL x:A. P (f x))$
 $!!A P. (\sim(ALL x:A. P x)) = (EX x:A. \sim P x)$
 $\langle proof \rangle$

lemma *bex-simps* [simp]:

$!!A P Q. (EX x:A. P x \& Q) = ((EX x:A. P x) \& Q)$
 $!!A P Q. (EX x:A. P \& Q x) = (P \& (EX x:A. Q x))$
 $!!P. (EX x:\{\}. P x) = False$
 $!!P. (EX x:UNIV. P x) = (EX x. P x)$
 $!!a B P. (EX x:insert a B. P x) = (P(a) \mid (EX x:B. P x))$
 $!!A P. (EX x:Union A. P x) = (EX y:A. EX x:y. P x)$
 $!!A B P. (EX x: UNION A B. P x) = (EX a:A. EX x:B a. P x)$
 $!!P Q. (EX x:Collect Q. P x) = (EX x. Q x \& P x)$
 $!!A P f. (EX x:f'A. P x) = (EX x:A. P (f x))$
 $!!A P. (\sim(EX x:A. P x)) = (ALL x:A. \sim P x)$
 $\langle proof \rangle$

lemma *ball-conj-distrib*:

$(ALL x:A. P x \& Q x) = ((ALL x:A. P x) \& (ALL x:A. Q x))$
 $\langle proof \rangle$

lemma *bex-disj-distrib*:

$(EX x:A. P x \mid Q x) = ((EX x:A. P x) \mid (EX x:A. Q x))$
 $\langle proof \rangle$

Maxiscoping: pulling out big Unions and Intersections.

lemma *UN-extend-simps*:

$!!a B C. insert a (UN x:C. B x) = (if C=\{\} then \{a\} else (UN x:C. insert a (B x)))$
 $!!A B C. (UN x:C. A x) Un B = (if C=\{\} then B else (UN x:C. A x Un B))$
 $!!A B C. A Un (UN x:C. B x) = (if C=\{\} then A else (UN x:C. A Un B x))$
 $!!A B C. ((UN x:C. A x) Int B) = (UN x:C. A x Int B)$
 $!!A B C. (A Int (UN x:C. B x)) = (UN x:C. A Int B x)$
 $!!A B C. ((UN x:C. A x) - B) = (UN x:C. A x - B)$
 $!!A B C. (A - (INT x:C. B x)) = (UN x:C. A - B x)$
 $!!A B. (UN y:A. UN x:y. B x) = (UN x: Union A. B x)$
 $!!A B C. (UN x:A. UN z: B(x). C z) = (UN z: UNION A B. C z)$
 $!!A B f. (UN a:A. B (f a)) = (UN x:f'A. B x)$
 $\langle proof \rangle$

lemma *INT-extend-simps*:

$!!A B C. (INT x:C. A x) Int B = (if C=\{\} then B else (INT x:C. A x Int B))$
 $!!A B C. A Int (INT x:C. B x) = (if C=\{\} then A else (INT x:C. A Int B x))$
 $!!A B C. (INT x:C. A x) - B = (if C=\{\} then UNIV-B else (INT x:C. A x - B))$
 $!!A B C. A - (INT x:C. B x) = (if C=\{\} then A else (INT x:C. A - B x))$
 $!!a B C. insert a (INT x:C. B x) = (INT x:C. insert a (B x))$
 $!!A B C. ((INT x:C. A x) Un B) = (INT x:C. A x Un B)$

$!!A \ B \ C. \ A \ \text{Un} \ (\text{INT } x:C. \ B \ x) = (\text{INT } x:C. \ A \ \text{Un} \ B \ x)$
 $!!A \ B. \ (\text{INT } y:A. \ \text{INT } x:y. \ B \ x) = (\text{INT } x: \text{Union } A. \ B \ x)$
 $!!A \ B \ C. \ (\text{INT } x:A. \ \text{INT } z: \ B(x). \ C \ z) = (\text{INT } z: \ \text{UNION } A \ B. \ C \ z)$
 $!!A \ B \ f. \ (\text{INT } a:A. \ B \ (f \ a)) = (\text{INT } x:f'A. \ B \ x)$
 $\langle \text{proof} \rangle$

5.5.3 Monotonicity of various operations

lemma *image-mono*: $A \subseteq B \implies f'A \subseteq f'B$
 $\langle \text{proof} \rangle$

lemma *Pow-mono*: $A \subseteq B \implies \text{Pow } A \subseteq \text{Pow } B$
 $\langle \text{proof} \rangle$

lemma *Union-mono*: $A \subseteq B \implies \bigcup A \subseteq \bigcup B$
 $\langle \text{proof} \rangle$

lemma *Inter-anti-mono*: $B \subseteq A \implies \bigcap A \subseteq \bigcap B$
 $\langle \text{proof} \rangle$

lemma *UN-mono*:
 $A \subseteq B \implies (!!x. \ x \in A \implies f \ x \subseteq g \ x) \implies$
 $(\bigcup_{x \in A}. \ f \ x) \subseteq (\bigcup_{x \in B}. \ g \ x)$
 $\langle \text{proof} \rangle$

lemma *INT-anti-mono*:
 $B \subseteq A \implies (!!x. \ x \in A \implies f \ x \subseteq g \ x) \implies$
 $(\bigcap_{x \in A}. \ f \ x) \subseteq (\bigcap_{x \in A}. \ g \ x)$
 — The last inclusion is POSITIVE!
 $\langle \text{proof} \rangle$

lemma *insert-mono*: $C \subseteq D \implies \text{insert } a \ C \subseteq \text{insert } a \ D$
 $\langle \text{proof} \rangle$

lemma *Un-mono*: $A \subseteq C \implies B \subseteq D \implies A \cup B \subseteq C \cup D$
 $\langle \text{proof} \rangle$

lemma *Int-mono*: $A \subseteq C \implies B \subseteq D \implies A \cap B \subseteq C \cap D$
 $\langle \text{proof} \rangle$

lemma *Diff-mono*: $A \subseteq C \implies D \subseteq B \implies A - B \subseteq C - D$
 $\langle \text{proof} \rangle$

lemma *Compl-anti-mono*: $A \subseteq B \implies -B \subseteq -A$
 $\langle \text{proof} \rangle$

Monotonicity of implications.

lemma *in-mono*: $A \subseteq B \implies x \in A \dashrightarrow x \in B$
 $\langle \text{proof} \rangle$

lemma *conj-mono*: $P1 \multimap Q1 \implies P2 \multimap Q2 \implies (P1 \ \& \ P2) \multimap (Q1 \ \& \ Q2)$
 ⟨proof⟩

lemma *disj-mono*: $P1 \multimap Q1 \implies P2 \multimap Q2 \implies (P1 \mid P2) \multimap (Q1 \mid Q2)$
 ⟨proof⟩

lemma *imp-mono*: $Q1 \multimap P1 \implies P2 \multimap Q2 \implies (P1 \multimap P2) \multimap (Q1 \multimap Q2)$
 ⟨proof⟩

lemma *imp-refl*: $P \multimap P$ ⟨proof⟩

lemma *ex-mono*: $(!!x. P \ x \multimap Q \ x) \implies (EX \ x. P \ x) \multimap (EX \ x. Q \ x)$
 ⟨proof⟩

lemma *all-mono*: $(!!x. P \ x \multimap Q \ x) \implies (ALL \ x. P \ x) \multimap (ALL \ x. Q \ x)$
 ⟨proof⟩

lemma *Collect-mono*: $(!!x. P \ x \multimap Q \ x) \implies Collect \ P \subseteq Collect \ Q$
 ⟨proof⟩

lemma *Int-Collect-mono*:
 $A \subseteq B \implies (!!x. x \in A \implies P \ x \multimap Q \ x) \implies A \cap Collect \ P \subseteq B \cap Collect \ Q$
 ⟨proof⟩

lemmas *basic-monos* =
subset-refl imp-refl disj-mono conj-mono
ex-mono Collect-mono in-mono

lemma *eq-to-mono*: $a = b \implies c = d \implies b \multimap d \implies a \multimap c$
 ⟨proof⟩

lemma *eq-to-mono2*: $a = b \implies c = d \implies \sim b \multimap \sim d \implies \sim a \multimap \sim c$
 ⟨proof⟩

lemma *Least-mono*:
 $mono \ (f::'a::order \Rightarrow \ 'b::order) \implies EX \ x:S. \ ALL \ y:S. \ x \leq y$
 $\implies (LEAST \ y. \ y : f \ 'S) = f \ (LEAST \ x. \ x : S)$
 — Courtesy of Stephan Merz
 ⟨proof⟩

5.6 Inverse image of a function

constdefs
vimage :: $('a \Rightarrow 'b) \Rightarrow 'b \ set \Rightarrow 'a \ set$ (infixr -‘ 90)

$$f -' B == \{x. f x : B\}$$

5.6.1 Basic rules

lemma *vimage-eq* [*simp*]: $(a : f -' B) = (f a : B)$
 $\langle proof \rangle$

lemma *vimage-singleton-eq*: $(a : f -' \{b\}) = (f a = b)$
 $\langle proof \rangle$

lemma *vimageI* [*intro*]: $f a = b ==> b:B ==> a : f -' B$
 $\langle proof \rangle$

lemma *vimageI2*: $f a : A ==> a : f -' A$
 $\langle proof \rangle$

lemma *vimageE* [*elim!*]: $a: f -' B ==> (!x. f a = x ==> x:B ==> P) ==> P$
 $\langle proof \rangle$

lemma *vimageD*: $a : f -' A ==> f a : A$
 $\langle proof \rangle$

5.6.2 Equations

lemma *vimage-empty* [*simp*]: $f -' \{\} = \{\}$
 $\langle proof \rangle$

lemma *vimage-Compl*: $f -' (-A) = -(f -' A)$
 $\langle proof \rangle$

lemma *vimage-Un* [*simp*]: $f -' (A \text{ Un } B) = (f -' A) \text{ Un } (f -' B)$
 $\langle proof \rangle$

lemma *vimage-Int* [*simp*]: $f -' (A \text{ Int } B) = (f -' A) \text{ Int } (f -' B)$
 $\langle proof \rangle$

lemma *vimage-Union*: $f -' (\text{Union } A) = (\text{UN } X:A. f -' X)$
 $\langle proof \rangle$

lemma *vimage-UN*: $f -' (\text{UN } x:A. B x) = (\text{UN } x:A. f -' B x)$
 $\langle proof \rangle$

lemma *vimage-INT*: $f -' (\text{INT } x:A. B x) = (\text{INT } x:A. f -' B x)$
 $\langle proof \rangle$

lemma *vimage-Collect-eq* [*simp*]: $f -' \text{Collect } P = \{y. P (f y)\}$
 $\langle proof \rangle$

lemma *vimage-Collect*: $(!x. P (f x) = Q x) ==> f -' (\text{Collect } P) = \text{Collect } Q$

$\langle proof \rangle$

lemma *image-insert*: $f - ' (insert\ a\ B) = (f - '\{a\})\ Un\ (f - 'B)$
 — NOT suitable for rewriting because of the recurrence of $\{a\}$.
 $\langle proof \rangle$

lemma *image-Diff*: $f - ' (A - B) = (f - 'A) - (f - 'B)$
 $\langle proof \rangle$

lemma *image-UNIV* [simp]: $f - ' UNIV = UNIV$
 $\langle proof \rangle$

lemma *image-eq-UN*: $f - 'B = (UN\ y:\ B.\ f - '\{y\})$
 — NOT suitable for rewriting
 $\langle proof \rangle$

lemma *image-mono*: $A \subseteq B ==> f - 'A \subseteq f - 'B$
 — monotonicity
 $\langle proof \rangle$

5.7 Getting the Contents of a Singleton Set

constdefs

contents :: 'a set ==> 'a
contents X == THE x. X = {x}

lemma *contents-eq* [simp]: *contents* {x} = x
 $\langle proof \rangle$

5.8 Transitivity rules for calculational reasoning

lemma *set-rev-mp*: $x:A ==> A \subseteq B ==> x:B$
 $\langle proof \rangle$

lemma *set-mp*: $A \subseteq B ==> x:A ==> x:B$
 $\langle proof \rangle$

lemma *ord-le-eq-trans*: $a <= b ==> b = c ==> a <= c$
 $\langle proof \rangle$

lemma *ord-eq-le-trans*: $a = b ==> b <= c ==> a <= c$
 $\langle proof \rangle$

lemma *ord-less-eq-trans*: $a < b ==> b = c ==> a < c$
 $\langle proof \rangle$

lemma *ord-eq-less-trans*: $a = b ==> b < c ==> a < c$
 $\langle proof \rangle$

lemma *order-less-subst2*: $(a::'a::order) < b ==> f\ b < (c::'c::order) ==>$

$(!!x y. x < y ==> f x < f y) ==> f a < c$
 $\langle proof \rangle$

lemma *order-less-subst1*: $(a::'a::order) < f b ==> (b::'b::order) < c ==>$
 $(!!x y. x < y ==> f x < f y) ==> a < f c$
 $\langle proof \rangle$

lemma *order-le-less-subst2*: $(a::'a::order) <= b ==> f b < (c::'c::order) ==>$
 $(!!x y. x <= y ==> f x <= f y) ==> f a < c$
 $\langle proof \rangle$

lemma *order-le-less-subst1*: $(a::'a::order) <= f b ==> (b::'b::order) < c ==>$
 $(!!x y. x < y ==> f x < f y) ==> a < f c$
 $\langle proof \rangle$

lemma *order-less-le-subst2*: $(a::'a::order) < b ==> f b <= (c::'c::order) ==>$
 $(!!x y. x < y ==> f x < f y) ==> f a < c$
 $\langle proof \rangle$

lemma *order-less-le-subst1*: $(a::'a::order) < f b ==> (b::'b::order) <= c ==>$
 $(!!x y. x <= y ==> f x <= f y) ==> a < f c$
 $\langle proof \rangle$

lemma *order-subst1*: $(a::'a::order) <= f b ==> (b::'b::order) <= c ==>$
 $(!!x y. x <= y ==> f x <= f y) ==> a <= f c$
 $\langle proof \rangle$

lemma *order-subst2*: $(a::'a::order) <= b ==> f b <= (c::'c::order) ==>$
 $(!!x y. x <= y ==> f x <= f y) ==> f a <= c$
 $\langle proof \rangle$

lemma *ord-le-eq-subst*: $a <= b ==> f b = c ==>$
 $(!!x y. x <= y ==> f x <= f y) ==> f a <= c$
 $\langle proof \rangle$

lemma *ord-eq-le-subst*: $a = f b ==> b <= c ==>$
 $(!!x y. x <= y ==> f x <= f y) ==> a <= f c$
 $\langle proof \rangle$

lemma *ord-less-eq-subst*: $a < b ==> f b = c ==>$
 $(!!x y. x < y ==> f x < f y) ==> f a < c$
 $\langle proof \rangle$

lemma *ord-eq-less-subst*: $a = f b ==> b < c ==>$
 $(!!x y. x < y ==> f x < f y) ==> a < f c$
 $\langle proof \rangle$

Note that this list of rules is in reverse order of priorities.

lemmas *basic-trans-rules* [trans] =

```

order-less-subst2
order-less-subst1
order-le-less-subst2
order-le-less-subst1
order-less-le-subst2
order-less-le-subst1
order-subst2
order-subst1
ord-le-eq-subst
ord-eq-le-subst
ord-less-eq-subst
ord-eq-less-subst
forw-subst
back-subst
rev-mp
mp
set-rev-mp
set-mp
order-neq-le-trans
order-le-neq-trans
order-less-trans
order-less-asym'
order-le-less-trans
order-less-le-trans
order-trans
order-antisym
ord-le-eq-trans
ord-eq-le-trans
ord-less-eq-trans
ord-eq-less-trans
trans

```

end

6 Typedef: HOL type definitions

```

theory Typedef
imports Set
uses (Tools/typedef-package.ML)
begin

locale type-definition =
  fixes Rep and Abs and A
  assumes Rep: Rep  $x \in A$ 
    and Rep-inverse: Abs (Rep  $x$ ) =  $x$ 
    and Abs-inverse:  $y \in A \implies$  Rep (Abs  $y$ ) =  $y$ 
  — This will be axiomatized for each typedef!

```

lemma (in *type-definition*) *Rep-inject*:
 $(Rep\ x = Rep\ y) = (x = y)$
 ⟨*proof*⟩

lemma (in *type-definition*) *Abs-inject*:
 assumes $x: x \in A$ and $y: y \in A$
 shows $(Abs\ x = Abs\ y) = (x = y)$
 ⟨*proof*⟩

lemma (in *type-definition*) *Rep-cases* [*cases set*]:
 assumes $y: y \in A$
 and $hyp: !!x. y = Rep\ x ==> P$
 shows P
 ⟨*proof*⟩

lemma (in *type-definition*) *Abs-cases* [*cases type*]:
 assumes $r: !!y. x = Abs\ y ==> y \in A ==> P$
 shows P
 ⟨*proof*⟩

lemma (in *type-definition*) *Rep-induct* [*induct set*]:
 assumes $y: y \in A$
 and $hyp: !!x. P\ (Rep\ x)$
 shows $P\ y$
 ⟨*proof*⟩

lemma (in *type-definition*) *Abs-induct* [*induct type*]:
 assumes $r: !!y. y \in A ==> P\ (Abs\ y)$
 shows $P\ x$
 ⟨*proof*⟩

⟨*ML*⟩

end

theory *Fun*
imports *Typedef*
begin

instance *set* :: (*type*) *order*
 ⟨*proof*⟩

constdefs
 $fun_upd :: ('a ==> 'b) ==> 'a ==> 'b ==> ('a ==> 'b)$
 $fun_upd\ f\ a\ b == \% x. if\ x=a\ then\ b\ else\ f\ x$

nonterminals

updbinds updbind

syntax

-updbind :: [*'a*, *'a*] => *updbind* ((2- :=/ -))
 :: *updbind* => *updbinds* (-)
-updbinds:: [*updbind*, *updbinds*] => *updbinds* (-,/ -)
-Update :: [*'a*, *updbinds*] => *'a* (-/'((-)') [1000,0] 900)

translations

-Update f (-updbinds b bs) == *-Update (-Update f b) bs*
f(x:=y) == *fun-upd f x y*

constdefs

override-on :: (*'a* => *'b*) => (*'a* => *'b*) => *'a set* => (*'a* => *'b*)
override-on f g A == %*a*. if *a* : A then *g a* else *f a*

id :: *'a* => *'a*
id == %*x*. *x*

comp :: [*'b* => *'c*, *'a* => *'b*, *'a*] => *'c* (**infixl** o 55)
f o g == %*x*. *f(g(x))*

compatibility

lemmas *o-def* = *comp-def*

syntax (*xsymbols*)

comp :: [*'b* => *'c*, *'a* => *'b*, *'a*] => *'c* (**infixl** o 55)

syntax (*HTML output*)

comp :: [*'b* => *'c*, *'a* => *'b*, *'a*] => *'c* (**infixl** o 55)

constdefs

inj-on :: [*'a* => *'b*, *'a set*] => *bool*
inj-on f A == ! *x:A*. ! *y:A*. *f(x)=f(y) --> x=y*

A common special case: functions injective over the entire domain type.

syntax *inj* :: (*'a* => *'b*) => *bool*

translations

inj f == *inj-on f UNIV*

constdefs

surj :: (*'a* => *'b*) => *bool*
surj f == ! *y*. ? *x*. *y=f(x)*

bij :: (*'a* => *'b*) => *bool*
bij f == *inj f* & *surj f*

As a simplification rule, it replaces all function equalities by first-order equal-

ities.

lemma *expand-fun-eq*: $(f = g) = (! x. f(x)=g(x))$
 $\langle proof \rangle$

lemma *apply-inverse*:
 $[| f(x)=u; !!x. P(x) ==> g(f(x)) = x; P(x) |] ==> x=g(u)$
 $\langle proof \rangle$

The Identity Function: *id*

lemma *id-apply* [simp]: $id\ x = x$
 $\langle proof \rangle$

lemma *inj-on-id*[simp]: $inj-on\ id\ A$
 $\langle proof \rangle$

lemma *inj-on-id2*[simp]: $inj-on\ (\%x. x)\ A$
 $\langle proof \rangle$

lemma *surj-id*[simp]: $surj\ id$
 $\langle proof \rangle$

lemma *bij-id*[simp]: $bij\ id$
 $\langle proof \rangle$

6.1 The Composition Operator: $f \circ g$

lemma *o-apply* [simp]: $(f \circ g)\ x = f\ (g\ x)$
 $\langle proof \rangle$

lemma *o-assoc*: $f \circ (g \circ h) = f \circ g \circ h$
 $\langle proof \rangle$

lemma *id-o* [simp]: $id \circ g = g$
 $\langle proof \rangle$

lemma *o-id* [simp]: $f \circ id = f$
 $\langle proof \rangle$

lemma *image-compose*: $(f \circ g)^{\circ} r = f^{\circ}(g^{\circ} r)$
 $\langle proof \rangle$

lemma *image-eq-UN*: $f^{\circ} A = (UN\ x:A. \{f\ x\})$
 $\langle proof \rangle$

lemma *UN-o*: $UNION\ A\ (g \circ f) = UNION\ (f^{\circ} A)\ g$
 $\langle proof \rangle$

6.2 The Injectivity Predicate, *inj*

NB: *inj* now just translates to *inj-on*

For Proofs in *Tools/datatype-rep-proofs*

lemma *datatype-injI*:

$(!! x. \text{ALL } y. f(x) = f(y) \longrightarrow x=y) \implies \text{inj}(f)$
 $\langle \text{proof} \rangle$

theorem *range-ex1-eq*: $\text{inj } f \implies b : \text{range } f = (EX! x. b = f x)$
 $\langle \text{proof} \rangle$

lemma *injD*: $[\text{inj}(f); f(x) = f(y)] \implies x=y$
 $\langle \text{proof} \rangle$

lemma *inj-eq*: $\text{inj}(f) \implies (f(x) = f(y)) = (x=y)$
 $\langle \text{proof} \rangle$

6.3 The Predicate *inj-on*: Injectivity On A Restricted Domain

lemma *inj-onI*:

$(!! x y. [\text{x:A}; \text{y:A}; f(x) = f(y)] \implies x=y) \implies \text{inj-on } f A$
 $\langle \text{proof} \rangle$

lemma *inj-on-inverseI*: $(!!x. x:A \implies g(f(x)) = x) \implies \text{inj-on } f A$
 $\langle \text{proof} \rangle$

lemma *inj-onD*: $[\text{inj-on } f A; f(x)=f(y); \text{x:A}; \text{y:A}] \implies x=y$
 $\langle \text{proof} \rangle$

lemma *inj-on-iff*: $[\text{inj-on } f A; \text{x:A}; \text{y:A}] \implies (f(x)=f(y)) = (x=y)$
 $\langle \text{proof} \rangle$

lemma *comp-inj-on*:

$[\text{inj-on } f A; \text{inj-on } g (f^{\circ} A)] \implies \text{inj-on } (g \circ f) A$
 $\langle \text{proof} \rangle$

lemma *inj-on-imageI*: $\text{inj-on } (g \circ f) A \implies \text{inj-on } g (f^{\circ} A)$
 $\langle \text{proof} \rangle$

lemma *inj-on-image-iff*: $[\text{ALL } x:A. \text{ALL } y:A. (g(f x) = g(f y)) = (g x = g y); \text{inj-on } f A] \implies \text{inj-on } g (f^{\circ} A) = \text{inj-on } g A$
 $\langle \text{proof} \rangle$

lemma *inj-on-contrad*: $[\text{inj-on } f A; \sim x=y; \text{x:A}; \text{y:A}] \implies \sim f(x)=f(y)$
 $\langle \text{proof} \rangle$

lemma *inj-singleton*: $\text{inj } (\%s. \{s\})$
 $\langle \text{proof} \rangle$

lemma *inj-on-empty*[*iff*]: $\text{inj-on } f \ \{\}$
 $\langle \text{proof} \rangle$

lemma *subset-inj-on*: $[\mid \text{inj-on } f \ B; \ A \leq B \mid] \implies \text{inj-on } f \ A$
 $\langle \text{proof} \rangle$

lemma *inj-on-Un*:
 $\text{inj-on } f \ (A \cup B) =$
 $(\text{inj-on } f \ A \ \& \ \text{inj-on } f \ B \ \& \ f'(A-B) \ \text{Int } f'(B-A) = \{\})$
 $\langle \text{proof} \rangle$

lemma *inj-on-insert*[*iff*]:
 $\text{inj-on } f \ (\text{insert } a \ A) = (\text{inj-on } f \ A \ \& \ f \ a \sim: f'(A-\{a\}))$
 $\langle \text{proof} \rangle$

lemma *inj-on-diff*: $\text{inj-on } f \ A \implies \text{inj-on } f \ (A-B)$
 $\langle \text{proof} \rangle$

6.4 The Predicate *surj*: Surjectivity

lemma *surjI*: $(!! \ x. \ g(f \ x) = x) \implies \text{surj } g$
 $\langle \text{proof} \rangle$

lemma *surj-range*: $\text{surj } f \implies \text{range } f = \text{UNIV}$
 $\langle \text{proof} \rangle$

lemma *surjD*: $\text{surj } f \implies \exists x. \ y = f \ x$
 $\langle \text{proof} \rangle$

lemma *surjE*: $\text{surj } f \implies (!x. \ y = f \ x \implies C) \implies C$
 $\langle \text{proof} \rangle$

lemma *comp-surj*: $[\mid \text{surj } f; \ \text{surj } g \mid] \implies \text{surj } (g \circ f)$
 $\langle \text{proof} \rangle$

6.5 The Predicate *bij*: Bijectivity

lemma *bijI*: $[\mid \text{inj } f; \ \text{surj } f \mid] \implies \text{bij } f$
 $\langle \text{proof} \rangle$

lemma *bij-is-inj*: $\text{bij } f \implies \text{inj } f$
 $\langle \text{proof} \rangle$

lemma *bij-is-surj*: $\text{bij } f \implies \text{surj } f$
 $\langle \text{proof} \rangle$

6.6 Facts About the Identity Function

We seem to need both the *id* forms and the $\lambda x. x$ forms. The latter can arise by rewriting, while *id* may be used explicitly.

lemma *image-ident* [simp]: $(\%x. x) \text{ ` } Y = Y$
 ⟨proof⟩

lemma *image-id* [simp]: *id* ` $Y = Y$
 ⟨proof⟩

lemma *vimage-ident* [simp]: $(\%x. x) \text{ -` } Y = Y$
 ⟨proof⟩

lemma *vimage-id* [simp]: *id* -` $A = A$
 ⟨proof⟩

lemma *vimage-image-eq*: $f \text{ -` } (f \text{ ` } A) = \{y. \text{ EX } x:A. f\ x = f\ y\}$
 ⟨proof⟩

lemma *image-vimage-subset*: $f \text{ ` } (f \text{ -` } A) \leq A$
 ⟨proof⟩

lemma *image-vimage-eq* [simp]: $f \text{ ` } (f \text{ -` } A) = A \text{ Int range } f$
 ⟨proof⟩

lemma *surj-image-vimage-eq*: $\text{surj } f \implies f \text{ ` } (f \text{ -` } A) = A$
 ⟨proof⟩

lemma *inj-vimage-image-eq*: $\text{inj } f \implies f \text{ -` } (f \text{ ` } A) = A$
 ⟨proof⟩

lemma *vimage-subsetD*: $\text{surj } f \implies f \text{ -` } B \leq A \implies B \leq f \text{ ` } A$
 ⟨proof⟩

lemma *vimage-subsetI*: $\text{inj } f \implies B \leq f \text{ ` } A \implies f \text{ -` } B \leq A$
 ⟨proof⟩

lemma *vimage-subset-eq*: $\text{bij } f \implies (f \text{ -` } B \leq A) = (B \leq f \text{ ` } A)$
 ⟨proof⟩

lemma *image-Int-subset*: $f \text{ ` } (A \text{ Int } B) \leq f \text{ ` } A \text{ Int } f \text{ ` } B$
 ⟨proof⟩

lemma *image-diff-subset*: $f \text{ ` } A - f \text{ ` } B \leq f \text{ ` } (A - B)$
 ⟨proof⟩

lemma *inj-on-image-Int*:
 $[\text{inj-on } f\ C; A \leq C; B \leq C] \implies f \text{ ` } (A \text{ Int } B) = f \text{ ` } A \text{ Int } f \text{ ` } B$
 ⟨proof⟩

lemma *inj-on-image-set-diff*:

$\llbracket \text{inj-on } f \ C; \ A \leq C; \ B \leq C \rrbracket \implies f'(A-B) = f'A - f'B$
 $\langle \text{proof} \rangle$

lemma *image-Int*: $\text{inj } f \implies f'(A \text{ Int } B) = f'A \text{ Int } f'B$
 $\langle \text{proof} \rangle$

lemma *image-set-diff*: $\text{inj } f \implies f'(A-B) = f'A - f'B$
 $\langle \text{proof} \rangle$

lemma *inj-image-mem-iff*: $\text{inj } f \implies (f \ a : f'A) = (a : A)$
 $\langle \text{proof} \rangle$

lemma *inj-image-subset-iff*: $\text{inj } f \implies (f'A \leq f'B) = (A \leq B)$
 $\langle \text{proof} \rangle$

lemma *inj-image-eq-iff*: $\text{inj } f \implies (f'A = f'B) = (A = B)$
 $\langle \text{proof} \rangle$

lemma *image-UN*: $(f' \ (\text{UNION } A \ B)) = (\text{UN } x:A. (f' \ (B \ x)))$
 $\langle \text{proof} \rangle$

lemma *image-INT*:

$\llbracket \text{inj-on } f \ C; \ \text{ALL } x:A. \ B \ x \leq C; \ j:A \rrbracket$
 $\implies f' \ (\text{INTER } A \ B) = (\text{INT } x:A. f' \ B \ x)$
 $\langle \text{proof} \rangle$

lemma *bij-image-INT*: $\text{bij } f \implies f' \ (\text{INTER } A \ B) = (\text{INT } x:A. f' \ B \ x)$
 $\langle \text{proof} \rangle$

lemma *surj-Compl-image-subset*: $\text{surj } f \implies -(f'A) \leq f'(-A)$
 $\langle \text{proof} \rangle$

lemma *inj-image-Compl-subset*: $\text{inj } f \implies f'(-A) \leq -(f'A)$
 $\langle \text{proof} \rangle$

lemma *bij-image-Compl-eq*: $\text{bij } f \implies f'(-A) = -(f'A)$
 $\langle \text{proof} \rangle$

6.7 Function Updating

lemma *fun-upd-idem-iff*: $(f(x:=y) = f) = (f \ x = y)$
 $\langle \text{proof} \rangle$

lemmas *fun-upd-idem* = *fun-upd-idem-iff* [THEN iffD2, standard]

lemmas *fun-upd-triv* = *refl* [*THEN fun-upd-idem*]
declare *fun-upd-triv* [*iff*]

lemma *fun-upd-apply* [*simp*]: $(f(x:=y))z = (\text{if } z=x \text{ then } y \text{ else } f\ z)$
 $\langle \text{proof} \rangle$

lemma *fun-upd-same*: $(f(x:=y))\ x = y$
 $\langle \text{proof} \rangle$

lemma *fun-upd-other*: $z \sim x \implies (f(x:=y))\ z = f\ z$
 $\langle \text{proof} \rangle$

lemma *fun-upd-upd* [*simp*]: $f(x:=y, x:=z) = f(x:=z)$
 $\langle \text{proof} \rangle$

lemma *fun-upd-twist*: $a \sim c \implies (m(a:=b))(c:=d) = (m(c:=d))(a:=b)$
 $\langle \text{proof} \rangle$

lemma *inj-on-fun-updI*: $\llbracket \text{inj-on } f\ A; y \notin f'A \rrbracket \implies \text{inj-on } (f(x:=y))\ A$
 $\langle \text{proof} \rangle$

lemma *fun-upd-image*:
 $f(x:=y)\ 'A = (\text{if } x \in A \text{ then insert } y\ (f\ ' (A - \{x\})) \text{ else } f\ ' A)$
 $\langle \text{proof} \rangle$

6.8 override-on

lemma *override-on-emptyset*[*simp*]: *override-on* *f g* $\{\}$ = *f*
 $\langle \text{proof} \rangle$

lemma *override-on-apply-notin*[*simp*]: $a \sim A \implies (\text{override-on } f\ g\ A)\ a = f\ a$
 $\langle \text{proof} \rangle$

lemma *override-on-apply-in*[*simp*]: $a : A \implies (\text{override-on } f\ g\ A)\ a = g\ a$
 $\langle \text{proof} \rangle$

6.9 swap

constdefs
 $\text{swap} :: ['a, 'a, 'a \Rightarrow 'b] \Rightarrow ('a \Rightarrow 'b)$
 $\text{swap } a\ b\ f == f(a := f\ b, b := f\ a)$

lemma *swap-self*: *swap* *a a f* = *f*
 $\langle \text{proof} \rangle$

lemma *swap-commute*: *swap* *a b f* = *swap* *b a f*
 $\langle \text{proof} \rangle$

lemma *swap-nilpotent* [simp]: $\text{swap } a \ b \ (\text{swap } a \ b \ f) = f$
 <proof>

lemma *inj-on-imp-inj-on-swap*:
 $[[\text{inj-on } f \ A; \ a \in A; \ b \in A]] \implies \text{inj-on } (\text{swap } a \ b \ f) \ A$
 <proof>

lemma *inj-on-swap-iff* [simp]:
assumes $A: a \in A \ b \in A$ **shows** $\text{inj-on } (\text{swap } a \ b \ f) \ A = \text{inj-on } f \ A$
 <proof>

lemma *surj-imp-surj-swap*: $\text{surj } f \implies \text{surj } (\text{swap } a \ b \ f)$
 <proof>

lemma *surj-swap-iff* [simp]: $\text{surj } (\text{swap } a \ b \ f) = \text{surj } f$
 <proof>

lemma *bij-swap-iff*: $\text{bij } (\text{swap } a \ b \ f) = \text{bij } f$
 <proof>

The ML section includes some compatibility bindings and a simproc for function updates, in addition to the usual ML-bindings of theorems.

<ML>

end

7 Product-Type: Cartesian products

theory *Product-Type*
imports *Fun*
uses (*Tools/split-rule.ML*)
begin

7.1 Unit

typedef *unit* = { *True* }
 <proof>

constdefs
 $\text{Unity} :: \text{unit} \quad (')()$
 $() == \text{Abs-unit } \text{True}$

lemma *unit-eq*: $u = ()$
 <proof>

Simplification procedure for *unit-eq*. Cannot use this rule directly — it loops!

$\langle ML \rangle$

lemma *unit-all-eq1*: ($!!x::unit. PROP P x$) == *PROP P* ()
 $\langle proof \rangle$

lemma *unit-all-eq2*: ($!!x::unit. PROP P$) == *PROP P*
 $\langle proof \rangle$

lemma *unit-induct* [*induct type: unit*]: *P* () ==> *P x*
 $\langle proof \rangle$

This rewrite counters the effect of *unit-eq-proc* on $\%u::unit. f u$, replacing it by *f* rather than by $\%u. f$ ().

lemma *unit-abs-eta-conv* [*simp*]: ($\%u::unit. f$ ()) = *f*
 $\langle proof \rangle$

7.2 Pairs

7.2.1 Type definition

constdefs
Pair-Rep :: [*a*, *b*] => [*a*, *b*] => *bool*
Pair-Rep == ($\%a b. \%x y. x=a \ \& \ y=b$)

global

typedef (*Prod*)
 (*a*, *b*) * (**infixr** 20)
 = {*f. EX a b. f = Pair-Rep (a::'a) (b::'b)*}
 $\langle proof \rangle$

syntax (*xsymbols*)
 * :: [*type*, *type*] => *type* ((- × / -) [21, 20] 20)
syntax (*HTML output*)
 * :: [*type*, *type*] => *type* ((- × / -) [21, 20] 20)

local

7.2.2 Abstract constants and syntax

global

consts
fst :: *a* * *b* => *a*
snd :: *a* * *b* => *b*
split :: [[*a*, *b*] => *c*, *a* * *b*] => *c*
curry :: [*a* * *b* => *c*, *a*, *b*] => *c*
prod-fun :: [*a* => *b*, *c* => *d*, *a* * *c*] => *b* * *d*
Pair :: [*a*, *b*] => *a* * *b*
Sigma :: [*a set*, *a* => *b set*] => (*a* * *b*) *set*

local

Patterns – extends pre-defined type *pttrn* used in abstractions.

nonterminals

tuple-args patterns

syntax

```

-tuple      :: 'a => tuple-args => 'a * 'b      ((1'(-, / -'))
-tuple-arg  :: 'a => tuple-args                  (-)
-tuple-args :: 'a => tuple-args => tuple-args    (-, / -)
-pattern    :: [pttrn, patterns] => pttrn       ('(-, / -'))
            :: pttrn => patterns                  (-)
-patterns   :: [pttrn, patterns] => patterns    (-, / -)
@Sigma      :: [pttrn, 'a set, 'b set] => ('a * 'b) set ((3SIGMA -:- / -) 10)
@Times      :: ['a set, 'a => 'b set] => ('a * 'b) set (infixr <*> 80)

```

translations

```

(x, y)      == Pair x y
-tuple x (-tuple-args y z) == -tuple x (-tuple-arg (-tuple y z))
%(x,y,zs).b == split(%x (y,zs).b)
%(x,y).b    == split(%x y. b)
-abs (Pair x y) t => %(x,y).t

```

```

SIGMA x:A. B => Sigma A (%x. B)
A <*> B      => Sigma A (-K B)

```

$\langle ML \rangle$

Deleted x-symbol and html support using Σ (Sigma) because of the danger of confusion with Sum.

syntax (*xsymbols*)

```

@Times :: ['a set, 'a => 'b set] => ('a * 'b) set (- × - [81, 80] 80)

```

syntax (*HTML output*)

```

@Times :: ['a set, 'a => 'b set] => ('a * 'b) set (- × - [81, 80] 80)

```

$\langle ML \rangle$

7.2.3 Definitions**defs**

```

Pair-def:   Pair a b == Abs-Prod(Pair-Rep a b)
fst-def:    fst p == THE a. EX b. p = (a, b)
snd-def:    snd p == THE b. EX a. p = (a, b)
split-def:  split == (%c p. c (fst p) (snd p))

```

curry-def: $\text{curry} == (\%c\ x\ y.\ c\ (x,y))$
prod-fun-def: $\text{prod-fun}\ f\ g == \text{split}(\%x\ y.(f(x), g(y)))$
Sigma-def: $\text{Sigma}\ A\ B == \text{UN}\ x:A.\ \text{UN}\ y:B(x).\ \{(x, y)\}$

7.2.4 Lemmas and proof tool setup

lemma *ProdI*: *Pair-Rep* *a b* : *Prod*
 ⟨*proof*⟩

lemma *Pair-Rep-inject*: *Pair-Rep* *a b* = *Pair-Rep* *a' b'* ==> *a* = *a'* & *b* = *b'*
 ⟨*proof*⟩

lemma *inj-on-Abs-Prod*: *inj-on* *Abs-Prod* *Prod*
 ⟨*proof*⟩

lemma *Pair-inject*:
 (*a*, *b*) = (*a'*, *b'*) ==> (*a* = *a'* ==> *b* = *b'* ==> *R*) ==> *R*
 ⟨*proof*⟩

lemma *Pair-eq [iff]*: ((*a*, *b*) = (*a'*, *b'*)) = (*a* = *a'* & *b* = *b'*)
 ⟨*proof*⟩

lemma *fst-conv [simp]*: *fst* (*a*, *b*) = *a*
 ⟨*proof*⟩

lemma *snd-conv [simp]*: *snd* (*a*, *b*) = *b*
 ⟨*proof*⟩

lemma *fst-eqD*: *fst* (*x*, *y*) = *a* ==> *x* = *a*
 ⟨*proof*⟩

lemma *snd-eqD*: *snd* (*x*, *y*) = *a* ==> *y* = *a*
 ⟨*proof*⟩

lemma *PairE-lemma*: *EX* *x y*. *p* = (*x*, *y*)
 ⟨*proof*⟩

lemma *PairE* [*cases type*: *]: (!!*x y*. *p* = (*x*, *y*) ==> *Q*) ==> *Q*
 ⟨*proof*⟩

⟨*ML*⟩

lemma *surjective-pairing*: *p* = (*fst* *p*, *snd* *p*)
 — Do not add as rewrite rule: invalidates some proofs in IMP
 ⟨*proof*⟩

lemmas *pair-collapse* = *surjective-pairing* [*symmetric*]
declare *pair-collapse* [*simp*]

lemma *surj-pair* [*simp*]: $EX\ x\ y.\ z = (x, y)$
 $\langle proof \rangle$

lemma *split-paired-all*: $(!!x.\ PROP\ P\ x) == (!!a\ b.\ PROP\ P\ (a, b))$
 $\langle proof \rangle$

lemmas *split-tupled-all* = *split-paired-all unit-all-eq2*

The rule *split-paired-all* does not work with the Simplifier because it also affects premises in congruence rules, where this can lead to premises of the form $!!a\ b.\ \dots = ?P(a, b)$ which cannot be solved by reflexivity.

$\langle ML \rangle$

lemma *split-paired-All* [*simp*]: $(ALL\ x.\ P\ x) = (ALL\ a\ b.\ P\ (a, b))$
 — [*iff*] is not a good idea because it makes *blast* loop
 $\langle proof \rangle$

lemma *curry-split* [*simp*]: $curry\ (split\ f) = f$
 $\langle proof \rangle$

lemma *split-curry* [*simp*]: $split\ (curry\ f) = f$
 $\langle proof \rangle$

lemma *curryI* [*intro!*]: $f\ (a, b) ==> curry\ f\ a\ b$
 $\langle proof \rangle$

lemma *curryD* [*dest!*]: $curry\ f\ a\ b ==> f\ (a, b)$
 $\langle proof \rangle$

lemma *curryE*: $[| curry\ f\ a\ b ; f\ (a, b) ==> Q |] ==> Q$
 $\langle proof \rangle$

lemma *curry-conv* [*simp*]: $curry\ f\ a\ b = f\ (a, b)$
 $\langle proof \rangle$

lemma *prod-induct* [*induct type: **]: $!!x.\ (!!a\ b.\ P\ (a, b)) ==> P\ x$
 $\langle proof \rangle$

lemma *split-paired-Ex* [*simp*]: $(EX\ x.\ P\ x) = (EX\ a\ b.\ P\ (a, b))$
 $\langle proof \rangle$

lemma *split-conv* [*simp*]: $split\ c\ (a, b) = c\ a\ b$
 $\langle proof \rangle$

lemmas *split* = *split-conv* — for backwards compatibility

lemmas *splitI* = *split-conv* [*THEN iffD2, standard*]

lemmas *splitD* = *split-conv* [*THEN iffD1, standard*]

lemma *split-Pair-apply*: $\text{split } (\%x\ y. f\ (x, y)) = f$
 — Subsumes the old *split-Pair* when f is the identity function.
 $\langle \text{proof} \rangle$

lemma *split-paired-The*: $(\text{THE } x. P\ x) = (\text{THE } (a, b). P\ (a, b))$
 — Can’t be added to simpset: loops!
 $\langle \text{proof} \rangle$

lemma *The-split*: $\text{The } (\text{split } P) = (\text{THE } xy. P\ (\text{fst } xy)\ (\text{snd } xy))$
 $\langle \text{proof} \rangle$

lemma *Pair-fst-snd-eq*: $!!s\ t. (s = t) = (\text{fst } s = \text{fst } t \ \& \ \text{snd } s = \text{snd } t)$
 $\langle \text{proof} \rangle$

lemma *prod-eqI* [*intro?*]: $\text{fst } p = \text{fst } q ==> \text{snd } p = \text{snd } q ==> p = q$
 $\langle \text{proof} \rangle$

lemma *split-weak-cong*: $p = q ==> \text{split } c\ p = \text{split } c\ q$
 — Prevents simplification of c : much faster
 $\langle \text{proof} \rangle$

lemma *split-eta*: $(\%(x, y). f\ (x, y)) = f$
 $\langle \text{proof} \rangle$

lemma *cond-split-eta*: $(!!x\ y. f\ x\ y = g\ (x, y)) ==> (\%(x, y). f\ x\ y) = g$
 $\langle \text{proof} \rangle$

Simplification procedure for *cond-split-eta*. Using *split-eta* as a rewrite rule is not general enough, and using *cond-split-eta* directly would render some existing proofs very inefficient; similarly for *split-beta*.

$\langle \text{ML} \rangle$

lemma *split-beta*: $(\%(x, y). P\ x\ y)\ z = P\ (\text{fst } z)\ (\text{snd } z)$
 $\langle \text{proof} \rangle$

lemma *split-split*: $R\ (\text{split } c\ p) = (\text{ALL } x\ y. p = (x, y) \longrightarrow R\ (c\ x\ y))$
 — For use with *split* and the Simplifier.
 $\langle \text{proof} \rangle$

split-split could be declared as [*split*] done after the Splitter has been speeded up significantly; precompute the constants involved and don’t do anything unless the current goal contains one of those constants.

lemma *split-split-asm*: $R\ (\text{split } c\ p) = (\sim(\text{EX } x\ y. p = (x, y) \ \& \ (\sim R\ (c\ x\ y))))$
 $\langle \text{proof} \rangle$

split used as a logical connective or set former.

These rules are for use with *blast*; could instead call *simp* using *split* as rewrite.

lemma *splitI2*: !!p. [| !!a b. p = (a, b) ==> c a b |] ==> *split* c p
 <proof>

lemma *splitI2'*: !!p. [| !!a b. (a, b) = p ==> c a b x |] ==> *split* c p x
 <proof>

lemma *splitE*: *split* c p ==> (!!x y. p = (x, y) ==> c x y ==> Q) ==> Q
 <proof>

lemma *splitE'*: *split* c p z ==> (!!x y. p = (x, y) ==> c x y z ==> Q) ==> Q
 <proof>

lemma *splitE2*:
 [| Q (*split* P z); !!x y. [| z = (x, y); Q (P x y) |] ==> R |] ==> R
 <proof>

lemma *splitD'*: *split* R (a,b) c ==> R a b c
 <proof>

lemma *mem-splitI*: z: c a b ==> z: *split* c (a, b)
 <proof>

lemma *mem-splitI2*: !!p. [| !!a b. p = (a, b) ==> z: c a b |] ==> z: *split* c p
 <proof>

lemma *mem-splitE*: [| z: *split* c p; !!x y. [| p = (x,y); z: c x y |] ==> Q |] ==> Q
 <proof>

declare *mem-splitI2* [intro!] *mem-splitI* [intro!] *splitI2'* [intro!] *splitI2* [intro!] *splitI* [intro!]

declare *mem-splitE* [elim!] *splitE'* [elim!] *splitE* [elim!]

<ML>

lemma *split-eta-SetCompr* [simp]: (%u. EX x y. u = (x, y) & P (x, y)) = P
 <proof>

lemma *split-eta-SetCompr2* [simp]: (%u. EX x y. u = (x, y) & P x y) = *split* P
 <proof>

lemma *split-part* [simp]: (%(a,b). P & Q a b) = (%ab. P & *split* Q ab)
 — Allows simplifications of nested splits in case of independent predicates.
 <proof>

lemma *split-comp-eq*:
 (%u. f (g (fst u)) (snd u)) = (*split* (%x. f (g x)))
 <proof>

lemma *The-split-eq* [simp]: (*THE* (x', y'). $x = x' \ \& \ y = y'$) = (x, y)
 ⟨proof⟩

lemma *injective-fst-snd*: $!!x \ y. [|fst \ x = fst \ y; \ snd \ x = snd \ y|] ==> x = y$
 ⟨proof⟩

prod-fun — action of the product functor upon functions.

lemma *prod-fun* [simp]: *prod-fun* $f \ g \ (a, b) = (f \ a, \ g \ b)$
 ⟨proof⟩

lemma *prod-fun-compose*: *prod-fun* ($f1 \ o \ f2$) ($g1 \ o \ g2$) = (*prod-fun* $f1 \ g1 \ o \ prod-fun \ f2 \ g2$)
 ⟨proof⟩

lemma *prod-fun-ident* [simp]: *prod-fun* ($\%x. \ x$) ($\%y. \ y$) = ($\%z. \ z$)
 ⟨proof⟩

lemma *prod-fun-imageI* [intro]: $(a, b) : r ==> (f \ a, \ g \ b) : prod-fun \ f \ g \ 'r$
 ⟨proof⟩

lemma *prod-fun-imageE* [elim!]:
 $[| \ c : (prod-fun \ f \ g) \ 'r; \ !!x \ y. [| \ c = (f(x), g(y)); \ (x, y) : r \ |] ==> P \ |] ==> P$
 ⟨proof⟩

constdefs

upd-fst :: ($'a ==> 'c$) ==> $'a * 'b ==> 'c * 'b$
upd-fst $f == prod-fun \ f \ id$

upd-snd :: ($'b ==> 'c$) ==> $'a * 'b ==> 'a * 'c$
upd-snd $f == prod-fun \ id \ f$

lemma *upd-fst-conv* [simp]: *upd-fst* $f \ (x, y) = (f \ x, y)$
 ⟨proof⟩

lemma *upd-snd-conv* [simp]: *upd-snd* $f \ (x, y) = (x, f \ y)$
 ⟨proof⟩

Disjoint union of a family of sets – Sigma.

lemma *SigmaI* [intro!]: $[| \ a : A; \ b : B(a) \ |] ==> (a, b) : Sigma \ A \ B$
 ⟨proof⟩

lemma *SigmaE* [elim!]:

$$\begin{aligned} & \llbracket c : \text{Sigma } A \ B; \\ & \quad !!x \ y. \llbracket x:A; \ y:B(x); \ c=(x,y) \rrbracket ==> P \\ & \rrbracket ==> P \end{aligned}$$
 — The general elimination rule.
 $\langle \text{proof} \rangle$

Elimination of $(a, b) \in A \times B$ – introduces no eigenvariables.

lemma *SigmaD1*: $(a, b) : \text{Sigma } A \ B ==> a : A$
 $\langle \text{proof} \rangle$

lemma *SigmaD2*: $(a, b) : \text{Sigma } A \ B ==> b : B \ a$
 $\langle \text{proof} \rangle$

lemma *SigmaE2*:

$$\begin{aligned} & \llbracket (a, b) : \text{Sigma } A \ B; \\ & \quad \llbracket a:A; \ b:B(a) \rrbracket ==> P \\ & \rrbracket ==> P \end{aligned}$$
 $\langle \text{proof} \rangle$

lemma *Sigma-cong*:

$$\begin{aligned} & \llbracket A = B; \ !x. x \in B ==> C \ x = D \ x \rrbracket \\ & ==> (\text{SIGMA } x: A. C \ x) = (\text{SIGMA } x: B. D \ x) \end{aligned}$$
 $\langle \text{proof} \rangle$

lemma *Sigma-mono*: $\llbracket A <= C; \ !x. x:A ==> B \ x <= D \ x \rrbracket ==> \text{Sigma } A \ B$
 $<= \text{Sigma } C \ D$
 $\langle \text{proof} \rangle$

lemma *Sigma-empty1* [simp]: $\text{Sigma } \{\} \ B = \{\}$
 $\langle \text{proof} \rangle$

lemma *Sigma-empty2* [simp]: $A <*> \{\} = \{\}$
 $\langle \text{proof} \rangle$

lemma *UNIV-Times-UNIV* [simp]: $\text{UNIV} <*> \text{UNIV} = \text{UNIV}$
 $\langle \text{proof} \rangle$

lemma *Compl-Times-UNIV1* [simp]: $\neg (\text{UNIV} <*> A) = \text{UNIV} <*> (\neg A)$
 $\langle \text{proof} \rangle$

lemma *Compl-Times-UNIV2* [simp]: $\neg (A <*> \text{UNIV}) = (\neg A) <*> \text{UNIV}$
 $\langle \text{proof} \rangle$

lemma *mem-Sigma-iff* [iff]: $((a,b) : \text{Sigma } A \ B) = (a:A \ \& \ b:B(a))$
 $\langle \text{proof} \rangle$

lemma *Times-subset-cancel2*: $x:C ==> (A <*> C <= B <*> C) = (A <= B)$
 $\langle \text{proof} \rangle$

lemma *Times-eq-cancel2*: $x:C \implies (A <*> C = B <*> C) = (A = B)$
 ⟨proof⟩

lemma *SetCompr-Sigma-eq*:
 $\text{Collect } (\text{split } (\%x\ y. P\ x \ \& \ Q\ x\ y)) = (\text{SIGMA } x:\text{Collect } P. \text{Collect } (Q\ x))$
 ⟨proof⟩

Complex rules for Sigma.

lemma *Collect-split [simp]*: $\{(a,b). P\ a \ \& \ Q\ b\} = \text{Collect } P <*> \text{Collect } Q$
 ⟨proof⟩

lemma *UN-Times-distrib*:
 $(\text{UN } (a,b):(A <*> B). E\ a <*> F\ b) = (\text{UNION } A\ E) <*> (\text{UNION } B\ F)$
 — Suggested by Pierre Chartier
 ⟨proof⟩

lemma *split-paired-Ball-Sigma [simp]*:
 $(\text{ALL } z:\text{Sigma } A\ B. P\ z) = (\text{ALL } x:A. \text{ALL } y:B\ x. P(x,y))$
 ⟨proof⟩

lemma *split-paired-Bex-Sigma [simp]*:
 $(\text{EX } z:\text{Sigma } A\ B. P\ z) = (\text{EX } x:A. \text{EX } y:B\ x. P(x,y))$
 ⟨proof⟩

lemma *Sigma-Un-distrib1*: $(\text{SIGMA } i:I\ \text{Un } J. C(i)) = (\text{SIGMA } i:I. C(i))\ \text{Un } (\text{SIGMA } j:J. C(j))$
 ⟨proof⟩

lemma *Sigma-Un-distrib2*: $(\text{SIGMA } i:I. A(i)\ \text{Un } B(i)) = (\text{SIGMA } i:I. A(i))\ \text{Un } (\text{SIGMA } i:I. B(i))$
 ⟨proof⟩

lemma *Sigma-Int-distrib1*: $(\text{SIGMA } i:I\ \text{Int } J. C(i)) = (\text{SIGMA } i:I. C(i))\ \text{Int } (\text{SIGMA } j:J. C(j))$
 ⟨proof⟩

lemma *Sigma-Int-distrib2*: $(\text{SIGMA } i:I. A(i)\ \text{Int } B(i)) = (\text{SIGMA } i:I. A(i))\ \text{Int } (\text{SIGMA } i:I. B(i))$
 ⟨proof⟩

lemma *Sigma-Diff-distrib1*: $(\text{SIGMA } i:I\ -\ J. C(i)) = (\text{SIGMA } i:I. C(i))\ -\ (\text{SIGMA } j:J. C(j))$
 ⟨proof⟩

lemma *Sigma-Diff-distrib2*: $(\text{SIGMA } i:I. A(i)\ -\ B(i)) = (\text{SIGMA } i:I. A(i))\ -\ (\text{SIGMA } i:I. B(i))$
 ⟨proof⟩

lemma *Sigma-Union*: $\text{Sigma } (\text{Union } X) B = (\text{UN } A:X. \text{Sigma } A B)$
 $\langle \text{proof} \rangle$

Non-dependent versions are needed to avoid the need for higher-order matching, especially when the rules are re-oriented.

lemma *Times-Un-distrib1*: $(A \text{ Un } B) <*> C = (A <*> C) \text{ Un } (B <*> C)$
 $\langle \text{proof} \rangle$

lemma *Times-Int-distrib1*: $(A \text{ Int } B) <*> C = (A <*> C) \text{ Int } (B <*> C)$
 $\langle \text{proof} \rangle$

lemma *Times-Diff-distrib1*: $(A - B) <*> C = (A <*> C) - (B <*> C)$
 $\langle \text{proof} \rangle$

lemma *pair-imageI* [intro]: $(a, b) : A \implies f a b : (\% (a, b). f a b) \text{ ‘ } A$
 $\langle \text{proof} \rangle$

Setup of internal *split-rule*.

constdefs

internal-split :: $('a \Rightarrow 'b \Rightarrow 'c) \Rightarrow 'a * 'b \Rightarrow 'c$
internal-split == *split*

lemma *internal-split-conv*: $\text{internal-split } c (a, b) = c a b$
 $\langle \text{proof} \rangle$

hide *const internal-split*

$\langle ML \rangle$

7.3 Code generator setup

types-code

*** ((- */ -))
attach (*term-of*) $\langle\langle$
 $\text{fun term-of-id-42 } f T g U (x, y) = \text{HOLogic.pair-const } T U \$ f x \$ g y;$
 $\rangle\rangle$
attach (*test*) $\langle\langle$
 $\text{fun gen-id-42 } aG bG i = (aG i, bG i);$
 $\rangle\rangle$

consts-code

Pair ((-,/ -))
fst (fst)
snd (snd)

$\langle ML \rangle$

end

8 FixedPoint: Fixed Points and the Knaster-Tarski Theorem

```
theory FixedPoint
imports Product-Type
begin
```

```
constdefs
  lfp :: ['a set  $\Rightarrow$  'a set]  $\Rightarrow$  'a set
  lfp(f) == Inter( $\{u. f(u) \subseteq u\}$ ) — least fixed point

  gfp :: ['a set  $\Rightarrow$  'a set]  $\Rightarrow$  'a set
  gfp(f) == Union( $\{u. u \subseteq f(u)\}$ )
```

8.1 Proof of Knaster-Tarski Theorem using *lfp*

lfp f is the least upper bound of the set $\{u. f u \subseteq u\}$

lemma *lfp-lowerbound*: $f(A) \subseteq A \Rightarrow lfp(f) \subseteq A$
 $\langle proof \rangle$

lemma *lfp-greatest*: $[\![\!| u. f(u) \subseteq u \Rightarrow A \subseteq u \!| \!]\!] \Rightarrow A \subseteq lfp(f)$
 $\langle proof \rangle$

lemma *lfp-lemma2*: $mono(f) \Rightarrow f(lfp(f)) \subseteq lfp(f)$
 $\langle proof \rangle$

lemma *lfp-lemma3*: $mono(f) \Rightarrow lfp(f) \subseteq f(lfp(f))$
 $\langle proof \rangle$

lemma *lfp-unfold*: $mono(f) \Rightarrow lfp(f) = f(lfp(f))$
 $\langle proof \rangle$

8.2 General induction rules for greatest fixed points

```
lemma lfp-induct:
  assumes lfp: a: lfp(f)
    and mono: mono(f)
    andindhyp:  $[\![ \!| x. f(lfp(f) \text{ Int } \{x. P(x)\}) \!| \!]\!] \Rightarrow P(x)$ 
  shows  $P(a)$ 
 $\langle proof \rangle$ 
```

Version of induction for binary relations

lemmas *lfp-induct2* = *lfp-induct* [*of* (*a,b*), *split-format* (*complete*)]

lemma *lfp-ordinal-induct*:

assumes *mono*: *mono f*
shows $\llbracket \text{!!}S. P\ S \implies P(f\ S); \text{!!}M. \text{!}S:M. P\ S \implies P(\text{Union}\ M) \rrbracket$
 $\implies P(\text{lfp}\ f)$
 $\langle \text{proof} \rangle$

Definition forms of *lfp-unfold* and *lfp-induct*, to control unfolding

lemma *def-lfp-unfold*: $\llbracket h == \text{lfp}(f); \text{mono}(f) \rrbracket \implies h = f(h)$
 $\langle \text{proof} \rangle$

lemma *def-lfp-induct*:
 $\llbracket A == \text{lfp}(f); \text{mono}(f); a:A;$
 $\text{!!}x. \llbracket x: f(A\ \text{Int}\ \{x. P(x)\}) \rrbracket \implies P(x)$
 $\rrbracket \implies P(a)$
 $\langle \text{proof} \rangle$

lemma *lfp-mono*: $\llbracket \text{!!}Z. f(Z) \subseteq g(Z) \rrbracket \implies \text{lfp}(f) \subseteq \text{lfp}(g)$
 $\langle \text{proof} \rangle$

8.3 Proof of Knaster-Tarski Theorem using *gfp*

gfp f is the greatest lower bound of the set $\{u. u \subseteq f\ u\}$

lemma *gfp-upperbound*: $\llbracket X \subseteq f(X) \rrbracket \implies X \subseteq \text{gfp}(f)$
 $\langle \text{proof} \rangle$

lemma *gfp-least*: $\llbracket \text{!!}u. u \subseteq f(u) \implies u \subseteq X \rrbracket \implies \text{gfp}(f) \subseteq X$
 $\langle \text{proof} \rangle$

lemma *gfp-lemma2*: $\text{mono}(f) \implies \text{gfp}(f) \subseteq f(\text{gfp}(f))$
 $\langle \text{proof} \rangle$

lemma *gfp-lemma3*: $\text{mono}(f) \implies f(\text{gfp}(f)) \subseteq \text{gfp}(f)$
 $\langle \text{proof} \rangle$

lemma *gfp-unfold*: $\text{mono}(f) \implies \text{gfp}(f) = f(\text{gfp}(f))$
 $\langle \text{proof} \rangle$

8.4 Coinduction rules for greatest fixed points

weak version

lemma *weak-coinduct*: $\llbracket a: X; X \subseteq f(X) \rrbracket \implies a: \text{gfp}(f)$
 $\langle \text{proof} \rangle$

lemma *weak-coinduct-image*: $\text{!!}X. \llbracket a: X; g'X \subseteq f(g'X) \rrbracket \implies g\ a: \text{gfp}\ f$
 $\langle \text{proof} \rangle$

lemma *coinduct-lemma*:
 $\llbracket X \subseteq f(X\ \text{Un}\ \text{gfp}(f)); \text{mono}(f) \rrbracket \implies X\ \text{Un}\ \text{gfp}(f) \subseteq f(X\ \text{Un}\ \text{gfp}(f))$

$\langle proof \rangle$

strong version, thanks to Coen and Frost

lemma *coinduct*: $\llbracket mono(f); a: X; X \subseteq f(X \text{ Un } gfp(f)) \rrbracket \implies a : gfp(f)$
 $\langle proof \rangle$

lemma *gfp-fun-UnI2*: $\llbracket mono(f); a: gfp(f) \rrbracket \implies a: f(X \text{ Un } gfp(f))$
 $\langle proof \rangle$

8.5 Even Stronger Coinduction Rule, by Martin Coen

Weakens the condition $X \subseteq f X$ to one expressed using both *lfp* and *gfp*

lemma *coinduct3-mono-lemma*: $mono(f) \implies mono(\%x. f(x) \text{ Un } X \text{ Un } B)$
 $\langle proof \rangle$

lemma *coinduct3-lemma*:
 $\llbracket X \subseteq f(lfp(\%x. f(x) \text{ Un } X \text{ Un } gfp(f))); mono(f) \rrbracket$
 $\implies lfp(\%x. f(x) \text{ Un } X \text{ Un } gfp(f)) \subseteq f(lfp(\%x. f(x) \text{ Un } X \text{ Un } gfp(f)))$
 $\langle proof \rangle$

lemma *coinduct3*:
 $\llbracket mono(f); a:X; X \subseteq f(lfp(\%x. f(x) \text{ Un } X \text{ Un } gfp(f))) \rrbracket \implies a : gfp(f)$
 $\langle proof \rangle$

Definition forms of *gfp-unfold* and *coinduct*, to control unfolding

lemma *def-gfp-unfold*: $\llbracket A == gfp(f); mono(f) \rrbracket \implies A = f(A)$
 $\langle proof \rangle$

lemma *def-coinduct*:
 $\llbracket A == gfp(f); mono(f); a:X; X \subseteq f(X \text{ Un } A) \rrbracket \implies a: A$
 $\langle proof \rangle$

lemma *def-Collect-coinduct*:
 $\llbracket A == gfp(\%w. Collect(P(w))); mono(\%w. Collect(P(w)));$
 $a: X; !!z. z: X \implies P(X \text{ Un } A) z \rrbracket \implies$
 $a : A$
 $\langle proof \rangle$

lemma *def-coinduct3*:
 $\llbracket A == gfp(f); mono(f); a:X; X \subseteq f(lfp(\%x. f(x) \text{ Un } X \text{ Un } A)) \rrbracket \implies a: A$
 $\langle proof \rangle$

Monotonicity of *gfp*!

lemma *gfp-mono*: $\llbracket !!Z. f(Z) \subseteq g(Z) \rrbracket \implies gfp(f) \subseteq gfp(g)$
 $\langle proof \rangle$

$\langle ML \rangle$

end

9 Sum-Type: The Disjoint Sum of Two Types

```
theory Sum-Type
imports Product-Type
begin
```

The representations of the two injections

```
constdefs
  Inl-Rep :: ['a, 'a, 'b, bool] => bool
  Inl-Rep == (%a. %x y p. x=a & p)

  Inr-Rep :: ['b, 'a, 'b, bool] => bool
  Inr-Rep == (%b. %x y p. y=b & ~p)
```

global

```
typedef (Sum)
  ('a, 'b) + (infixr 10)
  = {f. (? a. f = Inl-Rep(a::'a)) | (? b. f = Inr-Rep(b::'b))}
   $\langle proof \rangle$ 
```

local

abstract constants and syntax

```
constdefs
  Inl :: 'a => 'a + 'b
  Inl == (%a. Abs-Sum(Inl-Rep(a)))

  Inr :: 'b => 'a + 'b
  Inr == (%b. Abs-Sum(Inr-Rep(b)))

  Plus :: ['a set, 'b set] => ('a + 'b) set      (infixr <+> 65)
  A <+> B == (Inl'A) Un (Inr'B)
  — disjoint sum for sets; the operator + is overloaded with wrong type!

  Part :: ['a set, 'b => 'a] => 'a set
  Part A h == A Int {x. ? z. x = h(z)}
  — for selecting out the components of a mutually recursive definition
```

lemma *Inl-RepI*: $Inl\text{-}Rep(a) : Sum$
 $\langle proof \rangle$

lemma *Inr-RepI*: $Inr\text{-}Rep(b) : Sum$
 $\langle proof \rangle$

lemma *inj-on-Abs-Sum*: $inj\text{-}on\ Abs\text{-}Sum\ Sum$
 $\langle proof \rangle$

9.1 Freeness Properties for *Inl* and *Inr*

Distinctness

lemma *Inl-Rep-not-Inr-Rep*: $Inl\text{-}Rep(a) \sim = Inr\text{-}Rep(b)$
 $\langle proof \rangle$

lemma *Inl-not-Inr* [iff]: $Inl(a) \sim = Inr(b)$
 $\langle proof \rangle$

lemmas *Inr-not-Inl* = *Inl-not-Inr* [THEN not-sym, standard]
declare *Inr-not-Inl* [iff]

lemmas *Inl-neq-Inr* = *Inl-not-Inr* [THEN notE, standard]

lemmas *Inr-neq-Inl* = *sym* [THEN *Inl-neq-Inr*, standard]

Injectiveness

lemma *Inl-Rep-inject*: $Inl\text{-}Rep(a) = Inl\text{-}Rep(c) ==> a=c$
 $\langle proof \rangle$

lemma *Inr-Rep-inject*: $Inr\text{-}Rep(b) = Inr\text{-}Rep(d) ==> b=d$
 $\langle proof \rangle$

lemma *inj-Inl*: $inj(Inl)$
 $\langle proof \rangle$

lemmas *Inl-inject* = *inj-Inl* [THEN *injD*, standard]

lemma *inj-Inr*: $inj(Inr)$
 $\langle proof \rangle$

lemmas *Inr-inject* = *inj-Inr* [THEN *injD*, standard]

lemma *Inl-eq* [iff]: $(Inl(x)=Inl(y)) = (x=y)$
 $\langle proof \rangle$

lemma *Inr-eq* [iff]: $(Inr(x)=Inr(y)) = (x=y)$
 $\langle proof \rangle$

9.2 The Disjoint Sum of Sets

lemma *InlI* [*intro!*]: $a : A \implies \text{Inl}(a) : A <+> B$
 $\langle \text{proof} \rangle$

lemma *InrI* [*intro!*]: $b : B \implies \text{Inr}(b) : A <+> B$
 $\langle \text{proof} \rangle$

lemma *PlusE* [*elim!*]:

$$\begin{aligned} & [\text{u} : A <+> B; \\ & \quad !!x. [\text{x} : A; \text{u} = \text{Inl}(x)] \implies P; \\ & \quad !!y. [\text{y} : B; \text{u} = \text{Inr}(y)] \implies P \\ &] \implies P \end{aligned}$$

 $\langle \text{proof} \rangle$

Exhaustion rule for sums, a degenerate form of induction

lemma *sumE*:

$$\begin{aligned} & [!!x::'a. s = \text{Inl}(x) \implies P; !!y::'b. s = \text{Inr}(y) \implies P \\ &] \implies P \end{aligned}$$

 $\langle \text{proof} \rangle$

lemma *sum-induct*: $[!!x. P (\text{Inl } x); !!x. P (\text{Inr } x)] \implies P x$
 $\langle \text{proof} \rangle$

lemma *UNIV-Plus-UNIV* [*simp*]: $\text{UNIV} <+> \text{UNIV} = \text{UNIV}$
 $\langle \text{proof} \rangle$

9.3 The Part Primitive

lemma *Part-eqI* [*intro*]: $[a : A; a = h(b)] \implies a : \text{Part } A \ h$
 $\langle \text{proof} \rangle$

lemmas *PartI* = *Part-eqI* [*OF - refl, standard*]

lemma *PartE* [*elim!*]: $[a : \text{Part } A \ h; !!z. [a : A; a = h(z)] \implies P] \implies P$
 $\langle \text{proof} \rangle$

lemma *Part-subset*: $\text{Part } A \ h \leq A$
 $\langle \text{proof} \rangle$

lemma *Part-mono*: $A \leq B \implies \text{Part } A \ h \leq \text{Part } B \ h$
 $\langle \text{proof} \rangle$

lemmas *basic-monos* = *basic-monos Part-mono*

lemma *PartD1*: $a : \text{Part } A \ h \implies a : A$

⟨proof⟩

lemma *Part-id*: $\text{Part } A \ (\%x. x) = A$
 ⟨proof⟩

lemma *Part-Int*: $\text{Part } (A \text{ Int } B) \ h = (\text{Part } A \ h) \text{ Int } (\text{Part } B \ h)$
 ⟨proof⟩

lemma *Part-Collect*: $\text{Part } (A \text{ Int } \{x. P \ x\}) \ h = (\text{Part } A \ h) \text{ Int } \{x. P \ x\}$
 ⟨proof⟩

⟨ML⟩

end

10 Relation: Relations

theory *Relation*
imports *Product-Type*
begin

10.1 Definitions

constdefs
 $\text{converse} :: ('a * 'b) \text{ set} \Rightarrow ('b * 'a) \text{ set} \quad ((\text{r}^{\wedge} - 1) \ [1000] \ 999)$
 $\text{r}^{\wedge} - 1 == \{(y, x). (x, y) : r\}$
syntax (*xsymbols*)
 $\text{converse} :: ('a * 'b) \text{ set} \Rightarrow ('b * 'a) \text{ set} \quad ((\text{r}^{-1}) \ [1000] \ 999)$
constdefs
 $\text{rel-comp} :: [('b * 'c) \text{ set}, ('a * 'b) \text{ set}] \Rightarrow ('a * 'c) \text{ set} \quad (\text{infixr } O \ 60)$
 $r \ O \ s == \{(x, z). \text{EX } y. (x, y) : s \ \& \ (y, z) : r\}$
 $\text{Image} :: [('a * 'b) \text{ set}, 'a \text{ set}] \Rightarrow 'b \text{ set} \quad (\text{infixl } “ \ 90)$
 $r \ “ \ s == \{y. \text{EX } x:s. (x, y):r\}$
 $\text{Id} :: ('a * 'a) \text{ set} \text{ --- the identity relation}$
 $\text{Id} == \{p. \text{EX } x. p = (x, x)\}$
 $\text{diag} :: 'a \text{ set} \Rightarrow ('a * 'a) \text{ set} \text{ --- diagonal: identity over a set}$
 $\text{diag } A == \bigcup_{x \in A}. \{(x, x)\}$
 $\text{Domain} :: ('a * 'b) \text{ set} \Rightarrow 'a \text{ set}$
 $\text{Domain } r == \{x. \text{EX } y. (x, y):r\}$
 $\text{Range} :: ('a * 'b) \text{ set} \Rightarrow 'b \text{ set}$
 $\text{Range } r == \text{Domain}(r^{\wedge} - 1)$

Field :: ('a * 'a) set => 'a set
Field r == Domain r ∪ Range r

refl :: ['a set, ('a * 'a) set] => bool — reflexivity over a set
refl A r == r ⊆ A × A & (ALL x: A. (x,x) : r)

sym :: ('a * 'a) set => bool — symmetry predicate
sym r == ALL x y. (x,y): r --> (y,x): r

antisym:: ('a * 'a) set => bool — antisymmetry predicate
antisym r == ALL x y. (x,y):r --> (y,x):r --> x=y

trans :: ('a * 'a) set => bool — transitivity predicate
trans r == (ALL x y z. (x,y):r --> (y,z):r --> (x,z):r)

single-valued :: ('a * 'b) set => bool
single-valued r == ALL x y. (x,y):r --> (ALL z. (x,z):r --> y=z)

inv-image :: ('b * 'b) set => ('a => 'b) => ('a * 'a) set
inv-image r f == {(x, y). (f x, f y) : r}

syntax

reflexive :: ('a * 'a) set => bool — reflexivity over a type

translations

reflexive == *refl* UNIV

10.2 The identity relation

lemma *IdI* [intro]: (a, a) : Id
 <proof>

lemma *IdE* [elim!]: p : Id ==> (!!x. p = (x, x) ==> P) ==> P
 <proof>

lemma *pair-in-Id-conv* [iff]: ((a, b) : Id) = (a = b)
 <proof>

lemma *reflexive-Id*: reflexive Id
 <proof>

lemma *antisym-Id*: antisym Id
 — A strange result, since Id is also symmetric.
 <proof>

lemma *trans-Id*: trans Id
 <proof>

10.3 Diagonal: identity over a set

lemma *diag-empty* [*simp*]: $\text{diag } \{\} = \{\}$
 $\langle \text{proof} \rangle$

lemma *diag-eqI*: $a = b \implies a : A \implies (a, b) : \text{diag } A$
 $\langle \text{proof} \rangle$

lemma *diagI* [*intro!*]: $a : A \implies (a, a) : \text{diag } A$
 $\langle \text{proof} \rangle$

lemma *diagE* [*elim!*]:
 $c : \text{diag } A \implies (!x. x : A \implies c = (x, x) \implies P) \implies P$
 — The general elimination rule.
 $\langle \text{proof} \rangle$

lemma *diag-iff*: $((x, y) : \text{diag } A) = (x = y \ \& \ x : A)$
 $\langle \text{proof} \rangle$

lemma *diag-subset-Times*: $\text{diag } A \subseteq A \times A$
 $\langle \text{proof} \rangle$

10.4 Composition of two relations

lemma *rel-compI* [*intro*]:
 $(a, b) : s \implies (b, c) : r \implies (a, c) : r \circ s$
 $\langle \text{proof} \rangle$

lemma *rel-compE* [*elim!*]: $xz : r \circ s \implies$
 $(!x \ y \ z. xz = (x, z) \implies (x, y) : s \implies (y, z) : r \implies P) \implies P$
 $\langle \text{proof} \rangle$

lemma *rel-compEpair*:
 $(a, c) : r \circ s \implies (!y. (a, y) : s \implies (y, c) : r \implies P) \implies P$
 $\langle \text{proof} \rangle$

lemma *R-O-Id* [*simp*]: $R \circ \text{Id} = R$
 $\langle \text{proof} \rangle$

lemma *Id-O-R* [*simp*]: $\text{Id} \circ R = R$
 $\langle \text{proof} \rangle$

lemma *O-assoc*: $(R \circ S) \circ T = R \circ (S \circ T)$
 $\langle \text{proof} \rangle$

lemma *trans-O-subset*: $\text{trans } r \implies r \circ r \subseteq r$
 $\langle \text{proof} \rangle$

lemma *rel-comp-mono*: $r' \subseteq r \implies s' \subseteq s \implies (r' \circ s') \subseteq (r \circ s)$
 $\langle \text{proof} \rangle$

lemma *rel-comp-subset-Sigma*:

$$s \subseteq A \times B \implies r \subseteq B \times C \implies (r \circ s) \subseteq A \times C$$

<proof>

10.5 Reflexivity

lemma *reflI*: $r \subseteq A \times A \implies (!x. x : A \implies (x, x) : r) \implies \text{refl } A \ r$
<proof>

lemma *reflD*: $\text{refl } A \ r \implies a : A \implies (a, a) : r$
<proof>

10.6 Antisymmetry

lemma *antisymI*:

$$(!x \ y. (x, y) : r \implies (y, x) : r \implies x=y) \implies \text{antisym } r$$

<proof>

lemma *antisymD*: $\text{antisym } r \implies (a, b) : r \implies (b, a) : r \implies a = b$
<proof>

10.7 Symmetry and Transitivity

lemma *symD*: $\text{sym } r \implies (a, b) : r \implies (b, a) : r$
<proof>

lemma *transI*:

$$(!x \ y \ z. (x, y) : r \implies (y, z) : r \implies (x, z) : r) \implies \text{trans } r$$

<proof>

lemma *transD*: $\text{trans } r \implies (a, b) : r \implies (b, c) : r \implies (a, c) : r$
<proof>

10.8 Converse

lemma *converse-iff* [*iff*]: $((a,b) : r^{-1}) = ((b,a) : r)$
<proof>

lemma *converseI*[*sym*]: $(a, b) : r \implies (b, a) : r^{-1}$
<proof>

lemma *converseD*[*sym*]: $(a,b) : r^{-1} \implies (b, a) : r$
<proof>

lemma *converseE* [*elim!*]:

$$yx : r^{-1} \implies (!x \ y. yx = (y, x) \implies (x, y) : r \implies P) \implies P$$

— More general than *converseD*, as it “splits” the member of the relation.
<proof>

lemma *converse-converse* [simp]: $(r^{-1})^{-1} = r$
 ⟨proof⟩

lemma *converse-rel-comp*: $(r \circ s)^{-1} = s^{-1} \circ r^{-1}$
 ⟨proof⟩

lemma *converse-Id* [simp]: $Id^{-1} = Id$
 ⟨proof⟩

lemma *converse-diag* [simp]: $(diag\ A)^{-1} = diag\ A$
 ⟨proof⟩

lemma *refl-converse*: $refl\ A\ r \implies refl\ A\ (converse\ r)$
 ⟨proof⟩

lemma *antisym-converse*: $antisym\ (converse\ r) = antisym\ r$
 ⟨proof⟩

lemma *trans-converse*: $trans\ (converse\ r) = trans\ r$
 ⟨proof⟩

10.9 Domain

lemma *Domain-iff*: $(a : Domain\ r) = (EX\ y. (a, y) : r)$
 ⟨proof⟩

lemma *DomainI* [intro]: $(a, b) : r \implies a : Domain\ r$
 ⟨proof⟩

lemma *DomainE* [elim!]:
 $a : Domain\ r \implies (!y. (a, y) : r \implies P) \implies P$
 ⟨proof⟩

lemma *Domain-empty* [simp]: $Domain\ \{\} = \{\}$
 ⟨proof⟩

lemma *Domain-insert*: $Domain\ (insert\ (a, b)\ r) = insert\ a\ (Domain\ r)$
 ⟨proof⟩

lemma *Domain-Id* [simp]: $Domain\ Id = UNIV$
 ⟨proof⟩

lemma *Domain-diag* [simp]: $Domain\ (diag\ A) = A$
 ⟨proof⟩

lemma *Domain-Un-eq*: $Domain(A \cup B) = Domain(A) \cup Domain(B)$
 ⟨proof⟩

lemma *Domain-Int-subset*: $Domain(A \cap B) \subseteq Domain(A) \cap Domain(B)$

$\langle \text{proof} \rangle$

lemma *Domain-Diff-subset*: $\text{Domain}(A) - \text{Domain}(B) \subseteq \text{Domain}(A - B)$
 $\langle \text{proof} \rangle$

lemma *Domain-Union*: $\text{Domain} (\text{Union } S) = (\bigcup A \in S. \text{Domain } A)$
 $\langle \text{proof} \rangle$

lemma *Domain-mono*: $r \subseteq s \implies \text{Domain } r \subseteq \text{Domain } s$
 $\langle \text{proof} \rangle$

10.10 Range

lemma *Range-iff*: $(a : \text{Range } r) = (EX y. (y, a) : r)$
 $\langle \text{proof} \rangle$

lemma *RangeI [intro]*: $(a, b) : r \implies b : \text{Range } r$
 $\langle \text{proof} \rangle$

lemma *RangeE [elim!]*: $b : \text{Range } r \implies (!x. (x, b) : r \implies P) \implies P$
 $\langle \text{proof} \rangle$

lemma *Range-empty [simp]*: $\text{Range } \{\} = \{\}$
 $\langle \text{proof} \rangle$

lemma *Range-insert*: $\text{Range} (\text{insert } (a, b) r) = \text{insert } b (\text{Range } r)$
 $\langle \text{proof} \rangle$

lemma *Range-Id [simp]*: $\text{Range } \text{Id} = \text{UNIV}$
 $\langle \text{proof} \rangle$

lemma *Range-diag [simp]*: $\text{Range} (\text{diag } A) = A$
 $\langle \text{proof} \rangle$

lemma *Range-Un-eq*: $\text{Range}(A \cup B) = \text{Range}(A) \cup \text{Range}(B)$
 $\langle \text{proof} \rangle$

lemma *Range-Int-subset*: $\text{Range}(A \cap B) \subseteq \text{Range}(A) \cap \text{Range}(B)$
 $\langle \text{proof} \rangle$

lemma *Range-Diff-subset*: $\text{Range}(A) - \text{Range}(B) \subseteq \text{Range}(A - B)$
 $\langle \text{proof} \rangle$

lemma *Range-Union*: $\text{Range} (\text{Union } S) = (\bigcup A \in S. \text{Range } A)$
 $\langle \text{proof} \rangle$

10.11 Image of a set under a relation

lemma *Image-iff*: $(b : r `` A) = (EX x:A. (x, b) : r)$
 $\langle \text{proof} \rangle$

lemma *Image-singleton*: $r^{\text{“}}\{a\} = \{b. (a, b) : r\}$
 $\langle \text{proof} \rangle$

lemma *Image-singleton-iff* [iff]: $(b : r^{\text{“}}\{a\}) = ((a, b) : r)$
 $\langle \text{proof} \rangle$

lemma *ImageI* [intro]: $(a, b) : r ==> a : A ==> b : r^{\text{“}}A$
 $\langle \text{proof} \rangle$

lemma *ImageE* [elim!]:
 $b : r^{\text{“}}A ==> (!x. (x, b) : r ==> x : A ==> P) ==> P$
 $\langle \text{proof} \rangle$

lemma *rev-ImageI*: $a : A ==> (a, b) : r ==> b : r^{\text{“}}A$
 — This version’s more effective when we already have the required a
 $\langle \text{proof} \rangle$

lemma *Image-empty* [simp]: $R^{\text{“}}\{\} = \{\}$
 $\langle \text{proof} \rangle$

lemma *Image-Id* [simp]: $\text{Id}^{\text{“}}A = A$
 $\langle \text{proof} \rangle$

lemma *Image-diag* [simp]: $\text{diag } A^{\text{“}}B = A \cap B$
 $\langle \text{proof} \rangle$

lemma *Image-Int-subset*: $R^{\text{“}}(A \cap B) \subseteq R^{\text{“}}A \cap R^{\text{“}}B$
 $\langle \text{proof} \rangle$

lemma *Image-Int-eq*:
 $\text{single-valued } (\text{converse } R) ==> R^{\text{“}}(A \cap B) = R^{\text{“}}A \cap R^{\text{“}}B$
 $\langle \text{proof} \rangle$

lemma *Image-Un*: $R^{\text{“}}(A \cup B) = R^{\text{“}}A \cup R^{\text{“}}B$
 $\langle \text{proof} \rangle$

lemma *Un-Image*: $(R \cup S)^{\text{“}}A = R^{\text{“}}A \cup S^{\text{“}}A$
 $\langle \text{proof} \rangle$

lemma *Image-subset*: $r \subseteq A \times B ==> r^{\text{“}}C \subseteq B$
 $\langle \text{proof} \rangle$

lemma *Image-eq-UN*: $r^{\text{“}}B = (\bigcup_{y \in B. r^{\text{“}}\{y\}})$
 — NOT suitable for rewriting
 $\langle \text{proof} \rangle$

lemma *Image-mono*: $r' \subseteq r ==> A' \subseteq A ==> (r'^{\text{“}}A') \subseteq (r^{\text{“}}A)$
 $\langle \text{proof} \rangle$

lemma *Image-UN*: $(r \text{ “ } (UNION A B)) = (\bigcup x \in A. r \text{ “ } (B x))$
 $\langle proof \rangle$

lemma *Image-INT-subset*: $(r \text{ “ } INTER A B) \subseteq (\bigcap x \in A. r \text{ “ } (B x))$
 $\langle proof \rangle$

Converse inclusion requires some assumptions

lemma *Image-INT-eq*:
 $[[single\text{-}valued (r^{-1}); A \neq \{\}]] \implies r \text{ “ } INTER A B = (\bigcap x \in A. r \text{ “ } B x)$
 $\langle proof \rangle$

lemma *Image-subset-eq*: $(r \text{ “ } A \subseteq B) = (A \subseteq - ((r^{-1}) \text{ “ } (-B)))$
 $\langle proof \rangle$

10.12 Single valued relations

lemma *single-valuedI*:
 $ALL x y. (x, y):r \dashrightarrow (ALL z. (x, z):r \dashrightarrow y=z) \implies single\text{-}valued r$
 $\langle proof \rangle$

lemma *single-valuedD*:
 $single\text{-}valued r \implies (x, y) : r \implies (x, z) : r \implies y = z$
 $\langle proof \rangle$

10.13 Graphs given by Collect

lemma *Domain-Collect-split* [simp]: $Domain\{(x, y). P x y\} = \{x. EX y. P x y\}$
 $\langle proof \rangle$

lemma *Range-Collect-split* [simp]: $Range\{(x, y). P x y\} = \{y. EX x. P x y\}$
 $\langle proof \rangle$

lemma *Image-Collect-split* [simp]: $\{(x, y). P x y\} \text{ “ } A = \{y. EX x:A. P x y\}$
 $\langle proof \rangle$

10.14 Inverse image

lemma *trans-inv-image*: $trans r \implies trans (inv\text{-}image r f)$
 $\langle proof \rangle$

end

theory *Record*
imports *Product-Type*
uses (*Tools/record-package.ML*)
begin

lemma *rec-True-simp*: $(True \implies PROP\ P) \equiv PROP\ P$
 $\langle proof \rangle$

end

11 Inductive: Support for inductive sets and types

```

theory Inductive
imports FixedPoint Sum-Type Relation Record
uses
  (Tools/inductive-package.ML)
  (Tools/inductive-realizer.ML)
  (Tools/inductive-codegen.ML)
  (Tools/datatype-aux.ML)
  (Tools/datatype-prop.ML)
  (Tools/datatype-rep-proofs.ML)
  (Tools/datatype-abs-proofs.ML)
  (Tools/datatype-realizer.ML)
  (Tools/datatype-package.ML)
  (Tools/datatype-codegen.ML)
  (Tools/recfun-codegen.ML)
  (Tools/primrec-package.ML)
begin

```

11.1 Inductive sets

Inversion of injective functions.

```

constdefs
  myinv :: ('a ==> 'b) ==> ('b ==> 'a)
  myinv (f :: 'a ==> 'b) ==  $\lambda y. \text{THE } x. f\ x = y$ 

```

```

lemma myinv-f-f: inj f ==> myinv f (f x) = x
<proof>

```

```

lemma f-myinv-f: inj f ==>  $y \in \text{range } f \implies f (\text{myinv } f\ y) = y$ 
<proof>

```

```

hide const myinv

```

Package setup.

```

<ML>

```

```

theorems basic-monos [mono] =
  subset-refl imp-refl disj-mono conj-mono ex-mono all-mono if-def2
  Collect-mono in-mono vimage-mono
  imp-conv-disj not-not de-Morgan-disj de-Morgan-conj
  not-all not-ex
  Ball-def Bex-def
  induct-rulify2

```

11.2 Inductive datatypes and primitive recursion

Package setup.

$\langle ML \rangle$

end

12 Transitive-Closure: Reflexive and Transitive closure of a relation

```
theory Transitive-Closure
imports Inductive
uses (../Provers/trancl.ML)
begin
```

rtrancl is reflexive/transitive closure, *trancl* is transitive closure, *reflcl* is reflexive closure.

These postfix operators have *maximum priority*, forcing their operands to be atomic.

```
consts
  rtrancl :: ('a × 'a) set => ('a × 'a) set    ((-^*) [1000] 999)
```

```
inductive r^*
  intros
    rtrancl-refl [intro!, Pure.intro!, simp]: (a, a) : r^*
    rtrancl-into-rtrancl [Pure.intro]: (a, b) : r^* ==> (b, c) : r ==> (a, c) : r^*
```

```
consts
  trancl :: ('a × 'a) set => ('a × 'a) set    ((-^+) [1000] 999)
```

```
inductive r^+
  intros
    r-into-trancl [intro, Pure.intro]: (a, b) : r ==> (a, b) : r^+
    trancl-into-trancl [Pure.intro]: (a, b) : r^+ ==> (b, c) : r ==> (a, c) : r^+
```

```
syntax
  -reflcl :: ('a × 'a) set => ('a × 'a) set    ((-^=) [1000] 999)
```

```
translations
  r^= == r ∪ Id
```

```
syntax (xsymbols)
  rtrancl :: ('a × 'a) set => ('a × 'a) set    ((-*) [1000] 999)
  trancl :: ('a × 'a) set => ('a × 'a) set    ((-^+) [1000] 999)
  -reflcl :: ('a × 'a) set => ('a × 'a) set    ((-^=) [1000] 999)
```

```
syntax (HTML output)
  rtrancl :: ('a × 'a) set => ('a × 'a) set    ((-*) [1000] 999)
  trancl :: ('a × 'a) set => ('a × 'a) set    ((-^+) [1000] 999)
  -reflcl :: ('a × 'a) set => ('a × 'a) set    ((-^=) [1000] 999)
```

12.1 Reflexive-transitive closure

lemma *r-into-rtrancl* [intro]: $!!p. p \in r \implies p \in r^*$
 — *rtrancl* of *r* contains *r*
 $\langle proof \rangle$

lemma *rtrancl-mono*: $r \subseteq s \implies r^* \subseteq s^*$
 — monotonicity of *rtrancl*
 $\langle proof \rangle$

theorem *rtrancl-induct* [consumes 1, induct set: *rtrancl*]:
assumes *a*: $(a, b) : r^*$
and cases: $P\ a\ !!y\ z. [\ (a, y) : r^*; (y, z) : r; P\ y\] \implies P\ z$
shows $P\ b$
 $\langle proof \rangle$

lemmas *rtrancl-induct2* =
rtrancl-induct[of $(ax, ay)\ (bx, by)$, split-format (complete),
 consumes 1, case-names *refl step*]

lemma *trans-rtrancl*: $trans(r^*)$
 — transitivity of transitive closure!! – by induction
 $\langle proof \rangle$

lemmas *rtrancl-trans* = *trans-rtrancl* [THEN *transD*, standard]

lemma *rtranclE*:
 $[\ (a::'a, b) : r^*; (a = b) \implies P;$
 $!!y. [\ (a, y) : r^*; (y, b) : r\] \implies P$
 $]\implies P$
 — elimination of *rtrancl* – by induction on a special formula
 $\langle proof \rangle$

lemma *converse-rtrancl-into-rtrancl*:
 $(a, b) \in r \implies (b, c) \in r^* \implies (a, c) \in r^*$
 $\langle proof \rangle$

More r^* equations and inclusions.

lemma *rtrancl-idemp* [simp]: $(r^*)^* = r^*$
 $\langle proof \rangle$

lemma *rtrancl-idemp-self-comp* [simp]: $R^* \circ R^* = R^*$
 $\langle proof \rangle$

lemma *rtrancl-subset-rtrancl*: $r \subseteq s^* \implies r^* \subseteq s^*$
 $\langle proof \rangle$

lemma *rtrancl-subset*: $R \subseteq S \implies S \subseteq R^* \implies S^* = R^*$
 $\langle proof \rangle$

lemma *rtrancl-Un-rtrancl*: $(R^* \cup S^*)^* = (R \cup S)^*$
 $\langle proof \rangle$

lemma *rtrancl-reflcl [simp]*: $(R^*)^* = R^*$
 $\langle proof \rangle$

lemma *rtrancl-r-diff-Id*: $(r - Id)^* = r^*$
 $\langle proof \rangle$

theorem *rtrancl-converseD*:
 assumes $r: (x, y) \in (r^* - 1)^*$
 shows $(y, x) \in r^*$
 $\langle proof \rangle$

theorem *rtrancl-converseI*:
 assumes $r: (y, x) \in r^*$
 shows $(x, y) \in (r^* - 1)^*$
 $\langle proof \rangle$

lemma *rtrancl-converse*: $(r^* - 1)^* = (r^*)^* - 1$
 $\langle proof \rangle$

theorem *converse-rtrancl-induct[consumes 1]*:
 assumes *major*: $(a, b) : r^*$
 and *cases*: $P b !!y z. [] (y, z) : r; (z, b) : r^*; P z [] ==> P y$
 shows $P a$
 $\langle proof \rangle$

lemmas *converse-rtrancl-induct2* =
converse-rtrancl-induct[of (ax,ay) (bx,by), split-format (complete),
consumes 1, case-names refl step]

lemma *converse-rtranclE*:
 $[] (x,z):r^*;$
 $x=z ==> P;$
 $!!y. [] (x,y):r; (y,z):r^* [] ==> P$
 $[] ==> P$
 $\langle proof \rangle$

$\langle ML \rangle$

lemma *r-comp-rtrancl-eq*: $r \circ r^* = r^* \circ r$
 $\langle proof \rangle$

lemma *rtrancl-unfold*: $r^* = Id \cup (r \circ r^*)$
 $\langle proof \rangle$

12.2 Transitive closure

lemma *trancl-mono*: $!!p. p \in r^+ \implies r \subseteq s \implies p \in s^+$
 $\langle proof \rangle$

lemma *r-into-trancl'*: $!!p. p : r \implies p : r^+$
 $\langle proof \rangle$

Conversions between *trancl* and *rtrancl*.

lemma *trancl-into-rtrancl*: $(a, b) \in r^+ \implies (a, b) \in r^*$
 $\langle proof \rangle$

lemma *rtrancl-into-trancl1*: **assumes** $r: (a, b) \in r^*$
shows $!!c. (b, c) \in r \implies (a, c) \in r^+$ $\langle proof \rangle$

lemma *rtrancl-into-trancl2*: $[(a, b) : r; (b, c) : r^*] \implies (a, c) : r^+$
 — intro rule from *r* and *rtrancl*
 $\langle proof \rangle$

lemma *trancl-induct* [*consumes 1, induct set: trancl*]:
assumes $a: (a, b) : r^+$
and cases: $!!y. (a, y) : r \implies P y$
 $!!y z. (a, y) : r^+ \implies (y, z) : r \implies P y \implies P z$
shows $P b$
 — Nice induction rule for *trancl*
 $\langle proof \rangle$

lemma *trancl-trans-induct*:
 $[(x, y) : r^+;$
 $!!x y. (x, y) : r \implies P x y;$
 $!!x y z. [(x, y) : r^+; P x y; (y, z) : r^+; P y z] \implies P x z$
 $] \implies P x y$
 — Another induction rule for *trancl*, incorporating transitivity
 $\langle proof \rangle$

inductive-cases *tranclE*: $(a, b) : r^+$

lemma *trancl-unfold*: $r^+ = r \cup (r \circ r^+)$
 $\langle proof \rangle$

lemma *trans-trancl*: $trans(r^+)$
 — Transitivity of r^+
 $\langle proof \rangle$

lemmas *trancl-trans* = *trans-trancl* [*THEN transD, standard*]

lemma *rtrancl-trancl-trancl*: **assumes** $r: (x, y) \in r^*$
shows $!!z. (y, z) \in r^+ \implies (x, z) \in r^+$ $\langle proof \rangle$

lemma *tranc1-into-tranc12*: $(a, b) \in r \implies (b, c) \in r^+ \implies (a, c) \in r^+$
 $\langle \text{proof} \rangle$

lemma *tranc1-insert*:
 $(\text{insert } (y, x) \ r)^+ = r^+ \cup \{(a, b). (a, y) \in r^* \wedge (x, b) \in r^*\}$
 — primitive recursion for *tranc1* over finite relations
 $\langle \text{proof} \rangle$

lemma *tranc1-converseI*: $(x, y) \in (r^+)^{-1} \implies (x, y) \in (r^{-1})^+$
 $\langle \text{proof} \rangle$

lemma *tranc1-converseD*: $(x, y) \in (r^{-1})^+ \implies (x, y) \in (r^+)^{-1}$
 $\langle \text{proof} \rangle$

lemma *tranc1-converse*: $(r^{-1})^+ = (r^+)^{-1}$
 $\langle \text{proof} \rangle$

lemma *converse-tranc1-induct*:
 $\llbracket (a, b) : r^+; !!y. (y, b) : r \implies P(y);$
 $!!y \ z. \llbracket (y, z) : r; (z, b) : r^+; P(z) \rrbracket \implies P(y) \rrbracket$
 $\implies P(a)$
 $\langle \text{proof} \rangle$

lemma *tranc1D*: $(x, y) \in R^+ \implies \exists x. (x, z) \in R \wedge (z, y) \in R^*$
 $\langle \text{proof} \rangle$

lemma *irrefl-tranc1I*: $r^{-1} \cap r^* = \{\}$ $\implies (x, x) \notin r^+$
 $\langle \text{proof} \rangle$

lemma *irrefl-tranc1-rD*: $!!X. \text{ALL } x. (x, x) \notin r^+ \implies (x, y) \in r \implies x \neq y$
 $\langle \text{proof} \rangle$

lemma *tranc1-subset-Sigma-aux*:
 $(a, b) \in r^* \implies r \subseteq A \times A \implies a = b \vee a \in A$
 $\langle \text{proof} \rangle$

lemma *tranc1-subset-Sigma*: $r \subseteq A \times A \implies r^+ \subseteq A \times A$
 $\langle \text{proof} \rangle$

lemma *reflcl-tranc1 [simp]*: $(r^+)^+ = r^*$
 $\langle \text{proof} \rangle$

lemma *tranc1-reflcl [simp]*: $(r^+)^+ = r^*$
 $\langle \text{proof} \rangle$

lemma *tranc1-empty [simp]*: $\{\}^+ = \{\}$
 $\langle \text{proof} \rangle$

lemma *rtranc1-empty [simp]*: $\{\}^* = Id$

$\langle proof \rangle$

lemma *rtranclD*: $(a, b) \in R^* \implies a = b \vee a \neq b \wedge (a, b) \in R^+ +$
 $\langle proof \rangle$

lemma *rtrancl-eq-or-trancl*:
 $(x, y) \in R^* = (x = y \vee x \neq y \wedge (x, y) \in R^+)$
 $\langle proof \rangle$

Domain and Range

lemma *Domain-rtrancl* [simp]: $Domain (R^*) = UNIV$
 $\langle proof \rangle$

lemma *Range-rtrancl* [simp]: $Range (R^*) = UNIV$
 $\langle proof \rangle$

lemma *rtrancl-Un-subset*: $(R^* \cup S^*) \subseteq (R \cup S)^*$
 $\langle proof \rangle$

lemma *in-rtrancl-UnI*: $x \in R^* \vee x \in S^* \implies x \in (R \cup S)^*$
 $\langle proof \rangle$

lemma *trancl-domain* [simp]: $Domain (r^+) = Domain r$
 $\langle proof \rangle$

lemma *trancl-range* [simp]: $Range (r^+) = Range r$
 $\langle proof \rangle$

lemma *Not-Domain-rtrancl*:
 $x \sim: Domain R \implies ((x, y) : R^*) = (x = y)$
 $\langle proof \rangle$

More about converse *rtrancl* and *trancl*, should be merged with main body.

lemma *single-valued-confluent*:
 $\llbracket \text{single-valued } r; (x, y) \in r^*; (x, z) \in r^* \rrbracket$
 $\implies (y, z) \in r^* \vee (z, y) \in r^*$
 $\langle proof \rangle$

lemma *r-r-into-trancl*: $(a, b) \in R \implies (b, c) \in R \implies (a, c) \in R^+ +$
 $\langle proof \rangle$

lemma *trancl-into-trancl* [rule-format]:
 $(a, b) \in r^+ \implies (b, c) \in r \longrightarrow (a, c) \in r^+$
 $\langle proof \rangle$

lemma *trancl-rtrancl-trancl*:
 $(a, b) \in r^+ \implies (b, c) \in r^* \implies (a, c) \in r^+$
 $\langle proof \rangle$


```

lemmas transitive-closure-trans [trans] =
  r-r-into-trancl trancl-trans rtrancl-trans
  trancl-into-trancl trancl-into-trancl2
  rtrancl-into-rtrancl converse-rtrancl-into-rtrancl
  rtrancl-trancl-trancl trancl-rtrancl-trancl

```

```

declare trancl-into-rtrancl [elim]

```

```

declare rtranclE [cases set: rtrancl]

```

```

declare tranclE [cases set: trancl]

```

12.3 Setup of transitivity reasoner

$\langle ML \rangle$

end

13 Wellfounded-Recursion: Well-founded Recursion

```

theory Wellfounded-Recursion

```

```

imports Transitive-Closure

```

```

begin

```

```

consts

```

```

  wfrec-rel :: ('a * 'a) set => (('a => 'b) => 'a => 'b) => ('a * 'b) set

```

```

inductive wfrec-rel R F

```

```

intros

```

```

  wfrecI: ALL z. (z, x) : R --> (z, g z) : wfrec-rel R F ==>
    (x, F g x) : wfrec-rel R F

```

```

constdefs

```

```

  wf :: ('a * 'a) set => bool

```

```

  wf(r) == (!P. (!x. (!y. (y,x):r --> P(y)) --> P(x)) --> (!x. P(x)))

```

```

  acyclic :: ('a * 'a) set => bool

```

```

  acyclic r == !x. (x,x) ~: r^+

```

```

  cut :: ('a => 'b) => ('a * 'a) set => 'a => 'a => 'b

```

```

  cut f r x == (%y. if (y,x):r then f y else arbitrary)

```

```

  adm-wf :: ('a * 'a) set => (('a => 'b) => 'a => 'b) => bool

```

```

  adm-wf R F == ALL f g x.

```

```

    (ALL z. (z, x) : R --> f z = g z) --> F f x = F g x

```

$wfrec :: ('a * 'a) \text{ set} \Rightarrow (('a \Rightarrow 'b) \Rightarrow 'a \Rightarrow 'b) \Rightarrow 'a \Rightarrow 'b$
 $wfrec\ R\ F == \%x. \text{ THE } y. (x, y) : wfrec\text{-rel } R\ (\%f\ x. F\ (\text{cut } f\ R\ x)\ x)$

axclass *wellorder* \subseteq *linorder*
 $wf: wf\ \{(x,y::'a::ord). x < y\}$

lemma *wfUNIVI*:

$(!!P\ x. (ALL\ x. (ALL\ y. (y,x) : r \dashrightarrow P(y)) \dashrightarrow P(x)) \Rightarrow P(x)) \Rightarrow$
 $wf(r)$
 $\langle proof \rangle$

Restriction to domain A . If r is well-founded over A then $wf\ r$

lemma *wfI*:

$[| r <= A <*> A;$
 $!!x\ P. [| ALL\ x. (ALL\ y. (y,x) : r \dashrightarrow P\ y) \dashrightarrow P\ x; x:A |] \Rightarrow P\ x |]$
 $\Rightarrow wf\ r$
 $\langle proof \rangle$

lemma *wf-induct*:

$[| wf(r);$
 $!!x.[| ALL\ y. (y,x): r \dashrightarrow P(y) |] \Rightarrow P(x)$
 $|] \Rightarrow P(a)$
 $\langle proof \rangle$

lemmas *wf-induct-rule* = *wf-induct* [*rule-format*, *case-names less*, *induct set: wf*]

lemma *wf-not-sym* [*rule-format*]: $wf(r) \Rightarrow ALL\ x. (a,x):r \dashrightarrow (x,a) \sim: r$
 $\langle proof \rangle$

lemmas *wf-asym* = *wf-not-sym* [*elim-format*]

lemma *wf-not-refl* [*simp*]: $wf(r) \Rightarrow (a,a) \sim: r$
 $\langle proof \rangle$

lemmas *wf-irrefl* = *wf-not-refl* [*elim-format*]

transitive closure of a well-founded relation is well-founded!

lemma *wf-trancl*: $wf(r) \Rightarrow wf(r^+)$
 $\langle proof \rangle$

lemma *wf-converse-trancl*: $wf\ (r^+ - 1) \Rightarrow wf\ ((r^+)^+ - 1)$
 $\langle proof \rangle$

13.0.1 Minimal-element characterization of well-foundedness

lemma *lemma1*: $wf\ r ==> x:Q \dashrightarrow (EX\ z:Q. ALL\ y. (y,z):r \dashrightarrow y\sim:Q)$
 $\langle proof \rangle$

lemma *lemma2*: $(ALL\ Q\ x. x:Q \dashrightarrow (EX\ z:Q. ALL\ y. (y,z):r \dashrightarrow y\sim:Q))$
 $==> wf\ r$
 $\langle proof \rangle$

lemma *wf-eq-minimal*: $wf\ r = (ALL\ Q\ x. x:Q \dashrightarrow (EX\ z:Q. ALL\ y. (y,z):r \dashrightarrow y\sim:Q))$
 $\langle proof \rangle$

13.0.2 Other simple well-foundedness results

Well-foundedness of subsets

lemma *wf-subset*: $[| wf(r); p \leq r |] ==> wf(p)$
 $\langle proof \rangle$

Well-foundedness of the empty relation

lemma *wf-empty* [iff]: $wf(\{\})$
 $\langle proof \rangle$

Well-foundedness of insert

lemma *wf-insert* [iff]: $wf(insert\ (y,x)\ r) = (wf(r) \ \&\ (x,y) \sim: r^{\wedge*})$
 $\langle proof \rangle$

Well-foundedness of image

lemma *wf-prod-fun-image*: $[| wf\ r; inj\ f |] ==> wf(prod-fun\ f\ f'\ r)$
 $\langle proof \rangle$

13.0.3 Well-Foundedness Results for Unions

Well-foundedness of indexed union with disjoint domains and ranges

lemma *wf-UN*: $[| ALL\ i:I. wf(r\ i);$
 $ALL\ i:I. ALL\ j:I. r\ i \sim = r\ j \dashrightarrow Domain(r\ i)\ Int\ Range(r\ j) = \{\}$
 $|] ==> wf(UN\ i:I. r\ i)$
 $\langle proof \rangle$

lemma *wf-Union*:

$[| ALL\ r:R. wf\ r;$
 $ALL\ r:R. ALL\ s:R. r \sim = s \dashrightarrow Domain\ r\ Int\ Range\ s = \{\}$
 $|] ==> wf(Union\ R)$
 $\langle proof \rangle$

lemma *wf-Un*:

$[| wf\ r; wf\ s; Domain\ r\ Int\ Range\ s = \{\} |] ==> wf(r\ Un\ s)$
 $\langle proof \rangle$

13.0.4 acyclic

lemma *acyclicI*: $ALL\ x.\ (x, x) \sim: r^+ \implies acyclic\ r$
 $\langle proof \rangle$

lemma *wf-acyclic*: $wf\ r \implies acyclic\ r$
 $\langle proof \rangle$

lemma *acyclic-insert* [iff]:
 $acyclic(insert\ (y, x)\ r) = (acyclic\ r \ \&\ (x, y) \sim: r^*)$
 $\langle proof \rangle$

lemma *acyclic-converse* [iff]: $acyclic(r^{-1}) = acyclic\ r$
 $\langle proof \rangle$

lemma *acyclic-impl-antisym-rtrancl*: $acyclic\ r \implies antisym(r^*)$
 $\langle proof \rangle$

lemma *acyclic-subset*: $[| acyclic\ s;\ r \leq s |] \implies acyclic\ r$
 $\langle proof \rangle$

13.1 Well-Founded Recursion

cut

lemma *cuts-eq*: $(cut\ f\ r\ x = cut\ g\ r\ x) = (ALL\ y.\ (y, x):r \dashrightarrow f(y)=g(y))$
 $\langle proof \rangle$

lemma *cut-apply*: $(x, a):r \implies (cut\ f\ r\ a)(x) = f(x)$
 $\langle proof \rangle$

Inductive characterization of wfrec combinator; for details see: John Harrison, ”Inductive definitions: automation and application”

lemma *wfrec-unique*: $[| adm\text{-}wf\ R\ F;\ wf\ R |] \implies EX!\ y.\ (x, y) : wfrec\text{-}rel\ R\ F$
 $\langle proof \rangle$

lemma *adm-lemma*: $adm\text{-}wf\ R\ (\%f\ x.\ F\ (cut\ f\ R\ x)\ x)$
 $\langle proof \rangle$

lemma *wfrec*: $wf(r) \implies wfrec\ r\ H\ a = H\ (cut\ (wfrec\ r\ H)\ r\ a)\ a$
 $\langle proof \rangle$

* This form avoids giant explosions in proofs. NOTE USE OF ==

lemma *def-wfrec*: $[| f == wfrec\ r\ H;\ wf(r) |] \implies f(a) = H\ (cut\ f\ r\ a)\ a$
 $\langle proof \rangle$

13.2 Code generator setup

consts-code

```

  wfrec  (<module>wfrec?)
attach <<
fun wfrec f x = f (wfrec f) x;
>>

```

13.3 Variants for TFL: the Recdef Package

lemma *tfl-wf-induct*: $ALL\ R.\ wf\ R \longrightarrow$
 $(ALL\ P.\ (ALL\ x.\ (ALL\ y.\ (y,x):R \longrightarrow P\ y) \longrightarrow P\ x) \longrightarrow (ALL\ x.\ P\ x))$
 $\langle proof \rangle$

lemma *tfl-cut-apply*: $ALL\ f\ R.\ (x,a):R \longrightarrow (cut\ f\ R\ a)(x) = f(x)$
 $\langle proof \rangle$

lemma *tfl-wfrec*:
 $ALL\ M\ R\ f.\ (f=wfrec\ R\ M) \longrightarrow wf\ R \longrightarrow (ALL\ x.\ f\ x = M\ (cut\ f\ R\ x)\ x)$
 $\langle proof \rangle$

13.4 LEAST and wellorderings

See also *wf-linord-ex-has-least* and its consequences in *Wellfounded-Relations.ML*

lemma *wellorder-Least-lemma* [rule-format]:
 $P\ (k::'a::wellorder) \longrightarrow P\ (LEAST\ x.\ P(x)) \ \&\ (LEAST\ x.\ P(x)) \leq k$
 $\langle proof \rangle$

lemmas *LeastI* = *wellorder-Least-lemma* [THEN *conjunct1*, *standard*]
lemmas *Least-le* = *wellorder-Least-lemma* [THEN *conjunct2*, *standard*]

— The following 3 lemmas are due to Brian Huffman

lemma *LeastI-ex*: $EX\ x::'a::wellorder.\ P\ x \implies P\ (Least\ P)$
 $\langle proof \rangle$

lemma *LeastI2*:
 $[| P\ (a::'a::wellorder); !!x.\ P\ x \implies Q\ x |] \implies Q\ (Least\ P)$
 $\langle proof \rangle$

lemma *LeastI2-ex*:
 $[| EX\ a::'a::wellorder.\ P\ a; !!x.\ P\ x \implies Q\ x |] \implies Q\ (Least\ P)$
 $\langle proof \rangle$

lemma *not-less-Least*: $[| k < (LEAST\ x.\ P\ x) |] \implies \sim P\ (k::'a::wellorder)$
 $\langle proof \rangle$

$\langle ML \rangle$

end

14 OrderedGroup: Ordered Groups

```
theory OrderedGroup
imports Inductive LOrder
uses ../Provers/Arith/abel-cancel.ML
begin
```

The theory of partially ordered groups is taken from the books:

- *Lattice Theory* by Garret Birkhoff, American Mathematical Society 1979
- *Partially Ordered Algebraic Systems*, Pergamon Press 1963

Most of the used notions can also be looked up in

- <http://www.mathworld.com> by Eric Weisstein et. al.
- *Algebra I* by van der Waerden, Springer.

14.1 Semigroups, Groups

```
axclass semigroup-add  $\subseteq$  plus
  add-assoc:  $(a + b) + c = a + (b + c)$ 
```

```
axclass ab-semigroup-add  $\subseteq$  semigroup-add
  add-commute:  $a + b = b + a$ 
```

```
lemma add-left-commute:  $a + (b + c) = b + (a + (c::'a::ab-semigroup-add))$ 
  <proof>
```

```
theorems add-ac = add-assoc add-commute add-left-commute
```

```
axclass semigroup-mult  $\subseteq$  times
  mult-assoc:  $(a * b) * c = a * (b * c)$ 
```

```
axclass ab-semigroup-mult  $\subseteq$  semigroup-mult
  mult-commute:  $a * b = b * a$ 
```

```
lemma mult-left-commute:  $a * (b * c) = b * (a * (c::'a::ab-semigroup-mult))$ 
  <proof>
```

```
theorems mult-ac = mult-assoc mult-commute mult-left-commute
```

```
axclass comm-monoid-add  $\subseteq$  zero, ab-semigroup-add
```

add-0[simp]: $0 + a = a$

axclass *monoid-mult* \subseteq *one*, *semigroup-mult*
mult-1-left[simp]: $1 * a = a$
mult-1-right[simp]: $a * 1 = a$

axclass *comm-monoid-mult* \subseteq *one*, *ab-semigroup-mult*
mult-1: $1 * a = a$

instance *comm-monoid-mult* \subseteq *monoid-mult*
 \langle proof \rangle

axclass *cancel-semigroup-add* \subseteq *semigroup-add*
add-left-imp-eq: $a + b = a + c \implies b = c$
add-right-imp-eq: $b + a = c + a \implies b = c$

axclass *cancel-ab-semigroup-add* \subseteq *ab-semigroup-add*
add-imp-eq: $a + b = a + c \implies b = c$

instance *cancel-ab-semigroup-add* \subseteq *cancel-semigroup-add*
 \langle proof \rangle

axclass *ab-group-add* \subseteq *minus*, *comm-monoid-add*
left-minus[simp]: $- a + a = 0$
diff-minus: $a - b = a + (-b)$

instance *ab-group-add* \subseteq *cancel-ab-semigroup-add*
 \langle proof \rangle

lemma *add-0-right* [simp]: $a + 0 = (a::'a::\text{comm-monoid-add})$
 \langle proof \rangle

lemma *add-left-cancel* [simp]:
 $(a + b = a + c) = (b = (c::'a::\text{cancel-semigroup-add}))$
 \langle proof \rangle

lemma *add-right-cancel* [simp]:
 $(b + a = c + a) = (b = (c::'a::\text{cancel-semigroup-add}))$
 \langle proof \rangle

lemma *right-minus* [simp]: $a + -(a::'a::\text{ab-group-add}) = 0$
 \langle proof \rangle

lemma *right-minus-eq*: $(a - b = 0) = (a = (b::'a::\text{ab-group-add}))$
 \langle proof \rangle

lemma *minus-minus* [simp]: $- (- (a::'a::\text{ab-group-add})) = a$
 \langle proof \rangle

lemma *equals-zero-I*: $a + b = 0 \implies -a = (b::'a::ab\text{-group-add})$
 $\langle proof \rangle$

lemma *minus-zero* [simp]: $-0 = (0::'a::ab\text{-group-add})$
 $\langle proof \rangle$

lemma *diff-self* [simp]: $a - (a::'a::ab\text{-group-add}) = 0$
 $\langle proof \rangle$

lemma *diff-0* [simp]: $(0::'a::ab\text{-group-add}) - a = -a$
 $\langle proof \rangle$

lemma *diff-0-right* [simp]: $a - (0::'a::ab\text{-group-add}) = a$
 $\langle proof \rangle$

lemma *diff-minus-eq-add* [simp]: $a - -b = a + (b::'a::ab\text{-group-add})$
 $\langle proof \rangle$

lemma *neg-equal-iff-equal* [simp]: $(-a = -b) = (a = (b::'a::ab\text{-group-add}))$
 $\langle proof \rangle$

lemma *neg-equal-0-iff-equal* [simp]: $(-a = 0) = (a = (0::'a::ab\text{-group-add}))$
 $\langle proof \rangle$

lemma *neg-0-equal-iff-equal* [simp]: $(0 = -a) = (0 = (a::'a::ab\text{-group-add}))$
 $\langle proof \rangle$

The next two equations can make the simplifier loop!

lemma *equation-minus-iff*: $(a = -b) = (b = -(a::'a::ab\text{-group-add}))$
 $\langle proof \rangle$

lemma *minus-equation-iff*: $(-a = b) = (- (b::'a::ab\text{-group-add}) = a)$
 $\langle proof \rangle$

lemma *minus-add-distrib* [simp]: $-(a + b) = -a + -(b::'a::ab\text{-group-add})$
 $\langle proof \rangle$

lemma *minus-diff-eq* [simp]: $-(a - b) = b - (a::'a::ab\text{-group-add})$
 $\langle proof \rangle$

14.2 (Partially) Ordered Groups

axclass *pordered-ab-semigroup-add* \subseteq *order*, *ab-semigroup-add*
add-left-mono: $a \leq b \implies c + a \leq c + b$

axclass *pordered-cancel-ab-semigroup-add* \subseteq *pordered-ab-semigroup-add*, *cancel-ab-semigroup-add*

instance *pordered-cancel-ab-semigroup-add* \subseteq *pordered-ab-semigroup-add* $\langle proof \rangle$

axclass *pordered-ab-semigroup-add-imp-le* \subseteq *pordered-cancel-ab-semigroup-add*
add-le-imp-le-left: $c + a \leq c + b \implies a \leq b$

axclass *pordered-ab-group-add* \subseteq *ab-group-add*, *pordered-ab-semigroup-add*

instance *pordered-ab-group-add* \subseteq *pordered-ab-semigroup-add-imp-le*
 \langle *proof* \rangle

axclass *ordered-cancel-ab-semigroup-add* \subseteq *pordered-cancel-ab-semigroup-add*, *linorder*

instance *ordered-cancel-ab-semigroup-add* \subseteq *pordered-ab-semigroup-add-imp-le*
 \langle *proof* \rangle

lemma *add-right-mono*: $a \leq (b::'a::\text{pordered-ab-semigroup-add}) \implies a + c \leq b + c$
 \langle *proof* \rangle

non-strict, in both arguments

lemma *add-mono*:
 $[| a \leq b; c \leq d |] \implies a + c \leq b + (d::'a::\text{pordered-ab-semigroup-add})$
 \langle *proof* \rangle

lemma *add-strict-left-mono*:
 $a < b \implies c + a < c + (b::'a::\text{pordered-cancel-ab-semigroup-add})$
 \langle *proof* \rangle

lemma *add-strict-right-mono*:
 $a < b \implies a + c < b + (c::'a::\text{pordered-cancel-ab-semigroup-add})$
 \langle *proof* \rangle

Strict monotonicity in both arguments

lemma *add-strict-mono*: $[| a < b; c < d |] \implies a + c < b + (d::'a::\text{pordered-cancel-ab-semigroup-add})$
 \langle *proof* \rangle

lemma *add-less-le-mono*:
 $[| a < b; c \leq d |] \implies a + c < b + (d::'a::\text{pordered-cancel-ab-semigroup-add})$
 \langle *proof* \rangle

lemma *add-le-less-mono*:
 $[| a \leq b; c < d |] \implies a + c < b + (d::'a::\text{pordered-cancel-ab-semigroup-add})$
 \langle *proof* \rangle

lemma *add-less-imp-less-left*:
assumes *less*: $c + a < c + b$ **shows** $a < (b::'a::\text{pordered-ab-semigroup-add-imp-le})$
 \langle *proof* \rangle

lemma *add-less-imp-less-right*:
 $a + c < b + c \implies a < (b::'a::\text{pordered-ab-semigroup-add-imp-le})$
 \langle *proof* \rangle

lemma *add-less-cancel-left* [simp]:

$(c+a < c+b) = (a < (b::'a::\text{pordered-ab-semigroup-add-imp-le}))$
 $\langle \text{proof} \rangle$

lemma *add-less-cancel-right* [simp]:

$(a+c < b+c) = (a < (b::'a::\text{pordered-ab-semigroup-add-imp-le}))$
 $\langle \text{proof} \rangle$

lemma *add-le-cancel-left* [simp]:

$(c+a \leq c+b) = (a \leq (b::'a::\text{pordered-ab-semigroup-add-imp-le}))$
 $\langle \text{proof} \rangle$

lemma *add-le-cancel-right* [simp]:

$(a+c \leq b+c) = (a \leq (b::'a::\text{pordered-ab-semigroup-add-imp-le}))$
 $\langle \text{proof} \rangle$

lemma *add-le-imp-le-right*:

$a + c \leq b + c \implies a \leq (b::'a::\text{pordered-ab-semigroup-add-imp-le})$
 $\langle \text{proof} \rangle$

lemma *add-increasing*:

fixes $c :: 'a::\{\text{pordered-ab-semigroup-add-imp-le}, \text{comm-monoid-add}\}$
shows $[[0 \leq a; b \leq c]] \implies b \leq a + c$
 $\langle \text{proof} \rangle$

lemma *add-increasing2*:

fixes $c :: 'a::\{\text{pordered-ab-semigroup-add-imp-le}, \text{comm-monoid-add}\}$
shows $[[0 \leq c; b \leq a]] \implies b \leq a + c$
 $\langle \text{proof} \rangle$

lemma *add-strict-increasing*:

fixes $c :: 'a::\{\text{pordered-ab-semigroup-add-imp-le}, \text{comm-monoid-add}\}$
shows $[[0 < a; b \leq c]] \implies b < a + c$
 $\langle \text{proof} \rangle$

lemma *add-strict-increasing2*:

fixes $c :: 'a::\{\text{pordered-ab-semigroup-add-imp-le}, \text{comm-monoid-add}\}$
shows $[[0 \leq a; b < c]] \implies b < a + c$
 $\langle \text{proof} \rangle$

14.3 Ordering Rules for Unary Minus

lemma *le-imp-neg-le*:

assumes $a \leq (b::'a::\{\text{pordered-ab-semigroup-add-imp-le}, \text{ab-group-add}\})$ **shows**
 $-b \leq -a$
 $\langle \text{proof} \rangle$

lemma *neg-le-iff-le* [simp]: $(-b \leq -a) = (a \leq (b::'a::\text{pordered-ab-group-add}))$

$\langle proof \rangle$

lemma *neg-le-0-iff-le* [simp]: $(-a \leq 0) = (0 \leq (a::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *neg-0-le-iff-le* [simp]: $(0 \leq -a) = (a \leq (0::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *neg-less-iff-less* [simp]: $(-b < -a) = (a < (b::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *neg-less-0-iff-less* [simp]: $(-a < 0) = (0 < (a::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *neg-0-less-iff-less* [simp]: $(0 < -a) = (a < (0::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

The next several equations can make the simplifier loop!

lemma *less-minus-iff*: $(a < -b) = (b < -(a::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *minus-less-iff*: $(-a < b) = (-b < (a::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *le-minus-iff*: $(a \leq -b) = (b \leq -(a::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *minus-le-iff*: $(-a \leq b) = (-b \leq (a::'a::pordered-ab-group-add))$
 $\langle proof \rangle$

lemma *add-diff-eq*: $a + (b - c) = (a + b) - (c::'a::ab-group-add)$
 $\langle proof \rangle$

lemma *diff-add-eq*: $(a - b) + c = (a + c) - (b::'a::ab-group-add)$
 $\langle proof \rangle$

lemma *diff-eq-eq*: $(a - b = c) = (a = c + (b::'a::ab-group-add))$
 $\langle proof \rangle$

lemma *eq-diff-eq*: $(a = c - b) = (a + (b::'a::ab-group-add) = c)$
 $\langle proof \rangle$

lemma *diff-diff-eq*: $(a - b) - c = a - (b + (c::'a::ab-group-add))$
 $\langle proof \rangle$

lemma *diff-diff-eq2*: $a - (b - c) = (a + c) - (b::'a::ab-group-add)$
 $\langle proof \rangle$

lemma *diff-add-cancel*: $a - b + b = (a::'a::ab-group-add)$

$\langle \text{proof} \rangle$

lemma *add-diff-cancel*: $a + b - b = (a::'a::\text{ab-group-add})$
 $\langle \text{proof} \rangle$

Further subtraction laws

lemma *less-iff-diff-less-0*: $(a < b) = (a - b < (0::'a::\text{pordered-ab-group-add}))$
 $\langle \text{proof} \rangle$

lemma *diff-less-eq*: $(a - b < c) = (a < c + (b::'a::\text{pordered-ab-group-add}))$
 $\langle \text{proof} \rangle$

lemma *less-diff-eq*: $(a < c - b) = (a + (b::'a::\text{pordered-ab-group-add}) < c)$
 $\langle \text{proof} \rangle$

lemma *diff-le-eq*: $(a - b \leq c) = (a \leq c + (b::'a::\text{pordered-ab-group-add}))$
 $\langle \text{proof} \rangle$

lemma *le-diff-eq*: $(a \leq c - b) = (a + (b::'a::\text{pordered-ab-group-add}) \leq c)$
 $\langle \text{proof} \rangle$

This list of rewrites simplifies (in)equalities by bringing subtractions to the top and then moving negative terms to the other side. Use with *add-ac*

lemmas *compare-rls* =
diff-minus [symmetric]
add-diff-eq *diff-add-eq* *diff-diff-eq* *diff-diff-eq2*
diff-less-eq *less-diff-eq* *diff-le-eq* *le-diff-eq*
diff-eq-eq *eq-diff-eq*

14.4 Support for reasoning about signs

lemma *add-pos-pos*: $0 <$
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\})$
 $\implies 0 < y \implies 0 < x + y$
 $\langle \text{proof} \rangle$

lemma *add-pos-nonneg*: $0 <=$
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\})$
 $\implies 0 <= y \implies 0 < x + y$
 $\langle \text{proof} \rangle$

lemma *add-nonneg-pos*: $0 <=$
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\})$
 $\implies 0 < y \implies 0 < x + y$
 $\langle \text{proof} \rangle$

lemma *add-nonneg-nonneg*: $0 <=$
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\})$
 $\implies 0 <= y \implies 0 <= x + y$

$\langle \text{proof} \rangle$

lemma *add-neg-neg*: $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\})$
 $< 0 \implies y < 0 \implies x + y < 0$
 $\langle \text{proof} \rangle$

lemma *add-neg-nonpos*:
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\}) < 0$
 $\implies y \leq 0 \implies x + y < 0$
 $\langle \text{proof} \rangle$

lemma *add-nonpos-neg*:
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\}) \leq 0$
 $\implies y < 0 \implies x + y < 0$
 $\langle \text{proof} \rangle$

lemma *add-nonpos-nonpos*:
 $(x::'a::\{\text{comm-monoid-add}, \text{pordered-cancel-ab-semigroup-add}\}) \leq 0$
 $\implies y \leq 0 \implies x + y \leq 0$
 $\langle \text{proof} \rangle$

14.5 Lemmas for the *cancel-numerals* *simproc*

lemma *eq-iff-diff-eq-0*: $(a = b) = (a - b = (0::'a::\text{ab-group-add}))$
 $\langle \text{proof} \rangle$

lemma *le-iff-diff-le-0*: $(a \leq b) = (a - b \leq (0::'a::\text{pordered-ab-group-add}))$
 $\langle \text{proof} \rangle$

14.6 Lattice Ordered (Abelian) Groups

axclass *lordered-ab-group-meet* $< \text{pordered-ab-group-add}, \text{meet-semilorder}$

axclass *lordered-ab-group-join* $< \text{pordered-ab-group-add}, \text{join-semilorder}$

lemma *add-meet-distrib-left*: $a + (\text{meet } b \ c) = \text{meet } (a + b) \ (a + (c::'a::\{\text{pordered-ab-group-add}, \text{meet-semilorder}\}))$
 $\langle \text{proof} \rangle$

lemma *add-join-distrib-left*: $a + (\text{join } b \ c) = \text{join } (a + b) \ (a + (c::'a::\{\text{pordered-ab-group-add}, \text{join-semilorder}\}))$
 $\langle \text{proof} \rangle$

lemma *is-join-neg-meet*: $\text{is-join } (\% (a::'a::\{\text{pordered-ab-group-add}, \text{meet-semilorder}\})$
 $b. - (\text{meet } (-a) \ (-b)))$
 $\langle \text{proof} \rangle$

lemma *is-meet-neg-join*: $\text{is-meet } (\% (a::'a::\{\text{pordered-ab-group-add}, \text{join-semilorder}\})$
 $b. - (\text{join } (-a) \ (-b)))$
 $\langle \text{proof} \rangle$

axclass *lordered-ab-group* \subseteq *pordered-ab-group-add*, *lorder*

instance *lordered-ab-group-meet* \subseteq *lordered-ab-group*
 $\langle proof \rangle$

instance *lordered-ab-group-join* \subseteq *lordered-ab-group*
 $\langle proof \rangle$

lemma *add-join-distrib-right*: $(join\ a\ b) + (c::'a::lordered-ab-group) = join\ (a+c)\ (b+c)$
 $\langle proof \rangle$

lemma *add-meet-distrib-right*: $(meet\ a\ b) + (c::'a::lordered-ab-group) = meet\ (a+c)\ (b+c)$
 $\langle proof \rangle$

lemmas *add-meet-join-distrib* = *add-meet-distrib-right add-meet-distrib-left add-join-distrib-right add-join-distrib-left*

lemma *join-eq-neg-meet*: $join\ a\ (b::'a::lordered-ab-group) = -\ meet\ (-a)\ (-b)$
 $\langle proof \rangle$

lemma *meet-eq-neg-join*: $meet\ a\ (b::'a::lordered-ab-group) = -\ join\ (-a)\ (-b)$
 $\langle proof \rangle$

lemma *add-eq-meet-join*: $a + b = (join\ a\ b) + (meet\ a\ (b::'a::lordered-ab-group))$
 $\langle proof \rangle$

14.7 Positive Part, Negative Part, Absolute Value

constdefs
 $pprt :: 'a \Rightarrow ('a::lordered-ab-group)$
 $pprt\ x == join\ x\ 0$
 $nprr :: 'a \Rightarrow ('a::lordered-ab-group)$
 $nprr\ x == meet\ x\ 0$

lemma *prts*: $a = pprt\ a + nprr\ a$
 $\langle proof \rangle$

lemma *zero-le-pprt[simp]*: $0 \leq pprt\ a$
 $\langle proof \rangle$

lemma *nprr-le-zero[simp]*: $nprr\ a \leq 0$
 $\langle proof \rangle$

lemma *le-eq-neg*: $(a \leq -b) = (a + b \leq (0::'a::lordered-ab-group))$ (is ?l = ?r)
 $\langle proof \rangle$

lemma *pprt-0[simp]*: $\text{pprt } 0 = 0$ *<proof>*

lemma *nprrt-0[simp]*: $\text{nprrt } 0 = 0$ *<proof>*

lemma *pprt-eq-id[simp]*: $0 \leq x \implies \text{pprt } x = x$
<proof>

lemma *nprrt-eq-id[simp]*: $x \leq 0 \implies \text{nprrt } x = x$
<proof>

lemma *pprt-eq-0[simp]*: $x \leq 0 \implies \text{pprt } x = 0$
<proof>

lemma *nprrt-eq-0[simp]*: $0 \leq x \implies \text{nprrt } x = 0$
<proof>

lemma *join-0-imp-0*: $\text{join } a \ (-a) = 0 \implies a = (0::'a::\text{lordered-ab-group})$
<proof>

lemma *meet-0-imp-0*: $\text{meet } a \ (-a) = 0 \implies a = (0::'a::\text{lordered-ab-group})$
<proof>

lemma *join-0-eq-0[simp]*: $(\text{join } a \ (-a) = 0) = (a = (0::'a::\text{lordered-ab-group}))$
<proof>

lemma *meet-0-eq-0[simp]*: $(\text{meet } a \ (-a) = 0) = (a = (0::'a::\text{lordered-ab-group}))$
<proof>

lemma *zero-le-double-add-iff-zero-le-single-add[simp]*: $(0 \leq a + a) = (0 \leq (a::'a::\text{lordered-ab-group}))$
<proof>

lemma *double-add-le-zero-iff-single-add-le-zero[simp]*: $(a + a \leq 0) = ((a::'a::\text{lordered-ab-group}) \leq 0)$
<proof>

lemma *double-add-less-zero-iff-single-less-zero[simp]*: $(a + a < 0) = ((a::'a::\{\text{pordered-ab-group-add}, \text{linorder}\}) < 0)$ *(is ?s)*
<proof>

axclass *lordered-ab-group-abs* \subseteq *lordered-ab-group*
abs-lattice: $\text{abs } x = \text{join } x \ (-x)$

lemma *abs-zero[simp]*: $\text{abs } 0 = (0::'a::\text{lordered-ab-group-abs})$
<proof>

lemma *abs-eq-0[simp]*: $(\text{abs } a = 0) = (a = (0::'a::\text{lordered-ab-group-abs}))$
<proof>

lemma *abs-0-eq[simp]*: $(0 = \text{abs } a) = (a = (0::'a::\text{lordered-ab-group-abs}))$
<proof>

lemma *neg-meet-eq-join*[simp]: $- \text{meet } a \ (b::\text{ordered-ab-group}) = \text{join } (-a)$
 $(-b)$
 $\langle \text{proof} \rangle$

lemma *neg-join-eq-meet*[simp]: $- \text{join } a \ (b::\text{ordered-ab-group}) = \text{meet } (-a)$
 $(-b)$
 $\langle \text{proof} \rangle$

lemma *join-eq-if*: $\text{join } a \ (-a) = (\text{if } a < 0 \text{ then } -a \text{ else } (a::'a::\{\text{ordered-ab-group}, \text{linorder}\}))$
 $\langle \text{proof} \rangle$

lemma *abs-if-lattice*: $|a| = (\text{if } a < 0 \text{ then } -a \text{ else } (a::'a::\{\text{ordered-ab-group-abs}, \text{linorder}\}))$
 $\langle \text{proof} \rangle$

lemma *abs-ge-zero*[simp]: $0 \leq \text{abs } (a::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *abs-le-zero-iff* [simp]: $(\text{abs } a \leq (0::'a::\text{ordered-ab-group-abs})) = (a = 0)$
 $\langle \text{proof} \rangle$

lemma *zero-less-abs-iff* [simp]: $(0 < \text{abs } a) = (a \neq (0::'a::\text{ordered-ab-group-abs}))$
 $\langle \text{proof} \rangle$

lemma *abs-not-less-zero* [simp]: $\sim \text{abs } a < (0::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *abs-ge-self*: $a \leq \text{abs } (a::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *abs-ge-minus-self*: $-a \leq \text{abs } (a::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *le-imp-join-eq*: $a \leq b \implies \text{join } a \ b = b$
 $\langle \text{proof} \rangle$

lemma *ge-imp-join-eq*: $b \leq a \implies \text{join } a \ b = a$
 $\langle \text{proof} \rangle$

lemma *le-imp-meet-eq*: $a \leq b \implies \text{meet } a \ b = a$
 $\langle \text{proof} \rangle$

lemma *ge-imp-meet-eq*: $b \leq a \implies \text{meet } a \ b = b$
 $\langle \text{proof} \rangle$

lemma *abs-prts*: $\text{abs } (a::\text{ordered-ab-group-abs}) = \text{pprt } a - \text{nprrt } a$
 $\langle \text{proof} \rangle$

lemma *abs-minus-cancel* [simp]: $\text{abs } (-a) = \text{abs } (a::'a::\text{ordered-ab-group-abs})$
 <proof>

lemma *abs-idempotent* [simp]: $\text{abs } (\text{abs } a) = \text{abs } (a::'a::\text{ordered-ab-group-abs})$
 <proof>

lemma *abs-minus-commute*:
 fixes $a :: 'a::\text{ordered-ab-group-abs}$
 shows $\text{abs } (a-b) = \text{abs } (b-a)$
 <proof>

lemma *zero-le-iff-zero-nprt*: $(0 \leq a) = (\text{nprt } a = 0)$
 <proof>

lemma *le-zero-iff-zero-pprt*: $(a \leq 0) = (\text{pprt } a = 0)$
 <proof>

lemma *le-zero-iff-pprt-id*: $(0 \leq a) = (\text{pprt } a = a)$
 <proof>

lemma *zero-le-iff-nprt-id*: $(a \leq 0) = (\text{nprt } a = a)$
 <proof>

lemma *pprt-mono*[simp]: $(a::'\text{ordered-ab-group}) \leq b \implies \text{pprt } a \leq \text{pprt } b$
 <proof>

lemma *nprt-mono*[simp]: $(a::'\text{ordered-ab-group}) \leq b \implies \text{nprt } a \leq \text{nprt } b$
 <proof>

lemma *iff2imp*: $(A=B) \implies (A \implies B)$
 <proof>

lemma *abs-of-nonneg* [simp]: $0 \leq a \implies \text{abs } a = (a::'a::\text{ordered-ab-group-abs})$
 <proof>

lemma *abs-of-pos*: $0 < (x::'a::\text{ordered-ab-group-abs}) \implies \text{abs } x = x$
 <proof>

lemma *abs-of-nonpos* [simp]: $a \leq 0 \implies \text{abs } a = -(a::'a::\text{ordered-ab-group-abs})$
 <proof>

lemma *abs-of-neg*: $(x::'a::\text{ordered-ab-group-abs}) < 0 \implies$
 $\text{abs } x = -x$
 <proof>

lemma *abs-leI*: $[|a \leq b; -a \leq b|] \implies \text{abs } a \leq (b::'a::\text{ordered-ab-group-abs})$
 <proof>

lemma *le-minus-self-iff*: $(a \leq -a) = (a \leq (0::'a::\text{ordered-ab-group}))$
 $\langle \text{proof} \rangle$

lemma *minus-le-self-iff*: $(-a \leq a) = (0 \leq (a::'a::\text{ordered-ab-group}))$
 $\langle \text{proof} \rangle$

lemma *abs-le-D1*: $\text{abs } a \leq b \implies a \leq (b::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *abs-le-D2*: $\text{abs } a \leq b \implies -a \leq (b::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *abs-le-iff*: $(\text{abs } a \leq b) = (a \leq b \ \& \ -a \leq (b::'a::\text{ordered-ab-group-abs}))$
 $\langle \text{proof} \rangle$

lemma *abs-triangle-ineq*: $\text{abs}(a+b) \leq \text{abs } a + \text{abs}(b::'a::\text{ordered-ab-group-abs})$
 $\langle \text{proof} \rangle$

lemma *abs-triangle-ineq2*: $\text{abs } (a::'a::\text{ordered-ab-group-abs}) - \text{abs } b \leq \text{abs } (a - b)$
 $\langle \text{proof} \rangle$

lemma *abs-triangle-ineq3*:
 $\text{abs}(\text{abs } (a::'a::\text{ordered-ab-group-abs}) - \text{abs } b) \leq \text{abs } (a - b)$
 $\langle \text{proof} \rangle$

lemma *abs-triangle-ineq4*: $\text{abs } ((a::'a::\text{ordered-ab-group-abs}) - b) \leq \text{abs } a + \text{abs } b$
 $\langle \text{proof} \rangle$

lemma *abs-diff-triangle-ineq*:
 $|(a::'a::\text{ordered-ab-group-abs}) + b - (c+d)| \leq |a-c| + |b-d|$
 $\langle \text{proof} \rangle$

lemma *abs-add-abs[simp]*:
fixes $a::'a::\{\text{ordered-ab-group-abs}\}$
shows $\text{abs}(\text{abs } a + \text{abs } b) = \text{abs } a + \text{abs } b$ (**is** ?L = ?R)
 $\langle \text{proof} \rangle$

Needed for abelian cancellation simprocs:

lemma *add-cancel-21*: $((x::'a::\text{ab-group-add}) + (y + z) = y + u) = (x + z = u)$
 $\langle \text{proof} \rangle$

lemma *add-cancel-end*: $(x + (y + z) = y) = (x = - (z::'a::\text{ab-group-add}))$
 $\langle \text{proof} \rangle$

lemma *less-eqI*: $(x::'a::\text{pordered-ab-group-add}) - y = x' - y' \implies (x < y) = (x' < y')$
 $\langle \text{proof} \rangle$

lemma *le-eqI*: $(x::'a::\text{pordered-ab-group-add}) - y = x' - y' \implies (y \leq x) = (y' \leq x')$
 $\langle \text{proof} \rangle$

lemma *eq-eqI*: $(x::'a::\text{ab-group-add}) - y = x' - y' \implies (x = y) = (x' = y')$
 $\langle \text{proof} \rangle$

lemma *diff-def*: $(x::'a::\text{ab-group-add}) - y == x + (-y)$
 $\langle \text{proof} \rangle$

lemma *add-minus-cancel*: $(a::'a::\text{ab-group-add}) + (-a + b) = b$
 $\langle \text{proof} \rangle$

lemma *minus-add-cancel*: $-(a::'a::\text{ab-group-add}) + (a + b) = b$
 $\langle \text{proof} \rangle$

lemma *le-add-right-mono*:
assumes
 $a \leq b + (c::'a::\text{pordered-ab-group-add})$
 $c \leq d$
shows $a \leq b + d$
 $\langle \text{proof} \rangle$

lemmas *group-eq-simps* =
mult-ac
add-ac
add-diff-eq *diff-add-eq* *diff-diff-eq* *diff-diff-eq2*
diff-eq-eq *eq-diff-eq*

lemma *estimate-by-abs*:
 $a + b \leq (c::'a::\text{lordered-ab-group-abs}) \implies a \leq c + \text{abs } b$
 $\langle \text{proof} \rangle$

Simplification of $x - y < (0::'a)$, etc.

lemmas *diff-less-0-iff-less* = *less-iff-diff-less-0* [*symmetric*]
lemmas *diff-eq-0-iff-eq* = *eq-iff-diff-eq-0* [*symmetric*]
lemmas *diff-le-0-iff-le* = *le-iff-diff-le-0* [*symmetric*]
declare *diff-less-0-iff-less* [*simp*]
declare *diff-eq-0-iff-eq* [*simp*]
declare *diff-le-0-iff-le* [*simp*]

$\langle \text{ML} \rangle$

end

15 Ring-and-Field: (Ordered) Rings and Fields

```
theory Ring-and-Field
imports OrderedGroup
begin
```

The theory of partially ordered rings is taken from the books:

- *Lattice Theory* by Garret Birkhoff, American Mathematical Society 1979
- *Partially Ordered Algebraic Systems*, Pergamon Press 1963

Most of the used notions can also be looked up in

- <http://www.mathworld.com> by Eric Weisstein et. al.
- *Algebra I* by van der Waerden, Springer.

```
axclass semiring ⊆ ab-semigroup-add, semigroup-mult
  left-distrib:  $(a + b) * c = a * c + b * c$ 
  right-distrib:  $a * (b + c) = a * b + a * c$ 
```

```
axclass semiring-0 ⊆ semiring, comm-monoid-add
```

```
axclass semiring-0-cancel ⊆ semiring-0, cancel-ab-semigroup-add
```

```
axclass comm-semiring ⊆ ab-semigroup-add, ab-semigroup-mult
  distrib:  $(a + b) * c = a * c + b * c$ 
```

```
instance comm-semiring ⊆ semiring
⟨proof⟩
```

```
axclass comm-semiring-0 ⊆ comm-semiring, comm-monoid-add
```

```
instance comm-semiring-0 ⊆ semiring-0 ⟨proof⟩
```

```
axclass comm-semiring-0-cancel ⊆ comm-semiring-0, cancel-ab-semigroup-add
```

```
instance comm-semiring-0-cancel ⊆ semiring-0-cancel ⟨proof⟩
```

```
axclass axclass-0-neq-1 ⊆ zero, one
  zero-neq-one [simp]:  $0 \neq 1$ 
```

```
axclass semiring-1 ⊆ axclass-0-neq-1, semiring-0, monoid-mult
```

```
axclass comm-semiring-1 ⊆ axclass-0-neq-1, comm-semiring-0, comm-monoid-mult
```

```
instance comm-semiring-1 ⊆ semiring-1 ⟨proof⟩
```

```

axclass axclass-no-zero-divisors  $\subseteq$  zero, times
  no-zero-divisors:  $a \neq 0 \implies b \neq 0 \implies a * b \neq 0$ 

axclass semiring-1-cancel  $\subseteq$  semiring-1, cancel-ab-semigroup-add

instance semiring-1-cancel  $\subseteq$  semiring-0-cancel  $\langle$ proof $\rangle$ 

axclass comm-semiring-1-cancel  $\subseteq$  comm-semiring-1, cancel-ab-semigroup-add

instance comm-semiring-1-cancel  $\subseteq$  semiring-1-cancel  $\langle$ proof $\rangle$ 

instance comm-semiring-1-cancel  $\subseteq$  comm-semiring-0-cancel  $\langle$ proof $\rangle$ 

axclass ring  $\subseteq$  semiring, ab-group-add

instance ring  $\subseteq$  semiring-0-cancel  $\langle$ proof $\rangle$ 

axclass comm-ring  $\subseteq$  comm-semiring-0, ab-group-add

instance comm-ring  $\subseteq$  ring  $\langle$ proof $\rangle$ 

instance comm-ring  $\subseteq$  comm-semiring-0-cancel  $\langle$ proof $\rangle$ 

axclass ring-1  $\subseteq$  ring, semiring-1

instance ring-1  $\subseteq$  semiring-1-cancel  $\langle$ proof $\rangle$ 

axclass comm-ring-1  $\subseteq$  comm-ring, comm-semiring-1

instance comm-ring-1  $\subseteq$  ring-1  $\langle$ proof $\rangle$ 

instance comm-ring-1  $\subseteq$  comm-semiring-1-cancel  $\langle$ proof $\rangle$ 

axclass idom  $\subseteq$  comm-ring-1, axclass-no-zero-divisors

axclass field  $\subseteq$  comm-ring-1, inverse
  left-inverse [simp]:  $a \neq 0 \implies \text{inverse } a * a = 1$ 
  divide-inverse:  $a / b = a * \text{inverse } b$ 

lemma mult-zero-left [simp]:  $0 * a = (0::'a::\text{semiring-0-cancel})$ 
 $\langle$ proof $\rangle$ 

lemma mult-zero-right [simp]:  $a * 0 = (0::'a::\text{semiring-0-cancel})$ 
 $\langle$ proof $\rangle$ 

lemma field-mult-eq-0-iff [simp]:  $(a * b = (0::'a::\text{field})) = (a = 0 \mid b = 0)$ 
 $\langle$ proof $\rangle$ 

```

instance *field* \subseteq *idom*
 $\langle \text{proof} \rangle$

axclass *division-by-zero* \subseteq *zero*, *inverse*
inverse-zero [*simp*]: *inverse* 0 = 0

15.1 Distribution rules

theorems *ring-distrib* = *right-distrib* *left-distrib*

For the *combine-numerals* *simproc*

lemma *combine-common-factor*:
 $a * e + (b * e + c) = (a + b) * e + (c :: 'a :: \text{semiring})$
 $\langle \text{proof} \rangle$

lemma *minus-mult-left*: $-(a * b) = (-a) * (b :: 'a :: \text{ring})$
 $\langle \text{proof} \rangle$

lemma *minus-mult-right*: $-(a * b) = a * -(b :: 'a :: \text{ring})$
 $\langle \text{proof} \rangle$

lemma *minus-mult-minus* [*simp*]: $(-a) * (-b) = a * (b :: 'a :: \text{ring})$
 $\langle \text{proof} \rangle$

lemma *minus-mult-commute*: $(-a) * b = a * (-b :: 'a :: \text{ring})$
 $\langle \text{proof} \rangle$

lemma *right-diff-distrib*: $a * (b - c) = a * b - a * (c :: 'a :: \text{ring})$
 $\langle \text{proof} \rangle$

lemma *left-diff-distrib*: $(a - b) * c = a * c - b * (c :: 'a :: \text{ring})$
 $\langle \text{proof} \rangle$

axclass *pordered-semiring* \subseteq *semiring-0*, *pordered-ab-semigroup-add*
mult-left-mono: $a \leq b \implies 0 \leq c \implies c * a \leq c * b$
mult-right-mono: $a \leq b \implies 0 \leq c \implies a * c \leq b * c$

axclass *pordered-cancel-semiring* \subseteq *pordered-semiring*, *cancel-ab-semigroup-add*

instance *pordered-cancel-semiring* \subseteq *semiring-0-cancel* $\langle \text{proof} \rangle$

axclass *ordered-semiring-strict* \subseteq *semiring-0*, *ordered-cancel-ab-semigroup-add*
mult-strict-left-mono: $a < b \implies 0 < c \implies c * a < c * b$
mult-strict-right-mono: $a < b \implies 0 < c \implies a * c < b * c$

instance *ordered-semiring-strict* \subseteq *semiring-0-cancel* $\langle \text{proof} \rangle$

instance *ordered-semiring-strict* \subseteq *pordered-cancel-semiring*
 $\langle \text{proof} \rangle$

```

axclass pordered-comm-semiring  $\subseteq$  comm-semiring-0, pordered-ab-semigroup-add
  mult-mono:  $a \leq b \implies 0 \leq c \implies c * a \leq c * b$ 

axclass pordered-cancel-comm-semiring  $\subseteq$  pordered-comm-semiring, cancel-ab-semigroup-add

instance pordered-cancel-comm-semiring  $\subseteq$  pordered-comm-semiring <proof>

axclass ordered-comm-semiring-strict  $\subseteq$  comm-semiring-0, ordered-cancel-ab-semigroup-add
  mult-strict-mono:  $a < b \implies 0 < c \implies c * a < c * b$ 

instance pordered-comm-semiring  $\subseteq$  pordered-semiring
  <proof>

instance pordered-cancel-comm-semiring  $\subseteq$  pordered-cancel-semiring <proof>

instance ordered-comm-semiring-strict  $\subseteq$  ordered-semiring-strict
  <proof>

instance ordered-comm-semiring-strict  $\subseteq$  pordered-cancel-comm-semiring
  <proof>

axclass pordered-ring  $\subseteq$  ring, pordered-semiring

instance pordered-ring  $\subseteq$  pordered-ab-group-add <proof>

instance pordered-ring  $\subseteq$  pordered-cancel-semiring <proof>

axclass lordered-ring  $\subseteq$  pordered-ring, lordered-ab-group-abs

instance lordered-ring  $\subseteq$  lordered-ab-group-meet <proof>

instance lordered-ring  $\subseteq$  lordered-ab-group-join <proof>

axclass axclass-abs-if  $\subseteq$  minus, ord, zero
  abs-if:  $\text{abs } a = (\text{if } (a < 0) \text{ then } (-a) \text{ else } a)$ 

axclass ordered-ring-strict  $\subseteq$  ring, ordered-semiring-strict, axclass-abs-if

instance ordered-ring-strict  $\subseteq$  lordered-ab-group <proof>

instance ordered-ring-strict  $\subseteq$  lordered-ring
  <proof>

axclass pordered-comm-ring  $\subseteq$  comm-ring, pordered-comm-semiring

axclass ordered-semidom  $\subseteq$  comm-semiring-1-cancel, ordered-comm-semiring-strict

  zero-less-one [simp]:  $0 < 1$ 

```

axclass *ordered-idom* \subseteq *comm-ring-1*, *ordered-comm-semiring-strict*, *axclass-abs-if*

instance *ordered-idom* \subseteq *ordered-ring-strict* \langle proof \rangle

axclass *ordered-field* \subseteq *field*, *ordered-idom*

lemmas *linorder-neqE-ordered-idom* =
linorder-neqE[**where** 'a = ?'b::*ordered-idom*]

lemma *eq-add-iff1*:
 $(a * e + c = b * e + d) = ((a - b) * e + c = (d :: 'a :: ring))$
 \langle proof \rangle

lemma *eq-add-iff2*:
 $(a * e + c = b * e + d) = (c = (b - a) * e + (d :: 'a :: ring))$
 \langle proof \rangle

lemma *less-add-iff1*:
 $(a * e + c < b * e + d) = ((a - b) * e + c < (d :: 'a :: pordered-ring))$
 \langle proof \rangle

lemma *less-add-iff2*:
 $(a * e + c < b * e + d) = (c < (b - a) * e + (d :: 'a :: pordered-ring))$
 \langle proof \rangle

lemma *le-add-iff1*:
 $(a * e + c \leq b * e + d) = ((a - b) * e + c \leq (d :: 'a :: pordered-ring))$
 \langle proof \rangle

lemma *le-add-iff2*:
 $(a * e + c \leq b * e + d) = (c \leq (b - a) * e + (d :: 'a :: pordered-ring))$
 \langle proof \rangle

15.2 Ordering Rules for Multiplication

lemma *mult-left-le-imp-le*:
 $[|c * a \leq c * b; 0 < c|] ==> a \leq (b :: 'a :: ordered-semiring-strict)$
 \langle proof \rangle

lemma *mult-right-le-imp-le*:
 $[|a * c \leq b * c; 0 < c|] ==> a \leq (b :: 'a :: ordered-semiring-strict)$
 \langle proof \rangle

lemma *mult-left-less-imp-less*:
 $[|c * a < c * b; 0 \leq c|] ==> a < (b :: 'a :: ordered-semiring-strict)$
 \langle proof \rangle

lemma *mult-right-less-imp-less*:

$$[[a * c < b * c; 0 \leq c]] ==> a < (b :: 'a :: \text{ordered-semiring-strict})$$

<proof>

lemma *mult-strict-left-mono-neg*:

$$[[b < a; c < 0]] ==> c * a < c * (b :: 'a :: \text{ordered-ring-strict})$$

<proof>

lemma *mult-left-mono-neg*:

$$[[b \leq a; c \leq 0]] ==> c * a \leq c * (b :: 'a :: \text{pordered-ring})$$

<proof>

lemma *mult-strict-right-mono-neg*:

$$[[b < a; c < 0]] ==> a * c < b * (c :: 'a :: \text{ordered-ring-strict})$$

<proof>

lemma *mult-right-mono-neg*:

$$[[b \leq a; c \leq 0]] ==> a * c \leq (b :: 'a :: \text{pordered-ring}) * c$$

<proof>

15.3 Products of Signs

lemma *mult-pos-pos*: $[[(0 :: 'a :: \text{ordered-semiring-strict}) < a; 0 < b]] ==> 0 < a * b$

<proof>

lemma *mult-nonneg-nonneg*: $[[(0 :: 'a :: \text{pordered-cancel-semiring}) \leq a; 0 \leq b]] ==> 0 \leq a * b$

<proof>

lemma *mult-pos-neg*: $[[(0 :: 'a :: \text{ordered-semiring-strict}) < a; b < 0]] ==> a * b < 0$

<proof>

lemma *mult-nonneg-nonpos*: $[[(0 :: 'a :: \text{pordered-cancel-semiring}) \leq a; b \leq 0]] ==> a * b \leq 0$

<proof>

lemma *mult-pos-neg2*: $[[(0 :: 'a :: \text{ordered-semiring-strict}) < a; b < 0]] ==> b * a < 0$

<proof>

lemma *mult-nonneg-nonpos2*: $[[(0 :: 'a :: \text{pordered-cancel-semiring}) \leq a; b \leq 0]] ==> b * a \leq 0$

<proof>

lemma *mult-neg-neg*: $[[a < (0 :: 'a :: \text{ordered-ring-strict}); b < 0]] ==> 0 < a * b$

<proof>

lemma *mult-nonpos-nonpos*: $[[a \leq (0::'a::\text{pordered-ring}); b \leq 0]] \implies 0 \leq a*b$
 $\langle \text{proof} \rangle$

lemma *zero-less-mult-pos*:
 $[[0 < a*b; 0 < a]] \implies 0 < (b::'a::\text{ordered-semiring-strict})$
 $\langle \text{proof} \rangle$

lemma *zero-less-mult-pos2*:
 $[[0 < b*a; 0 < a]] \implies 0 < (b::'a::\text{ordered-semiring-strict})$
 $\langle \text{proof} \rangle$

lemma *zero-less-mult-iff*:
 $((0::'a::\text{ordered-ring-strict}) < a*b) = (0 < a \ \& \ 0 < b \mid a < 0 \ \& \ b < 0)$
 $\langle \text{proof} \rangle$

A field has no “zero divisors”, and this theorem holds without the assumption of an ordering. See *field-mult-eq-0-iff* below.

lemma *mult-eq-0-iff* [simp]: $(a*b = (0::'a::\text{ordered-ring-strict})) = (a = 0 \mid b = 0)$
 $\langle \text{proof} \rangle$

lemma *zero-le-mult-iff*:
 $((0::'a::\text{ordered-ring-strict}) \leq a*b) = (0 \leq a \ \& \ 0 \leq b \mid a \leq 0 \ \& \ b \leq 0)$
 $\langle \text{proof} \rangle$

lemma *mult-less-0-iff*:
 $(a*b < (0::'a::\text{ordered-ring-strict})) = (0 < a \ \& \ b < 0 \mid a < 0 \ \& \ 0 < b)$
 $\langle \text{proof} \rangle$

lemma *mult-le-0-iff*:
 $(a*b \leq (0::'a::\text{ordered-ring-strict})) = (0 \leq a \ \& \ b \leq 0 \mid a \leq 0 \ \& \ 0 \leq b)$
 $\langle \text{proof} \rangle$

lemma *split-mult-pos-le*: $(0 \leq a \ \& \ 0 \leq b) \mid (a \leq 0 \ \& \ b \leq 0) \implies 0 \leq a * (b::'\text{pordered-ring})$
 $\langle \text{proof} \rangle$

lemma *split-mult-neg-le*: $(0 \leq a \ \& \ b \leq 0) \mid (a \leq 0 \ \& \ 0 \leq b) \implies a * b \leq (0::'\text{pordered-cancel-semiring})$
 $\langle \text{proof} \rangle$

lemma *zero-le-square*: $(0::'a::\text{ordered-ring-strict}) \leq a*a$
 $\langle \text{proof} \rangle$

Proving axiom *zero-less-one* makes all *ordered-semidom* theorems available to members of *ordered-idom*

instance *ordered-idom* \subseteq *ordered-semidom*
 $\langle \text{proof} \rangle$

instance *ordered-ring-strict* \subseteq *axclass-no-zero-divisors*
 $\langle \text{proof} \rangle$

instance *ordered-idom* \subseteq *idom* $\langle \text{proof} \rangle$

All three types of comparison involving 0 and 1 are covered.

lemmas *one-neq-zero* = *zero-neq-one* [THEN not-sym]
declare *one-neq-zero* [simp]

lemma *zero-le-one* [simp]: $(0::'a::\text{ordered-semidom}) \leq 1$
 $\langle \text{proof} \rangle$

lemma *not-one-le-zero* [simp]: $\sim (1::'a::\text{ordered-semidom}) \leq 0$
 $\langle \text{proof} \rangle$

lemma *not-one-less-zero* [simp]: $\sim (1::'a::\text{ordered-semidom}) < 0$
 $\langle \text{proof} \rangle$

15.4 More Monotonicity

Strict monotonicity in both arguments

lemma *mult-strict-mono*:
 $[[a < b; c < d; 0 < b; 0 \leq c]] \implies a * c < b * (d::'a::\text{ordered-semiring-strict})$
 $\langle \text{proof} \rangle$

This weaker variant has more natural premises

lemma *mult-strict-mono'*:
 $[[a < b; c < d; 0 \leq a; 0 \leq c]] \implies a * c < b * (d::'a::\text{ordered-semiring-strict})$
 $\langle \text{proof} \rangle$

lemma *mult-mono*:
 $[[a \leq b; c \leq d; 0 \leq b; 0 \leq c]]$
 $\implies a * c \leq b * (d::'a::\text{ordered-semiring})$
 $\langle \text{proof} \rangle$

lemma *less-1-mult*: $[[1 < m; 1 < n]] \implies 1 < m * (n::'a::\text{ordered-semidom})$
 $\langle \text{proof} \rangle$

lemma *mult-less-le-imp-less*: $(a::'a::\text{ordered-semiring-strict}) < b \implies$
 $c \leq d \implies 0 \leq a \implies 0 < c \implies a * c < b * d$
 $\langle \text{proof} \rangle$

lemma *mult-le-less-imp-less*: $(a::'a::\text{ordered-semiring-strict}) \leq b \implies$
 $c < d \implies 0 < a \implies 0 \leq c \implies a * c < b * d$
 $\langle \text{proof} \rangle$

15.5 Cancellation Laws for Relationships With a Common Factor

Cancellation laws for $c * a < c * b$ and $a * c < b * c$, also with the relations \leq and equality.

These “disjunction” versions produce two cases when the comparison is an assumption, but effectively four when the comparison is a goal.

lemma *mult-less-cancel-right-disj*:

$(a * c < b * c) = ((0 < c \ \& \ a < b) \mid (c < 0 \ \& \ b < (a :: 'a :: \text{ordered-ring-strict})))$
 $\langle \text{proof} \rangle$

lemma *mult-less-cancel-left-disj*:

$(c * a < c * b) = ((0 < c \ \& \ a < b) \mid (c < 0 \ \& \ b < (a :: 'a :: \text{ordered-ring-strict})))$
 $\langle \text{proof} \rangle$

The “conjunction of implication” lemmas produce two cases when the comparison is a goal, but give four when the comparison is an assumption.

lemma *mult-less-cancel-right*:

fixes $c :: 'a :: \text{ordered-ring-strict}$
shows $(a * c < b * c) = ((0 \leq c \longrightarrow a < b) \ \& \ (c \leq 0 \longrightarrow b < a))$
 $\langle \text{proof} \rangle$

lemma *mult-less-cancel-left*:

fixes $c :: 'a :: \text{ordered-ring-strict}$
shows $(c * a < c * b) = ((0 \leq c \longrightarrow a < b) \ \& \ (c \leq 0 \longrightarrow b < a))$
 $\langle \text{proof} \rangle$

lemma *mult-le-cancel-right*:

$(a * c \leq b * c) = ((0 < c \longrightarrow a \leq b) \ \& \ (c < 0 \longrightarrow b \leq (a :: 'a :: \text{ordered-ring-strict})))$
 $\langle \text{proof} \rangle$

lemma *mult-le-cancel-left*:

$(c * a \leq c * b) = ((0 < c \longrightarrow a \leq b) \ \& \ (c < 0 \longrightarrow b \leq (a :: 'a :: \text{ordered-ring-strict})))$
 $\langle \text{proof} \rangle$

lemma *mult-less-imp-less-left*:

assumes *less*: $c * a < c * b$ **and** *nonneg*: $0 \leq c$
shows $a < (b :: 'a :: \text{ordered-semiring-strict})$
 $\langle \text{proof} \rangle$

lemma *mult-less-imp-less-right*:

assumes *less*: $a * c < b * c$ **and** *nonneg*: $0 \leq c$
shows $a < (b :: 'a :: \text{ordered-semiring-strict})$
 $\langle \text{proof} \rangle$

Cancellation of equalities with a common factor

lemma *mult-cancel-right* [*simp*]:

$(a * c = b * c) = (c = (0 :: 'a :: \text{ordered-ring-strict}) \mid a = b)$
 $\langle \text{proof} \rangle$

These cancellation theorems require an ordering. Versions are proved below that work for fields without an ordering.

lemma *mult-cancel-left [simp]*:

$(c * a = c * b) = (c = (0 :: 'a :: \text{ordered-ring-strict}) \mid a = b)$
 $\langle \text{proof} \rangle$

15.5.1 Special Cancellation Simprules for Multiplication

These also produce two cases when the comparison is a goal.

lemma *mult-le-cancel-right1*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(c \leq b * c) = ((0 < c \longrightarrow 1 \leq b) \ \& \ (c < 0 \longrightarrow b \leq 1))$
 $\langle \text{proof} \rangle$

lemma *mult-le-cancel-right2*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(a * c \leq c) = ((0 < c \longrightarrow a \leq 1) \ \& \ (c < 0 \longrightarrow 1 \leq a))$
 $\langle \text{proof} \rangle$

lemma *mult-le-cancel-left1*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(c \leq c * b) = ((0 < c \longrightarrow 1 \leq b) \ \& \ (c < 0 \longrightarrow b \leq 1))$
 $\langle \text{proof} \rangle$

lemma *mult-le-cancel-left2*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(c * a \leq c) = ((0 \leq c \longrightarrow a \leq 1) \ \& \ (c \leq 0 \longrightarrow 1 \leq a))$
 $\langle \text{proof} \rangle$

lemma *mult-less-cancel-right1*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(c < b * c) = ((0 \leq c \longrightarrow 1 < b) \ \& \ (c \leq 0 \longrightarrow b < 1))$
 $\langle \text{proof} \rangle$

lemma *mult-less-cancel-right2*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(a * c < c) = ((0 \leq c \longrightarrow a < 1) \ \& \ (c \leq 0 \longrightarrow 1 < a))$
 $\langle \text{proof} \rangle$

lemma *mult-less-cancel-left1*:

fixes $c :: 'a :: \text{ordered-idom}$
shows $(c < c * b) = ((0 \leq c \longrightarrow 1 < b) \ \& \ (c \leq 0 \longrightarrow b < 1))$
 $\langle \text{proof} \rangle$

lemma *mult-less-cancel-left2*:

```

fixes  $c :: 'a :: \text{ordered-idom}$ 
shows  $(c * a < c) = ((0 \leq c \longrightarrow a < 1) \ \& \ (c \leq 0 \longrightarrow 1 < a))$ 
 $\langle \text{proof} \rangle$ 

```

```

lemma mult-cancel-right1 [simp]:
fixes  $c :: 'a :: \text{ordered-idom}$ 
shows  $(c = b * c) = (c = 0 \mid b = 1)$ 
 $\langle \text{proof} \rangle$ 

```

```

lemma mult-cancel-right2 [simp]:
fixes  $c :: 'a :: \text{ordered-idom}$ 
shows  $(a * c = c) = (c = 0 \mid a = 1)$ 
 $\langle \text{proof} \rangle$ 

```

```

lemma mult-cancel-left1 [simp]:
fixes  $c :: 'a :: \text{ordered-idom}$ 
shows  $(c = c * b) = (c = 0 \mid b = 1)$ 
 $\langle \text{proof} \rangle$ 

```

```

lemma mult-cancel-left2 [simp]:
fixes  $c :: 'a :: \text{ordered-idom}$ 
shows  $(c * a = c) = (c = 0 \mid a = 1)$ 
 $\langle \text{proof} \rangle$ 

```

Simprules for comparisons where common factors can be cancelled.

```

lemmas mult-compare-simps =
  mult-le-cancel-right mult-le-cancel-left
  mult-le-cancel-right1 mult-le-cancel-right2
  mult-le-cancel-left1 mult-le-cancel-left2
  mult-less-cancel-right mult-less-cancel-left
  mult-less-cancel-right1 mult-less-cancel-right2
  mult-less-cancel-left1 mult-less-cancel-left2
  mult-cancel-right mult-cancel-left
  mult-cancel-right1 mult-cancel-right2
  mult-cancel-left1 mult-cancel-left2

```

This list of rewrites decides ring equalities by ordered rewriting.

```

lemmas ring-eq-simps =

```

```

  left-distrib right-distrib left-diff-distrib right-diff-distrib
  group-eq-simps

```

15.6 Fields

```

lemma right-inverse [simp]:
assumes  $\text{not0}: a \neq 0$  shows  $a * \text{inverse } (a :: 'a :: \text{field}) = 1$ 
 $\langle \text{proof} \rangle$ 

```

```

lemma right-inverse-eq:  $b \neq 0 \implies (a / b = 1) = (a = (b :: 'a :: \text{field}))$ 

```

$\langle proof \rangle$

lemma *nonzero-inverse-eq-divide*: $a \neq 0 \implies \text{inverse } (a::'a::\text{field}) = 1/a$
 $\langle proof \rangle$

lemma *divide-self*: $a \neq 0 \implies a / (a::'a::\text{field}) = 1$
 $\langle proof \rangle$

lemma *divide-zero* [simp]: $a / 0 = (0::'a::\{\text{field}, \text{division-by-zero}\})$
 $\langle proof \rangle$

lemma *divide-self-if* [simp]:
 $a / (a::'a::\{\text{field}, \text{division-by-zero}\}) = (\text{if } a=0 \text{ then } 0 \text{ else } 1)$
 $\langle proof \rangle$

lemma *divide-zero-left* [simp]: $0/a = (0::'a::\text{field})$
 $\langle proof \rangle$

lemma *inverse-eq-divide*: $\text{inverse } (a::'a::\text{field}) = 1/a$
 $\langle proof \rangle$

lemma *add-divide-distrib*: $(a+b)/(c::'a::\text{field}) = a/c + b/c$
 $\langle proof \rangle$

Compared with *mult-eq-0-iff*, this version removes the requirement of an ordering.

lemma *field-mult-eq-0-iff* [simp]: $(a*b = (0::'a::\text{field})) = (a = 0 \mid b = 0)$
 $\langle proof \rangle$

Cancellation of equalities with a common factor

lemma *field-mult-cancel-right-lemma*:
assumes *cnz*: $c \neq (0::'a::\text{field})$
and *eq*: $a*c = b*c$
shows $a=b$
 $\langle proof \rangle$

lemma *field-mult-cancel-right* [simp]:
 $(a*c = b*c) = (c = (0::'a::\text{field}) \mid a=b)$
 $\langle proof \rangle$

lemma *field-mult-cancel-left* [simp]:
 $(c*a = c*b) = (c = (0::'a::\text{field}) \mid a=b)$
 $\langle proof \rangle$

lemma *nonzero-imp-inverse-nonzero*: $a \neq 0 \implies \text{inverse } a \neq (0::'a::\text{field})$
 $\langle proof \rangle$

15.7 Basic Properties of *inverse*

lemma *inverse-zero-imp-zero*: $\text{inverse } a = 0 \implies a = (0::'a::\text{field})$
 ⟨proof⟩

lemma *inverse-nonzero-imp-nonzero*:
 $\text{inverse } a = 0 \implies a = (0::'a::\text{field})$
 ⟨proof⟩

lemma *inverse-nonzero-iff-nonzero* [simp]:
 $(\text{inverse } a = 0) = (a = (0::'a::\{\text{field}, \text{division-by-zero}\}))$
 ⟨proof⟩

lemma *nonzero-inverse-minus-eq*:
assumes [simp]: $a \neq 0$ **shows** $\text{inverse}(-a) = -\text{inverse}(a::'a::\text{field})$
 ⟨proof⟩

lemma *inverse-minus-eq* [simp]:
 $\text{inverse}(-a) = -\text{inverse}(a::'a::\{\text{field}, \text{division-by-zero}\})$
 ⟨proof⟩

lemma *nonzero-inverse-eq-imp-eq*:
assumes *ineq*: $\text{inverse } a = \text{inverse } b$
and *anz*: $a \neq 0$
and *bnz*: $b \neq 0$
shows $a = (b::'a::\text{field})$
 ⟨proof⟩

lemma *inverse-eq-imp-eq*:
 $\text{inverse } a = \text{inverse } b \implies a = (b::'a::\{\text{field}, \text{division-by-zero}\})$
 ⟨proof⟩

lemma *inverse-eq-iff-eq* [simp]:
 $(\text{inverse } a = \text{inverse } b) = (a = (b::'a::\{\text{field}, \text{division-by-zero}\}))$
 ⟨proof⟩

lemma *nonzero-inverse-inverse-eq*:
assumes [simp]: $a \neq 0$ **shows** $\text{inverse}(\text{inverse } (a::'a::\text{field})) = a$
 ⟨proof⟩

lemma *inverse-inverse-eq* [simp]:
 $\text{inverse}(\text{inverse } (a::'a::\{\text{field}, \text{division-by-zero}\})) = a$
 ⟨proof⟩

lemma *inverse-1* [simp]: $\text{inverse } 1 = (1::'a::\text{field})$
 ⟨proof⟩

lemma *inverse-unique*:
assumes *ab*: $a * b = 1$
shows $\text{inverse } a = (b::'a::\text{field})$

$\langle proof \rangle$

lemma *nonzero-inverse-mult-distrib*:

assumes *anz*: $a \neq 0$

and *bnz*: $b \neq 0$

shows $inverse(a*b) = inverse(b) * inverse(a::'a::field)$

$\langle proof \rangle$

This version builds in division by zero while also re-orienting the right-hand side.

lemma *inverse-mult-distrib [simp]*:

$inverse(a*b) = inverse(a) * inverse(b::'a::{field,division-by-zero})$

$\langle proof \rangle$

There is no slick version using division by zero.

lemma *inverse-add*:

$[| a \neq 0; b \neq 0 |]$

$\implies inverse\ a + inverse\ b = (a+b) * inverse\ a * inverse\ (b::'a::field)$

$\langle proof \rangle$

lemma *inverse-divide [simp]*:

$inverse\ (a/b) = b / (a::'a::{field,division-by-zero})$

$\langle proof \rangle$

15.8 Calculations with fractions

lemma *nonzero-mult-divide-cancel-left*:

assumes *[simp]*: $b \neq 0$ **and** *[simp]*: $c \neq 0$

shows $(c*a)/(c*b) = a/(b::'a::field)$

$\langle proof \rangle$

lemma *mult-divide-cancel-left*:

$c \neq 0 \implies (c*a) / (c*b) = a / (b::'a::{field,division-by-zero})$

$\langle proof \rangle$

lemma *nonzero-mult-divide-cancel-right*:

$[| b \neq 0; c \neq 0 |] \implies (a*c) / (b*c) = a/(b::'a::field)$

$\langle proof \rangle$

lemma *mult-divide-cancel-right*:

$c \neq 0 \implies (a*c) / (b*c) = a / (b::'a::{field,division-by-zero})$

$\langle proof \rangle$

lemma *mult-divide-cancel-eq-if*:

$(c*a) / (c*b) =$

$(if\ c=0\ then\ 0\ else\ a / (b::'a::{field,division-by-zero}))$

$\langle proof \rangle$

lemma *divide-1* [simp]: $a/1 = (a::'a::field)$
 ⟨proof⟩

lemma *times-divide-eq-right*: $a * (b/c) = (a*b) / (c::'a::field)$
 ⟨proof⟩

lemma *times-divide-eq-left*: $(b/c) * a = (b*a) / (c::'a::field)$
 ⟨proof⟩

lemma *divide-divide-eq-right* [simp]:
 $a / (b/c) = (a*c) / (b::'a::\{field, division-by-zero\})$
 ⟨proof⟩

lemma *divide-divide-eq-left* [simp]:
 $(a / b) / (c::'a::\{field, division-by-zero\}) = a / (b*c)$
 ⟨proof⟩

lemma *add-frac-eq*: $(y::'a::field) \sim 0 ==> z \sim 0 ==>$
 $x / y + w / z = (x * z + w * y) / (y * z)$
 ⟨proof⟩

15.8.1 Special Cancellation Simprules for Division

lemma *mult-divide-cancel-left-if* [simp]:
fixes $c :: 'a :: \{field, division-by-zero\}$
shows $(c*a) / (c*b) = (if\ c=0\ then\ 0\ else\ a/b)$
 ⟨proof⟩

lemma *mult-divide-cancel-right-if* [simp]:
fixes $c :: 'a :: \{field, division-by-zero\}$
shows $(a*c) / (b*c) = (if\ c=0\ then\ 0\ else\ a/b)$
 ⟨proof⟩

lemma *mult-divide-cancel-left-if1* [simp]:
fixes $c :: 'a :: \{field, division-by-zero\}$
shows $c / (c*b) = (if\ c=0\ then\ 0\ else\ 1/b)$
 ⟨proof⟩

lemma *mult-divide-cancel-left-if2* [simp]:
fixes $c :: 'a :: \{field, division-by-zero\}$
shows $(c*a) / c = (if\ c=0\ then\ 0\ else\ a)$
 ⟨proof⟩

lemma *mult-divide-cancel-right-if1* [simp]:
fixes $c :: 'a :: \{field, division-by-zero\}$
shows $c / (b*c) = (if\ c=0\ then\ 0\ else\ 1/b)$
 ⟨proof⟩

lemma *mult-divide-cancel-right-if2* [simp]:

```

fixes  $c :: 'a :: \{\text{field}, \text{division-by-zero}\}$ 
shows  $(a * c) / c = (\text{if } c=0 \text{ then } 0 \text{ else } a)$ 
<proof>

```

Two lemmas for cancelling the denominator

```

lemma times-divide-self-right [simp]:
  fixes  $a :: 'a :: \{\text{field}, \text{division-by-zero}\}$ 
  shows  $a * (b/a) = (\text{if } a=0 \text{ then } 0 \text{ else } b)$ 
<proof>

```

```

lemma times-divide-self-left [simp]:
  fixes  $a :: 'a :: \{\text{field}, \text{division-by-zero}\}$ 
  shows  $(b/a) * a = (\text{if } a=0 \text{ then } 0 \text{ else } b)$ 
<proof>

```

15.9 Division and Unary Minus

```

lemma nonzero-minus-divide-left:  $b \neq 0 \implies -(a/b) = (-a) / (b::'a::\text{field})$ 
<proof>

```

```

lemma nonzero-minus-divide-right:  $b \neq 0 \implies -(a/b) = a / -(b::'a::\text{field})$ 
<proof>

```

```

lemma nonzero-minus-divide-divide:  $b \neq 0 \implies (-a)/(-b) = a / (b::'a::\text{field})$ 
<proof>

```

```

lemma minus-divide-left:  $-(a/b) = (-a) / (b::'a::\text{field})$ 
<proof>

```

```

lemma minus-divide-right:  $-(a/b) = a / -(b::'a::\{\text{field}, \text{division-by-zero}\})$ 
<proof>

```

The effect is to extract signs from divisions

```

lemmas divide-minus-left = minus-divide-left [symmetric]
lemmas divide-minus-right = minus-divide-right [symmetric]
declare divide-minus-left [simp] divide-minus-right [simp]

```

Also, extract signs from products

```

lemmas mult-minus-left = minus-mult-left [symmetric]
lemmas mult-minus-right = minus-mult-right [symmetric]
declare mult-minus-left [simp] mult-minus-right [simp]

```

```

lemma minus-divide-divide [simp]:
   $(-a)/(-b) = a / (b::'a::\{\text{field}, \text{division-by-zero}\})$ 
<proof>

```

```

lemma diff-divide-distrib:  $(a-b)/(c::'a::\text{field}) = a/c - b/c$ 
<proof>

```

lemma *diff-fraction-eq*: $(y::'a::\text{field}) \sim 0 \implies z \sim 0 \implies$
 $x / y - w / z = (x * z - w * y) / (y * z)$
 $\langle \text{proof} \rangle$

15.10 Ordered Fields

lemma *positive-imp-inverse-positive*:
assumes *a-gt-0*: $0 < a$ **shows** $0 < \text{inverse } (a::'a::\text{ordered-field})$
 $\langle \text{proof} \rangle$

lemma *negative-imp-inverse-negative*:
 $a < 0 \implies \text{inverse } a < (0::'a::\text{ordered-field})$
 $\langle \text{proof} \rangle$

lemma *inverse-le-imp-le*:
assumes *invle*: $\text{inverse } a \leq \text{inverse } b$
and *apos*: $0 < a$
shows $b \leq (a::'a::\text{ordered-field})$
 $\langle \text{proof} \rangle$

lemma *inverse-positive-imp-positive*:
assumes *inv-gt-0*: $0 < \text{inverse } a$
and [*simp*]: $a \neq 0$
shows $0 < (a::'a::\text{ordered-field})$
 $\langle \text{proof} \rangle$

lemma *inverse-positive-iff-positive* [*simp*]:
 $(0 < \text{inverse } a) = (0 < (a::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *inverse-negative-imp-negative*:
assumes *inv-less-0*: $\text{inverse } a < 0$
and [*simp*]: $a \neq 0$
shows $a < (0::'a::\text{ordered-field})$
 $\langle \text{proof} \rangle$

lemma *inverse-negative-iff-negative* [*simp*]:
 $(\text{inverse } a < 0) = (a < (0::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *inverse-nonnegative-iff-nonnegative* [*simp*]:
 $(0 \leq \text{inverse } a) = (0 \leq (a::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *inverse-nonpositive-iff-nonpositive* [*simp*]:
 $(\text{inverse } a \leq 0) = (a \leq (0::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

15.11 Anti-Monotonicity of *inverse*

lemma *less-imp-inverse-less*:

assumes *less*: $a < b$

and *apos*: $0 < a$

shows $\text{inverse } b < \text{inverse } (a::'a::\text{ordered-field})$

<proof>

lemma *inverse-less-imp-less*:

$[[\text{inverse } a < \text{inverse } b; 0 < a]] \implies b < (a::'a::\text{ordered-field})$

<proof>

Both premises are essential. Consider -1 and 1.

lemma *inverse-less-iff-less* [*simp*]:

$[[0 < a; 0 < b]]$

$\implies (\text{inverse } a < \text{inverse } b) = (b < (a::'a::\text{ordered-field}))$

<proof>

lemma *le-imp-inverse-le*:

$[[a \leq b; 0 < a]] \implies \text{inverse } b \leq \text{inverse } (a::'a::\text{ordered-field})$

<proof>

lemma *inverse-le-iff-le* [*simp*]:

$[[0 < a; 0 < b]]$

$\implies (\text{inverse } a \leq \text{inverse } b) = (b \leq (a::'a::\text{ordered-field}))$

<proof>

These results refer to both operands being negative. The opposite-sign case is trivial, since *inverse* preserves signs.

lemma *inverse-le-imp-le-neg*:

$[[\text{inverse } a \leq \text{inverse } b; b < 0]] \implies b \leq (a::'a::\text{ordered-field})$

<proof>

lemma *less-imp-inverse-less-neg*:

$[[a < b; b < 0]] \implies \text{inverse } b < \text{inverse } (a::'a::\text{ordered-field})$

<proof>

lemma *inverse-less-imp-less-neg*:

$[[\text{inverse } a < \text{inverse } b; b < 0]] \implies b < (a::'a::\text{ordered-field})$

<proof>

lemma *inverse-less-iff-less-neg* [*simp*]:

$[[a < 0; b < 0]]$

$\implies (\text{inverse } a < \text{inverse } b) = (b < (a::'a::\text{ordered-field}))$

<proof>

lemma *le-imp-inverse-le-neg*:

$[[a \leq b; b < 0]] \implies \text{inverse } b \leq \text{inverse } (a::'a::\text{ordered-field})$

<proof>

lemma *inverse-le-iff-le-neg* [simp]:

$$[[a < 0; b < 0]] \\ \implies (\text{inverse } a \leq \text{inverse } b) = (b \leq (a::'a::\text{ordered-field}))$$

 <proof>

15.12 Inverses and the Number One

lemma *one-less-inverse-iff*:

$$(1 < \text{inverse } x) = (0 < x \ \& \ x < (1::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

 <proof>

lemma *inverse-eq-1-iff* [simp]:

$$(\text{inverse } x = 1) = (x = (1::'a::\{\text{field}, \text{division-by-zero}\}))$$

 <proof>

lemma *one-le-inverse-iff*:

$$(1 \leq \text{inverse } x) = (0 < x \ \& \ x \leq (1::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

 <proof>

lemma *inverse-less-1-iff*:

$$(\text{inverse } x < 1) = (x \leq 0 \mid 1 < (x::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

 <proof>

lemma *inverse-le-1-iff*:

$$(\text{inverse } x \leq 1) = (x \leq 0 \mid 1 \leq (x::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

 <proof>

15.13 Simplification of Inequalities Involving Literal Divisors

lemma *pos-le-divide-eq*: $0 < (c::'a::\text{ordered-field}) \implies (a \leq b/c) = (a*c \leq b)$
 <proof>

lemma *neg-le-divide-eq*: $c < (0::'a::\text{ordered-field}) \implies (a \leq b/c) = (b \leq a*c)$
 <proof>

lemma *le-divide-eq*:

$$(a \leq b/c) = \\ (\text{if } 0 < c \text{ then } a*c \leq b \\ \text{else if } c < 0 \text{ then } b \leq a*c \\ \text{else } a \leq (0::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

 <proof>

lemma *pos-divide-le-eq*: $0 < (c::'a::\text{ordered-field}) \implies (b/c \leq a) = (b \leq a*c)$
 <proof>

lemma *neg-divide-le-eq*: $c < (0::'a::\text{ordered-field}) \implies (b/c \leq a) = (a*c \leq b)$
 <proof>

lemma *divide-le-eq*:

$$(b/c \leq a) =$$

$$(\text{if } 0 < c \text{ then } b \leq a*c$$

$$\quad \text{else if } c < 0 \text{ then } a*c \leq b$$

$$\quad \text{else } 0 \leq (a::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

<proof>

lemma *pos-less-divide-eq*:

$$0 < (c::'a::\text{ordered-field}) \implies (a < b/c) = (a*c < b)$$

<proof>

lemma *neg-less-divide-eq*:

$$c < (0::'a::\text{ordered-field}) \implies (a < b/c) = (b < a*c)$$

<proof>

lemma *less-divide-eq*:

$$(a < b/c) =$$

$$(\text{if } 0 < c \text{ then } a*c < b$$

$$\quad \text{else if } c < 0 \text{ then } b < a*c$$

$$\quad \text{else } a < (0::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

<proof>

lemma *pos-divide-less-eq*:

$$0 < (c::'a::\text{ordered-field}) \implies (b/c < a) = (b < a*c)$$

<proof>

lemma *neg-divide-less-eq*:

$$c < (0::'a::\text{ordered-field}) \implies (b/c < a) = (a*c < b)$$

<proof>

lemma *divide-less-eq*:

$$(b/c < a) =$$

$$(\text{if } 0 < c \text{ then } b < a*c$$

$$\quad \text{else if } c < 0 \text{ then } a*c < b$$

$$\quad \text{else } 0 < (a::'a::\{\text{ordered-field}, \text{division-by-zero}\}))$$

<proof>

lemma *nonzero-eq-divide-eq*: $c \neq 0 \implies ((a::'a::\text{field}) = b/c) = (a*c = b)$

<proof>

lemma *eq-divide-eq*:

$$((a::'a::\{\text{field}, \text{division-by-zero}\}) = b/c) = (\text{if } c \neq 0 \text{ then } a*c = b \text{ else } a=0)$$

<proof>

lemma *nonzero-divide-eq-eq*: $c \neq 0 \implies (b/c = (a::'a::\text{field})) = (b = a*c)$

<proof>

lemma *divide-eq-eq*:

$$(b/c = (a::'a::\{\text{field}, \text{division-by-zero}\})) = (\text{if } c \neq 0 \text{ then } b = a*c \text{ else } a=0)$$

$\langle \text{proof} \rangle$

lemma *divide-eq-imp*: $(c::'a::\{\text{division-by-zero,field}\}) \sim= 0 ==>$
 $b = a * c ==> b / c = a$
 $\langle \text{proof} \rangle$

lemma *eq-divide-imp*: $(c::'a::\{\text{division-by-zero,field}\}) \sim= 0 ==>$
 $a * c = b ==> a = b / c$
 $\langle \text{proof} \rangle$

lemma *frac-eq-eq*: $(y::'a::\text{field}) \sim= 0 ==> z \sim= 0 ==>$
 $(x / y = w / z) = (x * z = w * y)$
 $\langle \text{proof} \rangle$

15.14 Division and Signs

lemma *zero-less-divide-iff*:
 $((0::'a::\{\text{ordered-field,division-by-zero}\}) < a/b) = (0 < a \ \& \ 0 < b \mid a < 0 \ \& \ b < 0)$
 $\langle \text{proof} \rangle$

lemma *divide-less-0-iff*:
 $(a/b < (0::'a::\{\text{ordered-field,division-by-zero}\})) =$
 $(0 < a \ \& \ b < 0 \mid a < 0 \ \& \ 0 < b)$
 $\langle \text{proof} \rangle$

lemma *zero-le-divide-iff*:
 $((0::'a::\{\text{ordered-field,division-by-zero}\}) \leq a/b) =$
 $(0 \leq a \ \& \ 0 \leq b \mid a \leq 0 \ \& \ b \leq 0)$
 $\langle \text{proof} \rangle$

lemma *divide-le-0-iff*:
 $(a/b \leq (0::'a::\{\text{ordered-field,division-by-zero}\})) =$
 $(0 \leq a \ \& \ b \leq 0 \mid a \leq 0 \ \& \ 0 \leq b)$
 $\langle \text{proof} \rangle$

lemma *divide-eq-0-iff* [simp]:
 $(a/b = 0) = (a=0 \mid b=(0::'a::\{\text{field,division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *divide-pos-pos*: $0 < (x::'a::\text{ordered-field}) ==>$
 $0 < y ==> 0 < x / y$
 $\langle \text{proof} \rangle$

lemma *divide-nonneg-pos*: $0 \leq (x::'a::\text{ordered-field}) ==> 0 < y ==>$
 $0 \leq x / y$
 $\langle \text{proof} \rangle$

lemma *divide-neg-pos*: $(x::'a::\text{ordered-field}) < 0 ==> 0 < y ==> x / y < 0$

$\langle \text{proof} \rangle$

lemma *divide-nonpos-pos*: $(x::'a::\text{ordered-field}) \leq 0 \implies$
 $0 < y \implies x / y \leq 0$
 $\langle \text{proof} \rangle$

lemma *divide-pos-neg*: $0 < (x::'a::\text{ordered-field}) \implies y < 0 \implies x / y < 0$
 $\langle \text{proof} \rangle$

lemma *divide-nonneg-neg*: $0 \leq (x::'a::\text{ordered-field}) \implies$
 $y < 0 \implies x / y \leq 0$
 $\langle \text{proof} \rangle$

lemma *divide-neg-neg*: $(x::'a::\text{ordered-field}) < 0 \implies y < 0 \implies 0 < x / y$
 $\langle \text{proof} \rangle$

lemma *divide-nonpos-neg*: $(x::'a::\text{ordered-field}) \leq 0 \implies y < 0 \implies$
 $0 \leq x / y$
 $\langle \text{proof} \rangle$

15.15 Cancellation Laws for Division

lemma *divide-cancel-right* [simp]:
 $(a/c = b/c) = (c = 0 \mid a = (b::'a::\{\text{field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *divide-cancel-left* [simp]:
 $(c/a = c/b) = (c = 0 \mid a = (b::'a::\{\text{field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

15.16 Division and the Number One

Simplify expressions equated with 1

lemma *divide-eq-1-iff* [simp]:
 $(a/b = 1) = (b \neq 0 \ \& \ a = (b::'a::\{\text{field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *one-eq-divide-iff* [simp]:
 $(1 = a/b) = (b \neq 0 \ \& \ a = (b::'a::\{\text{field}, \text{division-by-zero}\}))$
 $\langle \text{proof} \rangle$

lemma *zero-eq-1-divide-iff* [simp]:
 $((0::'a::\{\text{ordered-field}, \text{division-by-zero}\}) = 1/a) = (a = 0)$
 $\langle \text{proof} \rangle$

lemma *one-divide-eq-0-iff* [simp]:
 $(1/a = (0::'a::\{\text{ordered-field}, \text{division-by-zero}\})) = (a = 0)$
 $\langle \text{proof} \rangle$

Simplify expressions such as $0 < 1/x$ to $0 < x$

lemmas *zero-less-divide-1-iff* = *zero-less-divide-iff* [of 1]

lemmas *divide-less-0-1-iff* = *divide-less-0-iff* [of 1]

lemmas *zero-le-divide-1-iff* = *zero-le-divide-iff* [of 1]

lemmas *divide-le-0-1-iff* = *divide-le-0-iff* [of 1]

declare *zero-less-divide-1-iff* [simp]

declare *divide-less-0-1-iff* [simp]

declare *zero-le-divide-1-iff* [simp]

declare *divide-le-0-1-iff* [simp]

15.17 Ordering Rules for Division

lemma *divide-strict-right-mono*:

$[[a < b; 0 < c]] \implies a / c < b / c \text{ (} c :: 'a :: \text{ordered-field} \text{)}$
 $\langle \text{proof} \rangle$

lemma *divide-right-mono*:

$[[a \leq b; 0 \leq c]] \implies a / c \leq b / c \text{ (} c :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\} \text{)}$
 $\langle \text{proof} \rangle$

lemma *divide-right-mono-neg*: $(a :: 'a :: \{\text{division-by-zero}, \text{ordered-field}\}) <= b$

$\implies c <= 0 \implies b / c <= a / c$
 $\langle \text{proof} \rangle$

lemma *divide-strict-right-mono-neg*:

$[[b < a; c < 0]] \implies a / c < b / c \text{ (} c :: 'a :: \text{ordered-field} \text{)}$
 $\langle \text{proof} \rangle$

The last premise ensures that a and b have the same sign

lemma *divide-strict-left-mono*:

$[[b < a; 0 < c; 0 < a * b]] \implies c / a < c / b \text{ (} b :: 'a :: \text{ordered-field} \text{)}$
 $\langle \text{proof} \rangle$

lemma *divide-left-mono*:

$[[b \leq a; 0 \leq c; 0 < a * b]] \implies c / a \leq c / b \text{ (} b :: 'a :: \text{ordered-field} \text{)}$
 $\langle \text{proof} \rangle$

lemma *divide-left-mono-neg*: $(a :: 'a :: \{\text{division-by-zero}, \text{ordered-field}\}) <= b$

$\implies c <= 0 \implies 0 < a * b \implies c / a <= c / b$
 $\langle \text{proof} \rangle$

lemma *divide-strict-left-mono-neg*:

$[[a < b; c < 0; 0 < a * b]] \implies c / a < c / b \text{ (} b :: 'a :: \text{ordered-field} \text{)}$
 $\langle \text{proof} \rangle$

Simplify quotients that are compared with the value 1.

lemma *le-divide-eq-1*:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$

shows $(1 \leq b / a) = ((0 < a \ \& \ a \leq b) \mid (a < 0 \ \& \ b \leq a))$
 $\langle \text{proof} \rangle$

lemma *divide-le-eq-1*:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $(b / a \leq 1) = ((0 < a \ \& \ b \leq a) \mid (a < 0 \ \& \ a \leq b) \mid a=0)$
 $\langle \text{proof} \rangle$

lemma *less-divide-eq-1*:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $(1 < b / a) = ((0 < a \ \& \ a < b) \mid (a < 0 \ \& \ b < a))$
 $\langle \text{proof} \rangle$

lemma *divide-less-eq-1*:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $(b / a < 1) = ((0 < a \ \& \ b < a) \mid (a < 0 \ \& \ a < b) \mid a=0)$
 $\langle \text{proof} \rangle$

15.18 Conditional Simplification Rules: No Case Splits

lemma *le-divide-eq-1-pos* [simp]:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $0 < a \implies (1 \leq b / a) = (a \leq b)$
 $\langle \text{proof} \rangle$

lemma *le-divide-eq-1-neg* [simp]:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $a < 0 \implies (1 \leq b / a) = (b \leq a)$
 $\langle \text{proof} \rangle$

lemma *divide-le-eq-1-pos* [simp]:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $0 < a \implies (b / a \leq 1) = (b \leq a)$
 $\langle \text{proof} \rangle$

lemma *divide-le-eq-1-neg* [simp]:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $a < 0 \implies (b / a \leq 1) = (a \leq b)$
 $\langle \text{proof} \rangle$

lemma *less-divide-eq-1-pos* [simp]:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $0 < a \implies (1 < b / a) = (a < b)$
 $\langle \text{proof} \rangle$

lemma *less-divide-eq-1-neg* [simp]:

fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $a < 0 \implies (1 < b / a) = (b < a)$
 $\langle \text{proof} \rangle$

lemma *divide-less-eq-1-pos* [simp]:
fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $0 < a \implies (b / a < 1) = (b < a)$
 $\langle \text{proof} \rangle$

lemma *eq-divide-eq-1* [simp]:
fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $(1 = b / a) = ((a \neq 0 \ \& \ a = b))$
 $\langle \text{proof} \rangle$

lemma *divide-eq-eq-1* [simp]:
fixes $a :: 'a :: \{\text{ordered-field}, \text{division-by-zero}\}$
shows $(b / a = 1) = ((a \neq 0 \ \& \ a = b))$
 $\langle \text{proof} \rangle$

15.19 Reasoning about inequalities with division

lemma *mult-right-le-one-le*: $0 \leq (x :: 'a :: \text{ordered-idom}) \implies 0 \leq y \implies y \leq 1 \implies x * y \leq x$
 $\langle \text{proof} \rangle$

lemma *mult-left-le-one-le*: $0 \leq (x :: 'a :: \text{ordered-idom}) \implies 0 \leq y \implies y \leq 1 \implies y * x \leq x$
 $\langle \text{proof} \rangle$

lemma *mult-imp-div-pos-le*: $0 < (y :: 'a :: \text{ordered-field}) \implies x \leq z * y \implies x / y \leq z$
 $\langle \text{proof} \rangle$

lemma *mult-imp-le-div-pos*: $0 < (y :: 'a :: \text{ordered-field}) \implies z * y \leq x \implies z \leq x / y$
 $\langle \text{proof} \rangle$

lemma *mult-imp-div-pos-less*: $0 < (y :: 'a :: \text{ordered-field}) \implies x < z * y \implies x / y < z$
 $\langle \text{proof} \rangle$

lemma *mult-imp-less-div-pos*: $0 < (y :: 'a :: \text{ordered-field}) \implies z * y < x \implies z < x / y$
 $\langle \text{proof} \rangle$

lemma *frac-le*: $(0 :: 'a :: \text{ordered-field}) \leq x \implies x \leq y \implies 0 < w \implies w \leq z \implies x / z \leq y / w$
 $\langle \text{proof} \rangle$

lemma *frac-less*: $(0 :: 'a :: \text{ordered-field}) < x \implies$

$x < y \implies 0 < w \implies w < z \implies x / z < y / w$
 $\langle \text{proof} \rangle$

lemma *frac-less2*: $(0 :: 'a :: \text{ordered-field}) < x \implies$
 $x <= y \implies 0 < w \implies w < z \implies x / z < y / w$
 $\langle \text{proof} \rangle$

lemmas *times-divide-eq* = *times-divide-eq-right times-divide-eq-left*

It’s not obvious whether these should be *simprules* or not. Their effect is to gather terms into one big fraction, like $a*b*c / x*y*z$. The rationale for that is unclear, but many proofs seem to need them.

declare *times-divide-eq* [*simp*]

15.20 Ordered Fields are Dense

lemma *less-add-one*: $a < (a+1 :: 'a :: \text{ordered-semidom})$
 $\langle \text{proof} \rangle$

lemma *zero-less-two*: $0 < (1+1 :: 'a :: \text{ordered-semidom})$
 $\langle \text{proof} \rangle$

lemma *less-half-sum*: $a < b \implies a < (a+b) / (1+1 :: 'a :: \text{ordered-field})$
 $\langle \text{proof} \rangle$

lemma *gt-half-sum*: $a < b \implies (a+b)/(1+1 :: 'a :: \text{ordered-field}) < b$
 $\langle \text{proof} \rangle$

lemma *dense*: $a < b \implies \exists r :: 'a :: \text{ordered-field}. a < r \ \& \ r < b$
 $\langle \text{proof} \rangle$

15.21 Absolute Value

lemma *abs-one* [*simp*]: $\text{abs } 1 = (1 :: 'a :: \text{ordered-idom})$
 $\langle \text{proof} \rangle$

lemma *abs-le-mult*: $\text{abs } (a * b) \leq (\text{abs } a) * (\text{abs } (b :: 'a :: \text{ordered-ring}))$
 $\langle \text{proof} \rangle$

lemma *abs-eq-mult*:
assumes $(0 \leq a \vee a \leq 0) \wedge (0 \leq b \vee b \leq 0)$
shows $\text{abs } (a*b) = \text{abs } a * \text{abs } (b :: 'a :: \text{ordered-ring})$
 $\langle \text{proof} \rangle$

lemma *abs-mult*: $\text{abs } (a * b) = \text{abs } a * \text{abs } (b :: 'a :: \text{ordered-idom})$
 $\langle \text{proof} \rangle$

lemma *abs-mult-self*: $\text{abs } a * \text{abs } a = a * (a :: 'a :: \text{ordered-idom})$
 $\langle \text{proof} \rangle$

lemma *nonzero-abs-inverse*:

$a \neq 0 \implies \text{abs } (\text{inverse } (a::'a::\text{ordered-field})) = \text{inverse } (\text{abs } a)$
 $\langle \text{proof} \rangle$

lemma *abs-inverse [simp]*:

$\text{abs } (\text{inverse } (a::'a::\{\text{ordered-field}, \text{division-by-zero}\})) =$
 $\text{inverse } (\text{abs } a)$
 $\langle \text{proof} \rangle$

lemma *nonzero-abs-divide*:

$b \neq 0 \implies \text{abs } (a / (b::'a::\text{ordered-field})) = \text{abs } a / \text{abs } b$
 $\langle \text{proof} \rangle$

lemma *abs-divide [simp]*:

$\text{abs } (a / (b::'a::\{\text{ordered-field}, \text{division-by-zero}\})) = \text{abs } a / \text{abs } b$
 $\langle \text{proof} \rangle$

lemma *abs-mult-less*:

$[\text{abs } a < c; \text{abs } b < d] \implies \text{abs } a * \text{abs } b < c * (d::'a::\text{ordered-idom})$
 $\langle \text{proof} \rangle$

lemma *eq-minus-self-iff*: $(a = -a) = (a = (0::'a::\text{ordered-idom}))$

$\langle \text{proof} \rangle$

lemma *less-minus-self-iff*: $(a < -a) = (a < (0::'a::\text{ordered-idom}))$

$\langle \text{proof} \rangle$

lemma *abs-less-iff*: $(\text{abs } a < b) = (a < b \ \& \ -a < (b::'a::\text{ordered-idom}))$

$\langle \text{proof} \rangle$

lemma *abs-mult-pos*: $(0::'a::\text{ordered-idom}) \leq x \implies$

$(\text{abs } y) * x = \text{abs } (y * x)$

$\langle \text{proof} \rangle$

lemma *abs-div-pos*: $(0::'a::\{\text{division-by-zero}, \text{ordered-field}\}) < y \implies$

$\text{abs } x / y = \text{abs } (x / y)$

$\langle \text{proof} \rangle$

15.22 Miscellaneous

lemma *linprog-dual-estimate*:

assumes

$A * x \leq (b::'a::\text{lordered-ring})$

$0 \leq y$

$\text{abs } (A - A') \leq \delta A$

$b \leq b'$

$\text{abs } (c - c') \leq \delta c$

$\text{abs } x \leq r$

shows
 $c * x \leq y * b' + (y * \delta A + \text{abs } (y * A' - c') + \delta c) * r$
 $\langle \text{proof} \rangle$

lemma *le-ge-imp-abs-diff-1*:
assumes
 $A1 \leq (A::'a::\text{ordered-ring})$
 $A \leq A2$
shows $\text{abs } (A - A1) \leq A2 - A1$
 $\langle \text{proof} \rangle$

lemma *mult-le-prts*:
assumes
 $a1 \leq (a::'a::\text{ordered-ring})$
 $a \leq a2$
 $b1 \leq b$
 $b \leq b2$
shows
 $a * b \leq \text{pprt } a2 * \text{pprt } b2 + \text{pprt } a1 * \text{nprt } b2 + \text{nprt } a2 * \text{pprt } b1 + \text{nprt } a1$
 $* \text{nprt } b1$
 $\langle \text{proof} \rangle$

lemma *mult-le-dual-prts*:
assumes
 $A * x \leq (b::'a::\text{ordered-ring})$
 $0 \leq y$
 $A1 \leq A$
 $A \leq A2$
 $c1 \leq c$
 $c \leq c2$
 $r1 \leq x$
 $x \leq r2$
shows
 $c * x \leq y * b + (\text{let } s1 = c1 - y * A2; s2 = c2 - y * A1 \text{ in } \text{pprt } s2 * \text{pprt } r2$
 $+ \text{pprt } s1 * \text{nprt } r2 + \text{nprt } s2 * \text{pprt } r1 + \text{nprt } s1 * \text{nprt } r1)$
 $(\text{is } - \leq - + ?C)$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

end

16 Nat: Natural numbers

theory *Nat*
imports *Wellfounded-Rursion Ring-and-Field*
begin

16.1 Type *ind*

typedecl *ind*

consts

Zero-Rep :: *ind*
Suc-Rep :: *ind* ==> *ind*

axioms

— the axiom of infinity in 2 parts

inj-Suc-Rep: *inj Suc-Rep*
Suc-Rep-not-Zero-Rep: *Suc-Rep x* ≠ *Zero-Rep*

finalconsts

Zero-Rep
Suc-Rep

16.2 Type *nat*

Type definition

consts

Nat :: *ind set*

inductive *Nat*

intros

Zero-RepI: *Zero-Rep* : *Nat*
Suc-RepI: *i* : *Nat* ==> *Suc-Rep i* : *Nat*

global

typedef (**open** *Nat*)

nat = *Nat* ⟨*proof*⟩

instance *nat* :: {*ord*, *zero*, *one*} ⟨*proof*⟩

Abstract constants and syntax

consts

Suc :: *nat* ==> *nat*
pred-nat :: (*nat* * *nat*) *set*

local

defs

Zero-nat-def: *0* == *Abs-Nat Zero-Rep*
Suc-def: *Suc* == (%*n*. *Abs-Nat (Suc-Rep (Rep-Nat n))*)
One-nat-def [*simp*]: *1* == *Suc 0*

— *nat* operations

pred-nat-def: *pred-nat* == {(*m*, *n*). *n* = *Suc m*}

less-def: $m < n == (m, n) : \text{tranc1 pred-nat}$

le-def: $m \leq (n::\text{nat}) == \sim (n < m)$

Induction

theorem *nat-induct*: $P\ 0 ==> (!n. P\ n ==> P\ (\text{Suc}\ n)) ==> P\ n$
 $\langle \text{proof} \rangle$

Distinctness of constructors

lemma *Suc-not-Zero* [iff]: $\text{Suc}\ m \neq 0$
 $\langle \text{proof} \rangle$

lemma *Zero-not-Suc* [iff]: $0 \neq \text{Suc}\ m$
 $\langle \text{proof} \rangle$

lemma *Suc-neq-Zero*: $\text{Suc}\ m = 0 ==> R$
 $\langle \text{proof} \rangle$

lemma *Zero-neq-Suc*: $0 = \text{Suc}\ m ==> R$
 $\langle \text{proof} \rangle$

Injectiveness of *Suc*

lemma *inj-Suc*[simp]: *inj-on* *Suc* *N*
 $\langle \text{proof} \rangle$

lemma *Suc-inject*: $\text{Suc}\ x = \text{Suc}\ y ==> x = y$
 $\langle \text{proof} \rangle$

lemma *Suc-Suc-eq* [iff]: $(\text{Suc}\ m = \text{Suc}\ n) = (m = n)$
 $\langle \text{proof} \rangle$

lemma *nat-not-singleton*: $(\forall x. x = (0::\text{nat})) = \text{False}$
 $\langle \text{proof} \rangle$

nat is a datatype

rep-datatype *nat*

distinct *Suc-not-Zero Zero-not-Suc*

inject *Suc-Suc-eq*

induction *nat-induct*

lemma *n-not-Suc-n*: $n \neq \text{Suc}\ n$
 $\langle \text{proof} \rangle$

lemma *Suc-n-not-n*: $\text{Suc}\ t \neq t$
 $\langle \text{proof} \rangle$

A special form of induction for reasoning about $m < n$ and $m - n$

theorem *diff-induct*: $(!x. P\ x\ 0) ==> (!y. P\ 0\ (\text{Suc}\ y)) ==>$

$(!!x\ y.\ P\ x\ y \implies P\ (Suc\ x)\ (Suc\ y)) \implies P\ m\ n$
 $\langle proof \rangle$

16.3 Basic properties of “less than”

lemma *wf-pred-nat*: *wf pred-nat*
 $\langle proof \rangle$

lemma *wf-less*: *wf $\{(x, y::nat). x < y\}$*
 $\langle proof \rangle$

lemma *less-eq*: $((m, n) : pred\text{-}nat^+) = (m < n)$
 $\langle proof \rangle$

16.3.1 Introduction properties

lemma *less-trans*: $i < j \implies j < k \implies i < (k::nat)$
 $\langle proof \rangle$

lemma *lessI* [*iff*]: $n < Suc\ n$
 $\langle proof \rangle$

lemma *less-SucI*: $i < j \implies i < Suc\ j$
 $\langle proof \rangle$

lemma *zero-less-Suc* [*iff*]: $0 < Suc\ n$
 $\langle proof \rangle$

16.3.2 Elimination properties

lemma *less-not-sym*: $n < m \implies \sim m < (n::nat)$
 $\langle proof \rangle$

lemma *less-asm*:
assumes *h1*: $(n::nat) < m$ **and** *h2*: $\sim P \implies m < n$ **shows** *P*
 $\langle proof \rangle$

lemma *less-not-refl*: $\sim n < (n::nat)$
 $\langle proof \rangle$

lemma *less-irrefl* [*elim!*]: $(n::nat) < n \implies R$
 $\langle proof \rangle$

lemma *less-not-refl2*: $n < m \implies m \neq (n::nat)$ $\langle proof \rangle$

lemma *less-not-refl3*: $(s::nat) < t \implies s \neq t$
 $\langle proof \rangle$

lemma *lessE*:
assumes *major*: $i < k$

and $p1: k = \text{Suc } i \implies P$ **and** $p2: \forall j. i < j \implies k = \text{Suc } j \implies P$
shows P
 $\langle \text{proof} \rangle$

lemma *not-less0* [iff]: $\sim n < (0::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *less-zeroE*: $(n::\text{nat}) < 0 \implies R$
 $\langle \text{proof} \rangle$

lemma *less-SucE*: **assumes** *major*: $m < \text{Suc } n$
and *less*: $m < n \implies P$ **and** *eq*: $m = n \implies P$ **shows** P
 $\langle \text{proof} \rangle$

lemma *less-Suc-eq*: $(m < \text{Suc } n) = (m < n \mid m = n)$
 $\langle \text{proof} \rangle$

lemma *less-one* [iff]: $(n < (1::\text{nat})) = (n = 0)$
 $\langle \text{proof} \rangle$

lemma *less-Suc0* [iff]: $(n < \text{Suc } 0) = (n = 0)$
 $\langle \text{proof} \rangle$

lemma *Suc-mono*: $m < n \implies \text{Suc } m < \text{Suc } n$
 $\langle \text{proof} \rangle$

”Less than” is a linear ordering

lemma *less-linear*: $m < n \mid m = n \mid n < (m::\text{nat})$
 $\langle \text{proof} \rangle$

”Less than” is antisymmetric, sort of

lemma *less-antisym*: $\llbracket \neg n < m; n < \text{Suc } m \rrbracket \implies m = n$
 $\langle \text{proof} \rangle$

lemma *nat-neq-iff*: $((m::\text{nat}) \neq n) = (m < n \mid n < m)$
 $\langle \text{proof} \rangle$

lemma *nat-less-cases*: **assumes** *major*: $(m::\text{nat}) < n \implies P \ n \ m$
and *eqCase*: $m = n \implies P \ n \ m$ **and** *lessCase*: $n < m \implies P \ n \ m$
shows $P \ n \ m$
 $\langle \text{proof} \rangle$

16.3.3 Inductive (?) properties

lemma *Suc-lessI*: $m < n \implies \text{Suc } m \neq n \implies \text{Suc } m < n$
 $\langle \text{proof} \rangle$

lemma *Suc-lessD*: $\text{Suc } m < n \implies m < n$
 $\langle \text{proof} \rangle$

lemma *Suc-lessE*: **assumes** *major*: $\text{Suc } i < k$
and *minor*: $\forall j. i < j \implies k = \text{Suc } j \implies P$ **shows** P
 $\langle \text{proof} \rangle$

lemma *Suc-less-SucD*: $\text{Suc } m < \text{Suc } n \implies m < n$
 $\langle \text{proof} \rangle$

lemma *Suc-less-eq* [*iff*, *code*]: $(\text{Suc } m < \text{Suc } n) = (m < n)$
 $\langle \text{proof} \rangle$

lemma *less-trans-Suc*:
assumes *le*: $i < j$ **shows** $j < k \implies \text{Suc } i < k$
 $\langle \text{proof} \rangle$

lemma [*code*]: $((n::\text{nat}) < 0) = \text{False}$ $\langle \text{proof} \rangle$

lemma [*code*]: $(0 < \text{Suc } n) = \text{True}$ $\langle \text{proof} \rangle$

Can be used with *less-Suc-eq* to get $n = m \vee n < m$

lemma *not-less-eq*: $(\sim m < n) = (n < \text{Suc } m)$
 $\langle \text{proof} \rangle$

Complete induction, aka course-of-values induction

lemma *nat-less-induct*:
assumes *prem*: $\forall n. \forall m::\text{nat}. m < n \longrightarrow P m \implies P n$ **shows** $P n$
 $\langle \text{proof} \rangle$

lemmas *less-induct* = *nat-less-induct* [*rule-format*, *case-names less*]

16.4 Properties of “less than or equal”

Was *le-eq-less-Suc*, but this orientation is more useful

lemma *less-Suc-eq-le*: $(m < \text{Suc } n) = (m \leq n)$
 $\langle \text{proof} \rangle$

lemma *le-imp-less-Suc*: $m \leq n \implies m < \text{Suc } n$
 $\langle \text{proof} \rangle$

lemma *le0* [*iff*]: $(0::\text{nat}) \leq n$
 $\langle \text{proof} \rangle$

lemma *Suc-n-not-le-n*: $\sim \text{Suc } n \leq n$
 $\langle \text{proof} \rangle$

lemma *le-0-eq* [*iff*]: $((i::\text{nat}) \leq 0) = (i = 0)$
 $\langle \text{proof} \rangle$

lemma *le-Suc-eq*: $(m \leq \text{Suc } n) = (m \leq n \mid m = \text{Suc } n)$

$\langle \text{proof} \rangle$

lemma *le-SucE*: $m \leq \text{Suc } n \implies (m \leq n \implies R) \implies (m = \text{Suc } n \implies R) \implies R$
 $\langle \text{proof} \rangle$

lemma *Suc-leI*: $m < n \implies \text{Suc}(m) \leq n$
 $\langle \text{proof} \rangle$

lemma *Suc-leD*: $\text{Suc}(m) \leq n \implies m \leq n$
 $\langle \text{proof} \rangle$

Stronger version of *Suc-leD*

lemma *Suc-le-lessD*: $\text{Suc } m \leq n \implies m < n$
 $\langle \text{proof} \rangle$

lemma *Suc-le-eq*: $(\text{Suc } m \leq n) = (m < n)$
 $\langle \text{proof} \rangle$

lemma *le-SucI*: $m \leq n \implies m \leq \text{Suc } n$
 $\langle \text{proof} \rangle$

lemma *less-imp-le*: $m < n \implies m \leq (n::\text{nat})$
 $\langle \text{proof} \rangle$

For instance, $(\text{Suc } m < \text{Suc } n) = (\text{Suc } m \leq n) = (m < n)$

lemmas *le-simps* = *less-imp-le less-Suc-eq-le Suc-le-eq*

Equivalence of $m \leq n$ and $m < n \vee m = n$

lemma *le-imp-less-or-eq*: $m \leq n \implies m < n \mid m = (n::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *less-or-eq-imp-le*: $m < n \mid m = n \implies m \leq (n::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *le-eq-less-or-eq*: $(m \leq (n::\text{nat})) = (m < n \mid m = n)$
 $\langle \text{proof} \rangle$

Useful with *Blast*.

lemma *eq-imp-le*: $(m::\text{nat}) = n \implies m \leq n$
 $\langle \text{proof} \rangle$

lemma *le-refl*: $n \leq (n::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *le-less-trans*: $[[i \leq j; j < k]] \implies i < (k::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *less-le-trans*: $[[i < j; j \leq k]] \implies i < (k::nat)$
 $\langle proof \rangle$

lemma *le-trans*: $[[i \leq j; j \leq k]] \implies i \leq (k::nat)$
 $\langle proof \rangle$

lemma *le-anti-sym*: $[[m \leq n; n \leq m]] \implies m = (n::nat)$
 $\langle proof \rangle$

lemma *Suc-le-mono* [iff]: $(Suc\ n \leq Suc\ m) = (n \leq m)$
 $\langle proof \rangle$

Axiom *order-less-le* of class *order*:

lemma *nat-less-le*: $((m::nat) < n) = (m \leq n \ \& \ m \neq n)$
 $\langle proof \rangle$

lemma *le-neq-implies-less*: $(m::nat) \leq n \implies m \neq n \implies m < n$
 $\langle proof \rangle$

Axiom *linorder-linear* of class *linorder*:

lemma *nat-le-linear*: $(m::nat) \leq n \mid n \leq m$
 $\langle proof \rangle$

Type @typ nat is a wellfounded linear order

instance *nat* :: {*order*, *linorder*, *wellorder*}
 $\langle proof \rangle$

lemmas *linorder-neqE-nat* = *linorder-neqE*[**where** 'a = nat]

lemma *not-less-less-Suc-eq*: $\sim n < m \implies (n < Suc\ m) = (n = m)$
 $\langle proof \rangle$

Rewrite $n < Suc\ m$ to $n = m$ if $\neg n < m$ or $m \leq n$ hold. Not suitable as default simprules because they often lead to looping

lemma *le-less-Suc-eq*: $m \leq n \implies (n < Suc\ m) = (n = m)$
 $\langle proof \rangle$

lemmas *not-less-simps* = *not-less-less-Suc-eq* *le-less-Suc-eq*

Re-orientation of the equations $0 = x$ and $1 = x$. No longer added as simprules (they loop) but via *reorient-simproc* in Bin

Polymorphic, not just for *nat*

lemma *zero-reorient*: $(0 = x) = (x = 0)$
 $\langle proof \rangle$

lemma *one-reorient*: $(1 = x) = (x = 1)$
 $\langle proof \rangle$

16.5 Arithmetic operators

axclass *power* < *type*

consts

power :: ('a::power) => nat => 'a (infixr ^ 80)

arithmetic operators + − and *

instance *nat* :: {*plus*, *minus*, *times*, *power*} <proof>

size of a datatype value; overloaded

consts *size* :: 'a => nat

primrec

add-0: $0 + n = n$

add-Suc: $\text{Suc } m + n = \text{Suc } (m + n)$

primrec

diff-0: $m - 0 = m$

diff-Suc: $m - \text{Suc } n = (\text{case } m - n \text{ of } 0 \Rightarrow 0 \mid \text{Suc } k \Rightarrow k)$

primrec

mult-0: $0 * n = 0$

mult-Suc: $\text{Suc } m * n = n + (m * n)$

These two rules ease the use of primitive recursion. NOTE USE OF ==

lemma *def-nat-rec-0*: $(!!n. f\ n == \text{nat-rec } c\ h\ n) \Rightarrow f\ 0 = c$
<proof>

lemma *def-nat-rec-Suc*: $(!!n. f\ n == \text{nat-rec } c\ h\ n) \Rightarrow f\ (\text{Suc } n) = h\ n\ (f\ n)$
<proof>

lemma *not0-implies-Suc*: $n \neq 0 \Rightarrow \exists m. n = \text{Suc } m$
<proof>

lemma *gr-implies-not0*: $!!n::\text{nat}. m < n \Rightarrow n \neq 0$
<proof>

lemma *neq0-conv* [iff]: $!!n::\text{nat}. (n \neq 0) = (0 < n)$
<proof>

This theorem is useful with *blast*

lemma *gr0I*: $((n::\text{nat}) = 0 \Rightarrow \text{False}) \Rightarrow 0 < n$
<proof>

lemma *gr0-conv-Suc*: $(0 < n) = (\exists m. n = \text{Suc } m)$
<proof>

lemma *not-gr0* [iff]: $!!n::\text{nat}. (\sim (0 < n)) = (n = 0)$

$\langle proof \rangle$

lemma *Suc-le-D*: $(Suc\ n \leq m') \implies (?\ m.\ m' = Suc\ m)$
 $\langle proof \rangle$

Useful in certain inductive arguments

lemma *less-Suc-eq-0-disj*: $(m < Suc\ n) = (m = 0 \mid (\exists j.\ m = Suc\ j \ \&\ j < n))$
 $\langle proof \rangle$

lemma *nat-induct2*: $[[P\ 0; P\ (Suc\ 0); !!k.\ P\ k \implies P\ (Suc\ (Suc\ k))]] \implies P\ n$
 $\langle proof \rangle$

16.6 LEAST theorems for type nat

lemma *Least-Suc*:
 $[[P\ n; \sim P\ 0]] \implies (LEAST\ n.\ P\ n) = Suc\ (LEAST\ m.\ P(Suc\ m))$
 $\langle proof \rangle$

lemma *Least-Suc2*:
 $[[P\ n; Q\ m; \sim P\ 0; !k.\ P\ (Suc\ k) = Q\ k]] \implies Least\ P = Suc\ (Least\ Q)$
 $\langle proof \rangle$

16.7 min and max

lemma *min-0L [simp]*: $min\ 0\ n = (0::nat)$
 $\langle proof \rangle$

lemma *min-0R [simp]*: $min\ n\ 0 = (0::nat)$
 $\langle proof \rangle$

lemma *min-Suc-Suc [simp]*: $min\ (Suc\ m)\ (Suc\ n) = Suc\ (min\ m\ n)$
 $\langle proof \rangle$

lemma *max-0L [simp]*: $max\ 0\ n = (n::nat)$
 $\langle proof \rangle$

lemma *max-0R [simp]*: $max\ n\ 0 = (n::nat)$
 $\langle proof \rangle$

lemma *max-Suc-Suc [simp]*: $max\ (Suc\ m)\ (Suc\ n) = Suc(max\ m\ n)$
 $\langle proof \rangle$

16.8 Basic rewrite rules for the arithmetic operators

Difference

lemma *diff-0-eq-0 [simp, code]*: $0 - n = (0::nat)$
 $\langle proof \rangle$

lemma *diff-Suc-Suc [simp, code]*: $Suc(m) - Suc(n) = m - n$

$\langle proof \rangle$

Could be (and is, below) generalized in various ways However, none of the generalizations are currently in the simpset, and I dread to think what happens if I put them in

lemma *Suc-pred* [simp]: $0 < n \implies \text{Suc } (n - \text{Suc } 0) = n$
 $\langle proof \rangle$

declare *diff-Suc* [simp del, code del]

16.9 Addition

lemma *add-0-right* [simp]: $m + 0 = (m::nat)$
 $\langle proof \rangle$

lemma *add-Suc-right* [simp]: $m + \text{Suc } n = \text{Suc } (m + n)$
 $\langle proof \rangle$

lemma [code]: $\text{Suc } m + n = m + \text{Suc } n$ $\langle proof \rangle$

Associative law for addition

lemma *nat-add-assoc*: $(m + n) + k = m + ((n + k)::nat)$
 $\langle proof \rangle$

Commutative law for addition

lemma *nat-add-commute*: $m + n = n + (m::nat)$
 $\langle proof \rangle$

lemma *nat-add-left-commute*: $x + (y + z) = y + ((x + z)::nat)$
 $\langle proof \rangle$

lemma *nat-add-left-cancel* [simp]: $(k + m = k + n) = (m = (n::nat))$
 $\langle proof \rangle$

lemma *nat-add-right-cancel* [simp]: $(m + k = n + k) = (m = (n::nat))$
 $\langle proof \rangle$

lemma *nat-add-left-cancel-le* [simp]: $(k + m \leq k + n) = (m \leq (n::nat))$
 $\langle proof \rangle$

lemma *nat-add-left-cancel-less* [simp]: $(k + m < k + n) = (m < (n::nat))$
 $\langle proof \rangle$

Reasoning about $m + 0 = 0$, etc.

lemma *add-is-0* [iff]: $!!m::nat. (m + n = 0) = (m = 0 \ \& \ n = 0)$
 $\langle proof \rangle$

lemma *add-is-1*: $(m+n = \text{Suc } 0) = (m = \text{Suc } 0 \ \& \ n=0 \mid m=0 \ \& \ n = \text{Suc } 0)$

$\langle proof \rangle$

lemma *one-is-add*: $(Suc\ 0 = m + n) = (m = Suc\ 0 \ \&\ n = 0 \mid m = 0 \ \&\ n = Suc\ 0)$
 $\langle proof \rangle$

lemma *add-gr-0* [iff]: $!!m::nat. (0 < m + n) = (0 < m \mid 0 < n)$
 $\langle proof \rangle$

lemma *add-eq-self-zero*: $!!m::nat. m + n = m ==> n = 0$
 $\langle proof \rangle$

lemma *inj-on-add-nat*[simp]: *inj-on* $(\%n::nat. n+k)$ *N*
 $\langle proof \rangle$

16.10 Multiplication

right annihilation in product

lemma *mult-0-right* [simp]: $(m::nat) * 0 = 0$
 $\langle proof \rangle$

right successor law for multiplication

lemma *mult-Suc-right* [simp]: $m * Suc\ n = m + (m * n)$
 $\langle proof \rangle$

Commutative law for multiplication

lemma *nat-mult-commute*: $m * n = n * (m::nat)$
 $\langle proof \rangle$

addition distributes over multiplication

lemma *add-mult-distrib*: $(m + n) * k = (m * k) + ((n * k)::nat)$
 $\langle proof \rangle$

lemma *add-mult-distrib2*: $k * (m + n) = (k * m) + ((k * n)::nat)$
 $\langle proof \rangle$

Associative law for multiplication

lemma *nat-mult-assoc*: $(m * n) * k = m * ((n * k)::nat)$
 $\langle proof \rangle$

The naturals form a *comm-semiring-1-cancel*

instance *nat* :: *comm-semiring-1-cancel*
 $\langle proof \rangle$

lemma *mult-is-0* [simp]: $((m::nat) * n = 0) = (m=0 \mid n=0)$
 $\langle proof \rangle$

16.11 Monotonicity of Addition

strict, in 1st argument

lemma *add-less-mono1*: $i < j \implies i + k < j + (k::nat)$
 $\langle proof \rangle$

strict, in both arguments

lemma *add-less-mono*: $[i < j; k < l] \implies i + k < j + (l::nat)$
 $\langle proof \rangle$

Deleted *less-natE*; use *less-imp-Suc-add RS exE*

lemma *less-imp-Suc-add*: $m < n \implies (\exists k. n = Suc (m + k))$
 $\langle proof \rangle$

strict, in 1st argument; proof is by induction on $k > 0$

lemma *mult-less-mono2*: $(i::nat) < j \implies 0 < k \implies k * i < k * j$
 $\langle proof \rangle$

The naturals form an ordered *comm-semiring-1-cancel*

instance *nat :: ordered-semidom*
 $\langle proof \rangle$

lemma *nat-mult-1*: $(1::nat) * n = n$
 $\langle proof \rangle$

lemma *nat-mult-1-right*: $n * (1::nat) = n$
 $\langle proof \rangle$

16.12 Additional theorems about “less than”

A [clumsy] way of lifting $<$ monotonicity to \leq monotonicity

lemma *less-mono-imp-le-mono*:
assumes *lt-mono*: $!!i j::nat. i < j \implies f i < f j$
and *le*: $i \leq j$ **shows** $f i \leq ((f j)::nat)$ $\langle proof \rangle$

non-strict, in 1st argument

lemma *add-le-mono1*: $i \leq j \implies i + k \leq j + (k::nat)$
 $\langle proof \rangle$

non-strict, in both arguments

lemma *add-le-mono*: $[i \leq j; k \leq l] \implies i + k \leq j + (l::nat)$
 $\langle proof \rangle$

lemma *le-add2*: $n \leq ((m + n)::nat)$
 $\langle proof \rangle$

lemma *le-add1*: $n \leq ((n + m)::nat)$

$\langle proof \rangle$

lemma *less-add-Suc1*: $i < \text{Suc } (i + m)$
 $\langle proof \rangle$

lemma *less-add-Suc2*: $i < \text{Suc } (m + i)$
 $\langle proof \rangle$

lemma *less-iff-Suc-add*: $(m < n) = (\exists k. n = \text{Suc } (m + k))$
 $\langle proof \rangle$

lemma *trans-le-add1*: $(i::\text{nat}) \leq j \implies i \leq j + m$
 $\langle proof \rangle$

lemma *trans-le-add2*: $(i::\text{nat}) \leq j \implies i \leq m + j$
 $\langle proof \rangle$

lemma *trans-less-add1*: $(i::\text{nat}) < j \implies i < j + m$
 $\langle proof \rangle$

lemma *trans-less-add2*: $(i::\text{nat}) < j \implies i < m + j$
 $\langle proof \rangle$

lemma *add-lessD1*: $i + j < (k::\text{nat}) \implies i < k$
 $\langle proof \rangle$

lemma *not-add-less1* [iff]: $\sim (i + j < (i::\text{nat}))$
 $\langle proof \rangle$

lemma *not-add-less2* [iff]: $\sim (j + i < (i::\text{nat}))$
 $\langle proof \rangle$

lemma *add-leD1*: $m + k \leq n \implies m \leq (n::\text{nat})$
 $\langle proof \rangle$

lemma *add-leD2*: $m + k \leq n \implies k \leq (n::\text{nat})$
 $\langle proof \rangle$

lemma *add-leE*: $(m::\text{nat}) + k \leq n \implies (m \leq n \implies k \leq n \implies R) \implies R$
 $\langle proof \rangle$

needs !!k for *add-ac* to work

lemma *less-add-eq-less*: $!!k::\text{nat}. k < l \implies m + l = k + n \implies m < n$
 $\langle proof \rangle$

16.13 Difference

lemma *diff-self-eq-0* [simp]: $(m::\text{nat}) - m = 0$
 $\langle proof \rangle$

Addition is the inverse of subtraction: if $n \leq m$ then $n + (m - n) = m$.

lemma *add-diff-inverse*: $\sim \quad m < n \implies n + (m - n) = (m::nat)$
 $\langle proof \rangle$

lemma *le-add-diff-inverse* [simp]: $n \leq m \implies n + (m - n) = (m::nat)$
 $\langle proof \rangle$

lemma *le-add-diff-inverse2* [simp]: $n \leq m \implies (m - n) + n = (m::nat)$
 $\langle proof \rangle$

16.14 More results about difference

lemma *Suc-diff-le*: $n \leq m \implies Suc\ m - n = Suc\ (m - n)$
 $\langle proof \rangle$

lemma *diff-less-Suc*: $m - n < Suc\ m$
 $\langle proof \rangle$

lemma *diff-le-self* [simp]: $m - n \leq (m::nat)$
 $\langle proof \rangle$

lemma *less-imp-diff-less*: $(j::nat) < k \implies j - n < k$
 $\langle proof \rangle$

lemma *diff-diff-left*: $(i::nat) - j - k = i - (j + k)$
 $\langle proof \rangle$

lemma *Suc-diff-diff* [simp]: $(Suc\ m - n) - Suc\ k = m - n - k$
 $\langle proof \rangle$

lemma *diff-Suc-less* [simp]: $0 < n \implies n - Suc\ i < n$
 $\langle proof \rangle$

This and the next few suggested by Florian Kammüller

lemma *diff-commute*: $(i::nat) - j - k = i - k - j$
 $\langle proof \rangle$

lemma *diff-add-assoc*: $k \leq (j::nat) \implies (i + j) - k = i + (j - k)$
 $\langle proof \rangle$

lemma *diff-add-assoc2*: $k \leq (j::nat) \implies (j + i) - k = (j - k) + i$
 $\langle proof \rangle$

lemma *diff-add-inverse*: $(n + m) - n = (m::nat)$
 $\langle proof \rangle$

lemma *diff-add-inverse2*: $(m + n) - n = (m::nat)$
 $\langle proof \rangle$

lemma *le-imp-diff-is-add*: $i \leq (j::nat) \implies (j - i = k) = (j = k + i)$
 $\langle proof \rangle$

lemma *diff-is-0-eq* [simp]: $((m::nat) - n = 0) = (m \leq n)$
 $\langle proof \rangle$

lemma *diff-is-0-eq'* [simp]: $m \leq n \implies (m::nat) - n = 0$
 $\langle proof \rangle$

lemma *zero-less-diff* [simp]: $(0 < n - (m::nat)) = (m < n)$
 $\langle proof \rangle$

lemma *less-imp-add-positive*: $i < j \implies \exists k::nat. 0 < k \ \& \ i + k = j$
 $\langle proof \rangle$

lemma *zero-induct-lemma*: $P \ k \implies (!n. P \ (Suc \ n) \implies P \ n) \implies P \ (k - i)$
 $\langle proof \rangle$

lemma *zero-induct*: $P \ k \implies (!n. P \ (Suc \ n) \implies P \ n) \implies P \ 0$
 $\langle proof \rangle$

lemma *diff-cancel*: $(k + m) - (k + n) = m - (n::nat)$
 $\langle proof \rangle$

lemma *diff-cancel2*: $(m + k) - (n + k) = m - (n::nat)$
 $\langle proof \rangle$

lemma *diff-add-0*: $n - (n + m) = (0::nat)$
 $\langle proof \rangle$

Difference distributes over multiplication

lemma *diff-mult-distrib*: $((m::nat) - n) * k = (m * k) - (n * k)$
 $\langle proof \rangle$

lemma *diff-mult-distrib2*: $k * ((m::nat) - n) = (k * m) - (k * n)$
 $\langle proof \rangle$

lemmas *nat-distrib* =
add-mult-distrib add-mult-distrib2 diff-mult-distrib diff-mult-distrib2

16.15 Monotonicity of Multiplication

lemma *mult-le-mono1*: $i \leq (j::nat) \implies i * k \leq j * k$
 $\langle proof \rangle$

lemma *mult-le-mono2*: $i \leq (j::nat) \implies k * i \leq k * j$
 $\langle proof \rangle$

\leq monotonicity, BOTH arguments

lemma *mult-le-mono*: $i \leq (j::nat) \implies k \leq l \implies i * k \leq j * l$
 $\langle proof \rangle$

lemma *mult-less-mono1*: $(i::nat) < j \implies 0 < k \implies i * k < j * k$
 $\langle proof \rangle$

Differs from the standard *zero-less-mult-iff* in that there are no negative numbers.

lemma *nat-0-less-mult-iff* [simp]: $(0 < (m::nat) * n) = (0 < m \ \& \ 0 < n)$
 $\langle proof \rangle$

lemma *one-le-mult-iff* [simp]: $(Suc\ 0 \leq m * n) = (1 \leq m \ \& \ 1 \leq n)$
 $\langle proof \rangle$

lemma *mult-eq-1-iff* [simp]: $(m * n = Suc\ 0) = (m = 1 \ \& \ n = 1)$
 $\langle proof \rangle$

lemma *one-eq-mult-iff* [simp]: $(Suc\ 0 = m * n) = (m = 1 \ \& \ n = 1)$
 $\langle proof \rangle$

lemma *mult-less-cancel2* [simp]: $((m::nat) * k < n * k) = (0 < k \ \& \ m < n)$
 $\langle proof \rangle$

lemma *mult-less-cancel1* [simp]: $(k * (m::nat) < k * n) = (0 < k \ \& \ m < n)$
 $\langle proof \rangle$

lemma *mult-le-cancel1* [simp]: $(k * (m::nat) \leq k * n) = (0 < k \longrightarrow m \leq n)$
 $\langle proof \rangle$

lemma *mult-le-cancel2* [simp]: $((m::nat) * k \leq n * k) = (0 < k \longrightarrow m \leq n)$
 $\langle proof \rangle$

lemma *mult-cancel2* [simp]: $(m * k = n * k) = (m = n \mid (k = (0::nat)))$
 $\langle proof \rangle$

lemma *mult-cancel1* [simp]: $(k * m = k * n) = (m = n \mid (k = (0::nat)))$
 $\langle proof \rangle$

lemma *Suc-mult-less-cancel1*: $(Suc\ k * m < Suc\ k * n) = (m < n)$
 $\langle proof \rangle$

lemma *Suc-mult-le-cancel1*: $(Suc\ k * m \leq Suc\ k * n) = (m \leq n)$
 $\langle proof \rangle$

lemma *Suc-mult-cancel1*: $(Suc\ k * m = Suc\ k * n) = (m = n)$
 $\langle proof \rangle$

Lemma for *gcd*

lemma *mult-eq-self-implies-10*: $(m::nat) = m * n \implies n = 1 \mid m = 0$

$\langle proof \rangle$

end

17 NatArith: Further Arithmetic Facts Concerning the Natural Numbers

```
theory NatArith
imports Nat
uses arith-data.ML
begin
```

$\langle ML \rangle$

The following proofs may rely on the arithmetic proof procedures.

lemma *le-iff-add*: $(m::nat) \leq n = (\exists k. n = m + k)$
 $\langle proof \rangle$

lemma *pred-nat-trancl-eq-le*: $((m, n) : pred\text{-}nat^*) = (m \leq n)$
 $\langle proof \rangle$

lemma *nat-diff-split*:
 $P(a - b::nat) = ((a < b \longrightarrow P\ 0) \ \&\ (ALL\ d. a = b + d \longrightarrow P\ d))$
— elimination of $-$ on *nat*
 $\langle proof \rangle$

lemma *nat-diff-split-asm*:
 $P(a - b::nat) = (\sim (a < b \ \&\ \sim P\ 0 \mid (EX\ d. a = b + d \ \&\ \sim P\ d)))$
— elimination of $-$ on *nat* in assumptions
 $\langle proof \rangle$

lemmas [*arith-split*] = *nat-diff-split split-min split-max*

lemma *le-square*: $m \leq m*(m::nat)$
 $\langle proof \rangle$

lemma *le-cube*: $(m::nat) \leq m*(m*m)$
 $\langle proof \rangle$

Subtraction laws, mostly by Clemens Ballarin

lemma *diff-less-mono*: $[| a < (b::nat); c \leq a |] \implies a - c < b - c$
 $\langle proof \rangle$

lemma *less-diff-conv*: $(i < j - k) = (i + k < (j::nat))$

$\langle proof \rangle$

lemma *le-diff-conv*: $(j - k \leq (i :: nat)) = (j \leq i + k)$
 $\langle proof \rangle$

lemma *le-diff-conv2*: $k \leq j \implies (i \leq j - k) = (i + k \leq (j :: nat))$
 $\langle proof \rangle$

lemma *diff-diff-cancel* [*simp*]: $i \leq (n :: nat) \implies n - (n - i) = i$
 $\langle proof \rangle$

lemma *le-add-diff*: $k \leq (n :: nat) \implies m \leq n + m - k$
 $\langle proof \rangle$

lemma *diff-less* [*simp*]: $!!m :: nat. [\ 0 < n; 0 < m \] \implies m - n < m$
 $\langle proof \rangle$

lemma *diff-diff-eq*: $[\ k \leq m; k \leq (n :: nat) \] \implies ((m - k) - (n - k)) = (m - n)$
 $\langle proof \rangle$

lemma *eq-diff-iff*: $[\ k \leq m; k \leq (n :: nat) \] \implies (m - k = n - k) = (m = n)$
 $\langle proof \rangle$

lemma *less-diff-iff*: $[\ k \leq m; k \leq (n :: nat) \] \implies (m - k < n - k) = (m < n)$
 $\langle proof \rangle$

lemma *le-diff-iff*: $[\ k \leq m; k \leq (n :: nat) \] \implies (m - k \leq n - k) = (m \leq n)$
 $\langle proof \rangle$

(Anti)Monotonicity of subtraction – by Stephan Merz

lemma *diff-le-mono*: $m \leq (n :: nat) \implies (m - l) \leq (n - l)$
 $\langle proof \rangle$

lemma *diff-le-mono2*: $m \leq (n :: nat) \implies (l - n) \leq (l - m)$
 $\langle proof \rangle$

lemma *diff-less-mono2*: $[\ m < (n :: nat); m < l \] \implies (l - n) < (l - m)$
 $\langle proof \rangle$

lemma *diffs0-imp-equal*: $!!m :: nat. [\ m - n = 0; n - m = 0 \] \implies m = n$
 $\langle proof \rangle$

Lemmas for ex/Factorization

lemma *one-less-mult*: $[\ Suc\ 0 < n; Suc\ 0 < m \] \implies Suc\ 0 < m * n$
 $\langle proof \rangle$

lemma *n-less-m-mult-n*: $[| \text{Suc } 0 < n; \text{Suc } 0 < m |] \implies n < m * n$
 $\langle \text{proof} \rangle$

lemma *n-less-n-mult-m*: $[| \text{Suc } 0 < n; \text{Suc } 0 < m |] \implies n < n * m$
 $\langle \text{proof} \rangle$

Rewriting to pull differences out

lemma *diff-diff-right* [simp]: $k \leq j \implies i - (j - k) = i + (k :: \text{nat}) - j$
 $\langle \text{proof} \rangle$

lemma *diff-Suc-diff-eq1* [simp]: $k \leq j \implies m - \text{Suc } (j - k) = m + k - \text{Suc } j$
 $\langle \text{proof} \rangle$

lemma *diff-Suc-diff-eq2* [simp]: $k \leq j \implies \text{Suc } (j - k) - m = \text{Suc } j - (k + m)$
 $\langle \text{proof} \rangle$

lemmas *add-diff-assoc* = *diff-add-assoc* [symmetric]

lemmas *add-diff-assoc2* = *diff-add-assoc2* [symmetric]

declare *diff-diff-left* [simp] *add-diff-assoc* [simp] *add-diff-assoc2* [simp]

At present we prove no analogue of *not-less-Least* or *Least-Suc*, since there appears to be no need.

$\langle \text{ML} \rangle$

17.1 Embedding of the Naturals into any *comm-semiring-1-cancel*: *of-nat*

consts *of-nat* :: $\text{nat} \Rightarrow 'a :: \text{comm-semiring-1-cancel}$

primrec

of-nat-0: $\text{of-nat } 0 = 0$

of-nat-Suc: $\text{of-nat } (\text{Suc } m) = \text{of-nat } m + 1$

lemma *of-nat-1* [simp]: $\text{of-nat } 1 = 1$
 $\langle \text{proof} \rangle$

lemma *of-nat-add* [simp]: $\text{of-nat } (m + n) = \text{of-nat } m + \text{of-nat } n$
 $\langle \text{proof} \rangle$

lemma *of-nat-mult* [simp]: $\text{of-nat } (m * n) = \text{of-nat } m * \text{of-nat } n$
 $\langle \text{proof} \rangle$

lemma *zero-le-imp-of-nat*: $0 \leq (\text{of-nat } m :: 'a :: \text{ordered-semidom})$
 $\langle \text{proof} \rangle$

lemma *less-imp-of-nat-less*:

$m < n \implies \text{of-nat } m < (\text{of-nat } n :: 'a :: \text{ordered-semidom})$

<proof>

lemma *of-nat-less-imp-less*:

of-nat m < (of-nat n :: 'a :: ordered-semidom) ==> m < n

<proof>

lemma *of-nat-less-iff [simp]*:

(of-nat m < (of-nat n :: 'a :: ordered-semidom)) = (m < n)

<proof>

Special cases where either operand is zero

lemmas *of-nat-0-less-iff = of-nat-less-iff [of 0, simplified]*

lemmas *of-nat-less-0-iff = of-nat-less-iff [of - 0, simplified]*

declare *of-nat-0-less-iff [simp]*

declare *of-nat-less-0-iff [simp]*

lemma *of-nat-le-iff [simp]*:

(of-nat m ≤ (of-nat n :: 'a :: ordered-semidom)) = (m ≤ n)

<proof>

Special cases where either operand is zero

lemmas *of-nat-0-le-iff = of-nat-le-iff [of 0, simplified]*

lemmas *of-nat-le-0-iff = of-nat-le-iff [of - 0, simplified]*

declare *of-nat-0-le-iff [simp]*

declare *of-nat-le-0-iff [simp]*

The ordering on the *comm-semiring-1-cancel* is necessary to exclude the possibility of a finite field, which indeed wraps back to zero.

lemma *of-nat-eq-iff [simp]*:

(of-nat m = (of-nat n :: 'a :: ordered-semidom)) = (m = n)

<proof>

Special cases where either operand is zero

lemmas *of-nat-0-eq-iff = of-nat-eq-iff [of 0, simplified]*

lemmas *of-nat-eq-0-iff = of-nat-eq-iff [of - 0, simplified]*

declare *of-nat-0-eq-iff [simp]*

declare *of-nat-eq-0-iff [simp]*

lemma *of-nat-diff [simp]*:

n ≤ m ==> of-nat (m - n) = of-nat m - (of-nat n :: 'a :: comm-ring-1)

<proof>

end

18 Datatype-Universe: Analogues of the Cartesian Product and Disjoint Sum for Datatypes

```

theory Datatype-Universe
imports NatArith Sum-Type
begin

```

```

typedef (Node)
  ('a,'b) node = {p. EX f x k. p = (f::nat=>'b+nat, x::'a+nat) & f k = Inr 0}
  — it is a subtype of (nat=>'b+nat) * ('a+nat)
  ⟨proof⟩

```

Datatypes will be represented by sets of type *node*

```

types 'a item          = ('a, unit) node set
      ('a, 'b) dtree = ('a, 'b) node set

```

consts

```

apfst    :: ['a=>'c, 'a*'b] => 'c*'b
Push     :: [('b + nat), nat => ('b + nat)] => (nat => ('b + nat))

```

```

Push-Node :: [('b + nat), ('a, 'b) node] => ('a, 'b) node
ndepth    :: ('a, 'b) node => nat

```

```

Atom      :: ('a + nat) => ('a, 'b) dtree
Leaf      :: 'a => ('a, 'b) dtree
Numb      :: nat => ('a, 'b) dtree
Scons     :: [('a, 'b) dtree, ('a, 'b) dtree] => ('a, 'b) dtree
In0       :: ('a, 'b) dtree => ('a, 'b) dtree
In1       :: ('a, 'b) dtree => ('a, 'b) dtree
Lim       :: ('b => ('a, 'b) dtree) => ('a, 'b) dtree

```

```

ntrunc    :: [nat, ('a, 'b) dtree] => ('a, 'b) dtree

```

```

uprod     :: [('a, 'b) dtree set, ('a, 'b) dtree set] => ('a, 'b) dtree set
usum      :: [('a, 'b) dtree set, ('a, 'b) dtree set] => ('a, 'b) dtree set

```

```

Split     :: [[('a, 'b) dtree, ('a, 'b) dtree] => 'c, ('a, 'b) dtree] => 'c
Case      :: [[('a, 'b) dtree] => 'c, [('a, 'b) dtree] => 'c, ('a, 'b) dtree] => 'c

```

```

dprod     :: [((('a, 'b) dtree * ('a, 'b) dtree)set, (('a, 'b) dtree * ('a, 'b) dtree)set]
              => (('a, 'b) dtree * ('a, 'b) dtree)set
dsum      :: [((('a, 'b) dtree * ('a, 'b) dtree)set, (('a, 'b) dtree * ('a, 'b) dtree)set]
              => (('a, 'b) dtree * ('a, 'b) dtree)set

```

defs

```

Push-Node-def: Push-Node == (%n x. Abs-Node (apfst (Push n) (Rep-Node

```

$x)))$

apfst-def: $apfst == (\%f \ (x,y). \ (f(x),y))$
Push-def: $Push == (\%b \ h. \ nat-case \ b \ h)$

Atom-def: $Atom == (\%x. \ \{Abs-Node((\%k. \ Inr \ 0, \ x))\})$
Scons-def: $Scons \ M \ N == (Push-Node \ (Inr \ 1) \ 'M) \ Un \ (Push-Node \ (Inr \ (Suc \ 1)) \ 'N)$

Leaf-def: $Leaf == Atom \ o \ Inl$
Numb-def: $Numb == Atom \ o \ Inr$

In0-def: $In0(M) == Scons \ (Numb \ 0) \ M$
In1-def: $In1(M) == Scons \ (Numb \ 1) \ M$

Lim-def: $Lim \ f == Union \ \{z. \ ? \ x. \ z = Push-Node \ (Inl \ x) \ ' \ (f \ x)\}$

ndepth-def: $ndepth(n) == (\%(f,x). \ LEAST \ k. \ f \ k = Inr \ 0) \ (Rep-Node \ n)$
ntrunc-def: $ntrunc \ k \ N == \{n. \ n:N \ \& \ ndepth(n) < k\}$

uprod-def: $uprod \ A \ B == UN \ x:A. \ UN \ y:B. \ \{ \ Scons \ x \ y \}$
usum-def: $usum \ A \ B == In0'A \ Un \ In1'B$

Split-def: $Split \ c \ M == THE \ u. \ EX \ x \ y. \ M = Scons \ x \ y \ \& \ u = c \ x \ y$

Case-def: $Case \ c \ d \ M == THE \ u. \ (EX \ x. \ M = In0(x) \ \& \ u = c(x))$
 $\quad \quad \quad | \ (EX \ y. \ M = In1(y) \ \& \ u = d(y))$

dprod-def: $dprod \ r \ s == UN \ (x,x'):r. \ UN \ (y,y'):s. \ \{(Scons \ x \ y, \ Scons \ x' \ y')\}$

dsum-def: $dsum \ r \ s == (UN \ (x,x'):r. \ \{(In0(x), In0(x'))\}) \ Un$
 $\quad \quad \quad (UN \ (y,y'):s. \ \{(In1(y), In1(y'))\})$

lemma *apfst-conv* [*simp*]: $\text{apfst } f \ (a,b) = (f(a),b)$
 $\langle \text{proof} \rangle$

lemma *apfst-convE*:

$$\begin{aligned} & [[\ q = \text{apfst } f \ p; \ \forall x \ y. \ [[\ p = (x,y); \ q = (f(x),y) \]]] ==> R \\ & \quad]]] ==> R \end{aligned}$$

 $\langle \text{proof} \rangle$

lemma *Push-inject1*: $\text{Push } i \ f = \text{Push } j \ g ==> i=j$
 $\langle \text{proof} \rangle$

lemma *Push-inject2*: $\text{Push } i \ f = \text{Push } j \ g ==> f=g$
 $\langle \text{proof} \rangle$

lemma *Push-inject*:

$$[[\ \text{Push } i \ f = \text{Push } j \ g; \ [[\ i=j; \ f=g \]]] ==> P \]]] ==> P$$

 $\langle \text{proof} \rangle$

lemma *Push-neq-K0*: $\text{Push } (\text{Inr } (\text{Suc } k)) \ f = (\%z. \text{Inr } 0) ==> P$
 $\langle \text{proof} \rangle$

lemmas *Abs-Node-inj* = *Abs-Node-inject* [*THEN* [2] *rev-iffD1*, *standard*]

lemma *Node-K0-I*: $(\%k. \text{Inr } 0, \ a) : \text{Node}$
 $\langle \text{proof} \rangle$

lemma *Node-Push-I*: $p : \text{Node} ==> \text{apfst } (\text{Push } i) \ p : \text{Node}$
 $\langle \text{proof} \rangle$

18.1 Freeness: Distinctness of Constructors

lemma *Scons-not-Atom* [*iff*]: $\text{Scons } M \ N \neq \text{Atom}(a)$
 $\langle \text{proof} \rangle$

lemmas *Atom-not-Scons* = *Scons-not-Atom* [*THEN not-sym*, *standard*]
declare *Atom-not-Scons* [*iff*]

lemma *inj-Atom*: $\text{inj}(\text{Atom})$

$\langle proof \rangle$

lemmas *Atom-inject* = *inj-Atom* [*THEN injD*, *standard*]

lemma *Atom-Atom-eq* [*iff*]: (*Atom*(*a*)=*Atom*(*b*)) = (*a*=*b*)

$\langle proof \rangle$

lemma *inj-Leaf*: *inj*(*Leaf*)

$\langle proof \rangle$

lemmas *Leaf-inject* = *inj-Leaf* [*THEN injD*, *standard*]

declare *Leaf-inject* [*dest!*]

lemma *inj-Numb*: *inj*(*Numb*)

$\langle proof \rangle$

lemmas *Numb-inject* = *inj-Numb* [*THEN injD*, *standard*]

declare *Numb-inject* [*dest!*]

lemma *Push-Node-inject*:

[[*Push-Node i m = Push-Node j n*; [[*i=j*; *m=n*]] ==> *P*
[[]] ==> *P*

$\langle proof \rangle$

lemma *Scons-inject-lemma1*: *Scons M N* <= *Scons M' N'* ==> *M* <= *M'*

$\langle proof \rangle$

lemma *Scons-inject-lemma2*: *Scons M N* <= *Scons M' N'* ==> *N* <= *N'*

$\langle proof \rangle$

lemma *Scons-inject1*: *Scons M N* = *Scons M' N'* ==> *M* = *M'*

$\langle proof \rangle$

lemma *Scons-inject2*: *Scons M N* = *Scons M' N'* ==> *N* = *N'*

$\langle proof \rangle$

lemma *Scons-inject*:

[[*Scons M N* = *Scons M' N'*; [[*M*=*M'*; *N*=*N'*]] ==> *P*]] ==> *P*

$\langle proof \rangle$

lemma *Scons-Scons-eq* [*iff*]: (*Scons M N* = *Scons M' N'*) = (*M*=*M'* & *N*=*N'*)

$\langle proof \rangle$

lemma *Scons-not-Leaf* [iff]: *Scons* *M N* \neq *Leaf*(*a*)
 ⟨proof⟩

lemmas *Leaf-not-Scons* = *Scons-not-Leaf* [THEN not-sym, standard]
declare *Leaf-not-Scons* [iff]

lemma *Scons-not-Numb* [iff]: *Scons* *M N* \neq *Numb*(*k*)
 ⟨proof⟩

lemmas *Numb-not-Scons* = *Scons-not-Numb* [THEN not-sym, standard]
declare *Numb-not-Scons* [iff]

lemma *Leaf-not-Numb* [iff]: *Leaf*(*a*) \neq *Numb*(*k*)
 ⟨proof⟩

lemmas *Numb-not-Leaf* = *Leaf-not-Numb* [THEN not-sym, standard]
declare *Numb-not-Leaf* [iff]

lemma *ndepth-K0*: *ndepth* (*Abs-Node*(%*k*. *Inr* 0, *x*)) = 0
 ⟨proof⟩

lemma *ndepth-Push-Node-aux*:
 nat-case (*Inr* (*Suc* *i*)) *f k* = *Inr* 0 \longrightarrow *Suc*(*LEAST* *x*. *f x* = *Inr* 0) \leq *k*
 ⟨proof⟩

lemma *ndepth-Push-Node*:
 ndepth (*Push-Node* (*Inr* (*Suc* *i*)) *n*) = *Suc*(*ndepth*(*n*))
 ⟨proof⟩

lemma *ntrunc-0* [simp]: *ntrunc* 0 *M* = {}
 ⟨proof⟩

lemma *ntrunc-Atom* [simp]: *ntrunc* (*Suc* *k*) (*Atom* *a*) = *Atom*(*a*)
 ⟨proof⟩

lemma *ntrunc-Leaf* [simp]: $\text{ntrunc } (\text{Suc } k) (\text{Leaf } a) = \text{Leaf}(a)$
 $\langle \text{proof} \rangle$

lemma *ntrunc-Numb* [simp]: $\text{ntrunc } (\text{Suc } k) (\text{Numb } i) = \text{Numb}(i)$
 $\langle \text{proof} \rangle$

lemma *ntrunc-Scons* [simp]:
 $\text{ntrunc } (\text{Suc } k) (\text{Scons } M N) = \text{Scons } (\text{ntrunc } k M) (\text{ntrunc } k N)$
 $\langle \text{proof} \rangle$

lemma *ntrunc-one-In0* [simp]: $\text{ntrunc } (\text{Suc } 0) (\text{In0 } M) = \{\}$
 $\langle \text{proof} \rangle$

lemma *ntrunc-In0* [simp]: $\text{ntrunc } (\text{Suc}(\text{Suc } k)) (\text{In0 } M) = \text{In0 } (\text{ntrunc } (\text{Suc } k) M)$
 $\langle \text{proof} \rangle$

lemma *ntrunc-one-In1* [simp]: $\text{ntrunc } (\text{Suc } 0) (\text{In1 } M) = \{\}$
 $\langle \text{proof} \rangle$

lemma *ntrunc-In1* [simp]: $\text{ntrunc } (\text{Suc}(\text{Suc } k)) (\text{In1 } M) = \text{In1 } (\text{ntrunc } (\text{Suc } k) M)$
 $\langle \text{proof} \rangle$

18.2 Set Constructions

lemma *uprodI* [intro!]: $[\![M:A; N:B]\!] \implies \text{Scons } M N : \text{uprod } A B$
 $\langle \text{proof} \rangle$

lemma *uprodE* [elim!]:
 $[\![c : \text{uprod } A B;$
 $\quad \text{!!}x y. [\![x:A; y:B; c = \text{Scons } x y]\!] \implies P$
 $\quad]\!] \implies P$
 $\langle \text{proof} \rangle$

lemma *uprodE2*: $[\![\text{Scons } M N : \text{uprod } A B; [\![M:A; N:B]\!] \implies P]\!] \implies P$
 $\langle \text{proof} \rangle$

lemma *usum-In0I* [intro]: $M:A \implies \text{In0}(M) : \text{usum } A B$

$\langle proof \rangle$

lemma *usum-In1I* [*intro*]: $N:B \implies In1(N) : usum\ A\ B$
 $\langle proof \rangle$

lemma *usumE* [*elim!*]:

$$\begin{aligned} & [| u : usum\ A\ B; \\ & \quad !!x. [| x:A; u=In0(x) |] \implies P; \\ & \quad !!y. [| y:B; u=In1(y) |] \implies P \\ & |] \implies P \end{aligned}$$

 $\langle proof \rangle$

lemma *In0-not-In1* [*iff*]: $In0(M) \neq In1(N)$
 $\langle proof \rangle$

lemmas *In1-not-In0 = In0-not-In1* [*THEN not-sym, standard*]
declare *In1-not-In0* [*iff*]

lemma *In0-inject*: $In0(M) = In0(N) \implies M=N$
 $\langle proof \rangle$

lemma *In1-inject*: $In1(M) = In1(N) \implies M=N$
 $\langle proof \rangle$

lemma *In0-eq* [*iff*]: $(In0\ M = In0\ N) = (M=N)$
 $\langle proof \rangle$

lemma *In1-eq* [*iff*]: $(In1\ M = In1\ N) = (M=N)$
 $\langle proof \rangle$

lemma *inj-In0*: $inj\ In0$
 $\langle proof \rangle$

lemma *inj-In1*: $inj\ In1$
 $\langle proof \rangle$

lemma *Lim-inject*: $Lim\ f = Lim\ g \implies f = g$
 $\langle proof \rangle$

lemma *ntrunc-subsetI*: $ntrunc\ k\ M \leq M$

$\langle proof \rangle$

lemma *ntrunc-subsetD*: $(!!k. \text{ntrunc } k \ M \leq N) \implies M \leq N$
 $\langle proof \rangle$

lemma *ntrunc-equality*: $(!!k. \text{ntrunc } k \ M = \text{ntrunc } k \ N) \implies M = N$
 $\langle proof \rangle$

lemma *ntrunc-o-equality*:
 $[! \text{ntrunc}(k) \circ h1 = \text{ntrunc}(k) \circ h2] \implies h1 = h2$
 $\langle proof \rangle$

lemma *uprod-mono*: $[! \ A \leq A'; \ B \leq B'] \implies \text{uprod } A \ B \leq \text{uprod } A' \ B'$
 $\langle proof \rangle$

lemma *usum-mono*: $[! \ A \leq A'; \ B \leq B'] \implies \text{usum } A \ B \leq \text{usum } A' \ B'$
 $\langle proof \rangle$

lemma *Scons-mono*: $[! \ M \leq M'; \ N \leq N'] \implies \text{Scons } M \ N \leq \text{Scons } M' \ N'$
 $\langle proof \rangle$

lemma *In0-mono*: $M \leq N \implies \text{In0}(M) \leq \text{In0}(N)$
 $\langle proof \rangle$

lemma *In1-mono*: $M \leq N \implies \text{In1}(M) \leq \text{In1}(N)$
 $\langle proof \rangle$

lemma *Split [simp]*: $\text{Split } c \ (\text{Scons } M \ N) = c \ M \ N$
 $\langle proof \rangle$

lemma *Case-In0 [simp]*: $\text{Case } c \ d \ (\text{In0 } M) = c(M)$
 $\langle proof \rangle$

lemma *Case-In1 [simp]*: $\text{Case } c \ d \ (\text{In1 } N) = d(N)$
 $\langle proof \rangle$

lemma *ntrunc-UN1*: $\text{ntrunc } k \ (\text{UN } x. f(x)) = (\text{UN } x. \text{ntrunc } k \ (f \ x))$
 $\langle proof \rangle$

lemma *Scons-UN1-x*: $Scons (UN\ x.\ f\ x)\ M = (UN\ x.\ Scons\ (f\ x)\ M)$
 $\langle proof \rangle$

lemma *Scons-UN1-y*: $Scons\ M\ (UN\ x.\ f\ x) = (UN\ x.\ Scons\ M\ (f\ x))$
 $\langle proof \rangle$

lemma *In0-UN1*: $In0(UN\ x.\ f(x)) = (UN\ x.\ In0(f(x)))$
 $\langle proof \rangle$

lemma *In1-UN1*: $In1(UN\ x.\ f(x)) = (UN\ x.\ In1(f(x)))$
 $\langle proof \rangle$

lemma *dprodI* [intro!]:
 $[[\ (M,M'):r;\ (N,N'):s\]]\ ==> (Scons\ M\ N,\ Scons\ M'\ N') : dprod\ r\ s$
 $\langle proof \rangle$

lemma *dprodE* [elim!]:
 $[[\ c : dprod\ r\ s;$
 $\quad !!x\ y\ x'\ y'.\ [[\ (x,x') : r;\ (y,y') : s;$
 $\quad \quad \quad \quad \quad \quad \quad \quad c = (Scons\ x\ y,\ Scons\ x'\ y')\]]\ ==> P$
 $]]\ ==> P$
 $\langle proof \rangle$

lemma *dsum-In0I* [intro]: $(M,M'):r ==> (In0(M), In0(M')) : dsum\ r\ s$
 $\langle proof \rangle$

lemma *dsum-In1I* [intro]: $(N,N'):s ==> (In1(N), In1(N')) : dsum\ r\ s$
 $\langle proof \rangle$

lemma *dsumE* [elim!]:
 $[[\ w : dsum\ r\ s;$
 $\quad !!x\ x'.\ [[\ (x,x') : r;\ w = (In0(x), In0(x'))\]]\ ==> P;$
 $\quad !!y\ y'.\ [[\ (y,y') : s;\ w = (In1(y), In1(y'))\]]\ ==> P$
 $]]\ ==> P$
 $\langle proof \rangle$

lemma *dprod-mono*: $[[\ r <= r';\ s <= s'\]]\ ==> dprod\ r\ s <= dprod\ r'\ s'$
 $\langle proof \rangle$

lemma *dsum-mono*: $[[\ r <= r';\ s <= s' \] \implies \text{dsum } r\ s <= \text{dsum } r'\ s']$
 $\langle \text{proof} \rangle$

lemma *dprod-Sigma*: $(\text{dprod } (A <*> B) (C <*> D)) <= (\text{uprod } A\ C) <*> (\text{uprod } B\ D)$
 $\langle \text{proof} \rangle$

lemmas *dprod-subset-Sigma* = *subset-trans* [OF *dprod-mono* *dprod-Sigma*, *standard*]

lemma *dprod-subset-Sigma2*:
 $(\text{dprod } (\text{Sigma } A\ B) (\text{Sigma } C\ D)) <=$
 $\text{Sigma } (\text{uprod } A\ C) (\text{Split } (\%x\ y. \text{uprod } (B\ x) (D\ y)))$
 $\langle \text{proof} \rangle$

lemma *dsum-Sigma*: $(\text{dsum } (A <*> B) (C <*> D)) <= (\text{usum } A\ C) <*> (\text{usum } B\ D)$
 $\langle \text{proof} \rangle$

lemmas *dsum-subset-Sigma* = *subset-trans* [OF *dsum-mono* *dsum-Sigma*, *standard*]

lemma *Domain-dprod* [simp]: $\text{Domain } (\text{dprod } r\ s) = \text{uprod } (\text{Domain } r) (\text{Domain } s)$
 $\langle \text{proof} \rangle$

lemma *Domain-dsum* [simp]: $\text{Domain } (\text{dsum } r\ s) = \text{usum } (\text{Domain } r) (\text{Domain } s)$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

end

19 Datatype: Datatypes

theory *Datatype*
imports *Datatype-Universe*
begin

19.1 Representing primitive types

rep-datatype *bool*

distinct *True-not-False False-not-True*

induction *bool-induct*

declare *case-split* [*cases type: bool*]

— prefer plain propositional version

rep-datatype *unit*

induction *unit-induct*

rep-datatype *prod*

inject *Pair-eq*

induction *prod-induct*

rep-datatype *sum*

distinct *Inl-not-Inr Inr-not-Inl*

inject *Inl-eq Inr-eq*

induction *sum-induct*

$\langle ML \rangle$

lemma *surjective-sum*: *sum-case* ($\%x::'a. f (Inl x)$) ($\%y::'b. f (Inr y)$) *s* = *f(s)*

$\langle proof \rangle$

lemma *sum-case-weak-cong*: *s* = *t* \implies *sum-case* *f g s* = *sum-case* *f g t*

— Prevents simplification of *f* and *g*: much faster.

$\langle proof \rangle$

lemma *sum-case-inject*:

sum-case *f1 f2* = *sum-case* *g1 g2* \implies (*f1* = *g1* \implies *f2* = *g2* \implies *P*) \implies *P*

$\langle proof \rangle$

constdefs

Suml :: (*'a* \implies *'c*) \implies *'a* + *'b* \implies *'c*

Suml == ($\%f. \text{sum-case } f \text{ arbitrary}$)

Sumr :: (*'b* \implies *'c*) \implies *'a* + *'b* \implies *'c*

Sumr == *sum-case arbitrary*

lemma *Suml-inject*: *Suml f* = *Suml g* \implies *f* = *g*

$\langle proof \rangle$

lemma *Sumr-inject*: *Sumr f* = *Sumr g* \implies *f* = *g*

$\langle proof \rangle$

19.2 Finishing the datatype package setup

Belongs to theory *Datatype-Universe*; hides popular names.

hide *const Push Node Atom Leaf Numb Lim Split Case Suml Sumr*
hide *type node item*

19.3 Further cases/induct rules for tuples

lemma *prod-cases3* [*case-names fields, cases type*]:
 $(!!a\ b\ c. y = (a, b, c) ==> P) ==> P$
 $\langle proof \rangle$

lemma *prod-induct3* [*case-names fields, induct type*]:
 $(!!a\ b\ c. P\ (a, b, c)) ==> P\ x$
 $\langle proof \rangle$

lemma *prod-cases4* [*case-names fields, cases type*]:
 $(!!a\ b\ c\ d. y = (a, b, c, d) ==> P) ==> P$
 $\langle proof \rangle$

lemma *prod-induct4* [*case-names fields, induct type*]:
 $(!!a\ b\ c\ d. P\ (a, b, c, d)) ==> P\ x$
 $\langle proof \rangle$

lemma *prod-cases5* [*case-names fields, cases type*]:
 $(!!a\ b\ c\ d\ e. y = (a, b, c, d, e) ==> P) ==> P$
 $\langle proof \rangle$

lemma *prod-induct5* [*case-names fields, induct type*]:
 $(!!a\ b\ c\ d\ e. P\ (a, b, c, d, e)) ==> P\ x$
 $\langle proof \rangle$

lemma *prod-cases6* [*case-names fields, cases type*]:
 $(!!a\ b\ c\ d\ e\ f. y = (a, b, c, d, e, f) ==> P) ==> P$
 $\langle proof \rangle$

lemma *prod-induct6* [*case-names fields, induct type*]:
 $(!!a\ b\ c\ d\ e\ f. P\ (a, b, c, d, e, f)) ==> P\ x$
 $\langle proof \rangle$

lemma *prod-cases7* [*case-names fields, cases type*]:
 $(!!a\ b\ c\ d\ e\ f\ g. y = (a, b, c, d, e, f, g) ==> P) ==> P$
 $\langle proof \rangle$

lemma *prod-induct7* [*case-names fields, induct type*]:
 $(!!a\ b\ c\ d\ e\ f\ g. P\ (a, b, c, d, e, f, g)) ==> P\ x$
 $\langle proof \rangle$

19.4 The option type

datatype *'a option* = *None* | *Some 'a*

lemma *not-None-eq* [iff]: $(x \sim = \text{None}) = (\text{EX } y. x = \text{Some } y)$
 $\langle \text{proof} \rangle$

lemma *not-Some-eq* [iff]: $(\text{ALL } y. x \sim = \text{Some } y) = (x = \text{None})$
 $\langle \text{proof} \rangle$

lemma *option-caseE*:
 $(\text{case } x \text{ of } \text{None} \Rightarrow P \mid \text{Some } y \Rightarrow Q \ y) \Rightarrow \Rightarrow$
 $(x = \text{None} \Rightarrow \Rightarrow P \Rightarrow \Rightarrow R) \Rightarrow \Rightarrow$
 $(!!y. x = \text{Some } y \Rightarrow \Rightarrow Q \ y \Rightarrow \Rightarrow R) \Rightarrow \Rightarrow R$
 $\langle \text{proof} \rangle$

19.4.1 Operations

consts
 $the :: 'a \text{ option} \Rightarrow 'a$
primrec
 $the (\text{Some } x) = x$

consts
 $o2s :: 'a \text{ option} \Rightarrow 'a \text{ set}$
primrec
 $o2s \ \text{None} = \{\}$
 $o2s (\text{Some } x) = \{x\}$

lemma *ospec* [dest]: $(\text{ALL } x:o2s \ A. P \ x) \Rightarrow \Rightarrow A = \text{Some } x \Rightarrow \Rightarrow P \ x$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

lemma *elem-o2s* [iff]: $(x : o2s \ xo) = (xo = \text{Some } x)$
 $\langle \text{proof} \rangle$

lemma *o2s-empty-eq* [simp]: $(o2s \ xo = \{\}) = (xo = \text{None})$
 $\langle \text{proof} \rangle$

constdefs
 $option\text{-}map :: ('a \Rightarrow 'b) \Rightarrow ('a \text{ option} \Rightarrow 'b \text{ option})$
 $option\text{-}map == \%f \ y. \text{case } y \text{ of } \text{None} \Rightarrow \text{None} \mid \text{Some } x \Rightarrow \text{Some } (f \ x)$

lemma *option-map-None* [simp]: $option\text{-}map \ f \ \text{None} = \text{None}$
 $\langle \text{proof} \rangle$

lemma *option-map-Some* [simp]: $option\text{-}map \ f \ (\text{Some } x) = \text{Some } (f \ x)$
 $\langle \text{proof} \rangle$

lemma *option-map-is-None* [iff]:

$(\text{option-map } f \text{ opt} = \text{None}) = (\text{opt} = \text{None})$
 $\langle \text{proof} \rangle$

lemma *option-map-eq-Some* [iff]:

$(\text{option-map } f \text{ xo} = \text{Some } y) = (\exists z. \text{xo} = \text{Some } z \ \& \ f \ z = y)$
 $\langle \text{proof} \rangle$

lemma *option-map-comp*:

$\text{option-map } f \ (\text{option-map } g \ \text{opt}) = \text{option-map } (f \circ g) \ \text{opt}$
 $\langle \text{proof} \rangle$

lemma *option-map-o-sum-case* [simp]:

$\text{option-map } f \circ \text{sum-case } g \ h = \text{sum-case } (\text{option-map } f \circ g) \ (\text{option-map } f \circ h)$
 $\langle \text{proof} \rangle$

lemmas [code] = *imp-conv-disj*

end

theory *Divides*

imports *Datatype*

begin

axclass

div < *type*

instance *nat* :: *div* $\langle \text{proof} \rangle$

consts

div :: '*a*::*div* \Rightarrow '*a* \Rightarrow '*a* (**infixl** 70)
mod :: '*a*::*div* \Rightarrow '*a* \Rightarrow '*a* (**infixl** 70)
dvd :: '*a*::*times* \Rightarrow '*a* \Rightarrow *bool* (**infixl** 50)

defs

mod-def: $m \text{ mod } n == \text{wfrec } (\text{tranc1 pred-nat})$
 $(\%f \ j. \text{ if } j < n \mid n=0 \text{ then } j \text{ else } f \ (j-n)) \ m$

div-def: $m \text{ div } n == \text{wfrec } (\text{tranc1 pred-nat})$
 $(\%f \ j. \text{ if } j < n \mid n=0 \text{ then } 0 \text{ else } \text{Suc } (f \ (j-n))) \ m$

dvd-def: $m \text{ dvd } n == \exists k. \ n = m * k$

constdefs

```

quorem :: (nat*nat) * (nat*nat) => bool
quorem == %0((a,b), (q,r)).
          a = b*q + r &
          (if 0<b then 0≤r & r<b else b<r & r ≤0)

```

19.5 Initial Lemmas**lemmas** *wf-less-trans* =

```

def-wfrec [THEN trans, OF eq-reflection wf-pred-nat [THEN wf-trancl],
          standard]

```

lemma *mod-eq*: (%m. m mod n) =

```

wfrec (trancl pred-nat) (%f j. if j<n | n=0 then j else f (j-n))

```

⟨proof⟩

lemma *div-eq*: (%m. m div n) = wfrec (trancl pred-nat)

```

(%f j. if j<n | n=0 then 0 else Suc (f (j-n)))

```

⟨proof⟩

lemma *DIVISION-BY-ZERO-DIV* [simp]: a div 0 = (0::nat)

⟨proof⟩

lemma *DIVISION-BY-ZERO-MOD* [simp]: a mod 0 = (a::nat)

⟨proof⟩

19.6 Remainder**lemma** *mod-less* [simp]: m<n ==> m mod n = (m::nat)

⟨proof⟩

lemma *mod-geq*: ~ m < (n::nat) ==> m mod n = (m-n) mod n

⟨proof⟩

lemma *le-mod-geq*: (n::nat) ≤ m ==> m mod n = (m-n) mod n

⟨proof⟩

lemma *mod-if*: m mod (n::nat) = (if m<n then m else (m-n) mod n)

⟨proof⟩

lemma *mod-1* [simp]: m mod Suc 0 = 0

⟨proof⟩

lemma *mod-self* [simp]: n mod n = (0::nat)

$\langle proof \rangle$

lemma *mod-add-self2* [simp]: $(m+n) \bmod n = m \bmod (n::nat)$
 $\langle proof \rangle$

lemma *mod-add-self1* [simp]: $(n+m) \bmod n = m \bmod (n::nat)$
 $\langle proof \rangle$

lemma *mod-mult-self1* [simp]: $(m + k*n) \bmod n = m \bmod (n::nat)$
 $\langle proof \rangle$

lemma *mod-mult-self2* [simp]: $(m + n*k) \bmod n = m \bmod (n::nat)$
 $\langle proof \rangle$

lemma *mod-mult-distrib*: $(m \bmod n) * (k::nat) = (m*k) \bmod (n*k)$
 $\langle proof \rangle$

lemma *mod-mult-distrib2*: $(k::nat) * (m \bmod n) = (k*m) \bmod (k*n)$
 $\langle proof \rangle$

lemma *mod-mult-self-is-0* [simp]: $(m*n) \bmod n = (0::nat)$
 $\langle proof \rangle$

lemma *mod-mult-self1-is-0* [simp]: $(n*m) \bmod n = (0::nat)$
 $\langle proof \rangle$

19.7 Quotient

lemma *div-less* [simp]: $m < n ==> m \operatorname{div} n = (0::nat)$
 $\langle proof \rangle$

lemma *div-geq*: $[| 0 < n; \sim m < n |] ==> m \operatorname{div} n = \operatorname{Suc}((m-n) \operatorname{div} n)$
 $\langle proof \rangle$

lemma *le-div-geq*: $[| 0 < n; n \leq m |] ==> m \operatorname{div} n = \operatorname{Suc}((m-n) \operatorname{div} n)$
 $\langle proof \rangle$

lemma *div-if*: $0 < n ==> m \operatorname{div} n = (\text{if } m < n \text{ then } 0 \text{ else } \operatorname{Suc}((m-n) \operatorname{div} n))$
 $\langle proof \rangle$

lemma *mod-div-equality*: $(m \operatorname{div} n)*n + m \bmod n = (m::nat)$
 $\langle proof \rangle$

lemma *mod-div-equality2*: $n * (m \operatorname{div} n) + m \bmod n = (m::nat)$
 $\langle proof \rangle$

19.8 Simproc for Cancelling Div and Mod

lemma *div-mod-equality*: $((m \text{ div } n) * n + m \text{ mod } n) + k = (m::nat) + k$
 $\langle proof \rangle$

lemma *div-mod-equality2*: $(n * (m \text{ div } n) + m \text{ mod } n) + k = (m::nat) + k$
 $\langle proof \rangle$

$\langle ML \rangle$

lemma *mult-div-cancel*: $(n::nat) * (m \text{ div } n) = m - (m \text{ mod } n)$
 $\langle proof \rangle$

lemma *mod-less-divisor* [simp]: $0 < n ==> m \text{ mod } n < (n::nat)$
 $\langle proof \rangle$

lemma *mod-le-divisor*[simp]: $0 < n ==> m \text{ mod } n \leq (n::nat)$
 $\langle proof \rangle$

lemma *div-mult-self-is-m* [simp]: $0 < n ==> (m * n) \text{ div } n = (m::nat)$
 $\langle proof \rangle$

lemma *div-mult-self1-is-m* [simp]: $0 < n ==> (n * m) \text{ div } n = (m::nat)$
 $\langle proof \rangle$

19.9 Proving facts about Quotient and Remainder

lemma *unique-quotient-lemma*:
 $\llbracket b * q' + r' \leq b * q + r; \ x < b; \ r < b \rrbracket$
 $==> q' \leq (q::nat)$
 $\langle proof \rangle$

lemma *unique-quotient*:
 $\llbracket \text{quorem } ((a,b), (q,r)); \ \text{quorem } ((a,b), (q',r')); \ 0 < b \rrbracket$
 $==> q = q'$
 $\langle proof \rangle$

lemma *unique-remainder*:
 $\llbracket \text{quorem } ((a,b), (q,r)); \ \text{quorem } ((a,b), (q',r')); \ 0 < b \rrbracket$
 $==> r = r'$
 $\langle proof \rangle$

lemma *quorem-div-mod*: $0 < b ==> \text{quorem } ((a, b), (a \text{ div } b, a \text{ mod } b))$
 $\langle proof \rangle$

lemma *quorem-div*: $\llbracket \text{quorem } ((a,b), (q,r)); \ 0 < b \rrbracket ==> a \text{ div } b = q$
 $\langle proof \rangle$

lemma *quorem-mod*: $[[\text{quorem}((a,b),(q,r)); \ 0 < b]] \implies a \bmod b = r$
 $\langle \text{proof} \rangle$

lemma *div-0* [*simp*]: $0 \text{ div } m = (0::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *mod-0* [*simp*]: $0 \bmod m = (0::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *quorem-mult1-eq*:
 $[[\text{quorem}((b,c),(q,r)); \ 0 < c]] \implies \text{quorem}((a*b, c), (a*q + a*r \text{ div } c, a*r \bmod c))$
 $\langle \text{proof} \rangle$

lemma *div-mult1-eq*: $(a*b) \text{ div } c = a*(b \text{ div } c) + a*(b \bmod c) \text{ div } (c::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *mod-mult1-eq*: $(a*b) \bmod c = a*(b \bmod c) \bmod (c::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *mod-mult1-eq'*: $(a*b) \bmod (c::\text{nat}) = ((a \bmod c) * b) \bmod c$
 $\langle \text{proof} \rangle$

lemma *mod-mult-distrib-mod*: $(a*b) \bmod (c::\text{nat}) = ((a \bmod c) * (b \bmod c)) \bmod c$
 $\langle \text{proof} \rangle$

lemma *quorem-add1-eq*:
 $[[\text{quorem}((a,c),(aq,ar)); \ \text{quorem}((b,c),(bq,br)); \ 0 < c]] \implies \text{quorem}((a+b, c), (aq + bq + (ar+br) \text{ div } c, (ar+br) \bmod c))$
 $\langle \text{proof} \rangle$

lemma *div-add1-eq*:
 $(a+b) \text{ div } (c::\text{nat}) = a \text{ div } c + b \text{ div } c + ((a \bmod c + b \bmod c) \text{ div } c)$
 $\langle \text{proof} \rangle$

lemma *mod-add1-eq*: $(a+b) \bmod (c::\text{nat}) = (a \bmod c + b \bmod c) \bmod c$
 $\langle \text{proof} \rangle$

19.10 Proving $a \text{ div } (b * c) = a \text{ div } b \text{ div } c$

lemma *mod-lemma*: $[[(0::\text{nat}) < c; \ r < b]] \implies b * (q \bmod c) + r < b * c$

$\langle proof \rangle$

lemma *quorem-mult2-eq*: $[[\text{quorem } ((a,b), (q,r)); \ 0 < b; \ 0 < c]]$
 $\implies \text{quorem } ((a, b*c), (q \text{ div } c, b*(q \text{ mod } c) + r))$
 $\langle proof \rangle$

lemma *div-mult2-eq*: $a \text{ div } (b*c) = (a \text{ div } b) \text{ div } (c::nat)$
 $\langle proof \rangle$

lemma *mod-mult2-eq*: $a \text{ mod } (b*c) = b*(a \text{ div } b \text{ mod } c) + a \text{ mod } (b::nat)$
 $\langle proof \rangle$

19.11 Cancellation of Common Factors in Division

lemma *div-mult-mult-lemma*:
 $[[(0::nat) < b; \ 0 < c]] \implies (c*a) \text{ div } (c*b) = a \text{ div } b$
 $\langle proof \rangle$

lemma *div-mult-mult1* [simp]: $(0::nat) < c \implies (c*a) \text{ div } (c*b) = a \text{ div } b$
 $\langle proof \rangle$

lemma *div-mult-mult2* [simp]: $(0::nat) < c \implies (a*c) \text{ div } (b*c) = a \text{ div } b$
 $\langle proof \rangle$

19.12 Further Facts about Quotient and Remainder

lemma *div-1* [simp]: $m \text{ div } \text{Suc } 0 = m$
 $\langle proof \rangle$

lemma *div-self* [simp]: $0 < n \implies n \text{ div } n = (1::nat)$
 $\langle proof \rangle$

lemma *div-add-self2*: $0 < n \implies (m+n) \text{ div } n = \text{Suc } (m \text{ div } n)$
 $\langle proof \rangle$

lemma *div-add-self1*: $0 < n \implies (n+m) \text{ div } n = \text{Suc } (m \text{ div } n)$
 $\langle proof \rangle$

lemma *div-mult-self1* [simp]: $!!n::nat. \ 0 < n \implies (m + k*n) \text{ div } n = k + m \text{ div } n$
 $\langle proof \rangle$

lemma *div-mult-self2* [simp]: $0 < n \implies (m + n*k) \text{ div } n = k + m \text{ div } (n::nat)$
 $\langle proof \rangle$

lemma *div-le-mono* [rule-format (no-asm)]:
 $\forall m::nat. \ m \leq n \implies (m \text{ div } k) \leq (n \text{ div } k)$
 $\langle proof \rangle$

lemma *div-le-mono2*: $!!m::nat. [| \ 0 < m; m \leq n \ |] ==> (k \text{ div } n) \leq (k \text{ div } m)$
 $\langle proof \rangle$

lemma *div-le-dividend* [*simp*]: $m \text{ div } n \leq (m::nat)$
 $\langle proof \rangle$

lemma *div-less-dividend* [*rule-format*]:
 $!!n::nat. 1 < n ==> 0 < m \dashrightarrow m \text{ div } n < m$
 $\langle proof \rangle$

declare *div-less-dividend* [*simp*]

A fact for the mutilated chess board

lemma *mod-Suc*: $Suc(m) \text{ mod } n = (if \ Suc(m \text{ mod } n) = n \text{ then } 0 \text{ else } Suc(m \text{ mod } n))$
 $\langle proof \rangle$

lemma *nat-mod-div-trivial* [*simp*]: $m \text{ mod } n \text{ div } n = (0 :: nat)$
 $\langle proof \rangle$

lemma *nat-mod-mod-trivial* [*simp*]: $m \text{ mod } n \text{ mod } n = (m \text{ mod } n :: nat)$
 $\langle proof \rangle$

19.13 The Divides Relation

lemma *dvdI* [*intro?*]: $n = m * k ==> m \text{ dvd } n$
 $\langle proof \rangle$

lemma *dvdE* [*elim?*]: $!!P. [| m \text{ dvd } n; !!k. n = m*k ==> P |] ==> P$
 $\langle proof \rangle$

lemma *dvd-0-right* [*iff*]: $m \text{ dvd } (0::nat)$
 $\langle proof \rangle$

lemma *dvd-0-left*: $0 \text{ dvd } m ==> m = (0::nat)$
 $\langle proof \rangle$

lemma *dvd-0-left-iff* [*iff*]: $(0 \text{ dvd } (m::nat)) = (m = 0)$
 $\langle proof \rangle$

lemma *dvd-1-left* [*iff*]: $Suc \ 0 \text{ dvd } k$
 $\langle proof \rangle$

lemma *dvd-1-iff-1* [*simp*]: $(m \text{ dvd } Suc \ 0) = (m = Suc \ 0)$
 $\langle proof \rangle$

lemma *dvd-refl* [*simp*]: $m \text{ dvd } (m::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-trans* [*trans*]: $[| m \text{ dvd } n; n \text{ dvd } p |] ==> m \text{ dvd } (p::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-anti-sym*: $[| m \text{ dvd } n; n \text{ dvd } m |] ==> m = (n::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-add*: $[| k \text{ dvd } m; k \text{ dvd } n |] ==> k \text{ dvd } (m+n :: \text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-diff*: $[| k \text{ dvd } m; k \text{ dvd } n |] ==> k \text{ dvd } (m-n :: \text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-diffD*: $[| k \text{ dvd } m-n; k \text{ dvd } n; n \leq m |] ==> k \text{ dvd } (m::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-diffD1*: $[| k \text{ dvd } m-n; k \text{ dvd } m; n \leq m |] ==> k \text{ dvd } (n::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-mult*: $k \text{ dvd } n ==> k \text{ dvd } (m*n :: \text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-mult2*: $k \text{ dvd } m ==> k \text{ dvd } (m*n :: \text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-triv-right* [*iff*]: $k \text{ dvd } (m*k :: \text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-triv-left* [*iff*]: $k \text{ dvd } (k*m :: \text{nat})$
 $\langle \text{proof} \rangle$

lemma *dvd-reduce*: $(k \text{ dvd } n + k) = (k \text{ dvd } (n::\text{nat}))$
 $\langle \text{proof} \rangle$

lemma *dvd-mod*: $!!n::\text{nat}. [| f \text{ dvd } m; f \text{ dvd } n |] ==> f \text{ dvd } m \text{ mod } n$
 $\langle \text{proof} \rangle$

lemma *dvd-mod-imp-dvd*: $[| (k::\text{nat}) \text{ dvd } m \text{ mod } n; k \text{ dvd } n |] ==> k \text{ dvd } m$
 $\langle \text{proof} \rangle$

lemma *dvd-mod-iff*: $k \text{ dvd } n ==> ((k::\text{nat}) \text{ dvd } m \text{ mod } n) = (k \text{ dvd } m)$
 $\langle \text{proof} \rangle$

lemma *dvd-mult-cancel*: $!!k::\text{nat}. [| k*m \text{ dvd } k*n; 0 < k |] ==> m \text{ dvd } n$
 $\langle \text{proof} \rangle$

lemma *dvd-mult-cancel1*: $0 < m ==> (m*n \text{ dvd } m) = (n = (1::\text{nat}))$

$\langle proof \rangle$

lemma *dvd-mult-cancel2*: $0 < m \implies (n * m \text{ dvd } m) = (n = (1 :: nat))$
 $\langle proof \rangle$

lemma *mult-dvd-mono*: $[i \text{ dvd } m; j \text{ dvd } n] \implies i * j \text{ dvd } (m * n :: nat)$
 $\langle proof \rangle$

lemma *dvd-mult-left*: $(i * j :: nat) \text{ dvd } k \implies i \text{ dvd } k$
 $\langle proof \rangle$

lemma *dvd-mult-right*: $(i * j :: nat) \text{ dvd } k \implies j \text{ dvd } k$
 $\langle proof \rangle$

lemma *dvd-imp-le*: $[k \text{ dvd } n; 0 < n] \implies k \leq (n :: nat)$
 $\langle proof \rangle$

lemma *dvd-eq-mod-eq-0*: $!!k :: nat. (k \text{ dvd } n) = (n \bmod k = 0)$
 $\langle proof \rangle$

lemma *dvd-mult-div-cancel*: $n \text{ dvd } m \implies n * (m \text{ div } n) = (m :: nat)$
 $\langle proof \rangle$

lemma *mod-eq-0-iff*: $(m \bmod d = 0) = (\exists q :: nat. m = d * q)$
 $\langle proof \rangle$

lemmas *mod-eq-0D* = *mod-eq-0-iff* [THEN *iffD1*]
declare *mod-eq-0D* [dest!]

lemma *mod-eqD*: $(m \bmod d = r) \implies \exists q :: nat. m = r + q * d$
 $\langle proof \rangle$

lemma *split-div*:

$P(n \text{ div } k :: nat) =$
 $((k = 0 \longrightarrow P\ 0) \wedge (k \neq 0 \longrightarrow (!i. !j < k. n = k * i + j \longrightarrow P\ i)))$
 $(\text{is } ?P = ?Q \text{ is } - = (- \wedge (- \longrightarrow ?R)))$
 $\langle proof \rangle$

lemma *split-div-lemma*:

$0 < n \implies (n * q \leq m \wedge m < n * (\text{Suc } q)) = (q = ((m :: nat) \text{ div } n))$
 $\langle proof \rangle$

theorem *split-div'*:

$P((m :: nat) \text{ div } n) = ((n = 0 \wedge P\ 0) \vee$
 $(\exists q. (n * q \leq m \wedge m < n * (\text{Suc } q)) \wedge P\ q))$
 $\langle proof \rangle$

lemma *split-mod*:

$P(n \text{ mod } k :: \text{nat}) =$
 $((k = 0 \longrightarrow P\ n) \wedge (k \neq 0 \longrightarrow (!i. !j < k. n = k*i + j \longrightarrow P\ j)))$
 $(\text{is } ?P = ?Q \text{ is } - = (- \wedge (- \longrightarrow ?R)))$
 $\langle \text{proof} \rangle$

theorem *mod-div-equality'*: $(m :: \text{nat}) \text{ mod } n = m - (m \text{ div } n) * n$
 $\langle \text{proof} \rangle$

19.14 An “induction” law for modulus arithmetic.

lemma *mod-induct-0*:

assumes *step*: $\forall i < p. P\ i \longrightarrow P\ ((\text{Suc } i) \text{ mod } p)$
and base: $P\ i$ **and** $i: i < p$
shows $P\ 0$
 $\langle \text{proof} \rangle$

lemma *mod-induct*:

assumes *step*: $\forall i < p. P\ i \longrightarrow P\ ((\text{Suc } i) \text{ mod } p)$
and base: $P\ i$ **and** $i: i < p$ **and** $j: j < p$
shows $P\ j$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

end

20 Power: Exponentiation

theory *Power*
imports *Divides*
begin

20.1 Powers for Arbitrary Semirings

axclass *recpower* \subseteq *comm-semiring-1-cancel*, *power*
power-0 [*simp*]: $a \wedge 0 = 1$
power-Suc: $a \wedge (\text{Suc } n) = a * (a \wedge n)$

lemma *power-0-Suc* [*simp*]: $(0 :: 'a :: \text{recpower}) \wedge (\text{Suc } n) = 0$
 $\langle \text{proof} \rangle$

It looks plausible as a simprule, but its effect can be strange.

lemma *power-0-left*: $0 \wedge n = (\text{if } n=0 \text{ then } 1 \text{ else } (0 :: 'a :: \text{recpower}))$
 $\langle \text{proof} \rangle$

lemma *power-one* [simp]: $1^n = (1::'a::\text{recpower})$
 <proof>

lemma *power-one-right* [simp]: $(a::'a::\text{recpower})^1 = a$
 <proof>

lemma *power-add*: $(a::'a::\text{recpower})^{m+n} = (a^m) * (a^n)$
 <proof>

lemma *power-mult*: $(a::'a::\text{recpower})^{m*n} = (a^m)^n$
 <proof>

lemma *power-mult-distrib*: $((a::'a::\text{recpower}) * b)^n = (a^n) * (b^n)$
 <proof>

lemma *zero-less-power*:
 $0 < (a::'a::\{\text{ordered-semidom}, \text{recpower}\}) \implies 0 < a^n$
 <proof>

lemma *zero-le-power*:
 $0 \leq (a::'a::\{\text{ordered-semidom}, \text{recpower}\}) \implies 0 \leq a^n$
 <proof>

lemma *one-le-power*:
 $1 \leq (a::'a::\{\text{ordered-semidom}, \text{recpower}\}) \implies 1 \leq a^n$
 <proof>

lemma *gt1-imp-ge0*: $1 < a \implies 0 \leq (a::'a::\text{ordered-semidom})$
 <proof>

lemma *power-gt1-lemma*:
 assumes *gt1*: $1 < (a::'a::\{\text{ordered-semidom}, \text{recpower}\})$
 shows $1 < a * a^n$
 <proof>

lemma *power-gt1*:
 $1 < (a::'a::\{\text{ordered-semidom}, \text{recpower}\}) \implies 1 < a^{(\text{Suc } n)}$
 <proof>

lemma *power-le-imp-le-exp*:
 assumes *gt1*: $(1::'a::\{\text{recpower}, \text{ordered-semidom}\}) < a$
 shows $!!n. a^m \leq a^n \implies m \leq n$
 <proof>

Surely we can strengthen this? It holds for $0 < a < 1$ too.

lemma *power-inject-exp* [simp]:
 $1 < (a::'a::\{\text{ordered-semidom}, \text{recpower}\}) \implies (a^m = a^n) = (m=n)$
 <proof>

Can relax the first premise to $(0::'a) < a$ in the case of the natural numbers.

lemma *power-less-imp-less-exp*:

$$[[(1::'a::\{\text{recpower}, \text{ordered-semidom}\}) < a; a^m < a^n]] ==> m < n$$

 $\langle \text{proof} \rangle$

lemma *power-mono*:

$$[[a \leq b; (0::'a::\{\text{recpower}, \text{ordered-semidom}\}) \leq a]] ==> a^n \leq b^n$$

 $\langle \text{proof} \rangle$

lemma *power-strict-mono* [rule-format]:

$$[[a < b; (0::'a::\{\text{recpower}, \text{ordered-semidom}\}) \leq a]]$$

$$==> 0 < n \dashrightarrow a^n < b^n$$

 $\langle \text{proof} \rangle$

lemma *power-eq-0-iff* [simp]:

$$(a^n = 0) = (a = (0::'a::\{\text{ordered-idom}, \text{recpower}\}) \ \& \ 0 < n)$$

 $\langle \text{proof} \rangle$

lemma *field-power-eq-0-iff* [simp]:

$$(a^n = 0) = (a = (0::'a::\{\text{field}, \text{recpower}\}) \ \& \ 0 < n)$$

 $\langle \text{proof} \rangle$

lemma *field-power-not-zero*: $a \neq (0::'a::\{\text{field}, \text{recpower}\}) ==> a^n \neq 0$
 $\langle \text{proof} \rangle$

lemma *nonzero-power-inverse*:

$$a \neq 0 ==> \text{inverse} ((a::'a::\{\text{field}, \text{recpower}\})^n) = (\text{inverse } a)^n$$

 $\langle \text{proof} \rangle$

Perhaps these should be simprules.

lemma *power-inverse*:

$$\text{inverse} ((a::'a::\{\text{field}, \text{division-by-zero}, \text{recpower}\})^n) = (\text{inverse } a)^n$$

 $\langle \text{proof} \rangle$

lemma *power-one-over*: $1 / (a::'a::\{\text{field}, \text{division-by-zero}, \text{recpower}\})^n =$

$$(1 / a)^n$$

 $\langle \text{proof} \rangle$

lemma *nonzero-power-divide*:

$$b \neq 0 ==> (a/b)^n = ((a::'a::\{\text{field}, \text{recpower}\})^n) / (b^n)$$

 $\langle \text{proof} \rangle$

lemma *power-divide*:

$$(a/b)^n = ((a::'a::\{\text{field}, \text{division-by-zero}, \text{recpower}\})^n) / b^n$$

 $\langle \text{proof} \rangle$

lemma *power-abs*: $\text{abs}(a^n) = \text{abs}(a::'a::\{\text{ordered-idom}, \text{recpower}\})^n$

$\langle \text{proof} \rangle$

lemma *zero-less-power-abs-iff* [simp]:

$$(0 < (\text{abs } a) ^ n) = (a \neq (0 :: 'a :: \{\text{ordered-idom}, \text{recpower}\}) \mid n = 0)$$

⟨proof⟩

lemma *zero-le-power-abs* [simp]:

$$(0 :: 'a :: \{\text{ordered-idom}, \text{recpower}\}) \leq (\text{abs } a) ^ n$$

⟨proof⟩

lemma *power-minus*: $(-a) ^ n = (-1) ^ n * (a :: 'a :: \{\text{comm-ring-1}, \text{recpower}\}) ^ n$

⟨proof⟩

Lemma for *power-strict-decreasing*

lemma *power-Suc-less*:

$$[[(0 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) < a; a < 1]] \\ \implies a * a ^ n < a ^ n$$

⟨proof⟩

lemma *power-strict-decreasing*:

$$[[n < N; 0 < a; a < (1 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\})]] \\ \implies a ^ N < a ^ n$$

⟨proof⟩

Proof resembles that of *power-strict-decreasing*

lemma *power-decreasing*:

$$[[n \leq N; 0 \leq a; a \leq (1 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\})]] \\ \implies a ^ N \leq a ^ n$$

⟨proof⟩

lemma *power-Suc-less-one*:

$$[[0 < a; a < (1 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\})]] \implies a ^ \text{Suc } n < 1$$

⟨proof⟩

Proof again resembles that of *power-strict-decreasing*

lemma *power-increasing*:

$$[[n \leq N; (1 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) \leq a]] \implies a ^ n \leq a ^ N$$

⟨proof⟩

Lemma for *power-strict-increasing*

lemma *power-less-power-Suc*:

$$(1 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) < a \implies a ^ n < a * a ^ n$$

⟨proof⟩

lemma *power-strict-increasing*:

$$[[n < N; (1 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) < a]] \implies a ^ n < a ^ N$$

⟨proof⟩

lemma *power-increasing-iff* [simp]:

$1 < (b :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) \implies (b \wedge x \leq b \wedge y) = (x \leq y)$
 $\langle \text{proof} \rangle$

lemma *power-strict-increasing-iff* [simp]:

$1 < (b :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) \implies (b \wedge x < b \wedge y) = (x < y)$
 $\langle \text{proof} \rangle$

lemma *power-le-imp-le-base*:

assumes $le: a \wedge \text{Suc } n \leq b \wedge \text{Suc } n$
and $x_{\text{nonneg}}: (0 :: 'a :: \{\text{ordered-semidom}, \text{recpower}\}) \leq a$
and $y_{\text{nonneg}}: 0 \leq b$
shows $a \leq b$
 $\langle \text{proof} \rangle$

lemma *power-inject-base*:

$[| a \wedge \text{Suc } n = b \wedge \text{Suc } n; 0 \leq a; 0 \leq b |]$
 $\implies a = (b :: 'a :: \{\text{ordered-semidom}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

20.2 Exponentiation for the Natural Numbers

primrec (*power*)

$p \wedge 0 = 1$
 $p \wedge (\text{Suc } n) = (p :: \text{nat}) * (p \wedge n)$

instance $\text{nat} :: \text{recpower}$

$\langle \text{proof} \rangle$

lemma *nat-one-le-power* [simp]: $1 \leq i \implies \text{Suc } 0 \leq i \wedge n$

$\langle \text{proof} \rangle$

lemma *le-imp-power-dvd*: $!!i :: \text{nat}. m \leq n \implies i \wedge m \text{ dvd } i \wedge n$

$\langle \text{proof} \rangle$

Valid for the naturals, but what if $0 < i < 1$? Premises cannot be weakened:
 consider the case where $i = (0 :: 'a)$, $m = (1 :: 'a)$ and $n = (0 :: 'a)$.

lemma *nat-power-less-imp-less*: $!!i :: \text{nat}. [| 0 < i; i \wedge m < i \wedge n |] \implies m < n$

$\langle \text{proof} \rangle$

lemma *nat-zero-less-power-iff* [simp]: $(0 < x \wedge n) = (x \neq (0 :: \text{nat}) \mid n = 0)$

$\langle \text{proof} \rangle$

lemma *power-le-dvd* [rule-format]: $k \wedge j \text{ dvd } n \longrightarrow i \leq j \longrightarrow k \wedge i \text{ dvd } (n :: \text{nat})$

$\langle \text{proof} \rangle$

lemma *power-dvd-imp-le*: $[| i \wedge m \text{ dvd } i \wedge n; (1 :: \text{nat}) < i |] \implies m \leq n$

$\langle \text{proof} \rangle$

lemma *power-diff*:

```

assumes  $nz: a \sim = 0$ 
shows  $n \leq m \implies (a :: 'a :: \{\text{recpower}, \text{field}\}) \wedge (m - n) = (a^m) / (a^n)$ 
 $\langle \text{proof} \rangle$ 

```

ML bindings for the general exponentiation theorems

$\langle ML \rangle$

ML bindings for the remaining theorems

$\langle ML \rangle$

end

21 Finite-Set: Finite sets

```

theory Finite-Set
imports Power Inductive Lattice-Locales
begin

```

21.1 Definition and basic properties

```

consts Finites :: 'a set set
syntax
  finite :: 'a set  $\Rightarrow$  bool
translations
  finite  $A \equiv A : \text{Finites}$ 

```

inductive *Finites*

intros

```

  emptyI [simp, intro!]:  $\{\} : \text{Finites}$ 
  insertI [simp, intro!]:  $A : \text{Finites} \implies \text{insert } a \ A : \text{Finites}$ 

```

axclass *finite* \subseteq *type*

finite: *finite* *UNIV*

lemma *ex-new-if-finite*: — does not depend on def of finite at all

```

assumes  $\neg \text{finite } (\text{UNIV} :: 'a \text{ set})$  and finite  $A$ 
shows  $\exists a :: 'a. a \notin A$ 

```

$\langle \text{proof} \rangle$

lemma *finite-induct* [*case-names* *empty insert*, *induct set*: *Finites*]:

```

  finite  $F \implies$ 
     $P \ \{\} \implies (!x \ F. \text{finite } F \implies x \notin F \implies P \ F \implies P \ (\text{insert } x \ F)) \implies$ 
     $P \ F$ 
  — Discharging  $x \notin F$  entails extra work.

```

$\langle \text{proof} \rangle$

lemma *finite-ne-induct*[*case-names* *singleton insert*, *consumes* 2]:

assumes *fin*: *finite F* **shows** $F \neq \{\} \implies$
 $\llbracket \bigwedge x. P\{x\};$
 $\bigwedge x F. \llbracket \text{finite } F; F \neq \{\}; x \notin F; P F \rrbracket \implies P (\text{insert } x F) \rrbracket$
 $\implies P F$
 $\langle \text{proof} \rangle$

lemma *finite-subset-induct* [*consumes 2, case-names empty insert*]:
 $\text{finite } F \implies F \subseteq A \implies$
 $P \{\} \implies (!a F. \text{finite } F \implies a \in A \implies a \notin F \implies P F \implies P (\text{insert } a F)) \implies$
 $P F$
 $\langle \text{proof} \rangle$

Finite sets are the images of initial segments of natural numbers:

lemma *finite-imp-nat-seg-image-inj-on*:
assumes *fin*: *finite A*
shows $\exists (n::\text{nat}). f. A = f \text{ ‘ } \{i. i < n\} \ \& \ \text{inj-on } f \ \{i. i < n\}$
 $\langle \text{proof} \rangle$

lemma *nat-seg-image-imp-finite*:
 $!!f A. A = f \text{ ‘ } \{i::\text{nat}. i < n\} \implies \text{finite } A$
 $\langle \text{proof} \rangle$

lemma *finite-conv-nat-seg-image*:
 $\text{finite } A = (\exists (n::\text{nat}). f. A = f \text{ ‘ } \{i::\text{nat}. i < n\})$
 $\langle \text{proof} \rangle$

21.1.1 Finiteness and set theoretic constructions

lemma *finite-UnI*: $\text{finite } F \implies \text{finite } G \implies \text{finite } (F \text{ Un } G)$
— The union of two finite sets is finite.
 $\langle \text{proof} \rangle$

lemma *finite-subset*: $A \subseteq B \implies \text{finite } B \implies \text{finite } A$
— Every subset of a finite set is finite.
 $\langle \text{proof} \rangle$

lemma *finite-Un [iff]*: $\text{finite } (F \text{ Un } G) = (\text{finite } F \ \& \ \text{finite } G)$
 $\langle \text{proof} \rangle$

lemma *finite-Int [simp, intro]*: $\text{finite } F \mid \text{finite } G \implies \text{finite } (F \text{ Int } G)$
— The converse obviously fails.
 $\langle \text{proof} \rangle$

lemma *finite-insert [simp]*: $\text{finite } (\text{insert } a A) = \text{finite } A$
 $\langle \text{proof} \rangle$

lemma *finite-Union[simp, intro]*:
 $\llbracket \text{finite } A; !!M. M \in A \rrbracket \implies \text{finite } M \rrbracket \implies \text{finite}(\bigcup A)$

⟨proof⟩

lemma *finite-empty-induct*:

$finite\ A ==>$
 $P\ A ==> (!!a\ A.\ finite\ A ==> a:A ==> P\ A ==> P\ (A - \{a\})) ==> P\ \{\}$
 ⟨proof⟩

lemma *finite-Diff [simp]*: $finite\ B ==> finite\ (B - Ba)$
 ⟨proof⟩

lemma *finite-Diff-insert [iff]*: $finite\ (A - insert\ a\ B) = finite\ (A - B)$
 ⟨proof⟩

Image and Inverse Image over Finite Sets

lemma *finite-imageI [simp]*: $finite\ F ==> finite\ (h\ ' F)$
 — The image of a finite set is finite.
 ⟨proof⟩

lemma *finite-surj*: $finite\ A ==> B\ <= f\ ' A ==> finite\ B$
 ⟨proof⟩

lemma *finite-range-imageI*:
 $finite\ (range\ g) ==> finite\ (range\ (\%x.\ f\ (g\ x)))$
 ⟨proof⟩

lemma *finite-imageD*: $finite\ (f\ ' A) ==> inj\text{-}on\ f\ A ==> finite\ A$
 ⟨proof⟩

lemma *inj-vimage-singleton*: $inj\ f ==> f\ ' \{a\} \subseteq \{THE\ x.\ f\ x = a\}$
 — The inverse image of a singleton under an injective function is included in a singleton.
 ⟨proof⟩

lemma *finite-vimageI*: $[finite\ F; inj\ h] ==> finite\ (h\ ' F)$
 — The inverse image of a finite set under an injective function is finite.
 ⟨proof⟩

The finite UNION of finite sets

lemma *finite-UN-I*: $finite\ A ==> (!!a.\ a:A ==> finite\ (B\ a)) ==> finite\ (UN\ a:A.\ B\ a)$
 ⟨proof⟩

Strengthen RHS to $(\forall x \in A.\ finite\ (B\ x)) \wedge finite\ \{x \in A.\ B\ x \neq \{\}\}$?

We'd need to prove $finite\ C \implies \forall A\ B.\ UNION\ A\ B \subseteq C \implies finite\ \{x \in A.\ B\ x \neq \{\}\}$ by induction.

lemma *finite-UN [simp]*: $finite\ A ==> finite\ (UNION\ A\ B) = (ALL\ x:A.\ finite\ (B\ x))$

$\langle proof \rangle$

lemma *finite-Plus*: $[| \text{finite } A; \text{finite } B |] \implies \text{finite } (A <+> B)$
 $\langle proof \rangle$

Sigma of finite sets

lemma *finite-SigmaI* [simp]:
 $\text{finite } A \implies (!a. a:A \implies \text{finite } (B a)) \implies \text{finite } (\text{SIGMA } a:A. B a)$
 $\langle proof \rangle$

lemma *finite-cartesian-product*: $[| \text{finite } A; \text{finite } B |] \implies$
 $\text{finite } (A <*> B)$
 $\langle proof \rangle$

lemma *finite-Prod-UNIV*:
 $\text{finite } (\text{UNIV}::'a \text{ set}) \implies \text{finite } (\text{UNIV}::'b \text{ set}) \implies \text{finite } (\text{UNIV}::('a * 'b) \text{ set})$
 $\langle proof \rangle$

lemma *finite-cartesian-productD1*:
 $[| \text{finite } (A <*> B); B \neq \{\} |] \implies \text{finite } A$
 $\langle proof \rangle$

lemma *finite-cartesian-productD2*:
 $[| \text{finite } (A <*> B); A \neq \{\} |] \implies \text{finite } B$
 $\langle proof \rangle$

The powerset of a finite set

lemma *finite-Pow-iff* [iff]: $\text{finite } (\text{Pow } A) = \text{finite } A$
 $\langle proof \rangle$

lemma *finite-UnionD*: $\text{finite}(\bigcup A) \implies \text{finite } A$
 $\langle proof \rangle$

lemma *finite-converse* [iff]: $\text{finite } (r^{-1}) = \text{finite } r$
 $\langle proof \rangle$

Finiteness of transitive closure (Thanks to Sidi Ehmety)

lemma *finite-Field*: $\text{finite } r \implies \text{finite } (\text{Field } r)$
 — A finite relation has a finite field (= $\text{domain} \cup \text{range}$).
 $\langle proof \rangle$

lemma *trancl-subset-Field2*: $r^+ \leq \text{Field } r \times \text{Field } r$
 $\langle proof \rangle$

lemma *finite-trancl*: $\text{finite } (r^+)= \text{finite } r$
 $\langle \text{proof} \rangle$

21.2 A fold functional for finite sets

The intended behaviour is $\text{fold } f \ g \ z \ \{x_1, \dots, x_n\} = f \ (g \ x_1) \ (\dots (f \ (g \ x_n) \ z) \dots)$ if f is associative-commutative. For an application of *fold* see the definitions of sums and products over finite sets.

consts

$\text{foldSet} :: ('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow ('b \Rightarrow 'a) \Rightarrow 'a \Rightarrow ('b \text{ set} \times 'a) \text{ set}$

inductive *foldSet* $f \ g \ z$

intros

emptyI [*intro*]: $(\{\}, z) : \text{foldSet } f \ g \ z$

insertI [*intro*]:

$\llbracket x \notin A; (A, y) : \text{foldSet } f \ g \ z \rrbracket$
 $\implies (\text{insert } x \ A, f \ (g \ x) \ y) : \text{foldSet } f \ g \ z$

inductive-cases *empty-foldSetE* [*elim!*]: $(\{\}, x) : \text{foldSet } f \ g \ z$

constdefs

$\text{fold} :: ('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow ('b \Rightarrow 'a) \Rightarrow 'a \Rightarrow 'b \text{ set} \Rightarrow 'a$
 $\text{fold } f \ g \ z \ A == \text{THE } x. (A, x) : \text{foldSet } f \ g \ z$

A tempting alternative for the definiens is *if finite A then THE x. (A, x) ∈ foldSet f g e else e*. It allows the removal of finiteness assumptions from the theorems *fold-commute*, *fold-reindex* and *fold-distrib*. The proofs become ugly, with *rule-format*. It is not worth the effort.

lemma *Diff1-foldSet*:

$(A - \{x\}, y) : \text{foldSet } f \ g \ z \implies x : A \implies (A, f \ (g \ x) \ y) : \text{foldSet } f \ g \ z$
 $\langle \text{proof} \rangle$

lemma *foldSet-imp-finite*: $(A, x) : \text{foldSet } f \ g \ z \implies \text{finite } A$
 $\langle \text{proof} \rangle$

lemma *finite-imp-foldSet*: $\text{finite } A \implies \text{EX } x. (A, x) : \text{foldSet } f \ g \ z$
 $\langle \text{proof} \rangle$

21.2.1 Commutative monoids

locale *ACf* =

fixes $f :: 'a \Rightarrow 'a \Rightarrow 'a$ (**infixl** \cdot 70)
assumes *commute*: $x \cdot y = y \cdot x$
and *assoc*: $(x \cdot y) \cdot z = x \cdot (y \cdot z)$

locale *ACe* = *ACf* +

fixes $e :: 'a$

assumes *ident* [*simp*]: $x \cdot e = x$

locale *ACIf* = *ACf* +
assumes *idem*: $x \cdot x = x$

lemma (in *ACf*) *left-commute*: $x \cdot (y \cdot z) = y \cdot (x \cdot z)$
 $\langle \text{proof} \rangle$

lemmas (in *ACf*) *AC* = *assoc* *commute* *left-commute*

lemma (in *ACe*) *left-ident* [*simp*]: $e \cdot x = x$
 $\langle \text{proof} \rangle$

lemma (in *ACIf*) *idem2*: $x \cdot (x \cdot y) = x \cdot y$
 $\langle \text{proof} \rangle$

lemmas (in *ACIf*) *ACI* = *AC* *idem* *idem2*

Interpretation of locales:

interpretation *AC-add*: *ACe* [*op* + *0*::'*a*::*comm-monoid-add*]
 $\langle \text{proof} \rangle$

interpretation *AC-mult*: *ACe* [*op* * *1*::'*a*::*comm-monoid-mult*]
 $\langle \text{proof} \rangle$

21.2.2 From *foldSet* to *fold*

lemma *image-less-Suc*: $h \cdot \{i. i < \text{Suc } m\} = \text{insert } (h \ m) (h \cdot \{i. i < m\})$
 $\langle \text{proof} \rangle$

lemma *insert-image-inj-on-eq*:
 $[[\text{insert } (h \ m) \ A = h \cdot \{i. i < \text{Suc } m\}; h \ m \notin A;$
 $\text{inj-on } h \ \{i. i < \text{Suc } m\}]]$
 $\implies A = h \cdot \{i. i < m\}$
 $\langle \text{proof} \rangle$

lemma *insert-inj-onE*:
assumes *aA*: $\text{insert } a \ A = h \cdot \{i::\text{nat}. i < n\}$ **and** *anot*: $a \notin A$
and *inj-on*: $\text{inj-on } h \ \{i::\text{nat}. i < n\}$
shows $\exists hm \ m. \text{inj-on } hm \ \{i::\text{nat}. i < m\} \ \& \ A = hm \cdot \{i. i < m\} \ \& \ m < n$
 $\langle \text{proof} \rangle$

lemma (in *ACf*) *foldSet-determ-aux*:
 $!!A \ x \ x' \ h. \llbracket A = h \cdot \{i::\text{nat}. i < n\}; \text{inj-on } h \ \{i. i < n\};$
 $(A, x) : \text{foldSet } f \ g \ z; (A, x') : \text{foldSet } f \ g \ z \rrbracket$
 $\implies x' = x$
 $\langle \text{proof} \rangle$

lemma (in ACf) *foldSet-determ*:
 $(A, x) : \text{foldSet } f \ g \ z \implies (A, y) : \text{foldSet } f \ g \ z \implies y = x$
 ⟨proof⟩

lemma (in ACf) *fold-equality*: $(A, y) : \text{foldSet } f \ g \ z \implies \text{fold } f \ g \ z \ A = y$
 ⟨proof⟩

The base case for *fold*:

lemma *fold-empty [simp]*: $\text{fold } f \ g \ z \ \{\} = z$
 ⟨proof⟩

lemma (in ACf) *fold-insert-aux*: $x \notin A \implies$
 $((\text{insert } x \ A, v) : \text{foldSet } f \ g \ z) =$
 $(EX \ y. (A, y) : \text{foldSet } f \ g \ z \ \& \ v = f \ (g \ x) \ y)$
 ⟨proof⟩

The recursion equation for *fold*:

lemma (in ACf) *fold-insert[simp]*:
 $\text{finite } A \implies x \notin A \implies \text{fold } f \ g \ z \ (\text{insert } x \ A) = f \ (g \ x) \ (\text{fold } f \ g \ z \ A)$
 ⟨proof⟩

lemma (in ACf) *fold-rec*:
assumes *fin*: $\text{finite } A$ **and** *a*: $a : A$
shows $\text{fold } f \ g \ z \ A = f \ (g \ a) \ (\text{fold } f \ g \ z \ (A - \{a\}))$
 ⟨proof⟩

A simplified version for idempotent functions:

lemma (in ACIf) *fold-insert-idem*:
assumes *finA*: $\text{finite } A$
shows $\text{fold } f \ g \ z \ (\text{insert } a \ A) = g \ a \cdot \text{fold } f \ g \ z \ A$
 ⟨proof⟩

lemma (in ACIf) *foldI-conv-id*:
 $\text{finite } A \implies \text{fold } f \ g \ z \ A = \text{fold } f \ id \ z \ (g \ ` \ A)$
 ⟨proof⟩

21.2.3 Lemmas about *fold*

lemma (in ACf) *fold-commute*:
 $\text{finite } A \implies (!z. f \ x \ (\text{fold } f \ g \ z \ A) = \text{fold } f \ g \ (f \ x \ z) \ A)$
 ⟨proof⟩

lemma (in ACf) *fold-nest-Un-Int*:
 $\text{finite } A \implies \text{finite } B$
 $\implies \text{fold } f \ g \ (\text{fold } f \ g \ z \ B) \ A = \text{fold } f \ g \ (\text{fold } f \ g \ z \ (A \ \text{Int } B)) \ (A \ \text{Un } B)$
 ⟨proof⟩

lemma (in ACf) *fold-nest-Un-disjoint*:
 $\text{finite } A \implies \text{finite } B \implies A \ \text{Int } B = \{\}$

$\implies \text{fold } f \ g \ z \ (A \ \text{Un} \ B) = \text{fold } f \ g \ (\text{fold } f \ g \ z \ B) \ A$
 <proof>

lemma (in ACf) *fold-reindex*:

assumes *fin*: *finite A*

shows *inj-on h A $\implies \text{fold } f \ g \ z \ (h \text{ ` } A) = \text{fold } f \ (g \circ h) \ z \ A$*

<proof>

lemma (in ACe) *fold-Un-Int*:

finite A $\implies \text{finite B} \implies$

fold f g e A $\cdot \text{fold f g e B} =$

fold f g e (A Un B) $\cdot \text{fold f g e (A Int B)}$

<proof>

corollary (in ACe) *fold-Un-disjoint*:

finite A $\implies \text{finite B} \implies A \ \text{Int} \ B = \{\} \implies$

fold f g e (A Un B) = fold f g e A $\cdot \text{fold f g e B}$

<proof>

lemma (in ACe) *fold-UN-disjoint*:

$\llbracket \text{finite } I; \text{ALL } i:I. \text{finite } (A \ i);$

$\text{ALL } i:I. \text{ALL } j:I. i \neq j \dashrightarrow A \ i \ \text{Int} \ A \ j = \{\} \rrbracket$

$\implies \text{fold } f \ g \ e \ (\text{UNION } I \ A) =$

$\text{fold } f \ (\%i. \text{fold } f \ g \ e \ (A \ i)) \ e \ I$

<proof>

Fusion theorem, as described in Graham Hutton’s paper, A Tutorial on the Universality and Expressiveness of Fold, JFP 9:4 (355-372), 1999.

lemma (in ACf) *fold-fusion*:

includes ACf g

shows

finite A \implies

(!!x y. h (g x y) = f x (h y)) \implies

h (fold g j w A) = fold f j (h w) A

<proof>

lemma (in ACf) *fold-cong*:

finite A $\implies (!!x. x:A \implies g \ x = h \ x) \implies \text{fold } f \ g \ z \ A = \text{fold } f \ h \ z \ A$

<proof>

lemma (in ACe) *fold-Sigma*: *finite A $\implies \text{ALL } x:A. \text{finite } (B \ x) \implies$*

fold f (%x. fold f (g x) e (B x)) e A =

fold f (split g) e (SIGMA x:A. B x)

<proof>

lemma (in ACe) *fold-distrib*: *finite A \implies*

fold f (%x. f (g x) (h x)) e A = f (fold f g e A) (fold f h e A)

<proof>

21.3 Generalized summation over a set

constdefs

```
setsum :: ('a => 'b) => 'a set => 'b::comm-monoid-add
setsum f A == if finite A then fold (op +) f 0 A else 0
```

Now: lot's of fancy syntax. First, $\text{setsum } (\lambda x. e) A$ is written $\sum_{x \in A} e$.

syntax

```
-setsum :: pttrn => 'a set => 'b => 'b::comm-monoid-add  ((\SUM -:-. -) [0,
51, 10] 10)
```

syntax (xsymbols)

```
-setsum :: pttrn => 'a set => 'b => 'b::comm-monoid-add  ((\SUM -\in-. -) [0,
51, 10] 10)
```

syntax (HTML output)

```
-setsum :: pttrn => 'a set => 'b => 'b::comm-monoid-add  ((\SUM -\in-. -) [0,
51, 10] 10)
```

translations — Beware of argument permutation!

```
SUM i:A. b == setsum (%i. b) A
\sum i \in A. b == setsum (%i. b) A
```

Instead of $\sum_{x \in \{x. P\}} e$ we introduce the shorter $\sum_{x|P} e$.

syntax

```
-qsetsum :: pttrn => bool => 'a => 'a ((\SUM - | / - / -) [0,0,10] 10)
```

syntax (xsymbols)

```
-qsetsum :: pttrn => bool => 'a => 'a ((\SUM - | (-) / -) [0,0,10] 10)
```

syntax (HTML output)

```
-qsetsum :: pttrn => bool => 'a => 'a ((\SUM - | (-) / -) [0,0,10] 10)
```

translations

```
SUM x|P. t => setsum (%x. t) {x. P}
\sum x | P. t => setsum (%x. t) {x. P}
```

Finally we abbreviate $\sum_{x \in A} x$ by $\sum A$.

syntax

```
-Setsum :: 'a set => 'a::comm-monoid-mult  (\SUM - [1000] 999)
```

$\langle ML \rangle$

lemma *setsum-empty* [simp]: $\text{setsum } f \ \{\} = 0$
 $\langle \text{proof} \rangle$

lemma *setsum-insert* [simp]:

```
finite F ==> a \notin F ==> setsum f (insert a F) = f a + setsum f F
\proof
```

lemma *setsum-infinite* [simp]: $\sim \text{finite } A ==> \text{setsum } f \ A = 0$
 $\langle \text{proof} \rangle$

lemma *setsum-reindex*:

$$\text{inj-on } f \ B \implies \text{setsum } h \ (f \cdot B) = \text{setsum } (h \circ f) \ B$$

<proof>

lemma *setsum-reindex-id*:

$$\text{inj-on } f \ B \implies \text{setsum } f \ B = \text{setsum } \text{id} \ (f \cdot B)$$

<proof>

lemma *setsum-cong*:

$$A = B \implies (!x. x:B \implies f \ x = g \ x) \implies \text{setsum } f \ A = \text{setsum } g \ B$$

<proof>

lemma *strong-setsum-cong*[*cong*]:

$$\begin{aligned} A = B &\implies (!x. x:B \text{simp} \implies f \ x = g \ x) \\ &\implies \text{setsum } (\%x. f \ x) \ A = \text{setsum } (\%x. g \ x) \ B \end{aligned}$$

<proof>

lemma *setsum-cong2*: $\llbracket \bigwedge x. x \in A \implies f \ x = g \ x \rrbracket \implies \text{setsum } f \ A = \text{setsum } g \ A$

<proof>

lemma *setsum-reindex-cong*:

$$\begin{aligned} &\llbracket \text{inj-on } f \ A; B = f \cdot A; !a. a:A \implies g \ a = h \ (f \ a) \rrbracket \\ &\implies \text{setsum } h \ B = \text{setsum } g \ A \end{aligned}$$

<proof>

lemma *setsum-0*[*simp*]: $\text{setsum } (\%i. 0) \ A = 0$

<proof>

lemma *setsum-0'*: $\text{ALL } a:A. f \ a = 0 \implies \text{setsum } f \ A = 0$

<proof>

lemma *setsum-Un-Int*: $\text{finite } A \implies \text{finite } B \implies$

$$\text{setsum } g \ (A \ \text{Un} \ B) + \text{setsum } g \ (A \ \text{Int} \ B) = \text{setsum } g \ A + \text{setsum } g \ B$$

— The reversed orientation looks more natural, but LOOPS as a simplrule!

<proof>

lemma *setsum-Un-disjoint*: $\text{finite } A \implies \text{finite } B$

$$\implies A \ \text{Int} \ B = \{\} \implies \text{setsum } g \ (A \ \text{Un} \ B) = \text{setsum } g \ A + \text{setsum } g \ B$$

<proof>

lemma *setsum-UN-disjoint*:

$$\begin{aligned} \text{finite } I &\implies (\text{ALL } i:I. \text{finite } (A \ i)) \implies \\ &(\text{ALL } i:I. \text{ALL } j:I. i \neq j \longrightarrow A \ i \ \text{Int} \ A \ j = \{\}) \implies \\ &\text{setsum } f \ (\text{UNION } I \ A) = (\sum i \in I. \text{setsum } f \ (A \ i)) \end{aligned}$$

<proof>

No need to assume that C is finite. If infinite, the rhs is directly 0, and $\bigcup C$ is also infinite, hence the lhs is also 0.

lemma *setsum-Union-disjoint*:

$$\begin{aligned} & [[(ALL\ A:C. \text{finite}\ A); \\ & \quad (ALL\ A:C. ALL\ B:C. A \neq B \longrightarrow A \text{ Int } B = \{\})]] \\ & \implies \text{setsum } f (\text{Union } C) = \text{setsum } (\text{setsum } f) C \\ & \langle \text{proof} \rangle \end{aligned}$$

lemma *setsum-Sigma*: $\text{finite } A \implies ALL\ x:A. \text{finite } (B\ x) \implies$

$$(\sum x \in A. (\sum y \in B\ x. f\ x\ y)) = (\sum (x,y) \in (\text{SIGMA } x:A. B\ x). f\ x\ y)$$

 $\langle \text{proof} \rangle$

Here we can eliminate the finiteness assumptions, by cases.

lemma *setsum-cartesian-product*:

$$(\sum x \in A. (\sum y \in B. f\ x\ y)) = (\sum (x,y) \in A <*> B. f\ x\ y)$$

 $\langle \text{proof} \rangle$

lemma *setsum-addf*: $\text{setsum } (\%x. f\ x + g\ x) A = (\text{setsum } f\ A + \text{setsum } g\ A)$

$\langle \text{proof} \rangle$

21.3.1 Properties in more restricted classes of structures

lemma *setsum-SucD*: $\text{setsum } f\ A = \text{Suc } n \implies EX\ a:A. 0 < f\ a$

$\langle \text{proof} \rangle$

lemma *setsum-eq-0-iff* [*simp*]:

$\text{finite } F \implies (\text{setsum } f\ F = 0) = (ALL\ a:F. f\ a = (0::nat))$

$\langle \text{proof} \rangle$

lemma *setsum-Un-nat*: $\text{finite } A \implies \text{finite } B \implies$

$(\text{setsum } f\ (A\ \text{Un } B) :: nat) = \text{setsum } f\ A + \text{setsum } f\ B - \text{setsum } f\ (A\ \text{Int } B)$

— For the natural numbers, we have subtraction.

$\langle \text{proof} \rangle$

lemma *setsum-Un*: $\text{finite } A \implies \text{finite } B \implies$

$(\text{setsum } f\ (A\ \text{Un } B) :: 'a :: \text{ab-group-add}) =$
 $\text{setsum } f\ A + \text{setsum } f\ B - \text{setsum } f\ (A\ \text{Int } B)$

$\langle \text{proof} \rangle$

lemma *setsum-diff1-nat*: $(\text{setsum } f\ (A - \{a\}) :: nat) =$

$(\text{if } a:A \text{ then } \text{setsum } f\ A - f\ a \text{ else } \text{setsum } f\ A)$

$\langle \text{proof} \rangle$

lemma *setsum-diff1*: $\text{finite } A \implies$

$(\text{setsum } f\ (A - \{a\}) :: ('a :: \text{ab-group-add})) =$
 $(\text{if } a:A \text{ then } \text{setsum } f\ A - f\ a \text{ else } \text{setsum } f\ A)$

$\langle \text{proof} \rangle$

lemma *setsum-diff1'* [*rule-format*]: $\text{finite } A \implies a \in A \longrightarrow (\sum x \in A. f\ x) = f\ a$
 $+ (\sum x \in (A - \{a\}). f\ x)$

$\langle \text{proof} \rangle$

lemma *setsum-diff-nat*:

assumes *finB*: *finite B*

shows $B \subseteq A \implies (\text{setsum } f \ (A - B) :: \text{nat}) = (\text{setsum } f \ A) - (\text{setsum } f \ B)$

$\langle \text{proof} \rangle$

lemma *setsum-diff*:

assumes *le*: *finite A B* $B \subseteq A$

shows $\text{setsum } f \ (A - B) = \text{setsum } f \ A - ((\text{setsum } f \ B)::('a::\text{ab-group-add}))$

$\langle \text{proof} \rangle$

lemma *setsum-mono*:

assumes *le*: $\bigwedge i. i \in K \implies f \ (i::'a) \leq ((g \ i)::('b::\{\text{comm-monoid-add}, \text{pordered-ab-semigroup-add}\}))$

shows $(\sum i \in K. f \ i) \leq (\sum i \in K. g \ i)$

$\langle \text{proof} \rangle$

lemma *setsum-strict-mono*:

fixes *f* :: *'a* \Rightarrow *'b*:: $\{\text{pordered-cancel-ab-semigroup-add}, \text{comm-monoid-add}\}$

assumes *fin-ne*: *finite A* $A \neq \{\}$

shows $(!!x. x:A \implies f \ x < g \ x) \implies \text{setsum } f \ A < \text{setsum } g \ A$

$\langle \text{proof} \rangle$

lemma *setsum-negf*:

$\text{setsum } (\%x. - (f \ x)::'a::\text{ab-group-add}) \ A = - \text{setsum } f \ A$

$\langle \text{proof} \rangle$

lemma *setsum-subtractf*:

$\text{setsum } (\%x. ((f \ x)::'a::\text{ab-group-add}) - g \ x) \ A =$

$\text{setsum } f \ A - \text{setsum } g \ A$

$\langle \text{proof} \rangle$

lemma *setsum-nonneg*:

assumes *nn*: $\forall x \in A. (0::'a::\{\text{pordered-ab-semigroup-add}, \text{comm-monoid-add}\}) \leq f \ x$

shows $0 \leq \text{setsum } f \ A$

$\langle \text{proof} \rangle$

lemma *setsum-nonpos*:

assumes *np*: $\forall x \in A. f \ x \leq (0::'a::\{\text{pordered-ab-semigroup-add}, \text{comm-monoid-add}\})$

shows $\text{setsum } f \ A \leq 0$

$\langle \text{proof} \rangle$

lemma *setsum-mono2*:

fixes *f* :: *'a* \Rightarrow *'b* :: $\{\text{pordered-ab-semigroup-add-imp-le}, \text{comm-monoid-add}\}$

assumes *fin*: *finite B* **and** *sub*: $A \subseteq B$ **and** *nn*: $\bigwedge b. b \in B - A \implies 0 \leq f \ b$

shows $\text{setsum } f \ A \leq \text{setsum } f \ B$

$\langle proof \rangle$

lemma *setsum-mono3*: $finite\ B \implies A \leq B \implies$
 $ALL\ x: B - A.$
 $0 \leq ((f\ x)::'a::\{comm-monoid-add,pordered-ab-semigroup-add\}) \implies$
 $setsum\ f\ A \leq setsum\ f\ B$
 $\langle proof \rangle$

lemma *setsum-mult*:
fixes $f :: 'a \Rightarrow ('b::semiring-0-cancel)$
shows $r * setsum\ f\ A = setsum\ (\%n. r * f\ n)\ A$
 $\langle proof \rangle$

lemma *setsum-left-distrib*:
 $setsum\ f\ A * (r::'a::semiring-0-cancel) = (\sum n \in A. f\ n * r)$
 $\langle proof \rangle$

lemma *setsum-divide-distrib*:
 $setsum\ f\ A / (r::'a::field) = (\sum n \in A. f\ n / r)$
 $\langle proof \rangle$

lemma *setsum-abs[iff]*:
fixes $f :: 'a \Rightarrow ('b::lordered-ab-group-abs)$
shows $abs\ (setsum\ f\ A) \leq setsum\ (\%i. abs(f\ i))\ A$
 $\langle proof \rangle$

lemma *setsum-abs-ge-zero[iff]*:
fixes $f :: 'a \Rightarrow ('b::lordered-ab-group-abs)$
shows $0 \leq setsum\ (\%i. abs(f\ i))\ A$
 $\langle proof \rangle$

lemma *abs-setsum-abs[simp]*:
fixes $f :: 'a \Rightarrow ('b::lordered-ab-group-abs)$
shows $abs\ (\sum a \in A. abs(f\ a)) = (\sum a \in A. abs(f\ a))$
 $\langle proof \rangle$

Commuting outer and inner summation

lemma *swap-inj-on*:
 $inj-on\ (\%(i, j). (j, i))\ (A \times B)$
 $\langle proof \rangle$

lemma *swap-product*:
 $(\%(i, j). (j, i))\ ` (A \times B) = B \times A$
 $\langle proof \rangle$

lemma *setsum-commute*:

$$(\sum_{i \in A}. \sum_{j \in B}. f \ i \ j) = (\sum_{j \in B}. \sum_{i \in A}. f \ i \ j)$$

<proof>

21.4 Generalized product over a set

constdefs

setprod :: ('a => 'b) => 'a set => 'b::comm-monoid-mult
setprod f A == if finite A then fold (op *) f 1 A else 1

syntax

-setprod :: ptttrn => 'a set => 'b => 'b::comm-monoid-mult ((3PROD -:-. -) [0, 51, 10] 10)

syntax (xsymbols)

-setprod :: ptttrn => 'a set => 'b => 'b::comm-monoid-mult ((3Π -∈-. -) [0, 51, 10] 10)

syntax (HTML output)

-setprod :: ptttrn => 'a set => 'b => 'b::comm-monoid-mult ((3Π -∈-. -) [0, 51, 10] 10)

translations — Beware of argument permutation!

PROD i:A. b == *setprod* (%i. b) A
 $\prod_{i \in A}. b == \text{setprod } (\%i. b) A$

Instead of $\prod_{x \in \{x. P\}. e}$ we introduce the shorter $\prod x | P. e$.

syntax

-qsetprod :: ptttrn => bool => 'a => 'a ((3PROD - | / - / -) [0,0,10] 10)

syntax (xsymbols)

-qsetprod :: ptttrn => bool => 'a => 'a ((3Π - | (-) / -) [0,0,10] 10)

syntax (HTML output)

-qsetprod :: ptttrn => bool => 'a => 'a ((3Π - | (-) / -) [0,0,10] 10)

translations

PROD x|P. t => *setprod* (%x. t) {x. P}
 $\prod x | P. t == \text{setprod } (\%x. t) \{x. P\}$

Finally we abbreviate $\prod_{x \in A}. x$ by $\prod A$.

syntax

-Setprod :: 'a set => 'a::comm-monoid-mult (Π - [1000] 999)

<ML>

lemma *setprod-empty* [simp]: *setprod* f {} = 1
<proof>

lemma *setprod-insert* [simp]: [| finite A; a ∉ A |] ==>
setprod f (insert a A) = f a * *setprod* f A
<proof>

lemma *setprod-infinite* [*simp*]: $\sim \text{finite } A \implies \text{setprod } f \ A = 1$
 $\langle \text{proof} \rangle$

lemma *setprod-reindex*:
 $\text{inj-on } f \ B \implies \text{setprod } h \ (f \ ' \ B) = \text{setprod } (h \circ f) \ B$
 $\langle \text{proof} \rangle$

lemma *setprod-reindex-id*: $\text{inj-on } f \ B \implies \text{setprod } f \ B = \text{setprod } \text{id} \ (f \ ' \ B)$
 $\langle \text{proof} \rangle$

lemma *setprod-cong*:
 $A = B \implies (!x. x:B \implies f \ x = g \ x) \implies \text{setprod } f \ A = \text{setprod } g \ B$
 $\langle \text{proof} \rangle$

lemma *strong-setprod-cong*:
 $A = B \implies (!x. x:B = \text{simp} \implies f \ x = g \ x) \implies \text{setprod } f \ A = \text{setprod } g \ B$
 $\langle \text{proof} \rangle$

lemma *setprod-reindex-cong*: $\text{inj-on } f \ A \implies$
 $B = f \ ' \ A \implies g = h \circ f \implies \text{setprod } h \ B = \text{setprod } g \ A$
 $\langle \text{proof} \rangle$

lemma *setprod-1*: $\text{setprod } (\%i. 1) \ A = 1$
 $\langle \text{proof} \rangle$

lemma *setprod-1'*: $\text{ALL } a:F. f \ a = 1 \implies \text{setprod } f \ F = 1$
 $\langle \text{proof} \rangle$

lemma *setprod-Un-Int*: $\text{finite } A \implies \text{finite } B$
 $\implies \text{setprod } g \ (A \ \text{Un} \ B) * \text{setprod } g \ (A \ \text{Int} \ B) = \text{setprod } g \ A * \text{setprod } g \ B$
 $\langle \text{proof} \rangle$

lemma *setprod-Un-disjoint*: $\text{finite } A \implies \text{finite } B$
 $\implies A \ \text{Int} \ B = \{\} \implies \text{setprod } g \ (A \ \text{Un} \ B) = \text{setprod } g \ A * \text{setprod } g \ B$
 $\langle \text{proof} \rangle$

lemma *setprod-UN-disjoint*:
 $\text{finite } I \implies (\text{ALL } i:I. \text{finite } (A \ i)) \implies$
 $(\text{ALL } i:I. \text{ALL } j:I. i \neq j \longrightarrow A \ i \ \text{Int} \ A \ j = \{\}) \implies$
 $\text{setprod } f \ (\text{UNION } I \ A) = \text{setprod } (\%i. \text{setprod } f \ (A \ i)) \ I$
 $\langle \text{proof} \rangle$

lemma *setprod-Union-disjoint*:
 $[| (\text{ALL } A:C. \text{finite } A);$
 $(\text{ALL } A:C. \text{ALL } B:C. A \neq B \longrightarrow A \ \text{Int} \ B = \{\}) |]$
 $\implies \text{setprod } f \ (\text{Union } C) = \text{setprod } (\text{setprod } f) \ C$
 $\langle \text{proof} \rangle$

lemma *setprod-Sigma*: $\text{finite } A \implies \text{ALL } x:A. \text{finite } (B \ x) \implies$
 $(\prod_{x \in A}. (\prod_{y \in B \ x}. f \ x \ y)) =$
 $(\prod_{(x,y) \in (\text{SIGMA } x:A. B \ x)}. f \ x \ y)$
 $\langle \text{proof} \rangle$

Here we can eliminate the finiteness assumptions, by cases.

lemma *setprod-cartesian-product*:
 $(\prod_{x \in A}. (\prod_{y \in B}. f \ x \ y)) = (\prod_{(x,y) \in (A \lt * > B)}. f \ x \ y)$
 $\langle \text{proof} \rangle$

lemma *setprod-timesf*:
 $\text{setprod } (\%x. f \ x \ * \ g \ x) \ A = (\text{setprod } f \ A \ * \ \text{setprod } g \ A)$
 $\langle \text{proof} \rangle$

21.4.1 Properties in more restricted classes of structures

lemma *setprod-eq-1-iff* [*simp*]:
 $\text{finite } F \implies (\text{setprod } f \ F = 1) = (\text{ALL } a:F. f \ a = (1::\text{nat}))$
 $\langle \text{proof} \rangle$

lemma *setprod-zero*:
 $\text{finite } A \implies \text{EX } x: A. f \ x = (0::'a::\text{comm-semiring-1-cancel}) \implies \text{setprod } f \ A = 0$
 $\langle \text{proof} \rangle$

lemma *setprod-nonneg* [*rule-format*]:
 $(\text{ALL } x: A. (0::'a::\text{ordered-idom}) \leq f \ x) \implies 0 \leq \text{setprod } f \ A$
 $\langle \text{proof} \rangle$

lemma *setprod-pos* [*rule-format*]: $(\text{ALL } x: A. (0::'a::\text{ordered-idom}) < f \ x)$
 $\implies 0 < \text{setprod } f \ A$
 $\langle \text{proof} \rangle$

lemma *setprod-nonzero* [*rule-format*]:
 $(\text{ALL } x \ y. (x::'a::\text{comm-semiring-1-cancel}) * y = 0 \implies x = 0 \mid y = 0) \implies$
 $\text{finite } A \implies (\text{ALL } x: A. f \ x \neq (0::'a)) \implies \text{setprod } f \ A \neq 0$
 $\langle \text{proof} \rangle$

lemma *setprod-zero-eq*:
 $(\text{ALL } x \ y. (x::'a::\text{comm-semiring-1-cancel}) * y = 0 \implies x = 0 \mid y = 0) \implies$
 $\text{finite } A \implies (\text{setprod } f \ A = (0::'a)) = (\text{EX } x: A. f \ x = 0)$
 $\langle \text{proof} \rangle$

lemma *setprod-nonzero-field*:
 $\text{finite } A \implies (\text{ALL } x: A. f \ x \neq (0::'a::\text{field})) \implies \text{setprod } f \ A \neq 0$
 $\langle \text{proof} \rangle$

lemma *setprod-zero-eq-field*:
 $\text{finite } A \implies (\text{setprod } f \ A = (0::'a::\text{field})) = (\text{EX } x: A. f \ x = 0)$

$\langle \text{proof} \rangle$

lemma *setprod-Un*: $\text{finite } A \implies \text{finite } B \implies (\text{ALL } x: A \text{ Int } B. f x \neq 0) \implies$
 $(\text{setprod } f (A \text{ Un } B) :: 'a :: \{\text{field}\})$
 $= \text{setprod } f A * \text{setprod } f B / \text{setprod } f (A \text{ Int } B)$
 $\langle \text{proof} \rangle$

lemma *setprod-diff1*: $\text{finite } A \implies f a \neq 0 \implies$
 $(\text{setprod } f (A - \{a\}) :: 'a :: \{\text{field}\}) =$
 $(\text{if } a:A \text{ then } \text{setprod } f A / f a \text{ else } \text{setprod } f A)$
 $\langle \text{proof} \rangle$

lemma *setprod-inversef*: $\text{finite } A \implies$
 $\text{ALL } x: A. f x \neq (0 :: 'a :: \{\text{field}, \text{division-by-zero}\}) \implies$
 $\text{setprod } (\text{inverse} \circ f) A = \text{inverse } (\text{setprod } f A)$
 $\langle \text{proof} \rangle$

lemma *setprod-dividef*:
 $[[\text{finite } A;$
 $\forall x \in A. g x \neq (0 :: 'a :: \{\text{field}, \text{division-by-zero}\})]]$
 $\implies \text{setprod } (\%x. f x / g x) A = \text{setprod } f A / \text{setprod } g A$
 $\langle \text{proof} \rangle$

21.5 Finite cardinality

This definition, although traditional, is ugly to work with: $\text{card } A == \text{LEAST } n. \text{EX } f. A = \{f i \mid i. i < n\}$. But now that we have *setsum* things are easy:

constdefs
 $\text{card} :: 'a \text{ set} \Rightarrow \text{nat}$
 $\text{card } A == \text{setsum } (\%x. 1 :: \text{nat}) A$

lemma *card-empty* [simp]: $\text{card } \{\} = 0$
 $\langle \text{proof} \rangle$

lemma *card-infinite* [simp]: $\sim \text{finite } A \implies \text{card } A = 0$
 $\langle \text{proof} \rangle$

lemma *card-eq-setsum*: $\text{card } A = \text{setsum } (\%x. 1) A$
 $\langle \text{proof} \rangle$

lemma *card-insert-disjoint* [simp]:
 $\text{finite } A \implies x \notin A \implies \text{card } (\text{insert } x A) = \text{Suc}(\text{card } A)$
 $\langle \text{proof} \rangle$

lemma *card-insert-if*:
 $\text{finite } A \implies \text{card } (\text{insert } x A) = (\text{if } x:A \text{ then } \text{card } A \text{ else } \text{Suc}(\text{card}(A)))$
 $\langle \text{proof} \rangle$

lemma *card-0-eq* [simp]: $\text{finite } A \implies (\text{card } A = 0) = (A = \{\})$
 ⟨proof⟩

lemma *card-eq-0-iff*: $(\text{card } A = 0) = (A = \{\} \mid \sim \text{finite } A)$
 ⟨proof⟩

lemma *card-Suc-Diff1*: $\text{finite } A \implies x: A \implies \text{Suc } (\text{card } (A - \{x\})) = \text{card } A$
 ⟨proof⟩

lemma *card-Diff-singleton*:
 $\text{finite } A \implies x: A \implies \text{card } (A - \{x\}) = \text{card } A - 1$
 ⟨proof⟩

lemma *card-Diff-singleton-if*:
 $\text{finite } A \implies \text{card } (A - \{x\}) = (\text{if } x : A \text{ then } \text{card } A - 1 \text{ else } \text{card } A)$
 ⟨proof⟩

lemma *card-insert*: $\text{finite } A \implies \text{card } (\text{insert } x \ A) = \text{Suc } (\text{card } (A - \{x\}))$
 ⟨proof⟩

lemma *card-insert-le*: $\text{finite } A \implies \text{card } A \leq \text{card } (\text{insert } x \ A)$
 ⟨proof⟩

lemma *card-mono*: $\llbracket \text{finite } B; A \subseteq B \rrbracket \implies \text{card } A \leq \text{card } B$
 ⟨proof⟩

lemma *card-seteq*: $\text{finite } B \implies (!A. A \leq B \implies \text{card } B \leq \text{card } A \implies A = B)$
 ⟨proof⟩

lemma *psubset-card-mono*: $\text{finite } B \implies A < B \implies \text{card } A < \text{card } B$
 ⟨proof⟩

lemma *card-Un-Int*: $\text{finite } A \implies \text{finite } B$
 $\implies \text{card } A + \text{card } B = \text{card } (A \cup B) + \text{card } (A \cap B)$
 ⟨proof⟩

lemma *card-Un-disjoint*: $\text{finite } A \implies \text{finite } B$
 $\implies A \cap B = \{\} \implies \text{card } (A \cup B) = \text{card } A + \text{card } B$
 ⟨proof⟩

lemma *card-Diff-subset*:
 $\text{finite } B \implies B \leq A \implies \text{card } (A - B) = \text{card } A - \text{card } B$
 ⟨proof⟩

lemma *card-Diff1-less*: $\text{finite } A \implies x: A \implies \text{card } (A - \{x\}) < \text{card } A$
 ⟨proof⟩

lemma *card-Diff2-less*:

finite $A \implies x: A \implies y: A \implies \text{card } (A - \{x\} - \{y\}) < \text{card } A$
 $\langle \text{proof} \rangle$

lemma *card-Diff1-le*: *finite* $A \implies \text{card } (A - \{x\}) \leq \text{card } A$
 $\langle \text{proof} \rangle$

lemma *card-psubset*: *finite* $B \implies A \subseteq B \implies \text{card } A < \text{card } B \implies A < B$
 $\langle \text{proof} \rangle$

lemma *insert-partition*:
 $\llbracket x \notin F; \forall c1 \in \text{insert } x F. \forall c2 \in \text{insert } x F. c1 \neq c2 \longrightarrow c1 \cap c2 = \{\} \rrbracket$
 $\implies x \cap \bigcup F = \{\}$
 $\langle \text{proof} \rangle$

lemma *card-partition* [rule-format]:
 $\text{finite } C \implies$
 $\text{finite } (\bigcup C) \dashrightarrow$
 $(\forall c \in C. \text{card } c = k) \dashrightarrow$
 $(\forall c1 \in C. \forall c2 \in C. c1 \neq c2 \dashrightarrow c1 \cap c2 = \{\}) \dashrightarrow$
 $k * \text{card}(C) = \text{card } (\bigcup C)$
 $\langle \text{proof} \rangle$

lemma *setsum-constant* [simp]: $(\sum x \in A. y) = \text{of-nat}(\text{card } A) * y$
 $\langle \text{proof} \rangle$

lemma *setprod-constant*: *finite* $A \implies (\prod x \in A. (y :: 'a :: \text{recpower})) = y^{\text{card } A}$
 $\langle \text{proof} \rangle$

lemma *setsum-bounded*:
assumes *le*: $\bigwedge i. i \in A \implies f i \leq (K :: 'a :: \{\text{comm-semiring-1-cancel}, \text{pordered-ab-semigroup-add}\})$
shows $\text{setsum } f A \leq \text{of-nat}(\text{card } A) * K$
 $\langle \text{proof} \rangle$

21.5.1 Cardinality of unions

lemma *of-nat-id*[simp]: $(\text{of-nat } n :: \text{nat}) = n$
 $\langle \text{proof} \rangle$

lemma *card-UN-disjoint*:
 $\text{finite } I \implies (\text{ALL } i:I. \text{finite } (A \ i)) \implies$
 $(\text{ALL } i:I. \text{ALL } j:I. i \neq j \dashrightarrow A \ i \cap A \ j = \{\}) \implies$
 $\text{card } (\text{UNION } I A) = (\sum i \in I. \text{card}(A \ i))$
 $\langle \text{proof} \rangle$

lemma *card-Union-disjoint*:
 $\text{finite } C \implies (\text{ALL } A:C. \text{finite } A) \implies$

$(\text{ALL } A:C. \text{ ALL } B:C. A \neq B \dashv\dashv A \text{ Int } B = \{\}) \implies$
 $\text{card } (\text{Union } C) = \text{setsum card } C$
 $\langle \text{proof} \rangle$

21.5.2 Cardinality of image

The image of a finite set can be expressed using *fold*.

lemma *image-eq-fold*: $\text{finite } A \implies f \circ A = \text{fold } (\text{op } \text{Un}) (\%x. \{f x\}) \{\} A$
 $\langle \text{proof} \rangle$

lemma *card-image-le*: $\text{finite } A \implies \text{card } (f \circ A) \leq \text{card } A$
 $\langle \text{proof} \rangle$

lemma *card-image*: $\text{inj-on } f A \implies \text{card } (f \circ A) = \text{card } A$
 $\langle \text{proof} \rangle$

lemma *endo-inj-surj*: $\text{finite } A \implies f \circ A \subseteq A \implies \text{inj-on } f A \implies f \circ A = A$
 $\langle \text{proof} \rangle$

lemma *eq-card-imp-inj-on*:
 $\llbracket \text{finite } A; \text{card}(f \circ A) = \text{card } A \rrbracket \implies \text{inj-on } f A$
 $\langle \text{proof} \rangle$

lemma *inj-on-iff-eq-card*:
 $\text{finite } A \implies \text{inj-on } f A = (\text{card}(f \circ A) = \text{card } A)$
 $\langle \text{proof} \rangle$

lemma *card-inj-on-le*:
 $\llbracket \text{inj-on } f A; f \circ A \subseteq B; \text{finite } B \rrbracket \implies \text{card } A \leq \text{card } B$
 $\langle \text{proof} \rangle$

lemma *card-bij-eq*:
 $\llbracket \text{inj-on } f A; f \circ A \subseteq B; \text{inj-on } g B; g \circ B \subseteq A; \text{finite } A; \text{finite } B \rrbracket \implies \text{card } A = \text{card } B$
 $\langle \text{proof} \rangle$

21.5.3 Cardinality of products

lemma *card-SigmaI [simp]*:
 $\llbracket \text{finite } A; \text{ALL } a:A. \text{finite } (B a) \rrbracket$
 $\implies \text{card } (\text{SIGMA } x: A. B x) = (\sum a \in A. \text{card } (B a))$
 $\langle \text{proof} \rangle$

lemma *card-cartesian-product*: $\text{card } (A <*> B) = \text{card}(A) * \text{card}(B)$
 $\langle \text{proof} \rangle$

lemma *card-cartesian-product-singleton*: $\text{card}(\{x\} <*> A) = \text{card}(A)$
 $\langle \text{proof} \rangle$

21.5.4 Cardinality of the Powerset

lemma *card-Pow*: $\text{finite } A \implies \text{card } (\text{Pow } A) = \text{Suc } (\text{Suc } 0) ^ \text{card } A$
 $\langle \text{proof} \rangle$

Relates to equivalence classes. Based on a theorem of F. Kammüller’s.

lemma *dvd-partition*:
 $\text{finite } (\text{Union } C) \implies$
 $\text{ALL } c : C. k \text{ dvd card } c \implies$
 $(\text{ALL } c1 : C. \text{ALL } c2 : C. c1 \neq c2 \longrightarrow c1 \text{ Int } c2 = \{\}) \implies$
 $k \text{ dvd card } (\text{Union } C)$
 $\langle \text{proof} \rangle$

21.6 A fold functional for non-empty sets

Does not require start value.

consts
 $\text{fold1Set} :: ('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow ('a \text{ set} \times 'a) \text{ set}$

inductive *fold1Set* *f*

intros

fold1Set-insertI [*intro*]:
 $\llbracket (A, x) \in \text{foldSet } f \text{ id } a; a \notin A \rrbracket \implies (\text{insert } a \ A, x) \in \text{fold1Set } f$

constdefs

$\text{fold1} :: ('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow 'a \text{ set} \Rightarrow 'a$
 $\text{fold1 } f \ A == \text{THE } x. (A, x) : \text{fold1Set } f$

lemma *fold1Set-nonempty*:
 $(A, x) : \text{fold1Set } f \implies A \neq \{\}$
 $\langle \text{proof} \rangle$

inductive-cases *empty-fold1SetE* [*elim!*]: $(\{\}, x) : \text{fold1Set } f$

inductive-cases *insert-fold1SetE* [*elim!*]: $(\text{insert } a \ X, x) : \text{fold1Set } f$

lemma *fold1Set-sing* [*iff*]: $((\{a\}, b) : \text{fold1Set } f) = (a = b)$
 $\langle \text{proof} \rangle$

lemma *fold1-singleton*[*simp*]: $\text{fold1 } f \ \{a\} = a$
 $\langle \text{proof} \rangle$

lemma *finite-nonempty-imp-fold1Set*:
 $\llbracket \text{finite } A; A \neq \{\} \rrbracket \implies \text{EX } x. (A, x) : \text{fold1Set } f$
 $\langle \text{proof} \rangle$

First, some lemmas about *foldSet*.

lemma (in *ACf*) *foldSet-insert-swap*:
assumes *fold*: $(A, y) \in \text{foldSet } f \text{ id } b$
shows $b \notin A \implies (\text{insert } b \ A, z \cdot y) \in \text{foldSet } f \text{ id } z$
 $\langle \text{proof} \rangle$

lemma (in *ACf*) *foldSet-permute-diff*:
assumes *fold*: $(A, x) \in \text{foldSet } f \text{ id } b$
shows $\llbracket a \in A; b \notin A \rrbracket \implies (\text{insert } b \ (A - \{a\}), x) \in \text{foldSet } f \text{ id } a$
 $\langle \text{proof} \rangle$

lemma (in *ACf*) *fold1-eq-fold*:
 $\llbracket \text{finite } A; a \notin A \rrbracket \implies \text{fold1 } f \ (\text{insert } a \ A) = \text{fold } f \text{ id } a \ A$
 $\langle \text{proof} \rangle$

lemma *nonempty-iff*: $(A \neq \{\}) = (\exists x \ B. A = \text{insert } x \ B \ \& \ x \notin B)$
 $\langle \text{proof} \rangle$

lemma (in *ACf*) *fold1-insert*:
assumes *nonempty*: $A \neq \{\}$ **and** A : *finite* $A \ x \notin A$
shows $\text{fold1 } f \ (\text{insert } x \ A) = f \ x \ (\text{fold1 } f \ A)$
 $\langle \text{proof} \rangle$

lemma (in *ACIf*) *fold1-insert-idem* [*simp*]:
assumes *nonempty*: $A \neq \{\}$ **and** A : *finite* A
shows $\text{fold1 } f \ (\text{insert } x \ A) = f \ x \ (\text{fold1 } f \ A)$
 $\langle \text{proof} \rangle$

Now the recursion rules for definitions:

lemma *fold1-singleton-def*: $g \equiv \text{fold1 } f \implies g \ \{a\} = a$
 $\langle \text{proof} \rangle$

lemma (in *ACf*) *fold1-insert-def*:
 $\llbracket g \equiv \text{fold1 } f; \text{finite } A; x \notin A; A \neq \{\} \rrbracket \implies g(\text{insert } x \ A) = x \cdot (g \ A)$
 $\langle \text{proof} \rangle$

lemma (in *ACIf*) *fold1-insert-idem-def*:
 $\llbracket g \equiv \text{fold1 } f; \text{finite } A; A \neq \{\} \rrbracket \implies g(\text{insert } x \ A) = x \cdot (g \ A)$
 $\langle \text{proof} \rangle$

21.6.1 Determinacy for *fold1Set*

Not actually used!!

lemma (in *ACf*) *foldSet-permute*:
 $\llbracket (\text{insert } a \ A, x) \in \text{foldSet } f \text{ id } b; a \notin A; b \notin A \rrbracket$
 $\implies (\text{insert } b \ A, x) \in \text{foldSet } f \text{ id } a$
 $\langle \text{proof} \rangle$

lemma (in *ACf*) *fold1Set-determ*:
 $(A, x) \in \text{fold1Set } f \implies (A, y) \in \text{fold1Set } f \implies y = x$

$\langle proof \rangle$

lemma (in *ACf*) *fold1Set-equality*: $(A, y) : fold1Set\ f ==> fold1\ f\ A = y$
 $\langle proof \rangle$

declare

empty-foldSetE [rule *del*] *foldSet.intros* [rule *del*]
empty-fold1SetE [rule *del*] *insert-fold1SetE* [rule *del*]
 — No more proves involve these relations.

21.6.2 Semi-Lattices

locale *ACIfSL* = *ACIf* +
fixes *below* :: $'a \Rightarrow 'a \Rightarrow bool$ (**infixl** \sqsubseteq 50)
assumes *below-def*: $(x \sqsubseteq y) = (x \cdot y = x)$

locale *ACIfSLlin* = *ACIfSL* +
assumes *lin*: $x \cdot y \in \{x, y\}$

lemma (in *ACIfSL*) *below-refl*[*simp*]: $x \sqsubseteq x$
 $\langle proof \rangle$

lemma (in *ACIfSL*) *below-f-conv*[*simp*]: $x \sqsubseteq y \cdot z = (x \sqsubseteq y \wedge x \sqsubseteq z)$
 $\langle proof \rangle$

lemma (in *ACIfSLlin*) *above-f-conv*:
 $x \cdot y \sqsubseteq z = (x \sqsubseteq z \vee y \sqsubseteq z)$
 $\langle proof \rangle$

21.6.3 Lemmas about *fold1*

lemma (in *ACf*) *fold1-Un*:
assumes *A*: *finite* *A* $A \neq \{\}$
shows *finite* *B* $\implies B \neq \{\} \implies A\ Int\ B = \{\} \implies$
 $fold1\ f\ (A\ Un\ B) = f\ (fold1\ f\ A)\ (fold1\ f\ B)$
 $\langle proof \rangle$

lemma (in *ACIf*) *fold1-Un2*:
assumes *A*: *finite* *A* $A \neq \{\}$
shows *finite* *B* $\implies B \neq \{\} \implies$
 $fold1\ f\ (A\ Un\ B) = f\ (fold1\ f\ A)\ (fold1\ f\ B)$
 $\langle proof \rangle$

lemma (in *ACf*) *fold1-in*:
assumes *A*: *finite* (*A*) $A \neq \{\}$ **and** *elem*: $\bigwedge x\ y. x \cdot y \in \{x, y\}$
shows $fold1\ f\ A \in A$
 $\langle proof \rangle$

lemma (in *ACIfSL*) *below-fold1-iff*:
assumes *A*: *finite* *A* $A \neq \{\}$

shows $x \sqsubseteq \text{fold1 } f \ A = (\forall a \in A. \ x \sqsubseteq a)$
 $\langle \text{proof} \rangle$

lemma (in *ACIfSL*) *fold1-belowI*:
assumes A : *finite* A $A \neq \{\}$
shows $a \in A \implies \text{fold1 } f \ A \sqsubseteq a$
 $\langle \text{proof} \rangle$

lemma (in *ACIfSLlin*) *fold1-below-iff*:
assumes A : *finite* A $A \neq \{\}$
shows $\text{fold1 } f \ A \sqsubseteq x = (\exists a \in A. \ a \sqsubseteq x)$
 $\langle \text{proof} \rangle$

21.6.4 Lattices

locale *Lattice* = *lattice* +
fixes $\text{Inf} :: 'a \text{ set} \Rightarrow 'a$ (\sqcap - [900] 900)
and $\text{Sup} :: 'a \text{ set} \Rightarrow 'a$ (\sqcup - [900] 900)
defines $\text{Inf} == \text{fold1 } \text{inf}$ **and** $\text{Sup} == \text{fold1 } \text{sup}$

locale *Distrib-Lattice* = *distrib-lattice* + *Lattice*

Lattices are semilattices

lemma (in *Lattice*) *ACf-inf*: $\text{ACf } \text{inf}$
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *ACf-sup*: $\text{ACf } \text{sup}$
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *ACIf-inf*: $\text{ACIf } \text{inf}$
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *ACIf-sup*: $\text{ACIf } \text{sup}$
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *ACIfSL-inf*: $\text{ACIfSL } \text{inf}$ ($op \sqsubseteq$)
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *ACIfSL-sup*: $\text{ACIfSL } \text{sup}$ ($\%x \ y. \ y \sqsubseteq x$)
 $\langle \text{proof} \rangle$

21.6.5 Fold laws in lattices

lemma (in *Lattice*) *Inf-le-Sup[simp]*: $\llbracket \text{finite } A; \ A \neq \{\} \rrbracket \implies \sqcap A \sqsubseteq \sqcup A$
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *sup-Inf-absorb[simp]*:
 $\llbracket \text{finite } A; \ A \neq \{\}; \ a \in A \rrbracket \implies (a \sqcup \sqcap A) = a$
 $\langle \text{proof} \rangle$

lemma (in *Lattice*) *inf-Sup-absorb[simp]*:
 $\llbracket \text{finite } A; A \neq \{\}; a \in A \rrbracket \implies (a \sqcap \bigsqcup A) = a$
 $\langle \text{proof} \rangle$

lemma (in *Distrib-Lattice*) *sup-Inf1-distrib*:
assumes $A: \text{finite } A \ A \neq \{\}$
shows $(x \sqcup \bigsqcap A) = \bigsqcap \{x \sqcup a \mid a. a \in A\}$
 $\langle \text{proof} \rangle$

lemma (in *Distrib-Lattice*) *sup-Inf2-distrib*:
assumes $A: \text{finite } A \ A \neq \{\}$ **and** $B: \text{finite } B \ B \neq \{\}$
shows $(\bigsqcap A \sqcup \bigsqcap B) = \bigsqcap \{a \sqcup b \mid a. a \in A \wedge b \in B\}$
 $\langle \text{proof} \rangle$

21.7 Min and Max

As an application of *fold1* we define the minimal and maximal element of a (non-empty) set over a linear order.

constdefs
 $\text{Min} :: ('a::\text{linorder})\text{set} \Rightarrow 'a$
 $\text{Min} == \text{fold1 } \text{min}$

$\text{Max} :: ('a::\text{linorder})\text{set} \Rightarrow 'a$
 $\text{Max} == \text{fold1 } \text{max}$

Before we can do anything, we need to show that *min* and *max* are ACI and the ordering is linear:

interpretation *min*: *ACf* [*min*:: $'a::\text{linorder} \Rightarrow 'a \Rightarrow 'a$]
 $\langle \text{proof} \rangle$

interpretation *min*: *ACIf* [*min*:: $'a::\text{linorder} \Rightarrow 'a \Rightarrow 'a$]
 $\langle \text{proof} \rangle$

interpretation *max*: *ACf* [*max*:: $'a::\text{linorder} \Rightarrow 'a \Rightarrow 'a$]
 $\langle \text{proof} \rangle$

interpretation *max*: *ACIf* [*max*:: $'a::\text{linorder} \Rightarrow 'a \Rightarrow 'a$]
 $\langle \text{proof} \rangle$

interpretation *min*:
ACIfSL [*min*:: $'a::\text{linorder} \Rightarrow 'a \Rightarrow 'a \text{ op } \leq$]
 $\langle \text{proof} \rangle$

interpretation *min*:
ACIfSLlin [*min*:: $'a::\text{linorder} \Rightarrow 'a \Rightarrow 'a \text{ op } \leq$]
 $\langle \text{proof} \rangle$

interpretation *max*:

ACIfSL [*max* :: 'a::linorder \Rightarrow 'a \Rightarrow 'a %x y. $y \leq x$]
 $\langle \text{proof} \rangle$

interpretation *max*:

ACIfSLlin [*max* :: 'a::linorder \Rightarrow 'a \Rightarrow 'a %x y. $y \leq x$]
 $\langle \text{proof} \rangle$

interpretation *min-max*:

Lattice [*op* \leq *min* :: 'a::linorder \Rightarrow 'a \Rightarrow 'a *max* *Min* *Max*]
 $\langle \text{proof} \rangle$

interpretation *min-max*:

Distrib-Lattice [*op* \leq *min* :: 'a::linorder \Rightarrow 'a \Rightarrow 'a *max* *Min* *Max*]
 $\langle \text{proof} \rangle$

Now we instantiate the recursion equations and declare them simplification rules:

lemmas *Min-singleton* = *fold1-singleton-def* [*OF Min-def*]

lemmas *Max-singleton* = *fold1-singleton-def* [*OF Max-def*]

lemmas *Min-insert* = *min.fold1-insert-idem-def* [*OF Min-def*]

lemmas *Max-insert* = *max.fold1-insert-idem-def* [*OF Max-def*]

declare *Min-singleton* [*simp*] *Max-singleton* [*simp*]

declare *Min-insert* [*simp*] *Max-insert* [*simp*]

Now we instantiate some *fold1* properties:

lemma *Min-in* [*simp*]:

shows *finite* A \Rightarrow A $\neq \{\}$ \Rightarrow *Min* A \in A
 $\langle \text{proof} \rangle$

lemma *Max-in* [*simp*]:

shows *finite* A \Rightarrow A $\neq \{\}$ \Rightarrow *Max* A \in A
 $\langle \text{proof} \rangle$

lemma *Min-le* [*simp*]: $\llbracket \text{finite } A; A \neq \{\}; x \in A \rrbracket \Rightarrow \text{Min } A \leq x$

$\langle \text{proof} \rangle$

lemma *Max-ge* [*simp*]: $\llbracket \text{finite } A; A \neq \{\}; x \in A \rrbracket \Rightarrow x \leq \text{Max } A$

$\langle \text{proof} \rangle$

lemma *Min-ge-iff* [*simp*]:

$\llbracket \text{finite } A; A \neq \{\} \rrbracket \Rightarrow (x \leq \text{Min } A) = (\forall a \in A. x \leq a)$
 $\langle \text{proof} \rangle$

lemma *Max-le-iff* [*simp*]:

$\llbracket \text{finite } A; A \neq \{\} \rrbracket \Rightarrow (\text{Max } A \leq x) = (\forall a \in A. a \leq x)$
 $\langle \text{proof} \rangle$

lemma *Min-le-iff*:

$\llbracket \text{finite } A; A \neq \{\} \rrbracket \implies (\text{Min } A \leq x) = (\exists a \in A. a \leq x)$
 $\langle \text{proof} \rangle$

lemma *Max-ge-iff*:

$\llbracket \text{finite } A; A \neq \{\} \rrbracket \implies (x \leq \text{Max } A) = (\exists a \in A. x \leq a)$
 $\langle \text{proof} \rangle$

21.8 Properties of axclass *finite*

Many of these are by Brian Huffman.

lemma *finite-set*: *finite* (*A*::'*a*::*finite set*)
 $\langle \text{proof} \rangle$

instance *unit* :: *finite*
 $\langle \text{proof} \rangle$

instance *bool* :: *finite*
 $\langle \text{proof} \rangle$

instance *** :: (*finite*, *finite*) *finite*
 $\langle \text{proof} \rangle$

instance *+* :: (*finite*, *finite*) *finite*
 $\langle \text{proof} \rangle$

instance *set* :: (*finite*) *finite*
 $\langle \text{proof} \rangle$

lemma *inj-graph*: *inj* (%*f*. {(*x*, *y*). *y* = *f x*})
 $\langle \text{proof} \rangle$

instance *fun* :: (*finite*, *finite*) *finite*
 $\langle \text{proof} \rangle$

end

22 Wellfounded-Relations: Well-founded Relations

theory *Wellfounded-Relations*
imports *Finite-Set*
begin

Derived WF relations such as inverse image, lexicographic product and measure. The simple relational product, in which (x', y') precedes (x, y) if $x' < x$ and $y' < y$, is a subset of the lexicographic product, and therefore does not need to be defined separately.

constdefs

less-than :: (nat*nat)set
less-than == trans pred-nat

measure :: ('a => nat) => ('a * 'a)set
measure == inv-image *less-than*

lex-prod :: [('a*'a)set, ('b*'b)set] => (('a*'b)*('a*'b))set
 (infixr <*lex*> 80)
ra <*lex*> *rb* == {(a,b),(a',b') . (a,a') : *ra* | a=a' & (b,b') : *rb*}

finite-psubset :: ('a set * 'a set) set
 — finite proper subset
finite-psubset == {(A,B). A < B & finite B}

same-fst :: ('a => bool) => ('a => ('b * 'b)set) => (('a*'b)*('a*'b))set
same-fst *P* *R* == {(x',y'),(x,y) . x'=x & *P* x & (y',y) : *R* x}

— For *rec-def* declarations where the first n parameters stay unchanged in the recursive call. See *Library/While-Combinator.thy* for an application.

22.1 Measure Functions make Wellfounded Relations

22.1.1 ‘Less than’ on the natural numbers

lemma *wf-less-than* [iff]: *wf less-than*
 <proof>

lemma *trans-less-than* [iff]: *trans less-than*
 <proof>

lemma *less-than-iff* [iff]: ((x,y): *less-than*) = (x<y)
 <proof>

lemma *full-nat-induct*:
 assumes *ih*: (!n. (ALL m. Suc m <= n --> *P* m) ==> *P* n)
 shows *P* n
 <proof>

22.1.2 The Inverse Image into a Wellfounded Relation is Wellfounded.

lemma *wf-inv-image* [simp,intro!]: *wf*(*r*) ==> *wf*(inv-image *r* (f::'a=>'b))
 <proof>

22.1.3 Finally, All Measures are Wellfounded.

lemma *wf-measure [iff]: wf (measure f)*
<proof>

lemmas *measure-induct =*
wf-measure [THEN wf-induct, unfolded measure-def inv-image-def,
simplified, standard]

22.2 Other Ways of Constructing Wellfounded Relations

Wellfoundedness of lexicographic combinations

lemma *wf-lex-prod [intro!]: [| wf(ra); wf(rb) |] ==> wf(ra <*lex*> rb)*
<proof>

Transitivity of WF combinators.

lemma *trans-lex-prod [intro!]:*
*[| trans R1; trans R2 |] ==> trans (R1 <*lex*> R2)*
<proof>

22.2.1 Wellfoundedness of proper subset on finite sets.

lemma *wf-finite-psubset: wf (finite-psubset)*
<proof>

lemma *trans-finite-psubset: trans finite-psubset*
<proof>

22.2.2 Wellfoundedness of finite acyclic relations

This proof belongs in this theory because it needs Finite.

lemma *finite-acyclic-wf [rule-format]: finite r ==> acyclic r --> wf r*
<proof>

lemma *finite-acyclic-wf-converse: [|finite r; acyclic r|] ==> wf (r⁻¹)*
<proof>

lemma *wf-iff-acyclic-if-finite: finite r ==> wf r = acyclic r*
<proof>

22.2.3 Wellfoundedness of same-fst

lemma *same-fstI [intro!]:*
[| P x; (y',y) : R x |] ==> ((x,y'),(x,y)) : same-fst P R
<proof>

lemma *wf-same-fst:*
assumes *prem: (!x. P x ==> wf (R x))*
shows *wf (same-fst P R)*

<proof>

22.3 Weakly decreasing sequences (w.r.t. some well-founded order) stabilize.

This material does not appear to be used any longer.

lemma *lemma1*: $[\![\text{ALL } i. (f \text{ (Suc } i), f \text{ } i) : r^* \]\!] \implies (f \text{ (} i+k \text{)}, f \text{ } i) : r^*$
<proof>

lemma *lemma2*: $[\![\text{ALL } i. (f \text{ (Suc } i), f \text{ } i) : r^*; \text{wf } (r^+) \]\!] \implies \text{ALL } m. f \text{ } m = x \longrightarrow (\text{EX } i. \text{ALL } k. f \text{ (} m+i+k \text{)} = f \text{ (} m+i \text{)})$
<proof>

lemma *wf-weak-decr-stable*: $[\![\text{ALL } i. (f \text{ (Suc } i), f \text{ } i) : r^*; \text{wf } (r^+) \]\!] \implies \text{EX } i. \text{ALL } k. f \text{ (} i+k \text{)} = f \text{ } i$
<proof>

lemma *weak-decr-stable*:

$\text{ALL } i. f \text{ (Suc } i) \leq ((f \text{ } i)::\text{nat}) \implies \text{EX } i. \text{ALL } k. f \text{ (} i+k \text{)} = f \text{ } i$
<proof>

<ML>

end

23 Equiv-Relations: Equivalence Relations in Higher-Order Set Theory

theory *Equiv-Relations*
imports *Relation Finite-Set*
begin

23.1 Equivalence relations

locale *equiv* =
fixes *A* and *r*
assumes *refl*: *refl A r*
and *sym*: *sym r*
and *trans*: *trans r*

Suppes, Theorem 70: *r* is an equiv relation iff $r^{-1} \circ r = r$.

First half: *equiv A r* $\implies r^{-1} \circ r = r$.

lemma *sym-trans-comp-subset*:

$\text{sym } r \implies \text{trans } r \implies r^{-1} \circ r \subseteq r$
 ⟨proof⟩

lemma *refl-comp-subset*: $\text{refl } A \ r \implies r \subseteq r^{-1} \circ r$
 ⟨proof⟩

lemma *equiv-comp-eq*: $\text{equiv } A \ r \implies r^{-1} \circ r = r$
 ⟨proof⟩

Second half.

lemma *comp-equivI*:

$r^{-1} \circ r = r \implies \text{Domain } r = A \implies \text{equiv } A \ r$
 ⟨proof⟩

23.2 Equivalence classes

lemma *equiv-class-subset*:

$\text{equiv } A \ r \implies (a, b) \in r \implies r^{\prime\prime}\{a\} \subseteq r^{\prime\prime}\{b\}$
 — lemma for the next result
 ⟨proof⟩

theorem *equiv-class-eq*: $\text{equiv } A \ r \implies (a, b) \in r \implies r^{\prime\prime}\{a\} = r^{\prime\prime}\{b\}$
 ⟨proof⟩

lemma *equiv-class-self*: $\text{equiv } A \ r \implies a \in A \implies a \in r^{\prime\prime}\{a\}$
 ⟨proof⟩

lemma *subset-equiv-class*:

$\text{equiv } A \ r \implies r^{\prime\prime}\{b\} \subseteq r^{\prime\prime}\{a\} \implies b \in A \implies (a, b) \in r$
 — lemma for the next result
 ⟨proof⟩

lemma *eq-equiv-class*:

$r^{\prime\prime}\{a\} = r^{\prime\prime}\{b\} \implies \text{equiv } A \ r \implies b \in A \implies (a, b) \in r$
 ⟨proof⟩

lemma *equiv-class-nondisjoint*:

$\text{equiv } A \ r \implies x \in (r^{\prime\prime}\{a\} \cap r^{\prime\prime}\{b\}) \implies (a, b) \in r$
 ⟨proof⟩

lemma *equiv-type*: $\text{equiv } A \ r \implies r \subseteq A \times A$
 ⟨proof⟩

theorem *equiv-class-eq-iff*:

$\text{equiv } A \ r \implies ((x, y) \in r) = (r^{\prime\prime}\{x\} = r^{\prime\prime}\{y\} \ \& \ x \in A \ \& \ y \in A)$
 ⟨proof⟩

theorem *eq-equiv-class-iff*:

$\text{equiv } A \ r \implies x \in A \implies y \in A \implies (r^{\prime\prime}\{x\} = r^{\prime\prime}\{y\}) = ((x, y) \in r)$

$\langle proof \rangle$

23.3 Quotients

constdefs

$quotient :: ['a\ set, ('a * 'a)\ set] \Rightarrow 'a\ set\ set\ (\text{infixl } '//' \ 90)$
 $A//r == \bigcup x \in A. \{r''\{x\}\} \quad \text{— set of equiv classes}$

lemma *quotientI*: $x \in A \Rightarrow r''\{x\} \in A//r$
 $\langle proof \rangle$

lemma *quotientE*:
 $X \in A//r \Rightarrow (!x. X = r''\{x\} \Rightarrow x \in A \Rightarrow P) \Rightarrow P$
 $\langle proof \rangle$

lemma *Union-quotient*: $equiv\ A\ r \Rightarrow Union\ (A//r) = A$
 $\langle proof \rangle$

lemma *quotient-disj*:
 $equiv\ A\ r \Rightarrow X \in A//r \Rightarrow Y \in A//r \Rightarrow X = Y \mid (X \cap Y = \{\})$
 $\langle proof \rangle$

lemma *quotient-eqI*:
 $[|equiv\ A\ r; X \in A//r; Y \in A//r; x \in X; y \in Y; (x,y) \in r|] \Rightarrow X = Y$
 $\langle proof \rangle$

lemma *quotient-eq-iff*:
 $[|equiv\ A\ r; X \in A//r; Y \in A//r; x \in X; y \in Y|] \Rightarrow (X = Y) = ((x,y) \in r)$
 $\langle proof \rangle$

lemma *quotient-empty* [*simp*]: $\{\}/r = \{\}$
 $\langle proof \rangle$

lemma *quotient-is-empty* [*iff*]: $(A//r = \{\}) = (A = \{\})$
 $\langle proof \rangle$

lemma *quotient-is-empty2* [*iff*]: $(\{\} = A//r) = (A = \{\})$
 $\langle proof \rangle$

lemma *singleton-quotient*: $\{x\}/r = \{r''\{x\}\}$
 $\langle proof \rangle$

lemma *quotient-diff1*:
 $[|inj-on\ (\%a. \{a\}/r)\ A; a \in A|] \Rightarrow (A - \{a\})//r = A//r - \{a\}/r$
 $\langle proof \rangle$

23.4 Defining unary operations upon equivalence classes

A congruence-preserving function

```

locale congruent =
  fixes r and f
  assumes congruent:  $(y,z) \in r \implies f\ y = f\ z$ 

syntax
  RESPECTS :: [a => b, (a * a) set] => bool (infixr respects 80)

translations
  f respects r == congruent r f

```

lemma *UN-constant-eq*: $a \in A \implies \forall y \in A. f\ y = c \implies (\bigcup y \in A. f(y)) = c$
 — lemma required to prove *UN-equiv-class*
 $\langle proof \rangle$

lemma *UN-equiv-class*:
 $equiv\ A\ r \implies f\ respects\ r \implies a \in A$
 $\implies (\bigcup x \in r^{\{a\}}. f\ x) = f\ a$
 — Conversion rule
 $\langle proof \rangle$

lemma *UN-equiv-class-type*:
 $equiv\ A\ r \implies f\ respects\ r \implies X \in A//r \implies$
 $(!!x. x \in A \implies f\ x \in B) \implies (\bigcup x \in X. f\ x) \in B$
 $\langle proof \rangle$

Sufficient conditions for injectiveness. Could weaken premises! major premise could be an inclusion; bcong could be $!!y. y \in A \implies f\ y \in B$.

lemma *UN-equiv-class-inject*:
 $equiv\ A\ r \implies f\ respects\ r \implies$
 $(\bigcup x \in X. f\ x) = (\bigcup y \in Y. f\ y) \implies X \in A//r \implies Y \in A//r$
 $\implies (!!x\ y. x \in A \implies y \in A \implies f\ x = f\ y \implies (x, y) \in r)$
 $\implies X = Y$
 $\langle proof \rangle$

23.5 Defining binary operations upon equivalence classes

A congruence-preserving function of two arguments

```

locale congruent2 =
  fixes r1 and r2 and f
  assumes congruent2:
     $(y1,z1) \in r1 \implies (y2,z2) \in r2 \implies f\ y1\ y2 = f\ z1\ z2$ 

```

Abbreviation for the common case where the relations are identical

syntax

$RESPECTS2 :: ['a \Rightarrow 'b, ('a * 'a) \text{ set}] \Rightarrow \text{bool} \text{ (infixr respects2 80)}$

translations

$f \text{ respects2 } r \Rightarrow \text{congruent2 } r \text{ } r \text{ } f$

lemma congruent2-implies-congruent:

$\text{equiv } A \text{ } r1 \Rightarrow \text{congruent2 } r1 \text{ } r2 \text{ } f \Rightarrow a \in A \Rightarrow \text{congruent } r2 \text{ } (f \text{ } a)$
 $\langle \text{proof} \rangle$

lemma congruent2-implies-congruent-UN:

$\text{equiv } A1 \text{ } r1 \Rightarrow \text{equiv } A2 \text{ } r2 \Rightarrow \text{congruent2 } r1 \text{ } r2 \text{ } f \Rightarrow a \in A2 \Rightarrow$
 $\text{congruent } r1 \text{ } (\lambda x1. \bigcup x2 \in r2^{\text{``}\{a\}}. f \text{ } x1 \text{ } x2)$
 $\langle \text{proof} \rangle$

lemma UN-equiv-class2:

$\text{equiv } A1 \text{ } r1 \Rightarrow \text{equiv } A2 \text{ } r2 \Rightarrow \text{congruent2 } r1 \text{ } r2 \text{ } f \Rightarrow a1 \in A1 \Rightarrow a2$
 $\in A2$
 $\Rightarrow (\bigcup x1 \in r1^{\text{``}\{a1\}}. \bigcup x2 \in r2^{\text{``}\{a2\}}. f \text{ } x1 \text{ } x2) = f \text{ } a1 \text{ } a2$
 $\langle \text{proof} \rangle$

lemma UN-equiv-class-type2:

$\text{equiv } A1 \text{ } r1 \Rightarrow \text{equiv } A2 \text{ } r2 \Rightarrow \text{congruent2 } r1 \text{ } r2 \text{ } f$
 $\Rightarrow X1 \in A1 // r1 \Rightarrow X2 \in A2 // r2$
 $\Rightarrow (!x1 \text{ } x2. x1 \in A1 \Rightarrow x2 \in A2 \Rightarrow f \text{ } x1 \text{ } x2 \in B)$
 $\Rightarrow (\bigcup x1 \in X1. \bigcup x2 \in X2. f \text{ } x1 \text{ } x2) \in B$
 $\langle \text{proof} \rangle$

lemma UN-UN-split-split-eq:

$(\bigcup (x1, x2) \in X. \bigcup (y1, y2) \in Y. A \text{ } x1 \text{ } x2 \text{ } y1 \text{ } y2) =$
 $(\bigcup x \in X. \bigcup y \in Y. (\lambda (x1, x2). (\lambda (y1, y2). A \text{ } x1 \text{ } x2 \text{ } y1 \text{ } y2) \text{ } y) \text{ } x)$
 — Allows a natural expression of binary operators,
 — without explicit calls to *split*
 $\langle \text{proof} \rangle$

lemma congruent2I:

$\text{equiv } A1 \text{ } r1 \Rightarrow \text{equiv } A2 \text{ } r2$
 $\Rightarrow (!y \text{ } z \text{ } w. w \in A2 \Rightarrow (y, z) \in r1 \Rightarrow f \text{ } y \text{ } w = f \text{ } z \text{ } w)$
 $\Rightarrow (!y \text{ } z \text{ } w. w \in A1 \Rightarrow (y, z) \in r2 \Rightarrow f \text{ } w \text{ } y = f \text{ } w \text{ } z)$
 $\Rightarrow \text{congruent2 } r1 \text{ } r2 \text{ } f$
 — Suggested by John Harrison – the two subproofs may be
 — *much* simpler than the direct proof.
 $\langle \text{proof} \rangle$

lemma congruent2-commuteI:

assumes $\text{equivA: equiv } A \text{ } r$
and $\text{commute: } !y \text{ } z. y \in A \Rightarrow z \in A \Rightarrow f \text{ } y \text{ } z = f \text{ } z \text{ } y$
and $\text{cong: } !y \text{ } z \text{ } w. w \in A \Rightarrow (y, z) \in r \Rightarrow f \text{ } w \text{ } y = f \text{ } w \text{ } z$
shows $f \text{ respects2 } r$
 $\langle \text{proof} \rangle$

23.6 Cardinality results

Suggested by Florian Kammüller

lemma *finite-quotient*: $\text{finite } A \implies r \subseteq A \times A \implies \text{finite } (A/r)$
 — recall $\text{equiv } ?A \ ?r \implies ?r \subseteq ?A \times ?A$
 $\langle \text{proof} \rangle$

lemma *finite-equiv-class*:
 $\text{finite } A \implies r \subseteq A \times A \implies X \in A/r \implies \text{finite } X$
 $\langle \text{proof} \rangle$

lemma *equiv-imp-dvd-card*:
 $\text{finite } A \implies \text{equiv } A \ r \implies \forall X \in A/r. k \text{ dvd card } X$
 $\implies k \text{ dvd card } A$
 $\langle \text{proof} \rangle$

lemma *card-quotient-disjoint*:
 $\llbracket \text{finite } A; \text{inj-on } (\lambda x. \{x\} // r) \ A \rrbracket \implies \text{card}(A/r) = \text{card } A$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

end

24 IntDef: The Integers as Equivalence Classes over Pairs of Natural Numbers

theory *IntDef*
imports *Equiv-Relations NatArith*
begin

constdefs
 $\text{intrel} :: ((\text{nat} * \text{nat}) * (\text{nat} * \text{nat})) \text{ set}$
 — the equivalence relation underlying the integers
 $\text{intrel} == \{((x,y),(u,v)) \mid x \ y \ u \ v. \ x+v = u+y\}$

typedef (*Integ*)
 $\text{int} = \text{UNIV} // \text{intrel}$
 $\langle \text{proof} \rangle$

instance *int* :: $\{\text{ord}, \text{zero}, \text{one}, \text{plus}, \text{times}, \text{minus}\}$ $\langle \text{proof} \rangle$

constdefs
 $\text{int} :: \text{nat} \Rightarrow \text{int}$
 $\text{int } m == \text{Abs-Integ}(\text{intrel} \text{ “ } \{(m,0)\})$

defs (overloaded)

Zero-int-def: $0 == \text{int } 0$

One-int-def: $1 == \text{int } 1$

minus-int-def:

$-z == \text{Abs-Integ } (\bigcup (x,y) \in \text{Rep-Integ } z. \text{intrel}^{\prime\prime}\{(y,x)\})$

add-int-def:

$z + w ==$

$\text{Abs-Integ } (\bigcup (x,y) \in \text{Rep-Integ } z. \bigcup (u,v) \in \text{Rep-Integ } w. \text{intrel}^{\prime\prime}\{(x+u, y+v)\})$

diff-int-def: $z - (w::\text{int}) == z + (-w)$

mult-int-def:

$z * w ==$

$\text{Abs-Integ } (\bigcup (x,y) \in \text{Rep-Integ } z. \bigcup (u,v) \in \text{Rep-Integ } w. \text{intrel}^{\prime\prime}\{(x*u + y*v, x*v + y*u)\})$

le-int-def:

$z \leq (w::\text{int}) ==$

$\exists x \ y \ u \ v. x+v \leq u+y \ \& \ (x,y) \in \text{Rep-Integ } z \ \& \ (u,v) \in \text{Rep-Integ } w$

less-int-def: $(z < (w::\text{int})) == (z \leq w \ \& \ z \neq w)$

24.1 Construction of the Integers

24.1.1 Preliminary Lemmas about the Equivalence Relation

lemma *intrel-iff [simp]:* $((x,y),(u,v)) \in \text{intrel} = (x+v = u+y)$

<proof>

lemma *equiv-intrel:* *equiv UNIV intrel*

<proof>

Reduces equality of equivalence classes to the *intrel* relation: $(\text{intrel}^{\prime\prime}\{x\} = \text{intrel}^{\prime\prime}\{y\}) = ((x, y) \in \text{intrel})$

lemmas *equiv-intrel-iff = eq-equiv-class-iff [OF equiv-intrel UNIV-I UNIV-I]*

declare *equiv-intrel-iff [simp]*

All equivalence classes belong to set of representatives

lemma *[simp]:* $\text{intrel}^{\prime\prime}\{(x,y)\} \in \text{Integ}$

<proof>

Reduces equality on abstractions to equality on representatives: $\llbracket x \in \text{Integ}; y \in \text{Integ} \rrbracket \implies (\text{Abs-Integ } x = \text{Abs-Integ } y) = (x = y)$

declare *Abs-Integ-inject [simp] Abs-Integ-inverse [simp]*

Case analysis on the representation of an integer as an equivalence class of pairs of naturals.

lemma *eq-Abs-Integ* [case-names *Abs-Integ*, cases type: *int*]:

$$(!x\ y.\ z = \text{Abs-Integ}(\text{intrel}\{\{x,y\}\}) \implies P) \implies P$$
 $\langle \text{proof} \rangle$

24.1.2 *int*: Embedding the Naturals into the Integers

lemma *inj-int*: *inj int*
 $\langle \text{proof} \rangle$

lemma *int-int-eq* [iff]: $(\text{int } m = \text{int } n) = (m = n)$
 $\langle \text{proof} \rangle$

24.1.3 Integer Unary Negation

lemma *minus*: $-\text{Abs-Integ}(\text{intrel}\{\{x,y\}\}) = \text{Abs-Integ}(\text{intrel}\{\{y,x\}\})$
 $\langle \text{proof} \rangle$

lemma *zminus-zminus*: $-(-z) = (z::\text{int})$
 $\langle \text{proof} \rangle$

lemma *zminus-0*: $-0 = (0::\text{int})$
 $\langle \text{proof} \rangle$

24.2 Integer Addition

lemma *add*:

$$\text{Abs-Integ}(\text{intrel}\{\{x,y\}\}) + \text{Abs-Integ}(\text{intrel}\{\{u,v\}\}) = \text{Abs-Integ}(\text{intrel}\{\{x+u, y+v\}\})$$
 $\langle \text{proof} \rangle$

lemma *zminus-zadd-distrib*: $-(z + w) = (-z) + (-w::\text{int})$
 $\langle \text{proof} \rangle$

lemma *zadd-commute*: $(z::\text{int}) + w = w + z$
 $\langle \text{proof} \rangle$

lemma *zadd-assoc*: $((z1::\text{int}) + z2) + z3 = z1 + (z2 + z3)$
 $\langle \text{proof} \rangle$

lemma *zadd-left-commute*: $x + (y + z) = y + ((x + z) ::\text{int})$
 $\langle \text{proof} \rangle$

lemmas *zadd-ac* = *zadd-assoc zadd-commute zadd-left-commute*

lemmas *zmult-ac* = *OrderedGroup.mmult-ac*

lemma *zadd-int*: $(\text{int } m) + (\text{int } n) = \text{int } (m + n)$
 $\langle \text{proof} \rangle$

lemma *zadd-int-left*: $(\text{int } m) + (\text{int } n + z) = \text{int } (m + n) + z$
 $\langle \text{proof} \rangle$

lemma *int-Suc*: $\text{int } (\text{Suc } m) = 1 + (\text{int } m)$
 $\langle \text{proof} \rangle$

lemma *zadd-0*: $(0::\text{int}) + z = z$
 $\langle \text{proof} \rangle$

lemma *zadd-0-right*: $z + (0::\text{int}) = z$
 $\langle \text{proof} \rangle$

lemma *zadd-zminus-inverse2*: $(- z) + z = (0::\text{int})$
 $\langle \text{proof} \rangle$

24.3 Integer Multiplication

Congruence property for multiplication

lemma *mult-congruent2*:
 $(\%p1 \ p2. (\%(x,y). (\%(u,v). \text{intrel} \{ \{(x*u + y*v, x*v + y*u)\} \} p2) \ p1)$
 $\text{respects2 } \text{intrel}$
 $\langle \text{proof} \rangle$

lemma *mult*:
 $\text{Abs-Integ}((\text{intrel} \{ \{(x,y)\} \}) * \text{Abs-Integ}((\text{intrel} \{ \{(u,v)\} \})) =$
 $\text{Abs-Integ}(\text{intrel} \{ \{(x*u + y*v, x*v + y*u)\} \})$
 $\langle \text{proof} \rangle$

lemma *zmult-zminus*: $(- z) * w = - (z * (w::\text{int}))$
 $\langle \text{proof} \rangle$

lemma *zmult-commute*: $(z::\text{int}) * w = w * z$
 $\langle \text{proof} \rangle$

lemma *zmult-assoc*: $((z1::\text{int}) * z2) * z3 = z1 * (z2 * z3)$
 $\langle \text{proof} \rangle$

lemma *zadd-zmult-distrib*: $((z1::\text{int}) + z2) * w = (z1 * w) + (z2 * w)$
 $\langle \text{proof} \rangle$

lemma *zadd-zmult-distrib2*: $(w::\text{int}) * (z1 + z2) = (w * z1) + (w * z2)$
 $\langle \text{proof} \rangle$

lemma *zdiff-zmult-distrib*: $((z1::\text{int}) - z2) * w = (z1 * w) - (z2 * w)$

$\langle proof \rangle$

lemma *zdiff-zmult-distrib2*: $(w::int) * (z1 - z2) = (w * z1) - (w * z2)$
 $\langle proof \rangle$

lemmas *int-distrib* =
 zadd-zmult-distrib zadd-zmult-distrib2
 zdiff-zmult-distrib zdiff-zmult-distrib2

lemma *int-mult*: $int (m * n) = (int m) * (int n)$
 $\langle proof \rangle$

Compatibility binding

lemmas *zmult-int* = *int-mult* [*symmetric*]

lemma *zmult-1*: $(1::int) * z = z$
 $\langle proof \rangle$

lemma *zmult-1-right*: $z * (1::int) = z$
 $\langle proof \rangle$

The integers form a *comm-ring-1*

instance *int :: comm-ring-1*
 $\langle proof \rangle$

24.4 The \leq Ordering

lemma *le*:
 $(Abs-Integ(intrel\{\{(x,y)\}\}) \leq Abs-Integ(intrel\{\{(u,v)\}\})) = (x+v \leq u+y)$
 $\langle proof \rangle$

lemma *zle-refl*: $w \leq (w::int)$
 $\langle proof \rangle$

lemma *zle-trans*: $[| i \leq j; j \leq k |] ==> i \leq (k::int)$
 $\langle proof \rangle$

lemma *zle-anti-sym*: $[| z \leq w; w \leq z |] ==> z = (w::int)$
 $\langle proof \rangle$

lemma *zless-le*: $((w::int) < z) = (w \leq z \ \& \ w \neq z)$
 $\langle proof \rangle$

instance *int :: order*
 $\langle proof \rangle$

lemma *zle-linear*: $(z::int) \leq w \mid w \leq z$

$\langle proof \rangle$

instance *int* :: *linorder*
 $\langle proof \rangle$

lemmas *zless-linear* = *linorder-less-linear* [**where** *'a* = *int*]
lemmas *linorder-neqE-int* = *linorder-neqE* [**where** *'a* = *int*]

lemma *int-eq-0-conv* [*simp*]: (*int* *n* = 0) = (*n* = 0)
 $\langle proof \rangle$

lemma *zless-int* [*simp*]: (*int* *m* < *int* *n*) = (*m* < *n*)
 $\langle proof \rangle$

lemma *int-less-0-conv* [*simp*]: \sim (*int* *k* < 0)
 $\langle proof \rangle$

lemma *zero-less-int-conv* [*simp*]: (0 < *int* *n*) = (0 < *n*)
 $\langle proof \rangle$

lemma *int-0-less-1*: 0 < (1::*int*)
 $\langle proof \rangle$

lemma *int-0-neq-1* [*simp*]: 0 \neq (1::*int*)
 $\langle proof \rangle$

lemma *zle-int* [*simp*]: (*int* *m* \leq *int* *n*) = (*m* \leq *n*)
 $\langle proof \rangle$

lemma *zero-zle-int* [*simp*]: (0 \leq *int* *n*)
 $\langle proof \rangle$

lemma *int-le-0-conv* [*simp*]: (*int* *n* \leq 0) = (*n* = 0)
 $\langle proof \rangle$

lemma *int-0* [*simp*]: *int* 0 = (0::*int*)
 $\langle proof \rangle$

lemma *int-1* [*simp*]: *int* 1 = 1
 $\langle proof \rangle$

lemma *int-Suc0-eq-1*: *int* (Suc 0) = 1
 $\langle proof \rangle$

24.5 Monotonicity results

lemma *zadd-left-mono*: $i \leq j \implies k + i \leq k + j$ (*j*::*int*)

$\langle proof \rangle$

lemma *zadd-strict-right-mono*: $i < j \implies i + k < j + (k::int)$
 $\langle proof \rangle$

lemma *zadd-zless-mono*: $[| w' < w; z' \leq z |] \implies w' + z' < w + (z::int)$
 $\langle proof \rangle$

24.6 Strict Monotonicity of Multiplication

strict, in 1st argument; proof is by induction on $k \geq 0$

lemma *zmult-zless-mono2-lemma*:
 $i < j \implies 0 < k \implies int\ k * i < int\ k * j$
 $\langle proof \rangle$

lemma *zero-le-imp-eq-int*: $0 \leq k \implies \exists n. k = int\ n$
 $\langle proof \rangle$

lemma *zmult-zless-mono2*: $[| i < j; (0::int) < k |] \implies k*i < k*j$
 $\langle proof \rangle$

defs (overloaded)
zabs-def: $abs(i::int) == \text{if } i < 0 \text{ then } -i \text{ else } i$

The integers form an ordered *comm-ring-1*

instance *int* :: *ordered-idom*
 $\langle proof \rangle$

lemma *zless-imp-add1-zle*: $w < z \implies w + (1::int) \leq z$
 $\langle proof \rangle$

24.7 Magnitude of an Integer, as a Natural Number: *nat*

constdefs
 $nat :: int \Rightarrow nat$
 $nat\ z == contents\ (\bigcup (x,y) \in Rep-Integ\ z. \{ x-y \})$

lemma *nat*: $nat\ (Abs-Integ\ (intrel^{''}\{(x,y)\})) = x-y$
 $\langle proof \rangle$

lemma *nat-int* [simp]: $nat(int\ n) = n$
 $\langle proof \rangle$

lemma *nat-zero* [simp]: $nat\ 0 = 0$
 $\langle proof \rangle$

lemma *int-nat-eq* [simp]: $int\ (nat\ z) = (\text{if } 0 \leq z \text{ then } z \text{ else } 0)$

$\langle proof \rangle$

corollary *nat-0-le*: $0 \leq z \implies \text{int } (\text{nat } z) = z$
 $\langle proof \rangle$

lemma *nat-le-0* [simp]: $z \leq 0 \implies \text{nat } z = 0$
 $\langle proof \rangle$

lemma *nat-le-eq-zle*: $0 < w \mid 0 \leq z \implies (\text{nat } w \leq \text{nat } z) = (w \leq z)$
 $\langle proof \rangle$

An alternative condition is $(0::'a) \leq w$

corollary *nat-mono-iff*: $0 < z \implies (\text{nat } w < \text{nat } z) = (w < z)$
 $\langle proof \rangle$

corollary *nat-less-eq-zless*: $0 \leq w \implies (\text{nat } w < \text{nat } z) = (w < z)$
 $\langle proof \rangle$

lemma *zless-nat-conj*: $(\text{nat } w < \text{nat } z) = (0 < z \ \& \ w < z)$
 $\langle proof \rangle$

lemma *nonneg-eq-int*: $[\mid 0 \leq z; \ !m. z = \text{int } m \implies P \mid] \implies P$
 $\langle proof \rangle$

lemma *nat-eq-iff*: $(\text{nat } w = m) = (\text{if } 0 \leq w \text{ then } w = \text{int } m \text{ else } m=0)$
 $\langle proof \rangle$

corollary *nat-eq-iff2*: $(m = \text{nat } w) = (\text{if } 0 \leq w \text{ then } w = \text{int } m \text{ else } m=0)$
 $\langle proof \rangle$

lemma *nat-less-iff*: $0 \leq w \implies (\text{nat } w < m) = (w < \text{int } m)$
 $\langle proof \rangle$

lemma *int-eq-iff*: $(\text{int } m = z) = (m = \text{nat } z \ \& \ 0 \leq z)$
 $\langle proof \rangle$

lemma *zero-less-nat-eq* [simp]: $(0 < \text{nat } z) = (0 < z)$
 $\langle proof \rangle$

lemma *nat-add-distrib*:
 $[\mid (0::\text{int}) \leq z; \ 0 \leq z' \mid] \implies \text{nat } (z+z') = \text{nat } z + \text{nat } z'$
 $\langle proof \rangle$

lemma *nat-diff-distrib*:
 $[\mid (0::\text{int}) \leq z'; \ z' \leq z \mid] \implies \text{nat } (z-z') = \text{nat } z - \text{nat } z'$
 $\langle proof \rangle$

lemma *nat-zminus-int* [simp]: $\text{nat } (- (\text{int } n)) = 0$

$\langle \text{proof} \rangle$

lemma *zless-nat-eq-int-zless*: $(m < \text{nat } z) = (\text{int } m < z)$
 $\langle \text{proof} \rangle$

24.8 Lemmas about the Function *int* and Orderings

lemma *negative-zless-0*: $-(\text{int } (\text{Suc } n)) < 0$
 $\langle \text{proof} \rangle$

lemma *negative-zless [iff]*: $-(\text{int } (\text{Suc } n)) < \text{int } m$
 $\langle \text{proof} \rangle$

lemma *negative-zle-0*: $-\text{int } n \leq 0$
 $\langle \text{proof} \rangle$

lemma *negative-zle [iff]*: $-\text{int } n \leq \text{int } m$
 $\langle \text{proof} \rangle$

lemma *not-zle-0-negative [simp]*: $\sim (0 \leq -(\text{int } (\text{Suc } n)))$
 $\langle \text{proof} \rangle$

lemma *int-zle-neg*: $(\text{int } n \leq -\text{int } m) = (n = 0 \ \& \ m = 0)$
 $\langle \text{proof} \rangle$

lemma *not-int-zless-negative [simp]*: $\sim (\text{int } n < -\text{int } m)$
 $\langle \text{proof} \rangle$

lemma *negative-eq-positive [simp]*: $(-\text{int } n = \text{int } m) = (n = 0 \ \& \ m = 0)$
 $\langle \text{proof} \rangle$

lemma *zle-iff-zadd*: $(w \leq z) = (\exists n. z = w + \text{int } n)$
 $\langle \text{proof} \rangle$

lemma *abs-int-eq [simp]*: $\text{abs } (\text{int } m) = \text{int } m$
 $\langle \text{proof} \rangle$

This version is proved for all ordered rings, not just integers! It is proved here because attribute *arith-split* is not available in theory *Ring-and-Field*. But is it really better than just rewriting with *abs-if*?

lemma *abs-split [arith-split]*:
 $P(\text{abs}(a::'a::\text{ordered-idom})) = ((0 \leq a \longrightarrow P \ a) \ \& \ (a < 0 \longrightarrow P(-a)))$
 $\langle \text{proof} \rangle$

24.9 The Constants *neg* and *iszero*

constdefs

neg :: $'a::\text{ordered-idom} \Rightarrow \text{bool}$

$neg(Z) == Z < 0$

$iszero :: 'a::comm-semiring-1-cancel ==> bool$
 $iszero\ z == z = (0)$

lemma *not-neg-int* [simp]: $\sim neg(int\ n)$
 $\langle proof \rangle$

lemma *neg-zminus-int* [simp]: $neg(-\ (int\ (Suc\ n)))$
 $\langle proof \rangle$

lemmas *neg-eq-less-0* = *neg-def*

lemma *not-neg-eq-ge-0*: $(\sim neg\ x) = (0 \leq x)$
 $\langle proof \rangle$

24.10 To simplify inequalities when Numeral1 can get simplified to 1

lemma *not-neg-0*: $\sim neg\ 0$
 $\langle proof \rangle$

lemma *not-neg-1*: $\sim neg\ 1$
 $\langle proof \rangle$

lemma *iszero-0*: $iszero\ 0$
 $\langle proof \rangle$

lemma *not-iszero-1*: $\sim iszero\ 1$
 $\langle proof \rangle$

lemma *neg-nat*: $neg\ z ==> nat\ z = 0$
 $\langle proof \rangle$

lemma *not-neg-nat*: $\sim neg\ z ==> int\ (nat\ z) = z$
 $\langle proof \rangle$

24.11 The Set of Natural Numbers

constdefs

$Nats :: 'a::comm-semiring-1-cancel\ set$
 $Nats == range\ of-nat$

syntax (*xsymbols*) $Nats :: 'a\ set\ (\mathbb{N})$

lemma *of-nat-in-Nats* [simp]: $of-nat\ n \in Nats$
 $\langle proof \rangle$

lemma *Nats-0* [simp]: $0 \in \text{Nats}$
 $\langle \text{proof} \rangle$

lemma *Nats-1* [simp]: $1 \in \text{Nats}$
 $\langle \text{proof} \rangle$

lemma *Nats-add* [simp]: $[|a \in \text{Nats}; b \in \text{Nats}|] \implies a+b \in \text{Nats}$
 $\langle \text{proof} \rangle$

lemma *Nats-mult* [simp]: $[|a \in \text{Nats}; b \in \text{Nats}|] \implies a*b \in \text{Nats}$
 $\langle \text{proof} \rangle$

Agreement with the specific embedding for the integers

lemma *int-eq-of-nat*: $\text{int} = (\text{of-nat} :: \text{nat} \implies \text{int})$
 $\langle \text{proof} \rangle$

lemma *of-nat-eq-id* [simp]: $\text{of-nat} = (\text{id} :: \text{nat} \implies \text{nat})$
 $\langle \text{proof} \rangle$

24.12 Embedding of the Integers into any *comm-ring-1*: *of-int*

constdefs

$\text{of-int} :: \text{int} \implies 'a::\text{comm-ring-1}$
 $\text{of-int } z == \text{contents } (\bigcup (i,j) \in \text{Rep-Integ } z. \{ \text{of-nat } i - \text{of-nat } j \})$

lemma *of-int*: $\text{of-int } (\text{Abs-Integ } (\text{intrel } “ \{(i,j)\} ”)) = \text{of-nat } i - \text{of-nat } j$
 $\langle \text{proof} \rangle$

lemma *of-int-0* [simp]: $\text{of-int } 0 = 0$
 $\langle \text{proof} \rangle$

lemma *of-int-1* [simp]: $\text{of-int } 1 = 1$
 $\langle \text{proof} \rangle$

lemma *of-int-add* [simp]: $\text{of-int } (w+z) = \text{of-int } w + \text{of-int } z$
 $\langle \text{proof} \rangle$

lemma *of-int-minus* [simp]: $\text{of-int } (-z) = -(\text{of-int } z)$
 $\langle \text{proof} \rangle$

lemma *of-int-diff* [simp]: $\text{of-int } (w-z) = \text{of-int } w - \text{of-int } z$
 $\langle \text{proof} \rangle$

lemma *of-int-mult* [simp]: $\text{of-int } (w*z) = \text{of-int } w * \text{of-int } z$
 $\langle \text{proof} \rangle$

lemma *of-int-le-iff* [simp]:

$(\text{of-int } w \leq (\text{of-int } z :: 'a :: \text{ordered-idom})) = (w \leq z)$
 $\langle \text{proof} \rangle$

Special cases where either operand is zero

lemmas $\text{of-int-0-le-iff} = \text{of-int-le-iff} \text{ [of 0, simplified]}$
lemmas $\text{of-int-le-0-iff} = \text{of-int-le-iff} \text{ [of - 0, simplified]}$
declare $\text{of-int-0-le-iff} \text{ [simp]}$
declare $\text{of-int-le-0-iff} \text{ [simp]}$

lemma $\text{of-int-less-iff} \text{ [simp]}:$
 $(\text{of-int } w < (\text{of-int } z :: 'a :: \text{ordered-idom})) = (w < z)$
 $\langle \text{proof} \rangle$

Special cases where either operand is zero

lemmas $\text{of-int-0-less-iff} = \text{of-int-less-iff} \text{ [of 0, simplified]}$
lemmas $\text{of-int-less-0-iff} = \text{of-int-less-iff} \text{ [of - 0, simplified]}$
declare $\text{of-int-0-less-iff} \text{ [simp]}$
declare $\text{of-int-less-0-iff} \text{ [simp]}$

The ordering on the *comm-ring-1* is necessary. See *of-nat-eq-iff* above.

lemma $\text{of-int-eq-iff} \text{ [simp]}:$
 $(\text{of-int } w = (\text{of-int } z :: 'a :: \text{ordered-idom})) = (w = z)$
 $\langle \text{proof} \rangle$

Special cases where either operand is zero

lemmas $\text{of-int-0-eq-iff} = \text{of-int-eq-iff} \text{ [of 0, simplified]}$
lemmas $\text{of-int-eq-0-iff} = \text{of-int-eq-iff} \text{ [of - 0, simplified]}$
declare $\text{of-int-0-eq-iff} \text{ [simp]}$
declare $\text{of-int-eq-0-iff} \text{ [simp]}$

lemma $\text{of-int-eq-id} \text{ [simp]}:$ $\text{of-int} = (\text{id} :: \text{int} \Rightarrow \text{int})$
 $\langle \text{proof} \rangle$

24.13 The Set of Integers

constdefs

$\text{Ints} :: 'a :: \text{comm-ring-1} \text{ set}$
 $\text{Ints} == \text{range of-int}$

syntax (*xsymbols*)

$\text{Ints} \quad :: 'a \text{ set} \quad (\mathbb{Z})$

lemma $\text{Ints-0} \text{ [simp]}:$ $0 \in \text{Ints}$
 $\langle \text{proof} \rangle$

lemma $\text{Ints-1} \text{ [simp]}:$ $1 \in \text{Ints}$
 $\langle \text{proof} \rangle$

lemma *Ints-add* [simp]: $[| a \in \text{Ints}; b \in \text{Ints} |] \implies a + b \in \text{Ints}$
 $\langle \text{proof} \rangle$

lemma *Ints-minus* [simp]: $a \in \text{Ints} \implies -a \in \text{Ints}$
 $\langle \text{proof} \rangle$

lemma *Ints-diff* [simp]: $[| a \in \text{Ints}; b \in \text{Ints} |] \implies a - b \in \text{Ints}$
 $\langle \text{proof} \rangle$

lemma *Ints-mult* [simp]: $[| a \in \text{Ints}; b \in \text{Ints} |] \implies a * b \in \text{Ints}$
 $\langle \text{proof} \rangle$

Collapse nested embeddings

lemma *of-int-of-nat-eq* [simp]: $\text{of-int} (\text{of-nat } n) = \text{of-nat } n$
 $\langle \text{proof} \rangle$

lemma *of-int-int-eq* [simp]: $\text{of-int} (\text{int } n) = \text{of-nat } n$
 $\langle \text{proof} \rangle$

lemma *Ints-cases* [case-names of-int, cases set: Ints]:
 $q \in \mathbb{Z} \implies (!z. q = \text{of-int } z \implies C) \implies C$
 $\langle \text{proof} \rangle$

lemma *Ints-induct* [case-names of-int, induct set: Ints]:
 $q \in \mathbb{Z} \implies (!z. P (\text{of-int } z)) \implies P q$
 $\langle \text{proof} \rangle$

declare *int-Suc* [simp]

24.14 More Properties of *setsum* and *setprod*

By Jeremy Avigad

lemma *of-nat-setsum*: $\text{of-nat} (\text{setsum } f A) = (\sum x \in A. \text{of-nat}(f x))$
 $\langle \text{proof} \rangle$

lemma *of-int-setsum*: $\text{of-int} (\text{setsum } f A) = (\sum x \in A. \text{of-int}(f x))$
 $\langle \text{proof} \rangle$

lemma *int-setsum*: $\text{int} (\text{setsum } f A) = (\sum x \in A. \text{int}(f x))$
 $\langle \text{proof} \rangle$

lemma *of-nat-setprod*: $\text{of-nat} (\text{setprod } f A) = (\prod x \in A. \text{of-nat}(f x))$
 $\langle \text{proof} \rangle$

lemma *of-int-setprod*: $\text{of-int} (\text{setprod } f A) = (\prod x \in A. \text{of-int}(f x))$
 $\langle \text{proof} \rangle$

lemma *int-setprod*: $\text{int } (\text{setprod } f \ A) = (\prod_{x \in A} \text{int}(f \ x))$
 $\langle \text{proof} \rangle$

lemma *setprod-nonzero-nat*:
 $\text{finite } A \implies (\forall x \in A. f \ x \neq (0::\text{nat})) \implies \text{setprod } f \ A \neq 0$
 $\langle \text{proof} \rangle$

lemma *setprod-zero-eq-nat*:
 $\text{finite } A \implies (\text{setprod } f \ A = (0::\text{nat})) = (\exists x \in A. f \ x = 0)$
 $\langle \text{proof} \rangle$

lemma *setprod-nonzero-int*:
 $\text{finite } A \implies (\forall x \in A. f \ x \neq (0::\text{int})) \implies \text{setprod } f \ A \neq 0$
 $\langle \text{proof} \rangle$

lemma *setprod-zero-eq-int*:
 $\text{finite } A \implies (\text{setprod } f \ A = (0::\text{int})) = (\exists x \in A. f \ x = 0)$
 $\langle \text{proof} \rangle$

Now we replace the case analysis rule by a more conventional one: whether an integer is negative or not.

lemma *zless-iff-Suc-zadd*:
 $(w < z) = (\exists n. z = w + \text{int}(\text{Suc } n))$
 $\langle \text{proof} \rangle$

lemma *negD*: $x < 0 \implies \exists n. x = -(\text{int } (\text{Suc } n))$
 $\langle \text{proof} \rangle$

theorem *int-cases* [*cases type: int, case-names nonneg neg*]:
 $[[!n. z = \text{int } n \implies P; !n. z = -(\text{int } (\text{Suc } n)) \implies P] \implies P$
 $\langle \text{proof} \rangle$

theorem *int-induct* [*induct type: int, case-names nonneg neg*]:
 $[[!n. P (\text{int } n); !n. P (- (\text{int } (\text{Suc } n)))] \implies P \ z$
 $\langle \text{proof} \rangle$

Contributed by Brian Huffman

theorem *int-diff-cases* [*case-names diff*]:
assumes *prem*: $!m \ n. z = \text{int } m - \text{int } n \implies P$ **shows** P
 $\langle \text{proof} \rangle$

lemma *of-nat-nat*: $0 \leq z \implies \text{of-nat } (\text{nat } z) = \text{of-int } z$
 $\langle \text{proof} \rangle$

24.15 Configuration of the code generator

types-code

int (*int*)

attach (*term-of*) \ll

```

val term-of-int = HLogic.mk-int o IntInf.fromInt;
>>
attach (test) <<
fun gen-int i = one-of [ $\sim 1$ , 1] * random-range 0 i;
>>

```

constdefs

```

int-aux :: int  $\Rightarrow$  nat  $\Rightarrow$  int
int-aux i n == (i + int n)
nat-aux :: nat  $\Rightarrow$  int  $\Rightarrow$  nat
nat-aux n i == (n + nat i)

```

lemma [code]:

```

int-aux i 0 = i
int-aux i (Suc n) = int-aux (i + 1) n — tail recursive
int n = int-aux 0 n
<proof>

```

lemma [code]: nat-aux n i = (if i <= 0 then n else nat-aux (Suc n) (i - 1))

— tail recursive

<proof>

lemma [code]: nat i = nat-aux 0 i

<proof>

consts-code

```

0 :: int                (0)
1 :: int                (1)
uminus :: int  $\Rightarrow$  int    ( $\sim$ )
op + :: int  $\Rightarrow$  int  $\Rightarrow$  int ((- +/ -))
op * :: int  $\Rightarrow$  int  $\Rightarrow$  int ((- */ -))
op < :: int  $\Rightarrow$  int  $\Rightarrow$  bool ((- </ -))
op <= :: int  $\Rightarrow$  int  $\Rightarrow$  bool ((- <=/ -))
neg                ((- < 0))

```

<ML>

quickcheck-params [default-type = int]

<ML>

end

25 Numeral: Arithmetic on Binary Integers

theory Numeral

imports IntDef Datatype

```
uses ../Tools/numeral-syntax.ML
begin
```

The file *numeral-syntax.ML* hides the constructors *Pls* and *Min*. Only qualified access *Numeral.Pls* and *Numeral.Min* is allowed. The datatype constructors *bit.B0* and *bit.B1* are similarly hidden. We do not hide *Bit* because we need the *BIT* infix syntax.

This formalization defines binary arithmetic in terms of the integers rather than using a datatype. This avoids multiple representations (leading zeroes, etc.) See *ZF/Integ/two-compl.ML*, function *int-of-binary*, for the numerical interpretation.

The representation expects that $(m \bmod 2)$ is 0 or 1, even if *m* is negative; For instance, $-5 \operatorname{div} 2 = -3$ and $-5 \bmod 2 = 1$; thus $-5 = (-3)*2 + 1$.

```
typedef (Bin)
  bin = UNIV::int set
  <proof>
```

This datatype avoids the use of type *bool*, which would make all of the rewrite rules higher-order. If the use of datatype causes problems, this two-element type can easily be formalized using *typedef*.

```
datatype bit = B0 | B1
```

```
constdefs
```

```
Pls :: bin
Pls == Abs-Bin 0
```

```
Min :: bin
Min == Abs-Bin (- 1)
```

```
Bit :: [bin,bit] => bin    (infixl BIT 90)
— That is, 2w+b
w BIT b == Abs-Bin ((case b of B0 => 0 | B1 => 1) + Rep-Bin w + Rep-Bin
w)
```

```
axclass
```

```
number < type — for numeric types: nat, int, real, ...
```

```
consts
```

```
number-of :: bin => 'a::number
```

```
syntax
```

```
-Numeral :: num-const => 'a    (-)
Numeral0 :: 'a
Numeral1 :: 'a
```

```
translations
```


Numeral0 == *number-of Numeral.Pls*
Numeral1 == *number-of (Numeral.Pls BIT bit.B1)*

$\langle ML \rangle$

syntax (*xsymbols*)
 -*square* :: 'a => 'a ((⁻²) [1000] 999)
syntax (*HTML output*)
 -*square* :: 'a => 'a ((⁻²) [1000] 999)
syntax (*output*)
 -*square* :: 'a => 'a ((⁻ / 2) [81] 80)
translations
 $x^2 == x^{\wedge}2$
 $x^2 <= x^{\wedge}(2::nat)$

lemma *Let-number-of [simp]: Let (number-of v) f == f (number-of v)*
 — Unfold all *lets* involving constants
 $\langle proof \rangle$

lemma *Let-0 [simp]: Let 0 f == f 0*
 $\langle proof \rangle$

lemma *Let-1 [simp]: Let 1 f == f 1*
 $\langle proof \rangle$

constdefs

bin-succ :: *bin* => *bin*
bin-succ *w* == *Abs-Bin*(*Rep-Bin* *w* + 1)

bin-pred :: *bin* => *bin*
bin-pred *w* == *Abs-Bin*(*Rep-Bin* *w* - 1)

bin-minus :: *bin* => *bin*
bin-minus *w* == *Abs-Bin*(- (*Rep-Bin* *w*))

bin-add :: [*bin*, *bin*] => *bin*
bin-add *v* *w* == *Abs-Bin*(*Rep-Bin* *v* + *Rep-Bin* *w*)

bin-mult :: [*bin*, *bin*] => *bin*
bin-mult *v* *w* == *Abs-Bin*(*Rep-Bin* *v* * *Rep-Bin* *w*)

lemmas *Bin-simps* =
bin-succ-def bin-pred-def bin-minus-def bin-add-def bin-mult-def
Pls-def Min-def Bit-def Abs-Bin-inverse Rep-Bin-inverse Bin-def

Removal of leading zeroes

lemma *Pls-0-eq* [simp]: $\text{Numeral.Pls BIT bit.B0} = \text{Numeral.Pls}$
 ⟨proof⟩

lemma *Min-1-eq* [simp]: $\text{Numeral.Min BIT bit.B1} = \text{Numeral.Min}$
 ⟨proof⟩

25.1 The Functions *bin-succ*, *bin-pred* and *bin-minus*

lemma *bin-succ-Pls* [simp]: $\text{bin-succ Numeral.Pls} = \text{Numeral.Pls BIT bit.B1}$
 ⟨proof⟩

lemma *bin-succ-Min* [simp]: $\text{bin-succ Numeral.Min} = \text{Numeral.Pls}$
 ⟨proof⟩

lemma *bin-succ-1* [simp]: $\text{bin-succ}(w \text{ BIT bit.B1}) = (\text{bin-succ } w) \text{ BIT bit.B0}$
 ⟨proof⟩

lemma *bin-succ-0* [simp]: $\text{bin-succ}(w \text{ BIT bit.B0}) = w \text{ BIT bit.B1}$
 ⟨proof⟩

lemma *bin-pred-Pls* [simp]: $\text{bin-pred Numeral.Pls} = \text{Numeral.Min}$
 ⟨proof⟩

lemma *bin-pred-Min* [simp]: $\text{bin-pred Numeral.Min} = \text{Numeral.Min BIT bit.B0}$
 ⟨proof⟩

lemma *bin-pred-1* [simp]: $\text{bin-pred}(w \text{ BIT bit.B1}) = w \text{ BIT bit.B0}$
 ⟨proof⟩

lemma *bin-pred-0* [simp]: $\text{bin-pred}(w \text{ BIT bit.B0}) = (\text{bin-pred } w) \text{ BIT bit.B1}$
 ⟨proof⟩

lemma *bin-minus-Pls* [simp]: $\text{bin-minus Numeral.Pls} = \text{Numeral.Pls}$
 ⟨proof⟩

lemma *bin-minus-Min* [simp]: $\text{bin-minus Numeral.Min} = \text{Numeral.Pls BIT bit.B1}$
 ⟨proof⟩

lemma *bin-minus-1* [simp]:
 $\text{bin-minus } (w \text{ BIT bit.B1}) = \text{bin-pred } (\text{bin-minus } w) \text{ BIT bit.B1}$
 ⟨proof⟩

lemma *bin-minus-0* [simp]: $\text{bin-minus}(w \text{ BIT bit.B0}) = (\text{bin-minus } w) \text{ BIT bit.B0}$
 ⟨proof⟩

25.2 Binary Addition and Multiplication: *bin-add* and *bin-mult*

lemma *bin-add-Pls* [simp]: $\text{bin-add Numeral.Pls } w = w$
 ⟨proof⟩

lemma *bin-add-Min* [simp]: *bin-add Numeral.Min w = bin-pred w*
 ⟨proof⟩

lemma *bin-add-BIT-11* [simp]:
bin-add (v BIT bit.B1) (w BIT bit.B1) = bin-add v (bin-succ w) BIT bit.B0
 ⟨proof⟩

lemma *bin-add-BIT-10* [simp]:
bin-add (v BIT bit.B1) (w BIT bit.B0) = (bin-add v w) BIT bit.B1
 ⟨proof⟩

lemma *bin-add-BIT-0* [simp]:
bin-add (v BIT bit.B0) (w BIT y) = bin-add v w BIT y
 ⟨proof⟩

lemma *bin-add-Pls-right* [simp]: *bin-add w Numeral.Pls = w*
 ⟨proof⟩

lemma *bin-add-Min-right* [simp]: *bin-add w Numeral.Min = bin-pred w*
 ⟨proof⟩

lemma *bin-mult-Pls* [simp]: *bin-mult Numeral.Pls w = Numeral.Pls*
 ⟨proof⟩

lemma *bin-mult-Min* [simp]: *bin-mult Numeral.Min w = bin-minus w*
 ⟨proof⟩

lemma *bin-mult-1* [simp]:
bin-mult (v BIT bit.B1) w = bin-add ((bin-mult v w) BIT bit.B0) w
 ⟨proof⟩

lemma *bin-mult-0* [simp]: *bin-mult (v BIT bit.B0) w = (bin-mult v w) BIT bit.B0*
 ⟨proof⟩

25.3 Converting Numerals to Rings: *number-of*

axclass *number-ring* \subseteq *number*, *comm-ring-1*
number-of-eq: *number-of w = of-int (Rep-Bin w)*

lemma *number-of-succ*:
number-of (bin-succ w) = (1 + number-of w :: 'a::number-ring)
 ⟨proof⟩

lemma *number-of-pred*:
number-of (bin-pred w) = (- 1 + number-of w :: 'a::number-ring)
 ⟨proof⟩

lemma *number-of-minus*:

$number-of(bin-minus\ w) = (-\ (number-of\ w)::'a::number-ring)$
 $\langle proof \rangle$

lemma *number-of-add*:

$number-of(bin-add\ v\ w) = (number-of\ v + number-of\ w)::'a::number-ring)$
 $\langle proof \rangle$

lemma *number-of-mult*:

$number-of(bin-mult\ v\ w) = (number-of\ v * number-of\ w)::'a::number-ring)$
 $\langle proof \rangle$

The correctness of shifting. But it doesn't seem to give a measurable speed-up.

lemma *double-number-of-BIT*:

$(1+1) * number-of\ w = (number-of\ (w\ BIT\ bit.B0) ::'a::number-ring)$
 $\langle proof \rangle$

Converting numerals 0 and 1 to their abstract versions

lemma *numeral-0-eq-0* [simp]: $Numeral0 = (0::'a::number-ring)$
 $\langle proof \rangle$

lemma *numeral-1-eq-1* [simp]: $Numeral1 = (1::'a::number-ring)$
 $\langle proof \rangle$

Special-case simplification for small constants

Unary minus for the abstract constant 1. Cannot be inserted as a simp rule until later: it is *number-of-Min* re-oriented!

lemma *numeral-m1-eq-minus-1*: $(-1::'a::number-ring) = -\ 1$
 $\langle proof \rangle$

lemma *mult-minus1* [simp]: $-1 * z = -(z::'a::number-ring)$
 $\langle proof \rangle$

lemma *mult-minus1-right* [simp]: $z * -1 = -(z::'a::number-ring)$
 $\langle proof \rangle$

lemma *minus-number-of-mult* [simp]:

$-(number-of\ w) * z = number-of(bin-minus\ w) * (z::'a::number-ring)$
 $\langle proof \rangle$

Subtraction

lemma *diff-number-of-eq*:

$number-of\ v - number-of\ w =$
 $(number-of(bin-add\ v\ (bin-minus\ w))::'a::number-ring)$
 $\langle proof \rangle$

lemma *number-of-Pls*: *number-of Numeral.Pls* = $(0 :: 'a :: \text{number-ring})$
 $\langle \text{proof} \rangle$

lemma *number-of-Min*: *number-of Numeral.Min* = $(- 1 :: 'a :: \text{number-ring})$
 $\langle \text{proof} \rangle$

lemma *number-of-BIT*:
 $\text{number-of}(w \text{ BIT } x) = (\text{case } x \text{ of } \text{bit.B0} \Rightarrow 0 \mid \text{bit.B1} \Rightarrow (1 :: 'a :: \text{number-ring}))$
 $+$
 $(\text{number-of } w) + (\text{number-of } w)$
 $\langle \text{proof} \rangle$

25.4 Equality of Binary Numbers

First version by Norbert Voelker

lemma *eq-number-of-eq*:
 $((\text{number-of } x :: 'a :: \text{number-ring}) = \text{number-of } y) =$
 $\text{iszero } (\text{number-of } (\text{bin-add } x (\text{bin-minus } y)) :: 'a)$
 $\langle \text{proof} \rangle$

lemma *iszero-number-of-Pls*: *iszero* $((\text{number-of Numeral.Pls}) :: 'a :: \text{number-ring})$
 $\langle \text{proof} \rangle$

lemma *nonzero-number-of-Min*: $\sim \text{iszero } ((\text{number-of Numeral.Min}) :: 'a :: \text{number-ring})$
 $\langle \text{proof} \rangle$

25.5 Comparisons, for Ordered Rings

lemma *double-eq-0-iff*: $(a + a = 0) = (a = (0 :: 'a :: \text{ordered-idom}))$
 $\langle \text{proof} \rangle$

lemma *le-imp-0-less*:
assumes *le*: $0 \leq z$ **shows** $(0 :: \text{int}) < 1 + z$
 $\langle \text{proof} \rangle$

lemma *odd-nonzero*: $1 + z + z \neq (0 :: \text{int})$
 $\langle \text{proof} \rangle$

The premise involving \mathbb{Z} prevents $a = (1 :: 'a) / (2 :: 'a)$.

lemma *Ints-odd-nonzero*: $a \in \text{Ints} \Rightarrow 1 + a + a \neq (0 :: 'a :: \text{ordered-idom})$
 $\langle \text{proof} \rangle$

lemma *Ints-number-of*: $(\text{number-of } w :: 'a :: \text{number-ring}) \in \text{Ints}$
 $\langle \text{proof} \rangle$

lemma *iszero-number-of-BIT*:

$$\text{iszero } (\text{number-of } (w \text{ BIT } x) :: 'a) =$$

$$(x = \text{bit}.B0 \ \& \ \text{iszero } (\text{number-of } w :: 'a :: \{\text{ordered-idom}, \text{number-ring}\}))$$

$$\langle \text{proof} \rangle$$

lemma *iszero-number-of-0*:

$$\text{iszero } (\text{number-of } (w \text{ BIT } \text{bit}.B0) :: 'a :: \{\text{ordered-idom}, \text{number-ring}\}) =$$

$$\text{iszero } (\text{number-of } w :: 'a)$$

$$\langle \text{proof} \rangle$$

lemma *iszero-number-of-1*:

$$\sim \text{iszero } (\text{number-of } (w \text{ BIT } \text{bit}.B1) :: 'a :: \{\text{ordered-idom}, \text{number-ring}\})$$

$$\langle \text{proof} \rangle$$

25.6 The Less-Than Relation

lemma *less-number-of-eq-neg*:

$$((\text{number-of } x :: 'a :: \{\text{ordered-idom}, \text{number-ring}\}) < \text{number-of } y)$$

$$= \text{neg } (\text{number-of } (\text{bin-add } x \ (\text{bin-minus } y)) :: 'a)$$

$$\langle \text{proof} \rangle$$

If *Numeral0* is rewritten to 0 then this rule can't be applied: *Numeral0* IS *Numeral0*

lemma *not-neg-number-of-Pls*:

$$\sim \text{neg } (\text{number-of } \text{Numeral}.Pls :: 'a :: \{\text{ordered-idom}, \text{number-ring}\})$$

$$\langle \text{proof} \rangle$$

lemma *neg-number-of-Min*:

$$\text{neg } (\text{number-of } \text{Numeral}.Min :: 'a :: \{\text{ordered-idom}, \text{number-ring}\})$$

$$\langle \text{proof} \rangle$$

lemma *double-less-0-iff*: $(a + a < 0) = (a < (0 :: 'a :: \text{ordered-idom}))$

$$\langle \text{proof} \rangle$$

lemma *odd-less-0*: $(1 + z + z < 0) = (z < (0 :: \text{int}))$

$$\langle \text{proof} \rangle$$

The premise involving \mathbb{Z} prevents $a = (1 :: 'a) / (2 :: 'a)$.

lemma *Ints-odd-less-0*:

$$a \in \text{Ints} ==> (1 + a + a < 0) = (a < (0 :: 'a :: \text{ordered-idom}))$$

$$\langle \text{proof} \rangle$$

lemma *neg-number-of-BIT*:

$$\text{neg } (\text{number-of } (w \text{ BIT } x) :: 'a) =$$

$$\text{neg } (\text{number-of } w :: 'a :: \{\text{ordered-idom}, \text{number-ring}\})$$

$$\langle \text{proof} \rangle$$

Less-Than or Equals

Reduces $a \leq b$ to $\neg b < a$ for ALL numerals

lemmas *le-number-of-eq-not-less* =
linorder-not-less [of number-of *w* number-of *v*, symmetric,
 standard]

lemma *le-number-of-eq*:
 $((\text{number-of } x :: 'a :: \{\text{ordered-idom}, \text{number-ring}\}) \leq \text{number-of } y)$
 $= (\sim (\text{neg } (\text{number-of } (\text{bin-add } y (\text{bin-minus } x)) :: 'a)))$
 <proof>

Absolute value (*abs*)

lemma *abs-number-of*:
 $\text{abs}(\text{number-of } x :: 'a :: \{\text{ordered-idom}, \text{number-ring}\}) =$
 $(\text{if } \text{number-of } x < (0 :: 'a) \text{ then } -\text{number-of } x \text{ else } \text{number-of } x)$
 <proof>

Re-orientation of the equation *nnn=x*

lemma *number-of-reorient*: $(\text{number-of } w = x) = (x = \text{number-of } w)$
 <proof>

25.7 Simplification of arithmetic operations on integer constants.

lemmas *bin-arith-extra-simps* =
number-of-add [symmetric]
number-of-minus [symmetric] *numeral-m1-eq-minus-1* [symmetric]
number-of-mult [symmetric]
diff-number-of-eq abs-number-of

For making a minimal simpset, one must include these default simprules.
 Also include *simp-thms*

lemmas *bin-arith-simps* =
Numeral.bit.distinct
Pls-0-eq Min-1-eq
bin-pred-Pls bin-pred-Min bin-pred-1 bin-pred-0
bin-succ-Pls bin-succ-Min bin-succ-1 bin-succ-0
bin-add-Pls bin-add-Min bin-add-BIT-0 bin-add-BIT-10 bin-add-BIT-11
bin-minus-Pls bin-minus-Min bin-minus-1 bin-minus-0
bin-mult-Pls bin-mult-Min bin-mult-1 bin-mult-0
bin-add-Pls-right bin-add-Min-right
abs-zero abs-one bin-arith-extra-simps

Simplification of relational operations

lemmas *bin-rel-simps* =
eq-number-of-eq iszero-number-of-Pls nonzero-number-of-Min
iszero-number-of-0 iszero-number-of-1
less-number-of-eq-neg
not-neg-number-of-Pls not-neg-0 not-neg-1 not-iszero-1
neg-number-of-Min neg-number-of-BIT

le-number-of-eq

declare *bin-arith-extra-simps* [*simp*]
declare *bin-rel-simps* [*simp*]

25.8 Simplification of arithmetic when nested to the right

lemma *add-number-of-left* [*simp*]:

$$\text{number-of } v + (\text{number-of } w + z) =$$

$$(\text{number-of } (\text{bin-add } v \ w) + z :: 'a :: \text{number-ring})$$

$$\langle \text{proof} \rangle$$

lemma *mult-number-of-left* [*simp*]:

$$\text{number-of } v * (\text{number-of } w * z) =$$

$$(\text{number-of } (\text{bin-mult } v \ w) * z :: 'a :: \text{number-ring})$$

$$\langle \text{proof} \rangle$$

lemma *add-number-of-diff1*:

$$\text{number-of } v + (\text{number-of } w - c) =$$

$$\text{number-of } (\text{bin-add } v \ w) - (c :: 'a :: \text{number-ring})$$

$$\langle \text{proof} \rangle$$

lemma *add-number-of-diff2* [*simp*]: $\text{number-of } v + (c - \text{number-of } w) =$

$$\text{number-of } (\text{bin-add } v \ (\text{bin-minus } w)) + (c :: 'a :: \text{number-ring})$$

$$\langle \text{proof} \rangle$$

end

26 IntArith: Integer arithmetic

theory *IntArith*
imports *N numeral*
uses (*int-arith1.ML*)
begin

Duplicate: can't understand why it's necessary

declare *numeral-0-eq-0* [*simp*]

26.1 Instantiating Binary Arithmetic for the Integers

instance
 $\text{int} :: \text{number} \langle \text{proof} \rangle$

defs (**overloaded**)
 $\text{int-number-of-def}: (\text{number-of } w :: \text{int}) == \text{of-int } (\text{Rep-Bin } w)$
 — the type constraint is essential!

instance $\text{int} :: \text{number-ring}$

$\langle proof \rangle$

26.2 Inequality Reasoning for the Arithmetic Simproc

lemma *add-numeral-0*: $\text{Numeral0} + a = (a::'a::\text{number-ring})$

$\langle proof \rangle$

lemma *add-numeral-0-right*: $a + \text{Numeral0} = (a::'a::\text{number-ring})$

$\langle proof \rangle$

lemma *mult-numeral-1*: $\text{Numeral1} * a = (a::'a::\text{number-ring})$

$\langle proof \rangle$

lemma *mult-numeral-1-right*: $a * \text{Numeral1} = (a::'a::\text{number-ring})$

$\langle proof \rangle$

Theorem lists for the cancellation simprocs. The use of binary numerals for 0 and 1 reduces the number of special cases.

lemmas *add-0s* = *add-numeral-0 add-numeral-0-right*

lemmas *mult-1s* = *mult-numeral-1 mult-numeral-1-right*
mult-minus1 mult-minus1-right

26.3 Special Arithmetic Rules for Abstract 0 and 1

Arithmetic computations are defined for binary literals, which leaves 0 and 1 as special cases. Addition already has rules for 0, but not 1. Multiplication and unary minus already have rules for both 0 and 1.

lemma *binop-eq*: $[[f\ x\ y = g\ x\ y; x = x'; y = y']] ==> f\ x'\ y' = g\ x'\ y'$

$\langle proof \rangle$

lemmas *add-number-of-eq* = *number-of-add* [*symmetric*]

Allow 1 on either or both sides

lemma *one-add-one-is-two*: $1 + 1 = (2::'a::\text{number-ring})$

$\langle proof \rangle$

lemmas *add-special* =

one-add-one-is-two

binop-eq [*of op +, OF add-number-of-eq numeral-1-eq-1 refl, standard*]

binop-eq [*of op +, OF add-number-of-eq refl numeral-1-eq-1, standard*]

Allow 1 on either or both sides (1-1 already simplifies to 0)

lemmas *diff-special* =

binop-eq [*of op -, OF diff-number-of-eq numeral-1-eq-1 refl, standard*]

binop-eq [*of op -, OF diff-number-of-eq refl numeral-1-eq-1, standard*]

Allow 0 or 1 on either side with a binary numeral on the other

lemmas *eq-special* =
 binop-eq [of op =, OF eq-number-of-eq numeral-0-eq-0 refl, standard]
 binop-eq [of op =, OF eq-number-of-eq numeral-1-eq-1 refl, standard]
 binop-eq [of op =, OF eq-number-of-eq refl numeral-0-eq-0, standard]
 binop-eq [of op =, OF eq-number-of-eq refl numeral-1-eq-1, standard]

Allow 0 or 1 on either side with a binary numeral on the other

lemmas *less-special* =
 binop-eq [of op <, OF less-number-of-eq-neg numeral-0-eq-0 refl, standard]
 binop-eq [of op <, OF less-number-of-eq-neg numeral-1-eq-1 refl, standard]
 binop-eq [of op <, OF less-number-of-eq-neg refl numeral-0-eq-0, standard]
 binop-eq [of op <, OF less-number-of-eq-neg refl numeral-1-eq-1, standard]

Allow 0 or 1 on either side with a binary numeral on the other

lemmas *le-special* =
 binop-eq [of op ≤, OF le-number-of-eq numeral-0-eq-0 refl, standard]
 binop-eq [of op ≤, OF le-number-of-eq numeral-1-eq-1 refl, standard]
 binop-eq [of op ≤, OF le-number-of-eq refl numeral-0-eq-0, standard]
 binop-eq [of op ≤, OF le-number-of-eq refl numeral-1-eq-1, standard]

lemmas *arith-special* =
 add-special *diff-special* *eq-special* *less-special* *le-special*

⟨ML⟩

26.4 Lemmas About Small Numerals

lemma *of-int-m1* [simp]: *of-int* $-1 = (-1 :: 'a :: \text{number-ring})$
 ⟨proof⟩

lemma *abs-minus-one* [simp]: *abs* $(-1) = (1 :: 'a :: \{\text{ordered-idom}, \text{number-ring}\})$
 ⟨proof⟩

lemma *abs-power-minus-one* [simp]:
 abs $(-1 \wedge n) = (1 :: 'a :: \{\text{ordered-idom}, \text{number-ring}, \text{recpower}\})$
 ⟨proof⟩

lemma *of-int-number-of-eq*:
 of-int (*number-of* v) = (*number-of* $v :: 'a :: \text{number-ring}$)
 ⟨proof⟩

Lemmas for specialist use, NOT as default simprules

lemma *mult-2*: $2 * z = (z + z :: 'a :: \text{number-ring})$
 ⟨proof⟩

lemma *mult-2-right*: $z * 2 = (z + z :: 'a :: \text{number-ring})$
 ⟨proof⟩

26.5 More Inequality Reasoning

lemma *zless-add1-eq*: $(w < z + (1::int)) = (w < z \mid w = z)$
 $\langle proof \rangle$

lemma *add1-zle-eq*: $(w + (1::int) \leq z) = (w < z)$
 $\langle proof \rangle$

lemma *zle-diff1-eq* [simp]: $(w \leq z - (1::int)) = (w < z)$
 $\langle proof \rangle$

lemma *zle-add1-eq-le* [simp]: $(w < z + (1::int)) = (w \leq z)$
 $\langle proof \rangle$

lemma *int-one-le-iff-zero-less*: $((1::int) \leq z) = (0 < z)$
 $\langle proof \rangle$

26.6 The Functions *nat* and *int*

Simplify the terms *int 0*, *int (Suc 0)* and $w + - z$

declare *Zero-int-def* [symmetric, simp]

declare *One-int-def* [symmetric, simp]

cooper.ML refers to this theorem

lemmas *diff-int-def-symmetric* = *diff-int-def* [symmetric, simp]

lemma *nat-0*: $\text{nat } 0 = 0$
 $\langle proof \rangle$

lemma *nat-1*: $\text{nat } 1 = \text{Suc } 0$
 $\langle proof \rangle$

lemma *nat-2*: $\text{nat } 2 = \text{Suc } (\text{Suc } 0)$
 $\langle proof \rangle$

lemma *one-less-nat-eq* [simp]: $(\text{Suc } 0 < \text{nat } z) = (1 < z)$
 $\langle proof \rangle$

This simplifies expressions of the form $\text{int } n = z$ where z is an integer literal.

lemmas *int-eq-iff-number-of* = *int-eq-iff* [of - number-of v , standard]

declare *int-eq-iff-number-of* [simp]

lemma *split-nat* [arith-split]:

$P(\text{nat}(i::int)) = ((\forall n. i = \text{int } n \longrightarrow P n) \ \& \ (i < 0 \longrightarrow P 0))$
 $(\text{is } ?P = (?L \ \& \ ?R))$

$\langle proof \rangle$

lemma *zdiff-int*: $n \leq m \implies \text{int } m - \text{int } n = \text{int } (m - n)$
 $\langle \text{proof} \rangle$

lemma *nat-mult-distrib*: $(0::\text{int}) \leq z \implies \text{nat } (z * z') = \text{nat } z * \text{nat } z'$
 $\langle \text{proof} \rangle$

lemma *nat-mult-distrib-neg*: $z \leq (0::\text{int}) \implies \text{nat } (z * z') = \text{nat } (-z) * \text{nat } (-z')$
 $\langle \text{proof} \rangle$

lemma *nat-abs-mult-distrib*: $\text{nat } (\text{abs } (w * z)) = \text{nat } (\text{abs } w) * \text{nat } (\text{abs } z)$
 $\langle \text{proof} \rangle$

26.7 Induction principles for int

theorem *int-ge-induct*[*case-names base step, induct set:int*]:
 assumes *ge*: $k \leq (i::\text{int})$ and
 base: $P(k)$ and
 step: $\bigwedge i. \llbracket k \leq i; P \ i \rrbracket \implies P(i+1)$
 shows $P \ i$
 $\langle \text{proof} \rangle$

theorem *int-gr-induct*[*case-names base step, induct set:int*]:
 assumes *gr*: $k < (i::\text{int})$ and
 base: $P(k+1)$ and
 step: $\bigwedge i. \llbracket k < i; P \ i \rrbracket \implies P(i+1)$
 shows $P \ i$
 $\langle \text{proof} \rangle$

theorem *int-le-induct*[*consumes 1, case-names base step*]:
 assumes *le*: $i \leq (k::\text{int})$ and
 base: $P(k)$ and
 step: $\bigwedge i. \llbracket i \leq k; P \ i \rrbracket \implies P(i - 1)$
 shows $P \ i$
 $\langle \text{proof} \rangle$

theorem *int-less-induct* [*consumes 1, case-names base step*]:
 assumes *less*: $(i::\text{int}) < k$ and
 base: $P(k - 1)$ and
 step: $\bigwedge i. \llbracket i < k; P \ i \rrbracket \implies P(i - 1)$
 shows $P \ i$
 $\langle \text{proof} \rangle$

26.8 Intermediate value theorems

lemma *int-val-lemma*:
 $(\forall i < n::\text{nat}. \text{abs}(f(i+1) - f \ i) \leq 1) \dashv\dashv$
 $f \ 0 \leq k \dashv\dashv k \leq f \ n \dashv\dashv (\exists i \leq n. f \ i = (k::\text{int}))$
 $\langle \text{proof} \rangle$

lemmas *nat0-intermed-int-val* = *int-val-lemma* [rule-format (no-asm)]

lemma *nat-intermed-int-val*:

$$[[\forall i. m \leq i \ \& \ i < n \longrightarrow \text{abs}(f(i + 1::\text{nat}) - f\ i) \leq 1; m < n; \\ f\ m \leq k; k \leq f\ n]] \Longrightarrow ? i. m \leq i \ \& \ i \leq n \ \& \ f\ i = (k::\text{int})$$

 $\langle \text{proof} \rangle$

26.9 Products and 1, by T. M. Rasmussen

lemma *zabs-less-one-iff* [simp]: $(|z| < 1) = (z = (0::\text{int}))$
 $\langle \text{proof} \rangle$

lemma *abs-zmult-eq-1*: $(|m * n| = 1) \Longrightarrow |m| = (1::\text{int})$
 $\langle \text{proof} \rangle$

lemma *pos-zmult-eq-1-iff-lemma*: $(m * n = 1) \Longrightarrow m = (1::\text{int}) \mid m = -1$
 $\langle \text{proof} \rangle$

lemma *pos-zmult-eq-1-iff*: $0 < (m::\text{int}) \Longrightarrow (m * n = 1) = (m = 1 \ \& \ n = 1)$
 $\langle \text{proof} \rangle$

lemma *zmult-eq-1-iff*: $(m * n = (1::\text{int})) = ((m = 1 \ \& \ n = 1) \mid (m = -1 \ \& \ n = -1))$
 $\langle \text{proof} \rangle$

$\langle \text{ML} \rangle$

end

27 SetInterval: Set intervals

theory *SetInterval*

imports *IntArith*

begin

constdefs

lessThan :: $('a::\text{ord}) \Rightarrow 'a \text{ set } ((1\{-..-\}))$
 $\{-..<u\} == \{x. x < u\}$

atMost :: $('a::\text{ord}) \Rightarrow 'a \text{ set } ((1\{-..-\}))$
 $\{-..u\} == \{x. x \leq u\}$

greaterThan :: $('a::\text{ord}) \Rightarrow 'a \text{ set } ((1\{-<..\}))$
 $\{l<..\} == \{x. l < x\}$

atLeast :: $('a::\text{ord}) \Rightarrow 'a \text{ set } ((1\{-..-\}))$
 $\{l..\} == \{x. l \leq x\}$

greaterThanLessThan :: [*a*::ord, 'a] => 'a set ((1{-<..*u*-}))
 {*l*<..*u*} == {*l*<..*u*} Int {..*u*}

atLeastLessThan :: [*a*::ord, 'a] => 'a set ((1{-..*u*-}))
 {..*u*} == {..*u*} Int {..*u*}

greaterThanAtMost :: [*a*::ord, 'a] => 'a set ((1{-<..*u*-}))
 {*l*<..*u*} == {*l*<..*u*} Int {..*u*}

atLeastAtMost :: [*a*::ord, 'a] => 'a set ((1{-..*u*-}))
 {..*u*} == {..*u*} Int {..*u*}

syntax

-*lessThan* :: ('a::ord) => 'a set ((1{..'(')}))
 -*greaterThan* :: ('a::ord) => 'a set ((1{'(')-..}))
 -*greaterThanLessThan* :: [*a*::ord, 'a] => 'a set ((1{'(')-..'(')}))
 -*atLeastLessThan* :: [*a*::ord, 'a] => 'a set ((1{..'(')}))
 -*greaterThanAtMost* :: [*a*::ord, 'a] => 'a set ((1{'(')-..}))

translations

{..*m*()} => {..*m*}
 {}*m*..} => {*m*<..*u*}
 {}*m*..*n*() => {*m*<..*n*}
 {*m*..*n*()} => {*m*..*n*}
 {}*m*..*n*} => {*m*<..*n*}

A note of warning when using {..*n*} on type *nat*: it is equivalent to {0..*n*} but some lemmas involving {*m*..*n*} may not exist in {..*n*}-form as well.

syntax

@*UNION-le* :: nat => nat => 'b set => 'b set ((3UN -<= - / -) 10)
 @*UNION-less* :: nat => nat => 'b set => 'b set ((3UN -< - / -) 10)
 @*INTER-le* :: nat => nat => 'b set => 'b set ((3INT -<= - / -) 10)
 @*INTER-less* :: nat => nat => 'b set => 'b set ((3INT -< - / -) 10)

syntax (*input*)

@*UNION-le* :: nat => nat => 'b set => 'b set ((3U -≤ - / -) 10)
 @*UNION-less* :: nat => nat => 'b set => 'b set ((3U -< - / -) 10)
 @*INTER-le* :: nat => nat => 'b set => 'b set ((3I -≤ - / -) 10)
 @*INTER-less* :: nat => nat => 'b set => 'b set ((3I -< - / -) 10)

syntax (*xsymbols*)

@*UNION-le* :: nat ⇒ nat => 'b set => 'b set ((3U (00_ ≤ -) / -) 10)
 @*UNION-less* :: nat ⇒ nat => 'b set => 'b set ((3U (00_ < -) / -) 10)
 @*INTER-le* :: nat ⇒ nat => 'b set => 'b set ((3I (00_ ≤ -) / -) 10)
 @*INTER-less* :: nat ⇒ nat => 'b set => 'b set ((3I (00_ < -) / -) 10)

translations

UN *i*<= *n*. *A* == UN *i*:{..*n*}. *A*

$$\begin{aligned} UN\ i < n. A &== UN\ i: \{..<n\}. A \\ INT\ i <= n. A &== INT\ i: \{..n\}. A \\ INT\ i < n. A &== INT\ i: \{..<n\}. A \end{aligned}$$

27.1 Various equivalences

lemma *lessThan-iff* [iff]: $(i: lessThan\ k) = (i < k)$
 ⟨proof⟩

lemma *Compl-lessThan* [simp]:
 $!!k:: 'a::linorder. \neg lessThan\ k = atLeast\ k$
 ⟨proof⟩

lemma *single-Diff-lessThan* [simp]: $!!k:: 'a::order. \{k\} - lessThan\ k = \{k\}$
 ⟨proof⟩

lemma *greaterThan-iff* [iff]: $(i: greaterThan\ k) = (k < i)$
 ⟨proof⟩

lemma *Compl-greaterThan* [simp]:
 $!!k:: 'a::linorder. \neg greaterThan\ k = atMost\ k$
 ⟨proof⟩

lemma *Compl-atMost* [simp]: $!!k:: 'a::linorder. \neg atMost\ k = greaterThan\ k$
 ⟨proof⟩

lemma *atLeast-iff* [iff]: $(i: atLeast\ k) = (k \leq i)$
 ⟨proof⟩

lemma *Compl-atLeast* [simp]:
 $!!k:: 'a::linorder. \neg atLeast\ k = lessThan\ k$
 ⟨proof⟩

lemma *atMost-iff* [iff]: $(i: atMost\ k) = (i \leq k)$
 ⟨proof⟩

lemma *atMost-Int-atLeast*: $!!n:: 'a::order. atMost\ n\ Int\ atLeast\ n = \{n\}$
 ⟨proof⟩

27.2 Logical Equivalences for Set Inclusion and Equality

lemma *atLeast-subset-iff* [iff]:
 $(atLeast\ x \subseteq atLeast\ y) = (y \leq (x::'a::order))$
 ⟨proof⟩

lemma *atLeast-eq-iff* [iff]:
 $(atLeast\ x = atLeast\ y) = (x = (y::'a::linorder))$
 ⟨proof⟩

lemma *greaterThan-subset-iff* [iff]:

$(greaterThan\ x \subseteq greaterThan\ y) = (y \leq (x::'a::linorder))$
 $\langle proof \rangle$

lemma *greaterThan-eq-iff* [iff]:
 $(greaterThan\ x = greaterThan\ y) = (x = (y::'a::linorder))$
 $\langle proof \rangle$

lemma *atMost-subset-iff* [iff]: $(atMost\ x \subseteq atMost\ y) = (x \leq (y::'a::order))$
 $\langle proof \rangle$

lemma *atMost-eq-iff* [iff]: $(atMost\ x = atMost\ y) = (x = (y::'a::linorder))$
 $\langle proof \rangle$

lemma *lessThan-subset-iff* [iff]:
 $(lessThan\ x \subseteq lessThan\ y) = (x \leq (y::'a::linorder))$
 $\langle proof \rangle$

lemma *lessThan-eq-iff* [iff]:
 $(lessThan\ x = lessThan\ y) = (x = (y::'a::linorder))$
 $\langle proof \rangle$

27.3 Two-sided intervals

lemma *greaterThanLessThan-iff* [simp]:
 $(i : \{l <..<u\}) = (l < i \ \& \ i < u)$
 $\langle proof \rangle$

lemma *atLeastLessThan-iff* [simp]:
 $(i : \{l..<u\}) = (l \leq i \ \& \ i < u)$
 $\langle proof \rangle$

lemma *greaterThanAtMost-iff* [simp]:
 $(i : \{l <..u\}) = (l < i \ \& \ i \leq u)$
 $\langle proof \rangle$

lemma *atLeastAtMost-iff* [simp]:
 $(i : \{l..u\}) = (l \leq i \ \& \ i \leq u)$
 $\langle proof \rangle$

The above four lemmas could be declared as iffs. If we do so, a call to blast in Hyperreal/Star.ML, lemma *STAR-Int* seems to take forever (more than one hour).

27.3.1 Emptiness and singletons

lemma *atLeastAtMost-empty* [simp]: $n < m \implies \{m::'a::order..n\} = \{\}$
 $\langle proof \rangle$

lemma *atLeastLessThan-empty* [simp]: $n \leq m \implies \{m..<n::'a::order\} = \{\}$

$\langle proof \rangle$

lemma *greaterThanAtMost-empty*[simp]: $l \leq k \implies \{k <..(l::'a::order)\} = \{\}$
 $\langle proof \rangle$

lemma *greaterThanLessThan-empty*[simp]: $l \leq k \implies \{k <..(l::'a::order)\} = \{\}$
 $\langle proof \rangle$

lemma *atLeastAtMost-singleton* [simp]: $\{a::'a::order..a\} = \{a\}$
 $\langle proof \rangle$

27.4 Intervals of natural numbers

27.4.1 The Constant *lessThan*

lemma *lessThan-0* [simp]: $lessThan\ 0::nat = \{\}$
 $\langle proof \rangle$

lemma *lessThan-Suc*: $lessThan\ (Suc\ k) = insert\ k\ (lessThan\ k)$
 $\langle proof \rangle$

lemma *lessThan-Suc-atMost*: $lessThan\ (Suc\ k) = atMost\ k$
 $\langle proof \rangle$

lemma *UN-lessThan-UNIV*: $(UN\ m::nat.\ lessThan\ m) = UNIV$
 $\langle proof \rangle$

27.4.2 The Constant *greaterThan*

lemma *greaterThan-0* [simp]: $greaterThan\ 0 = range\ Suc$
 $\langle proof \rangle$

lemma *greaterThan-Suc*: $greaterThan\ (Suc\ k) = greaterThan\ k - \{Suc\ k\}$
 $\langle proof \rangle$

lemma *INT-greaterThan-UNIV*: $(INT\ m::nat.\ greaterThan\ m) = \{\}$
 $\langle proof \rangle$

27.4.3 The Constant *atLeast*

lemma *atLeast-0* [simp]: $atLeast\ 0::nat = UNIV$
 $\langle proof \rangle$

lemma *atLeast-Suc*: $atLeast\ (Suc\ k) = atLeast\ k - \{k\}$
 $\langle proof \rangle$

lemma *atLeast-Suc-greaterThan*: $atLeast\ (Suc\ k) = greaterThan\ k$
 $\langle proof \rangle$

lemma *UN-atLeast-UNIV*: $(UN\ m::nat.\ atLeast\ m) = UNIV$

$\langle proof \rangle$

27.4.4 The Constant *atMost*

lemma *atMost-0* [simp]: $atMost\ (0::nat) = \{0\}$
 $\langle proof \rangle$

lemma *atMost-Suc*: $atMost\ (Suc\ k) = insert\ (Suc\ k)\ (atMost\ k)$
 $\langle proof \rangle$

lemma *UN-atMost-UNIV*: $(UN\ m::nat.\ atMost\ m) = UNIV$
 $\langle proof \rangle$

27.4.5 The Constant *atLeastLessThan*

But not a simprule because some concepts are better left in terms of *atLeastLessThan*

lemma *atLeast0LessThan*: $\{0::nat..<n\} = \{..
 $\langle proof \rangle$$

27.4.6 Intervals of nats with *Suc*

Not a simprule because the RHS is too messy.

lemma *atLeastLessThanSuc*:
 $\{m..
 $\langle proof \rangle$$

lemma *atLeastLessThan-singleton* [simp]: $\{m..
 $\langle proof \rangle$$

lemma *atLeastLessThanSuc-atLeastAtMost*: $\{l..
 $\langle proof \rangle$$

lemma *atLeastSucAtMost-greaterThanAtMost*: $\{Suc\ l..u\} = \{l<..
 $\langle proof \rangle$$

lemma *atLeastSucLessThan-greaterThanLessThan*: $\{Suc\ l..
 $\langle proof \rangle$$

lemma *atLeastAtMostSuc-conv*: $m \leq Suc\ n \implies \{m..Suc\ n\} = insert\ (Suc\ n)\ \{m..n\}$
 $\langle proof \rangle$

27.4.7 Image

lemma *image-add-atLeastAtMost*:
 $(\%n::nat.\ n+k) \text{ ‘ } \{i..j\} = \{i+k..j+k\}\ (is\ ?A = ?B)$
 $\langle proof \rangle$

lemma *image-add-atLeastLessThan*:

(%n::nat. n+k) ‘ {i..
 <proof>

corollary *image-Suc-atLeastAtMost[simp]*:

Suc ‘ {i..
 <proof>

corollary *image-Suc-atLeastLessThan[simp]*:

Suc ‘ {i..
 <proof>

lemma *image-add-int-atLeastLessThan*:

(%x. x + (l::int)) ‘ {0..
 <proof>

27.4.8 Finiteness

lemma *finite-lessThan [iff]*: fixes k :: nat shows finite {..
 <proof>

lemma *finite-atMost [iff]*: fixes k :: nat shows finite {..k}
 <proof>

lemma *finite-greaterThanLessThan [iff]*:
 fixes l :: nat shows finite {l<..
 <proof>

lemma *finite-atLeastLessThan [iff]*:
 fixes l :: nat shows finite {l..
 <proof>

lemma *finite-greaterThanAtMost [iff]*:
 fixes l :: nat shows finite {l<..
 <proof>

lemma *finite-atLeastAtMost [iff]*:
 fixes l :: nat shows finite {l..
 <proof>

lemma *bounded-nat-set-is-finite*:

(ALL i:N. i < (n::nat)) ==> finite N
 — A bounded set of natural numbers is finite.
 <proof>

27.4.9 Cardinality

lemma *card-lessThan [simp]*: card {..
 <proof>

lemma *card-atMost* [simp]: $\text{card } \{..u\} = \text{Suc } u$
 ⟨proof⟩

lemma *card-atLeastLessThan* [simp]: $\text{card } \{l..\} = u - l$
 ⟨proof⟩

lemma *card-atLeastAtMost* [simp]: $\text{card } \{l..u\} = \text{Suc } u - l$
 ⟨proof⟩

lemma *card-greaterThanAtMost* [simp]: $\text{card } \{l<..\} = u - l$
 ⟨proof⟩

lemma *card-greaterThanLessThan* [simp]: $\text{card } \{l<..\} = u - \text{Suc } l$
 ⟨proof⟩

27.5 Intervals of integers

lemma *atLeastLessThanPlusOne-atLeastAtMost-int*: $\{l..+1\} = \{l..(u::\text{int})\}$
 ⟨proof⟩

lemma *atLeastPlusOneAtMost-greaterThanAtMost-int*: $\{l+1..u\} = \{l<..\}$
 ⟨proof⟩

lemma *atLeastPlusOneLessThan-greaterThanLessThan-int*:
 $\{l+1..\} = \{l<..\}$
 ⟨proof⟩

27.5.1 Finiteness

lemma *image-atLeastZeroLessThan-int*: $0 \leq u \implies$
 $\{(0::\text{int})..\} = \text{int } \text{‘ } \{..\}$
 ⟨proof⟩

lemma *finite-atLeastZeroLessThan-int*: $\text{finite } \{(0::\text{int})..\}$
 ⟨proof⟩

lemma *finite-atLeastLessThan-int* [iff]: $\text{finite } \{l..\}$
 ⟨proof⟩

lemma *finite-atLeastAtMost-int* [iff]: $\text{finite } \{l..(u::\text{int})\}$
 ⟨proof⟩

lemma *finite-greaterThanAtMost-int* [iff]: $\text{finite } \{l<..\}$
 ⟨proof⟩

lemma *finite-greaterThanLessThan-int* [iff]: $\text{finite } \{l<..\}$
 ⟨proof⟩

27.5.2 Cardinality

lemma *card-atLeastZeroLessThan-int*: $\text{card } \{(0::\text{int})..<u\} = \text{nat } u$
 $\langle \text{proof} \rangle$

lemma *card-atLeastLessThan-int* [simp]: $\text{card } \{l..<u\} = \text{nat } (u - l)$
 $\langle \text{proof} \rangle$

lemma *card-atLeastAtMost-int* [simp]: $\text{card } \{l..u\} = \text{nat } (u - l + 1)$
 $\langle \text{proof} \rangle$

lemma *card-greaterThanAtMost-int* [simp]: $\text{card } \{l<..u\} = \text{nat } (u - l)$
 $\langle \text{proof} \rangle$

lemma *card-greaterThanLessThan-int* [simp]: $\text{card } \{l<..
 $\langle \text{proof} \rangle$$

27.6 Lemmas useful with the summation operator setsum

For examples, see Algebra/poly/UnivPoly2.thy

27.6.1 Disjoint Unions

Singletons and open intervals

lemma *ivl-disj-un-singleton*:
 $\{l::'a::\text{linorder}\} \text{ Un } \{l<..\} = \{l..\}$
 $\{..
 $(l::'a::\text{linorder}) < u \implies \{l\} \text{ Un } \{l<..
 $(l::'a::\text{linorder}) < u \implies \{l<..
 $(l::'a::\text{linorder}) \leq u \implies \{l\} \text{ Un } \{l<..u\} = \{l..u\}$
 $(l::'a::\text{linorder}) \leq u \implies \{l..
 $\langle \text{proof} \rangle$$$$$

One- and two-sided intervals

lemma *ivl-disj-un-one*:
 $(l::'a::\text{linorder}) < u \implies \{..l\} \text{ Un } \{l<..
 $(l::'a::\text{linorder}) \leq u \implies \{..
 $(l::'a::\text{linorder}) \leq u \implies \{..l\} \text{ Un } \{l<..u\} = \{..u\}$
 $(l::'a::\text{linorder}) \leq u \implies \{..
 $(l::'a::\text{linorder}) \leq u \implies \{l<..u\} \text{ Un } \{u<..\} = \{l<..\}$
 $(l::'a::\text{linorder}) < u \implies \{l<..
 $(l::'a::\text{linorder}) \leq u \implies \{l..u\} \text{ Un } \{u<..\} = \{l..\}$
 $(l::'a::\text{linorder}) \leq u \implies \{l..
 $\langle \text{proof} \rangle$$$$$$

Two- and two-sided intervals

lemma *ivl-disj-un-two*:
 $[(l::'a::\text{linorder}) < m; m \leq u] \implies \{l<..$

$$\begin{aligned}
& \llbracket (l::'a::\text{linorder}) \leq m; m < u \rrbracket \implies \{l <..m\} \text{ Un } \{m <..\} = \{l <..\} \\
& \llbracket (l::'a::\text{linorder}) \leq m; m \leq u \rrbracket \implies \{l <..m\} \text{ Un } \{m <..\} = \{l <..\} \\
& \llbracket (l::'a::\text{linorder}) \leq m; m < u \rrbracket \implies \{l..m\} \text{ Un } \{m <..\} = \{l <..\} \\
& \llbracket (l::'a::\text{linorder}) < m; m \leq u \rrbracket \implies \{l <..\} \\
& \llbracket (l::'a::\text{linorder}) \leq m; m \leq u \rrbracket \implies \{l <..\} = \{l <..\} \\
& \llbracket (l::'a::\text{linorder}) \leq m; m \leq u \rrbracket \implies \{l..m\} \text{ Un } \{m..u\} = \{l..u\} \\
& \llbracket (l::'a::\text{linorder}) < m; m \leq u \rrbracket \implies \{l..m\} \text{ Un } \{m <..\} = \{l..u\}
\end{aligned}$$

<proof>

lemmas *ivl-disj-un* = *ivl-disj-un-singleton* *ivl-disj-un-one* *ivl-disj-un-two*

27.6.2 Disjoint Intersections

Singletons and open intervals

lemma *ivl-disj-int-singleton*:

$$\begin{aligned}
& \{l::'a::\text{order}\} \text{ Int } \{l <..\} = \{\} \\
& \{.. < u\} \text{ Int } \{u\} = \{\} \\
& \{l\} \text{ Int } \{l <..\} = \{\} \\
& \{l <..\} \text{ Int } \{u\} = \{\} \\
& \{l\} \text{ Int } \{l <..\} = \{\} \\
& \{l.. < u\} \text{ Int } \{u\} = \{\}
\end{aligned}$$

<proof>

One- and two-sided intervals

lemma *ivl-disj-int-one*:

$$\begin{aligned}
& \{..l::'a::\text{order}\} \text{ Int } \{l <..\} = \{\} \\
& \{.. < l\} \text{ Int } \{l.. < u\} = \{\} \\
& \{..l\} \text{ Int } \{l <..\} = \{\} \\
& \{.. < l\} \text{ Int } \{l..u\} = \{\} \\
& \{l <..\} \text{ Int } \{u <..\} = \{\} \\
& \{l <..\} \text{ Int } \{u.. \} = \{\} \\
& \{l..u\} \text{ Int } \{u <..\} = \{\} \\
& \{l.. < u\} \text{ Int } \{u.. \} = \{\}
\end{aligned}$$

<proof>

Two- and two-sided intervals

lemma *ivl-disj-int-two*:

$$\begin{aligned}
& \{l::'a::\text{order} <..\} = \{\} \\
& \{l.. < m\} \text{ Int } \{m.. < u\} = \{\} \\
& \{l..m\} \text{ Int } \{m <..\} = \{\} \\
& \{l <..\} = \{\} \\
& \{l.. < m\} \text{ Int } \{m..u\} = \{\} \\
& \{l..m\} \text{ Int } \{m <..\} = \{\}
\end{aligned}$$

<proof>

lemmas *ivl-disj-int* = *ivl-disj-int-singleton* *ivl-disj-int-one* *ivl-disj-int-two*

lemma *ivl-diff[simp]*:
 $i \leq n \implies \{i..<m\} - \{i..<n\} = \{n..<(m::'a::linorder)\}$
<proof>

lemma *ivl-subset[simp]*:
 $(\{i..<j\} \subseteq \{m..<n\}) = (j \leq i \mid m \leq i \ \& \ j \leq (n::'a::linorder))$
<proof>

syntax

- from-to-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((SUM - = \dots / -) [0,0,0,10] \ 10)$
- from-upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((SUM - = \dots < / -) [0,0,0,10] \ 10)$
- upt-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((SUM - < / -) [0,0,10] \ 10)$
- upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((SUM - <= / -) [0,0,10] \ 10)$

syntax (*xsymbols*)

- from-to-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - = \dots / -) [0,0,0,10] \ 10)$
- from-upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - = \dots < / -) [0,0,0,10] \ 10)$
- upt-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - < / -) [0,0,10] \ 10)$
- upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - <= / -) [0,0,10] \ 10)$

syntax (*HTML output*)

- from-to-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - = \dots / -) [0,0,0,10] \ 10)$
- from-upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - = \dots < / -) [0,0,0,10] \ 10)$
- upt-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - < / -) [0,0,10] \ 10)$
- upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b \ ((\mathcal{S}\Sigma - <= / -) [0,0,10] \ 10)$

syntax (*latex-sum output*)

- from-to-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b$
 $((\mathcal{S}\Sigma^- = - -) [0,0,0,10] \ 10)$
- from-upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b$
 $((\mathcal{S}\Sigma^{<-} = - -) [0,0,0,10] \ 10)$
- upt-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b$
 $((\mathcal{S}\Sigma_- < - -) [0,0,10] \ 10)$
- upto-setsum :: $idt \Rightarrow 'a \Rightarrow 'b \Rightarrow 'b$
 $((\mathcal{S}\Sigma_- <= - -) [0,0,10] \ 10)$

$$\begin{aligned} \sum x=a..b. t &== \text{setsum } (\%x. t) \{a..b\} \\ \sum x=a..$$

The above introduces some pretty alternative syntaxes for summation over intervals:

Old	New	L ^A T _E X
$\sum_{x \in \{a..b\}}. e$	$\sum x = a..b. e$	$\sum_{x=a}^b e$
$\sum_{x \in \{a..<b\}}. e$	$\sum x = a..<b. e$	$\sum_{x=a}^{<b} e$
$\sum_{x \in \{..b\}}. e$	$\sum x \leq b. e$	$\sum_{x \leq b} e$
$\sum_{x \in \{..<b\}}. e$	$\sum x < b. e$	$\sum_{x < b} e$

The left column shows the term before introduction of the new syntax, the middle column shows the new (default) syntax, and the right column shows a special syntax. The latter is only meaningful for latex output and has to be activated explicitly by setting the print mode to `latex_sum` (e.g. via `mode=latex_sum` in antiquotations). It is not the default L^AT_EX output because it only works well with italic-style formulae, not tt-style.

Note that for uniformity on *nat* it is better to use $\sum x = 0..<n. e$ rather than $\sum x < n. e$: *setsum* may not provide all lemmas available for $\{m..<n\}$ also in the special form for $\{..<n\}$.

This congruence rule should be used for sums over intervals as the standard theorem *setsum-cong* does not work well with the simplifier who adds the unsimplified premise $x \in B$ to the context.

lemma *setsum-ivl-cong*:

$\llbracket a = c; b = d; !!x. \llbracket c \leq x; x < d \rrbracket \implies f x = g x \rrbracket \implies$
 $\text{setsum } f \{a..<b\} = \text{setsum } g \{c..<d\}$
 $\langle \text{proof} \rangle$

lemma *setsum-atMost-Suc[simp]*: $(\sum i \leq \text{Suc } n. f i) = (\sum i \leq n. f i) + f(\text{Suc } n)$
 $\langle \text{proof} \rangle$

lemma *setsum-lessThan-Suc[simp]*: $(\sum i < \text{Suc } n. f i) = (\sum i < n. f i) + f n$
 $\langle \text{proof} \rangle$

lemma *setsum-cl-ivl-Suc[simp]*:

$\text{setsum } f \{m.. \text{Suc } n\} = (\text{if } \text{Suc } n < m \text{ then } 0 \text{ else } \text{setsum } f \{m..n\} + f(\text{Suc } n))$
 $\langle \text{proof} \rangle$

lemma *setsum-op-ivl-Suc[simp]*:

$\text{setsum } f \{m..<\text{Suc } n\} = (\text{if } n < m \text{ then } 0 \text{ else } \text{setsum } f \{m..<n\} + f(n))$
 $\langle \text{proof} \rangle$

lemma *setsum-add-nat-ivl*: $\llbracket m \leq n; n \leq p \rrbracket \implies$

$\text{setsum } f \{m..<n\} + \text{setsum } f \{n..<p\} = \text{setsum } f \{m..<p::\text{nat}\}$
 $\langle \text{proof} \rangle$

lemma *setsum-diff-nat-ivl*:

fixes $f :: \text{nat} \Rightarrow 'a::\text{ab-group-add}$

shows $\llbracket m \leq n; n \leq p \rrbracket \implies$

$setsum\ f\ \{m..<p\} - setsum\ f\ \{m..<n\} = setsum\ f\ \{n..<p\}$
 $\langle proof \rangle$

27.8 Shifting bounds

lemma *setsum-shift-bounds-nat-ivl*:

$setsum\ f\ \{m+k..<n+k\} = setsum\ (\%i.\ f(i + k))\{m..<n::nat\}$
 $\langle proof \rangle$

lemma *setsum-shift-bounds-cl-nat-ivl*:

$setsum\ f\ \{m+k..n+k\} = setsum\ (\%i.\ f(i + k))\{m..n::nat\}$
 $\langle proof \rangle$

corollary *setsum-shift-bounds-cl-Suc-ivl*:

$setsum\ f\ \{Suc\ m..Suc\ n\} = setsum\ (\%i.\ f(Suc\ i))\{m..n\}$
 $\langle proof \rangle$

corollary *setsum-shift-bounds-Suc-ivl*:

$setsum\ f\ \{Suc\ m..<Suc\ n\} = setsum\ (\%i.\ f(Suc\ i))\{m..<n\}$
 $\langle proof \rangle$

27.9 The formula for geometric sums

lemma *geometric-sum*:

$x \sim 1 ==> (\sum\ i=0..<n.\ x \wedge i) =$
 $(x \wedge n - 1) / (x - 1::'a::\{field, recpower, division-by-zero\})$
 $\langle proof \rangle$

$\langle ML \rangle$

end

28 Recdef: TFL: recursive function definitions

theory *Recdef*

imports *Wellfounded-Relations Datatype*

uses

(../TFL/casesplit.ML)
 (../TFL/utis.ML)
 (../TFL/usyntax.ML)
 (../TFL/dcterm.ML)
 (../TFL/thms.ML)
 (../TFL/rules.ML)
 (../TFL/thry.ML)
 (../TFL/tfl.ML)
 (../TFL/post.ML)

(*Tools/recdef-package.ML*)
begin

lemma *tfl-eq-True*: $(x = \text{True}) \dashrightarrow x$
<proof>

lemma *tfl-rev-eq-mp*: $(x = y) \dashrightarrow y \dashrightarrow x$
<proof>

lemma *tfl-simp-thm*: $(x \dashrightarrow y) \dashrightarrow (x = x') \dashrightarrow (x' \dashrightarrow y)$
<proof>

lemma *tfl-P-imp-P-iff-True*: $P \implies P = \text{True}$
<proof>

lemma *tfl-imp-trans*: $(A \dashrightarrow B) \implies (B \dashrightarrow C) \implies (A \dashrightarrow C)$
<proof>

lemma *tfl-disj-assoc*: $(a \vee b) \vee c == a \vee (b \vee c)$
<proof>

lemma *tfl-disjE*: $P \vee Q \implies P \dashrightarrow R \implies Q \dashrightarrow R \implies R$
<proof>

lemma *tfl-exE*: $\exists x. P x \implies \forall x. P x \dashrightarrow Q \implies Q$
<proof>

<ML>

lemmas [*recdef-simp*] =
inv-image-def
measure-def
lex-prod-def
same-fst-def
less-Suc-eq [*THEN iffD2*]

lemmas [*recdef-cong*] = *if-cong image-cong*

lemma *let-cong* [*recdef-cong*]:
 $M = N \implies (!x. x = N \implies f x = g x) \implies \text{Let } M f = \text{Let } N g$
<proof>

lemmas [*recdef-wf*] =
wf-trancl
wf-less-than
wf-lex-prod
wf-inv-image
wf-measure
wf-pred-nat

wf-same-fst
wf-empty

lemma *insert-None-conv-UNIV*: *insert None (range Some) = UNIV*
 ⟨*proof*⟩

instance *option* :: (*finite*) *finite*
 ⟨*proof*⟩

end

29 IntDiv: The Division Operators div and mod; the Divides Relation dvd

theory *IntDiv*
imports *SetInterval Recdef*
uses (*IntDiv-setup.ML*)
begin

declare *zless-nat-conj* [*simp*]

constdefs

*quo**rem* :: (*int***int*) * (*int***int*) => *bool*
 — definition of quotient and remainder
*quo**rem* == %((*a*,*b*), (*q*,*r*)).
 a = *b***q* + *r* &
 (*if* 0 < *b* then 0 ≤ *r* & *r* < *b* else *b* < *r* & *r* ≤ 0)

adjust :: [*int*, *int***int*] => *int***int*
 — for the division algorithm
adjust *b* == %(*q*,*r*). *if* 0 ≤ *r* − *b* then (2**q* + 1, *r* − *b*)
 else (2**q*, *r*)

algorithm for the case $a \geq 0, b > 0$

consts *posDivAlg* :: *int***int* => *int***int*
recdef *posDivAlg* *measure* (%(*a*,*b*). *nat*(*a* − *b* + 1))
 posDivAlg (*a*,*b*) =
 (*if* (*a* < *b* | *b* ≤ 0) then (0, *a*)
 else *adjust* *b* (*posDivAlg*(*a*, 2**b*)))

algorithm for the case $a < 0, b > 0$

consts *negDivAlg* :: *int***int* => *int***int*
recdef *negDivAlg* *measure* (%(*a*,*b*). *nat*(− *a* − *b*))
 negDivAlg (*a*,*b*) =
 (*if* (0 ≤ *a* + *b* | *b* ≤ 0) then (−1, *a* + *b*)

*else adjust b (negDivAlg(a, 2*b))*

algorithm for the general case $b \neq (0::'a)$

constdefs

negateSnd :: *int*int* => *int*int*
negateSnd == $\%(q,r). (q,-r)$

divAlg :: *int*int* => *int*int*

— The full division algorithm considers all possible signs for a, b including the special case $a=0, b<0$ because *negDivAlg* requires $a < (0::'a)$.

divAlg ==
 $\%(a,b). \text{ if } 0 \leq a \text{ then}$
 $\text{ if } 0 \leq b \text{ then } \text{posDivAlg } (a,b)$
 $\text{ else if } a=0 \text{ then } (0,0)$
 $\text{ else } \text{negateSnd } (\text{negDivAlg } (-a,-b))$
 else
 $\text{ if } 0 < b \text{ then } \text{negDivAlg } (a,b)$
 $\text{ else } \text{negateSnd } (\text{posDivAlg } (-a,-b))$

instance

int :: *Divides.div* <proof>

The operators are defined with reference to the algorithm, which is proved to satisfy the specification.

defs

div-def: $a \text{ div } b == \text{fst } (\text{divAlg } (a,b))$
mod-def: $a \text{ mod } b == \text{snd } (\text{divAlg } (a,b))$

Here is the division algorithm in ML:

```
fun posDivAlg (a,b) =
  if a<b then (0,a)
  else let val (q,r) = posDivAlg(a, 2*b)
        in if 0<le>r-b then (2*q+1, r-b) else (2*q, r)
        end

fun negDivAlg (a,b) =
  if 0<le>a+b then (~1,a+b)
  else let val (q,r) = negDivAlg(a, 2*b)
        in if 0<le>r-b then (2*q+1, r-b) else (2*q, r)
        end;

fun negateSnd (q,r:int) = (q,~r);

fun divAlg (a,b) = if 0<le>a then
  if b>0 then posDivAlg (a,b)
  else if a=0 then (0,0)
```

```

else negateSnd (negDivAlg (~a,~b))
else
  if 0<b then negDivAlg (a,b)
  else      negateSnd (posDivAlg (~a,~b));

```

29.1 Uniqueness and Monotonicity of Quotients and Remainders

lemma *unique-quotient-lemma*:

```

[[ b*q' + r' ≤ b*q + r; 0 ≤ r'; r' < b; r < b ]]
==> q' ≤ (q::int)
⟨proof⟩

```

lemma *unique-quotient-lemma-neg*:

```

[[ b*q' + r' ≤ b*q + r; r ≤ 0; b < r; b < r' ]]
==> q ≤ (q'::int)
⟨proof⟩

```

lemma *unique-quotient*:

```

[[ quorem ((a,b), (q,r)); quorem ((a,b), (q',r')); b ≠ 0 ]]
==> q = q'
⟨proof⟩

```

lemma *unique-remainder*:

```

[[ quorem ((a,b), (q,r)); quorem ((a,b), (q',r')); b ≠ 0 ]]
==> r = r'
⟨proof⟩

```

29.2 Correctness of *posDivAlg*, the Algorithm for Non-Negative Dividends

And positive divisors

lemma *adjust-eq* [simp]:

```

adjust b (q,r) =
  (let diff = r-b in
   if 0 ≤ diff then (2*q + 1, diff)
   else (2*q, r))
⟨proof⟩

```

declare *posDivAlg.simps* [simp del]

use with a simproc to avoid repeatedly proving the premise

lemma *posDivAlg-eqn*:

```

0 < b ==>
  posDivAlg (a,b) = (if a<b then (0,a) else adjust b (posDivAlg(a, 2*b)))
⟨proof⟩

```

Correctness of *posDivAlg*: it computes quotients correctly

theorem *posDivAlg-correct* [rule-format]:

$0 \leq a \dashv\dashv 0 < b \dashv\dashv \text{quorem } ((a, b), \text{posDivAlg } (a, b))$
 $\langle \text{proof} \rangle$

29.3 Correctness of *negDivAlg*, the Algorithm for Negative Dividends

And positive divisors

declare *negDivAlg.simps* [simp del]

use with a simproc to avoid repeatedly proving the premise

lemma *negDivAlg-eqn*:

$0 < b \implies$
 $\text{negDivAlg } (a, b) =$
 $(\text{if } 0 \leq a + b \text{ then } (-1, a + b) \text{ else adjust } b (\text{negDivAlg}(a, 2 * b)))$
 $\langle \text{proof} \rangle$

lemma *negDivAlg-correct* [rule-format]:

$a < 0 \dashv\dashv 0 < b \dashv\dashv \text{quorem } ((a, b), \text{negDivAlg } (a, b))$
 $\langle \text{proof} \rangle$

29.4 Existence Shown by Proving the Division Algorithm to be Correct

lemma *quorem-0*: $b \neq 0 \implies \text{quorem } ((0, b), (0, 0))$

$\langle \text{proof} \rangle$

lemma *posDivAlg-0* [simp]: $\text{posDivAlg } (0, b) = (0, 0)$

$\langle \text{proof} \rangle$

lemma *negDivAlg-minus1* [simp]: $\text{negDivAlg } (-1, b) = (-1, b - 1)$

$\langle \text{proof} \rangle$

lemma *negateSnd-eq* [simp]: $\text{negateSnd}(q, r) = (q, -r)$

$\langle \text{proof} \rangle$

lemma *quorem-neg*: $\text{quorem } ((-a, -b), qr) \implies \text{quorem } ((a, b), \text{negateSnd } qr)$

$\langle \text{proof} \rangle$

lemma *divAlg-correct*: $b \neq 0 \implies \text{quorem } ((a, b), \text{divAlg}(a, b))$

$\langle \text{proof} \rangle$

Arbitrary definitions for division by zero. Useful to simplify certain equations.

lemma *DIVISION-BY-ZERO* [simp]: $a \text{ div } (0::\text{int}) = 0 \ \& \ a \text{ mod } (0::\text{int}) = a$

$\langle proof \rangle$

Basic laws about division and remainder

lemma *zmod-zdiv-equality*: $(a::int) = b * (a \text{ div } b) + (a \text{ mod } b)$
 $\langle proof \rangle$

lemma *zdiv-zmod-equality*: $(b * (a \text{ div } b) + (a \text{ mod } b)) + k = (a::int)+k$
 $\langle proof \rangle$

lemma *zdiv-zmod-equality2*: $((a \text{ div } b) * b + (a \text{ mod } b)) + k = (a::int)+k$
 $\langle proof \rangle$

$\langle ML \rangle$

lemma *pos-mod-conj* : $(0::int) < b ==> 0 \leq a \text{ mod } b \ \& \ a \text{ mod } b < b$
 $\langle proof \rangle$

lemmas *pos-mod-sign[simp]* = *pos-mod-conj* [THEN conjunct1, standard]
and *pos-mod-bound[simp]* = *pos-mod-conj* [THEN conjunct2, standard]

lemma *neg-mod-conj* : $b < (0::int) ==> a \text{ mod } b \leq 0 \ \& \ b < a \text{ mod } b$
 $\langle proof \rangle$

lemmas *neg-mod-sign[simp]* = *neg-mod-conj* [THEN conjunct1, standard]
and *neg-mod-bound[simp]* = *neg-mod-conj* [THEN conjunct2, standard]

29.5 General Properties of div and mod

lemma *quorem-div-mod*: $b \neq 0 ==> \text{quorem}((a, b), (a \text{ div } b, a \text{ mod } b))$
 $\langle proof \rangle$

lemma *quorem-div*: $[\text{quorem}((a,b),(q,r)); \ b \neq 0] ==> a \text{ div } b = q$
 $\langle proof \rangle$

lemma *quorem-mod*: $[\text{quorem}((a,b),(q,r)); \ b \neq 0] ==> a \text{ mod } b = r$
 $\langle proof \rangle$

lemma *div-pos-pos-trivial*: $[(0::int) \leq a; \ a < b] ==> a \text{ div } b = 0$
 $\langle proof \rangle$

lemma *div-neg-neg-trivial*: $[a \leq (0::int); \ b < a] ==> a \text{ div } b = 0$
 $\langle proof \rangle$

lemma *div-pos-neg-trivial*: $[(0::int) < a; \ a+b \leq 0] ==> a \text{ div } b = -1$
 $\langle proof \rangle$

lemma *mod-pos-pos-trivial*: $[(0::int) \leq a; \ a < b] ==> a \text{ mod } b = a$

$\langle proof \rangle$

lemma *mod-neg-neg-trivial*: $[| a \leq (0::int); b < a |] ==> a \bmod b = a$
 $\langle proof \rangle$

lemma *mod-pos-neg-trivial*: $[| (0::int) < a; a+b \leq 0 |] ==> a \bmod b = a+b$
 $\langle proof \rangle$

There is no *mod-neg-pos-trivial*.

lemma *zdiv-zminus-zminus* [simp]: $(-a) \operatorname{div} (-b) = a \operatorname{div} (b::int)$
 $\langle proof \rangle$

lemma *zmod-zminus-zminus* [simp]: $(-a) \bmod (-b) = - (a \bmod (b::int))$
 $\langle proof \rangle$

29.6 Laws for div and mod with Unary Minus

lemma *zminus1-lemma*:
 $\operatorname{quorem}((a,b),(q,r))$
 $==> \operatorname{quorem}((-a,b), (\text{if } r=0 \text{ then } -q \text{ else } -q - 1),$
 $(\text{if } r=0 \text{ then } 0 \text{ else } b-r))$
 $\langle proof \rangle$

lemma *zdiv-zminus1-eq-if*:
 $b \neq (0::int)$
 $==> (-a) \operatorname{div} b =$
 $(\text{if } a \bmod b = 0 \text{ then } - (a \operatorname{div} b) \text{ else } - (a \operatorname{div} b) - 1)$
 $\langle proof \rangle$

lemma *zmod-zminus1-eq-if*:
 $(-a::int) \bmod b = (\text{if } a \bmod b = 0 \text{ then } 0 \text{ else } b - (a \bmod b))$
 $\langle proof \rangle$

lemma *zdiv-zminus2*: $a \operatorname{div} (-b) = (-a::int) \operatorname{div} b$
 $\langle proof \rangle$

lemma *zmod-zminus2*: $a \bmod (-b) = - ((-a::int) \bmod b)$
 $\langle proof \rangle$

lemma *zdiv-zminus2-eq-if*:
 $b \neq (0::int)$
 $==> a \operatorname{div} (-b) =$
 $(\text{if } a \bmod b = 0 \text{ then } - (a \operatorname{div} b) \text{ else } - (a \operatorname{div} b) - 1)$
 $\langle proof \rangle$

lemma *zmod-zminus2-eq-if*:
 $a \bmod (-b::int) = (\text{if } a \bmod b = 0 \text{ then } 0 \text{ else } (a \bmod b) - b)$

$\langle proof \rangle$

29.7 Division of a Number by Itself

lemma *self-quotient-aux1*: $\llbracket (0::int) < a; a = r + a*q; r < a \rrbracket \implies 1 \leq q$
 $\langle proof \rangle$

lemma *self-quotient-aux2*: $\llbracket (0::int) < a; a = r + a*q; 0 \leq r \rrbracket \implies q \leq 1$
 $\langle proof \rangle$

lemma *self-quotient*: $\llbracket quorem((a,a),(q,r)); a \neq (0::int) \rrbracket \implies q = 1$
 $\langle proof \rangle$

lemma *self-remainder*: $\llbracket quorem((a,a),(q,r)); a \neq (0::int) \rrbracket \implies r = 0$
 $\langle proof \rangle$

lemma *zdiv-self* [simp]: $a \neq 0 \implies a \text{ div } a = (1::int)$
 $\langle proof \rangle$

lemma *zmod-self* [simp]: $a \text{ mod } a = (0::int)$
 $\langle proof \rangle$

29.8 Computation of Division and Remainder

lemma *zdiv-zero* [simp]: $(0::int) \text{ div } b = 0$
 $\langle proof \rangle$

lemma *div-eq-minus1*: $(0::int) < b \implies -1 \text{ div } b = -1$
 $\langle proof \rangle$

lemma *zmod-zero* [simp]: $(0::int) \text{ mod } b = 0$
 $\langle proof \rangle$

lemma *zdiv-minus1*: $(0::int) < b \implies -1 \text{ div } b = -1$
 $\langle proof \rangle$

lemma *zmod-minus1*: $(0::int) < b \implies -1 \text{ mod } b = b - 1$
 $\langle proof \rangle$

a positive, b positive

lemma *div-pos-pos*: $\llbracket 0 < a; 0 \leq b \rrbracket \implies a \text{ div } b = fst (posDivAlg(a,b))$
 $\langle proof \rangle$

lemma *mod-pos-pos*: $\llbracket 0 < a; 0 \leq b \rrbracket \implies a \text{ mod } b = snd (posDivAlg(a,b))$
 $\langle proof \rangle$

a negative, b positive

lemma *div-neg-pos*: $\llbracket a < 0; 0 < b \rrbracket \implies a \text{ div } b = fst (negDivAlg(a,b))$

<proof>

lemma *mod-neg-pos*: $[[a < 0; 0 < b]] \implies a \text{ mod } b = \text{snd } (\text{negDivAlg}(a, b))$
<proof>

a positive, b negative

lemma *div-pos-neg*:
 $[[0 < a; b < 0]] \implies a \text{ div } b = \text{fst } (\text{negateSnd}(\text{negDivAlg}(-a, -b)))$
<proof>

lemma *mod-pos-neg*:
 $[[0 < a; b < 0]] \implies a \text{ mod } b = \text{snd } (\text{negateSnd}(\text{negDivAlg}(-a, -b)))$
<proof>

a negative, b negative

lemma *div-neg-neg*:
 $[[a < 0; b \leq 0]] \implies a \text{ div } b = \text{fst } (\text{negateSnd}(\text{posDivAlg}(-a, -b)))$
<proof>

lemma *mod-neg-neg*:
 $[[a < 0; b \leq 0]] \implies a \text{ mod } b = \text{snd } (\text{negateSnd}(\text{posDivAlg}(-a, -b)))$
<proof>

Simplify expresions in which div and mod combine numerical constants

lemmas *div-pos-pos-number-of* =
 $\text{div-pos-pos } [\text{of number-of } v \text{ number-of } w, \text{ standard}]$
declare *div-pos-pos-number-of* [simp]

lemmas *div-neg-pos-number-of* =
 $\text{div-neg-pos } [\text{of number-of } v \text{ number-of } w, \text{ standard}]$
declare *div-neg-pos-number-of* [simp]

lemmas *div-pos-neg-number-of* =
 $\text{div-pos-neg } [\text{of number-of } v \text{ number-of } w, \text{ standard}]$
declare *div-pos-neg-number-of* [simp]

lemmas *div-neg-neg-number-of* =
 $\text{div-neg-neg } [\text{of number-of } v \text{ number-of } w, \text{ standard}]$
declare *div-neg-neg-number-of* [simp]

lemmas *mod-pos-pos-number-of* =
 $\text{mod-pos-pos } [\text{of number-of } v \text{ number-of } w, \text{ standard}]$
declare *mod-pos-pos-number-of* [simp]

lemmas *mod-neg-pos-number-of* =
 $\text{mod-neg-pos } [\text{of number-of } v \text{ number-of } w, \text{ standard}]$
declare *mod-neg-pos-number-of* [simp]

lemmas *mod-pos-neg-number-of* =
 mod-pos-neg [of number-of *v* number-of *w*, standard]
declare *mod-pos-neg-number-of* [simp]

lemmas *mod-neg-neg-number-of* =
 mod-neg-neg [of number-of *v* number-of *w*, standard]
declare *mod-neg-neg-number-of* [simp]

lemmas *posDivAlg-eqn-number-of* =
 posDivAlg-eqn [of number-of *v* number-of *w*, standard]
declare *posDivAlg-eqn-number-of* [simp]

lemmas *negDivAlg-eqn-number-of* =
 negDivAlg-eqn [of number-of *v* number-of *w*, standard]
declare *negDivAlg-eqn-number-of* [simp]

Special-case simplification

lemma *zmod-1* [simp]: $a \bmod (1::\text{int}) = 0$
 ⟨proof⟩

lemma *zdiv-1* [simp]: $a \operatorname{div} (1::\text{int}) = a$
 ⟨proof⟩

lemma *zmod-minus1-right* [simp]: $a \bmod (-1::\text{int}) = 0$
 ⟨proof⟩

lemma *zdiv-minus1-right* [simp]: $a \operatorname{div} (-1::\text{int}) = -a$
 ⟨proof⟩

lemmas *div-pos-pos-1-number-of* =
 div-pos-pos [OF *int-0-less-1*, of number-of *w*, standard]
declare *div-pos-pos-1-number-of* [simp]

lemmas *div-pos-neg-1-number-of* =
 div-pos-neg [OF *int-0-less-1*, of number-of *w*, standard]
declare *div-pos-neg-1-number-of* [simp]

lemmas *mod-pos-pos-1-number-of* =
 mod-pos-pos [OF *int-0-less-1*, of number-of *w*, standard]
declare *mod-pos-pos-1-number-of* [simp]

lemmas *mod-pos-neg-1-number-of* =
 mod-pos-neg [OF *int-0-less-1*, of number-of *w*, standard]
declare *mod-pos-neg-1-number-of* [simp]

lemmas *posDivAlg-eqn-1-number-of* =
 posDivAlg-eqn [of **concl**: 1 number-of *w*, standard]
declare *posDivAlg-eqn-1-number-of* [simp]

lemmas *negDivAlg-eqn-1-number-of* =
 negDivAlg-eqn [of **concl**: 1 number-of *w*, standard]
declare *negDivAlg-eqn-1-number-of* [simp]

29.9 Monotonicity in the First Argument (Dividend)

lemma *zdiv-mono1*: $[[a \leq a'; \ 0 < (b::int)]] \implies a \text{ div } b \leq a' \text{ div } b$
 <proof>

lemma *zdiv-mono1-neg*: $[[a \leq a'; \ (b::int) < 0]] \implies a' \text{ div } b \leq a \text{ div } b$
 <proof>

29.10 Monotonicity in the Second Argument (Divisor)

lemma *q-pos-lemma*:
 $[[0 \leq b' * q' + r'; \ r' < b'; \ 0 < b']] \implies 0 \leq (q'::int)$
 <proof>

lemma *zdiv-mono2-lemma*:
 $[[b * q + r = b' * q' + r'; \ 0 \leq b' * q' + r';$
 $\quad r' < b'; \ 0 \leq r; \ 0 < b'; \ b' \leq b]]$
 $\implies q \leq (q'::int)$
 <proof>

lemma *zdiv-mono2*:
 $[[(0::int) \leq a; \ 0 < b'; \ b' \leq b]] \implies a \text{ div } b \leq a \text{ div } b'$
 <proof>

lemma *q-neg-lemma*:
 $[[b' * q' + r' < 0; \ 0 \leq r'; \ 0 < b']] \implies q' \leq (0::int)$
 <proof>

lemma *zdiv-mono2-neg-lemma*:
 $[[b * q + r = b' * q' + r'; \ b' * q' + r' < 0;$
 $\quad r < b; \ 0 \leq r'; \ 0 < b'; \ b' \leq b]]$
 $\implies q' \leq (q::int)$
 <proof>

lemma *zdiv-mono2-neg*:
 $[[a < (0::int); \ 0 < b'; \ b' \leq b]] \implies a \text{ div } b' \leq a \text{ div } b$
 <proof>

29.11 More Algebraic Laws for div and mod

proving $(a * b) \text{ div } c = a * (b \text{ div } c) + a * (b \text{ mod } c)$

lemma *zmult1-lemma*:

$$[| \text{quorem}((b,c),(q,r)); \ c \neq 0 \ |]$$

$$\implies \text{quorem}((a*b, c), (a*q + a*r \text{ div } c, a*r \text{ mod } c))$$

$$\langle \text{proof} \rangle$$

lemma *zdiv-zmult1-eq*: $(a*b) \text{ div } c = a*(b \text{ div } c) + a*(b \text{ mod } c) \text{ div } (c::int)$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult1-eq*: $(a*b) \text{ mod } c = a*(b \text{ mod } c) \text{ mod } (c::int)$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult1-eq'*: $(a*b) \text{ mod } (c::int) = ((a \text{ mod } c) * b) \text{ mod } c$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult-distrib*: $(a*b) \text{ mod } (c::int) = ((a \text{ mod } c) * (b \text{ mod } c)) \text{ mod } c$
 $\langle \text{proof} \rangle$

lemma *zdiv-zmult-self1* [simp]: $b \neq (0::int) \implies (a*b) \text{ div } b = a$
 $\langle \text{proof} \rangle$

lemma *zdiv-zmult-self2* [simp]: $b \neq (0::int) \implies (b*a) \text{ div } b = a$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult-self1* [simp]: $(a*b) \text{ mod } b = (0::int)$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult-self2* [simp]: $(b*a) \text{ mod } b = (0::int)$
 $\langle \text{proof} \rangle$

lemma *zmod-eq-0-iff*: $(m \text{ mod } d = 0) = (EX \ q::int. m = d*q)$
 $\langle \text{proof} \rangle$

lemmas *zmod-eq-0D* = *zmod-eq-0-iff* [THEN iffD1]
declare *zmod-eq-0D* [dest!]

proving $(a+b) \text{ div } c = a \text{ div } c + b \text{ div } c + ((a \text{ mod } c + b \text{ mod } c) \text{ div } c)$

lemma *zadd1-lemma*:

$$[| \text{quorem}((a,c),(aq,ar)); \ \text{quorem}((b,c),(bq,br)); \ c \neq 0 \ |]$$

$$\implies \text{quorem}((a+b, c), (aq + bq + (ar+br) \text{ div } c, (ar+br) \text{ mod } c))$$

$$\langle \text{proof} \rangle$$

lemma *zdiv-zadd1-eq*:

$$(a+b) \text{ div } (c::int) = a \text{ div } c + b \text{ div } c + ((a \text{ mod } c + b \text{ mod } c) \text{ div } c)$$

$$\langle \text{proof} \rangle$$

lemma *zmod-zadd1-eq*: $(a+b) \text{ mod } (c::int) = (a \text{ mod } c + b \text{ mod } c) \text{ mod } c$
 $\langle \text{proof} \rangle$

lemma *mod-div-trivial* [simp]: $(a \bmod b) \operatorname{div} b = (0::\text{int})$
 ⟨proof⟩

lemma *mod-mod-trivial* [simp]: $(a \bmod b) \bmod b = a \bmod (b::\text{int})$
 ⟨proof⟩

lemma *zmod-zadd-left-eq*: $(a+b) \bmod (c::\text{int}) = ((a \bmod c) + b) \bmod c$
 ⟨proof⟩

lemma *zmod-zadd-right-eq*: $(a+b) \bmod (c::\text{int}) = (a + (b \bmod c)) \bmod c$
 ⟨proof⟩

lemma *zdiv-zadd-self1* [simp]: $a \neq (0::\text{int}) \implies (a+b) \operatorname{div} a = b \operatorname{div} a + 1$
 ⟨proof⟩

lemma *zdiv-zadd-self2* [simp]: $a \neq (0::\text{int}) \implies (b+a) \operatorname{div} a = b \operatorname{div} a + 1$
 ⟨proof⟩

lemma *zmod-zadd-self1* [simp]: $(a+b) \bmod a = b \bmod (a::\text{int})$
 ⟨proof⟩

lemma *zmod-zadd-self2* [simp]: $(b+a) \bmod a = b \bmod (a::\text{int})$
 ⟨proof⟩

29.12 Proving $a \operatorname{div} (b * c) = a \operatorname{div} b \operatorname{div} c$

first, four lemmas to bound the remainder for the cases $b \neq 0$ and $b \neq 0$

lemma *zmult2-lemma-aux1*: $[| (0::\text{int}) < c; b < r; r \leq 0 |] \implies b*c < b*(q \bmod c) + r$
 ⟨proof⟩

lemma *zmult2-lemma-aux2*:
 $[| (0::\text{int}) < c; b < r; r \leq 0 |] \implies b * (q \bmod c) + r \leq 0$
 ⟨proof⟩

lemma *zmult2-lemma-aux3*: $[| (0::\text{int}) < c; 0 \leq r; r < b |] \implies 0 \leq b * (q \bmod c) + r$
 ⟨proof⟩

lemma *zmult2-lemma-aux4*: $[| (0::\text{int}) < c; 0 \leq r; r < b |] \implies b * (q \bmod c) + r < b * c$
 ⟨proof⟩

lemma *zmult2-lemma*: $[| \text{quorem}((a,b), (q,r)); b \neq 0; 0 < c |]$
 $\implies \text{quorem}((a, b*c), (q \operatorname{div} c, b*(q \bmod c) + r))$
 ⟨proof⟩

lemma *zdiv-zmult2-eq*: $(0::\text{int}) < c \implies a \operatorname{div} (b*c) = (a \operatorname{div} b) \operatorname{div} c$
 ⟨proof⟩

lemma *zmod-zmult2-eq*:

$(0::int) < c \implies a \bmod (b*c) = b*(a \operatorname{div} b \bmod c) + a \bmod b$
 $\langle \text{proof} \rangle$

29.13 Cancellation of Common Factors in div

lemma *zdiv-zmult-zmult1-aux1*:

$[| (0::int) < b; \ c \neq 0 |] \implies (c*a) \operatorname{div} (c*b) = a \operatorname{div} b$
 $\langle \text{proof} \rangle$

lemma *zdiv-zmult-zmult1-aux2*:

$[| b < (0::int); \ c \neq 0 |] \implies (c*a) \operatorname{div} (c*b) = a \operatorname{div} b$
 $\langle \text{proof} \rangle$

lemma *zdiv-zmult-zmult1*: $c \neq (0::int) \implies (c*a) \operatorname{div} (c*b) = a \operatorname{div} b$
 $\langle \text{proof} \rangle$

lemma *zdiv-zmult-zmult2*: $c \neq (0::int) \implies (a*c) \operatorname{div} (b*c) = a \operatorname{div} b$
 $\langle \text{proof} \rangle$

29.14 Distribution of Factors over mod

lemma *zmod-zmult-zmult1-aux1*:

$[| (0::int) < b; \ c \neq 0 |] \implies (c*a) \bmod (c*b) = c * (a \bmod b)$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult-zmult1-aux2*:

$[| b < (0::int); \ c \neq 0 |] \implies (c*a) \bmod (c*b) = c * (a \bmod b)$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult-zmult1*: $(c*a) \bmod (c*b) = (c::int) * (a \bmod b)$
 $\langle \text{proof} \rangle$

lemma *zmod-zmult-zmult2*: $(a*c) \bmod (b*c) = (a \bmod b) * (c::int)$
 $\langle \text{proof} \rangle$

29.15 Splitting Rules for div and mod

The proofs of the two lemmas below are essentially identical

lemma *split-pos-lemma*:

$0 < k \implies$
 $P(n \operatorname{div} k :: int)(n \bmod k) = (\forall i\ j. \ 0 \leq j \ \& \ j < k \ \& \ n = k*i + j \implies P\ i\ j)$
 $\langle \text{proof} \rangle$

lemma *split-neg-lemma*:

$k < 0 \implies$
 $P(n \operatorname{div} k :: int)(n \bmod k) = (\forall i\ j. \ k < j \ \& \ j \leq 0 \ \& \ n = k*i + j \implies P\ i\ j)$
 $\langle \text{proof} \rangle$

lemma *split-zdiv*:

$P(n \text{ div } k :: \text{int}) =$
 $((k = 0 \dashrightarrow P\ 0) \ \&$
 $(0 < k \dashrightarrow (\forall i\ j. \ 0 \leq j \ \& \ j < k \ \& \ n = k*i + j \dashrightarrow P\ i)) \ \&$
 $(k < 0 \dashrightarrow (\forall i\ j. \ k < j \ \& \ j \leq 0 \ \& \ n = k*i + j \dashrightarrow P\ i)))$
 $\langle \text{proof} \rangle$

lemma *split-zmod*:

$P(n \text{ mod } k :: \text{int}) =$
 $((k = 0 \dashrightarrow P\ n) \ \&$
 $(0 < k \dashrightarrow (\forall i\ j. \ 0 \leq j \ \& \ j < k \ \& \ n = k*i + j \dashrightarrow P\ j)) \ \&$
 $(k < 0 \dashrightarrow (\forall i\ j. \ k < j \ \& \ j \leq 0 \ \& \ n = k*i + j \dashrightarrow P\ j)))$
 $\langle \text{proof} \rangle$

declare *split-zdiv* [*of* - - *number-of* *k*, *simplified*, *standard*, *arith-split*]

declare *split-zmod* [*of* - - *number-of* *k*, *simplified*, *standard*, *arith-split*]

29.16 Speeding up the Division Algorithm with Shifting

computing div by shifting

lemma *pos-zdiv-mult-2*: $(0 :: \text{int}) \leq a \implies (1 + 2*b) \text{ div } (2*a) = b \text{ div } a$
 $\langle \text{proof} \rangle$

lemma *neg-zdiv-mult-2*: $a \leq (0 :: \text{int}) \implies (1 + 2*b) \text{ div } (2*a) = (b+1) \text{ div } a$
 $\langle \text{proof} \rangle$

lemma *not-0-le-lemma*: $\sim 0 \leq x \implies x \leq (0 :: \text{int})$
 $\langle \text{proof} \rangle$

lemma *zdiv-number-of-BIT*[*simp*]:

$\text{number-of } (v \text{ BIT } b) \text{ div } \text{number-of } (w \text{ BIT } \text{bit}.B0) =$
 $(\text{if } b = \text{bit}.B0 \mid (0 :: \text{int}) \leq \text{number-of } w$
 $\text{then } \text{number-of } v \text{ div } (\text{number-of } w)$
 $\text{else } (\text{number-of } v + (1 :: \text{int})) \text{ div } (\text{number-of } w))$

$\langle \text{proof} \rangle$

29.17 Computing mod by Shifting (proofs resemble those for div)

lemma *pos-zmod-mult-2*:

$(0 :: \text{int}) \leq a \implies (1 + 2*b) \text{ mod } (2*a) = 1 + 2 * (b \text{ mod } a)$
 $\langle \text{proof} \rangle$

lemma *neg-zmod-mult-2*:

$a \leq (0 :: \text{int}) \implies (1 + 2*b) \text{ mod } (2*a) = 2 * ((b+1) \text{ mod } a) - 1$

$\langle \text{proof} \rangle$

lemma *zmod-number-of-BIT* [simp]:

$$\begin{aligned} & \text{number-of } (v \text{ BIT } b) \text{ mod number-of } (w \text{ BIT } \text{bit.B0}) = \\ & \quad (\text{case } b \text{ of} \\ & \quad \quad \text{bit.B0} \Rightarrow 2 * (\text{number-of } v \text{ mod number-of } w) \\ & \quad \quad | \text{bit.B1} \Rightarrow \text{if } (0::\text{int}) \leq \text{number-of } w \\ & \quad \quad \quad \text{then } 2 * (\text{number-of } v \text{ mod number-of } w) + 1 \\ & \quad \quad \quad \text{else } 2 * ((\text{number-of } v + (1::\text{int})) \text{ mod number-of } w) - 1) \end{aligned}$$

$\langle \text{proof} \rangle$

29.18 Quotients of Signs

lemma *div-neg-pos-less0*: $[[a < (0::\text{int}); 0 < b]] \Rightarrow a \text{ div } b < 0$

$\langle \text{proof} \rangle$

lemma *div-nonneg-neg-le0*: $[(0::\text{int}) \leq a; b < 0] \Rightarrow a \text{ div } b \leq 0$

$\langle \text{proof} \rangle$

lemma *pos-imp-zdiv-nonneg-iff*: $(0::\text{int}) < b \Rightarrow (0 \leq a \text{ div } b) = (0 \leq a)$

$\langle \text{proof} \rangle$

lemma *neg-imp-zdiv-nonneg-iff*:

$$b < (0::\text{int}) \Rightarrow (0 \leq a \text{ div } b) = (a \leq (0::\text{int}))$$

$\langle \text{proof} \rangle$

lemma *pos-imp-zdiv-neg-iff*: $(0::\text{int}) < b \Rightarrow (a \text{ div } b < 0) = (a < 0)$

$\langle \text{proof} \rangle$

lemma *neg-imp-zdiv-neg-iff*: $b < (0::\text{int}) \Rightarrow (a \text{ div } b < 0) = (0 < a)$

$\langle \text{proof} \rangle$

29.19 The Divides Relation

lemma *zdvd-iff-zmod-eq-0*: $(m \text{ dvd } n) = (n \text{ mod } m = (0::\text{int}))$

$\langle \text{proof} \rangle$

lemma *zdvd-0-right* [iff]: $(m::\text{int}) \text{ dvd } 0$

$\langle \text{proof} \rangle$

lemma *zdvd-0-left* [iff]: $(0 \text{ dvd } (m::\text{int})) = (m = 0)$

$\langle \text{proof} \rangle$

lemma *zdvd-1-left* [iff]: $1 \text{ dvd } (m::\text{int})$

$\langle \text{proof} \rangle$

lemma *zdvd-refl* [simp]: $m \text{ dvd } (m::\text{int})$

$\langle \text{proof} \rangle$

lemma *zdvd-trans*: $m \text{ dvd } n \implies n \text{ dvd } k \implies m \text{ dvd } (k::int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zminus-iff*: $(m \text{ dvd } -n) = (m \text{ dvd } (n::int))$
 $\langle \text{proof} \rangle$

lemma *zdvd-zminus2-iff*: $(-m \text{ dvd } n) = (m \text{ dvd } (n::int))$
 $\langle \text{proof} \rangle$

lemma *zdvd-anti-sym*:
 $0 < m \implies 0 < n \implies m \text{ dvd } n \implies n \text{ dvd } m \implies m = (n::int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zadd*: $k \text{ dvd } m \implies k \text{ dvd } n \implies k \text{ dvd } (m + n :: int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zdiff*: $k \text{ dvd } m \implies k \text{ dvd } n \implies k \text{ dvd } (m - n :: int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zdiffD*: $k \text{ dvd } m - n \implies k \text{ dvd } n \implies k \text{ dvd } (m::int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmult*: $k \text{ dvd } (n::int) \implies k \text{ dvd } m * n$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmult2*: $k \text{ dvd } (m::int) \implies k \text{ dvd } m * n$
 $\langle \text{proof} \rangle$

lemma *zdvd-triv-right [iff]*: $(k::int) \text{ dvd } m * k$
 $\langle \text{proof} \rangle$

lemma *zdvd-triv-left [iff]*: $(k::int) \text{ dvd } k * m$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmultD2*: $j * k \text{ dvd } n \implies j \text{ dvd } (n::int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmultD*: $j * k \text{ dvd } n \implies k \text{ dvd } (n::int)$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmult-mono*: $i \text{ dvd } m \implies j \text{ dvd } (n::int) \implies i * j \text{ dvd } m * n$
 $\langle \text{proof} \rangle$

lemma *zdvd-reduce*: $(k \text{ dvd } n + k * m) = (k \text{ dvd } (n::int))$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmod*: $f \text{ dvd } m \implies f \text{ dvd } (n::int) \implies f \text{ dvd } m \text{ mod } n$
 $\langle \text{proof} \rangle$

lemma *zdvd-zmod-imp-zdvd*: $k \text{ dvd } m \text{ mod } n \implies k \text{ dvd } n \implies k \text{ dvd } (m::\text{int})$
 $\langle \text{proof} \rangle$

lemma *zdvd-not-zless*: $0 < m \implies m < n \implies \neg n \text{ dvd } (m::\text{int})$
 $\langle \text{proof} \rangle$

lemma *int-dvd-iff*: $(\text{int } m \text{ dvd } z) = (m \text{ dvd } \text{nat } (\text{abs } z))$
 $\langle \text{proof} \rangle$

lemma *dvd-int-iff*: $(z \text{ dvd } \text{int } m) = (\text{nat } (\text{abs } z) \text{ dvd } m)$
 $\langle \text{proof} \rangle$

lemma *nat-dvd-iff*: $(\text{nat } z \text{ dvd } m) = (\text{if } 0 \leq z \text{ then } (z \text{ dvd } \text{int } m) \text{ else } m = 0)$
 $\langle \text{proof} \rangle$

lemma *zminus-dvd-iff* [iff]: $(-z \text{ dvd } w) = (z \text{ dvd } (w::\text{int}))$
 $\langle \text{proof} \rangle$

lemma *dvd-zminus-iff* [iff]: $(z \text{ dvd } -w) = (z \text{ dvd } (w::\text{int}))$
 $\langle \text{proof} \rangle$

lemma *zdvd-imp-le*: $[| z \text{ dvd } n; 0 < n |] \implies z \leq (n::\text{int})$
 $\langle \text{proof} \rangle$

29.20 Integer Powers

instance *int :: power* $\langle \text{proof} \rangle$

primrec

$$p \text{ } ^0 = 1$$

$$p \text{ } ^{(\text{Suc } n)} = (p::\text{int}) * (p \text{ } ^n)$$

instance *int :: recpower*
 $\langle \text{proof} \rangle$

lemma *zpower-zmod*: $((x::\text{int}) \text{ mod } m) \text{ } ^y \text{ mod } m = x \text{ } ^y \text{ mod } m$
 $\langle \text{proof} \rangle$

lemma *zpower-zadd-distrib*: $x \text{ } ^{(y+z)} = ((x \text{ } ^y) * (x \text{ } ^z)::\text{int})$
 $\langle \text{proof} \rangle$

lemma *zpower-zpower*: $(x \text{ } ^y) \text{ } ^z = (x \text{ } ^{(y*z)}::\text{int})$
 $\langle \text{proof} \rangle$

lemma *zero-less-zpower-abs-iff* [simp]:
 $(0 < (\text{abs } x) \text{ } ^n) = (x \neq (0::\text{int}) \mid n=0)$

$\langle proof \rangle$

lemma *zero-le-zpower-abs* [simp]: $(0::int) \leq (abs\ x)^n$
 $\langle proof \rangle$

lemma *int-power*: $int\ (m^n) = (int\ m)^n$
 $\langle proof \rangle$

Compatibility binding

lemmas *zpower-int* = *int-power* [symmetric]

lemma *zdiv-int*: $int\ (a\ div\ b) = (int\ a)\ div\ (int\ b)$
 $\langle proof \rangle$

lemma *zmod-int*: $int\ (a\ mod\ b) = (int\ a)\ mod\ (int\ b)$
 $\langle proof \rangle$

Suggested by Matthias Daum

lemma *int-power-div-base*:
 $\llbracket 0 < m; 0 < k \rrbracket \implies k^m\ div\ k = (k::int)^m - Suc\ 0$
 $\langle proof \rangle$

$\langle ML \rangle$

end

30 NatBin: Binary arithmetic for the natural numbers

theory *NatBin*
imports *IntDiv*
begin

Arithmetic for naturals is reduced to that for the non-negative integers.

instance *nat* :: *number* $\langle proof \rangle$

defs (overloaded)
nat-number-of-def:
 $(number-of::bin \implies nat)\ v == nat\ ((number-of::bin \implies int)\ v)$

30.1 Function *nat*: Coercion from Type *int* to *nat*

declare *nat-0* [simp] *nat-1* [simp]

lemma *nat-number-of* [simp]: $nat\ (number-of\ w) = number-of\ w$
 $\langle proof \rangle$

lemma *nat-numeral-0-eq-0* [simp]: $\text{Numeral0} = (0::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *nat-numeral-1-eq-1* [simp]: $\text{Numeral1} = (1::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *numeral-1-eq-Suc-0*: $\text{Numeral1} = \text{Suc } 0$
 $\langle \text{proof} \rangle$

lemma *numeral-2-eq-2*: $2 = \text{Suc } (\text{Suc } 0)$
 $\langle \text{proof} \rangle$

Distributive laws for type *nat*. The others are in theory *IntArith*, but these require *div* and *mod* to be defined for type “int”. They also need some of the lemmas proved above.

lemma *nat-div-distrib*: $(0::\text{int}) \leq z \implies \text{nat } (z \text{ div } z') = \text{nat } z \text{ div } \text{nat } z'$
 $\langle \text{proof} \rangle$

lemma *nat-mod-distrib*:
 $\llbracket (0::\text{int}) \leq z; 0 \leq z' \rrbracket \implies \text{nat } (z \text{ mod } z') = \text{nat } z \text{ mod } \text{nat } z'$
 $\langle \text{proof} \rangle$

Suggested by Matthias Daum

lemma *int-div-less-self*: $\llbracket 0 < x; 1 < k \rrbracket \implies x \text{ div } k < (x::\text{int})$
 $\langle \text{proof} \rangle$

30.2 Function *int*: Coercion from Type *nat* to *int*

lemma *int-nat-number-of* [simp]:
 $\text{int } (\text{number-of } v :: \text{nat}) =$
 $(\text{if } \text{neg } (\text{number-of } v :: \text{int}) \text{ then } 0$
 $\text{else } (\text{number-of } v :: \text{int}))$
 $\langle \text{proof} \rangle$

30.2.1 Successor

lemma *Suc-nat-eq-nat-zadd1*: $(0::\text{int}) \leq z \implies \text{Suc } (\text{nat } z) = \text{nat } (1 + z)$
 $\langle \text{proof} \rangle$

lemma *Suc-nat-number-of-add*:
 $\text{Suc } (\text{number-of } v + n) =$
 $(\text{if } \text{neg } (\text{number-of } v :: \text{int}) \text{ then } 1+n \text{ else } \text{number-of } (\text{bin-succ } v) + n)$
 $\langle \text{proof} \rangle$

lemma *Suc-nat-number-of* [simp]:
 $\text{Suc } (\text{number-of } v) =$
 $(\text{if } \text{neg } (\text{number-of } v :: \text{int}) \text{ then } 1 \text{ else } \text{number-of } (\text{bin-succ } v))$
 $\langle \text{proof} \rangle$

30.2.2 Addition

lemma *add-nat-number-of* [simp]:

$$(number-of\ v :: nat) + number-of\ v' =$$

$$(if\ neg\ (number-of\ v :: int)\ then\ number-of\ v'$$

$$else\ if\ neg\ (number-of\ v' :: int)\ then\ number-of\ v$$

$$else\ number-of\ (bin-add\ v\ v'))$$

$$\langle proof \rangle$$

30.2.3 Subtraction

lemma *diff-nat-eq-if*:

$$nat\ z - nat\ z' =$$

$$(if\ neg\ z'\ then\ nat\ z$$

$$else\ let\ d = z - z'\ in$$

$$if\ neg\ d\ then\ 0\ else\ nat\ d)$$

$$\langle proof \rangle$$

lemma *diff-nat-number-of* [simp]:

$$(number-of\ v :: nat) - number-of\ v' =$$

$$(if\ neg\ (number-of\ v' :: int)\ then\ number-of\ v$$

$$else\ let\ d = number-of\ (bin-add\ v\ (bin-minus\ v'))\ in$$

$$if\ neg\ d\ then\ 0\ else\ nat\ d)$$

$$\langle proof \rangle$$

30.2.4 Multiplication

lemma *mult-nat-number-of* [simp]:

$$(number-of\ v :: nat) * number-of\ v' =$$

$$(if\ neg\ (number-of\ v :: int)\ then\ 0\ else\ number-of\ (bin-mult\ v\ v'))$$

$$\langle proof \rangle$$

30.2.5 Quotient

lemma *div-nat-number-of* [simp]:

$$(number-of\ v :: nat)\ div\ number-of\ v' =$$

$$(if\ neg\ (number-of\ v :: int)\ then\ 0$$

$$else\ nat\ (number-of\ v\ div\ number-of\ v'))$$

$$\langle proof \rangle$$

lemma *one-div-nat-number-of* [simp]:

$$(Suc\ 0)\ div\ number-of\ v' = (nat\ (1\ div\ number-of\ v'))$$

$$\langle proof \rangle$$

30.2.6 Remainder

lemma *mod-nat-number-of* [simp]:

$$(number-of\ v :: nat)\ mod\ number-of\ v' =$$

$$(if\ neg\ (number-of\ v :: int)\ then\ 0$$

$$else\ if\ neg\ (number-of\ v' :: int)\ then\ number-of\ v$$

else nat (number-of v mod number-of v')
 $\langle \text{proof} \rangle$

lemma *one-mod-nat-number-of [simp]:*
 $(\text{Suc } 0) \text{ mod number-of } v' =$
 $(\text{if neg (number-of } v' :: \text{int}) \text{ then Suc } 0$
 $\text{else nat (1 mod number-of } v'))$
 $\langle \text{proof} \rangle$

$\langle ML \rangle$

30.3 Comparisons

30.3.1 Equals (=)

lemma *eq-nat-nat-iff:*
 $[| (0 :: \text{int}) \leq z; 0 \leq z' |] ==> (\text{nat } z = \text{nat } z') = (z = z')$
 $\langle \text{proof} \rangle$

lemma *eq-nat-number-of [simp]:*
 $((\text{number-of } v :: \text{nat}) = \text{number-of } v') =$
 $(\text{if neg (number-of } v :: \text{int}) \text{ then } (\text{iszero (number-of } v' :: \text{int}) \mid \text{neg (number-of } v' :: \text{int}))$
 $\text{else if neg (number-of } v' :: \text{int}) \text{ then iszero (number-of } v :: \text{int})$
 $\text{else iszero (number-of (bin-add } v \text{ (bin-minus } v')) :: \text{int}))$
 $\langle \text{proof} \rangle$

30.3.2 Less-than (<)

lemma *less-nat-number-of [simp]:*
 $((\text{number-of } v :: \text{nat}) < \text{number-of } v') =$
 $(\text{if neg (number-of } v :: \text{int}) \text{ then neg (number-of (bin-minus } v') :: \text{int})$
 $\text{else neg (number-of (bin-add } v \text{ (bin-minus } v')) :: \text{int}))$
 $\langle \text{proof} \rangle$

lemmas *numerals = nat-numeral-0-eq-0 nat-numeral-1-eq-1 numeral-2-eq-2*

30.4 Powers with Numeric Exponents

We cannot refer to the number $2::'a$ in *Ring-and-Field.thy*. We cannot prove general results about the numeral $-1::'a$, so we have to use $-(1::'a)$ instead.

lemma *power2-eq-square*: $(a::'a::\{\text{comm-semiring-1-cancel}, \text{recpower}\})^2 = a * a$
 $\langle \text{proof} \rangle$

lemma *zero-power2* [simp]: $(0::'a::\{\text{comm-semiring-1-cancel}, \text{recpower}\})^2 = 0$
 $\langle \text{proof} \rangle$

lemma *one-power2* [simp]: $(1::'a::\{\text{comm-semiring-1-cancel}, \text{recpower}\})^2 = 1$
 $\langle \text{proof} \rangle$

lemma *power3-eq-cube*: $(x::'a::\text{recpower})^3 = x * x * x$
 $\langle \text{proof} \rangle$

Squares of literal numerals will be evaluated.

lemmas *power2-eq-square-number-of* =
power2-eq-square [of number-of w, standard]
declare *power2-eq-square-number-of* [simp]

lemma *zero-le-power2*: $0 \leq (a^2::'a::\{\text{ordered-idom}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

lemma *zero-less-power2*:
 $(0 < a^2) = (a \neq (0::'a::\{\text{ordered-idom}, \text{recpower}\}))$
 $\langle \text{proof} \rangle$

lemma *power2-less-0*:
fixes $a :: 'a::\{\text{ordered-idom}, \text{recpower}\}$
shows $\sim (a^2 < 0)$
 $\langle \text{proof} \rangle$

lemma *zero-eq-power2*:
 $(a^2 = 0) = (a = (0::'a::\{\text{ordered-idom}, \text{recpower}\}))$
 $\langle \text{proof} \rangle$

lemma *abs-power2*:
 $\text{abs}(a^2) = (a^2::'a::\{\text{ordered-idom}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

lemma *power2-abs*:
 $(\text{abs } a)^2 = (a^2::'a::\{\text{ordered-idom}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

lemma *power2-minus*:
 $(- a)^2 = (a^2::'a::\{\text{comm-ring-1}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

lemma *power-minus1-even*: $(- 1)^{2*n} = (1::'a::\{\text{comm-ring-1}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

lemma *power-even-eq*: $(a::'a::\text{recpower}) \wedge (2*n) = (a \wedge n) \wedge 2$
 $\langle \text{proof} \rangle$

lemma *power-odd-eq*: $(a::\text{int}) \wedge \text{Suc}(2*n) = a * (a \wedge n) \wedge 2$
 $\langle \text{proof} \rangle$

lemma *power-minus-even* [simp]:
 $(-a) \wedge (2*n) = (a::'a::\{\text{comm-ring-1}, \text{recpower}\}) \wedge (2*n)$
 $\langle \text{proof} \rangle$

lemma *zero-le-even-power'*:
 $0 \leq (a::'a::\{\text{ordered-idom}, \text{recpower}\}) \wedge (2*n)$
 $\langle \text{proof} \rangle$

lemma *odd-power-less-zero*:
 $(a::'a::\{\text{ordered-idom}, \text{recpower}\}) < 0 ==> a \wedge \text{Suc}(2*n) < 0$
 $\langle \text{proof} \rangle$

lemma *odd-0-le-power-imp-0-le*:
 $0 \leq a \wedge \text{Suc}(2*n) ==> 0 \leq (a::'a::\{\text{ordered-idom}, \text{recpower}\})$
 $\langle \text{proof} \rangle$

Simprules for comparisons where common factors can be cancelled.

lemmas *zero-compare-simps* =
add-strict-increasing add-strict-increasing2 add-increasing
zero-le-mult-iff zero-le-divide-iff
zero-less-mult-iff zero-less-divide-iff
mult-le-0-iff divide-le-0-iff
mult-less-0-iff divide-less-0-iff
zero-le-power2 power2-less-0

30.4.1 Nat

lemma *Suc-pred'*: $0 < n ==> n = \text{Suc}(n - 1)$
 $\langle \text{proof} \rangle$

lemmas *expand-Suc* = *Suc-pred'* [of number-of v, standard]

30.4.2 Arith

lemma *Suc-eq-add-numeral-1*: $\text{Suc } n = n + 1$
 $\langle \text{proof} \rangle$

lemma *Suc-eq-add-numeral-1-left*: $\text{Suc } n = 1 + n$
 $\langle \text{proof} \rangle$

lemma *add-eq-if*: $(m::\text{nat}) + n = (\text{if } m=0 \text{ then } n \text{ else } \text{Suc } ((m - 1) + n))$

$\langle proof \rangle$

lemma *mult-eq-if*: $(m :: nat) * n = (if\ m=0\ then\ 0\ else\ n + ((m - 1) * n))$
 $\langle proof \rangle$

lemma *power-eq-if*: $(p \wedge m :: nat) = (if\ m=0\ then\ 1\ else\ p * (p \wedge (m - 1)))$
 $\langle proof \rangle$

30.5 Comparisons involving $(0 :: nat)$

Simplification already does $n < (0 :: 'a)$, $n \leq (0 :: 'a)$ and $(0 :: 'a) \leq n$.

lemma *eq-number-of-0* [simp]:
 $(number-of\ v = (0 :: nat)) =$
 $(if\ neg\ (number-of\ v :: int)\ then\ True\ else\ iszero\ (number-of\ v :: int))$
 $\langle proof \rangle$

lemma *eq-0-number-of* [simp]:
 $((0 :: nat) = number-of\ v) =$
 $(if\ neg\ (number-of\ v :: int)\ then\ True\ else\ iszero\ (number-of\ v :: int))$
 $\langle proof \rangle$

lemma *less-0-number-of* [simp]:
 $((0 :: nat) < number-of\ v) = neg\ (number-of\ (bin-minus\ v) :: int)$
 $\langle proof \rangle$

lemma *neg-imp-number-of-eq-0*: $neg\ (number-of\ v :: int) ==> number-of\ v = (0 :: nat)$
 $\langle proof \rangle$

30.6 Comparisons involving Suc

lemma *eq-number-of-Suc* [simp]:
 $(number-of\ v = Suc\ n) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ False\ else\ nat\ pv = n)$
 $\langle proof \rangle$

lemma *Suc-eq-number-of* [simp]:
 $(Suc\ n = number-of\ v) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ False\ else\ nat\ pv = n)$
 $\langle proof \rangle$

lemma *less-number-of-Suc* [simp]:
 $(number-of\ v < Suc\ n) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ True\ else\ nat\ pv < n)$
 $\langle proof \rangle$

lemma *less-Suc-number-of* [simp]:
 (Suc n < number-of v) =
 (let pv = number-of (bin-pred v) in
 if neg pv then False else n < nat pv)
 <proof>

lemma *le-number-of-Suc* [simp]:
 (number-of v <= Suc n) =
 (let pv = number-of (bin-pred v) in
 if neg pv then True else nat pv <= n)
 <proof>

lemma *le-Suc-number-of* [simp]:
 (Suc n <= number-of v) =
 (let pv = number-of (bin-pred v) in
 if neg pv then False else n <= nat pv)
 <proof>

declare *zadd-int* [symmetric, simp]

lemma *lemma1*: (m+m = n+n) = (m = (n::int))
 <proof>

lemma *lemma2*: m+m ~ = (1::int) + (n + n)
 <proof>

lemma *eq-number-of-BIT-BIT*:
 ((number-of (v BIT x) ::int) = number-of (w BIT y)) =
 (x=y & (((number-of v) ::int) = number-of w))
 <proof>

lemma *eq-number-of-BIT-Pls*:
 ((number-of (v BIT x) ::int) = Numeral0) =
 (x=bit.B0 & (((number-of v) ::int) = Numeral0))
 <proof>

lemma *eq-number-of-BIT-Min*:
 ((number-of (v BIT x) ::int) = number-of Numeral.Min) =
 (x=bit.B1 & (((number-of v) ::int) = number-of Numeral.Min))
 <proof>

lemma *eq-number-of-Pls-Min*: (Numeral0 ::int) ~ = number-of Numeral.Min
 <proof>

30.7 Literal arithmetic involving powers

lemma *nat-power-eq*: $(0::int) \leq z \implies \text{nat } (z^n) = \text{nat } z ^ n$
 $\langle \text{proof} \rangle$

lemma *power-nat-number-of*:
 $(\text{number-of } v :: \text{nat}) ^ n =$
 $(\text{if } \text{neg } (\text{number-of } v :: \text{int}) \text{ then } 0^n \text{ else } \text{nat } ((\text{number-of } v :: \text{int}) ^ n))$
 $\langle \text{proof} \rangle$

lemmas *power-nat-number-of-number-of* = *power-nat-number-of* [of - number-of
w, standard]

declare *power-nat-number-of-number-of* [simp]

For the integers

lemma *zpower-number-of-even*:
 $(z::int) ^ \text{number-of } (w \text{ BIT } \text{bit}.B0) =$
 $(\text{let } w = z ^ (\text{number-of } w) \text{ in } w * w)$
 $\langle \text{proof} \rangle$

lemma *zpower-number-of-odd*:
 $(z::int) ^ \text{number-of } (w \text{ BIT } \text{bit}.B1) =$
 $(\text{if } (0::int) \leq \text{number-of } w$
 $\text{then } (\text{let } w = z ^ (\text{number-of } w) \text{ in } z * w * w)$
 $\text{else } 1)$
 $\langle \text{proof} \rangle$

lemmas *zpower-number-of-even-number-of* =
zpower-number-of-even [of number-of *v*, standard]

declare *zpower-number-of-even-number-of* [simp]

lemmas *zpower-number-of-odd-number-of* =
zpower-number-of-odd [of number-of *v*, standard]

declare *zpower-number-of-odd-number-of* [simp]

$\langle \text{ML} \rangle$

declare *split-div*[of - - number-of *k*, standard, arith-split]
declare *split-mod*[of - - number-of *k*, standard, arith-split]

lemma *nat-number-of-Pls*: *Natural0* = $(0::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *nat-number-of-Min*: *number-of Natural.Min* = $(0::\text{nat})$
 $\langle \text{proof} \rangle$

lemma *nat-number-of-BIT-1*:
 $\text{number-of } (w \text{ BIT bit.B1}) =$
 (if neg (number-of $w :: \text{int}$) then 0
 else let $n = \text{number-of } w$ in $\text{Suc } (n + n)$)
 ⟨proof⟩

lemma *nat-number-of-BIT-0*:
 $\text{number-of } (w \text{ BIT bit.B0}) = (\text{let } n :: \text{nat} = \text{number-of } w \text{ in } n + n)$
 ⟨proof⟩

lemmas *nat-number =*
nat-number-of-Pls nat-number-of-Min
nat-number-of-BIT-1 nat-number-of-BIT-0

lemma *Let-Suc [simp]*: Let $(\text{Suc } n) f == f (\text{Suc } n)$
 ⟨proof⟩

lemma *power-m1-even*: $(-1) ^ (2*n) = (1 :: 'a :: \{\text{number-ring}, \text{recpower}\})$
 ⟨proof⟩

lemma *power-m1-odd*: $(-1) ^ \text{Suc}(2*n) = (-1 :: 'a :: \{\text{number-ring}, \text{recpower}\})$
 ⟨proof⟩

30.8 Literal arithmetic and of-nat

lemma *of-nat-double*:
 $0 \leq x ==> \text{of-nat } (\text{nat } (2 * x)) = \text{of-nat } (\text{nat } x) + \text{of-nat } (\text{nat } x)$
 ⟨proof⟩

lemma *nat-numeral-m1-eq-0*: $-1 = (0 :: \text{nat})$
 ⟨proof⟩

lemma *of-nat-number-of-lemma*:
 $\text{of-nat } (\text{number-of } v :: \text{nat}) =$
 (if $0 \leq (\text{number-of } v :: \text{int})$
 then $(\text{number-of } v :: 'a :: \text{number-ring})$
 else 0)
 ⟨proof⟩

lemma *of-nat-number-of-eq [simp]*:
 $\text{of-nat } (\text{number-of } v :: \text{nat}) =$
 (if neg (number-of $v :: \text{int}$) then 0
 else $(\text{number-of } v :: 'a :: \text{number-ring})$)
 ⟨proof⟩

30.9 Lemmas for the Combination and Cancellation Sim-procs

lemma *nat-number-of-add-left:*

$$\begin{aligned} \text{number-of } v + (\text{number-of } v' + (k::\text{nat})) = \\ \text{(if neg (number-of } v :: \text{int) then number-of } v' + k \\ \text{else if neg (number-of } v' :: \text{int) then number-of } v + k \\ \text{else number-of (bin-add } v \ v') + k) \end{aligned}$$

<proof>

lemma *nat-number-of-mult-left:*

$$\begin{aligned} \text{number-of } v * (\text{number-of } v' * (k::\text{nat})) = \\ \text{(if neg (number-of } v :: \text{int) then 0} \\ \text{else number-of (bin-mult } v \ v') * k) \end{aligned}$$

<proof>

30.9.1 For combine-numerals

lemma *left-add-mult-distrib:* $i*u + (j*u + k) = (i+j)*u + (k::\text{nat})$

<proof>

30.9.2 For cancel-numerals

lemma *nat-diff-add-eq1:*

$$j <= (i::\text{nat}) \implies ((i*u + m) - (j*u + n)) = (((i-j)*u + m) - n)$$

<proof>

lemma *nat-diff-add-eq2:*

$$i <= (j::\text{nat}) \implies ((i*u + m) - (j*u + n)) = (m - ((j-i)*u + n))$$

<proof>

lemma *nat-eq-add-iff1:*

$$j <= (i::\text{nat}) \implies (i*u + m = j*u + n) = ((i-j)*u + m = n)$$

<proof>

lemma *nat-eq-add-iff2:*

$$i <= (j::\text{nat}) \implies (i*u + m = j*u + n) = (m = (j-i)*u + n)$$

<proof>

lemma *nat-less-add-iff1:*

$$j <= (i::\text{nat}) \implies (i*u + m < j*u + n) = ((i-j)*u + m < n)$$

<proof>

lemma *nat-less-add-iff2:*

$$i <= (j::\text{nat}) \implies (i*u + m < j*u + n) = (m < (j-i)*u + n)$$

<proof>

lemma *nat-le-add-iff1:*

$$j <= (i::\text{nat}) \implies (i*u + m \leq j*u + n) = ((i-j)*u + m \leq n)$$

<proof>

lemma *nat-le-add-iff2*:

$i \leq (j::nat) \implies (i*u + m \leq j*u + n) = (m \leq (j-i)*u + n)$
 $\langle proof \rangle$

30.9.3 For *cancel-numeral-factors*

lemma *nat-mult-le-cancel1*: $(0::nat) < k \implies (k*m \leq k*n) = (m \leq n)$
 $\langle proof \rangle$

lemma *nat-mult-less-cancel1*: $(0::nat) < k \implies (k*m < k*n) = (m < n)$
 $\langle proof \rangle$

lemma *nat-mult-eq-cancel1*: $(0::nat) < k \implies (k*m = k*n) = (m = n)$
 $\langle proof \rangle$

lemma *nat-mult-div-cancel1*: $(0::nat) < k \implies (k*m) \text{ div } (k*n) = (m \text{ div } n)$
 $\langle proof \rangle$

30.9.4 For *cancel-factor*

lemma *nat-mult-le-cancel-disj*: $(k*m \leq k*n) = ((0::nat) < k \implies m \leq n)$
 $\langle proof \rangle$

lemma *nat-mult-less-cancel-disj*: $(k*m < k*n) = ((0::nat) < k \ \& \ m < n)$
 $\langle proof \rangle$

lemma *nat-mult-eq-cancel-disj*: $(k*m = k*n) = (k = (0::nat) \mid m = n)$
 $\langle proof \rangle$

lemma *nat-mult-div-cancel-disj*:
 $(k*m) \text{ div } (k*n) = (\text{if } k = (0::nat) \text{ then } 0 \text{ else } m \text{ div } n)$
 $\langle proof \rangle$

$\langle ML \rangle$

end

31 NatSimpprocs: Simpprocs for the Naturals

theory *NatSimpprocs*

imports *NatBin*

uses *int-factor-simpprocs.ML nat-simpprocs.ML*

begin

$\langle ML \rangle$

31.1 For simplifying $Suc\ m - K$ and $K - Suc\ m$

Where K above is a literal

lemma *Suc-diff-eq-diff-pred*: $Numeral0 < n ==> Suc\ m - n = m - (n - Numeral1)$
 ⟨proof⟩

Now just instantiating n to $number-of\ v$ does the right simplification, but with some redundant inequality tests.

lemma *neg-number-of-bin-pred-iff-0*:
 $neg\ (number-of\ (bin-pred\ v)::int) = (number-of\ v = (0::nat))$
 ⟨proof⟩

No longer required as a simprule because of the *inverse-fold* simproc

lemma *Suc-diff-number-of*:
 $neg\ (number-of\ (bin-minus\ v)::int) ==>$
 $Suc\ m - (number-of\ v) = m - (number-of\ (bin-pred\ v))$
 ⟨proof⟩

lemma *diff-Suc-eq-diff-pred*: $m - Suc\ n = (m - 1) - n$
 ⟨proof⟩

31.2 For *nat-case* and *nat-rec*

lemma *nat-case-number-of [simp]*:
 $nat-case\ a\ f\ (number-of\ v) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ a\ else\ f\ (nat\ pv))$
 ⟨proof⟩

lemma *nat-case-add-eq-if [simp]*:
 $nat-case\ a\ f\ ((number-of\ v) + n) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ nat-case\ a\ f\ n\ else\ f\ (nat\ pv + n))$
 ⟨proof⟩

lemma *nat-rec-number-of [simp]*:
 $nat-rec\ a\ f\ (number-of\ v) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ a\ else\ f\ (nat\ pv)\ (nat-rec\ a\ f\ (nat\ pv)))$
 ⟨proof⟩

lemma *nat-rec-add-eq-if [simp]*:
 $nat-rec\ a\ f\ (number-of\ v + n) =$
 $(let\ pv = number-of\ (bin-pred\ v)\ in$
 $if\ neg\ pv\ then\ nat-rec\ a\ f\ n$
 $else\ f\ (nat\ pv + n)\ (nat-rec\ a\ f\ (nat\ pv + n)))$
 ⟨proof⟩

31.3 Various Other Lemmas

31.3.1 Evens and Odds, for Mutilated Chess Board

Lemmas for specialist use, NOT as default simprules

lemma *nat-mult-2*: $2 * z = (z + z :: nat)$
 $\langle proof \rangle$

lemma *nat-mult-2-right*: $z * 2 = (z + z :: nat)$
 $\langle proof \rangle$

Case analysis on $n < (2 :: 'a)$

lemma *less-2-cases*: $(n :: nat) < 2 ==> n = 0 \mid n = Suc\ 0$
 $\langle proof \rangle$

lemma *div2-Suc-Suc* [simp]: $Suc(Suc\ m) \mathit{div}\ 2 = Suc\ (m \mathit{div}\ 2)$
 $\langle proof \rangle$

lemma *add-self-div-2* [simp]: $(m + m) \mathit{div}\ 2 = (m :: nat)$
 $\langle proof \rangle$

lemma *mod2-Suc-Suc* [simp]: $Suc(Suc\ m) \mathit{mod}\ 2 = m \mathit{mod}\ 2$
 $\langle proof \rangle$

lemma *mod2-gr-0* [simp]: $!!m :: nat. (0 < m \mathit{mod}\ 2) = (m \mathit{mod}\ 2 = 1)$
 $\langle proof \rangle$

31.3.2 Removal of Small Numerals: 0, 1 and (in additive positions) 2

lemma *add-2-eq-Suc* [simp]: $2 + n = Suc\ (Suc\ n)$
 $\langle proof \rangle$

lemma *add-2-eq-Suc'* [simp]: $n + 2 = Suc\ (Suc\ n)$
 $\langle proof \rangle$

Can be used to eliminate long strings of Sucs, but not by default

lemma *Suc3-eq-add-3*: $Suc\ (Suc\ (Suc\ n)) = 3 + n$
 $\langle proof \rangle$

These lemmas collapse some needless occurrences of Suc: at least three Sucs, since two and fewer are rewritten back to Suc again! We already have some rules to simplify operands smaller than 3.

lemma *div-Suc-eq-div-add3* [simp]: $m \mathit{div}\ (Suc\ (Suc\ (Suc\ n))) = m \mathit{div}\ (3 + n)$
 $\langle proof \rangle$

lemma *mod-Suc-eq-mod-add3* [simp]: $m \mathit{mod}\ (Suc\ (Suc\ (Suc\ n))) = m \mathit{mod}\ (3 + n)$
 $\langle proof \rangle$

lemma *Suc-div-eq-add3-div*: $(\text{Suc } (\text{Suc } (\text{Suc } m))) \text{ div } n = (3+m) \text{ div } n$
 <proof>

lemma *Suc-mod-eq-add3-mod*: $(\text{Suc } (\text{Suc } (\text{Suc } m))) \text{ mod } n = (3+m) \text{ mod } n$
 <proof>

lemmas *Suc-div-eq-add3-div-number-of* =
 Suc-div-eq-add3-div [of - number-of *v*, standard]
declare *Suc-div-eq-add3-div-number-of* [simp]

lemmas *Suc-mod-eq-add3-mod-number-of* =
 Suc-mod-eq-add3-mod [of - number-of *v*, standard]
declare *Suc-mod-eq-add3-mod-number-of* [simp]

31.4 Special Simplification for Constants

These belong here, late in the development of HOL, to prevent their interfering with proofs of abstract properties of instances of the function *number-of*

These distributive laws move literals inside sums and differences.

lemmas *left-distrib-number-of* = *left-distrib* [of - - number-of *v*, standard]
declare *left-distrib-number-of* [simp]

lemmas *right-distrib-number-of* = *right-distrib* [of number-of *v*, standard]
declare *right-distrib-number-of* [simp]

lemmas *left-diff-distrib-number-of* =
 left-diff-distrib [of - - number-of *v*, standard]
declare *left-diff-distrib-number-of* [simp]

lemmas *right-diff-distrib-number-of* =
 right-diff-distrib [of number-of *v*, standard]
declare *right-diff-distrib-number-of* [simp]

These are actually for fields, like real: but where else to put them?

lemmas *zero-less-divide-iff-number-of* =
 zero-less-divide-iff [of number-of *w*, standard]
declare *zero-less-divide-iff-number-of* [simp]

lemmas *divide-less-0-iff-number-of* =
 divide-less-0-iff [of number-of *w*, standard]
declare *divide-less-0-iff-number-of* [simp]

lemmas *zero-le-divide-iff-number-of* =
 zero-le-divide-iff [of number-of *w*, standard]
declare *zero-le-divide-iff-number-of* [simp]

lemmas *divide-le-0-iff-number-of* =
 divide-le-0-iff [of number-of *w*, standard]
declare *divide-le-0-iff-number-of* [simp]

Replaces *inverse #nn* by $1/\#nn$. It looks strange, but then other simprocs simplify the quotient.

lemmas *inverse-eq-divide-number-of* =
 inverse-eq-divide [of number-of *w*, standard]
declare *inverse-eq-divide-number-of* [simp]

These laws simplify inequalities, moving unary minus from a term into the literal.

lemmas *less-minus-iff-number-of* =
 less-minus-iff [of number-of *v*, standard]
declare *less-minus-iff-number-of* [simp]

lemmas *le-minus-iff-number-of* =
 le-minus-iff [of number-of *v*, standard]
declare *le-minus-iff-number-of* [simp]

lemmas *equation-minus-iff-number-of* =
 equation-minus-iff [of number-of *v*, standard]
declare *equation-minus-iff-number-of* [simp]

lemmas *minus-less-iff-number-of* =
 minus-less-iff [of - number-of *v*, standard]
declare *minus-less-iff-number-of* [simp]

lemmas *minus-le-iff-number-of* =
 minus-le-iff [of - number-of *v*, standard]
declare *minus-le-iff-number-of* [simp]

lemmas *minus-equation-iff-number-of* =
 minus-equation-iff [of - number-of *v*, standard]
declare *minus-equation-iff-number-of* [simp]

These simplify inequalities where one side is the constant 1.

lemmas *less-minus-iff-1* = *less-minus-iff* [of 1, simplified]
declare *less-minus-iff-1* [simp]

lemmas *le-minus-iff-1* = *le-minus-iff* [of 1, simplified]
declare *le-minus-iff-1* [simp]

lemmas *equation-minus-iff-1* = *equation-minus-iff* [of 1, simplified]
declare *equation-minus-iff-1* [simp]

lemmas *minus-less-iff-1* = *minus-less-iff* [of - 1, simplified]

declare *minus-less-iff-1* [*simp*]

lemmas *minus-le-iff-1* = *minus-le-iff* [*of - 1, simplified*]

declare *minus-le-iff-1* [*simp*]

lemmas *minus-equation-iff-1* = *minus-equation-iff* [*of - 1, simplified*]

declare *minus-equation-iff-1* [*simp*]

Cancellation of constant factors in comparisons ($<$ and \leq)

lemmas *mult-less-cancel-left-number-of* =
mult-less-cancel-left [*of number-of v, standard*]

declare *mult-less-cancel-left-number-of* [*simp*]

lemmas *mult-less-cancel-right-number-of* =
mult-less-cancel-right [*of - number-of v, standard*]

declare *mult-less-cancel-right-number-of* [*simp*]

lemmas *mult-le-cancel-left-number-of* =
mult-le-cancel-left [*of number-of v, standard*]

declare *mult-le-cancel-left-number-of* [*simp*]

lemmas *mult-le-cancel-right-number-of* =
mult-le-cancel-right [*of - number-of v, standard*]

declare *mult-le-cancel-right-number-of* [*simp*]

Multiplying out constant divisors in comparisons ($<$, \leq and $=$)

lemmas *le-divide-eq-number-of* = *le-divide-eq* [*of - - number-of w, standard*]

declare *le-divide-eq-number-of* [*simp*]

lemmas *divide-le-eq-number-of* = *divide-le-eq* [*of - number-of w, standard*]

declare *divide-le-eq-number-of* [*simp*]

lemmas *less-divide-eq-number-of* = *less-divide-eq* [*of - - number-of w, standard*]

declare *less-divide-eq-number-of* [*simp*]

lemmas *divide-less-eq-number-of* = *divide-less-eq* [*of - number-of w, standard*]

declare *divide-less-eq-number-of* [*simp*]

lemmas *eq-divide-eq-number-of* = *eq-divide-eq* [*of - - number-of w, standard*]

declare *eq-divide-eq-number-of* [*simp*]

lemmas *divide-eq-eq-number-of* = *divide-eq-eq* [*of - number-of w, standard*]

declare *divide-eq-eq-number-of* [*simp*]

31.5 Optional Simplification Rules Involving Constants

Simplify quotients that are compared with a literal constant.

lemmas *le-divide-eq-number-of* = *le-divide-eq* [*of number-of w, standard*]

lemmas *divide-le-eq-number-of* = *divide-le-eq* [*of* - - *number-of w, standard*]
lemmas *less-divide-eq-number-of* = *less-divide-eq* [*of number-of w, standard*]
lemmas *divide-less-eq-number-of* = *divide-less-eq* [*of* - - *number-of w, standard*]
lemmas *eq-divide-eq-number-of* = *eq-divide-eq* [*of number-of w, standard*]
lemmas *divide-eq-eq-number-of* = *divide-eq-eq* [*of* - - *number-of w, standard*]

Not good as automatic simplrules because they cause case splits.

lemmas *divide-const-simps* =
le-divide-eq-number-of divide-le-eq-number-of less-divide-eq-number-of
divide-less-eq-number-of eq-divide-eq-number-of divide-eq-eq-number-of
le-divide-eq-1 divide-le-eq-1 less-divide-eq-1 divide-less-eq-1

31.5.1 Division By -1

lemma *divide-minus1* [*simp*]:
 $x / -1 = -(x :: 'a :: \{\text{field, division-by-zero, number-ring}\})$
 <proof>

lemma *minus1-divide* [*simp*]:
 $-1 / (x :: 'a :: \{\text{field, division-by-zero, number-ring}\}) = -(1/x)$
 <proof>

lemma *half-gt-zero-iff*:
 $(0 < r/2) = (0 < (r :: 'a :: \{\text{ordered-field, division-by-zero, number-ring}\}))$
 <proof>

lemmas *half-gt-zero* = *half-gt-zero-iff* [*THEN iffD2, simp*]

lemma *nat-dvd-not-less*:
 $[| 0 < m; m < n |] ==> \neg n \text{ dvd } (m :: \text{nat})$
 <proof>

<ML>

end

32 Presburger: Presburger Arithmetic: Cooper’s Algorithm

theory *Presburger*
imports *NatSimprocs SetInterval*
uses (*cooper-dec.ML*) (*cooper-proof.ML*) (*qelim.ML*)
 (*reflected-presburger.ML*) (*reflected-cooper.ML*) (*presburger.ML*)
begin

Theorem for unitifying the coefficients of x in an existential formula

theorem *unity-coeff-ex*: $(\exists x::int. P (l * x)) = (\exists x. l \text{ dvd } (1*x+0) \wedge P x)$
 $\langle proof \rangle$

lemma *uminus-dvd-conv*: $(d \text{ dvd } (t::int)) = (-d \text{ dvd } t)$
 $\langle proof \rangle$

lemma *uminus-dvd-conv'*: $(d \text{ dvd } (t::int)) = (d \text{ dvd } -t)$
 $\langle proof \rangle$

Theorems for the combination of proofs of the equality of P and $P\text{-}m$ for integers x less than some integer z .

theorem *eq-minf-conjI*: $\exists z1::int. \forall x. x < z1 \longrightarrow (A1\ x = A2\ x) \Longrightarrow$
 $\exists z2::int. \forall x. x < z2 \longrightarrow (B1\ x = B2\ x) \Longrightarrow$
 $\exists z::int. \forall x. x < z \longrightarrow ((A1\ x \wedge B1\ x) = (A2\ x \wedge B2\ x))$
 $\langle proof \rangle$

theorem *eq-minf-disjI*: $\exists z1::int. \forall x. x < z1 \longrightarrow (A1\ x = A2\ x) \Longrightarrow$
 $\exists z2::int. \forall x. x < z2 \longrightarrow (B1\ x = B2\ x) \Longrightarrow$
 $\exists z::int. \forall x. x < z \longrightarrow ((A1\ x \vee B1\ x) = (A2\ x \vee B2\ x))$
 $\langle proof \rangle$

Theorems for the combination of proofs of the equality of P and $P\text{-}m$ for integers x greather than some integer z .

theorem *eq-pinf-conjI*: $\exists z1::int. \forall x. z1 < x \longrightarrow (A1\ x = A2\ x) \Longrightarrow$
 $\exists z2::int. \forall x. z2 < x \longrightarrow (B1\ x = B2\ x) \Longrightarrow$
 $\exists z::int. \forall x. z < x \longrightarrow ((A1\ x \wedge B1\ x) = (A2\ x \wedge B2\ x))$
 $\langle proof \rangle$

theorem *eq-pinf-disjI*: $\exists z1::int. \forall x. z1 < x \longrightarrow (A1\ x = A2\ x) \Longrightarrow$
 $\exists z2::int. \forall x. z2 < x \longrightarrow (B1\ x = B2\ x) \Longrightarrow$
 $\exists z::int. \forall x. z < x \longrightarrow ((A1\ x \vee B1\ x) = (A2\ x \vee B2\ x))$
 $\langle proof \rangle$

Theorems for the combination of proofs of the modulo D property for P *plusinfinity*

FIXME: This is THE SAME theorem as for the *minusinf* version, but with $+k..$ instead of $-k..$. In the future replace these both with only one.

theorem *modd-pinf-conjI*: $\forall (x::int) k. A\ x = A\ (x+k*d) \Longrightarrow$
 $\forall (x::int) k. B\ x = B\ (x+k*d) \Longrightarrow$
 $\forall (x::int) (k::int). (A\ x \wedge B\ x) = (A\ (x+k*d) \wedge B\ (x+k*d))$
 $\langle proof \rangle$

theorem *modd-pinf-disjI*: $\forall (x::int) k. A\ x = A\ (x+k*d) \Longrightarrow$
 $\forall (x::int) k. B\ x = B\ (x+k*d) \Longrightarrow$

$$\forall (x::int) (k::int). (A \ x \vee B \ x) = (A \ (x+k*d) \vee B \ (x+k*d))$$

⟨proof⟩

This is one of the cases where the simplified formula is proved to have some property (in relation to $P\text{-}m$) but we need to prove the property for the original formula ($P\text{-}m$)

FIXME: This is exactly the same thm as for *minusinf*.

lemma *pinf-simp-eq*: $ALL \ x. P(x) = Q(x) \implies (EX \ (x::int). P(x)) \dashrightarrow (EX \ (x::int). F(x)) \implies (EX \ (x::int). Q(x)) \dashrightarrow (EX \ (x::int). F(x))$

⟨proof⟩

Theorems for the combination of proofs of the modulo D property for P *minusinfinity*

theorem *modd-minf-conjI*: $\forall (x::int) \ k. A \ x = A \ (x-k*d) \implies$
 $\forall (x::int) \ k. B \ x = B \ (x-k*d) \implies$
 $\forall (x::int) (k::int). (A \ x \wedge B \ x) = (A \ (x-k*d) \wedge B \ (x-k*d))$

⟨proof⟩

theorem *modd-minf-disjI*: $\forall (x::int) \ k. A \ x = A \ (x-k*d) \implies$
 $\forall (x::int) \ k. B \ x = B \ (x-k*d) \implies$
 $\forall (x::int) (k::int). (A \ x \vee B \ x) = (A \ (x-k*d) \vee B \ (x-k*d))$

⟨proof⟩

This is one of the cases where the simplified formula is proved to have some property (in relation to $P\text{-}m$) but we need to prove the property for the original formula ($P\text{-}m$).

lemma *minf-simp-eq*: $ALL \ x. P(x) = Q(x) \implies (EX \ (x::int). P(x)) \dashrightarrow (EX \ (x::int). F(x)) \implies (EX \ (x::int). Q(x)) \dashrightarrow (EX \ (x::int). F(x))$

⟨proof⟩

Theorem needed for proving at runtime divide properties using the arithmetic tactic (which knows only about modulo $= 0$).

lemma *zdvd-iff-zmod-eq-0*: $(m \ \text{dvd} \ n) = (n \ \text{mod} \ m = (0::int))$

⟨proof⟩

Theorems used for the combination of proof for the backwards direction of Cooper’s Theorem. They rely exclusively on Predicate calculus.

lemma *not-ast-p-disjI*: $(ALL \ x. Q(x::int) \wedge \sim (EX \ (j::int) : \{1..d\}. EX \ (a::int) : A. Q(a - j))) \dashrightarrow P1(x) \dashrightarrow P1(x + d)$

\implies

$(ALL \ x. Q(x::int) \wedge \sim (EX \ (j::int) : \{1..d\}. EX \ (a::int) : A. Q(a - j))) \dashrightarrow P2(x) \dashrightarrow P2(x + d)$

\implies

$(ALL \ x. Q(x::int) \wedge \sim (EX \ (j::int) : \{1..d\}. EX \ (a::int) : A. Q(a - j))) \dashrightarrow (P1(x) \vee P2(x)) \dashrightarrow (P1(x + d) \vee P2(x + d))$

⟨proof⟩

lemma not-ast-p-conjI: $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ Q(a - j)) \dashv\vdash P1(x) \dashv\vdash P1(x + d))$
 \implies
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ Q(a - j)) \dashv\vdash P2(x) \dashv\vdash P2(x + d))$
 \implies
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ Q(a - j)) \dashv\vdash (P1(x) \wedge P2(x)) \dashv\vdash (P1(x + d) \wedge P2(x + d)))$
 $\langle proof \rangle$

lemma not-ast-p-Q-elim:
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ Q(a - j)) \dashv\vdash P(x) \dashv\vdash P(x + d))$
 $\implies (P = Q)$
 $\implies (ALL\ x.\ \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ P(a - j)) \dashv\vdash P(x) \dashv\vdash P(x + d))$
 $\langle proof \rangle$

Theorems used for the combination of proof for the backwards direction of Cooper’s Theorem. They rely exclusively on Predicate calculus.

lemma not-bst-p-disjI: $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash P1(x) \dashv\vdash P1(x - d))$
 \implies
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash P2(x) \dashv\vdash P2(x - d))$
 \implies
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash (P1(x) \vee P2(x)) \dashv\vdash (P1(x - d) \vee P2(x - d)))$
 $\langle proof \rangle$

lemma not-bst-p-conjI: $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash P1(x) \dashv\vdash P1(x - d))$
 \implies
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash P2(x) \dashv\vdash P2(x - d))$
 \implies
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash (P1(x) \wedge P2(x)) \dashv\vdash (P1(x - d) \wedge P2(x - d)))$
 $\langle proof \rangle$

lemma not-bst-p-Q-elim:
 $(ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \dashv\vdash P(x) \dashv\vdash P(x - d))$
 $\implies (P = Q)$

$\implies (ALL\ x. \sim(EX\ (j::int) : \{1..d\}. EX\ (b::int) : B. P(b+j)) \dashv\dashv P(x) \dashv\dashv P(x - d))$
 $\langle proof \rangle$

This is the first direction of Cooper’s Theorem.

lemma *cooper-thm*: $(R \dashv\dashv (EX\ x::int. P\ x)) \implies (Q \dashv\dashv (EX\ x::int. P\ x)) \implies ((R|Q) \dashv\dashv (EX\ x::int. P\ x))$
 $\langle proof \rangle$

The full Cooper’s Theorem in its equivalence Form. Given the premises it is trivial too, it relies exclusively on prediacte calculus.

lemma *cooper-eq-thm*: $(R \dashv\dashv (EX\ x::int. P\ x)) \implies (Q \dashv\dashv (EX\ x::int. P\ x)) \implies ((\sim Q) \dashv\dashv (EX\ x::int. P\ x) \dashv\dashv R) \implies (EX\ x::int. P\ x) = R|Q$
 $\langle proof \rangle$

Some of the atomic theorems generated each time the atom does not depend on x , they are trivial.

lemma *fm-eq-minf*: $EX\ z::int. ALL\ x. x < z \dashv\dashv (P = P)$
 $\langle proof \rangle$

lemma *fm-modd-minf*: $ALL\ (x::int). ALL\ (k::int). (P = P)$
 $\langle proof \rangle$

lemma *not-bst-p-fm*: $ALL\ (x::int). Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}. EX\ (b::int) : B. Q(b+j)) \dashv\dashv fm \dashv\dashv fm$
 $\langle proof \rangle$

lemma *fm-eq-pinf*: $EX\ z::int. ALL\ x. z < x \dashv\dashv (P = P)$
 $\langle proof \rangle$

The next two thms are the same as the *minusinf* version.

lemma *fm-modd-pinf*: $ALL\ (x::int). ALL\ (k::int). (P = P)$
 $\langle proof \rangle$

lemma *not-ast-p-fm*: $ALL\ (x::int). Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}. EX\ (a::int) : A. Q(a - j)) \dashv\dashv fm \dashv\dashv fm$
 $\langle proof \rangle$

Theorems to be deleted from simpset when proving simplified formulaes.

lemma *P-eqtrue*: $(P = True) = P$
 $\langle proof \rangle$

lemma *P-eqfalse*: $(P = False) = (\sim P)$
 $\langle proof \rangle$

Theorems for the generation of the backwards direction of Cooper’s Theorem.

These are the 6 interesting atomic cases which have to be proved relying on the properties of B-set and the arithmetic and contradiction proofs.

lemma not-bst-p-lt: $0 < (d::int) ==>$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \longrightarrow (0 < -x + a) \longrightarrow (0 < -(x - d) + a)$
 $\langle proof \rangle$

lemma not-bst-p-gt: $\llbracket (g::int) \in B; g = -a \rrbracket \implies$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \longrightarrow (0 < (x) + a) \longrightarrow (0 < (x - d) + a)$
 $\langle proof \rangle$

lemma not-bst-p-eq: $\llbracket 0 < d; (g::int) \in B; g = -a - 1 \rrbracket \implies$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \longrightarrow (0 = x + a) \longrightarrow (0 = (x - d) + a)$
 $\langle proof \rangle$

lemma not-bst-p-ne: $\llbracket 0 < d; (g::int) \in B; g = -a \rrbracket \implies$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \longrightarrow \sim(0 = x + a) \longrightarrow \sim(0 = (x - d) + a)$
 $\langle proof \rangle$

lemma not-bst-p-dvd: $(d1::int)\ dvd\ d ==>$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \longrightarrow d1\ dvd\ (x + a) \longrightarrow d1\ dvd\ ((x - d) + a)$
 $\langle proof \rangle$

lemma not-bst-p-ndvd: $(d1::int)\ dvd\ d ==>$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (b::int) : B.\ Q(b+j)) \longrightarrow \sim(d1\ dvd\ (x + a)) \longrightarrow \sim(d1\ dvd\ ((x - d) + a))$
 $\langle proof \rangle$

Theorems for the generation of the backwards direction of Cooper’s Theorem.

These are the 6 interesting atomic cases which have to be proved relying on the properties of A-set and the arithmetic and contradiction proofs.

lemma not-ast-p-gt: $0 < (d::int) ==>$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ Q(a - j)) \longrightarrow (0 < x + t) \longrightarrow (0 < (x + d) + t)$
 $\langle proof \rangle$

lemma not-ast-p-lt: $\llbracket 0 < d; (t::int) \in A \rrbracket \implies$
 $ALL\ x.\ Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}.\ EX\ (a::int) : A.\ Q(a - j)) \longrightarrow (0$

$< -x + t \rangle \dashrightarrow (\ 0 < -(x + d) + t)$
 $\langle proof \rangle$

lemma *not-ast-p-eq*: $\llbracket 0 < d; (g::int) \in A; g = -t + 1 \rrbracket \implies$
 $ALL\ x. Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}. EX\ (a::int) : A. Q(a - j)) \dashrightarrow (0$
 $= x + t) \dashrightarrow (0 = (x + d) + t)$
 $\langle proof \rangle$

lemma *not-ast-p-ne*: $\llbracket 0 < d; (g::int) \in A; g = -t \rrbracket \implies$
 $ALL\ x. Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}. EX\ (a::int) : A. Q(a - j)) \dashrightarrow \sim(0$
 $= x + t) \dashrightarrow \sim(0 = (x + d) + t)$
 $\langle proof \rangle$

lemma *not-ast-p-dvd*: $(d1::int)\ dvd\ d \implies$
 $ALL\ x. Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}. EX\ (a::int) : A. Q(a - j)) \dashrightarrow d1$
 $dvd\ (x + t) \dashrightarrow d1\ dvd\ ((x + d) + t)$
 $\langle proof \rangle$

lemma *not-ast-p-ndvd*: $(d1::int)\ dvd\ d \implies$
 $ALL\ x. Q(x::int) \wedge \sim(EX\ (j::int) : \{1..d\}. EX\ (a::int) : A. Q(a - j)) \dashrightarrow$
 $\sim(d1\ dvd\ (x + t)) \dashrightarrow \sim(d1\ dvd\ ((x + d) + t))$
 $\langle proof \rangle$

These are the atomic cases for the proof generation for the modulo D property for P *plusinfinity*

They are fully based on arithmetics.

lemma *dvd-modd-pinf*: $((d::int)\ dvd\ d1) \implies$
 $(ALL\ (x::int). ALL\ (k::int). (((d::int)\ dvd\ (x + t)) = (d\ dvd\ (x + k*d1 + t))))$
 $\langle proof \rangle$

lemma *not-dvd-modd-pinf*: $((d::int)\ dvd\ d1) \implies$
 $(ALL\ (x::int). ALL\ k. (\sim((d::int)\ dvd\ (x + t))) = (\sim(d\ dvd\ (x + k*d1 + t))))$
 $\langle proof \rangle$

These are the atomic cases for the proof generation for the equivalence of P and P *plusinfinity* for integers x greater than some integer z .

They are fully based on arithmetics.

lemma *eq-eq-pinf*: $EX\ z::int. ALL\ x. z < x \dashrightarrow ((\ 0 = x + t) = False)$
 $\langle proof \rangle$

lemma *neq-eq-pinf*: $EX\ z::int. ALL\ x. z < x \dashrightarrow ((\sim(\ 0 = x + t)) = True)$
 $\langle proof \rangle$

lemma *le-eq-pinf*: $EX\ z::int. ALL\ x. z < x \dashrightarrow (\ 0 < x + t = True)$
 $\langle proof \rangle$

lemma *len-eq-pinf*: $EX\ z::int. ALL\ x. z < x \dashrightarrow (0 < -x + t = False)$

$\langle proof \rangle$

lemma *dvd-eq-pinf*: $EX\ z::int. ALL\ x. z < x \longrightarrow ((d\ dvd\ (x + t)) = (d\ dvd\ (x + t)))$
 $\langle proof \rangle$

lemma *not-dvd-eq-pinf*: $EX\ z::int. ALL\ x. z < x \longrightarrow ((\sim(d\ dvd\ (x + t))) = (\sim(d\ dvd\ (x + t))))$
 $\langle proof \rangle$

These are the atomic cases for the proof generation for the modulo D property for $P\ minusinfinity$.

They are fully based on arithmetics.

lemma *dvd-modd-minf*: $((d::int)\ dvd\ d1) ==>$
 $(ALL\ (x::int). ALL\ (k::int). (((d::int)\ dvd\ (x + t)) = (d\ dvd\ (x - k*d1 + t))))$
 $\langle proof \rangle$

lemma *not-dvd-modd-minf*: $((d::int)\ dvd\ d1) ==>$
 $(ALL\ (x::int). ALL\ k. (\sim((d::int)\ dvd\ (x + t))) = (\sim(d\ dvd\ (x - k*d1 + t))))$
 $\langle proof \rangle$

These are the atomic cases for the proof generation for the equivalence of P and $P\ minusinfinity$ for integers x less than some integer z .

They are fully based on arithmetics.

lemma *eq-eq-minf*: $EX\ z::int. ALL\ x. x < z \longrightarrow ((0 = x + t) = False)$
 $\langle proof \rangle$

lemma *neq-eq-minf*: $EX\ z::int. ALL\ x. x < z \longrightarrow ((\sim(0 = x + t)) = True)$
 $\langle proof \rangle$

lemma *le-eq-minf*: $EX\ z::int. ALL\ x. x < z \longrightarrow (0 < x + t = False)$
 $\langle proof \rangle$

lemma *len-eq-minf*: $EX\ z::int. ALL\ x. x < z \longrightarrow (0 < -x + t = True)$
 $\langle proof \rangle$

lemma *dvd-eq-minf*: $EX\ z::int. ALL\ x. x < z \longrightarrow ((d\ dvd\ (x + t)) = (d\ dvd\ (x + t)))$
 $\langle proof \rangle$

lemma *not-dvd-eq-minf*: $EX\ z::int. ALL\ x. x < z \longrightarrow ((\sim(d\ dvd\ (x + t))) = (\sim(d\ dvd\ (x + t))))$
 $\langle proof \rangle$

This Theorem combines whithnesses about $P\ minusinfinity$ to show one component of the equivalence proof for Cooper’s Theorem.

FIXME: remove once they are part of the distribution.

theorem *int-ge-induct*[consumes 1, case-names base step]:

assumes *ge*: $k \leq (i::int)$ and
 base: $P(k)$ and
 step: $\bigwedge i. \llbracket k \leq i; P\ i \rrbracket \implies P(i+1)$
 shows $P\ i$

<proof>

theorem *int-gr-induct*[consumes 1, case-names base step]:

assumes *gr*: $k < (i::int)$ and
 base: $P(k+1)$ and
 step: $\bigwedge i. \llbracket k < i; P\ i \rrbracket \implies P(i+1)$
 shows $P\ i$

<proof>

lemma *decr-lemma*: $0 < (d::int) \implies x - (abs(x-z)+1) * d < z$

<proof>

lemma *incr-lemma*: $0 < (d::int) \implies z < x + (abs(x-z)+1) * d$

<proof>

lemma *minusinfinity*:

assumes $0 < d$ and
 P1eqP1: $ALL\ x\ k. P1\ x = P1\ (x - k*d)$ and
 ePeqP1: $EX\ z::int. ALL\ x. x < z \longrightarrow (P\ x = P1\ x)$
 shows $(EX\ x. P1\ x) \longrightarrow (EX\ x. P\ x)$

<proof>

This Theorem combines whithnesses about P *minusinfinity* to show one component of the equivalence proof for Cooper’s Theorem.

lemma *plusinfinity*:

assumes $0 < d$ and
 P1eqP1: $ALL\ (x::int)\ (k::int). P1\ x = P1\ (x + k * d)$ and
 ePeqP1: $EX\ z::int. ALL\ x. z < x \longrightarrow (P\ x = P1\ x)$
 shows $(EX\ x::int. P1\ x) \longrightarrow (EX\ x::int. P\ x)$

<proof>

Theorem for periodic function on discrete sets.

lemma *minf-vee*:

assumes *dpos*: $(0::int) < d$ and *modd*: $ALL\ x\ k. P\ x = P(x - k*d)$
 shows $(EX\ x. P\ x) = (EX\ j : \{1..d\}. P\ j)$
 (is ?LHS = ?RHS)

<proof>

Theorem for periodic function on discrete sets.

lemma *pinf-vee*:

assumes *dpos*: $0 < (d::int)$ and *modd*: $ALL\ (x::int)\ (k::int). P\ x = P(x+k*d)$

shows $(EX\ x::int. P\ x) = (EX\ (j::int) : \{1..d\} . P\ j)$
(is $?LHS = ?RHS)$
 $\langle proof \rangle$

lemma *decr-mult-lemma*:
assumes $dpos: (0::int) < d$ **and**
 $minus: ALL\ x::int. P\ x \longrightarrow P(x - d)$ **and**
 $knneg: 0 \leq k$
shows $ALL\ x. P\ x \longrightarrow P(x - k*d)$
 $\langle proof \rangle$

lemma *incr-mult-lemma*:
assumes $dpos: (0::int) < d$ **and**
 $plus: ALL\ x::int. P\ x \longrightarrow P(x + d)$ **and**
 $knneg: 0 \leq k$
shows $ALL\ x. P\ x \longrightarrow P(x + k*d)$
 $\langle proof \rangle$

lemma *cpmi-eq*: $0 < D \implies (EX\ z::int. ALL\ x. x < z \dashrightarrow (P\ x = P1\ x))$
 $\implies ALL\ x. \sim (EX\ (j::int) : \{1..D\}. EX\ (b::int) : B. P(b+j)) \dashrightarrow P\ (x) \dashrightarrow$
 $P\ (x - D)$
 $\implies (ALL\ (x::int). ALL\ (k::int). ((P1\ x) = (P1\ (x-k*D))))$
 $\implies (EX\ (x::int). P(x)) = ((EX\ (j::int) : \{1..D\} . (P1(j))) \mid (EX\ (j::int) :$
 $\{1..D\}. EX\ (b::int) : B. P\ (b+j)))$
 $\langle proof \rangle$

Cooper Theorem, plus infinity version.

lemma *cppi-eq*: $0 < D \implies (EX\ z::int. ALL\ x. z < x \dashrightarrow (P\ x = P1\ x))$
 $\implies ALL\ x. \sim (EX\ (j::int) : \{1..D\}. EX\ (a::int) : A. P(a-j)) \dashrightarrow P\ (x) \dashrightarrow$
 $P\ (x + D)$
 $\implies (ALL\ (x::int). ALL\ (k::int). ((P1\ x) = (P1\ (x+k*D))))$
 $\implies (EX\ (x::int). P(x)) = ((EX\ (j::int) : \{1..D\} . (P1(j))) \mid (EX\ (j::int) :$
 $\{1..D\}. EX\ (a::int) : A. P\ (a-j)))$
 $\langle proof \rangle$

Theorems for the quantifier elimination Functions.

lemma *qe-ex-conj*: $(EX\ (x::int). A\ x) = R$
 $\implies (EX\ (x::int). P\ x) = (Q \ \& \ (EX\ x::int. A\ x))$
 $\implies (EX\ (x::int). P\ x) = (Q \ \& \ R)$
 $\langle proof \rangle$

lemma *qe-ex-nconj*: $(EX\ (x::int). P\ x) = (True \ \& \ Q)$
 $\implies (EX\ (x::int). P\ x) = Q$
 $\langle proof \rangle$

lemma *qe-conjI*: $P1 = P2 \implies Q1 = Q2 \implies (P1 \ \& \ Q1) = (P2 \ \& \ Q2)$
 $\langle proof \rangle$

lemma *qe-disjI*: $P1 = P2 \implies Q1 = Q2 \implies (P1 \mid Q1) = (P2 \mid Q2)$
 $\langle proof \rangle$

lemma *qe-impI*: $P1 = P2 \implies Q1 = Q2 \implies (P1 \dashrightarrow Q1) = (P2 \dashrightarrow Q2)$
 $\langle proof \rangle$

lemma *qe-eqI*: $P1 = P2 \implies Q1 = Q2 \implies (P1 = Q1) = (P2 = Q2)$
 $\langle proof \rangle$

lemma *qe-Not*: $P = Q \implies (\sim P) = (\sim Q)$
 $\langle proof \rangle$

lemma *qe-ALL*: $(EX\ x. \sim P\ x) = R \implies (ALL\ x. P\ x) = (\sim R)$
 $\langle proof \rangle$

Theorems for proving NNF

lemma *nnf-im*: $((\sim P) = P1) \implies (Q = Q1) \implies ((P \dashrightarrow Q) = (P1 \mid Q1))$
 $\langle proof \rangle$

lemma *nnf-eq*: $((P \& Q) = (P1 \& Q1)) \implies (((\sim P) \& (\sim Q)) = (P2 \& Q2))$
 $\implies ((P = Q) = ((P1 \& Q1) \mid (P2 \& Q2)))$
 $\langle proof \rangle$

lemma *nnf-nn*: $(P = Q) \implies ((\sim \sim P) = Q)$
 $\langle proof \rangle$

lemma *nnf-ncj*: $((\sim P) = P1) \implies ((\sim Q) = Q1) \implies ((\sim(P \& Q)) = (P1 \mid Q1))$
 $\langle proof \rangle$

lemma *nnf-ndj*: $((\sim P) = P1) \implies ((\sim Q) = Q1) \implies ((\sim(P \mid Q)) = (P1 \& Q1))$
 $\langle proof \rangle$

lemma *nnf-nim*: $(P = P1) \implies ((\sim Q) = Q1) \implies ((\sim(P \dashrightarrow Q)) = (P1 \& Q1))$
 $\langle proof \rangle$

lemma *nnf-neq*: $((P \& (\sim Q)) = (P1 \& Q1)) \implies (((\sim P) \& Q) = (P2 \& Q2))$
 $\implies ((\sim(P = Q)) = ((P1 \& Q1) \mid (P2 \& Q2)))$
 $\langle proof \rangle$

lemma *nnf-sdj*: $((A \& (\sim B)) = (A1 \& B1)) \implies ((C \& (\sim D)) = (C1 \& D1))$
 $\implies (A = (\sim C)) \implies ((\sim((A \& B) \mid (C \& D))) = ((A1 \& B1) \mid (C1 \& D1)))$
 $\langle proof \rangle$

lemma *qe-exI2*: $A = B \implies (EX\ (x::int). A(x)) = (EX\ (x::int). B(x))$
 $\langle proof \rangle$

lemma *qe-exI*: $(!!x::int. A\ x = B\ x) \implies (EX\ (x::int). A(x)) = (EX\ (x::int). B(x))$

$\langle \text{proof} \rangle$

lemma *qe-ALLI*: $(\forall x::\text{int}. A\ x = B\ x) \implies (ALL\ (x::\text{int}). A(x)) = (ALL\ (x::\text{int}). B(x))$
 $\langle \text{proof} \rangle$

lemma *cp-expand*: $(EX\ (x::\text{int}). P\ (x)) = (EX\ (j::\text{int}) : \{1..d\}. EX\ (b::\text{int}) : B. (P1\ (j) \mid P(b+j)))$
 $\implies (EX\ (x::\text{int}). P\ (x)) = (EX\ (j::\text{int}) : \{1..d\}. EX\ (b::\text{int}) : B. (P1\ (j) \mid P(b+j)))$
 $\langle \text{proof} \rangle$

lemma *cp-pi-expand*: $(EX\ (x::\text{int}). P\ (x)) = (EX\ (j::\text{int}) : \{1..d\}. EX\ (a::\text{int}) : A. (P1\ (j) \mid P(a-j)))$
 $\implies (EX\ (x::\text{int}). P\ (x)) = (EX\ (j::\text{int}) : \{1..d\}. EX\ (a::\text{int}) : A. (P1\ (j) \mid P(a-j)))$
 $\langle \text{proof} \rangle$

lemma *simp-from-to*: $\{i..j::\text{int}\} = (\text{if } j < i \text{ then } \{\} \text{ else insert } i\ \{i+1..j\})$
 $\langle \text{proof} \rangle$

Theorems required for the *adjustcoefficienteq*

lemma *ac-dvd-eq*: **assumes** *not0*: $0 \sim (k::\text{int})$
shows $((m::\text{int})\ \text{dvd}\ (c*n+t)) = (k*m\ \text{dvd}\ ((k*c)*n+(k*t)))$ (**is** $?P = ?Q$)
 $\langle \text{proof} \rangle$

lemma *ac-lt-eq*: **assumes** *gr0*: $0 < (k::\text{int})$
shows $((m::\text{int}) < (c*n+t)) = (k*m < ((k*c)*n+(k*t)))$ (**is** $?P = ?Q$)
 $\langle \text{proof} \rangle$

lemma *ac-eq-eq* : **assumes** *not0*: $0 \sim (k::\text{int})$ **shows** $((m::\text{int}) = (c*n+t)) = (k*m = ((k*c)*n+(k*t)))$ (**is** $?P = ?Q$)
 $\langle \text{proof} \rangle$

lemma *ac-pi-eq*: **assumes** *gr0*: $0 < (k::\text{int})$ **shows** $(\sim((0::\text{int}) < (c*n + t))) = (0 < ((-k)*c)*n + ((-k)*t + k))$
 $\langle \text{proof} \rangle$

lemma *binminus-uminus-conv*: $(a::\text{int}) - b = a + (-b)$
 $\langle \text{proof} \rangle$

lemma *linearize-dvd*: $(t::\text{int}) = t1 \implies (d\ \text{dvd}\ t) = (d\ \text{dvd}\ t1)$
 $\langle \text{proof} \rangle$

lemma *lf-lt*: $(l::\text{int}) = ll \implies (r::\text{int}) = lr \implies (l < r) = (ll < lr)$
 $\langle \text{proof} \rangle$

lemma *lf-eq*: $(l::int) = ll \implies (r::int) = lr \implies (l = r) = (ll = lr)$
 $\langle proof \rangle$

lemma *lf-dvd*: $(l::int) = ll \implies (r::int) = lr \implies (l \text{ dvd } r) = (ll \text{ dvd } lr)$
 $\langle proof \rangle$

Theorems for transforming predicates on *nat* to predicates on *int*

theorem *all-nat*: $(\forall x::nat. P\ x) = (\forall x::int. 0 \leq x \longrightarrow P\ (nat\ x))$
 $\langle proof \rangle$

theorem *ex-nat*: $(\exists x::nat. P\ x) = (\exists x::int. 0 \leq x \wedge P\ (nat\ x))$
 $\langle proof \rangle$

theorem *zdiff-int-split*: $P\ (int\ (x - y)) =$
 $((y \leq x \longrightarrow P\ (int\ x - int\ y)) \wedge (x < y \longrightarrow P\ 0))$
 $\langle proof \rangle$

theorem *zdvd-int*: $(x \text{ dvd } y) = (int\ x \text{ dvd } int\ y)$
 $\langle proof \rangle$

theorem *number-of1*: $(0::int) \leq number-of\ n \implies (0::int) \leq number-of\ (n\ BIT\ b)$
 $\langle proof \rangle$

theorem *number-of2*: $(0::int) \leq Numeral0\ \langle proof \rangle$

theorem *Suc-plus1*: $Suc\ n = n + 1\ \langle proof \rangle$

Specific instances of congruence rules, to prevent simplifier from looping.

theorem *imp-le-cong*: $(0 \leq x \implies P = P') \implies (0 \leq (x::int) \longrightarrow P) = (0 \leq x \longrightarrow P')$
 $\langle proof \rangle$

theorem *conj-le-cong*: $(0 \leq x \implies P = P') \implies (0 \leq (x::int) \wedge P) = (0 \leq x \wedge P')$
 $\langle proof \rangle$

$\langle ML \rangle$

end

33 Relation-Power: Powers of Relations and Functions

theory *Relation-Power*

imports *Nat*
begin

instance
 $set :: (type) \text{ power } \langle proof \rangle$

primrec (*relpow*)
 $R^0 = Id$
 $R^{(Suc\ n)} = R \circ (R^n)$

instance
 $fun :: (type, type) \text{ power } \langle proof \rangle$

primrec (*funpow*)
 $f^0 = id$
 $f^{(Suc\ n)} = f \circ (f^n)$

WARNING: due to the limits of Isabelle’s type classes, exponentiation on functions and relations has too general a domain, namely $(‘a \times ‘b)$ *set* and $‘a \Rightarrow ‘b$. Explicit type constraints may therefore be necessary. For example, $range\ (f^n) = A$ and $Range\ (R^n) = B$ need constraints.

lemma *funpow-add*: $f^{(m+n)} = f^m \circ f^n$
 $\langle proof \rangle$

lemma *rel-pow-1*: $!!R:: (‘a * ‘a) \text{ set}. R^1 = R$
 $\langle proof \rangle$

declare *rel-pow-1* [*simp*]

lemma *rel-pow-0-I*: $(x, x) : R^0$
 $\langle proof \rangle$

lemma *rel-pow-Suc-I*: $[(x, y) : R^n; (y, z) : R] \implies (x, z) : R^{(Suc\ n)}$
 $\langle proof \rangle$

lemma *rel-pow-Suc-I2* [*rule-format*]:
 $\forall z. (x, y) : R \longrightarrow (y, z) : R^n \longrightarrow (x, z) : R^{(Suc\ n)}$
 $\langle proof \rangle$

lemma *rel-pow-0-E*: $[(x, y) : R^0; x=y] \implies P \implies P$
 $\langle proof \rangle$

lemma *rel-pow-Suc-E*:
 $[(x, z) : R^{(Suc\ n)}; !!y. [(x, y) : R^n; (y, z) : R] \implies P] \implies P$
 $\langle proof \rangle$

lemma *rel-pow-E*:

$$\begin{aligned} & \llbracket (x,z) : R^n; \llbracket n=0; x = z \rrbracket \implies P; \\ & \quad !!y m. \llbracket n = \text{Suc } m; (x,y) : R^m; (y,z) : R \rrbracket \implies P \\ & \llbracket \rrbracket \implies P \\ & \langle \text{proof} \rangle \end{aligned}$$

lemma *rel-pow-Suc-D2* [rule-format]:

$$\forall x z. (x,z):R^{\wedge}(\text{Suc } n) \dashv\dashv \longrightarrow (\exists y. (x,y):R \ \& \ (y,z):R^n)$$

$$\langle \text{proof} \rangle$$

lemma *rel-pow-Suc-D2'*:

$$\forall x y z. (x,y) : R^n \ \& \ (y,z) : R \dashv\dashv \longrightarrow (\exists w. (x,w) : R \ \& \ (w,z) : R^n)$$

$$\langle \text{proof} \rangle$$

lemma *rel-pow-E2*:

$$\begin{aligned} & \llbracket (x,z) : R^n; \llbracket n=0; x = z \rrbracket \implies P; \\ & \quad !!y m. \llbracket n = \text{Suc } m; (x,y) : R; (y,z) : R^m \rrbracket \implies P \\ & \llbracket \rrbracket \implies P \\ & \langle \text{proof} \rangle \end{aligned}$$

lemma *rtrancl-imp-UN-rel-pow*: $!!p. p:R^{\wedge}* \implies p : (UN\ n. R^n)$

$$\langle \text{proof} \rangle$$

lemma *rel-pow-imp-rtrancl*: $!!p. p:R^n \implies p:R^{\wedge}* \langle \text{proof} \rangle$

lemma *rtrancl-is-UN-rel-pow*: $R^{\wedge}* = (UN\ n. R^n)$

$$\langle \text{proof} \rangle$$

lemma *single-valued-rel-pow* [rule-format]:

$$!!r::('a * 'a)\text{set}. \text{single-valued } r \implies \text{single-valued } (r^n)$$

$$\langle \text{proof} \rangle$$

$$\langle ML \rangle$$

end

34 Parity: Even and Odd for ints and nats

theory *Parity*

imports *Divides IntDiv NatSimprocs*

begin

axclass *even-odd* < type

instance *int* :: *even-odd* $\langle \text{proof} \rangle$

instance *nat* :: *even-odd* $\langle \text{proof} \rangle$

consts

even :: 'a::even-odd ==> bool

syntax

odd :: 'a::even-odd ==> bool

translations

odd *x* == \sim *even* *x*

defs (overloaded)

even-def: *even* (*x*::int) == *x* mod 2 = 0

even-nat-def: *even* (*x*::nat) == *even* (int *x*)

34.1 Even and odd are mutually exclusive

lemma *int-pos-lt-two-imp-zero-or-one*:

$0 <= x ==> (x::int) < 2 ==> x = 0 \mid x = 1$
 <proof>

lemma *neq-one-mod-two* [simp]: $((x::int) \bmod 2 \sim= 0) = (x \bmod 2 = 1)$

<proof>

34.2 Behavior under integer arithmetic operations

lemma *even-times-anything*: *even* (*x*::int) ==> *even* (*x* * *y*)

<proof>

lemma *anything-times-even*: *even* (*y*::int) ==> *even* (*x* * *y*)

<proof>

lemma *odd-times-odd*: *odd* (*x*::int) ==> *odd* *y* ==> *odd* (*x* * *y*)

<proof>

lemma *even-product*: *even*((*x*::int) * *y*) = (*even* *x* | *even* *y*)

<proof>

lemma *even-plus-even*: *even* (*x*::int) ==> *even* *y* ==> *even* (*x* + *y*)

<proof>

lemma *even-plus-odd*: *even* (*x*::int) ==> *odd* *y* ==> *odd* (*x* + *y*)

<proof>

lemma *odd-plus-even*: *odd* (*x*::int) ==> *even* *y* ==> *odd* (*x* + *y*)

<proof>

lemma *odd-plus-odd*: *odd* (*x*::int) ==> *odd* *y* ==> *even* (*x* + *y*)

<proof>

lemma *even-sum*: *even* ((*x*::int) + *y*) = ((*even* *x* & *even* *y*) | (*odd* *x* & *odd* *y*))

$\langle \text{proof} \rangle$

lemma *even-neg*: $\text{even } (-(x::\text{int})) = \text{even } x$
 $\langle \text{proof} \rangle$

lemma *even-difference*:
 $\text{even } ((x::\text{int}) - y) = ((\text{even } x \ \& \ \text{even } y) \mid (\text{odd } x \ \& \ \text{odd } y))$
 $\langle \text{proof} \rangle$

lemma *even-pow-gt-zero* [rule-format]:
 $\text{even } (x::\text{int}) ==> 0 < n \dashv\dashv \text{even } (x^n)$
 $\langle \text{proof} \rangle$

lemma *odd-pow*: $\text{odd } x ==> \text{odd } ((x::\text{int})^n)$
 $\langle \text{proof} \rangle$

lemma *even-power*: $\text{even } ((x::\text{int})^n) = (\text{even } x \ \& \ 0 < n)$
 $\langle \text{proof} \rangle$

lemma *even-zero*: $\text{even } (0::\text{int})$
 $\langle \text{proof} \rangle$

lemma *odd-one*: $\text{odd } (1::\text{int})$
 $\langle \text{proof} \rangle$

lemmas *even-odd-simps* [simp] = *even-def*[of number-of v,standard] *even-zero*
odd-one even-product even-sum even-neg even-difference even-power

34.3 Equivalent definitions

lemma *two-times-even-div-two*: $\text{even } (x::\text{int}) ==> 2 * (x \text{ div } 2) = x$
 $\langle \text{proof} \rangle$

lemma *two-times-odd-div-two-plus-one*: $\text{odd } (x::\text{int}) ==>$
 $2 * (x \text{ div } 2) + 1 = x$
 $\langle \text{proof} \rangle$

lemma *even-equiv-def*: $\text{even } (x::\text{int}) = (EX \ y. x = 2 * y)$
 $\langle \text{proof} \rangle$

lemma *odd-equiv-def*: $\text{odd } (x::\text{int}) = (EX \ y. x = 2 * y + 1)$
 $\langle \text{proof} \rangle$

34.4 even and odd for nats

lemma *pos-int-even-equiv-nat-even*: $0 \leq x ==> \text{even } x = \text{even } (\text{nat } x)$
 $\langle \text{proof} \rangle$

lemma *even-nat-product*: $\text{even } ((x::\text{nat}) * y) = (\text{even } x \mid \text{even } y)$
 $\langle \text{proof} \rangle$

lemma *even-nat-sum*: $\text{even } ((x::\text{nat}) + y) =$
 $((\text{even } x \ \& \ \text{even } y) \mid (\text{odd } x \ \& \ \text{odd } y))$
 $\langle \text{proof} \rangle$

lemma *even-nat-difference*:
 $\text{even } ((x::\text{nat}) - y) = (x < y \mid (\text{even } x \ \& \ \text{even } y) \mid (\text{odd } x \ \& \ \text{odd } y))$
 $\langle \text{proof} \rangle$

lemma *even-nat-Suc*: $\text{even } (\text{Suc } x) = \text{odd } x$
 $\langle \text{proof} \rangle$

lemma *even-nat-power*: $\text{even } ((x::\text{nat}) ^ y) = (\text{even } x \ \& \ 0 < y)$
 $\langle \text{proof} \rangle$

lemma *even-nat-zero*: $\text{even } (0::\text{nat})$
 $\langle \text{proof} \rangle$

lemmas *even-odd-nat-simps* [*simp*] = *even-nat-def*[*of number-of v, standard*]
even-nat-zero even-nat-Suc even-nat-product even-nat-sum even-nat-power

34.5 Equivalent definitions

lemma *nat-lt-two-imp-zero-or-one*: $(x::\text{nat}) < \text{Suc } (\text{Suc } 0) ==>$
 $x = 0 \mid x = \text{Suc } 0$
 $\langle \text{proof} \rangle$

lemma *even-nat-mod-two-eq-zero*: $\text{even } (x::\text{nat}) ==> x \bmod (\text{Suc } (\text{Suc } 0)) = 0$
 $\langle \text{proof} \rangle$

lemma *odd-nat-mod-two-eq-one*: $\text{odd } (x::\text{nat}) ==> x \bmod (\text{Suc } (\text{Suc } 0)) = \text{Suc } 0$
 $\langle \text{proof} \rangle$

lemma *even-nat-equiv-def*: $\text{even } (x::\text{nat}) = (x \bmod \text{Suc } (\text{Suc } 0) = 0)$
 $\langle \text{proof} \rangle$

lemma *odd-nat-equiv-def*: $\text{odd } (x::\text{nat}) = (x \bmod \text{Suc } (\text{Suc } 0) = \text{Suc } 0)$
 $\langle \text{proof} \rangle$

lemma *even-nat-div-two-times-two*: $\text{even } (x::\text{nat}) ==>$
 $\text{Suc } (\text{Suc } 0) * (x \text{ div } \text{Suc } (\text{Suc } 0)) = x$
 $\langle \text{proof} \rangle$

lemma *odd-nat-div-two-times-two-plus-one*: $\text{odd } (x::\text{nat}) ==>$
 $\text{Suc } (\text{Suc } (\text{Suc } 0) * (x \text{ div } \text{Suc } (\text{Suc } 0))) = x$
 $\langle \text{proof} \rangle$

lemma *even-nat-equiv-def2*: $\text{even } (x::\text{nat}) = (\text{EX } y. x = \text{Suc } (\text{Suc } 0) * y)$
 $\langle \text{proof} \rangle$

lemma *odd-nat-equiv-def2*: $\text{odd } (x::\text{nat}) = (\text{EX } y. x = \text{Suc}(\text{Suc } (\text{Suc } 0) * y))$
 $\langle \text{proof} \rangle$

34.6 Parity and powers

lemma *minus-one-even-odd-power*:
 $(\text{even } x \longrightarrow (-1::'a::\{\text{comm-ring-1}, \text{recpower}\})^x = 1) \ \&$
 $(\text{odd } x \longrightarrow (-1::'a::\{\text{comm-ring-1}, \text{recpower}\})^x = -1)$
 $\langle \text{proof} \rangle$

lemma *minus-one-even-power [simp]*:
 $\text{even } x \implies (-1::'a::\{\text{comm-ring-1}, \text{recpower}\})^x = 1$
 $\langle \text{proof} \rangle$

lemma *minus-one-odd-power [simp]*:
 $\text{odd } x \implies (-1::'a::\{\text{comm-ring-1}, \text{recpower}\})^x = -1$
 $\langle \text{proof} \rangle$

lemma *neg-one-even-odd-power*:
 $(\text{even } x \longrightarrow (-1::'a::\{\text{number-ring}, \text{recpower}\})^x = 1) \ \&$
 $(\text{odd } x \longrightarrow (-1::'a::\{\text{number-ring}, \text{recpower}\})^x = -1)$
 $\langle \text{proof} \rangle$

lemma *neg-one-even-power [simp]*:
 $\text{even } x \implies (-1::'a::\{\text{number-ring}, \text{recpower}\})^x = 1$
 $\langle \text{proof} \rangle$

lemma *neg-one-odd-power [simp]*:
 $\text{odd } x \implies (-1::'a::\{\text{number-ring}, \text{recpower}\})^x = -1$
 $\langle \text{proof} \rangle$

lemma *neg-power-if*:
 $(-x::'a::\{\text{comm-ring-1}, \text{recpower}\})^n =$
 $(\text{if even } n \text{ then } (x^{\wedge} n) \text{ else } -(x^{\wedge} n))$
 $\langle \text{proof} \rangle$

lemma *zero-le-even-power*: $\text{even } n \implies$
 $0 \leq (x::'a::\{\text{recpower}, \text{ordered-ring-strict}\})^n$
 $\langle \text{proof} \rangle$

lemma *zero-le-odd-power*: $\text{odd } n \implies$
 $(0 \leq (x::'a::\{\text{recpower}, \text{ordered-idom}\})^n) = (0 \leq x)$
 $\langle \text{proof} \rangle$

lemma *zero-le-power-eq*: $(0 \leq (x::'a::\{\text{recpower}, \text{ordered-idom}\})^n) =$
 $(\text{even } n \mid (\text{odd } n \ \& \ 0 \leq x))$
 $\langle \text{proof} \rangle$

lemma *zero-less-power-eq*: $(0 < (x::'a::\{\text{recpower}, \text{ordered-idom}\}) \wedge n) =$
 $(n = 0 \mid (\text{even } n \ \& \ x \sim= 0) \mid (\text{odd } n \ \& \ 0 < x))$
 $\langle \text{proof} \rangle$

lemma *power-less-zero-eq*: $((x::'a::\{\text{recpower}, \text{ordered-idom}\}) \wedge n < 0) =$
 $(\text{odd } n \ \& \ x < 0)$
 $\langle \text{proof} \rangle$

lemma *power-le-zero-eq*: $((x::'a::\{\text{recpower}, \text{ordered-idom}\}) \wedge n \leq 0) =$
 $(n \sim= 0 \ \& \ ((\text{odd } n \ \& \ x \leq 0) \mid (\text{even } n \ \& \ x = 0)))$
 $\langle \text{proof} \rangle$

lemma *power-even-abs*: $\text{even } n ==>$
 $(\text{abs } (x::'a::\{\text{recpower}, \text{ordered-idom}\})) \wedge n = x \wedge n$
 $\langle \text{proof} \rangle$

lemma *zero-less-power-nat-eq*: $(0 < (x::\text{nat}) \wedge n) = (n = 0 \mid 0 < x)$
 $\langle \text{proof} \rangle$

lemma *power-minus-even* [simp]: $\text{even } n ==>$
 $(- x) \wedge n = (x \wedge n::'a::\{\text{recpower}, \text{comm-ring-1}\})$
 $\langle \text{proof} \rangle$

lemma *power-minus-odd* [simp]: $\text{odd } n ==>$
 $(- x) \wedge n = - (x \wedge n::'a::\{\text{recpower}, \text{comm-ring-1}\})$
 $\langle \text{proof} \rangle$

lemmas *power-0-left-number-of* = *power-0-left* [of number-of w, standard]
declare *power-0-left-number-of* [simp]

lemmas *zero-le-power-eq-number-of* =
zero-le-power-eq [of - number-of w, standard]
declare *zero-le-power-eq-number-of* [simp]

lemmas *zero-less-power-eq-number-of* =
zero-less-power-eq [of - number-of w, standard]
declare *zero-less-power-eq-number-of* [simp]

lemmas *power-le-zero-eq-number-of* =
power-le-zero-eq [of - number-of w, standard]
declare *power-le-zero-eq-number-of* [simp]

lemmas *power-less-zero-eq-number-of* =
power-less-zero-eq [of - number-of w, standard]
declare *power-less-zero-eq-number-of* [simp]

lemmas *zero-less-power-nat-eq-number-of* =

zero-less-power-nat-eq [*of - number-of w, standard*]
declare *zero-less-power-nat-eq-number-of* [*simp*]

lemmas *power-eq-0-iff-number-of* = *power-eq-0-iff* [*of - number-of w, standard*]
declare *power-eq-0-iff-number-of* [*simp*]

lemmas *power-even-abs-number-of* = *power-even-abs* [*of number-of w -, standard*]
declare *power-even-abs-number-of* [*simp*]

34.7 An Equivalence for $0 \leq a^n$

lemma *even-power-le-0-imp-0*:
 $a^n (2*k) \leq (0 :: 'a :: \{\text{ordered-idom}, \text{recpower}\}) \implies a = 0$
 ⟨*proof*⟩

lemma *zero-le-power-iff*:
 $(0 \leq a^n) = (0 \leq (a :: 'a :: \{\text{ordered-idom}, \text{recpower}\}) \mid \text{even } n)$
 (is ?P n)
 ⟨*proof*⟩

34.8 Miscellaneous

lemma *even-plus-one-div-two*: *even* (*x::int*) $\implies (x + 1) \text{ div } 2 = x \text{ div } 2$
 ⟨*proof*⟩

lemma *odd-plus-one-div-two*: *odd* (*x::int*) $\implies (x + 1) \text{ div } 2 = x \text{ div } 2 + 1$
 ⟨*proof*⟩

lemma *div-Suc*: *Suc a div c* = *a div c* + *Suc 0 div c* +
 (*a mod c* + *Suc 0 mod c*) *div c*
 ⟨*proof*⟩

lemma *even-nat-plus-one-div-two*: *even* (*x::nat*) \implies
 (*Suc x*) *div Suc* (*Suc 0*) = *x div Suc* (*Suc 0*)
 ⟨*proof*⟩

lemma *odd-nat-plus-one-div-two*: *odd* (*x::nat*) \implies
 (*Suc x*) *div Suc* (*Suc 0*) = *Suc* (*x div Suc* (*Suc 0*))
 ⟨*proof*⟩

end

35 GCD: The Greatest Common Divisor

theory *GCD*
imports *Parity*
begin

See [1].

consts

$gcd :: nat \times nat \Rightarrow nat$ — Euclid’s algorithm

recdef gcd *measure* $((\lambda(m, n). n) :: nat \times nat \Rightarrow nat)$

$gcd (m, n) = (if\ n = 0\ then\ m\ else\ gcd\ (n, m\ mod\ n))$

constdefs

$is-gcd :: nat \Rightarrow nat \Rightarrow nat \Rightarrow bool$ — gcd as a relation

$is-gcd\ p\ m\ n == p\ dvd\ m \wedge p\ dvd\ n \wedge$
 $(\forall d. d\ dvd\ m \wedge d\ dvd\ n \longrightarrow d\ dvd\ p)$

lemma $gcd-induct$:

$(!!m. P\ m\ 0) ==>$

$(!!m\ n. 0 < n ==> P\ n\ (m\ mod\ n) ==> P\ m\ n)$

$==> P\ (m::nat)\ (n::nat)$

$\langle proof \rangle$

lemma $gcd-0$ [*simp*]: $gcd\ (m, 0) = m$

$\langle proof \rangle$

lemma $gcd-non-0$: $0 < n ==> gcd\ (m, n) = gcd\ (n, m\ mod\ n)$

$\langle proof \rangle$

declare $gcd.simps$ [*simp del*]

lemma $gcd-1$ [*simp*]: $gcd\ (m, Suc\ 0) = 1$

$\langle proof \rangle$

$gcd\ (m, n)$ divides m and n . The conjunctions don’t seem provable separately.

lemma $gcd-dvd1$ [*iff*]: $gcd\ (m, n)\ dvd\ m$

and $gcd-dvd2$ [*iff*]: $gcd\ (m, n)\ dvd\ n$

$\langle proof \rangle$

Maximality: for all m, n, k naturals, if k divides m and k divides n then k divides $gcd\ (m, n)$.

lemma $gcd-greatest$: $k\ dvd\ m ==> k\ dvd\ n ==> k\ dvd\ gcd\ (m, n)$

$\langle proof \rangle$

lemma $gcd-greatest-iff$ [*iff*]: $(k\ dvd\ gcd\ (m, n)) = (k\ dvd\ m \wedge k\ dvd\ n)$

$\langle proof \rangle$

lemma $gcd-zero$: $(gcd\ (m, n) = 0) = (m = 0 \wedge n = 0)$

$\langle proof \rangle$

Function gcd yields the Greatest Common Divisor.

lemma *is-gcd*: *is-gcd* (gcd (m, n)) m n
 $\langle proof \rangle$

Uniqueness of GCDs.

lemma *is-gcd-unique*: *is-gcd* m a b \implies *is-gcd* n a b \implies m = n
 $\langle proof \rangle$

lemma *is-gcd-dvd*: *is-gcd* m a b \implies k dvd a \implies k dvd b \implies k dvd m
 $\langle proof \rangle$

Commutativity

lemma *is-gcd-commute*: *is-gcd* k m n = *is-gcd* k n m
 $\langle proof \rangle$

lemma *gcd-commute*: gcd (m, n) = gcd (n, m)
 $\langle proof \rangle$

lemma *gcd-assoc*: gcd (gcd (k, m), n) = gcd (k, gcd (m, n))
 $\langle proof \rangle$

lemma *gcd-0-left* [simp]: gcd (0, m) = m
 $\langle proof \rangle$

lemma *gcd-1-left* [simp]: gcd (Suc 0, m) = 1
 $\langle proof \rangle$

Multiplication laws

lemma *gcd-mult-distrib2*: k * gcd (m, n) = gcd (k * m, k * n)
 — [1, page 27]
 $\langle proof \rangle$

lemma *gcd-mult* [simp]: gcd (k, k * n) = k
 $\langle proof \rangle$

lemma *gcd-self* [simp]: gcd (k, k) = k
 $\langle proof \rangle$

lemma *relprime-dvd-mult*: gcd (k, n) = 1 \implies k dvd m * n \implies k dvd m
 $\langle proof \rangle$

lemma *relprime-dvd-mult-iff*: gcd (k, n) = 1 \implies (k dvd m * n) = (k dvd m)
 $\langle proof \rangle$

lemma *gcd-mult-cancel*: $\text{gcd } (k, n) = 1 \implies \text{gcd } (k * m, n) = \text{gcd } (m, n)$
 ⟨proof⟩

Addition laws

lemma *gcd-add1* [simp]: $\text{gcd } (m + n, n) = \text{gcd } (m, n)$
 ⟨proof⟩

lemma *gcd-add2* [simp]: $\text{gcd } (m, m + n) = \text{gcd } (m, n)$
 ⟨proof⟩

lemma *gcd-add2'* [simp]: $\text{gcd } (m, n + m) = \text{gcd } (m, n)$
 ⟨proof⟩

lemma *gcd-add-mult*: $\text{gcd } (m, k * m + n) = \text{gcd } (m, n)$
 ⟨proof⟩

end

36 Binomial: Binomial Coefficients

theory *Binomial*
imports *GCD*
begin

This development is based on the work of Andy Gordon and Florian Kam-mueller

consts
binomial :: $\text{nat} \Rightarrow \text{nat} \Rightarrow \text{nat}$ (**infixl** *choose* 65)

primrec
binomial-0: $(0 \text{ choose } k) = (\text{if } k = 0 \text{ then } 1 \text{ else } 0)$
binomial-Suc: $(\text{Suc } n \text{ choose } k) =$
 $(\text{if } k = 0 \text{ then } 1 \text{ else } (n \text{ choose } (k - 1)) + (n \text{ choose } k))$

lemma *binomial-n-0* [simp]: $(n \text{ choose } 0) = 1$
 ⟨proof⟩

lemma *binomial-0-Suc* [simp]: $(0 \text{ choose } \text{Suc } k) = 0$
 ⟨proof⟩

lemma *binomial-Suc-Suc* [simp]:
 $(\text{Suc } n \text{ choose } \text{Suc } k) = (n \text{ choose } k) + (n \text{ choose } \text{Suc } k)$
 ⟨proof⟩

lemma *binomial-eq-0* [rule-format]: $\forall k. n < k \implies (n \text{ choose } k) = 0$
 ⟨proof⟩

declare *binomial-0* [*simp del*] *binomial-Suc* [*simp del*]

lemma *binomial-n-n* [*simp*]: $(n \text{ choose } n) = 1$
 $\langle \text{proof} \rangle$

lemma *binomial-Suc-n* [*simp*]: $(\text{Suc } n \text{ choose } n) = \text{Suc } n$
 $\langle \text{proof} \rangle$

lemma *binomial-1* [*simp*]: $(n \text{ choose } \text{Suc } 0) = n$
 $\langle \text{proof} \rangle$

lemma *zero-less-binomial* [*rule-format*]: $k \leq n \longrightarrow 0 < (n \text{ choose } k)$
 $\langle \text{proof} \rangle$

lemma *binomial-eq-0-iff*: $(n \text{ choose } k = 0) = (n < k)$
 $\langle \text{proof} \rangle$

lemma *zero-less-binomial-iff*: $(0 < n \text{ choose } k) = (k \leq n)$
 $\langle \text{proof} \rangle$

lemma *Suc-times-binomial-eq* [*rule-format*]:
 $\forall k. k \leq n \longrightarrow \text{Suc } n * (n \text{ choose } k) = (\text{Suc } n \text{ choose } \text{Suc } k) * \text{Suc } k$
 $\langle \text{proof} \rangle$

This is the well-known version, but it’s harder to use because of the need to reason about division.

lemma *binomial-Suc-Suc-eq-times*:
 $k \leq n \implies (\text{Suc } n \text{ choose } \text{Suc } k) = (\text{Suc } n * (n \text{ choose } k)) \text{ div } \text{Suc } k$
 $\langle \text{proof} \rangle$

Another version, with -1 instead of Suc.

lemma *times-binomial-minus1-eq*:
 $[|k \leq n; 0 < k|] \implies (n \text{ choose } k) * k = n * ((n - 1) \text{ choose } (k - 1))$
 $\langle \text{proof} \rangle$

36.0.1 Theorems about *choose*

Basic theorem about *choose*. By Florian Kammüller, tidied by LCP.

lemma *card-s-0-eq-empty*:
 $\text{finite } A \implies \text{card } \{B. B \subseteq A \ \& \ \text{card } B = 0\} = 1$
 $\langle \text{proof} \rangle$

lemma *choose-deconstruct*: $\text{finite } M \implies x \notin M$
 $\implies \{s. s \leq \text{insert } x \ M \ \& \ \text{card}(s) = \text{Suc } k\}$
 $= \{s. s \leq M \ \& \ \text{card}(s) = \text{Suc } k\} \text{ Un }$
 $\{s. \text{EX } t. t \leq M \ \& \ \text{card}(t) = k \ \& \ s = \text{insert } x \ t\}$

⟨proof⟩

There are as many subsets of A having cardinality k as there are sets obtained from the former by inserting a fixed element x into each.

lemma *constr-bij*:

[[finite A ; $x \notin A$]] ==>
 $\text{card } \{B. \text{EX } C. C \leq A \ \& \ \text{card}(C) = k \ \& \ B = \text{insert } x \ C\} =$
 $\text{card } \{B. B \leq A \ \& \ \text{card}(B) = k\}$
 ⟨proof⟩

Main theorem: combinatorial statement about number of subsets of a set.

lemma *n-sub-lemma*:

!! A . finite A ==> $\text{card } \{B. B \leq A \ \& \ \text{card } B = k\} = (\text{card } A \text{ choose } k)$
 ⟨proof⟩

theorem *n-subsets*:

finite A ==> $\text{card } \{B. B \leq A \ \& \ \text{card } B = k\} = (\text{card } A \text{ choose } k)$
 ⟨proof⟩

The binomial theorem (courtesy of Tobias Nipkow):

theorem *binomial*: $(a+b::\text{nat})^n = (\sum k=0..n. (n \text{ choose } k) * a^k * b^{(n-k)})$
 ⟨proof⟩

end

37 PreList: A Basis for Building the Theory of Lists

theory *PreList*

imports *Wellfounded-Relations Presburger Relation-Power Binomial*

begin

Is defined separately to serve as a basis for theory ToyList in the documentation.

end

38 List: The datatype of finite lists

theory *List*

imports *PreList*

begin

datatype *'a list* =

$\text{Nil} \quad ([])$
 | $\text{Cons } 'a \ 'a \text{ list} \quad (\text{infixr } \# \ 65)$

38.1 Basic list processing functions

consts

```

@ :: 'a list => 'a list => 'a list    (infixr 65)
filter:: ('a => bool) => 'a list => 'a list
concat:: 'a list list => 'a list
foldl :: ('b => 'a => 'b) => 'b => 'a list => 'b
foldr :: ('a => 'b => 'b) => 'a list => 'b => 'b
hd:: 'a list => 'a
tl:: 'a list => 'a list
last:: 'a list => 'a
butlast :: 'a list => 'a list
set :: 'a list => 'a set
list-all2 :: ('a => 'b => bool) => 'a list => 'b list => bool
map :: ('a=>'b) => ('a list => 'b list)
nth :: 'a list => nat => 'a    (infixl ! 100)
list-update :: 'a list => nat => 'a => 'a list
take:: nat => 'a list => 'a list
drop:: nat => 'a list => 'a list
takeWhile :: ('a => bool) => 'a list => 'a list
dropWhile :: ('a => bool) => 'a list => 'a list
rev :: 'a list => 'a list
zip :: 'a list => 'b list => ('a * 'b) list
upt :: nat => nat => nat list ((1[..<-/]))
remdups :: 'a list => 'a list
remove1 :: 'a => 'a list => 'a list
null:: 'a list => bool
distinct:: 'a list => bool
replicate :: nat => 'a => 'a list
rotate1 :: 'a list => 'a list
rotate :: nat => 'a list => 'a list
sublist :: 'a list => nat set => 'a list

mem :: 'a => 'a list => bool    (infixl 55)
list-inter :: 'a list => 'a list => 'a list
list-ex :: ('a => bool) => 'a list => bool
list-all:: ('a => bool) => ('a list => bool)
itrev :: 'a list => 'a list => 'a list
filtermap :: ('a => 'b option) => 'a list => 'b list
map-filter :: ('a => 'b) => ('a => bool) => 'a list => 'b list

```

nonterminals *lupdbinds lupdbind*

syntax

— list Enumeration

@list :: args => 'a list ([(-)])

— Special syntax for filter

@filter :: [pttrn, 'a list, bool] => 'a list ((1[:.-/ -]))

— list update
 $-lupdbind :: ['a, 'a] \Rightarrow lupdbind \quad ((2- := / -))$
 $:: lupdbind \Rightarrow lupdbinds \quad (-)$
 $-lupdbinds :: [lupdbind, lupdbinds] \Rightarrow lupdbinds \quad (-, / -)$
 $-LUpdate :: ['a, lupdbinds] \Rightarrow 'a \quad (-/[(-)] [900,0] 900)$

 $upto :: nat \Rightarrow nat \Rightarrow nat \text{ list} \quad ((1[-../-]))$

translations

$[x, xs] == x \# [xs]$
 $[x] == x \# []$
 $[x:xs . P] == filter (\%x. P) xs$

 $-LUpdate xs (-lupdbinds b bs) == -LUpdate (-LUpdate xs b) bs$
 $xs[i:=x] == list-update xs i x$

 $[i..j] == [i..<(Suc j)]$

syntax (*xsymbols*)

$@filter :: [pttrn, 'a \text{ list}, bool] \Rightarrow 'a \text{ list}((1[-\in- ./ -]))$

syntax (*HTML output*)

$@filter :: [pttrn, 'a \text{ list}, bool] \Rightarrow 'a \text{ list}((1[-\in- ./ -]))$

Function *size* is overloaded for all datatypes. Users may refer to the list version as *length*.

syntax $length :: 'a \text{ list} \Rightarrow nat$

translations $length \Rightarrow size :: - \text{ list} \Rightarrow nat$

$\langle ML \rangle$

primrec

$hd(x \# xs) = x$

primrec

$tl([]) = []$
 $tl(x \# xs) = xs$

primrec

$null([]) = True$
 $null(x \# xs) = False$

primrec

$last(x \# xs) = (if xs=[] \text{ then } x \text{ else } last \ xs)$

primrec

$butlast [] = []$

$$\text{butlast}(x\#xs) = (\text{if } xs = [] \text{ then } [] \text{ else } x\#\text{butlast } xs)$$

primrec

$$\begin{aligned} \text{set } [] &= \{\} \\ \text{set } (x\#xs) &= \text{insert } x (\text{set } xs) \end{aligned}$$

primrec

$$\begin{aligned} \text{map } f [] &= [] \\ \text{map } f (x\#xs) &= f(x)\#\text{map } f xs \end{aligned}$$

primrec

$$\begin{aligned} \text{append-Nil}: [] @ ys &= ys \\ \text{append-Cons}: (x\#xs) @ ys &= x\#(xs @ ys) \end{aligned}$$

primrec

$$\begin{aligned} \text{rev}([]) &= [] \\ \text{rev}(x\#xs) &= \text{rev}(xs) @ [x] \end{aligned}$$

primrec

$$\begin{aligned} \text{filter } P [] &= [] \\ \text{filter } P (x\#xs) &= (\text{if } P x \text{ then } x\#\text{filter } P xs \text{ else } \text{filter } P xs) \end{aligned}$$

primrec

$$\begin{aligned} \text{foldl-Nil}: \text{foldl } f a [] &= a \\ \text{foldl-Cons}: \text{foldl } f a (x\#xs) &= \text{foldl } f (f a x) xs \end{aligned}$$

primrec

$$\begin{aligned} \text{foldr } f [] a &= a \\ \text{foldr } f (x\#xs) a &= f x (\text{foldr } f xs a) \end{aligned}$$

primrec

$$\begin{aligned} \text{concat}([]) &= [] \\ \text{concat}(x\#xs) &= x @ \text{concat}(xs) \end{aligned}$$

primrec

$$\begin{aligned} \text{drop-Nil}: \text{drop } n [] &= [] \\ \text{drop-Cons}: \text{drop } n (x\#xs) &= (\text{case } n \text{ of } 0 => x\#xs \mid \text{Suc}(m) => \text{drop } m xs) \\ \text{--- Warning: simpset does not contain this definition, but separate theorems for} \\ n = 0 \text{ and } n = \text{Suc } k \end{aligned}$$

primrec

$$\begin{aligned} \text{take-Nil}: \text{take } n [] &= [] \\ \text{take-Cons}: \text{take } n (x\#xs) &= (\text{case } n \text{ of } 0 => [] \mid \text{Suc}(m) => x \# \text{take } m xs) \\ \text{--- Warning: simpset does not contain this definition, but separate theorems for} \\ n = 0 \text{ and } n = \text{Suc } k \end{aligned}$$

primrec

$$\begin{aligned} \text{nth-Cons}: (x\#xs)!n &= (\text{case } n \text{ of } 0 => x \mid (\text{Suc } k) => xs!k) \\ \text{--- Warning: simpset does not contain this definition, but separate theorems for} \end{aligned}$$

$n = 0$ and $n = \text{Suc } k$

primrec

$\llbracket [i:=v] \rrbracket = \llbracket \rrbracket$
 $(x \# xs)[i:=v] = (\text{case } i \text{ of } 0 \Rightarrow v \# xs \mid \text{Suc } j \Rightarrow x \# xs[j:=v])$

primrec

$\text{takeWhile } P \llbracket \rrbracket = \llbracket \rrbracket$
 $\text{takeWhile } P (x \# xs) = (\text{if } P x \text{ then } x \# \text{takeWhile } P xs \text{ else } \llbracket \rrbracket)$

primrec

$\text{dropWhile } P \llbracket \rrbracket = \llbracket \rrbracket$
 $\text{dropWhile } P (x \# xs) = (\text{if } P x \text{ then } \text{dropWhile } P xs \text{ else } x \# xs)$

primrec

$\text{zip } xs \llbracket \rrbracket = \llbracket \rrbracket$
 $\text{zip-Cons: } \text{zip } xs (y \# ys) = (\text{case } xs \text{ of } \llbracket \rrbracket \Rightarrow \llbracket \rrbracket \mid z \# zs \Rightarrow (z, y) \# \text{zip } zs ys)$
 — Warning: simpset does not contain this definition, but separate theorems for
 $xs = \llbracket \rrbracket$ and $xs = z \# zs$

primrec

$\text{upt-0: } [i..<0] = \llbracket \rrbracket$
 $\text{upt-Suc: } [i..<(\text{Suc } j)] = (\text{if } i \leq j \text{ then } [i..<j] @ [j] \text{ else } \llbracket \rrbracket)$

primrec

$\text{distinct } \llbracket \rrbracket = \text{True}$
 $\text{distinct } (x \# xs) = (x \sim: \text{set } xs \wedge \text{distinct } xs)$

primrec

$\text{remdups } \llbracket \rrbracket = \llbracket \rrbracket$
 $\text{remdups } (x \# xs) = (\text{if } x : \text{set } xs \text{ then } \text{remdups } xs \text{ else } x \# \text{remdups } xs)$

primrec

$\text{remove1 } x \llbracket \rrbracket = \llbracket \rrbracket$
 $\text{remove1 } x (y \# xs) = (\text{if } x=y \text{ then } xs \text{ else } y \# \text{remove1 } x xs)$

primrec

$\text{replicate-0: } \text{replicate } 0 x = \llbracket \rrbracket$
 $\text{replicate-Suc: } \text{replicate } (\text{Suc } n) x = x \# \text{replicate } n x$

defs

$\text{rotate1-def: } \text{rotate1 } xs == (\text{case } xs \text{ of } \llbracket \rrbracket \Rightarrow \llbracket \rrbracket \mid x \# xs \Rightarrow xs @ [x])$
 $\text{rotate-def: } \text{rotate } n == \text{rotate1 } ^n$

list-all2-def:

$\text{list-all2 } P xs ys ==$
 $\text{length } xs = \text{length } ys \wedge (\forall (x, y) \in \text{set } (\text{zip } xs ys). P x y)$

sublist-def:

$sublist\ xs\ A == map\ fst\ (filter\ (\%p.\ snd\ p : A)\ (zip\ xs\ [0..<size\ xs]))$

primrec

$x\ mem\ [] = False$
 $x\ mem\ (y\#\!ys) = (if\ y=x\ then\ True\ else\ x\ mem\ ys)$

primrec

$list-inter\ []\ bs = []$
 $list-inter\ (a\#\!as)\ bs =$
 $(if\ a \in set\ bs\ then\ a\#\!(list-inter\ as\ bs)\ else\ list-inter\ as\ bs)$

primrec

$list-all\ P\ [] = True$
 $list-all\ P\ (x\#\!xs) = (P(x) \wedge list-all\ P\ xs)$

primrec

$list-ex\ P\ [] = False$
 $list-ex\ P\ (x\#\!xs) = (P\ x \vee list-ex\ P\ xs)$

primrec

$filtermap\ f\ [] = []$
 $filtermap\ f\ (x\#\!xs) =$
 $(case\ f\ x\ of\ None \Rightarrow filtermap\ f\ xs$
 $\quad | Some\ y \Rightarrow y\ \#\ (filtermap\ f\ xs))$

primrec

$map-filter\ f\ P\ [] = []$
 $map-filter\ f\ P\ (x\#\!xs) = (if\ P\ x\ then\ f\ x\ \#\ map-filter\ f\ P\ xs\ else$
 $\quad map-filter\ f\ P\ xs)$

primrec

$itrev\ []\ ys = ys$
 $itrev\ (x\#\!xs)\ ys = itrev\ xs\ (x\#\!ys)$

lemma *not-Cons-self* [simp]: $xs \neq x\ \#\ xs$

$\langle proof \rangle$

lemmas *not-Cons-self2* [simp] = *not-Cons-self* [symmetric]

lemma *neq-Nil-conv*: $(xs \neq []) = (\exists y\ ys.\ xs = y\ \#\ ys)$

$\langle proof \rangle$

lemma *length-induct*:

$(!\!xs.\ \forall ys.\ length\ ys < length\ xs \longrightarrow P\ ys \Longrightarrow P\ xs) \Longrightarrow P\ xs$

$\langle proof \rangle$

38.1.1 *length*

Needs to come before @ because of theorem *append-eq-append-conv*.

lemma *length-append* [simp]: $\text{length } (xs @ ys) = \text{length } xs + \text{length } ys$
 ⟨proof⟩

lemma *length-map* [simp]: $\text{length } (\text{map } f \text{ } xs) = \text{length } xs$
 ⟨proof⟩

lemma *length-rev* [simp]: $\text{length } (\text{rev } xs) = \text{length } xs$
 ⟨proof⟩

lemma *length-tl* [simp]: $\text{length } (\text{tl } xs) = \text{length } xs - 1$
 ⟨proof⟩

lemma *length-0-conv* [iff]: $(\text{length } xs = 0) = (xs = [])$
 ⟨proof⟩

lemma *length-greater-0-conv* [iff]: $(0 < \text{length } xs) = (xs \neq [])$
 ⟨proof⟩

lemma *length-Suc-conv*:
 $(\text{length } xs = \text{Suc } n) = (\exists y \text{ } ys. xs = y \# ys \wedge \text{length } ys = n)$
 ⟨proof⟩

lemma *Suc-length-conv*:
 $(\text{Suc } n = \text{length } xs) = (\exists y \text{ } ys. xs = y \# ys \wedge \text{length } ys = n)$
 ⟨proof⟩

lemma *impossible-Cons* [rule-format]:
 $\text{length } xs <= \text{length } ys \longrightarrow xs = x \# ys = \text{False}$
 ⟨proof⟩

lemma *list-induct2*[consumes 1]: $\bigwedge ys.$
 $\llbracket \text{length } xs = \text{length } ys;$
 $P [] [];$
 $\bigwedge x \text{ } xs \text{ } y \text{ } ys. \llbracket \text{length } xs = \text{length } ys; P \text{ } xs \text{ } ys \rrbracket \Longrightarrow P (x \# xs) (y \# ys) \rrbracket$
 $\Longrightarrow P \text{ } xs \text{ } ys$
 ⟨proof⟩

38.1.2 @ – *append*

lemma *append-assoc* [simp]: $(xs @ ys) @ zs = xs @ (ys @ zs)$
 ⟨proof⟩

lemma *append-Nil2* [simp]: $xs @ [] = xs$
 ⟨proof⟩

lemma *append-is-Nil-conv* [iff]: $(xs @ ys = []) = (xs = [] \wedge ys = [])$

$\langle proof \rangle$

lemma *Nil-is-append-conv* [iff]: $([] = xs @ ys) = (xs = [] \wedge ys = [])$
 $\langle proof \rangle$

lemma *append-self-conv* [iff]: $(xs @ ys = xs) = (ys = [])$
 $\langle proof \rangle$

lemma *self-append-conv* [iff]: $(xs = xs @ ys) = (ys = [])$
 $\langle proof \rangle$

lemma *append-eq-append-conv* [simp]:
 $!!ys. \text{length } xs = \text{length } ys \vee \text{length } us = \text{length } vs$
 $\implies (xs @ us = ys @ vs) = (xs = ys \wedge us = vs)$
 $\langle proof \rangle$

lemma *append-eq-append-conv2*: $!!ys \ zs \ ts.$
 $(xs @ ys = zs @ ts) =$
 $(EX \ us. xs = zs @ us \ \& \ us @ ys = ts \mid xs @ us = zs \ \& \ ys = us @ ts)$
 $\langle proof \rangle$

lemma *same-append-eq* [iff]: $(xs @ ys = xs @ zs) = (ys = zs)$
 $\langle proof \rangle$

lemma *append1-eq-conv* [iff]: $(xs @ [x] = ys @ [y]) = (xs = ys \wedge x = y)$
 $\langle proof \rangle$

lemma *append-same-eq* [iff]: $(ys @ xs = zs @ xs) = (ys = zs)$
 $\langle proof \rangle$

lemma *append-self-conv2* [iff]: $(xs @ ys = ys) = (xs = [])$
 $\langle proof \rangle$

lemma *self-append-conv2* [iff]: $(ys = xs @ ys) = (xs = [])$
 $\langle proof \rangle$

lemma *hd-Cons-tl* [simp]: $xs \neq [] \implies \text{hd } xs \neq \text{tl } xs = xs$
 $\langle proof \rangle$

lemma *hd-append*: $\text{hd } (xs @ ys) = (\text{if } xs = [] \text{ then } \text{hd } ys \text{ else } \text{hd } xs)$
 $\langle proof \rangle$

lemma *hd-append2* [simp]: $xs \neq [] \implies \text{hd } (xs @ ys) = \text{hd } xs$
 $\langle proof \rangle$

lemma *tl-append*: $\text{tl } (xs @ ys) = (\text{case } xs \text{ of } [] \implies \text{tl } ys \mid z \# zs \implies zs @ ys)$
 $\langle proof \rangle$

lemma *tl-append2* [simp]: $xs \neq [] \implies \text{tl } (xs @ ys) = \text{tl } xs @ ys$

$\langle proof \rangle$

lemma *Cons-eq-append-conv*: $x \# xs = ys @ zs =$
 $(ys = [] \ \& \ x \# xs = zs \mid (EX \ ys'. \ x \# ys' = ys \ \& \ xs = ys' @ zs))$
 $\langle proof \rangle$

lemma *append-eq-Cons-conv*: $(ys @ zs = x \# xs) =$
 $(ys = [] \ \& \ zs = x \# xs \mid (EX \ ys'. \ ys = x \# ys' \ \& \ ys' @ zs = xs))$
 $\langle proof \rangle$

Trivial rules for solving @-equations automatically.

lemma *eq-Nil-appendI*: $xs = ys ==> xs = [] @ ys$
 $\langle proof \rangle$

lemma *Cons-eq-appendI*:
 $[| \ x \ \# \ xs1 = ys; \ xs = xs1 @ zs \ |] ==> x \ \# \ xs = ys @ zs$
 $\langle proof \rangle$

lemma *append-eq-appendI*:
 $[| \ xs @ xs1 = zs; \ ys = xs1 @ us \ |] ==> xs @ ys = zs @ us$
 $\langle proof \rangle$

Simplification procedure for all list equalities. Currently only tries to rearrange @ to see if - both lists end in a singleton list, - or both lists end in the same list.

$\langle ML \rangle$

38.1.3 map

lemma *map-ext*: $(!x. \ x : set \ xs \ --> \ f \ x = g \ x) ==> \ map \ f \ xs = map \ g \ xs$
 $\langle proof \rangle$

lemma *map-ident* [simp]: $map \ (\lambda x. \ x) = (\lambda xs. \ xs)$
 $\langle proof \rangle$

lemma *map-append* [simp]: $map \ f \ (xs @ ys) = map \ f \ xs @ map \ f \ ys$
 $\langle proof \rangle$

lemma *map-compose*: $map \ (f \ o \ g) \ xs = map \ f \ (map \ g \ xs)$
 $\langle proof \rangle$

lemma *rev-map*: $rev \ (map \ f \ xs) = map \ f \ (rev \ xs)$
 $\langle proof \rangle$

lemma *map-eq-conv*[simp]: $(map \ f \ xs = map \ g \ xs) = (!x : set \ xs. \ f \ x = g \ x)$
 $\langle proof \rangle$

lemma *map-cong* [recdef-cong]:

$xs = ys ==> (!!x. x : set\ ys ==> f\ x = g\ x) ==> map\ f\ xs = map\ g\ ys$
 — a congruence rule for *map*
 $\langle proof \rangle$

lemma *map-is-Nil-conv* [iff]: $(map\ f\ xs = []) = (xs = [])$
 $\langle proof \rangle$

lemma *Nil-is-map-conv* [iff]: $([] = map\ f\ xs) = (xs = [])$
 $\langle proof \rangle$

lemma *map-eq-Cons-conv*[iff]:
 $(map\ f\ xs = y\#\!ys) = (\exists z\ zs. xs = z\#\!zs \wedge f\ z = y \wedge map\ f\ zs = ys)$
 $\langle proof \rangle$

lemma *Cons-eq-map-conv*[iff]:
 $(x\#\!xs = map\ f\ ys) = (\exists z\ zs. ys = z\#\!zs \wedge x = f\ z \wedge xs = map\ f\ zs)$
 $\langle proof \rangle$

lemma *ex-map-conv*:
 $(EX\ xs. ys = map\ f\ xs) = (ALL\ y : set\ ys. EX\ x. y = f\ x)$
 $\langle proof \rangle$

lemma *map-eq-imp-length-eq*:
 $!!xs. map\ f\ xs = map\ f\ ys ==> length\ xs = length\ ys$
 $\langle proof \rangle$

lemma *map-inj-on*:
 $[| map\ f\ xs = map\ f\ ys; inj-on\ f\ (set\ xs\ Un\ set\ ys) |]$
 $==> xs = ys$
 $\langle proof \rangle$

lemma *inj-on-map-eq-map*:
 $inj-on\ f\ (set\ xs\ Un\ set\ ys) ==> (map\ f\ xs = map\ f\ ys) = (xs = ys)$
 $\langle proof \rangle$

lemma *map-injective*:
 $!!xs. map\ f\ xs = map\ f\ ys ==> inj\ f ==> xs = ys$
 $\langle proof \rangle$

lemma *inj-map-eq-map*[simp]: $inj\ f ==> (map\ f\ xs = map\ f\ ys) = (xs = ys)$
 $\langle proof \rangle$

lemma *inj-mapI*: $inj\ f ==> inj\ (map\ f)$
 $\langle proof \rangle$

lemma *inj-mapD*: $inj\ (map\ f) ==> inj\ f$
 $\langle proof \rangle$

lemma *inj-map*[iff]: $inj\ (map\ f) = inj\ f$

$\langle \text{proof} \rangle$

lemma *inj-on-mapI*: $\text{inj-on } f \ (\bigcup (\text{set } 'A)) \implies \text{inj-on } (\text{map } f) \ A$
 $\langle \text{proof} \rangle$

lemma *map-idI*: $(\bigwedge x. x \in \text{set } xs \implies f \ x = x) \implies \text{map } f \ xs = xs$
 $\langle \text{proof} \rangle$

lemma *map-fun-upd [simp]*: $y \notin \text{set } xs \implies \text{map } (f(y:=v)) \ xs = \text{map } f \ xs$
 $\langle \text{proof} \rangle$

lemma *map-fst-zip [simp]*:
 $\text{length } xs = \text{length } ys \implies \text{map fst } (\text{zip } xs \ ys) = xs$
 $\langle \text{proof} \rangle$

lemma *map-snd-zip [simp]*:
 $\text{length } xs = \text{length } ys \implies \text{map snd } (\text{zip } xs \ ys) = ys$
 $\langle \text{proof} \rangle$

38.1.4 rev

lemma *rev-append [simp]*: $\text{rev } (xs \ @ \ ys) = \text{rev } ys \ @ \ \text{rev } xs$
 $\langle \text{proof} \rangle$

lemma *rev-rev-ident [simp]*: $\text{rev } (\text{rev } xs) = xs$
 $\langle \text{proof} \rangle$

lemma *rev-swap*: $(\text{rev } xs = ys) = (xs = \text{rev } ys)$
 $\langle \text{proof} \rangle$

lemma *rev-is-Nil-conv [iff]*: $(\text{rev } xs = []) = (xs = [])$
 $\langle \text{proof} \rangle$

lemma *Nil-is-rev-conv [iff]*: $([] = \text{rev } xs) = (xs = [])$
 $\langle \text{proof} \rangle$

lemma *rev-singleton-conv [simp]*: $(\text{rev } xs = [x]) = (xs = [x])$
 $\langle \text{proof} \rangle$

lemma *singleton-rev-conv [simp]*: $([x] = \text{rev } xs) = (xs = [x])$
 $\langle \text{proof} \rangle$

lemma *rev-is-rev-conv [iff]*: $!!ys. (\text{rev } xs = \text{rev } ys) = (xs = ys)$
 $\langle \text{proof} \rangle$

lemma *inj-on-rev [iff]*: $\text{inj-on } \text{rev } A$
 $\langle \text{proof} \rangle$

lemma *rev-induct [case-names Nil snoc]*:

$\llbracket P \rrbracket; !!x\ xs.\ P\ xs \implies P\ (xs\ @\ [x])\ \llbracket \rrbracket \implies P\ xs$
 $\langle proof \rangle$

$\langle ML \rangle$

lemma *rev-exhaust* [case-names Nil snoc]:
 $(xs = [] \implies P) \implies (!!ys\ y.\ xs = ys\ @\ [y] \implies P) \implies P$
 $\langle proof \rangle$

lemmas *rev-cases* = *rev-exhaust*

38.1.5 set

lemma *finite-set* [iff]: *finite* (*set* *xs*)
 $\langle proof \rangle$

lemma *set-append* [simp]: *set* (*xs* @ *ys*) = (*set* *xs* \cup *set* *ys*)
 $\langle proof \rangle$

lemma *hd-in-set*: $l = x \# xs \implies x \in \text{set } l$
 $\langle proof \rangle$

lemma *set-subset-Cons*: *set* *xs* \subseteq *set* (*x* # *xs*)
 $\langle proof \rangle$

lemma *set-ConsD*: $y \in \text{set } (x \# xs) \implies y = x \vee y \in \text{set } xs$
 $\langle proof \rangle$

lemma *set-empty* [iff]: (*set* *xs* = {}) = (*xs* = [])
 $\langle proof \rangle$

lemma *set-empty2*[iff]: ({ } = *set* *xs*) = (*xs* = [])
 $\langle proof \rangle$

lemma *set-rev* [simp]: *set* (*rev* *xs*) = *set* *xs*
 $\langle proof \rangle$

lemma *set-map* [simp]: *set* (*map* *f* *xs*) = *f**(*set* *xs*)
 $\langle proof \rangle$

lemma *set-filter* [simp]: *set* (*filter* *P* *xs*) = {*x*. *x* : *set* *xs* \wedge *P* *x*}
 $\langle proof \rangle$

lemma *set-upt* [simp]: *set*[*i*..*j*] = {*k*. *i* \leq *k* \wedge *k* < *j*}
 $\langle proof \rangle$

lemma *in-set-conv-decomp*: (*x* : *set* *xs*) = ($\exists\ ys\ zs.\ xs = ys\ @\ x\ \# zs$)
 $\langle proof \rangle$

lemma *finite-list*: $\text{finite } A \implies \text{EX } l. \text{ set } l = A$
 $\langle \text{proof} \rangle$

lemma *card-length*: $\text{card } (\text{set } xs) \leq \text{length } xs$
 $\langle \text{proof} \rangle$

38.1.6 *filter*

lemma *filter-append* [simp]: $\text{filter } P (xs @ ys) = \text{filter } P xs @ \text{filter } P ys$
 $\langle \text{proof} \rangle$

lemma *rev-filter*: $\text{rev } (\text{filter } P xs) = \text{filter } P (\text{rev } xs)$
 $\langle \text{proof} \rangle$

lemma *filter-filter* [simp]: $\text{filter } P (\text{filter } Q xs) = \text{filter } (\lambda x. Q x \wedge P x) xs$
 $\langle \text{proof} \rangle$

lemma *length-filter-le* [simp]: $\text{length } (\text{filter } P xs) \leq \text{length } xs$
 $\langle \text{proof} \rangle$

lemma *filter-True* [simp]: $\forall x \in \text{set } xs. P x \implies \text{filter } P xs = xs$
 $\langle \text{proof} \rangle$

lemma *filter-False* [simp]: $\forall x \in \text{set } xs. \neg P x \implies \text{filter } P xs = []$
 $\langle \text{proof} \rangle$

lemma *filter-empty-conv*: $(\text{filter } P xs = []) = (\forall x \in \text{set } xs. \neg P x)$
 $\langle \text{proof} \rangle$

lemma *filter-id-conv*: $(\text{filter } P xs = xs) = (\forall x \in \text{set } xs. P x)$
 $\langle \text{proof} \rangle$

lemma *filter-map*:
 $\text{filter } P (\text{map } f xs) = \text{map } f (\text{filter } (P \circ f) xs)$
 $\langle \text{proof} \rangle$

lemma *length-filter-map*[simp]:
 $\text{length } (\text{filter } P (\text{map } f xs)) = \text{length } (\text{filter } (P \circ f) xs)$
 $\langle \text{proof} \rangle$

lemma *filter-is-subset* [simp]: $\text{set } (\text{filter } P xs) \leq \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *length-filter-less*:
 $\llbracket x : \text{set } xs; \sim P x \rrbracket \implies \text{length } (\text{filter } P xs) < \text{length } xs$
 $\langle \text{proof} \rangle$

lemma *length-filter-conv-card*:
 $\text{length } (\text{filter } p xs) = \text{card} \{i. i < \text{length } xs \ \& \ p(xs[i])\}$

$\langle proof \rangle$

lemma *Cons-eq-filterD*:

$x \# xs = \text{filter } P \text{ } ys \implies$
 $\exists us \text{ } vs. \text{ } ys = us @ x \# vs \wedge (\forall u \in \text{set } us. \neg P u) \wedge P x \wedge xs = \text{filter } P \text{ } vs$
 (concl is $\exists us \text{ } vs. \text{ } ?P \text{ } ys \text{ } us \text{ } vs$)
 $\langle proof \rangle$

lemma *filter-eq-ConsD*:

$\text{filter } P \text{ } ys = x \# xs \implies$
 $\exists us \text{ } vs. \text{ } ys = us @ x \# vs \wedge (\forall u \in \text{set } us. \neg P u) \wedge P x \wedge xs = \text{filter } P \text{ } vs$
 $\langle proof \rangle$

lemma *filter-eq-Cons-iff*:

$(\text{filter } P \text{ } ys = x \# xs) =$
 $(\exists us \text{ } vs. \text{ } ys = us @ x \# vs \wedge (\forall u \in \text{set } us. \neg P u) \wedge P x \wedge xs = \text{filter } P \text{ } vs)$
 $\langle proof \rangle$

lemma *Cons-eq-filter-iff*:

$(x \# xs = \text{filter } P \text{ } ys) =$
 $(\exists us \text{ } vs. \text{ } ys = us @ x \# vs \wedge (\forall u \in \text{set } us. \neg P u) \wedge P x \wedge xs = \text{filter } P \text{ } vs)$
 $\langle proof \rangle$

lemma *filter-cong*:

$xs = ys \implies (\bigwedge x. x \in \text{set } ys \implies P x = Q x) \implies \text{filter } P \text{ } xs = \text{filter } Q \text{ } ys$
 $\langle proof \rangle$

38.1.7 concat

lemma *concat-append [simp]*: $\text{concat } (xs @ ys) = \text{concat } xs @ \text{concat } ys$
 $\langle proof \rangle$

lemma *concat-eq-Nil-conv [iff]*: $(\text{concat } xss = []) = (\forall xs \in \text{set } xss. \text{ } xs = [])$
 $\langle proof \rangle$

lemma *Nil-eq-concat-conv [iff]*: $([] = \text{concat } xss) = (\forall xs \in \text{set } xss. \text{ } xs = [])$
 $\langle proof \rangle$

lemma *set-concat [simp]*: $\text{set } (\text{concat } xs) = \bigcup (\text{set } ' \text{set } xs)$
 $\langle proof \rangle$

lemma *map-concat*: $\text{map } f \text{ } (\text{concat } xs) = \text{concat } (\text{map } (\text{map } f) \text{ } xs)$
 $\langle proof \rangle$

lemma *filter-concat*: $\text{filter } p \text{ } (\text{concat } xs) = \text{concat } (\text{map } (\text{filter } p) \text{ } xs)$
 $\langle proof \rangle$

lemma *rev-concat*: $\text{rev } (\text{concat } xs) = \text{concat } (\text{map } \text{rev } (\text{rev } xs))$
 $\langle proof \rangle$

38.1.8 *nth*

lemma *nth-Cons-0* [simp]: $(x \# xs)!0 = x$
 ⟨proof⟩

lemma *nth-Cons-Suc* [simp]: $(x \# xs)!(\text{Suc } n) = xs!n$
 ⟨proof⟩

declare *nth.simps* [simp del]

lemma *nth-append*:

$!!n. (xs @ ys)!n = (\text{if } n < \text{length } xs \text{ then } xs!n \text{ else } ys!(n - \text{length } xs))$
 ⟨proof⟩

lemma *nth-append-length* [simp]: $(xs @ x \# ys) ! \text{length } xs = x$
 ⟨proof⟩

lemma *nth-append-length-plus* [simp]: $(xs @ ys) ! (\text{length } xs + n) = ys ! n$
 ⟨proof⟩

lemma *nth-map* [simp]: $!!n. n < \text{length } xs \implies (\text{map } f \text{ } xs)!n = f(xs!n)$
 ⟨proof⟩

lemma *set-conv-nth*: $\text{set } xs = \{xs!i \mid i. i < \text{length } xs\}$
 ⟨proof⟩

lemma *in-set-conv-nth*: $(x \in \text{set } xs) = (\exists i < \text{length } xs. xs!i = x)$
 ⟨proof⟩

lemma *list-ball-nth*: $[\mid n < \text{length } xs; !x : \text{set } xs. P \ x] \implies P(xs!n)$
 ⟨proof⟩

lemma *nth-mem* [simp]: $n < \text{length } xs \implies xs!n : \text{set } xs$
 ⟨proof⟩

lemma *all-nth-imp-all-set*:

$[\mid !i < \text{length } xs. P(xs!i); x : \text{set } xs] \implies P \ x$
 ⟨proof⟩

lemma *all-set-conv-all-nth*:

$(\forall x \in \text{set } xs. P \ x) = (\forall i. i < \text{length } xs \longrightarrow P \ (xs ! i))$
 ⟨proof⟩

38.1.9 *list-update*

lemma *length-list-update* [simp]: $!!i. \text{length}(xs[i:=x]) = \text{length } xs$
 ⟨proof⟩

lemma *nth-list-update*:

$!!i \ j. i < \text{length } xs \implies (xs[i:=x])!j = (\text{if } i = j \text{ then } x \text{ else } xs!j)$

$\langle proof \rangle$

lemma *nth-list-update-eq* [simp]: $i < \text{length } xs \implies (xs[i:=x])!i = x$
 $\langle proof \rangle$

lemma *nth-list-update-neq* [simp]: $!!i\ j. i \neq j \implies xs[i:=x]!j = xs!j$
 $\langle proof \rangle$

lemma *list-update-overwrite* [simp]:
 $!!i. i < \text{size } xs \implies xs[i:=x, i:=y] = xs[i:=y]$
 $\langle proof \rangle$

lemma *list-update-id*[simp]: $!!i. i < \text{length } xs \implies xs[i := xs!i] = xs$
 $\langle proof \rangle$

lemma *list-update-beyond*[simp]: $\bigwedge i. \text{length } xs \leq i \implies xs[i:=x] = xs$
 $\langle proof \rangle$

lemma *list-update-same-conv*:
 $!!i. i < \text{length } xs \implies (xs[i := x] = xs) = (xs!i = x)$
 $\langle proof \rangle$

lemma *list-update-append1*:
 $!!i. i < \text{size } xs \implies (xs @ ys)[i:=x] = xs[i:=x] @ ys$
 $\langle proof \rangle$

lemma *list-update-append*:
 $!!n. (xs @ ys) [n:=x] =$
 $(\text{if } n < \text{length } xs \text{ then } xs[n:=x] @ ys \text{ else } xs @ (ys [n-\text{length } xs:=x]))$
 $\langle proof \rangle$

lemma *list-update-length* [simp]:
 $(xs @ x \# ys)[\text{length } xs := y] = (xs @ y \# ys)$
 $\langle proof \rangle$

lemma *update-zip*:
 $!!i\ xy\ xs. \text{length } xs = \text{length } ys \implies$
 $(\text{zip } xs\ ys)[i:=xy] = \text{zip } (xs[i:=fst\ xy])\ (ys[i:=snd\ xy])$
 $\langle proof \rangle$

lemma *set-update-subset-insert*: $!!i. \text{set}(xs[i:=x]) \leq \text{insert } x\ (\text{set } xs)$
 $\langle proof \rangle$

lemma *set-update-subsetI*: $[\text{set } xs \leq A; x:A] \implies \text{set}(xs[i := x]) \leq A$
 $\langle proof \rangle$

lemma *set-update-memI*: $!!n. n < \text{length } xs \implies x \in \text{set } (xs[n := x])$
 $\langle proof \rangle$

38.1.10 *last and butlast*

lemma *last-snoc* [simp]: $\text{last } (xs @ [x]) = x$
 ⟨proof⟩

lemma *butlast-snoc* [simp]: $\text{butlast } (xs @ [x]) = xs$
 ⟨proof⟩

lemma *last-ConsL*: $xs = [] \implies \text{last}(x \# xs) = x$
 ⟨proof⟩

lemma *last-ConsR*: $xs \neq [] \implies \text{last}(x \# xs) = \text{last } xs$
 ⟨proof⟩

lemma *last-append*: $\text{last}(xs @ ys) = (\text{if } ys = [] \text{ then } \text{last } xs \text{ else } \text{last } ys)$
 ⟨proof⟩

lemma *last-appendL*[simp]: $ys = [] \implies \text{last}(xs @ ys) = \text{last } xs$
 ⟨proof⟩

lemma *last-appendR*[simp]: $ys \neq [] \implies \text{last}(xs @ ys) = \text{last } ys$
 ⟨proof⟩

lemma *length-butlast* [simp]: $\text{length } (\text{butlast } xs) = \text{length } xs - 1$
 ⟨proof⟩

lemma *butlast-append*:
 $!!ys. \text{butlast } (xs @ ys) = (\text{if } ys = [] \text{ then } \text{butlast } xs \text{ else } xs @ \text{butlast } ys)$
 ⟨proof⟩

lemma *append-butlast-last-id* [simp]:
 $xs \neq [] \implies \text{butlast } xs @ [\text{last } xs] = xs$
 ⟨proof⟩

lemma *in-set-butlastD*: $x : \text{set } (\text{butlast } xs) \implies x : \text{set } xs$
 ⟨proof⟩

lemma *in-set-butlast-appendI*:
 $x : \text{set } (\text{butlast } xs) \mid x : \text{set } (\text{butlast } ys) \implies x : \text{set } (\text{butlast } (xs @ ys))$
 ⟨proof⟩

lemma *last-drop*[simp]: $!!n. n < \text{length } xs \implies \text{last } (\text{drop } n \text{ } xs) = \text{last } xs$
 ⟨proof⟩

lemma *last-conv-nth*: $xs \neq [] \implies \text{last } xs = xs!(\text{length } xs - 1)$
 ⟨proof⟩

38.1.11 *take and drop*

lemma *take-0* [simp]: $\text{take } 0 \text{ } xs = []$
 ⟨proof⟩

lemma *drop-0* [simp]: $\text{drop } 0 \text{ } xs = xs$
 ⟨proof⟩

lemma *take-Suc-Cons* [simp]: $\text{take } (\text{Suc } n) \text{ } (x \# xs) = x \# \text{take } n \text{ } xs$
 ⟨proof⟩

lemma *drop-Suc-Cons* [simp]: $\text{drop } (\text{Suc } n) \text{ } (x \# xs) = \text{drop } n \text{ } xs$
 ⟨proof⟩

declare *take-Cons* [simp del] **and** *drop-Cons* [simp del]

lemma *take-Suc*: $xs \sim [] \implies \text{take } (\text{Suc } n) \text{ } xs = \text{hd } xs \# \text{take } n \text{ } (\text{tl } xs)$
 ⟨proof⟩

lemma *drop-Suc*: $\text{drop } (\text{Suc } n) \text{ } xs = \text{drop } n \text{ } (\text{tl } xs)$
 ⟨proof⟩

lemma *drop-tl*: $!!n. \text{drop } n \text{ } (\text{tl } xs) = \text{tl}(\text{drop } n \text{ } xs)$
 ⟨proof⟩

lemma *nth-via-drop*: $!!n. \text{drop } n \text{ } xs = y \# ys \implies xs!n = y$
 ⟨proof⟩

lemma *take-Suc-conv-app-nth*:
 $!!i. i < \text{length } xs \implies \text{take } (\text{Suc } i) \text{ } xs = \text{take } i \text{ } xs @ [xs!i]$
 ⟨proof⟩

lemma *drop-Suc-conv-tl*:
 $!!i. i < \text{length } xs \implies (xs!i) \# (\text{drop } (\text{Suc } i) \text{ } xs) = \text{drop } i \text{ } xs$
 ⟨proof⟩

lemma *length-take* [simp]: $!!xs. \text{length } (\text{take } n \text{ } xs) = \min (\text{length } xs) \text{ } n$
 ⟨proof⟩

lemma *length-drop* [simp]: $!!xs. \text{length } (\text{drop } n \text{ } xs) = (\text{length } xs - n)$
 ⟨proof⟩

lemma *take-all* [simp]: $!!xs. \text{length } xs \leq n \implies \text{take } n \text{ } xs = xs$
 ⟨proof⟩

lemma *drop-all* [simp]: $!!xs. \text{length } xs \leq n \implies \text{drop } n \text{ } xs = []$
 ⟨proof⟩

lemma *take-append* [simp]:
 $!!xs. \text{take } n \text{ } (xs @ ys) = (\text{take } n \text{ } xs @ \text{take } (n - \text{length } xs) \text{ } ys)$

$\langle proof \rangle$

lemma *drop-append* [simp]:

$!!xs. \text{drop } n (xs @ ys) = \text{drop } n xs @ \text{drop } (n - \text{length } xs) ys$

$\langle proof \rangle$

lemma *take-take* [simp]: $!!xs \ n. \text{take } n (\text{take } m xs) = \text{take } (\min n m) xs$

$\langle proof \rangle$

lemma *drop-drop* [simp]: $!!xs. \text{drop } n (\text{drop } m xs) = \text{drop } (n + m) xs$

$\langle proof \rangle$

lemma *take-drop*: $!!xs \ n. \text{take } n (\text{drop } m xs) = \text{drop } m (\text{take } (n + m) xs)$

$\langle proof \rangle$

lemma *drop-take*: $!!m \ n. \text{drop } n (\text{take } m xs) = \text{take } (m - n) (\text{drop } n xs)$

$\langle proof \rangle$

lemma *append-take-drop-id* [simp]: $!!xs. \text{take } n xs @ \text{drop } n xs = xs$

$\langle proof \rangle$

lemma *take-eq-Nil*[simp]: $!!n. (\text{take } n xs = []) = (n = 0 \vee xs = [])$

$\langle proof \rangle$

lemma *drop-eq-Nil*[simp]: $!!n. (\text{drop } n xs = []) = (\text{length } xs \leq n)$

$\langle proof \rangle$

lemma *take-map*: $!!xs. \text{take } n (\text{map } f xs) = \text{map } f (\text{take } n xs)$

$\langle proof \rangle$

lemma *drop-map*: $!!xs. \text{drop } n (\text{map } f xs) = \text{map } f (\text{drop } n xs)$

$\langle proof \rangle$

lemma *rev-take*: $!!i. \text{rev } (\text{take } i xs) = \text{drop } (\text{length } xs - i) (\text{rev } xs)$

$\langle proof \rangle$

lemma *rev-drop*: $!!i. \text{rev } (\text{drop } i xs) = \text{take } (\text{length } xs - i) (\text{rev } xs)$

$\langle proof \rangle$

lemma *nth-take* [simp]: $!!n \ i. i < n ==> (\text{take } n xs)!i = xs!i$

$\langle proof \rangle$

lemma *nth-drop* [simp]:

$!!xs \ i. n + i \leq \text{length } xs ==> (\text{drop } n xs)!i = xs!(n + i)$

$\langle proof \rangle$

lemma *set-take-subset*: $\bigwedge n. \text{set}(\text{take } n xs) \subseteq \text{set } xs$

$\langle proof \rangle$

lemma *set-drop-subset*: $\bigwedge n. \text{set}(\text{drop } n \text{ } xs) \subseteq \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *in-set-takeD*: $x : \text{set}(\text{take } n \text{ } xs) \implies x : \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *in-set-dropD*: $x : \text{set}(\text{drop } n \text{ } xs) \implies x : \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *append-eq-conv-conj*:
 $!!zs. (xs @ ys = zs) = (xs = \text{take } (\text{length } xs) \text{ } zs \wedge ys = \text{drop } (\text{length } xs) \text{ } zs)$
 $\langle \text{proof} \rangle$

lemma *take-add [rule-format]*:
 $\forall i. i+j \leq \text{length}(xs) \dashv\!\!\dashv\!\!\rightarrow \text{take } (i+j) \text{ } xs = \text{take } i \text{ } xs @ \text{take } j \text{ } (\text{drop } i \text{ } xs)$
 $\langle \text{proof} \rangle$

lemma *append-eq-append-conv-if*:
 $!! ys_1. (xs_1 @ xs_2 = ys_1 @ ys_2) =$
 $(\text{if } \text{size } xs_1 \leq \text{size } ys_1$
 $\text{ then } xs_1 = \text{take } (\text{size } xs_1) \text{ } ys_1 \wedge xs_2 = \text{drop } (\text{size } xs_1) \text{ } ys_1 @ ys_2$
 $\text{ else } \text{take } (\text{size } ys_1) \text{ } xs_1 = ys_1 \wedge \text{drop } (\text{size } ys_1) \text{ } xs_1 @ xs_2 = ys_2)$
 $\langle \text{proof} \rangle$

lemma *take-hd-drop*:
 $!!n. n < \text{length } xs \implies \text{take } n \text{ } xs @ [\text{hd } (\text{drop } n \text{ } xs)] = \text{take } (n+1) \text{ } xs$
 $\langle \text{proof} \rangle$

lemma *id-take-nth-drop*:
 $i < \text{length } xs \implies xs = \text{take } i \text{ } xs @ xs[i] \# \text{drop } (\text{Suc } i) \text{ } xs$
 $\langle \text{proof} \rangle$

lemma *upd-conv-take-nth-drop*:
 $i < \text{length } xs \implies xs[i:=a] = \text{take } i \text{ } xs @ a \# \text{drop } (\text{Suc } i) \text{ } xs$
 $\langle \text{proof} \rangle$

38.1.12 *takeWhile* and *dropWhile*

lemma *takeWhile-dropWhile-id [simp]*: $\text{takeWhile } P \text{ } xs @ \text{dropWhile } P \text{ } xs = xs$
 $\langle \text{proof} \rangle$

lemma *takeWhile-append1 [simp]*:
 $[[x:\text{set } xs; \sim P(x)]] \implies \text{takeWhile } P \text{ } (xs @ ys) = \text{takeWhile } P \text{ } xs$
 $\langle \text{proof} \rangle$

lemma *takeWhile-append2 [simp]*:
 $(!!x. x : \text{set } xs \implies P x) \implies \text{takeWhile } P \text{ } (xs @ ys) = xs @ \text{takeWhile } P \text{ } ys$
 $\langle \text{proof} \rangle$

lemma *takeWhile-tail*: $\neg P\ x \implies \text{takeWhile } P\ (xs\ @\ (x\ \#l)) = \text{takeWhile } P\ xs$
 $\langle \text{proof} \rangle$

lemma *dropWhile-append1* [simp]:
 $\llbracket x : \text{set } xs; \sim P(x) \rrbracket \implies \text{dropWhile } P\ (xs\ @\ ys) = (\text{dropWhile } P\ xs)@ys$
 $\langle \text{proof} \rangle$

lemma *dropWhile-append2* [simp]:
 $(\llbracket !x. x : \text{set } xs \implies P(x) \rrbracket \implies \text{dropWhile } P\ (xs\ @\ ys) = \text{dropWhile } P\ ys$
 $\langle \text{proof} \rangle$

lemma *set-take-whileD*: $x : \text{set } (\text{takeWhile } P\ xs) \implies x : \text{set } xs \wedge P\ x$
 $\langle \text{proof} \rangle$

lemma *takeWhile-eq-all-conv*[simp]:
 $(\text{takeWhile } P\ xs = xs) = (\forall x \in \text{set } xs. P\ x)$
 $\langle \text{proof} \rangle$

lemma *dropWhile-eq-Nil-conv*[simp]:
 $(\text{dropWhile } P\ xs = []) = (\forall x \in \text{set } xs. P\ x)$
 $\langle \text{proof} \rangle$

lemma *dropWhile-eq-Cons-conv*:
 $(\text{dropWhile } P\ xs = y\ \#ys) = (xs = \text{takeWhile } P\ xs\ @\ y\ \#ys \ \& \ \neg P\ y)$
 $\langle \text{proof} \rangle$

The following two lemmas could be generalized to an arbitrary property.

lemma *takeWhile-neq-rev*: $\llbracket \text{distinct } xs; x \in \text{set } xs \rrbracket \implies$
 $\text{takeWhile } (\lambda y. y \neq x) (\text{rev } xs) = \text{rev } (tl\ (\text{dropWhile } (\lambda y. y \neq x) xs))$
 $\langle \text{proof} \rangle$

lemma *dropWhile-neq-rev*: $\llbracket \text{distinct } xs; x \in \text{set } xs \rrbracket \implies$
 $\text{dropWhile } (\lambda y. y \neq x) (\text{rev } xs) = x\ \# \text{rev } (\text{takeWhile } (\lambda y. y \neq x) xs)$
 $\langle \text{proof} \rangle$

38.1.13 zip

lemma *zip-Nil* [simp]: $\text{zip } []\ ys = []$
 $\langle \text{proof} \rangle$

lemma *zip-Cons-Cons* [simp]: $\text{zip } (x\ \#xs)\ (y\ \#ys) = (x, y)\ \# \text{zip } xs\ ys$
 $\langle \text{proof} \rangle$

declare *zip-Cons* [simp del]

lemma *zip-Cons1*:
 $\text{zip } (x\ \#xs)\ ys = (\text{case } ys \text{ of } [] \Rightarrow [] \mid y\ \#ys \Rightarrow (x,y)\ \#\text{zip } xs\ ys)$
 $\langle \text{proof} \rangle$

lemma *length-zip* [*simp*]:

$!!xs. \text{length } (\text{zip } xs \ ys) = \min (\text{length } xs) (\text{length } ys)$

$\langle \text{proof} \rangle$

lemma *zip-append1*:

$!!xs. \text{zip } (xs \ @ \ ys) \ zs =$

$\text{zip } xs \ (\text{take } (\text{length } xs) \ zs) \ @ \ \text{zip } ys \ (\text{drop } (\text{length } xs) \ zs)$

$\langle \text{proof} \rangle$

lemma *zip-append2*:

$!!ys. \text{zip } xs \ (ys \ @ \ zs) =$

$\text{zip } (\text{take } (\text{length } ys) \ xs) \ ys \ @ \ \text{zip } (\text{drop } (\text{length } ys) \ xs) \ zs$

$\langle \text{proof} \rangle$

lemma *zip-append* [*simp*]:

$[\text{length } xs = \text{length } us; \text{length } ys = \text{length } vs] ==>$

$\text{zip } (xs @ ys) \ (us @ vs) = \text{zip } xs \ us \ @ \ \text{zip } ys \ vs$

$\langle \text{proof} \rangle$

lemma *zip-rev*:

$\text{length } xs = \text{length } ys ==> \text{zip } (\text{rev } xs) \ (\text{rev } ys) = \text{rev } (\text{zip } xs \ ys)$

$\langle \text{proof} \rangle$

lemma *nth-zip* [*simp*]:

$!!i \ xs. [\text{length } xs; \ i < \text{length } xs; \ i < \text{length } ys] ==> (\text{zip } xs \ ys)!i = (xs!i, \ ys!i)$

$\langle \text{proof} \rangle$

lemma *set-zip*:

$\text{set } (\text{zip } xs \ ys) = \{(xs!i, \ ys!i) \mid i. \ i < \min (\text{length } xs) (\text{length } ys)\}$

$\langle \text{proof} \rangle$

lemma *zip-update*:

$\text{length } xs = \text{length } ys ==> \text{zip } (xs[i:=x]) \ (ys[i:=y]) = (\text{zip } xs \ ys)[i:=(x,y)]$

$\langle \text{proof} \rangle$

lemma *zip-replicate* [*simp*]:

$!!j. \text{zip } (\text{replicate } i \ x) \ (\text{replicate } j \ y) = \text{replicate } (\min \ i \ j) \ (x,y)$

$\langle \text{proof} \rangle$

38.1.14 *list-all2*

lemma *list-all2-lengthD* [*intro?*]:

$\text{list-all2 } P \ xs \ ys ==> \text{length } xs = \text{length } ys$

$\langle \text{proof} \rangle$

lemma *list-all2-Nil* [*iff,code*]: $\text{list-all2 } P \ [] \ ys = (ys = [])$

$\langle \text{proof} \rangle$

lemma *list-all2-Nil2* [*iff*]: $\text{list-all2 } P \ xs \ [] = (xs = [])$

$\langle \text{proof} \rangle$

lemma *list-all2-Cons* [iff, code]:

$\text{list-all2 } P (x \# xs) (y \# ys) = (P x y \wedge \text{list-all2 } P xs ys)$

$\langle \text{proof} \rangle$

lemma *list-all2-Cons1*:

$\text{list-all2 } P (x \# xs) ys = (\exists z zs. ys = z \# zs \wedge P x z \wedge \text{list-all2 } P xs zs)$

$\langle \text{proof} \rangle$

lemma *list-all2-Cons2*:

$\text{list-all2 } P xs (y \# ys) = (\exists z zs. xs = z \# zs \wedge P z y \wedge \text{list-all2 } P zs ys)$

$\langle \text{proof} \rangle$

lemma *list-all2-rev* [iff]:

$\text{list-all2 } P (\text{rev } xs) (\text{rev } ys) = \text{list-all2 } P xs ys$

$\langle \text{proof} \rangle$

lemma *list-all2-rev1*:

$\text{list-all2 } P (\text{rev } xs) ys = \text{list-all2 } P xs (\text{rev } ys)$

$\langle \text{proof} \rangle$

lemma *list-all2-append1*:

$\text{list-all2 } P (xs @ ys) zs =$

$(\exists X us vs. zs = us @ vs \wedge \text{length } us = \text{length } xs \wedge \text{length } vs = \text{length } ys \wedge$

$\text{list-all2 } P xs us \wedge \text{list-all2 } P ys vs)$

$\langle \text{proof} \rangle$

lemma *list-all2-append2*:

$\text{list-all2 } P xs (ys @ zs) =$

$(\exists X us vs. xs = us @ vs \wedge \text{length } us = \text{length } ys \wedge \text{length } vs = \text{length } zs \wedge$

$\text{list-all2 } P us ys \wedge \text{list-all2 } P vs zs)$

$\langle \text{proof} \rangle$

lemma *list-all2-append*:

$\text{length } xs = \text{length } ys \implies$

$\text{list-all2 } P (xs @ us) (ys @ vs) = (\text{list-all2 } P xs ys \wedge \text{list-all2 } P us vs)$

$\langle \text{proof} \rangle$

lemma *list-all2-appendI* [intro?, trans]:

$\llbracket \text{list-all2 } P a b; \text{list-all2 } P c d \rrbracket \implies \text{list-all2 } P (a @ c) (b @ d)$

$\langle \text{proof} \rangle$

lemma *list-all2-conv-all-nth*:

$\text{list-all2 } P xs ys =$

$(\text{length } xs = \text{length } ys \wedge (\forall i < \text{length } xs. P (xs!i) (ys!i)))$

$\langle \text{proof} \rangle$

lemma *list-all2-trans*:

assumes $tr: !!a\ b\ c. P1\ a\ b \implies P2\ b\ c \implies P3\ a\ c$
shows $!!bs\ cs. list_all2\ P1\ as\ bs \implies list_all2\ P2\ bs\ cs \implies list_all2\ P3\ as\ cs$
 (is $!!bs\ cs. PROP\ ?Q\ as\ bs\ cs$)
 $\langle proof \rangle$

lemma *list-all2-all-nthI* [intro?]:
 $length\ a = length\ b \implies (\bigwedge n. n < length\ a \implies P\ (a!n)\ (b!n)) \implies list_all2\ P\ a\ b$
 $\langle proof \rangle$

lemma *list-all2I*:
 $\forall x \in set\ (zip\ a\ b). split\ P\ x \implies length\ a = length\ b \implies list_all2\ P\ a\ b$
 $\langle proof \rangle$

lemma *list-all2-nthD*:
 $\llbracket list_all2\ P\ xs\ ys; p < size\ xs \rrbracket \implies P\ (xs!p)\ (ys!p)$
 $\langle proof \rangle$

lemma *list-all2-nthD2*:
 $\llbracket list_all2\ P\ xs\ ys; p < size\ ys \rrbracket \implies P\ (xs!p)\ (ys!p)$
 $\langle proof \rangle$

lemma *list-all2-map1*:
 $list_all2\ P\ (map\ f\ as)\ bs = list_all2\ (\lambda x\ y. P\ (f\ x)\ y)\ as\ bs$
 $\langle proof \rangle$

lemma *list-all2-map2*:
 $list_all2\ P\ as\ (map\ f\ bs) = list_all2\ (\lambda x\ y. P\ x\ (f\ y))\ as\ bs$
 $\langle proof \rangle$

lemma *list-all2-refl* [intro?]:
 $(\bigwedge x. P\ x\ x) \implies list_all2\ P\ xs\ xs$
 $\langle proof \rangle$

lemma *list-all2-update-cong*:
 $\llbracket i < size\ xs; list_all2\ P\ xs\ ys; P\ x\ y \rrbracket \implies list_all2\ P\ (xs[i:=x])\ (ys[i:=y])$
 $\langle proof \rangle$

lemma *list-all2-update-cong2*:
 $\llbracket list_all2\ P\ xs\ ys; P\ x\ y; i < length\ ys \rrbracket \implies list_all2\ P\ (xs[i:=x])\ (ys[i:=y])$
 $\langle proof \rangle$

lemma *list-all2-takeI* [simp,intro?]:
 $\bigwedge n\ ys. list_all2\ P\ xs\ ys \implies list_all2\ P\ (take\ n\ xs)\ (take\ n\ ys)$
 $\langle proof \rangle$

lemma *list-all2-dropI* [simp,intro?]:
 $\bigwedge n\ bs. list_all2\ P\ as\ bs \implies list_all2\ P\ (drop\ n\ as)\ (drop\ n\ bs)$
 $\langle proof \rangle$

lemma *list-all2-mono* [intro?]:

$\bigwedge y. \text{list-all2 } P \ x \ y \implies (\bigwedge x \ y. P \ x \ y \implies Q \ x \ y) \implies \text{list-all2 } Q \ x \ y$
 <proof>

38.1.15 *foldl* and *foldr*

lemma *foldl-append* [simp]:

$!!a. \text{foldl } f \ a \ (xs \ @ \ ys) = \text{foldl } f \ (\text{foldl } f \ a \ xs) \ ys$
 <proof>

lemma *foldr-append*[simp]: $\text{foldr } f \ (xs \ @ \ ys) \ a = \text{foldr } f \ xs \ (\text{foldr } f \ ys \ a)$
 <proof>

lemma *foldr-foldl*: $\text{foldr } f \ xs \ a = \text{foldl } (\%x \ y. f \ y \ x) \ a \ (\text{rev } xs)$
 <proof>

lemma *foldl-foldr*: $\text{foldl } f \ a \ xs = \text{foldr } (\%x \ y. f \ y \ x) \ (\text{rev } xs) \ a$
 <proof>

Note: $n \leq \text{foldl } (op \ +) \ n \ ns$ looks simpler, but is more difficult to use because it requires an additional transitivity step.

lemma *start-le-sum*: $!!n::nat. m \leq n \implies m \leq \text{foldl } (op \ +) \ n \ ns$
 <proof>

lemma *elem-le-sum*: $!!n::nat. n : \text{set } ns \implies n \leq \text{foldl } (op \ +) \ 0 \ ns$
 <proof>

lemma *sum-eq-0-conv* [iff]:

$!!m::nat. (\text{foldl } (op \ +) \ m \ ns = 0) = (m = 0 \wedge (\forall n \in \text{set } ns. n = 0))$
 <proof>

38.1.16 *upto*

lemma *upt-rec*[code]: $[i..<j] = (\text{if } i < j \text{ then } i \# [\text{Suc } i..<j] \text{ else } [])$
 — simp does not terminate!
 <proof>

lemma *upt-conv-Nil* [simp]: $j \leq i \implies [i..<j] = []$
 <proof>

lemma *upt-eq-Nil-conv*[simp]: $([i..<j] = []) = (j = 0 \vee j \leq i)$
 <proof>

lemma *upt-eq-Cons-conv*:

$!!x \ xs. ([i..<j] = x \# xs) = (i < j \ \& \ i = x \ \& \ [i+1..<j] = xs)$
 <proof>

lemma *upt-Suc-append*: $i \leq j \implies [i..<(\text{Suc } j)] = [i..<j]@[j]$
 — Only needed if *upt-Suc* is deleted from the simpset.

$\langle \text{proof} \rangle$

lemma *upt-conv-Cons*: $i < j \implies [i..<j] = i \# [Suc\ i..<j]$
 $\langle \text{proof} \rangle$

lemma *upt-add-eq-append*: $i <= j \implies [i..<j+k] = [i..<j] @ [j..<j+k]$
 — LOOPS as a simprule, since $j <= j$.
 $\langle \text{proof} \rangle$

lemma *length-upt* [simp]: $length\ [i..<j] = j - i$
 $\langle \text{proof} \rangle$

lemma *nth-upt* [simp]: $i + k < j \implies [i..<j] ! k = i + k$
 $\langle \text{proof} \rangle$

lemma *take-upt* [simp]: $!!i. i + m <= n \implies take\ m\ [i..<n] = [i..<i+m]$
 $\langle \text{proof} \rangle$

lemma *drop-upt*[simp]: $drop\ m\ [i..<j] = [i+m..<j]$
 $\langle \text{proof} \rangle$

lemma *map-Suc-upt*: $map\ Suc\ [m..<n] = [Suc\ m..n]$
 $\langle \text{proof} \rangle$

lemma *nth-map-upt*: $!!i. i < n - m \implies (map\ f\ [m..<n]) ! i = f(m+i)$
 $\langle \text{proof} \rangle$

lemma *nth-take-lemma*:
 $!!xs\ ys. k <= length\ xs \implies k <= length\ ys \implies$
 $(!!i. i < k \longrightarrow xs!i = ys!i) \implies take\ k\ xs = take\ k\ ys$
 $\langle \text{proof} \rangle$

lemma *nth-equalityI*:
 $[| length\ xs = length\ ys; ALL\ i < length\ xs. xs!i = ys!i |] \implies xs = ys$
 $\langle \text{proof} \rangle$

lemma *list-all2-antisym*:
 $[| (\bigwedge x\ y. [P\ x\ y; Q\ y\ x] \implies x = y); list-all2\ P\ xs\ ys; list-all2\ Q\ ys\ xs |]$
 $\implies xs = ys$
 $\langle \text{proof} \rangle$

lemma *take-equalityI*: $(\forall i. take\ i\ xs = take\ i\ ys) \implies xs = ys$
 — The famous take-lemma.
 $\langle \text{proof} \rangle$

lemma *take-Cons'*:
 $take\ n\ (x \# xs) = (if\ n = 0\ then\ []\ else\ x \# take\ (n - 1)\ xs)$

$\langle \text{proof} \rangle$

lemma *drop-Cons'*:

$\text{drop } n \ (x \# xs) = (\text{if } n = 0 \text{ then } x \# xs \text{ else } \text{drop } (n - 1) \ xs)$

$\langle \text{proof} \rangle$

lemma *nth-Cons'*: $(x \# xs)!n = (\text{if } n = 0 \text{ then } x \text{ else } xs!(n - 1))$

$\langle \text{proof} \rangle$

lemmas $[\text{simp}] = \text{take-Cons}'[\text{of number-of } v, \text{standard}]$

$\text{drop-Cons}'[\text{of number-of } v, \text{standard}]$

$\text{nth-Cons}'[\text{of } - \text{ number-of } v, \text{standard}]$

38.1.17 *distinct and remdups*

lemma *distinct-append* $[\text{simp}]$:

$\text{distinct } (xs \ @ \ ys) = (\text{distinct } xs \wedge \text{distinct } ys \wedge \text{set } xs \cap \text{set } ys = \{\})$

$\langle \text{proof} \rangle$

lemma *distinct-rev* $[\text{simp}]$: $\text{distinct}(\text{rev } xs) = \text{distinct } xs$

$\langle \text{proof} \rangle$

lemma *set-remdups* $[\text{simp}]$: $\text{set } (\text{remdups } xs) = \text{set } xs$

$\langle \text{proof} \rangle$

lemma *distinct-remdups* $[\text{iff}]$: $\text{distinct } (\text{remdups } xs)$

$\langle \text{proof} \rangle$

lemma *remdups-eq-nil-iff* $[\text{simp}]$: $(\text{remdups } x = []) = (x = [])$

$\langle \text{proof} \rangle$

lemma *remdups-eq-nil-right-iff* $[\text{simp}]$: $([] = \text{remdups } x) = (x = [])$

$\langle \text{proof} \rangle$

lemma *length-remdups-leq* $[\text{iff}]$: $\text{length}(\text{remdups } xs) \leq \text{length } xs$

$\langle \text{proof} \rangle$

lemma *length-remdups-eq* $[\text{iff}]$:

$(\text{length } (\text{remdups } xs) = \text{length } xs) = (\text{remdups } xs = xs)$

$\langle \text{proof} \rangle$

lemma *distinct-filter* $[\text{simp}]$: $\text{distinct } xs \implies \text{distinct } (\text{filter } P \ xs)$

$\langle \text{proof} \rangle$

lemma *distinct-map-filterI*:

$\text{distinct}(\text{map } f \ xs) \implies \text{distinct}(\text{map } f \ (\text{filter } P \ xs))$

$\langle \text{proof} \rangle$

lemma *distinct-upt* $[\text{simp}]$: $\text{distinct}[i..<j]$

<proof>

lemma *distinct-take[simp]*: $\bigwedge i. \text{distinct } xs \implies \text{distinct } (\text{take } i \text{ } xs)$
<proof>

lemma *distinct-drop[simp]*: $\bigwedge i. \text{distinct } xs \implies \text{distinct } (\text{drop } i \text{ } xs)$
<proof>

lemma *distinct-list-update*:
assumes *d*: *distinct xs* **and** *a*: $a \notin \text{set } xs - \{xs!i\}$
shows *distinct (xs[i:=a])*
<proof>

It is best to avoid this indexed version of *distinct*, but sometimes it is useful.

lemma *distinct-conv-nth*:
 $\text{distinct } xs = (\forall i < \text{size } xs. \forall j < \text{size } xs. i \neq j \longrightarrow xs!i \neq xs!j)$
<proof>

lemma *distinct-card*: $\text{distinct } xs \implies \text{card } (\text{set } xs) = \text{size } xs$
<proof>

lemma *card-distinct*: $\text{card } (\text{set } xs) = \text{size } xs \implies \text{distinct } xs$
<proof>

lemma *inj-on-setI*: $\text{distinct}(\text{map } f \text{ } xs) \implies \text{inj-on } f \text{ } (\text{set } xs)$
<proof>

lemma *inj-on-set-conv*:
 $\text{distinct } xs \implies \text{inj-on } f \text{ } (\text{set } xs) = \text{distinct}(\text{map } f \text{ } xs)$
<proof>

38.1.18 *remove1*

lemma *set-remove1-subset*: $\text{set}(\text{remove1 } x \text{ } xs) \leq \text{set } xs$
<proof>

lemma *set-remove1-eq [simp]*: $\text{distinct } xs \implies \text{set}(\text{remove1 } x \text{ } xs) = \text{set } xs - \{x\}$
<proof>

lemma *notin-set-remove1[simp]*: $x \sim: \text{set } xs \implies x \sim: \text{set}(\text{remove1 } y \text{ } xs)$
<proof>

lemma *distinct-remove1[simp]*: $\text{distinct } xs \implies \text{distinct}(\text{remove1 } x \text{ } xs)$
<proof>

38.1.19 *replicate*

lemma *length-replicate [simp]*: $\text{length } (\text{replicate } n \text{ } x) = n$
<proof>

lemma *map-replicate* [simp]: $\text{map } f (\text{replicate } n \ x) = \text{replicate } n \ (f \ x)$
 ⟨proof⟩

lemma *replicate-app-Cons-same*:
 $(\text{replicate } n \ x) \ @ \ (x \ \# \ xs) = x \ \# \ \text{replicate } n \ x \ @ \ xs$
 ⟨proof⟩

lemma *rev-replicate* [simp]: $\text{rev } (\text{replicate } n \ x) = \text{replicate } n \ x$
 ⟨proof⟩

lemma *replicate-add*: $\text{replicate } (n + m) \ x = \text{replicate } n \ x \ @ \ \text{replicate } m \ x$
 ⟨proof⟩

Courtesy of Matthias Daum:

lemma *append-replicate-commute*:
 $\text{replicate } n \ x \ @ \ \text{replicate } k \ x = \text{replicate } k \ x \ @ \ \text{replicate } n \ x$
 ⟨proof⟩

lemma *hd-replicate* [simp]: $n \neq 0 \implies \text{hd } (\text{replicate } n \ x) = x$
 ⟨proof⟩

lemma *tl-replicate* [simp]: $n \neq 0 \implies \text{tl } (\text{replicate } n \ x) = \text{replicate } (n - 1) \ x$
 ⟨proof⟩

lemma *last-replicate* [simp]: $n \neq 0 \implies \text{last } (\text{replicate } n \ x) = x$
 ⟨proof⟩

lemma *nth-replicate* [simp]: $!!i. \ i < n \implies (\text{replicate } n \ x)!i = x$
 ⟨proof⟩

Courtesy of Matthias Daum (2 lemmas):

lemma *take-replicate* [simp]: $\text{take } i \ (\text{replicate } k \ x) = \text{replicate } (\min i \ k) \ x$
 ⟨proof⟩

lemma *drop-replicate* [simp]: $!!i. \ \text{drop } i \ (\text{replicate } k \ x) = \text{replicate } (k - i) \ x$
 ⟨proof⟩

lemma *set-replicate-Suc*: $\text{set } (\text{replicate } (\text{Suc } n) \ x) = \{x\}$
 ⟨proof⟩

lemma *set-replicate* [simp]: $n \neq 0 \implies \text{set } (\text{replicate } n \ x) = \{x\}$
 ⟨proof⟩

lemma *set-replicate-conv-if*: $\text{set } (\text{replicate } n \ x) = (\text{if } n = 0 \text{ then } \{\} \text{ else } \{x\})$
 ⟨proof⟩

lemma *in-set-replicateD*: $x : \text{set } (\text{replicate } n \ y) \implies x = y$
 ⟨proof⟩

38.1.20 *rotate1 and rotate*

lemma *rotate-simps[simp]*: $\text{rotate1 } [] = [] \wedge \text{rotate1 } (x\#xs) = xs @ [x]$
 $\langle \text{proof} \rangle$

lemma *rotate0[simp]*: $\text{rotate } 0 = \text{id}$
 $\langle \text{proof} \rangle$

lemma *rotate-Suc[simp]*: $\text{rotate } (\text{Suc } n) \ xs = \text{rotate1 } (\text{rotate } n \ xs)$
 $\langle \text{proof} \rangle$

lemma *rotate-add*:
 $\text{rotate } (m+n) = \text{rotate } m \circ \text{rotate } n$
 $\langle \text{proof} \rangle$

lemma *rotate-rotate*: $\text{rotate } m \ (\text{rotate } n \ xs) = \text{rotate } (m+n) \ xs$
 $\langle \text{proof} \rangle$

lemma *rotate1-length01[simp]*: $\text{length } xs \leq 1 \implies \text{rotate1 } xs = xs$
 $\langle \text{proof} \rangle$

lemma *rotate-length01[simp]*: $\text{length } xs \leq 1 \implies \text{rotate } n \ xs = xs$
 $\langle \text{proof} \rangle$

lemma *rotate1-hd-tl*: $xs \neq [] \implies \text{rotate1 } xs = \text{tl } xs @ [\text{hd } xs]$
 $\langle \text{proof} \rangle$

lemma *rotate-drop-take*:
 $\text{rotate } n \ xs = \text{drop } (n \bmod \text{length } xs) \ xs @ \text{take } (n \bmod \text{length } xs) \ xs$
 $\langle \text{proof} \rangle$

lemma *rotate-conv-mod*: $\text{rotate } n \ xs = \text{rotate } (n \bmod \text{length } xs) \ xs$
 $\langle \text{proof} \rangle$

lemma *rotate-id[simp]*: $n \bmod \text{length } xs = 0 \implies \text{rotate } n \ xs = xs$
 $\langle \text{proof} \rangle$

lemma *length-rotate1[simp]*: $\text{length}(\text{rotate1 } xs) = \text{length } xs$
 $\langle \text{proof} \rangle$

lemma *length-rotate[simp]*: $!!xs. \text{length}(\text{rotate } n \ xs) = \text{length } xs$
 $\langle \text{proof} \rangle$

lemma *distinct1-rotate[simp]*: $\text{distinct}(\text{rotate1 } xs) = \text{distinct } xs$
 $\langle \text{proof} \rangle$

lemma *distinct-rotate[simp]*: $\text{distinct}(\text{rotate } n \ xs) = \text{distinct } xs$
 $\langle \text{proof} \rangle$

lemma *rotate-map*: $\text{rotate } n \ (\text{map } f \ xs) = \text{map } f \ (\text{rotate } n \ xs)$

$\langle \text{proof} \rangle$

lemma *set-rotate1*[simp]: $\text{set}(\text{rotate1 } xs) = \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *set-rotate*[simp]: $\text{set}(\text{rotate } n \ xs) = \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *rotate1-is-Nil-conv*[simp]: $(\text{rotate1 } xs = []) = (xs = [])$
 $\langle \text{proof} \rangle$

lemma *rotate-is-Nil-conv*[simp]: $(\text{rotate } n \ xs = []) = (xs = [])$
 $\langle \text{proof} \rangle$

lemma *rotate-rev*:
 $\text{rotate } n \ (\text{rev } xs) = \text{rev}(\text{rotate } (\text{length } xs - (n \bmod \text{length } xs)) \ xs)$
 $\langle \text{proof} \rangle$

38.1.21 *sublist* — a generalization of *nth* to sets

lemma *sublist-empty* [simp]: $\text{sublist } xs \ \{\} = []$
 $\langle \text{proof} \rangle$

lemma *sublist-nil* [simp]: $\text{sublist } [] \ A = []$
 $\langle \text{proof} \rangle$

lemma *length-sublist*:
 $\text{length}(\text{sublist } xs \ I) = \text{card}\{i. i < \text{length } xs \wedge i : I\}$
 $\langle \text{proof} \rangle$

lemma *sublist-shift-lemma-Suc*:
 $!!is. \text{map fst } (\text{filter } (\%p. P(\text{Suc}(\text{snd } p))) (\text{zip } xs \ is)) =$
 $\text{map fst } (\text{filter } (\%p. P(\text{snd } p)) (\text{zip } xs \ (\text{map } \text{Suc } is)))$
 $\langle \text{proof} \rangle$

lemma *sublist-shift-lemma*:
 $\text{map fst } [p:\text{zip } xs \ [i..<i + \text{length } xs] . \text{snd } p : A] =$
 $\text{map fst } [p:\text{zip } xs \ [0..<\text{length } xs] . \text{snd } p + i : A]$
 $\langle \text{proof} \rangle$

lemma *sublist-append*:
 $\text{sublist } (l @ l') \ A = \text{sublist } l \ A @ \text{sublist } l' \ \{j. j + \text{length } l : A\}$
 $\langle \text{proof} \rangle$

lemma *sublist-Cons*:
 $\text{sublist } (x \# l) \ A = (\text{if } 0:A \text{ then } [x] \text{ else } []) @ \text{sublist } l \ \{j. \text{Suc } j : A\}$
 $\langle \text{proof} \rangle$

lemma *set-sublist*: $!!I. \text{set}(\text{sublist } xs \ I) = \{xs!i | i. i < \text{size } xs \wedge i \in I\}$

$\langle \text{proof} \rangle$

lemma *set-sublist-subset*: $\text{set}(\text{sublist } xs \ I) \subseteq \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *notin-set-sublistI[simp]*: $x \notin \text{set } xs \implies x \notin \text{set}(\text{sublist } xs \ I)$
 $\langle \text{proof} \rangle$

lemma *in-set-sublistD*: $x \in \text{set}(\text{sublist } xs \ I) \implies x \in \text{set } xs$
 $\langle \text{proof} \rangle$

lemma *sublist-singleton [simp]*: $\text{sublist } [x] \ A = (\text{if } 0 : A \text{ then } [x] \text{ else } [])$
 $\langle \text{proof} \rangle$

lemma *distinct-sublistI[simp]*: $!!I. \text{distinct } xs \implies \text{distinct}(\text{sublist } xs \ I)$
 $\langle \text{proof} \rangle$

lemma *sublist-upt-eq-take [simp]*: $\text{sublist } l \ \{..
 $\langle \text{proof} \rangle$$

lemma *filter-in-sublist*: $\bigwedge s. \text{distinct } xs \implies$
 $\text{filter } (\%x. x \in \text{set}(\text{sublist } xs \ s)) \ xs = \text{sublist } xs \ s$
 $\langle \text{proof} \rangle$

38.1.22 Sets of Lists

38.1.23 *lists*: the list-forming operator over sets

consts *lists* :: 'a set => 'a list set

inductive *lists* A

intros

Nil [intro!]: $[] : \text{lists } A$

Cons [intro!]: $[a : A; l : \text{lists } A] ==> a \# l : \text{lists } A$

inductive-cases *listsE* [elim!]: $x \# l : \text{lists } A$

lemma *lists-mono [mono]*: $A \subseteq B ==> \text{lists } A \subseteq \text{lists } B$
 $\langle \text{proof} \rangle$

lemma *lists-IntI*:

assumes $l : \text{lists } A$ **shows** $l : \text{lists } B ==> l : \text{lists } (A \text{ Int } B)$ $\langle \text{proof} \rangle$

lemma *lists-Int-eq [simp]*: $\text{lists } (A \cap B) = \text{lists } A \cap \text{lists } B$
 $\langle \text{proof} \rangle$

lemma *append-in-lists-conv [iff]*:

$(xs @ ys : \text{lists } A) = (xs : \text{lists } A \wedge ys : \text{lists } A)$

$\langle \text{proof} \rangle$

lemma *in-lists-conv-set*: $(xs : \text{lists } A) = (\forall x \in \text{set } xs. x : A)$
 — eliminate *lists* in favour of *set*
 $\langle \text{proof} \rangle$

lemma *in-listsD* [*dest!*]: $xs \in \text{lists } A \implies \forall x \in \text{set } xs. x \in A$
 $\langle \text{proof} \rangle$

lemma *in-listsI* [*intro!*]: $\forall x \in \text{set } xs. x \in A \implies xs \in \text{lists } A$
 $\langle \text{proof} \rangle$

lemma *lists-UNIV* [*simp*]: $\text{lists } UNIV = UNIV$
 $\langle \text{proof} \rangle$

38.1.24 For efficiency

Only use *mem* for generating executable code. Otherwise use $x \in \text{set } xs$ instead — it is much easier to reason about. The same is true for *list-all* and *list-ex*: write $\forall x \in \text{set } xs$ and $\exists x \in \text{set } xs$ instead because the HOL quantifiers are already known to the automatic provers. In fact, the declarations in the Code subsection make sure that \in , $\forall x \in \text{set } xs$ and $\exists x \in \text{set } xs$ are implemented efficiently.

The functions *itrev*, *filtermap* and *map-filter* are just there to generate efficient code. Do not use them for modelling and proving.

lemma *mem-iff*: $(x \text{ mem } xs) = (x : \text{set } xs)$
 $\langle \text{proof} \rangle$

lemma *list-inter-conv*: $\text{set}(\text{list-inter } xs \ ys) = \text{set } xs \cap \text{set } ys$
 $\langle \text{proof} \rangle$

lemma *list-all-iff*: $\text{list-all } P \ xs = (\forall x \in \text{set } xs. P \ x)$
 $\langle \text{proof} \rangle$

lemma *list-all-append* [*simp*]:
 $\text{list-all } P \ (xs \ @ \ ys) = (\text{list-all } P \ xs \wedge \text{list-all } P \ ys)$
 $\langle \text{proof} \rangle$

lemma *list-all-rev* [*simp*]: $\text{list-all } P \ (\text{rev } xs) = \text{list-all } P \ xs$
 $\langle \text{proof} \rangle$

lemma *list-ex-iff*: $\text{list-ex } P \ xs = (\exists x \in \text{set } xs. P \ x)$
 $\langle \text{proof} \rangle$

lemma *itrev* [*simp*]: $ALL \ ys. \text{itrev } xs \ ys = \text{rev } xs \ @ \ ys$
 $\langle \text{proof} \rangle$

lemma *filtermap-conv*:
 $\text{filtermap } f \ xs = \text{map } (\%x. \text{the}(f \ x)) \ (\text{filter } (\%x. f \ x \neq \text{None}) \ xs)$

<proof>

lemma *map-filter-conv*[simp]: *map-filter* *f P xs* = *map* *f* (*filter* *P xs*)
<proof>

38.1.25 Code generation

Defaults for generating efficient code for some standard functions.

lemmas *in-set-code*[code unfold] = *mem-iff*[symmetric, THEN *eq-reflection*]

lemma *rev-code*[code unfold]: *rev xs* == *itrev xs* []
<proof>

lemma *distinct-Cons-mem*[code]: *distinct* (*x#xs*) = (\sim (*x mem xs*) \wedge *distinct xs*)
<proof>

lemma *remdups-Cons-mem*[code]:
remdups (*x#xs*) = (*if* *x mem xs* *then* *remdups xs* *else* *x # remdups xs*)
<proof>

lemma *list-inter-Cons-mem*[code]: *list-inter* (*a#as*) *bs* =
(*if* *a mem bs* *then* *a#(list-inter as bs)* *else* *list-inter as bs*)
<proof>

For implementing bounded quantifiers over lists by *list-ex*/*list-all*:

lemmas *list-bex-code*[code unfold] = *list-ex-iff*[symmetric, THEN *eq-reflection*]
lemmas *list-ball-code*[code unfold] = *list-all-iff*[symmetric, THEN *eq-reflection*]

38.1.26 Inductive definition for membership

consts *ListMem* :: ('a \times 'a list) set

inductive *ListMem*

intros

elem: (*x,x#xs*) \in *ListMem*

insert: (*x,xs*) \in *ListMem* \implies (*x,y#xs*) \in *ListMem*

lemma *ListMem-iff*: ((*x,xs*) \in *ListMem*) = (*x* \in *set xs*)
<proof>

38.1.27 Lists as Cartesian products

set-Cons *A Xs*: the set of lists with head drawn from *A* and tail drawn from *Xs*.

constdefs

set-Cons :: 'a set \Rightarrow 'a list set \Rightarrow 'a list set

set-Cons *A XS* == {*z*. \exists *x xs*. *z* = *x#xs* & *x* \in *A* & *xs* \in *XS*}

lemma *set-Cons-sing-Nil* [simp]: *set-Cons* *A* {[]} = (%*x*. [*x*]) 'A

$\langle proof \rangle$

Yields the set of lists, all of the same length as the argument and with elements drawn from the corresponding element of the argument.

consts *listset* :: 'a set list \Rightarrow 'a list set

primrec

listset [] = {}

listset(A#As) = set-Cons A (*listset* As)

38.2 Relations on Lists

38.2.1 Length Lexicographic Ordering

These orderings preserve well-foundedness: shorter lists precede longer lists. These ordering are not used in dictionaries.

consts *lexn* :: ('a * 'a) set \Rightarrow nat \Rightarrow ('a list * 'a list) set

— The lexicographic ordering for lists of the specified length

primrec

lexn r 0 = {}

lexn r (Suc n) =

(prod-fun (%(x,xs). x#xs) (%(x,xs). x#xs) ‘ (r < *lex* > *lexn* r n)) Int
 {(x,ys). length xs = Suc n \wedge length ys = Suc n}

constdefs

lex :: ('a \times 'a) set \Rightarrow ('a list \times 'a list) set

lex r == $\bigcup n. \text{lexn } r \ n$

— Holds only between lists of the same length

lenlex :: ('a \times 'a) set \Rightarrow ('a list \times 'a list) set

lenlex r == inv-image (less-than < *lex* > *lex* r) (%xs. (length xs, xs))

— Compares lists by their length and then lexicographically

lemma *wf-lexn*: wf r \Rightarrow wf (*lexn* r n)

$\langle proof \rangle$

lemma *lexn-length*:

!!xs ys. (xs, ys) : *lexn* r n \Rightarrow length xs = n \wedge length ys = n

$\langle proof \rangle$

lemma *wf-lex* [intro!]: wf r \Rightarrow wf (*lex* r)

$\langle proof \rangle$

lemma *lexn-conv*:

lexn r n =

{(xs,ys). length xs = n \wedge length ys = n \wedge

($\exists xys \ x \ y \ xs' \ ys'. \ xs = xys @ x\#xs' \wedge \ ys = xys @ y\#ys' \wedge (x, y):r$)}

$\langle proof \rangle$

lemma *lex-conv*:

$lex\ r =$
 $\{(xs,ys). length\ xs = length\ ys \wedge$
 $(\exists\ xys\ x\ y\ xs'\ ys'. xs = xys @ x \# xs' \wedge ys = xys @ y \# ys' \wedge (x, y):r)\}$
 $\langle proof \rangle$

lemma *wf-lenlex [intro!]*: $wf\ r ==> wf\ (lenlex\ r)$

$\langle proof \rangle$

lemma *lenlex-conv*:

$lenlex\ r = \{(xs,ys). length\ xs < length\ ys \mid$
 $length\ xs = length\ ys \wedge (xs, ys) : lex\ r\}$
 $\langle proof \rangle$

lemma *Nil-notin-lex [iff]*: $([], ys) \notin lex\ r$

$\langle proof \rangle$

lemma *Nil2-notin-lex [iff]*: $(xs, []) \notin lex\ r$

$\langle proof \rangle$

lemma *Cons-in-lex [iff]*:

$((x \# xs, y \# ys) : lex\ r) =$
 $((x, y) : r \wedge length\ xs = length\ ys \mid x = y \wedge (xs, ys) : lex\ r)$
 $\langle proof \rangle$

38.2.2 Lexicographic Ordering

Classical lexicographic ordering on lists, ie. "a" i "ab" i "b". This ordering does *not* preserve well-foundedness. Author: N. Voelker, March 2005.

constdefs

$lexord :: ('a * 'a) set \Rightarrow ('a\ list * 'a\ list)\ set$
 $lexord\ r == \{(x,y). \exists\ a\ v. y = x @ a \# v \vee$
 $(\exists\ u\ a\ b\ v\ w. (a,b) \in r \wedge x = u @ (a \# v) \wedge y = u @ (b \# w))\}$

lemma *lexord-Nil-left[simp]*: $([],y) \in lexord\ r = (\exists\ a\ x. y = a \# x)$

$\langle proof \rangle$

lemma *lexord-Nil-right[simp]*: $(x,[]) \notin lexord\ r$

$\langle proof \rangle$

lemma *lexord-cons-cons[simp]*:

$((a \# x, b \# y) \in lexord\ r) = ((a,b) \in r \mid (a = b \ \& \ (x,y) \in lexord\ r))$
 $\langle proof \rangle$

lemmas *lexord-simps* = *lexord-Nil-left lexord-Nil-right lexord-cons-cons*

lemma *lexord-append-rightI*: $\exists\ b\ z. y = b \# z \implies (x, x @ y) \in lexord\ r$

$\langle proof \rangle$

lemma *lexord-append-left-rightI*:

$$(a, b) \in r \implies (u @ a \# x, u @ b \# y) \in \text{lexord } r$$

<proof>

lemma *lexord-append-leftI*: $(u, v) \in \text{lexord } r \implies (x @ u, x @ v) \in \text{lexord } r$

<proof>

lemma *lexord-append-leftD*:

$$\llbracket (x @ u, x @ v) \in \text{lexord } r; (! a. (a, a) \notin r) \rrbracket \implies (u, v) \in \text{lexord } r$$

<proof>

lemma *lexord-take-index-conv*:

$$\begin{aligned} ((x, y) : \text{lexord } r) = \\ ((\text{length } x < \text{length } y \wedge \text{take } (\text{length } x) \ y = x) \vee \\ (\exists i. i < \min(\text{length } x)(\text{length } y) \ \& \ \text{take } i \ x = \text{take } i \ y \ \& \ (x!i, y!i) \in r)) \end{aligned}$$

<proof>

lemma *lexord-lex*: $(x, y) \in \text{lex } r = ((x, y) \in \text{lexord } r \wedge \text{length } x = \text{length } y)$

<proof>

lemma *lexord-irreflexive*: $(! x. (x, x) \notin r) \implies (y, y) \notin \text{lexord } r$

<proof>

lemma *lexord-trans*:

$$\llbracket (x, y) \in \text{lexord } r; (y, z) \in \text{lexord } r; \text{trans } r \rrbracket \implies (x, z) \in \text{lexord } r$$

<proof>

lemma *lexord-transI*: $\text{trans } r \implies \text{trans } (\text{lexord } r)$

<proof>

lemma *lexord-linear*: $(! a \ b. (a, b) \in r \mid a = b \mid (b, a) \in r) \implies (x, y) : \text{lexord } r \mid x = y \mid (y, x) : \text{lexord } r$

<proof>

38.2.3 Lifting a Relation on List Elements to the Lists

consts *listrel* :: $('a * 'a)\text{set} \implies ('a \text{ list} * 'a \text{ list})\text{set}$

inductive *listrel*(*r*)

intros

Nil: $([], []) \in \text{listrel } r$

Cons: $\llbracket (x, y) \in r; (xs, ys) \in \text{listrel } r \rrbracket \implies (x \# xs, y \# ys) \in \text{listrel } r$

inductive-cases *listrel-Nil1* [*elim!*]: $([], xs) \in \text{listrel } r$

inductive-cases *listrel-Nil2* [*elim!*]: $(xs, []) \in \text{listrel } r$

inductive-cases *listrel-Cons1* [*elim!*]: $(y \# ys, xs) \in \text{listrel } r$

inductive-cases *listrel-Cons2* [*elim!*]: $(xs, y \# ys) \in \text{listrel } r$

lemma *listrel-mono*: $r \subseteq s \implies \text{listrel } r \subseteq \text{listrel } s$

<proof>

lemma *listrel-subset*: $r \subseteq A \times A \implies \text{listrel } r \subseteq \text{lists } A \times \text{lists } A$
<proof>

lemma *listrel-refl*: $\text{refl } A \implies \text{refl } (\text{lists } A) (\text{listrel } r)$
<proof>

lemma *listrel-sym*: $\text{sym } r \implies \text{sym } (\text{listrel } r)$
<proof>

lemma *listrel-trans*: $\text{trans } r \implies \text{trans } (\text{listrel } r)$
<proof>

theorem *equiv-listrel*: $\text{equiv } A \implies \text{equiv } (\text{lists } A) (\text{listrel } r)$
<proof>

lemma *listrel-Nil* [*simp*]: $\text{listrel } r \text{ “ } \{\} = \{\}$
<proof>

lemma *listrel-Cons*:
 $\text{listrel } r \text{ “ } \{x \# xs\} = \text{set-Cons } (r \text{ “ } \{x\}) (\text{listrel } r \text{ “ } \{xs\})$
<proof>

38.3 Miscellany

38.3.1 Characters and strings

datatype *nibble* =
 $\text{Nibble0} \mid \text{Nibble1} \mid \text{Nibble2} \mid \text{Nibble3} \mid \text{Nibble4} \mid \text{Nibble5} \mid \text{Nibble6} \mid \text{Nibble7}$
 $\mid \text{Nibble8} \mid \text{Nibble9} \mid \text{NibbleA} \mid \text{NibbleB} \mid \text{NibbleC} \mid \text{NibbleD} \mid \text{NibbleE} \mid \text{NibbleF}$

datatype *char* = *Char nibble nibble*
 — Note: canonical order of character encoding coincides with standard term ordering

types *string* = *char list*

syntax
 $\text{-Char} :: \text{xstr} \Rightarrow \text{char} \quad (\text{CHR } -)$
 $\text{-String} :: \text{xstr} \Rightarrow \text{string} \quad (-)$

<ML>

38.3.2 Code generator setup

<ML>

types-code
 $\text{list } (- \text{ list})$

```

attach (term-of) ⟨⟨
  val term-of-list = HOLogic.mk-list;
  ⟩⟩
attach (test) ⟨⟨
  fun gen-list' aG i j = frequency
    [(i, fn () => aG j :: gen-list' aG (i-1) j), (1, fn () => [])] ()
  and gen-list aG i = gen-list' aG i i;
  ⟩⟩
  char (string)
attach (term-of) ⟨⟨
  val nibbleT = Type (List.nibble, []);

  fun term-of-char c =
    Const (List.char.Char, nibbleT --> nibbleT --> Type (List.char, [])) $
    Const (List.nibble.Nibble ^ nibble-of-int (ord c div 16), nibbleT) $
    Const (List.nibble.Nibble ^ nibble-of-int (ord c mod 16), nibbleT);
  ⟩⟩
attach (test) ⟨⟨
  fun gen-char i = chr (random-range (ord a) (Int.min (ord a + i, ord z)));
  ⟩⟩

consts-code Cons ((- :: / -))

⟨ML⟩

end

```

39 Map: Maps

```

theory Map
imports List
begin

```

```

types ('a,'b) ~=> = 'a => 'b option (infixr 0)
translations (type) a ~=> b <= (type) a => b option

```

```

consts
chg-map :: ('b => 'b) => 'a => ('a ~=> 'b) => ('a ~=> 'b)
map-add :: ('a ~=> 'b) => ('a ~=> 'b) => ('a ~=> 'b) (infixl ++ 100)
restrict-map :: ('a ~=> 'b) => 'a set => ('a ~=> 'b) (infixl |' 110)
dom      :: ('a ~=> 'b) => 'a set
ran      :: ('a ~=> 'b) => 'b set
map-of   :: ('a * 'b)list => 'a ~=> 'b
map-upds:: ('a ~=> 'b) => 'a list => 'b list =>
  ('a ~=> 'b)
map-upd-s::('a ~=> 'b) => 'a set => 'b =>
  ('a ~=> 'b) (-/'{->}-/' [900,0,0]900)
map-subst::('a ~=> 'b) => 'b => 'b =>

```

$$\begin{array}{l} \text{map-le} :: ('a \rightsquigarrow 'b) \Rightarrow ('a \rightsquigarrow 'b) \Rightarrow \text{bool} \text{ (infix } \subseteq_m \text{ 50)} \\ \quad \quad \quad (-/'(-\rightsquigarrow-/') \quad [900,0,0]900) \end{array}$$

constdefs

$$\begin{array}{l} \text{map-comp} :: ('b \rightsquigarrow 'c) \Rightarrow ('a \rightsquigarrow 'b) \Rightarrow ('a \rightsquigarrow 'c) \text{ (infixl } o'-m \text{ 55)} \\ f \text{ o-}m \text{ } g == (\lambda k. \text{ case } g \text{ } k \text{ of } \text{None} \Rightarrow \text{None} \mid \text{Some } v \Rightarrow f \text{ } v) \end{array}$$

nonterminals

maplets maplet

syntax

$$\begin{array}{l} \text{empty} :: 'a \rightsquigarrow 'b \\ \text{-maplet} :: ['a, 'a] \Rightarrow \text{maplet} \quad (- \text{ /| } -> / -) \\ \text{-maplets} :: ['a, 'a] \Rightarrow \text{maplet} \quad (- \text{ /| } -> | / -) \\ \quad \quad \quad :: \text{maplet} \Rightarrow \text{maplets} \quad (-) \\ \text{-Maplets} :: [\text{maplet}, \text{maplets}] \Rightarrow \text{maplets} \quad (-, / -) \\ \text{-MapUpd} :: ['a \rightsquigarrow 'b, \text{maplets}] \Rightarrow 'a \rightsquigarrow 'b \quad (-/'(-') \text{ [900,0]900}) \\ \text{-Map} :: \text{maplets} \Rightarrow 'a \rightsquigarrow 'b \quad ((1[-])) \end{array}$$

syntax (*xsymbols*)

$$\rightsquigarrow :: [\text{type}, \text{type}] \Rightarrow \text{type} \quad (\text{infixr } \rightarrow 0)$$

$$\text{map-comp} :: ('b \rightsquigarrow 'c) \Rightarrow ('a \rightsquigarrow 'b) \Rightarrow ('a \rightsquigarrow 'c) \text{ (infixl } \circ_m \text{ 55)}$$

$$\begin{array}{l} \text{-maplet} :: ['a, 'a] \Rightarrow \text{maplet} \quad (- \text{ /| } \mapsto / -) \\ \text{-maplets} :: ['a, 'a] \Rightarrow \text{maplet} \quad (- \text{ /| } \mapsto | / -) \end{array}$$

$$\begin{array}{l} \text{map-upd-s} :: ('a \rightsquigarrow 'b) \Rightarrow 'a \text{ set} \Rightarrow 'b \Rightarrow ('a \rightsquigarrow 'b) \\ \quad \quad \quad (-/'(-/\{\mapsto\}/-') \text{ [900,0,0]900}) \end{array}$$

$$\begin{array}{l} \text{map-subst} :: ('a \rightsquigarrow 'b) \Rightarrow 'b \Rightarrow 'b \Rightarrow \\ \quad \quad \quad ('a \rightsquigarrow 'b) \quad (-/'(\rightsquigarrow-/') \text{ [900,0,0]900}) \end{array}$$

$$\begin{array}{l} @chg\text{-map} :: ('a \rightsquigarrow 'b) \Rightarrow 'a \Rightarrow ('b \Rightarrow 'b) \Rightarrow ('a \rightsquigarrow 'b) \\ \quad \quad \quad (-/'(-/\mapsto\lambda-. -') \text{ [900,0,0,0] 900}) \end{array}$$

syntax (*latex output*)

$$\begin{array}{l} \text{restrict-map} :: ('a \rightsquigarrow 'b) \Rightarrow 'a \text{ set} \Rightarrow ('a \rightsquigarrow 'b) \quad (-| \text{ [111,110] 110}) \\ \text{--- requires amssymb!} \end{array}$$

translations

$$\begin{array}{l} \text{empty} \Rightarrow -K \text{ None} \\ \text{empty} \Leftarrow \%x. \text{ None} \end{array}$$

$$m(x \mapsto \lambda y. f) == \text{chg-map } (\lambda y. f) \text{ } x \text{ } m$$

$$\begin{array}{l} \text{-MapUpd } m \text{ (-Maplets } xy \text{ } ms) == \text{-MapUpd } (\text{-MapUpd } m \text{ } xy) \text{ } ms \\ \text{-MapUpd } m \text{ (-maplet } x \text{ } y) == m(x := \text{Some } y) \\ \text{-MapUpd } m \text{ (-maplets } x \text{ } y) == \text{map-upds } m \text{ } x \text{ } y \\ \text{-Map } ms == \text{-MapUpd } \text{empty} \text{ } ms \\ \text{-Map } (-\text{Maplets } ms1 \text{ } ms2) \Leftarrow \text{-MapUpd } (-\text{Map } ms1) \text{ } ms2 \end{array}$$

$-Maplets\ ms1\ (-Maplets\ ms2\ ms3) \leq -Maplets\ (-Maplets\ ms1\ ms2)\ ms3$

defs

$chg-map-def: chg-map\ f\ a\ m == case\ m\ a\ of\ None \Rightarrow m \mid Some\ b \Rightarrow m(a|->f\ b)$

$map-add-def: m1++m2 == \%x. case\ m2\ x\ of\ None \Rightarrow m1\ x \mid Some\ y \Rightarrow Some\ y$

$restrict-map-def: m|'A == \%x. if\ x : A\ then\ m\ x\ else\ None$

$map-upds-def: m(xs\ [|->]\ ys) == m\ ++\ map-of\ (rev(zip\ xs\ ys))$

$map-upd-s-def: m(as\ \{|->\}b) == \%x. if\ x : as\ then\ Some\ b\ else\ m\ x$

$map-subst-def: m(a\sim>b) == \%x. if\ m\ x = Some\ a\ then\ Some\ b\ else\ m\ x$

$dom-def: dom(m) == \{a. m\ a \sim None\}$

$ran-def: ran(m) == \{b. EX\ a. m\ a = Some\ b\}$

$map-le-def: m_1 \subseteq_m m_2 == ALL\ a : dom\ m_1. m_1\ a = m_2\ a$

primrec

$map-of\ [] = empty$

$map-of\ (p\#ps) = (map-of\ ps)(fst\ p\ |->\ snd\ p)$

39.1 empty

lemma $empty-upd-none[simp]: empty(x := None) = empty$
 $\langle proof \rangle$

lemma $sum-case-empty-empty[simp]: sum-case\ empty\ empty = empty$
 $\langle proof \rangle$

39.2 map-upd

lemma $map-upd-triv: t\ k = Some\ x ==> t(k|->x) = t$
 $\langle proof \rangle$

lemma $map-upd-nonempty[simp]: t(k|->x) \sim empty$
 $\langle proof \rangle$

lemma $map-upd-eqD1: m(a\mapsto x) = n(a\mapsto y) \implies x = y$
 $\langle proof \rangle$

lemma $map-upd-Some-unfold:$

$((m(a|->b))\ x = Some\ y) = (x = a \wedge b = y \vee x \neq a \wedge m\ x = Some\ y)$
 $\langle proof \rangle$

lemma $image-map-upd[simp]: x \notin A \implies m(x \mapsto y) \restriction A = m \restriction A$
 $\langle proof \rangle$

lemma *finite-range-updI*: $\text{finite } (\text{range } f) \implies \text{finite } (\text{range } (f(a|-\>b)))$
 <proof>

39.3 *sum-case and empty/map-upd*

lemma *sum-case-map-upd-empty[simp]*:
 $\text{sum-case } (m(k|-\>y)) \text{ empty} = (\text{sum-case } m \text{ empty})(\text{Inl } k|-\>y)$
 <proof>

lemma *sum-case-empty-map-upd[simp]*:
 $\text{sum-case empty } (m(k|-\>y)) = (\text{sum-case empty } m)(\text{Inr } k|-\>y)$
 <proof>

lemma *sum-case-map-upd-map-upd[simp]*:
 $\text{sum-case } (m1(k1|-\>y1)) (m2(k2|-\>y2)) = (\text{sum-case } (m1(k1|-\>y1)) m2)(\text{Inr } k2|-\>y2)$
 <proof>

39.4 *chg-map*

lemma *chg-map-new[simp]*: $m \ a = \text{None} \implies \text{chg-map } f \ a \ m = m$
 <proof>

lemma *chg-map-upd[simp]*: $m \ a = \text{Some } b \implies \text{chg-map } f \ a \ m = m(a|-\>f \ b)$
 <proof>

lemma *chg-map-other [simp]*: $a \neq b \implies \text{chg-map } f \ a \ m \ b = m \ b$
 <proof>

39.5 *map-of*

lemma *map-of-eq-None-iff*:
 $(\text{map-of } xys \ x = \text{None}) = (x \notin \text{fst } ^\circ (\text{set } xys))$
 <proof>

lemma *map-of-is-SomeD*:
 $\text{map-of } xys \ x = \text{Some } y \implies (x, y) \in \text{set } xys$
 <proof>

lemma *map-of-eq-Some-iff[simp]*:
 $\text{distinct}(\text{map fst } xys) \implies (\text{map-of } xys \ x = \text{Some } y) = ((x, y) \in \text{set } xys)$
 <proof>

lemma *Some-eq-map-of-iff[simp]*:
 $\text{distinct}(\text{map fst } xys) \implies (\text{Some } y = \text{map-of } xys \ x) = ((x, y) \in \text{set } xys)$
 <proof>

lemma *map-of-is-SomeI [simp]*: $\llbracket \text{distinct}(\text{map fst } xys); (x, y) \in \text{set } xys \rrbracket$
 $\implies \text{map-of } xys \ x = \text{Some } y$

$\langle proof \rangle$

lemma *map-of-zip-is-None*[simp]:

$length\ xs = length\ ys \implies (map-of\ (zip\ xs\ ys)\ x = None) = (x \notin set\ xs)$
 $\langle proof \rangle$

lemma *finite-range-map-of*: *finite* (range (map-of *xy*s))

$\langle proof \rangle$

lemma *map-of-SomeD* [rule-format]: *map-of* *xs* *k* = *Some* *y* $\dashv\!\!\dashv\!\!\rightarrow$ (*k*,*y*):*set* *xs*

$\langle proof \rangle$

lemma *map-of-mapk-SomeI* [rule-format]:

$inj\ f \implies map-of\ t\ k = Some\ x \dashv\!\!\dashv\!\!\rightarrow$
 $map-of\ (map\ (split\ (\%k.\ Pair\ (f\ k)))\ t)\ (f\ k) = Some\ x$
 $\langle proof \rangle$

lemma *weak-map-of-SomeI* [rule-format]:

$(k, x) : set\ l \dashv\!\!\dashv\!\!\rightarrow (\exists x.\ map-of\ l\ k = Some\ x)$
 $\langle proof \rangle$

lemma *map-of-filter-in*:

$[| map-of\ xs\ k = Some\ z; P\ k\ z |] \implies map-of\ (filter\ (split\ P)\ xs)\ k = Some\ z$
 $\langle proof \rangle$

lemma *map-of-map*: *map-of* (map (%(*a*,*b*)). (*a*,*f* *b*)) *xs* *x* = *option-map* *f* (*map-of* *xs* *x*)

$\langle proof \rangle$

39.6 option-map related

lemma *option-map-o-empty*[simp]: *option-map* *f* *o* *empty* = *empty*

$\langle proof \rangle$

lemma *option-map-o-map-upd*[simp]:

$option-map\ f\ o\ m(a|->b) = (option-map\ f\ o\ m)(a|->f\ b)$
 $\langle proof \rangle$

39.7 map-comp related

lemma *map-comp-empty* [simp]:

$m \circ_m empty = empty$
 $empty \circ_m m = empty$
 $\langle proof \rangle$

lemma *map-comp-simps* [simp]:

$m2\ k = None \implies (m1 \circ_m m2)\ k = None$
 $m2\ k = Some\ k' \implies (m1 \circ_m m2)\ k = m1\ k'$
 $\langle proof \rangle$

lemma *map-comp-Some-iff*:

$((m1 \circ_m m2) \ k = \text{Some } v) = (\exists k'. m2 \ k = \text{Some } k' \wedge m1 \ k' = \text{Some } v)$
 $\langle \text{proof} \rangle$

lemma *map-comp-None-iff*:

$((m1 \circ_m m2) \ k = \text{None}) = (m2 \ k = \text{None} \vee (\exists k'. m2 \ k = \text{Some } k' \wedge m1 \ k' = \text{None}))$
 $\langle \text{proof} \rangle$

39.8 ++

lemma *map-add-empty[simp]*: $m \ ++ \ \text{empty} = m$
 $\langle \text{proof} \rangle$

lemma *empty-map-add[simp]*: $\text{empty} \ ++ \ m = m$
 $\langle \text{proof} \rangle$

lemma *map-add-assoc[simp]*: $m1 \ ++ \ (m2 \ ++ \ m3) = (m1 \ ++ \ m2) \ ++ \ m3$
 $\langle \text{proof} \rangle$

lemma *map-add-Some-iff*:

$((m \ ++ \ n) \ k = \text{Some } x) = (n \ k = \text{Some } x \mid n \ k = \text{None} \ \& \ m \ k = \text{Some } x)$
 $\langle \text{proof} \rangle$

lemmas *map-add-SomeD* = *map-add-Some-iff* [THEN *iffD1*, standard]

declare *map-add-SomeD* [dest!]

lemma *map-add-find-right[simp]*: $!!x. n \ k = \text{Some } x \implies (m \ ++ \ n) \ k = \text{Some } x$
 $\langle \text{proof} \rangle$

lemma *map-add-None [iff]*: $((m \ ++ \ n) \ k = \text{None}) = (n \ k = \text{None} \ \& \ m \ k = \text{None})$
 $\langle \text{proof} \rangle$

lemma *map-add-upd[simp]*: $f \ ++ \ g(x|->y) = (f \ ++ \ g)(x|->y)$
 $\langle \text{proof} \rangle$

lemma *map-add-upds[simp]*: $m1 \ ++ \ (m2(xs[\mapsto]ys)) = (m1 \ ++ \ m2)(xs[\mapsto]ys)$
 $\langle \text{proof} \rangle$

lemma *map-of-append[simp]*: $\text{map-of } (xs@ys) = \text{map-of } ys \ ++ \ \text{map-of } xs$
 $\langle \text{proof} \rangle$

declare *fun-upd-apply* [simp del]

lemma *finite-range-map-of-map-add*:

$\text{finite } (\text{range } f) \implies \text{finite } (\text{range } (f \ ++ \ \text{map-of } l))$
 $\langle \text{proof} \rangle$

declare *fun-upd-apply* [simp]

lemma *inj-on-map-add-dom*[*iff*]:
 $\text{inj-on } (m \text{ ++ } m') \text{ (dom } m') = \text{inj-on } m' \text{ (dom } m')$
 ⟨*proof*⟩

39.9 restrict-map

lemma *restrict-map-to-empty*[*simp*]: $m|'\{\} = \text{empty}$
 ⟨*proof*⟩

lemma *restrict-map-empty*[*simp*]: $\text{empty}|'D = \text{empty}$
 ⟨*proof*⟩

lemma *restrict-in* [*simp*]: $x \in A \implies (m|'A) x = m x$
 ⟨*proof*⟩

lemma *restrict-out* [*simp*]: $x \notin A \implies (m|'A) x = \text{None}$
 ⟨*proof*⟩

lemma *ran-restrictD*: $y \in \text{ran } (m|'A) \implies \exists x \in A. m x = \text{Some } y$
 ⟨*proof*⟩

lemma *dom-restrict* [*simp*]: $\text{dom } (m|'A) = \text{dom } m \cap A$
 ⟨*proof*⟩

lemma *restrict-upd-same* [*simp*]: $m(x \mapsto y)|'(-\{x\}) = m|'(-\{x\})$
 ⟨*proof*⟩

lemma *restrict-restrict* [*simp*]: $m|'A|'B = m|'(A \cap B)$
 ⟨*proof*⟩

lemma *restrict-fun-upd*[*simp*]:
 $m(x := y)|'D = (\text{if } x \in D \text{ then } (m|'(D - \{x\}))(x := y) \text{ else } m|'D)$
 ⟨*proof*⟩

lemma *fun-upd-None-restrict*[*simp*]:
 $(m|'D)(x := \text{None}) = (\text{if } x:D \text{ then } m|'(D - \{x\}) \text{ else } m|'D)$
 ⟨*proof*⟩

lemma *fun-upd-restrict*:
 $(m|'D)(x := y) = (m|'(D - \{x\}))(x := y)$
 ⟨*proof*⟩

lemma *fun-upd-restrict-conv*[*simp*]:
 $x \in D \implies (m|'D)(x := y) = (m|'(D - \{x\}))(x := y)$
 ⟨*proof*⟩

39.10 map-upds

lemma *map-upds-Nil1*[*simp*]: $m(\llbracket _ \rrbracket \text{ bs}) = m$

$\langle \text{proof} \rangle$

lemma *map-upds-Nil2*[simp]: $m(as \ [|->] \ []) = m$
 $\langle \text{proof} \rangle$

lemma *map-upds-Cons*[simp]: $m(a \# as \ [|->] \ b \# bs) = (m(a \ [|->] \ b))(as \ [|->] \ bs)$
 $\langle \text{proof} \rangle$

lemma *map-upds-append1*[simp]: $\bigwedge ys \ m. \ size \ xs < size \ ys \implies$
 $m(xs @ [x] \ [\mapsto] \ ys) = m(xs \ [\mapsto] \ ys)(x \mapsto ys!size \ xs)$
 $\langle \text{proof} \rangle$

lemma *map-upds-list-update2-drop*[simp]:
 $\bigwedge m \ ys \ i. \ [size \ xs \leq i; \ i < size \ ys] \implies$
 $m(xs \ [\mapsto] \ ys[i:=y]) = m(xs \ [\mapsto] \ ys)$
 $\langle \text{proof} \rangle$

lemma *map-upd-upds-conv-if*: $!!x \ y \ ys \ f.$
 $(f(x \ [|->] \ y))(xs \ [|->] \ ys) =$
 $(if \ x : set \ (take \ (length \ ys) \ xs) \ then \ f(xs \ [|->] \ ys)$
 $\quad \quad \quad else \ (f(xs \ [|->] \ ys))(x \ [|->] \ y))$
 $\langle \text{proof} \rangle$

lemma *map-upds-twist* [simp]:
 $a \sim : set \ as \implies m(a \ [|->] \ b)(as \ [|->] \ bs) = m(as \ [|->] \ bs)(a \ [|->] \ b)$
 $\langle \text{proof} \rangle$

lemma *map-upds-apply-nontin*[simp]:
 $!!ys. \ x \sim : set \ xs \implies (f(xs \ [|->] \ ys)) \ x = f \ x$
 $\langle \text{proof} \rangle$

lemma *fun-upds-append-drop*[simp]:
 $!!m \ ys. \ size \ xs = size \ ys \implies m(xs @ zs \ [\mapsto] \ ys) = m(xs \ [\mapsto] \ ys)$
 $\langle \text{proof} \rangle$

lemma *fun-upds-append2-drop*[simp]:
 $!!m \ ys. \ size \ xs = size \ ys \implies m(xs \ [\mapsto] \ ys @ zs) = m(xs \ [\mapsto] \ ys)$
 $\langle \text{proof} \rangle$

lemma *restrict-map-upds*[simp]: $!!m \ ys.$
 $[length \ xs = length \ ys; \ set \ xs \subseteq D] \implies$
 $m(xs \ [\mapsto] \ ys) \upharpoonright D = (m \upharpoonright (D - set \ xs))(xs \ [\mapsto] \ ys)$
 $\langle \text{proof} \rangle$

39.11 *map-upd-s*

lemma *map-upd-s-apply* [simp]:
 $(m(as \ [|->] \ b)) \ x = (if \ x : as \ then \ Some \ b \ else \ m \ x)$

<proof>

lemma *map-subst-apply* [*simp*]:
 $(m(a \sim > b))\ x = (\text{if } m\ x = \text{Some } a \text{ then Some } b \text{ else } m\ x)$
<proof>

39.12 *dom*

lemma *domI*: $m\ a = \text{Some } b \implies a : \text{dom } m$
<proof>

lemma *domD*: $a : \text{dom } m \implies \exists b. m\ a = \text{Some } b$
<proof>

lemma *domIff*[*iff*]: $(a : \text{dom } m) = (m\ a \sim = \text{None})$
<proof>

declare *domIff* [*simp del*]

lemma *dom-empty*[*simp*]: $\text{dom empty} = \{\}$
<proof>

lemma *dom-fun-upd*[*simp*]:
 $\text{dom}(f(x := y)) = (\text{if } y = \text{None} \text{ then } \text{dom } f - \{x\} \text{ else insert } x (\text{dom } f))$
<proof>

lemma *dom-map-of*: $\text{dom}(\text{map-of } xys) = \{x. \exists y. (x, y) : \text{set } xys\}$
<proof>

lemma *dom-map-of-conv-image-fst*:
 $\text{dom}(\text{map-of } xys) = \text{fst} \text{ ` } (\text{set } xys)$
<proof>

lemma *dom-map-of-zip*[*simp*]: $[\text{length } xs = \text{length } ys; \text{distinct } xs] \implies$
 $\text{dom}(\text{map-of}(\text{zip } xs\ ys)) = \text{set } xs$
<proof>

lemma *finite-dom-map-of*: $\text{finite } (\text{dom } (\text{map-of } l))$
<proof>

lemma *dom-map-upds*[*simp*]:
 $!!m\ ys. \text{dom}(m(xs[[->]ys])) = \text{set}(\text{take } (\text{length } ys)\ xs) \text{ Un } \text{dom } m$
<proof>

lemma *dom-map-add*[*simp*]: $\text{dom}(m++n) = \text{dom } n \text{ Un } \text{dom } m$
<proof>

lemma *dom-override-on*[*simp*]:
 $\text{dom}(\text{override-on } f\ g\ A) =$

$(\text{dom } f - \{a. a : A - \text{dom } g\}) \text{ Un } \{a. a : A \text{ Int dom } g\}$
 $\langle \text{proof} \rangle$

lemma *map-add-comm*: $\text{dom } m1 \cap \text{dom } m2 = \{\} \implies m1 ++ m2 = m2 ++ m1$
 $\langle \text{proof} \rangle$

39.13 *ran*

lemma *ranI*: $m \ a = \text{Some } b \implies b : \text{ran } m$
 $\langle \text{proof} \rangle$

lemma *ran-empty[simp]*: $\text{ran empty} = \{\}$
 $\langle \text{proof} \rangle$

lemma *ran-map-upd[simp]*: $m \ a = \text{None} \implies \text{ran}(m(a|->b)) = \text{insert } b (\text{ran } m)$
 $\langle \text{proof} \rangle$

39.14 *map-le*

lemma *map-le-empty [simp]*: $\text{empty} \subseteq_m g$
 $\langle \text{proof} \rangle$

lemma *upd-None-map-le [simp]*: $f(x := \text{None}) \subseteq_m f$
 $\langle \text{proof} \rangle$

lemma *map-le-upd[simp]*: $f \subseteq_m g \implies f(a := b) \subseteq_m g(a := b)$
 $\langle \text{proof} \rangle$

lemma *map-le-imp-upd-le [simp]*: $m1 \subseteq_m m2 \implies m1(x := \text{None}) \subseteq_m m2(x \mapsto y)$
 $\langle \text{proof} \rangle$

lemma *map-le-upds[simp]*:
 $!!f \ g \ bs. f \subseteq_m g \implies f(as \ [|->] \ bs) \subseteq_m g(as \ [|->] \ bs)$
 $\langle \text{proof} \rangle$

lemma *map-le-implies-dom-le*: $(f \subseteq_m g) \implies (\text{dom } f \subseteq \text{dom } g)$
 $\langle \text{proof} \rangle$

lemma *map-le-refl [simp]*: $f \subseteq_m f$
 $\langle \text{proof} \rangle$

lemma *map-le-trans[trans]*: $\llbracket m1 \subseteq_m m2; m2 \subseteq_m m3 \rrbracket \implies m1 \subseteq_m m3$
 $\langle \text{proof} \rangle$

lemma *map-le-antisym*: $\llbracket f \subseteq_m g; g \subseteq_m f \rrbracket \implies f = g$
 $\langle \text{proof} \rangle$

lemma *map-le-map-add* [simp]: $f \subseteq_m (g ++ f)$
 ⟨proof⟩

lemma *map-le-iff-map-add-commute*: $(f \subseteq_m f ++ g) = (f ++ g = g ++ f)$
 ⟨proof⟩

lemma *map-add-le-mapE*: $f ++ g \subseteq_m h \implies g \subseteq_m h$
 ⟨proof⟩

lemma *map-add-le-mapI*: $\llbracket f \subseteq_m h; g \subseteq_m h; f \subseteq_m f ++ g \rrbracket \implies f ++ g \subseteq_m h$
 ⟨proof⟩

end

40 Refute: Refute

theory *Refute*
imports *Map*
uses *Tools/prop-logic.ML*
 Tools/sat-solver.ML
 Tools/refute.ML
 Tools/refute-isar.ML
begin

⟨ML⟩

```
(* ----- *)
(* REFUTE                                           *)
(* ----- *)
(* We use a SAT solver to search for a (finite) model that refutes a given *)
(* HOL formula.                                     *)
(* ----- *)

(* ----- *)
(* NOTE                                             *)
(* ----- *)
(* I strongly recommend that you install a stand-alone SAT solver if you *)
(* want to use 'refute'. For details see 'HOL/Tools/sat_solver.ML'. If you *)
(* have installed (a supported version of) zChaff, simply set 'ZCHAFF_HOME' *)
(* in 'etc/settings'.                               *)
(* ----- *)

(* ----- *)
(* USAGE                                           *)
(* ----- *)
(* See the file 'HOL/ex/Refute_Examples.thy' for examples. The supported *)
(* parameters are explained below.                 *)
(* ----- *)
```

```

(* ----- *)

(* ----- *)
(* CURRENT LIMITATIONS *)
(* *)
(* 'refute' currently accepts formulas of higher-order predicate logic (with *)
(* equality), including free/bound/schematic variables, lambda abstractions, *)
(* sets and set membership, "arbitrary", "The", "Eps", records and *)
(* inductively defined sets. Defining equations for constants are added *)
(* automatically, as are sort axioms. Other, user-asserted axioms however *)
(* are ignored. Inductive datatypes and recursive functions are supported, *)
(* but may lead to spurious countermodels. *)
(* *)
(* The (space) complexity of the algorithm is non-elementary. *)
(* *)
(* Schematic type variables are not supported. *)
(* ----- *)

(* ----- *)
(* PARAMETERS *)
(* *)
(* The following global parameters are currently supported (and required): *)
(* *)
(* Name          Type      Description *)
(* *)
(* "minsize"      int       Only search for models with size at least *)
(*                  'minsize'. *)
(* "maxsize"      int       If >0, only search for models with size at most *)
(*                  'maxsize'. *)
(* "maxvars"      int       If >0, use at most 'maxvars' boolean variables *)
(*                  when transforming the term into a propositional *)
(*                  formula. *)
(* "maxtime"      int       If >0, terminate after at most 'maxtime' seconds. *)
(*                  This value is ignored under some ML compilers. *)
(* "satsolver"    string    Name of the SAT solver to be used. *)
(* *)
(* See 'HOL/SAT.thy' for default values. *)
(* *)
(* The size of particular types can be specified in the form type=size *)
(* (where 'type' is a string, and 'size' is an int). Examples: *)
(* "'a'=1 *)
(* "List.list=2 *)
(* ----- *)

(* ----- *)
(* FILES *)
(* *)
(* HOL/Tools/prop_logic.ML    Propositional logic *)
(* HOL/Tools/sat_solver.ML    SAT solvers *)

```

```

(* HOL/Tools/refute.ML      Translation HOL -> propositional logic and  *)
(*                          Boolean assignment -> HOL model             *)
(* HOL/Tools/refute_isar.ML Adds 'refute'/'refute_params' to Isabelle's *)
(*                          syntax                                       *)
(* HOL/Refute.thy           This file: loads the ML files, basic setup, *)
(*                          documentation                                 *)
(* HOL/SAT.thy              Sets default parameters                    *)
(* HOL/ex/RefuteExamples.thy Examples                                  *)
(* ----- *)

```

end

41 SAT: Reconstructing external resolution proofs for propositional logic

theory *SAT* **imports** *Refute*

uses

Tools/cnf-funcs.ML

Tools/sat-funcs.ML

begin

Late package setup: default values for refute, see also theory *Refute*.

refute-params

```

[itself=1,
 minsize=1,
 maxsize=8,
 maxvars=10000,
 maxtime=60,
 satsolver=auto]

```

$\langle ML \rangle$

end

42 Hilbert-Choice: Hilbert’s Epsilon-Operator and the Axiom of Choice

theory *Hilbert-Choice*

imports *NatArith*

uses (*Tools/meson.ML*) (*Tools/specification-package.ML*)

begin

42.1 Hilbert’s epsilon

consts

$Eps \quad :: ('a \Rightarrow bool) \Rightarrow 'a$

syntax (*epsilon*)

$-Eps \quad :: [pttrn, bool] \Rightarrow 'a \quad ((\exists \epsilon \text{ -./ -}) [0, 10] 10)$

syntax (*HOL*)

$-Eps \quad :: [pttrn, bool] \Rightarrow 'a \quad ((\exists @ \text{ -./ -}) [0, 10] 10)$

syntax

$-Eps \quad :: [pttrn, bool] \Rightarrow 'a \quad ((\exists SOME \text{ -./ -}) [0, 10] 10)$

translations

$SOME\ x.\ P == Eps\ (\%x.\ P)$

$\langle ML \rangle$

axioms

$someI: P\ (x::'a) \Rightarrow P\ (SOME\ x.\ P\ x)$

finalconsts

Eps

constdefs

$inv :: ('a \Rightarrow 'b) \Rightarrow ('b \Rightarrow 'a)$

$inv(f :: 'a \Rightarrow 'b) == \%y.\ SOME\ x.\ f\ x = y$

$Inv :: 'a\ set \Rightarrow ('a \Rightarrow 'b) \Rightarrow ('b \Rightarrow 'a)$

$Inv\ A\ f == \%x.\ SOME\ y.\ y \in A \ \& \ f\ y = x$

42.2 Hilbert’s Epsilon-operator

Easier to apply than *someI* if the witness comes from an existential formula

lemma *someI-ex* [*elim?*]: $\exists x.\ P\ x \Rightarrow P\ (SOME\ x.\ P\ x)$

$\langle proof \rangle$

Easier to apply than *someI* because the conclusion has only one occurrence of *P*.

lemma *someI2*: $[| P\ a; !!x.\ P\ x \Rightarrow Q\ x |] \Rightarrow Q\ (SOME\ x.\ P\ x)$

$\langle proof \rangle$

Easier to apply than *someI2* if the witness comes from an existential formula

lemma *someI2-ex*: $[| \exists a.\ P\ a; !!x.\ P\ x \Rightarrow Q\ x |] \Rightarrow Q\ (SOME\ x.\ P\ x)$

$\langle proof \rangle$

lemma *some-equality* [*intro*]:

$[| P\ a; !!x.\ P\ x \Rightarrow x=a |] \Rightarrow (SOME\ x.\ P\ x) = a$

$\langle proof \rangle$

lemma *some1-equality*: $[| EX!x.\ P\ x; P\ a |] \Rightarrow (SOME\ x.\ P\ x) = a$

$\langle \text{proof} \rangle$

lemma *some-eq-ex*: $P \ (SOME \ x. \ P \ x) = (\exists \ x. \ P \ x)$
 $\langle \text{proof} \rangle$

lemma *some-eq-trivial* [simp]: $(SOME \ y. \ y=x) = x$
 $\langle \text{proof} \rangle$

lemma *some-sym-eq-trivial* [simp]: $(SOME \ y. \ x=y) = x$
 $\langle \text{proof} \rangle$

42.3 Axiom of Choice, Proved Using the Description Operator

Used in *Tools/meson.ML*

lemma *choice*: $\forall x. \exists y. Q \ x \ y ==> \exists f. \forall x. Q \ x \ (f \ x)$
 $\langle \text{proof} \rangle$

lemma *bchoice*: $\forall x \in S. \exists y. Q \ x \ y ==> \exists f. \forall x \in S. Q \ x \ (f \ x)$
 $\langle \text{proof} \rangle$

42.4 Function Inverse

lemma *inv-id* [simp]: $inv \ id = id$
 $\langle \text{proof} \rangle$

A one-to-one function has an inverse.

lemma *inv-f-f* [simp]: $inj \ f ==> inv \ f \ (f \ x) = x$
 $\langle \text{proof} \rangle$

lemma *inv-f-eq*: $[| \ inj \ f; \ f \ x = y \ |] ==> inv \ f \ y = x$
 $\langle \text{proof} \rangle$

lemma *inj-imp-inv-eq*: $[| \ inj \ f; \ \forall x. \ f(g \ x) = x \ |] ==> inv \ f = g$
 $\langle \text{proof} \rangle$

But is it useful?

lemma *inj-transfer*:
assumes *injf*: $inj \ f$ **and** *minor*: $!!y. \ y \in range(f) ==> P(inv \ f \ y)$
shows $P \ x$
 $\langle \text{proof} \rangle$

lemma *inj-iff*: $(inj \ f) = (inv \ f \ o \ f = id)$
 $\langle \text{proof} \rangle$

lemma *inj-imp-surj-inv*: $inj \ f ==> surj \ (inv \ f)$
 $\langle \text{proof} \rangle$

lemma *f-inv-f*: $y \in \text{range}(f) \implies f(\text{inv } f \ y) = y$
 $\langle \text{proof} \rangle$

lemma *surj-f-inv-f*: $\text{surj } f \implies f(\text{inv } f \ y) = y$
 $\langle \text{proof} \rangle$

lemma *inv-injective*:
 assumes *eq*: $\text{inv } f \ x = \text{inv } f \ y$
 and *x*: $x \in \text{range } f$
 and *y*: $y \in \text{range } f$
 shows $x = y$
 $\langle \text{proof} \rangle$

lemma *inj-on-inv*: $A \subseteq \text{range}(f) \implies \text{inj-on } (\text{inv } f) \ A$
 $\langle \text{proof} \rangle$

lemma *surj-imp-inj-inv*: $\text{surj } f \implies \text{inj } (\text{inv } f)$
 $\langle \text{proof} \rangle$

lemma *surj-iff*: $(\text{surj } f) = (f \circ \text{inv } f = \text{id})$
 $\langle \text{proof} \rangle$

lemma *surj-imp-inv-eq*: $[\text{surj } f; \forall x. g(f \ x) = x] \implies \text{inv } f = g$
 $\langle \text{proof} \rangle$

lemma *bij-imp-bij-inv*: $\text{bij } f \implies \text{bij } (\text{inv } f)$
 $\langle \text{proof} \rangle$

lemma *inv-equality*: $[\forall x. g(f \ x) = x; \forall y. f(g \ y) = y] \implies \text{inv } f = g$
 $\langle \text{proof} \rangle$

lemma *inv-inv-eq*: $\text{bij } f \implies \text{inv } (\text{inv } f) = f$
 $\langle \text{proof} \rangle$

lemma *o-inv-distrib*: $[\text{bij } f; \text{bij } g] \implies \text{inv } (f \circ g) = \text{inv } g \circ \text{inv } f$
 $\langle \text{proof} \rangle$

lemma *image-surj-f-inv-f*: $\text{surj } f \implies f \circ (\text{inv } f \circ A) = A$
 $\langle \text{proof} \rangle$

lemma *image-inv-f-f*: $\text{inj } f \implies (\text{inv } f) \circ (f \circ A) = A$
 $\langle \text{proof} \rangle$

lemma *inv-image-comp*: $\text{inj } f \implies \text{inv } f \circ (f \circ X) = X$
 $\langle \text{proof} \rangle$

lemma *bij-image-Collect-eq*: $\text{bij } f \implies f \text{ ` Collect } P = \{y. P (\text{inv } f y)\}$
 $\langle \text{proof} \rangle$

lemma *bij-vimage-eq-inv-image*: $\text{bij } f \implies f \text{ ` } A = \text{inv } f \text{ ` } A$
 $\langle \text{proof} \rangle$

42.5 Inverse of a PI-function (restricted domain)

lemma *Inv-f-f*: $[\text{inj-on } f A; x \in A] \implies \text{Inv } A f (f x) = x$
 $\langle \text{proof} \rangle$

lemma *f-Inv-f*: $y \in f \text{ ` } A \implies f (\text{Inv } A f y) = y$
 $\langle \text{proof} \rangle$

lemma *Inv-injective*:
 assumes *eq*: $\text{Inv } A f x = \text{Inv } A f y$
 and *x*: $x: f \text{ ` } A$
 and *y*: $y: f \text{ ` } A$
 shows $x=y$
 $\langle \text{proof} \rangle$

lemma *inj-on-Inv*: $B \leq f \text{ ` } A \implies \text{inj-on } (\text{Inv } A f) B$
 $\langle \text{proof} \rangle$

lemma *Inv-mem*: $[\text{f ` } A = B; x \in B] \implies \text{Inv } A f x \in A$
 $\langle \text{proof} \rangle$

lemma *Inv-f-eq*: $[\text{inj-on } f A; f x = y; x \in A] \implies \text{Inv } A f y = x$
 $\langle \text{proof} \rangle$

lemma *Inv-comp*:
 $[\text{inj-on } f (g \text{ ` } A); \text{inj-on } g A; x \in f \text{ ` } g \text{ ` } A] \implies$
 $\text{Inv } A (f \circ g) x = (\text{Inv } A g \circ \text{Inv } (g \text{ ` } A) f) x$
 $\langle \text{proof} \rangle$

42.6 Other Consequences of Hilbert’s Epsilon

Hilbert’s Epsilon and the *split* Operator

Looping simprule

lemma *split-paired-Eps*: $(\text{SOME } x. P x) = (\text{SOME } (a,b). P(a,b))$
 $\langle \text{proof} \rangle$

lemma *Eps-split*: $\text{Eps } (\text{split } P) = (\text{SOME } xy. P (\text{fst } xy) (\text{snd } xy))$
 $\langle \text{proof} \rangle$

lemma *Eps-split-eq [simp]*: $(\text{@}(x',y'). x = x' \ \& \ y = y') = (x,y)$
 $\langle \text{proof} \rangle$

A relation is wellfounded iff it has no infinite descending chain

lemma *wf-iff-no-infinite-down-chain:*

$wf\ r = (\sim(\exists f. \forall i. (f(Suc\ i), f\ i) \in r))$
 $\langle proof \rangle$

A dynamically-scoped fact for TFL

lemma *tfl-some:* $\forall P\ x. P\ x \dashv\dashv P\ (Eps\ P)$

$\langle proof \rangle$

42.7 Least value operator

constdefs

$LeastM :: ['a \Rightarrow 'b::ord, 'a \Rightarrow bool] \Rightarrow 'a$
 $LeastM\ m\ P == SOME\ x. P\ x \ \&\ (\forall y. P\ y \dashv\dashv m\ x \leq m\ y)$

syntax

$-LeastM :: [pttrn, 'a \Rightarrow 'b::ord, bool] \Rightarrow 'a \quad (LEAST\ -\ WRT\ -. \ -\ [0, 4, 10])$

translations

$LEAST\ x\ WRT\ m. P == LeastM\ m\ (\%x. P)$

lemma *LeastMI2:*

$P\ x \implies (!y. P\ y \implies m\ x \leq m\ y)$
 $\implies (!x. P\ x \implies \forall y. P\ y \dashv\dashv m\ x \leq m\ y \implies Q\ x)$
 $\implies Q\ (LeastM\ m\ P)$
 $\langle proof \rangle$

lemma *LeastM-equality:*

$P\ k \implies (!x. P\ x \implies m\ k \leq m\ x)$
 $\implies m\ (LEAST\ x\ WRT\ m. P\ x) = (m\ k::'a::order)$
 $\langle proof \rangle$

lemma *wf-linord-ex-has-least:*

$wf\ r \implies \forall x\ y. ((x,y):r^+) = ((y,x):\sim r^*) \implies P\ k$
 $\implies \exists x. P\ x \ \&\ (!y. P\ y \dashv\dashv (m\ x, m\ y):r^*)$
 $\langle proof \rangle$

lemma *ex-has-least-nat:*

$P\ k \implies \exists x. P\ x \ \&\ (\forall y. P\ y \dashv\dashv m\ x \leq (m\ y::nat))$
 $\langle proof \rangle$

lemma *LeastM-nat-lemma:*

$P\ k \implies P\ (LeastM\ m\ P) \ \&\ (\forall y. P\ y \dashv\dashv m\ (LeastM\ m\ P) \leq (m\ y::nat))$
 $\langle proof \rangle$

lemmas *LeastM-natI = LeastM-nat-lemma [THEN conjunct1, standard]*

lemma *LeastM-nat-le:* $P\ x \implies m\ (LeastM\ m\ P) \leq (m\ x::nat)$

$\langle proof \rangle$

42.8 Greatest value operator

constdefs

$GreatestM :: ['a ==> 'b::ord, 'a ==> bool] ==> 'a$
 $GreatestM\ m\ P == SOME\ x.\ P\ x \ \& \ (\forall y.\ P\ y \longrightarrow m\ y \leq m\ x)$

 $Greatest :: ('a::ord ==> bool) ==> 'a \quad (\text{binder } GREATEST\ 10)$
 $Greatest == GreatestM\ (\%x.\ x)$

syntax

$-GreatestM :: [pttrn, 'a==>'b::ord, bool] ==> 'a$
 $(GREATEST - WRT\ -. - [0, 4, 10]\ 10)$

translations

$GREATEST\ x\ WRT\ m.\ P == GreatestM\ m\ (\%x.\ P)$

lemma GreatestMI2:

$P\ x ==> (!y.\ P\ y ==> m\ y \leq m\ x)$
 $==> (!x.\ P\ x ==> \forall y.\ P\ y \longrightarrow m\ y \leq m\ x ==> Q\ x)$
 $==> Q\ (GreatestM\ m\ P)$
 $\langle proof \rangle$

lemma GreatestM-equality:

$P\ k ==> (!x.\ P\ x ==> m\ x \leq m\ k)$
 $==> m\ (GREATEST\ x\ WRT\ m.\ P\ x) = (m\ k :: 'a::order)$
 $\langle proof \rangle$

lemma Greatest-equality:

$P\ (k :: 'a::order) ==> (!x.\ P\ x ==> x \leq k) ==> (GREATEST\ x.\ P\ x) = k$
 $\langle proof \rangle$

lemma ex-has-greatest-nat-lemma:

$P\ k ==> \forall x.\ P\ x \longrightarrow (\exists y.\ P\ y \ \& \ \sim ((m\ y::nat) \leq m\ x))$
 $==> \exists y.\ P\ y \ \& \ \sim (m\ y < m\ k + n)$
 $\langle proof \rangle$

lemma ex-has-greatest-nat:

$P\ k ==> \forall y.\ P\ y \longrightarrow m\ y < b$
 $==> \exists x.\ P\ x \ \& \ (\forall y.\ P\ y \longrightarrow (m\ y::nat) \leq m\ x)$
 $\langle proof \rangle$

lemma GreatestM-nat-lemma:

$P\ k ==> \forall y.\ P\ y \longrightarrow m\ y < b$
 $==> P\ (GreatestM\ m\ P) \ \& \ (\forall y.\ P\ y \longrightarrow (m\ y::nat) \leq m\ (GreatestM\ m\ P))$
 $\langle proof \rangle$

lemmas $GreatestM\ natI = GreatestM\ nat\ lemma\ [THEN\ conjunct1,\ standard]$

lemma GreatestM-nat-le:

$P\ x ==> \forall y. P\ y \dashrightarrow m\ y < b$
 $==> (m\ x::nat) <= m\ (GreatestM\ m\ P)$
 $\langle proof \rangle$

Specialization to *GREATEST*.

lemma *GreatestI*: $P\ (k::nat) ==> \forall y. P\ y \dashrightarrow y < b ==> P\ (GREATEST\ x. P\ x)$
 $\langle proof \rangle$

lemma *Greatest-le*:

$P\ x ==> \forall y. P\ y \dashrightarrow y < b ==> (x::nat) <= (GREATEST\ x. P\ x)$
 $\langle proof \rangle$

42.9 The Meson proof procedure

42.9.1 Negation Normal Form

de Morgan laws

lemma *meson-not-conjD*: $\sim(P \& Q) ==> \sim P \mid \sim Q$
and *meson-not-disjD*: $\sim(P \mid Q) ==> \sim P \& \sim Q$
and *meson-not-notD*: $\sim\sim P ==> P$
and *meson-not-allD*: $!!P. \sim(\forall x. P(x)) ==> \exists x. \sim P(x)$
and *meson-not-exD*: $!!P. \sim(\exists x. P(x)) ==> \forall x. \sim P(x)$
 $\langle proof \rangle$

Removal of \dashrightarrow and $<->$ (positive and negative occurrences)

lemma *meson-imp-to-disjD*: $P \dashrightarrow Q ==> \sim P \mid Q$
and *meson-not-impD*: $\sim(P \dashrightarrow Q) ==> P \& \sim Q$
and *meson-iff-to-disjD*: $P = Q ==> (\sim P \mid Q) \& (\sim Q \mid P)$
and *meson-not-iffD*: $\sim(P = Q) ==> (P \mid Q) \& (\sim P \mid \sim Q)$
 — Much more efficient than $P \wedge \neg Q \vee Q \wedge \neg P$ for computing CNF
 $\langle proof \rangle$

42.9.2 Pulling out the existential quantifiers

Conjunction

lemma *meson-conj-exD1*: $!!P\ Q. (\exists x. P(x)) \& Q ==> \exists x. P(x) \& Q$
and *meson-conj-exD2*: $!!P\ Q. P \& (\exists x. Q(x)) ==> \exists x. P \& Q(x)$
 $\langle proof \rangle$

Disjunction

lemma *meson-disj-exD*: $!!P\ Q. (\exists x. P(x)) \mid (\exists x. Q(x)) ==> \exists x. P(x) \mid Q(x)$
 — DO NOT USE with forall-Skolemization: makes fewer schematic variables!!
 — With ex-Skolemization, makes fewer Skolem constants
and *meson-disj-exD1*: $!!P\ Q. (\exists x. P(x)) \mid Q ==> \exists x. P(x) \mid Q$
and *meson-disj-exD2*: $!!P\ Q. P \mid (\exists x. Q(x)) ==> \exists x. P \mid Q(x)$
 $\langle proof \rangle$

42.9.3 Generating clauses for the Meson Proof Procedure

Disjunctions

lemma *meson-disj-assoc*: $(P|Q)|R \implies P|(Q|R)$
and *meson-disj-comm*: $P|Q \implies Q|P$
and *meson-disj-FalseD1*: $\text{False}|P \implies P$
and *meson-disj-FalseD2*: $P|\text{False} \implies P$
 $\langle \text{proof} \rangle$

42.10 Lemmas for Meson, the Model Elimination Procedure

Generation of contrapositives

Inserts negated disjunct after removing the negation; P is a literal. Model elimination requires assuming the negation of every attempted subgoal, hence the negated disjuncts.

lemma *make-neg-rule*: $\sim P|Q \implies ((\sim P \implies P) \implies Q)$
 $\langle \text{proof} \rangle$

Version for Plaisted’s “Positive refinement” of the Meson procedure

lemma *make-refined-neg-rule*: $\sim P|Q \implies (P \implies Q)$
 $\langle \text{proof} \rangle$

P should be a literal

lemma *make-pos-rule*: $P|Q \implies ((P \implies \sim P) \implies Q)$
 $\langle \text{proof} \rangle$

Versions of *make-neg-rule* and *make-pos-rule* that don’t insert new assumptions, for ordinary resolution.

lemmas *make-neg-rule'* = *make-refined-neg-rule*

lemma *make-pos-rule'*: $[|P|Q; \sim P|] \implies Q$
 $\langle \text{proof} \rangle$

Generation of a goal clause – put away the final literal

lemma *make-neg-goal*: $\sim P \implies ((\sim P \implies P) \implies \text{False})$
 $\langle \text{proof} \rangle$

lemma *make-pos-goal*: $P \implies ((P \implies \sim P) \implies \text{False})$
 $\langle \text{proof} \rangle$

42.10.1 Lemmas for Forward Proof

There is a similarity to congruence rules

lemma *conj-forward*: $[|P' \& Q'; P' \implies P; Q' \implies Q|] \implies P \& Q$
 $\langle \text{proof} \rangle$

lemma *disj-forward*: $[[P' | Q'; P' \implies P; Q' \implies Q]] \implies P | Q$
 $\langle proof \rangle$

lemma *disj-forward2*:
 $[[P' | Q'; P' \implies P; [[Q'; P \implies False]] \implies Q]] \implies P | Q$
 $\langle proof \rangle$

lemma *all-forward*: $[[\forall x. P'(x); !!x. P'(x) \implies P(x)]] \implies \forall x. P(x)$
 $\langle proof \rangle$

lemma *ex-forward*: $[[\exists x. P'(x); !!x. P'(x) \implies P(x)]] \implies \exists x. P(x)$
 $\langle proof \rangle$

Many of these bindings are used by the ATP linkup, and not just by legacy proof scripts.

$\langle ML \rangle$

end

43 Infinite-Set: Infinite Sets and Related Concepts

theory *Infinite-Set*
imports *Hilbert-Choice Binomial*
begin

43.1 Infinite Sets

Some elementary facts about infinite sets, by Stefan Merz.

syntax
 $infinite :: 'a\ set \Rightarrow bool$

translations
 $infinite\ S == S \notin Finites$

Infinite sets are non-empty, and if we remove some elements from an infinite set, the result is still infinite.

lemma *infinite-nonempty*:
 $\neg (infinite\ \{\})$
 $\langle proof \rangle$

lemma *infinite-remove*:
 $infinite\ S \implies infinite\ (S - \{a\})$
 $\langle proof \rangle$

lemma *Diff-infinite-finite*:

assumes T : *finite* T **and** S : *infinite* S
shows *infinite* $(S - T)$
 $\langle \text{proof} \rangle$

lemma *Un-infinite*:
 $\text{infinite } S \implies \text{infinite } (S \cup T)$
 $\langle \text{proof} \rangle$

lemma *infinite-super*:
assumes T : $S \subseteq T$ **and** S : *infinite* S
shows *infinite* T
 $\langle \text{proof} \rangle$

As a concrete example, we prove that the set of natural numbers is infinite.

lemma *finite-nat-bounded*:
assumes S : *finite* $(S::\text{nat set})$
shows $\exists k. S \subseteq \{.. $k\}$ (**is** $\exists k. ?\text{bounded } S \ k$)
 $\langle \text{proof} \rangle$$

lemma *finite-nat-iff-bounded*:
 $\text{finite } (S::\text{nat set}) = (\exists k. S \subseteq \{.. $k\})$ (**is** $?lhs = ?rhs$)
 $\langle \text{proof} \rangle$$

lemma *finite-nat-iff-bounded-le*:
 $\text{finite } (S::\text{nat set}) = (\exists k. S \subseteq \{.. $k\})$ (**is** $?lhs = ?rhs$)
 $\langle \text{proof} \rangle$$

lemma *infinite-nat-iff-unbounded*:
 $\text{infinite } (S::\text{nat set}) = (\forall m. \exists n. m < n \wedge n \in S)$
(**is** $?lhs = ?rhs$)
 $\langle \text{proof} \rangle$

lemma *infinite-nat-iff-unbounded-le*:
 $\text{infinite } (S::\text{nat set}) = (\forall m. \exists n. m \leq n \wedge n \in S)$
(**is** $?lhs = ?rhs$)
 $\langle \text{proof} \rangle$

For a set of natural numbers to be infinite, it is enough to know that for any number larger than some k , there is some larger number that is an element of the set.

lemma *unbounded-k-infinite*:
assumes k : $\forall m. k < m \longrightarrow (\exists n. m < n \wedge n \in S)$
shows *infinite* $(S::\text{nat set})$
 $\langle \text{proof} \rangle$

theorem *nat-infinite* [*simp*]:
 $\text{infinite } (\text{UNIV} :: \text{nat set})$
 $\langle \text{proof} \rangle$

theorem *nat-not-finite* [elim]:
 $\text{finite } (UNIV::\text{nat set}) \implies R$
 <proof>

Every infinite set contains a countable subset. More precisely we show that a set S is infinite if and only if there exists an injective function from the naturals into S .

lemma *range-inj-infinite*:
 $\text{inj } (f::\text{nat} \Rightarrow 'a) \implies \text{infinite } (\text{range } f)$
 <proof>

The “only if” direction is harder because it requires the construction of a sequence of pairwise different elements of an infinite set S . The idea is to construct a sequence of non-empty and infinite subsets of S obtained by successively removing elements of S .

lemma *linorder-injI*:
assumes *hyp*: $\forall x y. x < (y::'a::\text{linorder}) \longrightarrow f x \neq f y$
shows *inj* f
 <proof>

lemma *infinite-countable-subset*:
assumes *inf*: $\text{infinite } (S::'a \text{ set})$
shows $\exists f. \text{inj } (f::\text{nat} \Rightarrow 'a) \wedge \text{range } f \subseteq S$
 <proof>

theorem *infinite-iff-countable-subset*:
 $\text{infinite } S = (\exists f. \text{inj } (f::\text{nat} \Rightarrow 'a) \wedge \text{range } f \subseteq S)$
 (is ?lhs = ?rhs)
 <proof>

For any function with infinite domain and finite range there is some element that is the image of infinitely many domain elements. In particular, any infinite sequence of elements from a finite set contains some element that occurs infinitely often.

theorem *inf-img-fin-dom*:
assumes *img*: $\text{finite } (f'A)$ **and** *dom*: $\text{infinite } A$
shows $\exists y \in f'A. \text{infinite } (f - \{y\})$
 <proof>

theorems $\text{inf-img-fin-dom}E = \text{inf-img-fin-dom}[THEN \text{bex}E]$

43.2 Infinitely Many and Almost All

We often need to reason about the existence of infinitely many (resp., all but finitely many) objects satisfying some predicate, so we introduce corresponding binders and their proof rules.

consts

$Inf\text{-}many :: ('a \Rightarrow bool) \Rightarrow bool$ (**binder** INF 10)
 $Alm\text{-}all :: ('a \Rightarrow bool) \Rightarrow bool$ (**binder** $MOST$ 10)

defs

$INF\text{-}def: Inf\text{-}many\ P \equiv infinite\ \{x. P\ x\}$
 $MOST\text{-}def: Alm\text{-}all\ P \equiv \neg(INF\ x. \neg P\ x)$

syntax (*xsymbols*)

$MOST :: [idts, bool] \Rightarrow bool$ $((\exists \forall_{\infty} \neg \cdot / \neg) [0,10] 10)$
 $INF :: [idts, bool] \Rightarrow bool$ $((\exists \exists_{\infty} \neg \cdot / \neg) [0,10] 10)$

syntax (*HTML output*)

$MOST :: [idts, bool] \Rightarrow bool$ $((\exists \forall_{\infty} \neg \cdot / \neg) [0,10] 10)$
 $INF :: [idts, bool] \Rightarrow bool$ $((\exists \exists_{\infty} \neg \cdot / \neg) [0,10] 10)$

lemma $INF\text{-}EX$:

$(\exists_{\infty} x. P\ x) \Longrightarrow (\exists x. P\ x)$
 $\langle proof \rangle$

lemma $MOST\text{-}iff\text{-}finiteNeg$:

$(\forall_{\infty} x. P\ x) = finite\ \{x. \neg P\ x\}$
 $\langle proof \rangle$

lemma $ALL\text{-}MOST$:

$\forall x. P\ x \Longrightarrow \forall_{\infty} x. P\ x$
 $\langle proof \rangle$

lemma $INF\text{-}mono$:

assumes $inf: \exists_{\infty} x. P\ x$ **and** $q: \bigwedge x. P\ x \Longrightarrow Q\ x$
shows $\exists_{\infty} x. Q\ x$
 $\langle proof \rangle$

lemma $MOST\text{-}mono$:

$\llbracket \forall_{\infty} x. P\ x; \bigwedge x. P\ x \Longrightarrow Q\ x \rrbracket \Longrightarrow \forall_{\infty} x. Q\ x$
 $\langle proof \rangle$

lemma $INF\text{-}nat$: $(\exists_{\infty} n. P\ (n::nat)) = (\forall m. \exists n. m < n \wedge P\ n)$

$\langle proof \rangle$

lemma $INF\text{-}nat\text{-}le$: $(\exists_{\infty} n. P\ (n::nat)) = (\forall m. \exists n. m \leq n \wedge P\ n)$

$\langle proof \rangle$

lemma $MOST\text{-}nat$: $(\forall_{\infty} n. P\ (n::nat)) = (\exists m. \forall n. m < n \longrightarrow P\ n)$

$\langle proof \rangle$

lemma $MOST\text{-}nat\text{-}le$: $(\forall_{\infty} n. P\ (n::nat)) = (\exists m. \forall n. m \leq n \longrightarrow P\ n)$

$\langle proof \rangle$

43.3 Miscellaneous

A few trivial lemmas about sets that contain at most one element. These simplify the reasoning about deterministic automata.

constdefs

atmost-one :: 'a set \Rightarrow bool
atmost-one $S \equiv \forall x y. x \in S \wedge y \in S \longrightarrow x=y$

lemma *atmost-one-empty*: $S=\{\} \Longrightarrow \text{atmost-one } S$
 $\langle \text{proof} \rangle$

lemma *atmost-one-singleton*: $S = \{x\} \Longrightarrow \text{atmost-one } S$
 $\langle \text{proof} \rangle$

lemma *atmost-one-unique* [elim]: $\llbracket \text{atmost-one } S; x \in S; y \in S \rrbracket \Longrightarrow y=x$
 $\langle \text{proof} \rangle$

end

44 Extraction: Program extraction for HOL

theory *Extraction*

imports *Datatype*

uses *Tools/rewrite-hol-proof.ML*

begin

44.1 Setup

$\langle ML \rangle$

lemmas [*extraction-expand*] =
atomize-eq atomize-all atomize-imp
allE rev-mp conjE Eq-TrueI Eq-FalseI eqTrueI eqTrueE eq-cong2
notE' impE' impE iffE imp-cong simp-thms
induct-forall-eq induct-implies-eq induct-equal-eq
induct-forall-def induct-implies-def induct-impliesI
induct-atomize induct-rulify1 induct-rulify2

datatype *sumbool* = *Left* | *Right*

44.2 Type of extracted program

extract-type

typeof (*Trueprop* P) \equiv *typeof* P

typeof $P \equiv \text{Type } (\text{TYPE}(\text{Null})) \Longrightarrow \text{typeof } Q \equiv \text{Type } (\text{TYPE}('Q)) \Longrightarrow$
typeof ($P \longrightarrow Q$) $\equiv \text{Type } (\text{TYPE}('Q))$

$$\text{typeof } Q \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \text{typeof } (P \longrightarrow Q) \equiv \text{Type } (\text{TYPE}(\text{Null}))$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}('P)) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}('Q)) \implies \\ \text{typeof } (P \longrightarrow Q) \equiv \text{Type } (\text{TYPE}('P \Rightarrow 'Q)) \end{aligned}$$

$$\begin{aligned} (\lambda x. \text{typeof } (P x)) \equiv (\lambda x. \text{Type } (\text{TYPE}(\text{Null}))) \implies \\ \text{typeof } (\forall x. P x) \equiv \text{Type } (\text{TYPE}(\text{Null})) \end{aligned}$$

$$\begin{aligned} (\lambda x. \text{typeof } (P x)) \equiv (\lambda x. \text{Type } (\text{TYPE}('P))) \implies \\ \text{typeof } (\forall x::'a. P x) \equiv \text{Type } (\text{TYPE}('a \Rightarrow 'P)) \end{aligned}$$

$$\begin{aligned} (\lambda x. \text{typeof } (P x)) \equiv (\lambda x. \text{Type } (\text{TYPE}(\text{Null}))) \implies \\ \text{typeof } (\exists x::'a. P x) \equiv \text{Type } (\text{TYPE}('a)) \end{aligned}$$

$$\begin{aligned} (\lambda x. \text{typeof } (P x)) \equiv (\lambda x. \text{Type } (\text{TYPE}('P))) \implies \\ \text{typeof } (\exists x::'a. P x) \equiv \text{Type } (\text{TYPE}('a \times 'P)) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \\ \text{typeof } (P \vee Q) \equiv \text{Type } (\text{TYPE}(\text{sumbool})) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}('Q)) \implies \\ \text{typeof } (P \vee Q) \equiv \text{Type } (\text{TYPE}('Q \text{ option})) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}('P)) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \\ \text{typeof } (P \vee Q) \equiv \text{Type } (\text{TYPE}('P \text{ option})) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}('P)) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}('Q)) \implies \\ \text{typeof } (P \vee Q) \equiv \text{Type } (\text{TYPE}('P + 'Q)) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}('Q)) \implies \\ \text{typeof } (P \wedge Q) \equiv \text{Type } (\text{TYPE}('Q)) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}('P)) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \\ \text{typeof } (P \wedge Q) \equiv \text{Type } (\text{TYPE}('P)) \end{aligned}$$

$$\begin{aligned} \text{typeof } P \equiv \text{Type } (\text{TYPE}('P)) \implies \text{typeof } Q \equiv \text{Type } (\text{TYPE}('Q)) \implies \\ \text{typeof } (P \wedge Q) \equiv \text{Type } (\text{TYPE}('P \times 'Q)) \end{aligned}$$

$$\text{typeof } (P = Q) \equiv \text{typeof } ((P \longrightarrow Q) \wedge (Q \longrightarrow P))$$

$$\text{typeof } (x \in P) \equiv \text{typeof } P$$

44.3 Realizability

realizability

$$(\text{realizes } t \text{ (Trueprop } P)) \equiv (\text{Trueprop } (\text{realizes } t \text{ } P))$$

$$\begin{aligned} (\text{typeof } P) \equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\ (\text{realizes } t \text{ } (P \longrightarrow Q)) \equiv (\text{realizes } \text{Null } P \longrightarrow \text{realizes } t \text{ } Q) \end{aligned}$$

$$\begin{aligned}
(\text{typeof } P) &\equiv (\text{Type } (\text{TYPE}('P))) \implies \\
(\text{typeof } Q) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (P \longrightarrow Q)) &\equiv (\forall x::'P. \text{realizes } x \ P \longrightarrow \text{realizes } \text{Null } Q)
\end{aligned}$$

$$(\text{realizes } t \ (P \longrightarrow Q)) \equiv (\forall x. \text{realizes } x \ P \longrightarrow \text{realizes } (t \ x) \ Q)$$

$$\begin{aligned}
(\lambda x. \text{typeof } (P \ x)) &\equiv (\lambda x. \text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (\forall x. P \ x)) &\equiv (\forall x. \text{realizes } \text{Null } (P \ x))
\end{aligned}$$

$$(\text{realizes } t \ (\forall x. P \ x)) \equiv (\forall x. \text{realizes } (t \ x) \ (P \ x))$$

$$\begin{aligned}
(\lambda x. \text{typeof } (P \ x)) &\equiv (\lambda x. \text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (\exists x. P \ x)) &\equiv (\text{realizes } \text{Null } (P \ t))
\end{aligned}$$

$$(\text{realizes } t \ (\exists x. P \ x)) \equiv (\text{realizes } (\text{snd } t) \ (P \ (\text{fst } t)))$$

$$\begin{aligned}
(\text{typeof } P) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{typeof } Q) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (P \vee Q)) &\equiv \\
(\text{case } t \text{ of Left } \Rightarrow \text{realizes } \text{Null } P \mid \text{Right } \Rightarrow \text{realizes } \text{Null } Q)
\end{aligned}$$

$$\begin{aligned}
(\text{typeof } P) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (P \vee Q)) &\equiv \\
(\text{case } t \text{ of None } \Rightarrow \text{realizes } \text{Null } P \mid \text{Some } q \Rightarrow \text{realizes } q \ Q)
\end{aligned}$$

$$\begin{aligned}
(\text{typeof } Q) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (P \vee Q)) &\equiv \\
(\text{case } t \text{ of None } \Rightarrow \text{realizes } \text{Null } Q \mid \text{Some } p \Rightarrow \text{realizes } p \ P)
\end{aligned}$$

$$\begin{aligned}
(\text{realizes } t \ (P \vee Q)) &\equiv \\
(\text{case } t \text{ of Inl } p \Rightarrow \text{realizes } p \ P \mid \text{Inr } q \Rightarrow \text{realizes } q \ Q)
\end{aligned}$$

$$\begin{aligned}
(\text{typeof } P) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (P \wedge Q)) &\equiv (\text{realizes } \text{Null } P \wedge \text{realizes } t \ Q)
\end{aligned}$$

$$\begin{aligned}
(\text{typeof } Q) &\equiv (\text{Type } (\text{TYPE}(\text{Null}))) \implies \\
(\text{realizes } t \ (P \wedge Q)) &\equiv (\text{realizes } t \ P \wedge \text{realizes } \text{Null } Q)
\end{aligned}$$

$$(\text{realizes } t \ (P \wedge Q)) \equiv (\text{realizes } (\text{fst } t) \ P \wedge \text{realizes } (\text{snd } t) \ Q)$$

$$\begin{aligned}
\text{typeof } P &\equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \\
\text{realizes } t \ (\neg P) &\equiv \neg \text{realizes } \text{Null } P
\end{aligned}$$

$$\begin{aligned}
\text{typeof } P &\equiv \text{Type } (\text{TYPE}('P)) \implies \\
\text{realizes } t \ (\neg P) &\equiv (\forall x::'P. \neg \text{realizes } x \ P)
\end{aligned}$$

$$\begin{aligned}
\text{typeof } (P::\text{bool}) &\equiv \text{Type } (\text{TYPE}(\text{Null})) \implies \\
\text{typeof } Q &\equiv \text{Type } (\text{TYPE}(\text{Null})) \implies
\end{aligned}$$

realizes t $(P = Q) \equiv \text{realizes } \text{Null } P = \text{realizes } \text{Null } Q$

$(\text{realizes } t \ (P = Q)) \equiv (\text{realizes } t \ ((P \longrightarrow Q) \wedge (Q \longrightarrow P)))$

44.4 Computational content of basic inference rules

theorem *disjE-realizer*:

assumes r : *case* x of *Inl* $p \Rightarrow P$ $p \mid$ *Inr* $q \Rightarrow Q$ q
and $r1$: $\bigwedge p. P \ p \Longrightarrow R \ (f \ p)$ **and** $r2$: $\bigwedge q. Q \ q \Longrightarrow R \ (g \ q)$
shows $R \ (\text{case } x \text{ of } \text{Inl } p \Rightarrow f \ p \mid \text{Inr } q \Rightarrow g \ q)$

$\langle \text{proof} \rangle$

theorem *disjE-realizer2*:

assumes r : *case* x of *None* $\Rightarrow P \mid$ *Some* $q \Rightarrow Q$ q
and $r1$: $P \Longrightarrow R \ f$ **and** $r2$: $\bigwedge q. Q \ q \Longrightarrow R \ (g \ q)$
shows $R \ (\text{case } x \text{ of } \text{None} \Rightarrow f \mid \text{Some } q \Rightarrow g \ q)$

$\langle \text{proof} \rangle$

theorem *disjE-realizer3*:

assumes r : *case* x of *Left* $\Rightarrow P \mid$ *Right* $\Rightarrow Q$
and $r1$: $P \Longrightarrow R \ f$ **and** $r2$: $Q \Longrightarrow R \ g$
shows $R \ (\text{case } x \text{ of } \text{Left} \Rightarrow f \mid \text{Right} \Rightarrow g)$

$\langle \text{proof} \rangle$

theorem *conjI-realizer*:

$P \ p \Longrightarrow Q \ q \Longrightarrow P \ (fst \ (p, q)) \wedge Q \ (snd \ (p, q))$

$\langle \text{proof} \rangle$

theorem *exI-realizer*:

$P \ y \ x \Longrightarrow P \ (snd \ (x, y)) \ (fst \ (x, y)) \ \langle \text{proof} \rangle$

theorem *exE-realizer*: $P \ (snd \ p) \ (fst \ p) \Longrightarrow$

$(\bigwedge x \ y. P \ y \ x \Longrightarrow Q \ (f \ x \ y)) \Longrightarrow Q \ (\text{let } (x, y) = p \text{ in } f \ x \ y)$

$\langle \text{proof} \rangle$

theorem *exE-realizer'*: $P \ (snd \ p) \ (fst \ p) \Longrightarrow$

$(\bigwedge x \ y. P \ y \ x \Longrightarrow Q) \Longrightarrow Q \ \langle \text{proof} \rangle$

realizers

impI (P, Q) : $\lambda pq. pq$

$\Lambda P \ Q \ pq \ (h: -). \text{allI} \ \cdot \cdot \cdot (\Lambda x. \text{impI} \ \cdot \cdot \cdot \cdot (h \cdot x))$

impI (P) : *Null*

$\Lambda P \ Q \ (h: -). \text{allI} \ \cdot \cdot \cdot (\Lambda x. \text{impI} \ \cdot \cdot \cdot \cdot (h \cdot x))$

impI (Q) : $\lambda q. q \ \Lambda P \ Q \ q. \text{impI} \ \cdot \cdot \cdot \cdot$

impI: *Null impI*

$mp\ (P, Q): \lambda pq. pq$
 $\Lambda P Q pq\ (h: -)\ p. mp \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot p \cdot h)$

$mp\ (P): Null$
 $\Lambda P Q\ (h: -)\ p. mp \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot p \cdot h)$

$mp\ (Q): \lambda q. q \Lambda P Q q. mp \cdot \cdot \cdot$

$mp: Null\ mp$

$allI\ (P): \lambda p. p \Lambda P p. allI \cdot \cdot$

$allI: Null\ allI$

$spec\ (P): \lambda x\ p. p\ x \Lambda P x\ p. spec \cdot \cdot \cdot x$

$spec: Null\ spec$

$exI\ (P): \lambda x\ p. (x, p) \Lambda P x\ p. exI\text{-realizer} \cdot P \cdot p \cdot x$

$exI: \lambda x. x \Lambda P x\ (h: -). h$

$exE\ (P, Q): \lambda p\ pq. let\ (x, y) = p\ in\ pq\ x\ y$
 $\Lambda P Q\ p\ (h: -)\ pq. exE\text{-realizer} \cdot P \cdot p \cdot Q \cdot pq \cdot h$

$exE\ (P): Null$
 $\Lambda P Q\ p. exE\text{-realizer}' \cdot \cdot \cdot \cdot$

$exE\ (Q): \lambda x\ pq. pq\ x$
 $\Lambda P Q\ x\ (h1: -)\ pq\ (h2: -). h2 \cdot x \cdot h1$

$exE: Null$
 $\Lambda P Q\ x\ (h1: -)\ (h2: -). h2 \cdot x \cdot h1$

$conjI\ (P, Q): Pair$
 $\Lambda P Q\ p\ (h: -)\ q. conjI\text{-realizer} \cdot P \cdot p \cdot Q \cdot q \cdot h$

$conjI\ (P): \lambda p. p$
 $\Lambda P Q\ p. conjI \cdot \cdot \cdot$

$conjI\ (Q): \lambda q. q$
 $\Lambda P Q\ (h: -)\ q. conjI \cdot \cdot \cdot \cdot h$

$conjI: Null\ conjI$

$conjunct1\ (P, Q): fst$
 $\Lambda P Q\ pq. conjunct1 \cdot \cdot \cdot$

$conjunct1\ (P): \lambda p. p$

$\Lambda P Q p. \text{conjunct1} \cdot \cdot \cdot$

$\text{conjunct1} (Q): \text{Null}$

$\Lambda P Q q. \text{conjunct1} \cdot \cdot \cdot$

$\text{conjunct1}: \text{Null conjunct1}$

$\text{conjunct2} (P, Q): \text{snd}$

$\Lambda P Q pq. \text{conjunct2} \cdot \cdot \cdot$

$\text{conjunct2} (P): \text{Null}$

$\Lambda P Q p. \text{conjunct2} \cdot \cdot \cdot$

$\text{conjunct2} (Q): \lambda p. p$

$\Lambda P Q p. \text{conjunct2} \cdot \cdot \cdot$

$\text{conjunct2}: \text{Null conjunct2}$

$\text{disjI1} (P, Q): \text{Inl}$

$\Lambda P Q p. \text{iffD2} \cdot \cdot \cdot \cdot (\text{sum.cases-1} \cdot P \cdot \cdot \cdot p)$

$\text{disjI1} (P): \text{Some}$

$\Lambda P Q p. \text{iffD2} \cdot \cdot \cdot \cdot (\text{option.cases-2} \cdot \cdot \cdot P \cdot p)$

$\text{disjI1} (Q): \text{None}$

$\Lambda P Q. \text{iffD2} \cdot \cdot \cdot \cdot (\text{option.cases-1} \cdot \cdot \cdot -)$

$\text{disjI1}: \text{Left}$

$\Lambda P Q. \text{iffD2} \cdot \cdot \cdot \cdot (\text{sumbool.cases-1} \cdot \cdot \cdot -)$

$\text{disjI2} (P, Q): \text{Inr}$

$\Lambda Q P q. \text{iffD2} \cdot \cdot \cdot \cdot (\text{sum.cases-2} \cdot \cdot \cdot Q \cdot q)$

$\text{disjI2} (P): \text{None}$

$\Lambda Q P. \text{iffD2} \cdot \cdot \cdot \cdot (\text{option.cases-1} \cdot \cdot \cdot -)$

$\text{disjI2} (Q): \text{Some}$

$\Lambda Q P q. \text{iffD2} \cdot \cdot \cdot \cdot (\text{option.cases-2} \cdot \cdot \cdot Q \cdot q)$

$\text{disjI2}: \text{Right}$

$\Lambda Q P. \text{iffD2} \cdot \cdot \cdot \cdot (\text{sumbool.cases-2} \cdot \cdot \cdot -)$

$\text{disjE} (P, Q, R): \lambda pq pr qr.$

$(\text{case } pq \text{ of } \text{Inl } p \Rightarrow pr \cdot p \mid \text{Inr } q \Rightarrow qr \cdot q)$

$\Lambda P Q R pq (h1: -) pr (h2: -) qr.$

$\text{disjE-realizer} \cdot \cdot \cdot \cdot pq \cdot R \cdot pr \cdot qr \cdot h1 \cdot h2$

$\text{disjE} (Q, R): \lambda pq pr qr.$

$(\text{case } pq \text{ of } \text{None} \Rightarrow pr \mid \text{Some } q \Rightarrow qr \cdot q)$

$\Lambda P Q R pq (h1: -) pr (h2: -) qr.$
 $disjE\text{-realizer2} \cdot \cdot \cdot \cdot pq \cdot R \cdot pr \cdot qr \cdot h1 \cdot h2$

$disjE (P, R): \lambda pq pr qr.$
 $(case\ pq\ of\ None \Rightarrow qr \mid Some\ p \Rightarrow pr\ p)$
 $\Lambda P Q R pq (h1: -) pr (h2: -) qr (h3: -).$
 $disjE\text{-realizer2} \cdot \cdot \cdot \cdot pq \cdot R \cdot qr \cdot pr \cdot h1 \cdot h3 \cdot h2$

$disjE (R): \lambda pq pr qr.$
 $(case\ pq\ of\ Left \Rightarrow pr \mid Right \Rightarrow qr)$
 $\Lambda P Q R pq (h1: -) pr (h2: -) qr.$
 $disjE\text{-realizer3} \cdot \cdot \cdot \cdot pq \cdot R \cdot pr \cdot qr \cdot h1 \cdot h2$

$disjE (P, Q): Null$
 $\Lambda P Q R pq. disjE\text{-realizer} \cdot \cdot \cdot \cdot pq \cdot (\lambda x. R) \cdot \cdot \cdot$

$disjE (Q): Null$
 $\Lambda P Q R pq. disjE\text{-realizer2} \cdot \cdot \cdot \cdot pq \cdot (\lambda x. R) \cdot \cdot \cdot$

$disjE (P): Null$
 $\Lambda P Q R pq (h1: -) (h2: -) (h3: -).$
 $disjE\text{-realizer2} \cdot \cdot \cdot \cdot pq \cdot (\lambda x. R) \cdot \cdot \cdot \cdot h1 \cdot h3 \cdot h2$

$disjE: Null$
 $\Lambda P Q R pq. disjE\text{-realizer3} \cdot \cdot \cdot \cdot pq \cdot (\lambda x. R) \cdot \cdot \cdot$

$FalseE (P): arbitrary$
 $\Lambda P. FalseE \cdot$

$FalseE: Null FalseE$

$notI (P): Null$
 $\Lambda P (h: -). allI \cdot \cdot \cdot (\Lambda x. notI \cdot \cdot \cdot (h \cdot x))$

$notI: Null notI$

$notE (P, R): \lambda p. arbitrary$
 $\Lambda P R (h: -) p. notE \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot p \cdot h)$

$notE (P): Null$
 $\Lambda P R (h: -) p. notE \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot p \cdot h)$

$notE (R): arbitrary$
 $\Lambda P R. notE \cdot \cdot \cdot$

$notE: Null notE$

$subst (P): \lambda s t ps. ps$
 $\Lambda s t P (h: -) ps. subst \cdot s \cdot t \cdot P ps \cdot h$

subst: *Null subst*

iffD1 (*P*, *Q*): *fst*
 $\Lambda Q P pq (h: -) p.$
 $mp \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot p \cdot (conjunct1 \cdot \cdot \cdot \cdot h))$

iffD1 (*P*): $\lambda p. p$
 $\Lambda Q P p (h: -). mp \cdot \cdot \cdot \cdot (conjunct1 \cdot \cdot \cdot \cdot h)$

iffD1 (*Q*): *Null*
 $\Lambda Q P q1 (h: -) q2.$
 $mp \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot q2 \cdot (conjunct1 \cdot \cdot \cdot \cdot h))$

iffD1: *Null iffD1*

iffD2 (*P*, *Q*): *snd*
 $\Lambda P Q pq (h: -) q.$
 $mp \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot q \cdot (conjunct2 \cdot \cdot \cdot \cdot h))$

iffD2 (*P*): $\lambda p. p$
 $\Lambda P Q p (h: -). mp \cdot \cdot \cdot \cdot (conjunct2 \cdot \cdot \cdot \cdot h)$

iffD2 (*Q*): *Null*
 $\Lambda P Q q1 (h: -) q2.$
 $mp \cdot \cdot \cdot \cdot (spec \cdot \cdot \cdot q2 \cdot (conjunct2 \cdot \cdot \cdot \cdot h))$

iffD2: *Null iffD2*

iffI (*P*, *Q*): *Pair*
 $\Lambda P Q pq (h1 : -) qp (h2 : -). conjI\text{-realizer} \cdot$
 $(\lambda pq. \forall x. P x \longrightarrow Q (pq x)) \cdot pq \cdot$
 $(\lambda qp. \forall x. Q x \longrightarrow P (qp x)) \cdot qp \cdot$
 $(allI \cdot \cdot \cdot (\Lambda x. impI \cdot \cdot \cdot \cdot (h1 \cdot x))) \cdot$
 $(allI \cdot \cdot \cdot (\Lambda x. impI \cdot \cdot \cdot \cdot (h2 \cdot x)))$

iffI (*P*): $\lambda p. p$
 $\Lambda P Q (h1 : -) p (h2 : -). conjI \cdot \cdot \cdot \cdot$
 $(allI \cdot \cdot \cdot (\Lambda x. impI \cdot \cdot \cdot \cdot (h1 \cdot x))) \cdot$
 $(impI \cdot \cdot \cdot \cdot h2)$

iffI (*Q*): $\lambda q. q$
 $\Lambda P Q q (h1 : -) (h2 : -). conjI \cdot \cdot \cdot \cdot$
 $(impI \cdot \cdot \cdot \cdot h1) \cdot$
 $(allI \cdot \cdot \cdot (\Lambda x. impI \cdot \cdot \cdot \cdot (h2 \cdot x)))$

iffI: *Null iffI*

end

45 Reconstruction: Reconstructing external resolution proofs

theory *Reconstruction*
imports *Hilbert-Choice Map Infinite-Set Extraction*
uses *Tools/res-lib.ML*

Tools/res-clause.ML
Tools/res-skolem-function.ML
Tools/res-axioms.ML
Tools/res-types-sorts.ML

Tools/ATP/recon-order-clauses.ML
Tools/ATP/recon-translate-proof.ML
Tools/ATP/recon-parse.ML
Tools/ATP/recon-transfer-proof.ML
Tools/ATP/AtpCommunication.ML
Tools/ATP/watcher.ML
Tools/ATP/res-clasimpset.ML
Tools/res-atp.ML
Tools/reconstruction.ML

begin

$\langle ML \rangle$

end

46 Main: Main HOL

theory *Main*
imports *SAT Reconstruction*
begin

Theory *Main* includes everything. Note that theory *PreList* already includes most HOL theories.

Late clause setup: installs *all* simprules and claset rules into the clause cache; cf. theory *Reconstruction*.

$\langle ML \rangle$

end

References

- [1] H. Davenport. *The Higher Arithmetic*. Cambridge University Press, 1992.