

Examples of Inductive and Coinductive Definitions in HOL

Stefan Berghofer
Tobias Nipkow
Lawrence C Paulson
Markus Wenzel

October 1, 2005

Abstract

This is a collection of small examples to demonstrate Isabelle/HOL's (co)inductive definitions package. Large examples appear on many other sessions, such as Lambda, IMP, and Auth.

Contents

1	The Mutilated Chess Board Problem	5
2	Defining an Initial Algebra by Quotienting a Free Algebra	7
2.1	Defining the Free Algebra	7
2.2	Some Functions on the Free Algebra	8
2.2.1	The Set of Nonces	8
2.2.2	The Left Projection	9
2.2.3	The Right Projection	9
2.2.4	The Discriminator for Constructors	9
2.3	The Initial Algebra: A Quotiented Message Type	10
2.3.1	Characteristic Equations for the Abstract Constructors	11
2.4	The Abstract Function to Return the Set of Nonces	12
2.5	The Abstract Function to Return the Left Part	12
2.6	The Abstract Function to Return the Right Part	13
2.7	Injectivity Properties of Some Constructors	13
2.8	The Abstract Discriminator	15
3	Quotienting a Free Algebra Involving Nested Recursion	16
3.1	Defining the Free Algebra	16
3.2	Some Functions on the Free Algebra	18
3.2.1	The Set of Variables	18
3.2.2	Functions for Freeness	18

3.3	The Initial Algebra: A Quotiented Message Type	19
3.4	Every list of abstract expressions can be expressed in terms of a list of concrete expressions	20
3.4.1	Characteristic Equations for the Abstract Constructors	21
3.5	The Abstract Function to Return the Set of Variables	22
3.6	Injectivity Properties of Some Constructors	22
3.7	Injectivity of <i>FnCall</i>	23
3.8	The Abstract Discriminator	24
4	Terms over a given alphabet	25
5	Arithmetic and boolean expressions	26
6	Infinitely branching trees	27
6.1	The Brouwer ordinals, as in ZF/Induct/Brouwer.thy.	28
6.2	A WF Ordering for The Brouwer ordinals (Michael Compton)	29
7	Ordinals	30
8	Sigma algebras	31
9	Combinatory Logic example: the Church-Rosser Theorem	32
9.1	Definitions	32
9.2	Reflexive/Transitive closure preserves Church-Rosser property	33
9.3	Non-contraction results	34
9.4	Results about Parallel Contraction	35
9.5	Basic properties of parallel contraction	35
10	Meta-theory of propositional logic	36
10.1	The datatype of propositions	36
10.2	The proof system	36
10.3	The semantics	37
10.3.1	Semantics of propositional logic.	37
10.3.2	Logical consequence	37
10.4	Proof theory of propositional logic	37
10.4.1	Weakening, left and right	37
10.4.2	The deduction theorem	38
10.4.3	The cut rule	38
10.4.4	Soundness of the rules wrt truth-table semantics	38
10.5	Completeness	38
10.5.1	Towards the completeness proof	38
10.6	Completeness – lemmas for reducing the set of assumptions	39
10.6.1	Completeness theorem	40

11 Definition of type <i>l</i>list by a greatest fixed point	63
11.0.2 Sample function definitions. Item-based ones start with <i>L</i>	65
11.0.3 Simplification	65
11.1 Type checking by coinduction	66
11.2 <i>LList-corec</i> satisfies the desired recursion equation	66
11.2.1 The directions of the equality are proved separately	67
11.3 <i>l</i> list equality as a <i>gfp</i> ; the bisimulation principle	67
11.3.1 Coinduction, using <i>LListD-Fun</i>	68
11.3.2 To show two <i>L</i> Lists are equal, exhibit a bisimulation! [also admits true equality] Replace <i>A</i> by some partic- ular set, like $\{x. \text{True}\}$???	69
11.4 Finality of <i>l</i> list(<i>A</i>): Uniqueness of functions defined by core- cursion	70
11.4.1 Obsolete proof of <i>LList-corec-unique</i> : complete induc- tion, not coinduction	70
11.5 <i>Lconst</i> : defined directly by <i>lfp</i>	71
11.6 Isomorphisms	71
11.6.1 Distinctness of constructors	72
11.6.2 <i>l</i> list constructors	72
11.6.3 Injectiveness of <i>CONS</i> and <i>LCons</i>	72
11.7 Reasoning about <i>l</i> list(<i>A</i>)	72
11.8 The functional <i>Lmap</i>	73
11.8.1 Two easy results about <i>Lmap</i>	73
11.9 <i>Lappend</i> – its two arguments cause some complications!	74
11.9.1 Alternative type-checking proofs for <i>Lappend</i>	74
11.10 Lazy lists as the type ' <i>a l</i> list – strongly typed versions of above	75
11.10.1 <i>l</i> list-case: case analysis for ' <i>a l</i> list	75
11.10.2 <i>l</i> list-corec: corecursion for ' <i>a l</i> list	75
11.11 Proofs about type ' <i>a l</i> list functions	76
11.12 Deriving <i>l</i> list-equalityI – <i>l</i> list equality is a bisimulation	76
11.12.1 To show two <i>l</i> lists are equal, exhibit a bisimulation! [also admits true equality]	77
11.12.2 Rules to prove the 2nd premise of <i>l</i> list-equalityI	77
11.13 The functional <i>lmap</i>	78
11.13.1 Two easy results about <i>lmap</i>	78
11.14 iterates – <i>l</i> list-fun-equalityI cannot be used!	78
11.15 A rather complex proof about iterates – cf Andy Pitts	78
11.15.1 Two lemmas about <i>natrec</i> <i>n x (%m. g)</i> , which is es- sentially $(g^n)(x)$	78
11.16 <i>lappend</i> – its two arguments cause some complications!	79
11.16.1 Two proofs that <i>lmap</i> distributes over <i>lappend</i>	80

12 The "filter" functional for coinductive lists –defined by a combination of induction and coinduction	81
12.1 <i>findRel</i> : basic laws	81
12.2 Properties of <i>Domain (findRel p)</i>	81
12.3 <i>find</i> : basic equations	82
12.4 <i>lfilter</i> : basic equations	82
12.5 <i>lfilter</i> : simple facts by coinduction	83
12.6 Numerous lemmas required to prove <i>lfilter-conj</i>	84
12.7 Numerous lemmas required to prove <i>?: lfilter p (lmap f l) =</i> <i>lmap f (lfilter (%x. p(f x)) l)</i>	85

1 The Mutilated Chess Board Problem

theory *Mutil* **imports** *Main* **begin**

The Mutilated Chess Board Problem, formalized inductively.

Originator is Max Black, according to J A Robinson. Popularized as the Mutilated Checkerboard Problem by J McCarthy.

```
consts tiling :: 'a set set => 'a set set
inductive tiling A
  intros
    empty [simp, intro]: {} ∈ tiling A
    Un [simp, intro]: [| a ∈ A; t ∈ tiling A; a ∩ t = {} |]
                      ==> a ∪ t ∈ tiling A
```

```
consts domino :: (nat × nat) set set
inductive domino
  intros
    horiz [simp]: {(i, j), (i, Suc j)} ∈ domino
    vertl [simp]: {(i, j), (Suc i, j)} ∈ domino
```

Sets of squares of the given colour

```
constdefs
  coloured :: nat => (nat × nat) set
  coloured b == {(i, j). (i + j) mod 2 = b}
```

```
syntax whites :: (nat × nat) set
       blacks :: (nat × nat) set
```

```
translations
  whites == coloured 0
  blacks == coloured (Suc 0)
```

The union of two disjoint tilings is a tiling

```
lemma tiling-UnI [intro]:
  [| t ∈ tiling A; u ∈ tiling A; t ∩ u = {} |] ==> t ∪ u ∈ tiling A
apply (induct set: tiling)
apply (auto simp add: Un-assoc)
done
```

Chess boards

```
lemma Sigma-Suc1 [simp]:
  lessThan (Suc n) × B = ({n} × B) ∪ ((lessThan n) × B)
by (auto simp add: lessThan-def)
```

```
lemma Sigma-Suc2 [simp]:
  A × lessThan (Suc n) = (A × {n}) ∪ (A × (lessThan n))
by (auto simp add: lessThan-def)
```

lemma *sing-Times-lemma*: $(\{i\} \times \{n\}) \cup (\{i\} \times \{m\}) = \{(i, m), (i, n)\}$
by *auto*

lemma *dominoes-tile-row* [*intro!*]: $\{i\} \times \text{lessThan } (2 * n) \in \text{tiling domino}$
apply (*induct n*)
apply (*simp-all add: Un-assoc [symmetric]*)
apply (*rule tiling.Un*)
apply (*auto simp add: sing-Times-lemma*)
done

lemma *dominoes-tile-matrix*: $(\text{lessThan } m) \times \text{lessThan } (2 * n) \in \text{tiling domino}$
by (*induct m, auto*)

coloured and Dominoes

lemma *coloured-insert* [*simp*]:
 $\text{coloured } b \cap (\text{insert } (i, j) t) =$
 $(\text{if } (i + j) \bmod 2 = b \text{ then } \text{insert } (i, j) (\text{coloured } b \cap t)$
 $\text{else } \text{coloured } b \cap t)$
by (*auto simp add: coloured-def*)

lemma *domino-singletons*:
 $d \in \text{domino} ==>$
 $(\exists i j. \text{whites} \cap d = \{(i, j)\}) \wedge$
 $(\exists m n. \text{blacks} \cap d = \{(m, n)\})$
apply (*erule domino.cases*)
apply (*auto simp add: mod-Suc*)
done

lemma *domino-finite* [*simp*]: $d \in \text{domino} ==> \text{finite } d$
by (*erule domino.cases, auto*)

Tilings of dominoes

lemma *tiling-domino-finite* [*simp*]: $t \in \text{tiling domino} ==> \text{finite } t$
by (*induct set: tiling, auto*)

declare

Int-Un-distrib [*simp*]
Diff-Int-distrib [*simp*]

lemma *tiling-domino-0-1*:
 $t \in \text{tiling domino} ==> \text{card}(\text{whites} \cap t) = \text{card}(\text{blacks} \cap t)$
apply (*induct set: tiling*)
apply (*drule-tac [2] domino-singletons*)
apply *auto*
apply (*subgoal-tac* $\forall p C. C \cap a = \{p\} \dashv\vdash p \notin t$)
— this lemma tells us that both “inserts” are non-trivial
apply (*simp (no-asm-simp)*)

```

apply blast
done

```

Final argument is surprisingly complex

```

theorem gen-mutil-not-tiling:
   $t \in \text{tiling\_domino} \implies$ 
     $(i + j) \bmod 2 = 0 \implies (m + n) \bmod 2 = 0 \implies$ 
     $\{(i, j), (m, n)\} \subseteq t$ 
     $\implies (t - \{(i, j)\} - \{(m, n)\}) \notin \text{tiling\_domino}$ 
  apply (rule notI)
  apply (subgoal-tac)
     $\text{card } (\text{whites} \cap (t - \{(i, j)\} - \{(m, n)\})) <$ 
     $\text{card } (\text{blacks} \cap (t - \{(i, j)\} - \{(m, n)\}))$ 
  apply (force simp only: tiling-domino-0-1)
  apply (simp add: tiling-domino-0-1 [symmetric])
  apply (simp add: coloured-def card-Diff2-less)
done

```

Apply the general theorem to the well-known case

```

theorem mutil-not-tiling:
   $t = \text{lessThan } (2 * \text{Suc } m) \times \text{lessThan } (2 * \text{Suc } n)$ 
   $\implies t - \{(0, 0)\} - \{(\text{Suc } (2 * m), \text{Suc } (2 * n))\} \notin \text{tiling\_domino}$ 
  apply (rule gen-mutil-not-tiling)
  apply (blast intro!: dominoes-tile-matrix)
  apply auto
done

end

```

2 Defining an Initial Algebra by Quotienting a Free Algebra

```

theory QuoDataType imports Main begin

```

2.1 Defining the Free Algebra

Messages with encryption and decryption as free constructors.

```

datatype
  freemsg = NONCE nat
    | MPAIR freemsg freemsg
    | CRYPT nat freemsg
    | DECRYPT nat freemsg

```

The equivalence relation, which makes encryption and decryption inverses provided the keys are the same.

```

consts msgrel :: (freemsg * freemsg) set

syntax
  -msgrel :: [freemsg, freemsg] => bool (infixl ~~ 50)
syntax (xsymbols)
  -msgrel :: [freemsg, freemsg] => bool (infixl ~ 50)
syntax (HTML output)
  -msgrel :: [freemsg, freemsg] => bool (infixl ~ 50)
translations
  X ~ Y == (X, Y) ∈ msgrel

```

The first two rules are the desired equations. The next four rules make the equations applicable to subterms. The last two rules are symmetry and transitivity.

```

inductive msgrel
  intros
    CD: CRYPT K (DECRYPT K X) ~ X
    DC: DECRYPT K (CRYPT K X) ~ X
    NONCE: NONCE N ~ NONCE N
    MPAIR: [X ~ X'; Y ~ Y'] ==> MPAIR X Y ~ MPAIR X' Y'
    CRYPT: X ~ X' ==> CRYPT K X ~ CRYPT K X'
    DECRYPT: X ~ X' ==> DECRYPT K X ~ DECRYPT K X'
    SYM: X ~ Y ==> Y ~ X
    TRANS: [X ~ Y; Y ~ Z] ==> X ~ Z

```

Proving that it is an equivalence relation

```

lemma msgrel-refl: X ~ X
by (induct X, (blast intro: msgrel.intros)+)

```

```

theorem equiv-msgrel: equiv UNIV msgrel
proof (simp add: equiv-def, intro conjI)
  show reflexive msgrel by (simp add: refl-def msgrel-refl)
  show sym msgrel by (simp add: sym-def, blast intro: msgrel.SYM)
  show trans msgrel by (simp add: trans-def, blast intro: msgrel.TRANS)
qed

```

2.2 Some Functions on the Free Algebra

2.2.1 The Set of Nonces

A function to return the set of nonces present in a message. It will be lifted to the initial algebra, to serve as an example of that process.

```

consts
  freenonces :: freemsg => nat set

primrec
  freenonces (NONCE N) = {N}
  freenonces (MPAIR X Y) = freenonces X ∪ freenonces Y

```


$\text{freenonces } (\text{CRYPT } K \ X) = \text{freenonces } X$
 $\text{freenonces } (\text{DECRYPT } K \ X) = \text{freenonces } X$

This theorem lets us prove that the nonces function respects the equivalence relation. It also helps us prove that Nonce (the abstract constructor) is injective

theorem *msgrel-imp-eq-freenonces*: $U \sim V \implies \text{freenonces } U = \text{freenonces } V$
by (*erule msgrel.induct*, *auto*)

2.2.2 The Left Projection

A function to return the left part of the top pair in a message. It will be lifted to the initial algebra, to serve as an example of that process.

consts *freeleft* :: *freemsg* \Rightarrow *freemsg*
primrec
 $\text{freeleft } (\text{NONCE } N) = \text{NONCE } N$
 $\text{freeleft } (\text{MPAIR } X \ Y) = X$
 $\text{freeleft } (\text{CRYPT } K \ X) = \text{freeleft } X$
 $\text{freeleft } (\text{DECRYPT } K \ X) = \text{freeleft } X$

This theorem lets us prove that the left function respects the equivalence relation. It also helps us prove that MPair (the abstract constructor) is injective

theorem *msgrel-imp-eqv-freeleft*:
 $U \sim V \implies \text{freeleft } U \sim \text{freeleft } V$
by (*erule msgrel.induct*, *auto intro: msgrel.intros*)

2.2.3 The Right Projection

A function to return the right part of the top pair in a message.

consts *freeright* :: *freemsg* \Rightarrow *freemsg*
primrec
 $\text{freeright } (\text{NONCE } N) = \text{NONCE } N$
 $\text{freeright } (\text{MPAIR } X \ Y) = Y$
 $\text{freeright } (\text{CRYPT } K \ X) = \text{freeright } X$
 $\text{freeright } (\text{DECRYPT } K \ X) = \text{freeright } X$

This theorem lets us prove that the right function respects the equivalence relation. It also helps us prove that MPair (the abstract constructor) is injective

theorem *msgrel-imp-eqv-freeright*:
 $U \sim V \implies \text{freeright } U \sim \text{freeright } V$
by (*erule msgrel.induct*, *auto intro: msgrel.intros*)

2.2.4 The Discriminator for Constructors

A function to distinguish nonces, mpairs and encryptions

consts *freediscrim* :: *freemsg* \Rightarrow *int*

primrec

freediscrim (*NONCE* *N*) = 0

freediscrim (*MPAIR* *X* *Y*) = 1

freediscrim (*CRYPT* *K* *X*) = *freediscrim* *X* + 2

freediscrim (*DECRYPT* *K* *X*) = *freediscrim* *X* - 2

This theorem helps us prove *Nonce* *N* \neq *MPair* *X* *Y*

theorem *msgrel-imp-eq-freediscrim*:

$U \sim V \Longrightarrow \text{freediscrim } U = \text{freediscrim } V$

by (*erule msgrel.induct*, *auto*)

2.3 The Initial Algebra: A Quotiented Message Type

typedef (*Msg*) *msg* = *UNIV* // *msgrel*

by (*auto simp add: quotient-def*)

The abstract message constructors

constdefs

Nonce :: *nat* \Rightarrow *msg*

Nonce *N* == *Abs-Msg*(*msgrel*“{*NONCE* *N*}“)

MPair :: [*msg*, *msg*] \Rightarrow *msg*

MPair *X* *Y* ==

Abs-Msg ($\bigcup U \in \text{Rep-Msg } X. \bigcup V \in \text{Rep-Msg } Y. \text{msgrel}“\{\text{MPAIR } U \ V\}“$)

Crypt :: [*nat*, *msg*] \Rightarrow *msg*

Crypt *K* *X* ==

Abs-Msg ($\bigcup U \in \text{Rep-Msg } X. \text{msgrel}“\{\text{CRYPT } K \ U\}“$)

Decrypt :: [*nat*, *msg*] \Rightarrow *msg*

Decrypt *K* *X* ==

Abs-Msg ($\bigcup U \in \text{Rep-Msg } X. \text{msgrel}“\{\text{DECRYPT } K \ U\}“$)

Reduces equality of equivalence classes to the *msgrel* relation: (*msgrel* “{*x*}“ = *msgrel* “{*y*}“) = (*x* \sim *y*)

lemmas *equiv-msgrel-iff* = *eq-equiv-class-iff* [*OF equiv-msgrel UNIV-I UNIV-I*]

declare *equiv-msgrel-iff* [*simp*]

All equivalence classes belong to set of representatives

lemma [*simp*]: *msgrel*“{*U*}“ \in *Msg*

by (*auto simp add: Msg-def quotient-def intro: msgrel-refl*)

lemma *inj-on-Abs-Msg*: *inj-on* *Abs-Msg* *Msg*

apply (*rule inj-on-inverseI*)

apply (*erule Abs-Msg-inverse*)

done

Reduces equality on abstractions to equality on representatives

declare *inj-on-Abs-Msg* [*THEN inj-on-iff*, *simp*]

declare *Abs-Msg-inverse* [*simp*]

2.3.1 Characteristic Equations for the Abstract Constructors

lemma *MPair*: *MPair* (*Abs-Msg*(*msgrel*“{*U*}”) (*Abs-Msg*(*msgrel*“{*V*}”) =
Abs-Msg (*msgrel*“{*MPAIR U V*}”)

proof –

have ($\lambda U V. \text{msgrel} \text{ “ } \{ \text{MPAIR } U \ V \} \text{ respects2 msgrel}$

by (*simp add: congruent2-def msgrel.MPAIR*)

thus *?thesis*

by (*simp add: MPair-def UN-equiv-class2 [OF equiv-msgrel equiv-msgrel]*)

qed

lemma *Crypt*: *Crypt K* (*Abs-Msg*(*msgrel*“{*U*}”) = *Abs-Msg* (*msgrel*“{*CRYPT K U*}”)

proof –

have ($\lambda U. \text{msgrel} \text{ “ } \{ \text{CRYPT } K \ U \} \text{ respects msgrel}$

by (*simp add: congruent-def msgrel.CRYPT*)

thus *?thesis*

by (*simp add: Crypt-def UN-equiv-class [OF equiv-msgrel]*)

qed

lemma *Decrypt*:

Decrypt K (*Abs-Msg*(*msgrel*“{*U*}”) = *Abs-Msg* (*msgrel*“{*DECRYPT K U*}”)

proof –

have ($\lambda U. \text{msgrel} \text{ “ } \{ \text{DECRYPT } K \ U \} \text{ respects msgrel}$

by (*simp add: congruent-def msgrel.DECRYPT*)

thus *?thesis*

by (*simp add: Decrypt-def UN-equiv-class [OF equiv-msgrel]*)

qed

Case analysis on the representation of a msg as an equivalence class.

lemma *eq-Abs-Msg* [*case-names Abs-Msg*, *cases type: msg*]:

($\lambda U. z = \text{Abs-Msg}(\text{msgrel} \text{ “ } \{ U \}) \implies P \implies P$

apply (*rule Rep-Msg [of z, unfolded Msg-def, THEN quotientE]*)

apply (*drule arg-cong [where f=Abs-Msg]*)

apply (*auto simp add: Rep-Msg-inverse intro: msgrel-refl*)

done

Establishing these two equations is the point of the whole exercise

theorem *CD-eq* [*simp*]: *Crypt K* (*Decrypt K X*) = *X*

by (*cases X, simp add: Crypt Decrypt CD*)

theorem *DC-eq* [*simp*]: *Decrypt K* (*Crypt K X*) = *X*

by (*cases X, simp add: Crypt Decrypt DC*)

2.4 The Abstract Function to Return the Set of Nonces

constdefs

nonces :: *msg* \Rightarrow *nat set*
nonces *X* == $\bigcup U \in \text{Rep-Msg } X. \text{freenonces } U$

lemma *nonces-congruent*: *freenonces* respects *msgrel*
by (*simp add: congruent-def msgrel-imp-eq-freenonces*)

Now prove the four equations for *nonces*

lemma *nonces-Nonce* [*simp*]: *nonces* (*Nonce* *N*) = {*N*}
by (*simp add: nonces-def Nonce-def*
UN-equiv-class [OF equiv-msgrel nonces-congruent])

lemma *nonces-MPair* [*simp*]: *nonces* (*MPair* *X* *Y*) = *nonces* *X* \cup *nonces* *Y*
apply (*cases* *X*, *cases* *Y*)
apply (*simp add: nonces-def MPair*
UN-equiv-class [OF equiv-msgrel nonces-congruent])
done

lemma *nonces-Crypt* [*simp*]: *nonces* (*Crypt* *K* *X*) = *nonces* *X*
apply (*cases* *X*)
apply (*simp add: nonces-def Crypt*
UN-equiv-class [OF equiv-msgrel nonces-congruent])
done

lemma *nonces-Decrypt* [*simp*]: *nonces* (*Decrypt* *K* *X*) = *nonces* *X*
apply (*cases* *X*)
apply (*simp add: nonces-def Decrypt*
UN-equiv-class [OF equiv-msgrel nonces-congruent])
done

2.5 The Abstract Function to Return the Left Part

constdefs

left :: *msg* \Rightarrow *msg*
left *X* == *Abs-Msg* ($\bigcup U \in \text{Rep-Msg } X. \text{msgrel}''\{\text{freeleft } U\}$)

lemma *left-congruent*: ($\lambda U. \text{msgrel}''\{\text{freeleft } U\}$) respects *msgrel*
by (*simp add: congruent-def msgrel-imp-eqv-freeleft*)

Now prove the four equations for *left*

lemma *left-Nonce* [*simp*]: *left* (*Nonce* *N*) = *Nonce* *N*
by (*simp add: left-def Nonce-def*
UN-equiv-class [OF equiv-msgrel left-congruent])

lemma *left-MPair* [*simp*]: *left* (*MPair* *X* *Y*) = *X*
apply (*cases* *X*, *cases* *Y*)
apply (*simp add: left-def MPair*
UN-equiv-class [OF equiv-msgrel left-congruent])

done

lemma *left-Crypt* [simp]: *left* (*Crypt* *K* *X*) = *left* *X*
apply (*cases* *X*)
apply (*simp* *add*: *left-def Crypt*
 UN-equiv-class [*OF equiv-msgrel left-congruent*])
done

lemma *left-Decrypt* [simp]: *left* (*Decrypt* *K* *X*) = *left* *X*
apply (*cases* *X*)
apply (*simp* *add*: *left-def Decrypt*
 UN-equiv-class [*OF equiv-msgrel left-congruent*])
done

2.6 The Abstract Function to Return the Right Part

constdefs

right :: *msg* \Rightarrow *msg*
right *X* == *Abs-Msg* ($\bigcup U \in \text{Rep-Msg } X. \text{msgrel} \{ \text{freeright } U \}$)

lemma *right-congruent*: ($\lambda U. \text{msgrel} \{ \text{freeright } U \}$) respects *msgrel*
by (*simp* *add*: *congruent-def msgrel-imp-equiv-freeright*)

Now prove the four equations for *right*

lemma *right-Nonce* [simp]: *right* (*Nonce* *N*) = *Nonce* *N*
by (*simp* *add*: *right-def Nonce-def*
 UN-equiv-class [*OF equiv-msgrel right-congruent*])

lemma *right-MPair* [simp]: *right* (*MPair* *X* *Y*) = *Y*
apply (*cases* *X*, *cases* *Y*)
apply (*simp* *add*: *right-def MPair*
 UN-equiv-class [*OF equiv-msgrel right-congruent*])
done

lemma *right-Crypt* [simp]: *right* (*Crypt* *K* *X*) = *right* *X*
apply (*cases* *X*)
apply (*simp* *add*: *right-def Crypt*
 UN-equiv-class [*OF equiv-msgrel right-congruent*])
done

lemma *right-Decrypt* [simp]: *right* (*Decrypt* *K* *X*) = *right* *X*
apply (*cases* *X*)
apply (*simp* *add*: *right-def Decrypt*
 UN-equiv-class [*OF equiv-msgrel right-congruent*])
done

2.7 Injectivity Properties of Some Constructors

lemma *NONCE-imp-eq*: *NONCE* *m* \sim *NONCE* *n* \Longrightarrow *m* = *n*

by (*drule msgrel-imp-eq-freenonces, simp*)

Can also be proved using the function *nonces*

lemma *Nonce-Nonce-eq [iff]: (Nonce m = Nonce n) = (m = n)*

by (*auto simp add: Nonce-def msgrel-refl dest: NONCE-imp-eq*)

lemma *MPAIR-imp-eqv-left: MPAIR X Y ~ MPAIR X' Y' \implies X ~ X'*

by (*drule msgrel-imp-eqv-freeleft, simp*)

lemma *MPair-imp-eq-left:*

assumes *eq: MPair X Y = MPair X' Y'* **shows** *X = X'*

proof –

from *eq*

have *left (MPair X Y) = left (MPair X' Y')* **by** *simp*

thus *?thesis* **by** *simp*

qed

lemma *MPAIR-imp-eqv-right: MPAIR X Y ~ MPAIR X' Y' \implies Y ~ Y'*

by (*drule msgrel-imp-eqv-freeright, simp*)

lemma *MPair-imp-eq-right: MPair X Y = MPair X' Y' \implies Y = Y'*

apply (*cases X, cases X', cases Y, cases Y'*)

apply (*simp add: MPair*)

apply (*erule MPAIR-imp-eqv-right*)

done

theorem *MPair-MPair-eq [iff]: (MPair X Y = MPair X' Y') = (X=X' & Y=Y')*

by (*blast dest: MPair-imp-eq-left MPair-imp-eq-right*)

lemma *NONCE-neq-MPAIR: NONCE m ~ MPAIR X Y \implies False*

by (*drule msgrel-imp-eq-freediscrim, simp*)

theorem *Nonce-neq-MPair [iff]: Nonce N \neq MPair X Y*

apply (*cases X, cases Y*)

apply (*simp add: Nonce-def MPair*)

apply (*blast dest: NONCE-neq-MPAIR*)

done

Example suggested by a referee

theorem *Crypt-Nonce-neq-Nonce: Crypt K (Nonce M) \neq Nonce N*

by (*auto simp add: Nonce-def Crypt dest: msgrel-imp-eq-freediscrim*)

...and many similar results

theorem *Crypt2-Nonce-neq-Nonce: Crypt K (Crypt K' (Nonce M)) \neq Nonce N*

by (*auto simp add: Nonce-def Crypt dest: msgrel-imp-eq-freediscrim*)

theorem *Crypt-Crypt-eq [iff]: (Crypt K X = Crypt K X') = (X=X')*

proof

```

    assume Crypt K X = Crypt K X'
    hence Decrypt K (Crypt K X) = Decrypt K (Crypt K X') by simp
    thus X = X' by simp
next
  assume X = X'
  thus Crypt K X = Crypt K X' by simp
qed

theorem Decrypt-Decrypt-eq [iff]: (Decrypt K X = Decrypt K X') = (X=X')
proof
  assume Decrypt K X = Decrypt K X'
  hence Crypt K (Decrypt K X) = Crypt K (Decrypt K X') by simp
  thus X = X' by simp
next
  assume X = X'
  thus Decrypt K X = Decrypt K X' by simp
qed

lemma msg-induct [case-names Nonce MPair Crypt Decrypt, cases type: msg]:
  assumes N:  $\bigwedge N. P \text{ (Nonce } N\text{)}$ 
    and M:  $\bigwedge X Y. \llbracket P X; P Y \rrbracket \implies P \text{ (MPair } X Y\text{)}$ 
    and C:  $\bigwedge K X. P X \implies P \text{ (Crypt } K X\text{)}$ 
    and D:  $\bigwedge K X. P X \implies P \text{ (Decrypt } K X\text{)}$ 
  shows P msg
proof (cases msg, erule ssubst)
  fix U::freemsg
  show P (Abs-Msg (msgrel “ {U}))
  proof (induct U)
    case (NONCE N)
    with N show ?case by (simp add: Nonce-def)
  next
    case (MPAIR X Y)
    with M [of Abs-Msg (msgrel “ {X}) Abs-Msg (msgrel “ {Y})]
    show ?case by (simp add: MPair)
  next
    case (CRYPT K X)
    with C [of Abs-Msg (msgrel “ {X})]
    show ?case by (simp add: Crypt)
  next
    case (DECRYPT K X)
    with D [of Abs-Msg (msgrel “ {X})]
    show ?case by (simp add: Decrypt)
  qed
qed

```

2.8 The Abstract Discriminator

However, as *Crypt-Nonce-neq-Nonce* above illustrates, we don't need this function in order to prove discrimination theorems.

```

constdefs
  discrim :: msg  $\Rightarrow$  int
  discrim X == contents ( $\bigcup U \in \text{Rep-Msg } X. \{\text{freediscrim } U\}$ )

lemma discrim-congruent: ( $\lambda U. \{\text{freediscrim } U\}$ ) respects msgrel
by (simp add: congruent-def msgrel-imp-eq-freediscrim)

Now prove the four equations for discrim

lemma discrim-Nonce [simp]: discrim (Nonce N) = 0
by (simp add: discrim-def Nonce-def
      UN-equiv-class [OF equiv-msgrel discrim-congruent])

lemma discrim-MPair [simp]: discrim (MPair X Y) = 1
apply (cases X, cases Y)
apply (simp add: discrim-def MPair
      UN-equiv-class [OF equiv-msgrel discrim-congruent])
done

lemma discrim-Crypt [simp]: discrim (Crypt K X) = discrim X + 2
apply (cases X)
apply (simp add: discrim-def Crypt
      UN-equiv-class [OF equiv-msgrel discrim-congruent])
done

lemma discrim-Decrypt [simp]: discrim (Decrypt K X) = discrim X - 2
apply (cases X)
apply (simp add: discrim-def Decrypt
      UN-equiv-class [OF equiv-msgrel discrim-congruent])
done

end

```

3 Quotienting a Free Algebra Involving Nested Recursion

```

theory QuoNestedDataType imports Main begin

```

3.1 Defining the Free Algebra

Messages with encryption and decryption as free constructors.

```

datatype
  freeExp = VAR nat
           | PLUS freeExp freeExp
           | FNCALL nat freeExp list

```


The equivalence relation, which makes PLUS associative.

```

consts  exprel :: (freeExp * freeExp) set

syntax
  -exprel :: [freeExp, freeExp] => bool  (infixl ~~ 50)
syntax (xsymbols)
  -exprel :: [freeExp, freeExp] => bool  (infixl ~ 50)
syntax (HTML output)
  -exprel :: [freeExp, freeExp] => bool  (infixl ~ 50)
translations
  X ~ Y == (X,Y) ∈ exprel

```

The first rule is the desired equation. The next three rules make the equations applicable to subterms. The last two rules are symmetry and transitivity.

```

inductive exprel
intros
  ASSOC: PLUS X (PLUS Y Z) ~ PLUS (PLUS X Y) Z
  VAR: VAR N ~ VAR N
  PLUS:  $\llbracket X \sim X'; Y \sim Y' \rrbracket \implies PLUS\ X\ Y \sim PLUS\ X'\ Y'$ 
  FNCALL:  $(Xs, Xs') \in listrel\ exprel \implies FNCALL\ F\ Xs \sim FNCALL\ F\ Xs'$ 
  SYM:  $X \sim Y \implies Y \sim X$ 
  TRANS:  $\llbracket X \sim Y; Y \sim Z \rrbracket \implies X \sim Z$ 
monos listrel-mono

```

Proving that it is an equivalence relation

```

lemma exprel-refl-conj:  $X \sim X \ \& \ (Xs, Xs') \in listrel\ (exprel)$ 
apply (induct X and Xs)
apply (blast intro: exprel.intros listrel.intros)+
done

```

```

lemmas exprel-refl = exprel-refl-conj [THEN conjunct1]
lemmas list-exprel-refl = exprel-refl-conj [THEN conjunct2]

```

```

theorem equiv-exprel: equiv UNIV exprel
proof (simp add: equiv-def, intro conjI)
  show reflexive exprel by (simp add: refl-def exprel-refl)
  show sym exprel by (simp add: sym-def, blast intro: exprel.SYM)
  show trans exprel by (simp add: trans-def, blast intro: exprel.TRANS)
qed

```

```

theorem equiv-list-exprel: equiv UNIV (listrel exprel)
by (insert equiv-listrel [OF equiv-exprel], simp)

```

```

lemma FNCALL-Nil:  $FNCALL\ F\ [] \sim FNCALL\ F\ []$ 
apply (rule exprel.intros)
apply (rule listrel.intros)

```

done

lemma *FNCALL-Cons*:

$$\begin{aligned} & \llbracket X \sim X'; (Xs, Xs') \in \text{listrel}(\text{exprel}) \rrbracket \\ & \implies \text{FNCALL } F (X \# Xs) \sim \text{FNCALL } F (X' \# Xs') \end{aligned}$$

by (*blast intro: exprel.intros listrel.intros*)

3.2 Some Functions on the Free Algebra

3.2.1 The Set of Variables

A function to return the set of variables present in a message. It will be lifted to the initial algebra, to serve as an example of that process. Note that the "free" refers to the free datatype rather than to the concept of a free variable.

consts

freevars :: *freeExp* \Rightarrow *nat set*
freevars-list :: *freeExp list* \Rightarrow *nat set*

primrec

freevars (*VAR* *N*) = {*N*}
freevars (*PLUS* *X* *Y*) = *freevars* *X* \cup *freevars* *Y*
freevars (*FNCALL* *F* *Xs*) = *freevars-list* *Xs*

freevars-list [] = {}
freevars-list (*X* # *Xs*) = *freevars* *X* \cup *freevars-list* *Xs*

This theorem lets us prove that the vars function respects the equivalence relation. It also helps us prove that Variable (the abstract constructor) is injective

theorem *exprel-imp-eq-freevars*: $U \sim V \implies \text{freevars } U = \text{freevars } V$

apply (*erule exprel.induct*)

apply (*erule-tac* [4] *listrel.induct*)

apply (*simp-all add: Un-assoc*)

done

3.2.2 Functions for Freeness

A discriminator function to distinguish vars, sums and function calls

consts *freediscrim* :: *freeExp* \Rightarrow *int*

primrec

freediscrim (*VAR* *N*) = 0
freediscrim (*PLUS* *X* *Y*) = 1
freediscrim (*FNCALL* *F* *Xs*) = 2

theorem *exprel-imp-eq-freediscrim*:

$$U \sim V \implies \text{freediscrim } U = \text{freediscrim } V$$

by (*erule exprel.induct, auto*)

This function, which returns the function name, is used to prove part of the injectivity property for FnCall.

consts *freefun* :: *freeExp* \Rightarrow *nat*

primrec

freefun (*VAR* *N*) = 0
freefun (*PLUS* *X* *Y*) = 0
freefun (*FNCALL* *F* *Xs*) = *F*

theorem *exprel-imp-eq-freefun*:

$U \sim V \implies \text{freefun } U = \text{freefun } V$

by (*erule* *exprel.induct*, *simp-all* *add: listrel.intros*)

This function, which returns the list of function arguments, is used to prove part of the injectivity property for FnCall.

consts *freeargs* :: *freeExp* \Rightarrow *freeExp* *list*

primrec

freeargs (*VAR* *N*) = []
freeargs (*PLUS* *X* *Y*) = []
freeargs (*FNCALL* *F* *Xs*) = *Xs*

theorem *exprel-imp-eqv-freeargs*:

$U \sim V \implies (\text{freeargs } U, \text{freeargs } V) \in \text{listrel } \text{exprel}$

apply (*erule* *exprel.induct*)

apply (*erule-tac* [4] *listrel.induct*)

apply (*simp-all* *add: listrel.intros*)

apply (*blast* *intro: symD* [*OF* *equiv.sym* [*OF* *equiv-list-exprel*]])

apply (*blast* *intro: transD* [*OF* *equiv.trans* [*OF* *equiv-list-exprel*]])

done

3.3 The Initial Algebra: A Quotiented Message Type

typedef (*Exp*) *exp* = *UNIV* // *exprel*

by (*auto* *simp* *add: quotient-def*)

The abstract message constructors

constdefs

Var :: *nat* \Rightarrow *exp*

Var *N* == *Abs-Exp*(*exprel* “ { *VAR* *N* })

Plus :: [*exp*, *exp*] \Rightarrow *exp*

Plus *X* *Y* ==

Abs-Exp ($\bigcup U \in \text{Rep-Exp } X. \bigcup V \in \text{Rep-Exp } Y. \text{exprel} “ \{ \text{PLUS } U \ V \}$)

Fncall :: [*nat*, *exp* *list*] \Rightarrow *exp*

Fncall *F* *Xs* ==

Abs-Exp ($\bigcup Us \in \text{listset } (\text{map } \text{Rep-Exp } Xs). \text{exprel} “ \{ \text{FNCALL } F \ Us \}$)

Reduces equality of equivalence classes to the *exprel* relation: (*exprel* “ {*x*} = *exprel* “ {*y*}) = (*x* ~ *y*)

lemmas *equiv-exprel-iff* = *eq-equiv-class-iff* [*OF equiv-exprel UNIV-I UNIV-I*]

declare *equiv-exprel-iff* [*simp*]

All equivalence classes belong to set of representatives

lemma [*simp*]: *exprel*“{*U*} ∈ *Exp*

by (*auto simp add: Exp-def quotient-def intro: exprel-refl*)

lemma *inj-on-Abs-Exp*: *inj-on Abs-Exp Exp*

apply (*rule inj-on-inverseI*)

apply (*erule Abs-Exp-inverse*)

done

Reduces equality on abstractions to equality on representatives

declare *inj-on-Abs-Exp* [*THEN inj-on-iff, simp*]

declare *Abs-Exp-inverse* [*simp*]

Case analysis on the representation of a exp as an equivalence class.

lemma *eq-Abs-Exp* [*case-names Abs-Exp, cases type: exp*]:

(!!*U. z = Abs-Exp*(*exprel*“{*U*}) ==> *P*) ==> *P*

apply (*rule Rep-Exp [of z, unfolded Exp-def, THEN quotientE]*)

apply (*erule arg-cong [where f=Abs-Exp]*)

apply (*auto simp add: Rep-Exp-inverse intro: exprel-refl*)

done

3.4 Every list of abstract expressions can be expressed in terms of a list of concrete expressions

constdefs *Abs-ExpList* :: *freeExp list* => *exp list*

Abs-ExpList *Xs* == *map* (%*U. Abs-Exp*(*exprel*“{*U*})) *Xs*

lemma *Abs-ExpList-Nil* [*simp*]: *Abs-ExpList* [] == []

by (*simp add: Abs-ExpList-def*)

lemma *Abs-ExpList-Cons* [*simp*]:

Abs-ExpList (*X* # *Xs*) == *Abs-Exp* (*exprel*“{*X*}) # *Abs-ExpList* *Xs*

by (*simp add: Abs-ExpList-def*)

lemma *ExpList-rep*: ∃ *Us. z = Abs-ExpList Us*

apply (*induct z*)

apply (*rule-tac [2] z=a in eq-Abs-Exp*)

apply (*auto simp add: Abs-ExpList-def intro: exprel-refl*)

done

lemma *eq-Abs-ExpList* [*case-names Abs-ExpList*]:

(!! $Us. z = \text{Abs-ExpList } Us ==> P$) ==> P
by (rule $\text{exE [OF ExpList-rep], blast}$)

3.4.1 Characteristic Equations for the Abstract Constructors

lemma $\text{Plus: Plus (Abs-Exp (exprel "{U}")) (Abs-Exp (exprel "{V}")) =}$
 $\text{Abs-Exp (exprel "{PLUS U V})}$

proof –
have ($\lambda U V. \text{exprel "{ PLUS U V}"}$ respects2 exprel)
by (simp add: congruent2-def exprel.PLUS)
thus ?thesis
by (simp add: Plus-def UN-equiv-class2 [OF equiv-exprel equiv-exprel])
qed

It is not clear what to do with FnCall : it's argument is an abstraction of an exp list . Is it just Nil or Cons ? What seems to work best is to regard an exp list as a listrel exprel equivalence class

This theorem is easily proved but never used. There's no obvious way even to state the analogous result, FnCall-Cons .

lemma $\text{FnCall-Nil: FnCall F [] = Abs-Exp (exprel "{FNCALL F []})}$
by (simp add: FnCall-def)

lemma FnCall-respects:
 $(\lambda Us. \text{exprel "{ FNCALL F Us}"})$ respects (listrel exprel)
by (simp add: congruent-def exprel.FNCALL)

lemma FnCall-sing:
 $\text{FnCall F [Abs-Exp (exprel "{U}")] = Abs-Exp (exprel "{FNCALL F [U]})}$
proof –
have ($\lambda U. \text{exprel "{ FNCALL F [U]"}$) respects exprel
by (simp add: congruent-def $\text{FNCALL-Cons listrel.intros}$)
thus ?thesis
by (simp add: $\text{FnCall-def UN-equiv-class [OF equiv-exprel]}$)
qed

lemma $\text{listset-Rep-Exp-Abs-Exp:}$
 $\text{listset (map Rep-Exp (Abs-ExpList Us)) = listrel exprel "{ Us}"}$
by (induct-tac Us , simp-all add: $\text{listrel-Cons Abs-ExpList-def}$)

lemma FnCall:
 $\text{FnCall F (Abs-ExpList Us) = Abs-Exp (exprel "{FNCALL F Us}"})$
proof –
have ($\lambda Us. \text{exprel "{ FNCALL F Us}"}$) respects (listrel exprel)
by (simp add: congruent-def exprel.FNCALL)
thus ?thesis
by (simp add: $\text{FnCall-def UN-equiv-class [OF equiv-list-exprel]}$
 $\text{listset-Rep-Exp-Abs-Exp}$)
qed

Establishing this equation is the point of the whole exercise

theorem *Plus-assoc*: $Plus\ X\ (Plus\ Y\ Z) = Plus\ (Plus\ X\ Y)\ Z$
by (*cases* X , *cases* Y , *cases* Z , *simp* *add*: $Plus\ exprel.ASSOC$)

3.5 The Abstract Function to Return the Set of Variables

constdefs

$vars :: exp \Rightarrow nat\ set$
 $vars\ X == \bigcup U \in Rep-Exp\ X. freevars\ U$

lemma *vars-respects*: $freevars\ respects\ exprel$
by (*simp* *add*: *congruent-def exprel-imp-eq-freevars*)

The extension of the function *vars* to lists

consts *vars-list* :: $exp\ list \Rightarrow nat\ set$

primrec

$vars-list\ [] = \{\}$
 $vars-list\ (E\ \# Es) = vars\ E \cup vars-list\ Es$

Now prove the three equations for *vars*

lemma *vars-Variable* [*simp*]: $vars\ (Var\ N) = \{N\}$
by (*simp* *add*: *vars-def Var-def*
 $UN-equiv-class\ [OF\ equiv-exprel\ vars-respects]$)

lemma *vars-Plus* [*simp*]: $vars\ (Plus\ X\ Y) = vars\ X \cup vars\ Y$
apply (*cases* X , *cases* Y)
apply (*simp* *add*: *vars-def Plus*
 $UN-equiv-class\ [OF\ equiv-exprel\ vars-respects]$)
done

lemma *vars-FnCall* [*simp*]: $vars\ (FnCall\ F\ Xs) = vars-list\ Xs$
apply (*cases* Xs *rule*: *eq-Abs-ExpList*)
apply (*simp* *add*: *FnCall*)
apply (*induct-tac* Us)
apply (*simp-all* *add*: *vars-def UN-equiv-class* [*OF* *equiv-exprel vars-respects*])
done

lemma *vars-FnCall-Nil*: $vars\ (FnCall\ F\ Nil) = \{\}$
by *simp*

lemma *vars-FnCall-Cons*: $vars\ (FnCall\ F\ (X\ \# Xs)) = vars\ X \cup vars-list\ Xs$
by *simp*

3.6 Injectivity Properties of Some Constructors

lemma *VAR-imp-eq*: $VAR\ m \sim VAR\ n \implies m = n$
by (*drule* *exprel-imp-eq-freevars*, *simp*)

Can also be proved using the function *vars*

lemma *Var-Var-eq* [iff]: (Var m = Var n) = (m = n)
by (auto simp add: Var-def exprel-refl dest: VAR-imp-eq)

lemma *VAR-neqv-PLUS*: VAR $m \sim PLUS X Y \implies False$
by (drule exprel-imp-eq-freediscrim, simp)

theorem *Var-neq-Plus* [iff]: Var $N \neq Plus X Y$
apply (cases X , cases Y)
apply (simp add: Var-def Plus)
apply (blast dest: VAR-neqv-PLUS)
done

theorem *Var-neq-FnCall* [iff]: Var $N \neq FnCall F Xs$
apply (cases Xs rule: eq-Abs-ExpList)
apply (auto simp add: FnCall Var-def)
apply (drule exprel-imp-eq-freediscrim, simp)
done

3.7 Injectivity of *FnCall*

constdefs
 $fun :: exp \Rightarrow nat$
 $fun X == contents (\bigcup U \in Rep-Exp X. \{freefun U\})$

lemma *fun-respects*: (% $U. \{freefun U\}$) respects exprel
by (simp add: congruent-def exprel-imp-eq-freefun)

lemma *fun-FnCall* [simp]: fun (FnCall $F Xs$) = F
apply (cases Xs rule: eq-Abs-ExpList)
apply (simp add: FnCall fun-def UN-equiv-class [OF equiv-exprel fun-respects])
done

constdefs
 $args :: exp \Rightarrow exp list$
 $args X == contents (\bigcup U \in Rep-Exp X. \{Abs-ExpList (freeargs U)\})$

This result can probably be generalized to arbitrary equivalence relations, but with little benefit here.

lemma *Abs-ExpList-eq*:
 $(y, z) \in listrel exprel \implies Abs-ExpList (y) = Abs-ExpList (z)$
by (erule listrel.induct, simp-all)

lemma *args-respects*: (% $U. \{Abs-ExpList (freeargs U)\}$) respects exprel
by (simp add: congruent-def Abs-ExpList-eq exprel-imp-eqv-freeargs)

lemma *args-FnCall* [simp]: args (FnCall $F Xs$) = Xs
apply (cases Xs rule: eq-Abs-ExpList)
apply (simp add: FnCall args-def UN-equiv-class [OF equiv-exprel args-respects])
done

```

lemma FnCall-FnCall-eq [iff]:
  (FnCall F Xs = FnCall F' Xs') = (F=F' & Xs=Xs')
proof
  assume FnCall F Xs = FnCall F' Xs'
  hence fun (FnCall F Xs) = fun (FnCall F' Xs')
  and args (FnCall F Xs) = args (FnCall F' Xs') by auto
  thus F=F' & Xs=Xs' by simp
next
  assume F=F' & Xs=Xs' thus FnCall F Xs = FnCall F' Xs' by simp
qed

```

3.8 The Abstract Discriminator

However, as *FnCall-Var-neq-Var* illustrates, we don't need this function in order to prove discrimination theorems.

```

constdefs
  discrim :: exp  $\Rightarrow$  int
  discrim X == contents ( $\bigcup U \in \text{Rep-Exp } X. \{\text{freediscrim } U\}$ )

```

```

lemma discrim-respects: ( $\lambda U. \{\text{freediscrim } U\}$ ) respects exprel
by (simp add: congruent-def exprel-imp-eq-freediscrim)

```

Now prove the four equations for *discrim*

```

lemma discrim-Var [simp]: discrim (Var N) = 0
by (simp add: discrim-def Var-def
  UN-equiv-class [OF equiv-exprel discrim-respects])

```

```

lemma discrim-Plus [simp]: discrim (Plus X Y) = 1
apply (cases X, cases Y)
apply (simp add: discrim-def Plus
  UN-equiv-class [OF equiv-exprel discrim-respects])
done

```

```

lemma discrim-FnCall [simp]: discrim (FnCall F Xs) = 2
apply (rule-tac z=Xs in eq-Abs-ExpList)
apply (simp add: discrim-def FnCall
  UN-equiv-class [OF equiv-exprel discrim-respects])
done

```

The structural induction rule for the abstract type

```

theorem exp-induct:
  assumes V:  $\bigwedge \text{nat}. P1 \text{ (Var nat)}$ 
  and P:  $\bigwedge \text{exp1 exp2}. \llbracket P1 \text{ exp1}; P1 \text{ exp2} \rrbracket \Longrightarrow P1 \text{ (Plus exp1 exp2)}$ 
  and F:  $\bigwedge \text{nat list}. P2 \text{ list} \Longrightarrow P1 \text{ (FnCall nat list)}$ 
  and Nil:  $P2 []$ 
  and Cons:  $\bigwedge \text{exp list}. \llbracket P1 \text{ exp}; P2 \text{ list} \rrbracket \Longrightarrow P2 \text{ (exp \# list)}$ 

```



```

  shows  $P1\ exp \ \& \ P2\ list$ 
proof (cases exp, rule eq-Abs-ExpList [of list], clarify)
  fix U Us
  show  $P1\ (Abs-Exp\ (exprel\ \{\ U\})) \wedge$ 
        $P2\ (Abs-ExpList\ Us)$ 
proof (induct U and Us)
  case (VAR nat)
  with V show ?case by (simp add: Var-def)
next
  case (PLUS X Y)
  with P [of Abs-Exp (exprel “ {X}”) Abs-Exp (exprel “ {Y}”)]
  show ?case by (simp add: Plus)
next
  case (FNCALL nat list)
  with F [of Abs-ExpList list]
  show ?case by (simp add: FnCall)
next
  case Nil-freeExp
  with Nil show ?case by simp
next
  case Cons-freeExp
  with Cons
  show ?case by simp
qed
qed
end

```

4 Terms over a given alphabet

theory *Term* **imports** *Main* **begin**

```

datatype ('a, 'b) term =
  Var 'a
| App 'b ('a, 'b) term list

```

Substitution function on terms

```

consts
  subst-term :: ('a => ('a, 'b) term) => ('a, 'b) term => ('a, 'b) term
  subst-term-list ::
    ('a => ('a, 'b) term) => ('a, 'b) term list => ('a, 'b) term list

```

```

primrec
  subst-term f (Var a) = f a
  subst-term f (App b ts) = App b (subst-term-list f ts)

```

```

subst-term-list f [] = []
subst-term-list f (t # ts) =
  subst-term f t # subst-term-list f ts

```

A simple theorem about composition of substitutions

```

lemma subst-comp:
  subst-term (subst-term f1 ∘ f2) t =
    subst-term f1 (subst-term f2 t)
and subst-term-list (subst-term f1 ∘ f2) ts =
  subst-term-list f1 (subst-term-list f2 ts)
by (induct t and ts) simp-all

```

Alternative induction rule

```

lemma
  assumes var: !!v. P (Var v)
  and app: !!f ts. list-all P ts ==> P (App f ts)
  shows term-induct2: P t
and list-all P ts
  apply (induct t and ts)
  apply (rule var)
  apply (rule app)
  apply assumption
  apply simp-all
done

end

```

5 Arithmetic and boolean expressions

```

theory ABExp imports Main begin

```

```

datatype 'a aexp =
  IF 'a bexp 'a aexp 'a aexp
| Sum 'a aexp 'a aexp
| Diff 'a aexp 'a aexp
| Var 'a
| Num nat
and 'a bexp =
  Less 'a aexp 'a aexp
| And 'a bexp 'a bexp
| Neg 'a bexp

```

Evaluation of arithmetic and boolean expressions

```

consts
  evala :: ('a => nat) => 'a aexp => nat
  evalb :: ('a => nat) => 'a bexp => bool

```

primrec

$evala\ env\ (IF\ b\ a1\ a2) = (if\ evalb\ env\ b\ then\ evala\ env\ a1\ else\ evala\ env\ a2)$
 $evala\ env\ (Sum\ a1\ a2) = evala\ env\ a1 + evala\ env\ a2$
 $evala\ env\ (Diff\ a1\ a2) = evala\ env\ a1 - evala\ env\ a2$
 $evala\ env\ (Var\ v) = env\ v$
 $evala\ env\ (Num\ n) = n$

 $evalb\ env\ (Less\ a1\ a2) = (evala\ env\ a1 < evala\ env\ a2)$
 $evalb\ env\ (And\ b1\ b2) = (evalb\ env\ b1 \wedge evalb\ env\ b2)$
 $evalb\ env\ (Neg\ b) = (\neg evalb\ env\ b)$

Substitution on arithmetic and boolean expressions

consts

$subst :: ('a \Rightarrow 'b\ aexp) \Rightarrow 'a\ aexp \Rightarrow 'b\ aexp$
 $substb :: ('a \Rightarrow 'b\ aexp) \Rightarrow 'a\ bexp \Rightarrow 'b\ bexp$

primrec

$subst\ f\ (IF\ b\ a1\ a2) = IF\ (substb\ f\ b)\ (subst\ f\ a1)\ (subst\ f\ a2)$
 $subst\ f\ (Sum\ a1\ a2) = Sum\ (subst\ f\ a1)\ (subst\ f\ a2)$
 $subst\ f\ (Diff\ a1\ a2) = Diff\ (subst\ f\ a1)\ (subst\ f\ a2)$
 $subst\ f\ (Var\ v) = f\ v$
 $subst\ f\ (Num\ n) = Num\ n$

 $substb\ f\ (Less\ a1\ a2) = Less\ (subst\ f\ a1)\ (subst\ f\ a2)$
 $substb\ f\ (And\ b1\ b2) = And\ (substb\ f\ b1)\ (substb\ f\ b2)$
 $substb\ f\ (Neg\ b) = Neg\ (substb\ f\ b)$

lemma subst1-aexp:

$evala\ env\ (subst\ (Var\ (v := a'))\ a) = evala\ (env\ (v := evala\ env\ a'))\ a$

and subst1-bexp:

$evalb\ env\ (substb\ (Var\ (v := a'))\ b) = evalb\ (env\ (v := evala\ env\ a'))\ b$
— one variable
by (induct a **and** b) simp-all

lemma subst-all-aexp:

$evala\ env\ (subst\ s\ a) = evala\ (\lambda x. evala\ env\ (s\ x))\ a$

and subst-all-bexp:

$evalb\ env\ (substb\ s\ b) = evalb\ (\lambda x. evala\ env\ (s\ x))\ b$
by (induct a **and** b) auto

end

6 Infinitely branching trees

theory Tree **imports** Main **begin**

```

datatype 'a tree =
  Atom 'a
  | Branch nat => 'a tree

consts
  map-tree :: ('a => 'b) => 'a tree => 'b tree
primrec
  map-tree f (Atom a) = Atom (f a)
  map-tree f (Branch ts) = Branch ( $\lambda x.$  map-tree f (ts x))

lemma tree-map-compose: map-tree g (map-tree f t) = map-tree (g  $\circ$  f) t
by (induct t) simp-all

consts
  exists-tree :: ('a => bool) => 'a tree => bool
primrec
  exists-tree P (Atom a) = P a
  exists-tree P (Branch ts) = ( $\exists x.$  exists-tree P (ts x))

lemma exists-map:
  ( $\llbracket x.$  P x  $\impl$  Q (f x))  $\impl$ 
  exists-tree P ts  $\impl$  exists-tree Q (map-tree f ts)
by (induct ts) auto

```

6.1 The Brouwer ordinals, as in ZF/Induct/Brouwer.thy.

```

datatype brouwer = Zero | Succ brouwer | Lim nat => brouwer

```

Addition of ordinals

```

consts
  add :: [brouwer, brouwer] => brouwer
primrec
  add i Zero = i
  add i (Succ j) = Succ (add i j)
  add i (Lim f) = Lim ( $\%n.$  add i (f n))

lemma add-assoc: add (add i j) k = add i (add j k)
by (induct k, auto)

```

Multiplication of ordinals

```

consts
  mult :: [brouwer, brouwer] => brouwer
primrec
  mult i Zero = Zero
  mult i (Succ j) = add (mult i j) i
  mult i (Lim f) = Lim ( $\%n.$  mult i (f n))

lemma add-mult-distrib: mult i (add j k) = add (mult i j) (mult i k)
apply (induct k)

```

```

apply (auto simp add: add-assoc)
done

```

```

lemma mult-assoc: mult (mult i j) k = mult i (mult j k)
apply (induct k)
apply (auto simp add: add-mult-distrib)
done

```

We could probably instantiate some axiomatic type classes and use the standard infix operators.

6.2 A WF Ordering for The Brouwer ordinals (Michael Comp-ton)

To define recdef style functions we need an ordering on the Brouwer ordinals. Start with a predecessor relation and form its transitive closure.

```

constdefs
  brouwer-pred :: (brouwer * brouwer) set
  brouwer-pred ==  $\bigcup i. \{(m,n). n = \text{Succ } m \vee (\exists f. n = \text{Lim } f \ \& \ m = f \ i)\}$ 

  brouwer-order :: (brouwer * brouwer) set
  brouwer-order == brouwer-pred+

lemma wf-brouwer-pred: wf brouwer-pred
  by (unfold wf-def brouwer-pred-def, clarify, induct-tac x, blast+)

lemma wf-brouwer-order: wf brouwer-order
  by (unfold brouwer-order-def, rule wf-trancl[OF wf-brouwer-pred])

lemma [simp]: (j, Succ j) : brouwer-order
  by (auto simp add: brouwer-order-def brouwer-pred-def)

lemma [simp]: (f n, Lim f) : brouwer-order
  by (auto simp add: brouwer-order-def brouwer-pred-def)

```

Example of a recdef

```

consts
  add2 :: (brouwer*brouwer) => brouwer
recdef add2 inv-image brouwer-order ( $\lambda (x,y). y$ )
  add2 (i, Zero) = i
  add2 (i, (Succ j)) = Succ (add2 (i, j))
  add2 (i, (Lim f)) = Lim ( $\lambda n. \text{add2 } (i, (f \ n))$ )
  (hints recdef-wf: wf-brouwer-order)

lemma add2-assoc: add2 (add2 (i, j), k) = add2 (i, add2 (j, k))
by (induct k, auto)

```

end

7 Ordinals

theory *Ordinals* **imports** *Main* **begin**

Some basic definitions of ordinal numbers. Draws an Agda development (in Martin-Löf type theory) by Peter Hancock (see <http://www.dcs.ed.ac.uk/home/pgh/chat.html>).

datatype *ordinal* =
 Zero
 | *Succ ordinal*
 | *Limit nat => ordinal*

consts

pred :: *ordinal* => *nat* => *ordinal option*

primrec

pred Zero n = *None*
pred (Succ a) n = *Some a*
pred (Limit f) n = *Some (f n)*

consts

iter :: (*'a* => *'a*) => *nat* => (*'a* => *'a*)

primrec

iter f 0 = *id*
iter f (Suc n) = *f* \circ (*iter f n*)

constdefs

OpLim :: (*nat* => (*ordinal* => *ordinal*)) => (*ordinal* => *ordinal*)
OpLim F a == *Limit* ($\lambda n.$ *F n a*)
OpItw :: (*ordinal* => *ordinal*) => (*ordinal* => *ordinal*) (\sqcup)
 $\sqcup f$ == *OpLim* (*iter f*)

consts

cantor :: *ordinal* => *ordinal* => *ordinal*

primrec

cantor a Zero = *Succ a*
cantor a (Succ b) = $\sqcup (\lambda x.$ *cantor x b*) *a*
cantor a (Limit f) = *Limit* ($\lambda n.$ *cantor a (f n)*)

consts

Nabla :: (*ordinal* => *ordinal*) => (*ordinal* => *ordinal*) (∇)

primrec

∇f *Zero* = *f Zero*
 ∇f (*Succ a*) = *f* (*Succ* (∇f *a*))
 ∇f (*Limit h*) = *Limit* ($\lambda n.$ ∇f (*h n*))

```

constdefs
  deriv :: (ordinal => ordinal) => (ordinal => ordinal)
  deriv f ==  $\nabla(\bigsqcup f)$ 

consts
  veblen :: ordinal => ordinal => ordinal

primrec
  veblen Zero =  $\nabla(\text{OpLim } (\text{iter } (\text{cantor } \text{Zero})))$ 
  veblen (Succ a) =  $\nabla(\text{OpLim } (\text{iter } (\text{veblen } a)))$ 
  veblen (Limit f) =  $\nabla(\text{OpLim } (\lambda n. \text{veblen } (f\ n)))$ 

constdefs
  veb a == veblen a Zero
   $\varepsilon_0$  == veb Zero
   $\Gamma_0$  == Limit ( $\lambda n. \text{iter } \text{veb } n \text{ Zero}$ )

end

```

8 Sigma algebras

theory *Sigma-Algebra* **imports** *Main* **begin**

This is just a tiny example demonstrating the use of inductive definitions in classical mathematics. We define the least σ -algebra over a given set of sets.

```

consts
   $\sigma\text{-algebra} :: 'a \text{ set set} \Rightarrow 'a \text{ set set}$ 

inductive  $\sigma\text{-algebra } A$ 
  intros
    basic:  $a \in A \Rightarrow a \in \sigma\text{-algebra } A$ 
    UNIV:  $\text{UNIV} \in \sigma\text{-algebra } A$ 
    complement:  $a \in \sigma\text{-algebra } A \Rightarrow -a \in \sigma\text{-algebra } A$ 
    Union:  $(!!i::\text{nat}. a\ i \in \sigma\text{-algebra } A) \Rightarrow (\bigcup i. a\ i) \in \sigma\text{-algebra } A$ 

```

The following basic facts are consequences of the closure properties of any σ -algebra, merely using the introduction rules, but no induction nor cases.

```

theorem sigma-algebra-empty:  $\{\} \in \sigma\text{-algebra } A$ 
proof –
  have  $\text{UNIV} \in \sigma\text{-algebra } A$  by (rule  $\sigma\text{-algebra.UNIV}$ )
  hence  $-\text{UNIV} \in \sigma\text{-algebra } A$  by (rule  $\sigma\text{-algebra.complement}$ )
  also have  $-\text{UNIV} = \{\}$  by simp
  finally show ?thesis .
qed

```

```

theorem sigma-algebra-Inter:
   $(!!i::\text{nat}. a\ i \in \sigma\text{-algebra } A) \Rightarrow (\bigcap i. a\ i) \in \sigma\text{-algebra } A$ 
proof –

```

```

assume !!i::nat. a i ∈  $\sigma$ -algebra A
hence !!i::nat.  $\neg(a\ i) \in \sigma$ -algebra A by (rule  $\sigma$ -algebra.complement)
hence  $(\bigcup i. \neg(a\ i)) \in \sigma$ -algebra A by (rule  $\sigma$ -algebra.Union)
hence  $\neg(\bigcup i. \neg(a\ i)) \in \sigma$ -algebra A by (rule  $\sigma$ -algebra.complement)
also have  $\neg(\bigcup i. \neg(a\ i)) = (\bigcap i. a\ i)$  by simp
finally show ?thesis .
qed

end

```

9 Combinatory Logic example: the Church-Rosser Theorem

theory Comb **imports** Main **begin**

Curiously, combinators do not include free variables.

Example taken from [?].

HOL system proofs may be found in the HOL distribution at .../contrib/rule-induction/cl.ml

9.1 Definitions

Datatype definition of combinators S and K .

```

datatype comb = K
                | S
                | ## comb comb (infixl 90)

```

Inductive definition of contractions, $-1->$ and (multi-step) reductions, $---->$.

```

consts
  contract :: (comb*comb) set
  -1->     :: [comb,comb] => bool   (infixl 50)
  ---->    :: [comb,comb] => bool   (infixl 50)

```

translations

```

  x -1-> y == (x,y) ∈ contract
  x ----> y == (x,y) ∈ contract^*

```

syntax (xsymbols)

```

  op ## :: [comb,comb] => comb   (infixl . 90)

```

inductive contract

intros

```

  K:    K ## x ## y -1-> x
  S:    S ## x ## y ## z -1-> (x ## z) ## (y ## z)

```


$Ap1: x-1->y ==> x\#\#z-1->y\#\#z$
 $Ap2: x-1->y ==> z\#\#x-1->z\#\#y$

Inductive definition of parallel contractions, $=1=>$ and (multi-step) parallel reductions, $===>$.

consts

$parcontract :: (comb*comb) \text{ set}$
 $=1=> :: [comb,comb] ==> bool \quad (\text{infixl } 50)$
 $===> :: [comb,comb] ==> bool \quad (\text{infixl } 50)$

translations

$x =1=> y == (x,y) \in parcontract$
 $x ===> y == (x,y) \in parcontract^*$

inductive parcontract

intros

$refl: x =1=> x$
 $K: K\#\#x\#\#y =1=> x$
 $S: S\#\#x\#\#y\#\#z =1=> (x\#\#z)\#\#(y\#\#z)$
 $Ap: [| x=1=>y; z=1=>w |] ==> x\#\#z =1=> y\#\#w$

Misc definitions.

constdefs

$I :: comb$
 $I == S\#\#K\#\#K$

$diamond :: ('a * 'a) \text{ set} ==> bool$
 — confluence; Lambda/Commutation treats this more abstractly
 $diamond(r) == \forall x y. (x,y) \in r \dashrightarrow$
 $(\forall y'. (x,y') \in r \dashrightarrow$
 $(\exists z. (y',z) \in r \ \& \ (y,z) \in r))$

9.2 Reflexive/Transitive closure preserves Church-Rosser property

So does the Transitive closure, with a similar proof

Strip lemma. The induction hypothesis covers all but the last diamond of the strip.

lemma *diamond-strip-lemmaE* [rule-format]:

$[| diamond(r); (x,y) \in r^* |] ==>$
 $\forall y'. (x,y') \in r \dashrightarrow (\exists z. (y',z) \in r^* \ \& \ (y,z) \in r)$

apply (*unfold diamond-def*)

apply (*erule rtranc1-induct*)

apply (*meson rtranc1-refl*)

apply (*meson rtranc1-trans r-into-rtranc1*)

done

```

lemma diamond-rtrancl: diamond(r) ==> diamond(r^*)
apply (simp (no-asm-simp) add: diamond-def)
apply (rule impI [THEN allI, THEN allI])
apply (erule rtrancl-induct, blast)
apply (meson rtrancl-trans r-into-rtrancl diamond-strip-lemmaE)
done

```

9.3 Non-contraction results

Derive a case for each combinator constructor.

inductive-cases

```

      K-contractE [elim!]: K -1-> r
    and S-contractE [elim!]: S -1-> r
    and Ap-contractE [elim!]: p##q -1-> r

```

```

declare contract.K [intro!] contract.S [intro!]
declare contract.Ap1 [intro] contract.Ap2 [intro]

```

```

lemma I-contract-E [elim!]: I -1-> z ==> P
by (unfold I-def, blast)

```

```

lemma K1-contractD [elim!]: K##x -1-> z ==> ( $\exists x'. z = K##x' \ \& \ x$ 
-1-> x')
by blast

```

```

lemma Ap-reduce1 [intro]: x ----> y ==> x##z ----> y##z
apply (erule rtrancl-induct)
apply (blast intro: rtrancl-trans)+
done

```

```

lemma Ap-reduce2 [intro]: x ----> y ==> z##x ----> z##y
apply (erule rtrancl-induct)
apply (blast intro: rtrancl-trans)+
done

```

```

lemma KIII-contract1: K##I##(I##I) -1-> I
by (rule contract.K)

```

```

lemma KIII-contract2: K##I##(I##I) -1-> K##I##(K##I)##(K##I)
by (unfold I-def, blast)

```

```

lemma KIII-contract3: K##I##(K##I)##(K##I) -1-> I
by blast

```

```

lemma not-diamond-contract: ~ diamond(contract)
apply (unfold diamond-def)
apply (best intro: KIII-contract1 KIII-contract2 KIII-contract3)

```

done

9.4 Results about Parallel Contraction

Derive a case for each combinator constructor.

inductive-cases

K -parcontractE [elim!]: $K = 1 \Rightarrow r$
 S -parcontractE [elim!]: $S = 1 \Rightarrow r$
 Ap -parcontractE [elim!]: $p \# \# q = 1 \Rightarrow r$

declare parcontract.intros [intro]

9.5 Basic properties of parallel contraction

lemma $K1$ -parcontractD [dest!]: $K \# \# x = 1 \Rightarrow z \Rightarrow (\exists x'. z = K \# \# x' \ \& \ x = 1 \Rightarrow x')$
by blast

lemma $S1$ -parcontractD [dest!]: $S \# \# x = 1 \Rightarrow z \Rightarrow (\exists x'. z = S \# \# x' \ \& \ x = 1 \Rightarrow x')$
by blast

lemma $S2$ -parcontractD [dest!]:
 $S \# \# x \# \# y = 1 \Rightarrow z \Rightarrow (\exists x' y'. z = S \# \# x' \# \# y' \ \& \ x = 1 \Rightarrow x' \ \& \ y = 1 \Rightarrow y')$
by blast

The rules above are not essential but make proofs much faster

Church-Rosser property for parallel contraction

lemma diamond-parcontract: diamond parcontract
apply (unfold diamond-def)
apply (rule impI [THEN allI, THEN allI])
apply (erule parcontract.induct, fast+)
done

Equivalence of $p \dashv\dashv\dashv q$ and $p \Rightarrow \Rightarrow \Rightarrow q$.

lemma contract-subset-parcontract: contract \leq parcontract
apply (rule subsetI)
apply (simp only: split-tupled-all)
apply (erule contract.induct, blast+)
done

Reductions: simply throw together reflexivity, transitivity and the one-step reductions

declare r-into-rtrancl [intro] rtrancl-trans [intro]

```

lemma reduce-I:  $I \# \# x \dashv\dashv \rightarrow x$ 
by (unfold I-def, blast)

lemma parcontract-subset-reduce:  $\text{parcontract} \leq \text{contract}^*$ 
apply (rule subsetI)
apply (simp only: split-tupled-all)
apply (erule parcontract.induct, blast+)
done

lemma reduce-eq-parreduce:  $\text{contract}^* = \text{parcontract}^*$ 
by (rule equalityI contract-subset-parcontract [THEN rtrancl-mono]
      parcontract-subset-reduce [THEN rtrancl-subset-rtrancl])+

lemma diamond-reduce:  $\text{diamond}(\text{contract}^*)$ 
by (simp add: reduce-eq-parreduce diamond-rtrancl diamond-parcontract)

end

```

10 Meta-theory of propositional logic

theory PropLog **imports** Main **begin**

Datatype definition of propositional logic formulae and inductive definition of the propositional tautologies.

Inductive definition of propositional logic. Soundness and completeness w.r.t. truth-tables.

Prove: If $H \models p$ then $G \models p$ where $G \in \text{Fin}(H)$

10.1 The datatype of propositions

datatype

$'a \text{ pl} = \text{false} \mid \text{var } 'a (\#- [1000]) \mid \rightarrow 'a \text{ pl } 'a \text{ pl}$ (**infixr** 90)

10.2 The proof system

consts

$\text{thms} :: 'a \text{ pl set} \Rightarrow 'a \text{ pl set}$
 $\mid - :: ['a \text{ pl set}, 'a \text{ pl}] \Rightarrow \text{bool}$ (**infixl** 50)

translations

$H \mid - p \equiv p \in \text{thms}(H)$

inductive thms(H)

intros

$H \text{ [intro]: } p \in H \Rightarrow H \mid - p$

$K: H \mid - p \rightarrow q \rightarrow p$

$S: H \mid - (p \rightarrow q \rightarrow r) \rightarrow (p \rightarrow q) \rightarrow p \rightarrow r$

DN: $H \mid - ((p \rightarrow \text{false}) \rightarrow \text{false}) \rightarrow p$
MP: $[\mid H \mid - p \rightarrow q; H \mid - p \mid] ==> H \mid - q$

10.3 The semantics

10.3.1 Semantics of propositional logic.

consts

eval :: [*'a set*, *'a pl*] => *bool* (-[[]] [100,0] 100)

primrec *tt*[*false*] = *False*

tt[*#v*] = (*v* ∈ *tt*)

eval-imp: *tt*[*p* → *q*] = (*tt*[*p*] → *tt*[*q*])

A finite set of hypotheses from *t* and the *Vars* in *p*.

consts

hyps :: [*'a pl*, *'a set*] => *'a pl set*

primrec

hyps false *tt* = {}

hyps (*#v*) *tt* = {if *v* ∈ *tt* then *#v* else *#v* → *false*}

hyps (*p* → *q*) *tt* = *hyps p tt* ∪ *hyps q tt*

10.3.2 Logical consequence

For every valuation, if all elements of *H* are true then so is *p*.

constdefs

sat :: [*'a pl set*, *'a pl*] => *bool* (**infixl** | = 50)

H | = *p* == (∀ *tt*. (∀ *q* ∈ *H*. *tt*[*q*]) → *tt*[*p*])

10.4 Proof theory of propositional logic

lemma *thms-mono*: *G* ≤ *H* ==> *thms*(*G*) ≤ *thms*(*H*)

apply (*unfold thms.defs*)

apply (*rule lfp-mono*)

apply (*assumption* | *rule basic-monos*) +

done

lemma *thms-I*: *H* | - *p* → *p*

— Called *I* for Identity Combinator, not for Introduction.

by (*best intro: thms.K thms.S thms.MP*)

10.4.1 Weakening, left and right

lemma *weaken-left*: [*G* ⊆ *H*; *G* | - *p*] ==> *H* | - *p*

— Order of premises is convenient with *THEN*

by (*erule thms-mono* [*THEN subsetD*])

lemmas *weaken-left-insert* = *subset-insertI* [*THEN weaken-left*]

lemmas *weaken-left-Un1* = *Un-upper1* [THEN *weaken-left*]

lemmas *weaken-left-Un2* = *Un-upper2* [THEN *weaken-left*]

lemma *weaken-right*: $H \mid - q \implies H \mid - p \multimap q$

by (*fast intro*: *thms.K thms.MP*)

10.4.2 The deduction theorem

theorem *deduction*: $\text{insert } p \mid - q \implies H \mid - p \multimap q$

apply (*erule thms.induct*)

apply (*fast intro*: *thms-I thms.H thms.K thms.S thms.DN*
thms.S [THEN thms.MP, THEN thms.MP] weaken-right) +

done

10.4.3 The cut rule

lemmas *cut* = *deduction* [THEN *thms.MP*]

lemmas *thms-falseE* = *weaken-right* [THEN *thms.DN* [THEN *thms.MP*]]

lemmas *thms-notE* = *thms.MP* [THEN *thms-falseE*, *standard*]

10.4.4 Soundness of the rules wrt truth-table semantics

theorem *soundness*: $H \mid - p \implies H \models p$

apply (*unfold sat-def*)

apply (*erule thms.induct*, *auto*)

done

10.5 Completeness

10.5.1 Towards the completeness proof

lemma *false-imp*: $H \mid - p \multimap \text{false} \implies H \mid - p \multimap q$

apply (*rule deduction*)

apply (*erule weaken-left-insert* [THEN *thms-notE*])

apply *blast*

done

lemma *imp-false*:

$[[H \mid - p; H \mid - q \multimap \text{false}] \implies H \mid - (p \multimap q) \multimap \text{false}]$

apply (*rule deduction*)

apply (*blast intro*: *weaken-left-insert thms.MP thms.H*)

done

lemma *hyps-thms-if*: $\text{hyps } p \text{ tt} \mid - (\text{if } \text{tt}[[p]] \text{ then } p \text{ else } p \multimap \text{false})$

— Typical example of strengthening the induction statement.

apply *simp*

apply (*induct-tac p*)

```

apply (simp-all add: thms-I thms.H)
apply (blast intro: weaken-left-Un1 weaken-left-Un2 weaken-right
        imp-false false-imp)
done

lemma sat-thms-p:  $\{\} \models p \implies \text{hyps } p \text{ tt} \vdash p$ 
  — Key lemma for completeness; yields a set of assumptions satisfying  $p$ 
apply (unfold sat-def)
apply (drule spec, erule mp [THEN if-P, THEN subst],
        rule-tac [2] hyps-thms-if, simp)
done

```

For proving certain theorems in our new propositional logic.

```

declare deduction [intro!]
declare thms.H [THEN thms.MP, intro]

```

The excluded middle in the form of an elimination rule.

```

lemma thms-excluded-middle:  $H \vdash (p \rightarrow q) \rightarrow ((p \rightarrow \text{false}) \rightarrow q) \rightarrow q$ 
apply (rule deduction [THEN deduction])
apply (rule thms.DN [THEN thms.MP], best)
done

```

```

lemma thms-excluded-middle-rule:
   $[[ \text{insert } p \ H \vdash q; \text{insert } (p \rightarrow \text{false}) \ H \vdash q ]] \implies H \vdash q$ 
  — Hard to prove directly because it requires cuts
by (rule thms-excluded-middle [THEN thms.MP, THEN thms.MP], auto)

```

10.6 Completeness – lemmas for reducing the set of assumptions

For the case $\text{hyps } p \ t - \text{insert } \#v \ Y \vdash p$ we also have $\text{hyps } p \ t - \{\#v\} \subseteq \text{hyps } p \ (t - \{v\})$.

```

lemma hyps-Diff:  $\text{hyps } p \ (t - \{v\}) \leq \text{insert } (\#v \rightarrow \text{false}) \ (\text{hyps } p \ t - \{\#v\})$ 
by (induct-tac p, auto)

```

For the case $\text{hyps } p \ t - \text{insert } (\#v \rightarrow \text{Fls}) \ Y \vdash p$ we also have $\text{hyps } p \ t - \{\#v \rightarrow \text{Fls}\} \subseteq \text{hyps } p \ (\text{insert } v \ t)$.

```

lemma hyps-insert:  $\text{hyps } p \ (\text{insert } v \ t) \leq \text{insert } (\#v) \ (\text{hyps } p \ t - \{\#v \rightarrow \text{false}\})$ 
by (induct-tac p, auto)

```

Two lemmas for use with *weaken-left*

```

lemma insert-Diff-same:  $B - C \leq \text{insert } a \ (B - \text{insert } a \ C)$ 
by fast

```

```

lemma insert-Diff-subset2:  $\text{insert } a \ (B - \{c\}) - D \leq \text{insert } a \ (B - \text{insert } c \ D)$ 
by fast

```

The set $\text{hyps } p \ t$ is finite, and elements have the form $\#v$ or $\#v \rightarrow \text{Fls}$.

lemma *hyps-finite*: *finite(hyps p t)*
by (*induct-tac p, auto*)

lemma *hyps-subset*: *hyps p t <= (UN v. {#v, #v->false})*
by (*induct-tac p, auto*)

lemmas *Diff-weaken-left = Diff-mono [OF - subset-refl, THEN weaken-left]*

10.6.1 Completeness theorem

Induction on the finite set of assumptions *hyps p t0*. We may repeatedly subtract assumptions until none are left!

lemma *completeness-0-lemma*:

$\{\} \models p \implies \forall t. \text{hyps } p \ t - \text{hyps } p \ t0 \vdash p$
apply (*rule hyps-subset [THEN hyps-finite [THEN finite-subset-induct]]*)
apply (*simp add: sat-thms-p, safe*)

Case *hyps p t-insert(#v, Y) ⊢ p*

apply (*iprover intro: thms-excluded-middle-rule*
insert-Diff-same [THEN weaken-left]
insert-Diff-subset2 [THEN weaken-left]
hyps-Diff [THEN Diff-weaken-left])

Case *hyps p t-insert(#v -> false, Y) ⊢ p*

apply (*iprover intro: thms-excluded-middle-rule*
insert-Diff-same [THEN weaken-left]
insert-Diff-subset2 [THEN weaken-left]
hyps-insert [THEN Diff-weaken-left])

done

The base case for completeness

lemma *completeness-0*: $\{\} \models p \implies \{\} \vdash p$
apply (*rule Diff-cancel [THEN subst]*)
apply (*erule completeness-0-lemma [THEN spec]*)
done

A semantic analogue of the Deduction Theorem

lemma *sat-imp*: *insert p H ⊨ q ⟹ H ⊨ p -> q*
by (*unfold sat-def, auto*)

theorem *completeness [rule-format]*: *finite H ⟹ ∀ p. H ⊨ p ⟹ H ⊢ p*
apply (*erule finite-induct*)
apply (*blast intro: completeness-0*)
apply (*iprover intro: sat-imp thms.H insertI1 weaken-left-insert [THEN thms.MP]*)
done

theorem *syntax-iff-semantics*: *finite H ⟹ (H ⊢ p) = (H ⊨ p)*
by (*blast intro: soundness completeness*)

end

theory *Sexp* **imports** *Datatype-Universe Inductive* **begin**

consts

sexp :: 'a item set

inductive *sexp*

intros

LeafI: *Leaf*(*a*) ∈ *sexp*

NumbI: *Numb*(*i*) ∈ *sexp*

SconsI: [| *M* ∈ *sexp*; *N* ∈ *sexp* |] ==> *Scons* *M* *N* ∈ *sexp*

constdefs

sexp-case :: ['a=>'b, nat=>'b, ['a item, 'a item]=>'b,
 'a item] => 'b

sexp-case *c d e M* == *THE* *z*. (*EX* *x*. *M*=*Leaf*(*x*) & *z*=*c*(*x*))
 | (*EX* *k*. *M*=*Numb*(*k*) & *z*=*d*(*k*))
 | (*EX* *N1 N2*. *M* = *Scons* *N1* *N2* & *z*=*e* *N1* *N2*)

pred-sexp :: ('a item * 'a item)set

pred-sexp == $\bigcup M \in \textit{sexp}. \bigcup N \in \textit{sexp}. \{(M, \textit{Scons } M \ N), (N, \textit{Scons } M \ N)\}$

sexp-rec :: ['a item, 'a=>'b, nat=>'b,
 ['a item, 'a item, 'b, 'b]=>'b] => 'b

sexp-rec *M c d e* == *wfrec* *pred-sexp*
 (%*g*. *sexp-case* *c d* (%*N1 N2*. *e* *N1 N2* (*g* *N1*) (*g* *N2*))) *M*

lemma *sexp-case-Leaf* [*simp*]: *sexp-case* *c d e* (*Leaf* *a*) = *c*(*a*)

by (*simp* *add*: *sexp-case-def*, *blast*)

lemma *sexp-case-Numb* [*simp*]: *sexp-case* *c d e* (*Numb* *k*) = *d*(*k*)

by (*simp* *add*: *sexp-case-def*, *blast*)

lemma *sexp-case-Scons* [*simp*]: *sexp-case* *c d e* (*Scons* *M* *N*) = *e* *M* *N*

by (*simp* *add*: *sexp-case-def*)

lemma *sexp-In0I*: *M* ∈ *sexp* ==> *In0*(*M*) ∈ *sexp*

```

apply (simp add: In0-def)
apply (erule sexp.NumbI [THEN sexp.SconsI])
done

```

```

lemma sexp-In1I:  $M \in \text{sexp} \implies \text{In1}(M) \in \text{sexp}$ 
apply (simp add: In1-def)
apply (erule sexp.NumbI [THEN sexp.SconsI])
done

```

```

declare sexp.intros [intro, simp]

```

```

lemma range-Leaf-subset-sexp:  $\text{range}(\text{Leaf}) \leq \text{sexp}$ 
by blast

```

```

lemma Scons-D:  $\text{Scons } M \ N \in \text{sexp} \implies M \in \text{sexp} \ \& \ N \in \text{sexp}$ 
apply (erule setup-induction)
apply (erule sexp.induct, blast+)
done

```

```

lemma pred-sexp-subset-Sigma:  $\text{pred-sexp} \leq \text{sexp} <*> \text{sexp}$ 
by (simp add: pred-sexp-def, blast)

```

```

lemmas trancl-pred-sexpD1 =
  pred-sexp-subset-Sigma
  [THEN trancl-subset-Sigma, THEN subsetD, THEN SigmaD1]
and trancl-pred-sexpD2 =
  pred-sexp-subset-Sigma
  [THEN trancl-subset-Sigma, THEN subsetD, THEN SigmaD2]

```

```

lemma pred-sexpI1:
   $[[ M \in \text{sexp}; \ N \in \text{sexp} ]] \implies (M, \text{Scons } M \ N) \in \text{pred-sexp}$ 
by (simp add: pred-sexp-def, blast)

```

```

lemma pred-sexpI2:
   $[[ M \in \text{sexp}; \ N \in \text{sexp} ]] \implies (N, \text{Scons } M \ N) \in \text{pred-sexp}$ 
by (simp add: pred-sexp-def, blast)

```

```

lemmas pred-sexp-t1 [simp] = pred-sexpI1 [THEN r-into-trancl]
and pred-sexp-t2 [simp] = pred-sexpI2 [THEN r-into-trancl]

```

```

lemmas pred-sexp-trans1 [simp] = trans-trancl [THEN transD, OF - pred-sexp-t1]
and pred-sexp-trans2 [simp] = trans-trancl [THEN transD, OF - pred-sexp-t2]

```

```

declare cut-apply [simp]

```

```

lemma pred-sexpE:
  [|  $p \in \text{pred-sexp}$ ;
    !! $M\ N$ . [|  $p = (M, \text{Scons } M\ N)$ ;  $M \in \text{sexp}$ ;  $N \in \text{sexp}$  |] ==>  $R$ ;
    !! $M\ N$ . [|  $p = (N, \text{Scons } M\ N)$ ;  $M \in \text{sexp}$ ;  $N \in \text{sexp}$  |] ==>  $R$ 
  |] ==>  $R$ 
by (simp add: pred-sexp-def, blast)

lemma wf-pred-sexp:  $\text{wf}(\text{pred-sexp})$ 
apply (rule pred-sexp-subset-Sigma [THEN wfI])
apply (erule sexp.induct)
apply (blast elim!: pred-sexpE)+
done

lemma sexp-rec-unfold-lemma:
  (% $M$ .  $\text{sexp-rec } M\ c\ d\ e$ ) ==
  wfrec pred-sexp (% $g$ .  $\text{sexp-case } c\ d\ (\%N1\ N2. e\ N1\ N2\ (g\ N1)\ (g\ N2))$ )
by (simp add: sexp-rec-def)

lemmas sexp-rec-unfold = def-wfrec [OF sexp-rec-unfold-lemma wf-pred-sexp]

lemma sexp-rec-Leaf:  $\text{sexp-rec } (\text{Leaf } a)\ c\ d\ h = c(a)$ 
apply (subst sexp-rec-unfold)
apply (rule sexp-case-Leaf)
done

lemma sexp-rec-Numb:  $\text{sexp-rec } (\text{Numb } k)\ c\ d\ h = d(k)$ 
apply (subst sexp-rec-unfold)
apply (rule sexp-case-Numb)
done

lemma sexp-rec-Scons: [|  $M \in \text{sexp}$ ;  $N \in \text{sexp}$  |] ==>
   $\text{sexp-rec } (\text{Scons } M\ N)\ c\ d\ h = h\ M\ N\ (\text{sexp-rec } M\ c\ d\ h)\ (\text{sexp-rec } N\ c\ d\ h)$ 
apply (rule sexp-rec-unfold [THEN trans])
apply (simp add: pred-sexpI1 pred-sexpI2)
done

end

```

```
theory SList imports NatArith Sexp Hilbert-Choice begin
```

```
constdefs
```

```
NIL  :: 'a item  
NIL == In0(Numb(0))
```

```
CONS :: ['a item, 'a item] => 'a item  
CONS M N == In1(Scons M N)
```

```
consts
```

```
list    :: 'a item set => 'a item set
```

```
inductive list(A)
```

```
intros
```

```
NIL-I: NIL: list A  
CONS-I: [| a: A; M: list A |] ==> CONS a M : list A
```

```
typedef (List)
```

```
'a list = list(range Leaf) :: 'a item set  
by (blast intro: list.NIL-I)
```

```
constdefs
```

```
List-case :: ['b, ['a item, 'a item]=>'b, 'a item] => 'b  
List-case c d == Case(%x. c)(Split(d))
```

```
List-rec :: ['a item, 'b, ['a item, 'a item, 'b]=>'b] => 'b  
List-rec M c d == wfrec (tranc1 pred-sexp)  
                      (%g. List-case c (%x y. d x y (g y))) M
```

constdefs

$Nil \quad :: 'a \text{ list}$
 $Nil == Abs-List(NIL)$

$Cons \quad :: ['a, 'a \text{ list}] => 'a \text{ list} \quad (\text{infixr } \# \ 65)$
 $x \# xs == Abs-List(CONS (Leaf x)(Rep-List xs))$

$list-rec \quad :: ['a \text{ list}, 'b, ['a, 'a \text{ list}, 'b] => 'b] => 'b$
 $list-rec \ l \ c \ d ==$
 $List-rec(Rep-List \ l) \ c \ (\%x \ y \ r. \ d(inv \ Leaf \ x)(Abs-List \ y) \ r)$

$list-case \quad :: ['b, ['a, 'a \text{ list}] => 'b, 'a \text{ list}] => 'b$
 $list-case \ a \ f \ xs == list-rec \ xs \ a \ (\%x \ xs \ r. \ f \ x \ xs)$

consts

$[] \quad :: 'a \text{ list} \quad ([])$

syntax

$@list \quad :: args => 'a \text{ list} \quad ([(-)])$

translations

$[x, xs] == x \# [xs]$
 $[x] == x \# []$
 $[] == Nil$

$case \ xs \ of \ Nil \ => \ a \mid y \# ys \ => \ b == list-case(a, \%y \ ys. \ b, \ xs)$

constdefs

$Rep-map \quad :: ('b \Rightarrow 'a \text{ item}) \Rightarrow ('b \text{ list} \Rightarrow 'a \text{ item})$

Rep-map $f\ xs == list-rec\ xs\ NIL(\%x\ l\ r.\ CONS(f\ x)\ r)$

Abs-map $:: ('a\ item ==> 'b) ==> 'a\ item ==> 'b\ list$
Abs-map $g\ M == List-rec\ M\ Nil\ (\%N\ L\ r.\ g(N)\#r)$

constdefs

null $:: 'a\ list ==> bool$
null $xs == list-rec\ xs\ True\ (\%x\ xs\ r.\ False)$

hd $:: 'a\ list ==> 'a$
hd $xs == list-rec\ xs\ (@x.\ True)\ (\%x\ xs\ r.\ x)$

tl $:: 'a\ list ==> 'a\ list$
tl $xs == list-rec\ xs\ (@xs.\ True)\ (\%x\ xs\ r.\ xs)$

tll $:: 'a\ list ==> 'a\ list$
tll $xs == list-rec\ xs\ []\ (\%x\ xs\ r.\ xs)$

member $:: ['a,\ 'a\ list] ==> bool\ (\mathbf{infixl}\ mem\ 55)$
x mem $xs == list-rec\ xs\ False\ (\%y\ ys\ r.\ if\ y=x\ then\ True\ else\ r)$

list-all $:: ('a ==> bool) ==> ('a\ list ==> bool)$
list-all $P\ xs == list-rec\ xs\ True(\%x\ l\ r.\ P(x)\ \&\ r)$

map $:: ('a==>'b) ==> ('a\ list ==> 'b\ list)$
map $f\ xs == list-rec\ xs\ []\ (\%x\ l\ r.\ f(x)\#r)$

constdefs

append $:: ['a\ list,\ 'a\ list] ==> 'a\ list\ (\mathbf{infixr}\ @\ 65)$
xs@ys $== list-rec\ xs\ ys\ (\%x\ l\ r.\ x\#r)$

filter $:: ['a ==> bool,\ 'a\ list] ==> 'a\ list$
filter $P\ xs == list-rec\ xs\ []\ (\%x\ xs\ r.\ if\ P(x)\ then\ x\#r\ else\ r)$

foldl $:: [['b,\ 'a] ==> 'b,\ 'b,\ 'a\ list] ==> 'b$
foldl $f\ a\ xs == list-rec\ xs\ (\%a.\ a)(\%x\ xs\ r.\ \%a.\ r(f\ a\ x))(a)$

foldr $:: [['a,\ 'b] ==> 'b,\ 'b,\ 'a\ list] ==> 'b$
foldr $f\ a\ xs == list-rec\ xs\ a\ (\%x\ xs\ r.\ (f\ x\ r))$

length $:: 'a\ list ==> nat$
length $xs == list-rec\ xs\ 0\ (\%x\ xs\ r.\ Suc\ r)$

```

drop      :: ['a list, nat] => 'a list
drop t n == (nat-rec (%x. x) (%m r xs. r (ttl xs))) (n) (t)

copy      :: ['a, nat] => 'a list
copy t    == nat-rec [] (%m xs. t # xs)

flat      :: 'a list list => 'a list
flat      == foldr (op @) []

nth       :: [nat, 'a list] => 'a
nth       == nat-rec hd (%m r xs. r (tl xs))

rev       :: 'a list => 'a list
rev xs    == list-rec xs [] (%x xs xsa. xsa @ [x])

zipWith   :: ['a * 'b => 'c, 'a list * 'b list] => 'c list
zipWith f S == (list-rec (fst S) (%T. []))
              (%x xs r. %T. if null T then []
                           else f(x, hd T) # r (tl T))) (snd(S))

zip       :: 'a list * 'b list => ('a * 'b) list
zip       == zipWith (%s. s)

unzip     :: ('a * 'b) list => ('a list * 'b list)
unzip     == foldr (% (a,b)(c,d).(a#c,b#d)) ([], [])

consts take      :: ['a list, nat] => 'a list
primrec
  take-0: take xs 0 = []
  take-Suc: take xs (Suc n) = list-case [] (%x l. x # take l n) xs

consts enum      :: [nat, nat] => nat list
primrec
  enum-0: enum i 0 = []
  enum-Suc: enum i (Suc j) = (if i <= j then enum i j @ [j] else [])

syntax

@Alls     :: [idt, 'a list, bool] => bool      ((2Alls :- ./ -) 10)
@filter   :: [idt, 'a list, bool] => 'a list    ((1[- :- ./ -]) )

translations
[x:xs. P] == filter (%x. P) xs
Alls x:xs. P == list-all (%x. P) xs

```

```

lemma ListI:  $x : \text{list } (\text{range Leaf}) \implies x : \text{List}$ 
by (simp add: List-def)

lemma ListD:  $x : \text{List} \implies x : \text{list } (\text{range Leaf})$ 
by (simp add: List-def)

lemma list-unfold:  $\text{list}(A) = \text{usum } \{\text{Numb}(0)\} (\text{uprod } A (\text{list}(A)))$ 
by (fast intro!: list.intros [unfolded NIL-def CONS-def]
      elim: list.cases [unfolded NIL-def CONS-def])

lemma list-mono:  $A \leq B \implies \text{list}(A) \leq \text{list}(B)$ 
apply (unfold list.defs )
apply (rule lfp-mono)
apply (assumption | rule basic-monos)+
done

lemma list-sexp:  $\text{list}(\text{sexp}) \leq \text{sexp}$ 
apply (unfold NIL-def CONS-def list.defs)
apply (rule lfp-lowerbound)
apply (fast intro: sexp.intros sexp-In0I sexp-In1I)
done

lemmas list-subset-sexp = subset-trans [OF list-mono list-sexp]

lemma list-induct:
  [|  $P(\text{Nil})$ ;
     $\forall x \text{ xs}. P(\text{xs}) \implies P(x \# \text{xs})$  |]  $\implies P(l)$ 
apply (unfold Nil-def Cons-def)
apply (rule Rep-List-inverse [THEN subst])

apply (rule Rep-List [unfolded List-def, THEN list.induct], simp)
apply (erule Abs-List-inverse [unfolded List-def, THEN subst], blast)
done

lemma inj-on-Abs-list:  $\text{inj-on Abs-List } (\text{list}(\text{range Leaf}))$ 
apply (rule inj-on-inverseI)
apply (erule Abs-List-inverse [unfolded List-def])
done

```



```

lemma CONS-not-NIL [iff]: CONS M N  $\sim$  NIL
by (simp add: NIL-def CONS-def)

lemmas NIL-not-CONS [iff] = CONS-not-NIL [THEN not-sym]
lemmas CONS-neq-NIL = CONS-not-NIL [THEN notE, standard]
lemmas NIL-neq-CONS = sym [THEN CONS-neq-NIL]

lemma Cons-not-Nil [iff]: x # xs  $\sim$  Nil
apply (unfold Nil-def Cons-def)
apply (rule CONS-not-NIL [THEN inj-on-Abs-list [THEN inj-on-contrad]])
apply (simp-all add: list.intros rangeI Rep-List [unfolded List-def])
done

lemmas Nil-not-Cons [iff] = Cons-not-Nil [THEN not-sym, standard]
lemmas Cons-neq-Nil = Cons-not-Nil [THEN notE, standard]
lemmas Nil-neq-Cons = sym [THEN Cons-neq-Nil]

lemma CONS-CONS-eq [iff]: (CONS K M) = (CONS L N) = (K=L & M=N)
by (simp add: CONS-def)

declare Rep-List [THEN ListD, intro] ListI [intro]
declare list.intros [intro, simp]
declare Leaf-inject [dest!]

lemma Cons-Cons-eq [iff]: (x # xs = y # ys) = (x=y & xs=ys)
apply (simp add: Cons-def)
apply (subst Abs-List-inject)
apply (auto simp add: Rep-List-inject)
done

lemmas Cons-inject2 = Cons-Cons-eq [THEN iffD1, THEN conjE, standard]

lemma CONS-D: CONS M N: list(A) ==> M: A & N: list(A)
apply (erule setup-induction)
apply (erule list.induct, blast+)
done

lemma sexp-CONS-D: CONS M N: sexp ==> M: sexp & N: sexp
apply (simp add: CONS-def In1-def)
apply (fast dest!: Scons-D)
done

```

lemma *not-CONS-self*: $N: \text{list}(A) \implies !M. N \sim = \text{CONS } M \ N$
by (*erule list.induct, simp-all*)

lemma *not-Cons-self2*: $\forall x. l \sim = x \# l$
by (*induct-tac l rule: list-induct, simp-all*)

lemma *neq-Nil-conv2*: $(xs \sim = []) = (\exists y \text{ ys}. xs = y \# \text{ys})$
by (*induct-tac xs rule: list-induct, auto*)

lemma *List-case-NIL* [*simp*]: $\text{List-case } c \ h \ \text{NIL} = c$
by (*simp add: List-case-def NIL-def*)

lemma *List-case-CONS* [*simp*]: $\text{List-case } c \ h \ (\text{CONS } M \ N) = h \ M \ N$
by (*simp add: List-case-def CONS-def*)

lemma *List-rec-unfold-lemma*:
 $(\%M. \text{List-rec } M \ c \ d) ==$
 $\text{wfrec } (\text{tranc1 pred-sexp}) \ (\%g. \text{List-case } c \ (\%x \ y. d \ x \ y \ (g \ y)))$
by (*simp add: List-rec-def*)

lemmas *List-rec-unfold* =
 $\text{def-wfrec } [\text{OF } \text{List-rec-unfold-lemma } \text{wf-pred-sexp } [\text{THEN } \text{wf-tranc1}],$
 $\text{standard}]$

lemma *pred-sexp-CONS-I1*:
 $[[M: \text{sexp}; \ N: \text{sexp}]] \implies (M, \text{CONS } M \ N) : \text{pred-sexp}^+ +$
by (*simp add: CONS-def In1-def*)

lemma *pred-sexp-CONS-I2*:
 $[[M: \text{sexp}; \ N: \text{sexp}]] \implies (N, \text{CONS } M \ N) : \text{pred-sexp}^+ +$
by (*simp add: CONS-def In1-def*)

lemma *pred-sexp-CONS-D*:
 $(\text{CONS } M1 \ M2, N) : \text{pred-sexp}^+ \implies$
 $(M1, N) : \text{pred-sexp}^+ \ \& \ (M2, N) : \text{pred-sexp}^+ +$
apply (*frule pred-sexp-subset-Sigma [THEN transcl-subset-Sigma, THEN subsetD]*)
apply (*blast dest!: sexp-CONS-D intro: pred-sexp-CONS-I1 pred-sexp-CONS-I2*
 $\text{trans-tranc1 [THEN transD]}$)

done

lemma *List-rec-NIL* [simp]: *List-rec NIL c h = c*
apply (rule *List-rec-unfold* [THEN trans])
apply (simp add: *List-case-NIL*)
done

lemma *List-rec-CONS* [simp]:
 [| *M*: *sexp*; *N*: *sexp* |]
 ==> *List-rec (CONS M N) c h = h M N (List-rec N c h)*
apply (rule *List-rec-unfold* [THEN trans])
apply (simp add: *pred-sexp-CONS-I2*)
done

lemmas *Rep-List-in-sexp* =
subsetD [*OF range-Leaf-subset-sexp* [THEN *list-subset-sexp*]
Rep-List [THEN *ListD*]]

lemma *list-rec-Nil* [simp]: *list-rec Nil c h = c*
by (simp add: *list-rec-def ListI* [THEN *Abs-List-inverse*] *Nil-def*)

lemma *list-rec-Cons* [simp]: *list-rec (a#l) c h = h a l (list-rec l c h)*
by (simp add: *list-rec-def ListI* [THEN *Abs-List-inverse*] *Cons-def*
Rep-List-inverse Rep-List [THEN *ListD*] *inj-Leaf Rep-List-in-sexp*)

lemma *List-rec-type*:
 [| *M*: *list*(*A*);
 A <= *sexp*;
 c: *C*(*NIL*);
 !!*x y r*. [| *x*: *A*; *y*: *list*(*A*); *r*: *C*(*y*) |] ==> *h x y r*: *C*(*CONS x y*)
 |] ==> *List-rec M c h* : *C*(*M* :: 'a item)

apply (erule *list.induct*, simp)
apply (insert *list-subset-sexp*)
apply (subst *List-rec-CONS*, blast+)
done

lemma *Rep-map-Nil* [*simp*]: $\text{Rep-map } f \text{ Nil} = \text{NIL}$
by (*simp add: Rep-map-def*)

lemma *Rep-map-Cons* [*simp*]:
 $\text{Rep-map } f (x \# xs) = \text{CONS}(f x) (\text{Rep-map } f xs)$
by (*simp add: Rep-map-def*)

lemma *Rep-map-type*: $(!!x. f(x): A) ==> \text{Rep-map } f xs: \text{list}(A)$
apply (*simp add: Rep-map-def*)
apply (*rule list-induct, auto*)
done

lemma *Abs-map-NIL* [*simp*]: $\text{Abs-map } g \text{ NIL} = \text{Nil}$
by (*simp add: Abs-map-def*)

lemma *Abs-map-CONS* [*simp*]:
 $[! M: \text{sexp}; N: \text{sexp}] ==> \text{Abs-map } g (\text{CONS } M N) = g(M) \# \text{Abs-map } g N$
by (*simp add: Abs-map-def*)

lemma *def-list-rec-NilCons*:
 $[! xs. f(xs) == \text{list-rec } xs \ c \ h] ==> f [] = c \ \& \ f(x \# xs) = h \ x \ xs \ (f \ xs)$
by *simp*

lemma *Abs-map-inverse*:
 $[! M: \text{list}(A); A <= \text{sexp}; !!z. z: A ==> f(g(z)) = z] ==> \text{Rep-map } f (\text{Abs-map } g M) = M$
apply (*erule list.induct, simp-all*)
apply (*insert list-subset-sexp*)
apply (*subst Abs-map-CONS, blast*)
apply *blast*
apply *simp*
done

Better to have a single theorem with a conjunctive conclusion.

declare *def-list-rec-NilCons* [*OF list-case-def, simp*]

lemma *expand-list-case*:
 $P(\text{list-case } a \ f \ xs) = ((xs = [] \ --> P \ a) \ \& \ (!y \ ys. xs = y \# ys \ --> P(f \ y \ ys)))$
by (*induct-tac xs rule: list-induct, simp-all*)

```

declare def-list-rec-NilCons [OF null-def, simp]
declare def-list-rec-NilCons [OF hd-def, simp]
declare def-list-rec-NilCons [OF tl-def, simp]
declare def-list-rec-NilCons [OF ttl-def, simp]
declare def-list-rec-NilCons [OF append-def, simp]
declare def-list-rec-NilCons [OF member-def, simp]
declare def-list-rec-NilCons [OF map-def, simp]
declare def-list-rec-NilCons [OF filter-def, simp]
declare def-list-rec-NilCons [OF list-all-def, simp]

```

```

lemma def-nat-rec-0-eta:
  [| !!n. f == nat-rec c h |] ==> f(0) = c
by simp

```

```

lemma def-nat-rec-Suc-eta:
  [| !!n. f == nat-rec c h |] ==> f(Suc(n)) = h n (f n)
by simp

```

```

declare def-nat-rec-0-eta [OF nth-def, simp]
declare def-nat-rec-Suc-eta [OF nth-def, simp]

```

```

lemma length-Nil [simp]: length([]) = 0
by (simp add: length-def)

```

```

lemma length-Cons [simp]: length(a#xs) = Suc(length(xs))
by (simp add: length-def)

```

```

lemma append-assoc [simp]: (xs@ys)@zs = xs@(ys@zs)
by (induct-tac xs rule: list-induct, simp-all)

```

```

lemma append-Nil2 [simp]: xs @ [] = xs
by (induct-tac xs rule: list-induct, simp-all)

```

```

lemma mem-append [simp]: x mem (xs@ys) = (x mem xs | x mem ys)
by (induct-tac xs rule: list-induct, simp-all)

```

```

lemma mem-filter [simp]: x mem [x:xs. P x] = (x mem xs & P(x))

```

by (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)

lemma *list-all-True* [*simp*]: (*Alls* *x:xs*. *True*) = *True*
by (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)

lemma *list-all-conj* [*simp*]:
 $list-all\ p\ (xs@ys) = ((list-all\ p\ xs) \& (list-all\ p\ ys))$
by (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)

lemma *list-all-mem-conv*: (*Alls* *x:xs*. *P*(*x*)) = (!*x*. *x mem xs* \longrightarrow *P*(*x*))
apply (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)
apply *blast*
done

lemma *nat-case-dist* : (! *n*. *P n*) = (*P 0* & (! *n*. *P (Suc n)*))
apply *auto*
apply (*induct-tac* *n*, *auto*)
done

lemma *alls-P-eq-P-nth*: (*Alls* *u:A*. *P u*) = (!*n*. *n < length A* \longrightarrow *P*(*nth n A*))
apply (*induct-tac* *A* *rule*: *list-induct*, *simp-all*)
apply (*rule trans*)
apply (*rule-tac* [2] *nat-case-dist* [*symmetric*], *simp-all*)
done

lemma *list-all-imp*:
 $[[!x. P\ x \longrightarrow Q\ x; (Alls\ x:xs. P(x))]] \Longrightarrow (Alls\ x:xs. Q(x))$
by (*simp add*: *list-all-mem-conv*)

lemma *Abs-Rep-map*:
 $(!x. f(x): sexp) \Longrightarrow$
 $Abs-map\ g\ (Rep-map\ f\ xs) = map\ (\%t. g(f(t)))\ xs$
apply (*induct-tac* *xs* *rule*: *list-induct*)
apply (*simp-all add*: *Rep-map-type list-sexp* [*THEN subsetD*])
done

lemma *map-ident* [*simp*]: $map(\%x. x)(xs) = xs$
by (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)

lemma *map-append* [*simp*]: $\text{map } f \ (xs @ ys) = \text{map } f \ xs \ @ \ \text{map } f \ ys$
by (*induct-tac xs rule: list-induct, simp-all*)

lemma *map-compose*: $\text{map}(f \circ g)(xs) = \text{map } f \ (\text{map } g \ xs)$
apply (*simp add: o-def*)
apply (*induct-tac xs rule: list-induct, simp-all*)
done

lemma *mem-map-aux1* [*rule-format*]:
 $x \text{ mem } (\text{map } f \ q) \longrightarrow (\exists y. y \text{ mem } q \ \& \ x = f \ y)$
by (*induct-tac q rule: list-induct, simp-all, blast*)

lemma *mem-map-aux2* [*rule-format*]:
 $(\exists y. y \text{ mem } q \ \& \ x = f \ y) \longrightarrow x \text{ mem } (\text{map } f \ q)$
by (*induct-tac q rule: list-induct, auto*)

lemma *mem-map*: $x \text{ mem } (\text{map } f \ q) = (\exists y. y \text{ mem } q \ \& \ x = f \ y)$
apply (*rule iffI*)
apply (*erule mem-map-aux1*)
apply (*erule mem-map-aux2*)
done

lemma *hd-append* [*rule-format*]: $A \sim [] \longrightarrow \text{hd}(A @ B) = \text{hd}(A)$
by (*induct-tac A rule: list-induct, auto*)

lemma *tl-append* [*rule-format*]: $A \sim [] \longrightarrow \text{tl}(A @ B) = \text{tl}(A) @ B$
by (*induct-tac A rule: list-induct, auto*)

lemma *take-Suc1* [*simp*]: $\text{take } [] \ (\text{Suc } x) = []$
by *simp*

lemma *take-Suc2* [*simp*]: $\text{take}(a \# xs)(\text{Suc } x) = a \# \text{take } xs \ x$
by *simp*

lemma *drop-0* [*simp*]: $\text{drop } xs \ 0 = xs$
by (*simp add: drop-def*)

lemma *drop-Suc1* [*simp*]: $\text{drop } [] \ (\text{Suc } x) = []$
apply (*simp add: drop-def*)
apply (*induct-tac x, auto*)
done

lemma *drop-Suc2* [*simp*]: $\text{drop}(a\#xs)(\text{Suc } x) = \text{drop } xs \ x$
by (*simp add: drop-def*)

lemma *copy-0* [*simp*]: $\text{copy } x \ 0 = []$
by (*simp add: copy-def*)

lemma *copy-Suc* [*simp*]: $\text{copy } x \ (\text{Suc } y) = x \ \# \ \text{copy } x \ y$
by (*simp add: copy-def*)

lemma *foldl-Nil* [*simp*]: $\text{foldl } f \ a \ [] = a$
by (*simp add: foldl-def*)

lemma *foldl-Cons* [*simp*]: $\text{foldl } f \ a \ (x\#xs) = \text{foldl } f \ (f \ a \ x) \ xs$
by (*simp add: foldl-def*)

lemma *foldr-Nil* [*simp*]: $\text{foldr } f \ a \ [] = a$
by (*simp add: foldr-def*)

lemma *foldr-Cons* [*simp*]: $\text{foldr } f \ z \ (x\#xs) = f \ x \ (\text{foldr } f \ z \ xs)$
by (*simp add: foldr-def*)

lemma *flat-Nil* [*simp*]: $\text{flat } [] = []$
by (*simp add: flat-def*)

lemma *flat-Cons* [*simp*]: $\text{flat } (x \ \# \ xs) = x \ @ \ \text{flat } xs$
by (*simp add: flat-def*)

lemma *rev-Nil* [*simp*]: $\text{rev } [] = []$
by (*simp add: rev-def*)

lemma *rev-Cons* [*simp*]: $\text{rev } (x \ \# \ xs) = \text{rev } xs \ @ \ [x]$
by (*simp add: rev-def*)

lemma *zipWith-Cons-Cons* [*simp*]:
 $\text{zipWith } f \ (a\#as, b\#bs) = f(a,b) \ \# \ \text{zipWith } f \ (as, bs)$

by (*simp add: zipWith-def*)

lemma *zipWith-Nil-Nil* [*simp*]: *zipWith f* ($[], []$) = $[]$
by (*simp add: zipWith-def*)

lemma *zipWith-Cons-Nil* [*simp*]: *zipWith f* ($x, []$) = $[]$
apply (*simp add: zipWith-def*)
apply (*induct-tac x rule: list-induct, simp-all*)
done

lemma *zipWith-Nil-Cons* [*simp*]: *zipWith f* ($[], x$) = $[]$
by (*simp add: zipWith-def*)

lemma *unzip-Nil* [*simp*]: *unzip* $[]$ = $([], [])$
by (*simp add: unzip-def*)

lemma *map-compose-ext*: *map*($f \circ g$) = (*map* f) *o* (*map* g)
apply (*simp add: o-def*)
apply (*rule ext*)
apply (*simp add: map-compose [symmetric] o-def*)
done

lemma *map-flat*: *map f* (*flat* S) = *flat*(*map* (*map f*) S)
by (*induct-tac S rule: list-induct, simp-all*)

lemma *list-all-map-eq*: (*ALL* $u:xs. f(u) = g(u)$) \longrightarrow *map f* xs = *map g* xs
by (*induct-tac xs rule: list-induct, simp-all*)

lemma *filter-map-d*: *filter p* (*map f* xs) = *map f* (*filter*($p \circ f$)(xs))
by (*induct-tac xs rule: list-induct, simp-all*)

lemma *filter-compose*: *filter p* (*filter q* xs) = *filter*($\%x. p\ x \ \&\ q\ x$) xs
by (*induct-tac xs rule: list-induct, simp-all*)

lemma *filter-append* [*rule-format, simp*]:
 $\forall B. \text{filter } p\ (A @ B) = (\text{filter } p\ A @ \text{filter } p\ B)$
by (*induct-tac A rule: list-induct, simp-all*)

lemma *length-append*: $\text{length}(xs@ys) = \text{length}(xs) + \text{length}(ys)$
by (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)

lemma *length-map*: $\text{length}(\text{map } f \text{ } xs) = \text{length}(xs)$
by (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)

lemma *take-Nil* [*simp*]: $\text{take } [] \text{ } n = []$
by (*induct-tac* *n*, *simp-all*)

lemma *take-take-eq* [*simp*]: $\forall n. \text{take } (\text{take } xs \text{ } n) \text{ } n = \text{take } xs \text{ } n$
apply (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)
apply (*rule allI*)
apply (*induct-tac* *n*, *auto*)
done

lemma *take-take-Suc-eq1* [*rule-format*]:
 $\forall n. \text{take } (\text{take } xs (\text{Suc}(n+m))) \text{ } n = \text{take } xs \text{ } n$
apply (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)
apply (*rule allI*)
apply (*induct-tac* *n*, *auto*)
done

declare *take-Suc* [*simp del*]

lemma *take-take-1*: $\text{take } (\text{take } xs \text{ } (n+m)) \text{ } n = \text{take } xs \text{ } n$
apply (*induct-tac* *m*)
apply (*simp-all add*: *take-take-Suc-eq1*)
done

lemma *take-take-Suc-eq2* [*rule-format*]:
 $\forall n. \text{take } (\text{take } xs \text{ } n) (\text{Suc}(n+m)) = \text{take } xs \text{ } n$
apply (*induct-tac* *xs* *rule*: *list-induct*, *simp-all*)
apply (*rule allI*)
apply (*induct-tac* *n*, *auto*)
done

lemma *take-take-2*: $\text{take}(\text{take } xs \text{ } n)(n+m) = \text{take } xs \text{ } n$
apply (*induct-tac* *m*)
apply (*simp-all add*: *take-take-Suc-eq2*)
done

lemma *drop-Nil* [*simp*]: $\text{drop } [] \text{ } n = []$
by (*induct-tac* *n*, *auto*)

lemma *drop-drop* [rule-format]: $\forall xs. \text{drop} (\text{drop } xs \ m) \ n = \text{drop } xs (m+n)$
apply (*induct-tac* *m*, *auto*)
apply (*induct-tac* *xs* rule: *list-induct*, *auto*)
done

lemma *take-drop* [rule-format]: $\forall xs. (\text{take } xs \ n) @ (\text{drop } xs \ n) = xs$
apply (*induct-tac* *n*, *auto*)
apply (*induct-tac* *xs* rule: *list-induct*, *auto*)
done

lemma *copy-copy*: $\text{copy } x \ n @ \text{copy } x \ m = \text{copy } x \ (n+m)$
by (*induct-tac* *n*, *auto*)

lemma *length-copy*: $\text{length}(\text{copy } x \ n) = n$
by (*induct-tac* *n*, *auto*)

lemma *length-take* [rule-format, *simp*]:
 $\forall xs. \text{length}(\text{take } xs \ n) = \min (\text{length } xs) \ n$
apply (*induct-tac* *n*)
apply *auto*
apply (*induct-tac* *xs* rule: *list-induct*)
apply *auto*
done

lemma *length-take-drop*: $\text{length}(\text{take } A \ k) + \text{length}(\text{drop } A \ k) = \text{length}(A)$
by (*simp only: length-append [symmetric] take-drop*)

lemma *take-append* [rule-format]: $\forall A. \text{length}(A) = n \dashrightarrow \text{take}(A @ B) \ n = A$
apply (*induct-tac* *n*)
apply (*rule allI*)
apply (*rule-tac* [2] *allI*)
apply (*induct-tac* *A* rule: *list-induct*)
apply (*induct-tac* [3] *A* rule: *list-induct*, *simp-all*)
done

lemma *take-append2* [rule-format]:
 $\forall A. \text{length}(A) = n \dashrightarrow \text{take}(A @ B) \ (n+k) = A @ \text{take } B \ k$
apply (*induct-tac* *n*)
apply (*rule allI*)
apply (*rule-tac* [2] *allI*)
apply (*induct-tac* *A* rule: *list-induct*)
apply (*induct-tac* [3] *A* rule: *list-induct*, *simp-all*)
done

lemma *take-map* [rule-format]: $\forall n. \text{take} (\text{map } f \ A) \ n = \text{map } f \ (\text{take } A \ n)$
apply (*induct-tac* *A* rule: *list-induct*, *simp-all*)
apply (*rule allI*)
apply (*induct-tac* *n*, *simp-all*)

done

lemma *drop-append* [rule-format]: $\forall A. \text{length}(A) = n \dashv\vdash \text{drop}(A @ B)n = B$
apply (*induct-tac* *n*)
apply (*rule allI*)
apply (*rule-tac* [2] *allI*)
apply (*induct-tac* *A* *rule: list-induct*)
apply (*induct-tac* [3] *A* *rule: list-induct, simp-all*)
done

lemma *drop-append2* [rule-format]:
 $\forall A. \text{length}(A) = n \dashv\vdash \text{drop}(A @ B)(n+k) = \text{drop } B \ k$
apply (*induct-tac* *n*)
apply (*rule allI*)
apply (*rule-tac* [2] *allI*)
apply (*induct-tac* *A* *rule: list-induct*)
apply (*induct-tac* [3] *A* *rule: list-induct, simp-all*)
done

lemma *drop-all* [rule-format]: $\forall A. \text{length}(A) = n \dashv\vdash \text{drop } A \ n = []$
apply (*induct-tac* *n*)
apply (*rule allI*)
apply (*rule-tac* [2] *allI*)
apply (*induct-tac* *A* *rule: list-induct*)
apply (*induct-tac* [3] *A* *rule: list-induct, auto*)
done

lemma *drop-map* [rule-format]: $\forall n. \text{drop } (\text{map } f \ A) \ n = \text{map } f \ (\text{drop } A \ n)$
apply (*induct-tac* *A* *rule: list-induct, simp-all*)
apply (*rule allI*)
apply (*induct-tac* *n*, *simp-all*)
done

lemma *take-all* [rule-format]: $\forall A. \text{length}(A) = n \dashv\vdash \text{take } A \ n = A$
apply (*induct-tac* *n*)
apply (*rule allI*)
apply (*rule-tac* [2] *allI*)
apply (*induct-tac* *A* *rule: list-induct*)
apply (*induct-tac* [3] *A* *rule: list-induct, auto*)
done

lemma *foldl-single*: $\text{foldl } f \ a \ [b] = f \ a \ b$
by *simp-all*

lemma *foldl-append* [rule-format, simp]:
 $\forall a. \text{foldl } f \ a \ (A @ B) = \text{foldl } f \ (\text{foldl } f \ a \ A) \ B$
by (*induct-tac* *A* *rule: list-induct, simp-all*)

lemma *foldl-map* [*rule-format*]:
 $\forall e. \text{foldl } f \ e \ (\text{map } g \ S) = \text{foldl } (\%x \ y. f \ x \ (g \ y)) \ e \ S$
by (*induct-tac* *S* *rule*: *list-induct*, *simp-all*)

lemma *foldl-neutr-distr* [*rule-format*]:
assumes *r-neutr*: $\forall a. f \ a \ e = a$
and *r-neutl*: $\forall a. f \ e \ a = a$
and *assoc*: $\forall a \ b \ c. f \ a \ (f \ b \ c) = f \ (f \ a \ b) \ c$
shows $\forall y. f \ y \ (\text{foldl } f \ e \ A) = \text{foldl } f \ y \ A$
apply (*induct-tac* *A* *rule*: *list-induct*)
apply (*simp-all* *add*: *r-neutr* *r-neutl*, *clarify*)
apply (*erule* *all-dupE*)
apply (*rule* *trans*)
prefer 2 **apply** *assumption*
apply (*simp* (*no-asm-use*) *add*: *assoc* [*THEN spec*, *THEN spec*, *THEN spec*, *THEN sym*])
apply *simp*
done

lemma *foldl-append-sym*:
 $[[!a. f \ a \ e = a; !a. f \ e \ a = a;$
 $!a \ b \ c. f \ a \ (f \ b \ c) = f \ (f \ a \ b) \ c]]$
 $\implies \text{foldl } f \ e \ (A \ @ \ B) = f \ (\text{foldl } f \ e \ A) (\text{foldl } f \ e \ B)$
apply (*rule* *trans*)
apply (*rule* *foldl-append*)
apply (*rule* *sym*)
apply (*rule* *foldl-neutr-distr*, *auto*)
done

lemma *foldr-append* [*rule-format*, *simp*]:
 $\forall a. \text{foldr } f \ a \ (A \ @ \ B) = \text{foldr } f \ (\text{foldr } f \ a \ B) \ A$
apply (*induct-tac* *A* *rule*: *list-induct*, *simp-all*)
done

lemma *foldr-map* [*rule-format*]: $\forall e. \text{foldr } f \ e \ (\text{map } g \ S) = \text{foldr } (f \ o \ g) \ e \ S$
apply (*simp* *add*: *o-def*)
apply (*induct-tac* *S* *rule*: *list-induct*, *simp-all*)
done

lemma *foldr-Un-eq-UN*: $\text{foldr } op \ Un \ \{ \} \ S = (UN \ X: \{t. t \ mem \ S\}. X)$
by (*induct-tac* *S* *rule*: *list-induct*, *auto*)

lemma *foldr-neutr-distr*:
 $[[!a. f \ e \ a = a; !a \ b \ c. f \ a \ (f \ b \ c) = f \ (f \ a \ b) \ c]]$
 $\implies \text{foldr } f \ y \ S = f \ (\text{foldr } f \ e \ S) \ y$
by (*induct-tac* *S* *rule*: *list-induct*, *auto*)

lemma *foldr-append2*:

```

    [| !a. f e a = a; !a b c. f a (f b c) = f(f a b) c |]
    ==> foldr f e (A @ B) = f (foldr f e A) (foldr f e B)
  apply auto
  apply (rule foldr-neutr-distr, auto)
  done

```

```

lemma foldr-flat:
  [| !a. f e a = a; !a b c. f a (f b c) = f(f a b) c |] ==>
    foldr f e (flat S) = (foldr f e)(map (foldr f e) S)
  apply (induct-tac S rule: list-induct)
  apply (simp-all del: foldr-append add: foldr-append2)
  done

```

```

lemma list-all-map: (Alls x:map f xs .P(x)) = (Alls x:xs.(P o f)(x))
by (induct-tac xs rule: list-induct, auto)

```

```

lemma list-all-and:
  (Alls x:xs. P(x)&Q(x)) = ((Alls x:xs. P(x))&(Alls x:xs. Q(x)))
by (induct-tac xs rule: list-induct, auto)

```

```

lemma nth-map [rule-format]:
  ∀ i. i < length(A) --> nth i (map f A) = f(nth i A)
  apply (induct-tac A rule: list-induct, simp-all)
  apply (rule allI)
  apply (induct-tac i, auto)
  done

```

```

lemma nth-app-cancel-right [rule-format]:
  ∀ i. i < length(A) --> nth i (A@B) = nth i A
  apply (induct-tac A rule: list-induct, simp-all)
  apply (rule allI)
  apply (induct-tac i, simp-all)
  done

```

```

lemma nth-app-cancel-left [rule-format]:
  ∀ n. n = length(A) --> nth(n+i)(A@B) = nth i B
by (induct-tac A rule: list-induct, simp-all)

```

```

lemma flat-append [simp]: flat(xs@ys) = flat(xs) @ flat(ys)
by (induct-tac xs rule: list-induct, auto)

```

```

lemma filter-flat: filter p (flat S) = flat(map (filter p) S)
by (induct-tac S rule: list-induct, auto)

```

lemma *rev-append* [simp]: $rev(xs@ys) = rev(ys) @ rev(xs)$
by (*induct-tac* *xs* rule: *list-induct*, *auto*)

lemma *rev-rev-ident* [simp]: $rev(rev\ l) = l$
by (*induct-tac* *l* rule: *list-induct*, *auto*)

lemma *rev-flat*: $rev(flat\ ls) = flat\ (map\ rev\ (rev\ ls))$
by (*induct-tac* *ls* rule: *list-induct*, *auto*)

lemma *rev-map-distrib*: $rev(map\ f\ l) = map\ f\ (rev\ l)$
by (*induct-tac* *l* rule: *list-induct*, *auto*)

lemma *foldl-rev*: $foldl\ f\ b\ (rev\ l) = foldr\ (\%x\ y.\ f\ y\ x)\ b\ l$
by (*induct-tac* *l* rule: *list-induct*, *auto*)

lemma *foldr-rev*: $foldr\ f\ b\ (rev\ l) = foldl\ (\%x\ y.\ f\ y\ x)\ b\ l$
apply (*rule sym*)
apply (*rule trans*)
apply (*rule-tac* [2] *foldl-rev*, *simp*)
done

end

11 Definition of type *llist* by a greatest fixed point

theory *LList* **imports** *Main SList* **begin**

consts

llist :: '*a* item set => '*a* item set
LListD :: ('*a* item * '*a* item) set => ('*a* item * '*a* item) set

coinductive *llist*(*A*)

intros

NIL-I: $NIL \in llist(A)$

CONS-I: $[| a \in A; M \in llist(A) |] ==> CONS\ a\ M \in llist(A)$

coinductive *LListD*(*r*)

intros

NIL-I: $(NIL, NIL) \in LListD(r)$

CONS-I: $[| (a,b) \in r; (M,N) \in LListD(r) |] ==> (CONS\ a\ M, CONS\ b\ N) \in LListD(r)$

```

typedef (LList)
  'a llist = llist(range Leaf) :: 'a item set
  by (blast intro: llist.NIL-I)

constdefs
  list-Fun :: ['a item set, 'a item set] => 'a item set
  — Now used exclusively for abbreviating the coinduction rule
  list-Fun A X == {z. z = NIL | (∃ M a. z = CONS a M & a ∈ A & M ∈ X)}

  LListD-Fun ::
    [('a item * 'a item)set, ('a item * 'a item)set] =>
      ('a item * 'a item)set
  LListD-Fun r X ==
    {z. z = (NIL, NIL) |
      (∃ M N a b. z = (CONS a M, CONS b N) & (a, b) ∈ r & (M, N) ∈ X)}

  LNil :: 'a llist
  — abstract constructor
  LNil == Abs-LList NIL

  LCons :: ['a, 'a llist] => 'a llist
  — abstract constructor
  LCons x xs == Abs-LList(CONS (Leaf x) (Rep-LList xs))

  llist-case :: ['b, ['a, 'a llist]=>'b, 'a llist] => 'b
  llist-case c d l ==
    List-case c (%x y. d (inv Leaf x) (Abs-LList y)) (Rep-LList l)

  LList-corec-fun :: [nat, 'a=>('b item * 'a) option, 'a] => 'b item
  LList-corec-fun k f ==
    nat-rec (%x. { })
      (%j r x. case f x of None    => NIL
                  | Some(z,w) => CONS z (r w))
      k

  LList-corec :: ['a, 'a => ('b item * 'a) option] => 'b item
  LList-corec a f == ⋃ k. LList-corec-fun k f a

  llist-corec :: ['a, 'a => ('b * 'a) option] => 'b llist
  llist-corec a f ==
    Abs-LList(LList-corec a
      (%z. case f z of None    => None
                  | Some(v,w) => Some(Leaf(v), w)))

  llistD-Fun :: ('a llist * 'a llist)set => ('a llist * 'a llist)set
  llistD-Fun(r) ==
    prod-fun Abs-LList Abs-LList '
      LListD-Fun (diag(range Leaf))
      (prod-fun Rep-LList Rep-LList ' r)

```


The case syntax for type *'a llist*

translations

case p of LNil => a | LCons x l => b == llist-case a (%x l. b) p

11.0.2 Sample function definitions. Item-based ones start with *L*

constdefs

Lmap :: ('a item => 'b item) => ('a llist => 'b llist)
Lmap f M == LList-corec M (List-case None (%x M'. Some((f(x), M'))))

lmap :: ('a=>'b) => ('a llist => 'b llist)
*lmap f l == llist-corec l (%z. case z of LNil => None
| LCons y z => Some(f(y), z))*

iterates :: ['a => 'a, 'a] => 'a llist
iterates f a == llist-corec a (%x. Some((x, f(x))))

Lconst :: 'a item => 'a item
Lconst(M) == lfp(%N. CONS M N)

Lappend :: ['a item, 'a item] => 'a item
*Lappend M N == LList-corec (M,N)
(split(List-case (List-case None (%N1 N2. Some((N1, (NIL,N2))))
(%M1 M2 N. Some((M1, (M2,N))))))*

lappend :: ['a llist, 'a llist] => 'a llist
*lappend l n == llist-corec (l,n)
(split(llist-case (llist-case None (%n1 n2. Some((n1, (LNil,n2))))
(%l1 l2 n. Some((l1, (l2,n))))))*

Append generates its result by applying f, where f((NIL,NIL)) = None
f((NIL, CONS N1 N2)) = Some((N1, (NIL,N2))) f((CONS M1 M2, N)) =
Some((M1, (M2,N)))

SHOULD *LListD-Fun-CONS-I*, etc., be equations (for rewriting)?

lemmas *UN1-I = UNIV-I [THEN UN-I, standard]*

11.0.3 Simplification

declare *option.split [split]*

This justifies using llist in other recursive type definitions

lemma *llist-mono: A<=B ==> llist(A) <= llist(B)*

apply (*unfold llist.defs*)

apply (*rule gfp-mono*)

apply (*assumption | rule basic-monos*)+

done

```

lemma llist-unfold:  $llist(A) = usum \{Numb(0)\} (uprod A (llist A))$ 
  by (fast intro!: llist.intros [unfolded NIL-def CONS-def]
      elim: llist.cases [unfolded NIL-def CONS-def])

```

11.1 Type checking by coinduction

... using *list-Fun* THE COINDUCTIVE DEFINITION PACKAGE COULD DO THIS!

```

lemma llist-coinduct:
  [|  $M \in X$ ;  $X \leq list-Fun A (X \text{ Un } llist(A))$  |] ==>  $M \in llist(A)$ 
apply (unfold list-Fun-def)
apply (erule llist.coinduct)
apply (erule subsetD [THEN CollectD], assumption)
done

```

```

lemma list-Fun-NIL-I [iff]:  $NIL \in list-Fun A X$ 
by (unfold list-Fun-def NIL-def, fast)

```

```

lemma list-Fun-CONS-I [intro!, simp]:
  [|  $M \in A$ ;  $N \in X$  |] ==>  $CONS M N \in list-Fun A X$ 
apply (unfold list-Fun-def CONS-def, fast)
done

```

Utilise the “strong” part, i.e. $gfp(f)$

```

lemma list-Fun-llist-I:  $M \in llist(A) ==> M \in list-Fun A (X \text{ Un } llist(A))$ 
apply (unfold llist.defs list-Fun-def)
apply (rule gfp-fun-UnI2)
apply (rule monoI, blast)
apply assumption
done

```

11.2 *LList-corec* satisfies the desired recursion equation

A continuity result?

```

lemma CONS-UN1:  $CONS M (\bigcup x. f(x)) = (\bigcup x. CONS M (f x))$ 
apply (unfold CONS-def)
apply (simp add: In1-UN1 Scons-UN1-y)
done

```

```

lemma CONS-mono: [|  $M \leq M'$ ;  $N \leq N'$  |] ==>  $CONS M N \leq CONS M' N'$ 
apply (unfold CONS-def)
apply (assumption | rule In1-mono Scons-mono) +
done

```

```

declare LList-corec-fun-def [THEN def-nat-rec-0, simp]
          LList-corec-fun-def [THEN def-nat-rec-Suc, simp]

```

11.2.1 The directions of the equality are proved separately

lemma *LList-corec-subset1*:

```

  LList-corec a f <=
    (case f a of None => NIL | Some(z,w) => CONS z (LList-corec w f))
apply (unfold LList-corec-def)
apply (rule UN-least)
apply (case-tac k)
apply (simp-all (no-asm-simp))
apply (rule allI impI subset-refl [THEN CONS-mono] UNIV-I [THEN UN-upper])+
done

```

lemma *LList-corec-subset2*:

```

  (case f a of None => NIL | Some(z,w) => CONS z (LList-corec w f)) <=
    LList-corec a f
apply (unfold LList-corec-def)
apply (simp add: CONS-UN1, safe)
apply (rule-tac a=Suc(?k) in UN-I, simp, simp)+
done

```

the recursion equation for *LList-corec* – NOT SUITABLE FOR REWRITING!

lemma *LList-corec*:

```

  LList-corec a f =
    (case f a of None => NIL | Some(z,w) => CONS z (LList-corec w f))
by (rule equalityI LList-corec-subset1 LList-corec-subset2)+

```

definitional version of same

lemma *def-LList-corec*:

```

  [| !!x. h(x) == LList-corec x f |]
  ==> h(a) = (case f a of None => NIL | Some(z,w) => CONS z (h w))
by (simp add: LList-corec)

```

A typical use of co-induction to show membership in the *gfp*. Bisimulation is *range*(%x. *LList-corec* x f)

lemma *LList-corec-type*: *LList-corec* a f ∈ *lList* UNIV

```

apply (rule-tac X = range (%x. LList-corec x ?g) in lList-coinduct)
apply (rule rangeI, safe)
apply (subst LList-corec, simp)
done

```

11.3 *lList* equality as a *gfp*; the bisimulation principle

This theorem is actually used, unlike the many similar ones in ZF

```

lemma LListD-unfold: LListD r = dsum (diag {Numb 0}) (dprod r (LListD r))
  by (fast intro!: LListD.intros [unfolded NIL-def CONS-def]
    elim: LListD.cases [unfolded NIL-def CONS-def])

```

```

lemma LListD-implies-ntrunc-equality [rule-format]:
   $\forall M N. (M, N) \in \text{LListD}(\text{diag } A) \longrightarrow \text{ntrunc } k \, M = \text{ntrunc } k \, N$ 
apply (induct-tac k rule: nat-less-induct)
apply (safe del: equalityI)
apply (erule LListD.cases)
apply (safe del: equalityI)
apply (case-tac n, simp)
apply (rename-tac n')
apply (case-tac n')
apply (simp-all add: CONS-def less-Suc-eq)
done

```

The domain of the *LListD* relation

```

lemma Domain-LListD:
   $\text{Domain } (\text{LListD}(\text{diag } A)) \leq \text{llist}(A)$ 
apply (unfold llist.defs NIL-def CONS-def)
apply (rule gfp-upperbound)

```

avoids unfolding *LListD* on the rhs

```

apply (rule-tac  $P = \%x. \text{Domain } x \leq ?B$  in LListD-unfold [THEN ssubst],
simp)
apply blast
done

```

This inclusion justifies the use of coinduction to show $M = N$

```

lemma LListD-subset-diag:  $\text{LListD}(\text{diag } A) \leq \text{diag}(\text{llist}(A))$ 
apply (rule subsetI)
apply (rule-tac  $p = x$  in PairE, safe)
apply (rule diag-eqI)
apply (rule LListD-implies-ntrunc-equality [THEN ntrunc-equality], assumption)
apply (erule DomainI [THEN Domain-LListD [THEN subsetD]])
done

```

11.3.1 Coinduction, using *LListD-Fun*

THE COINDUCTIVE DEFINITION PACKAGE COULD DO THIS!

```

lemma LListD-Fun-mono:  $A \leq B \implies \text{LListD-Fun } r \, A \leq \text{LListD-Fun } r \, B$ 
apply (unfold LListD-Fun-def)
apply (assumption | rule basic-monos)
done

```

```

lemma LListD-coinduct:
   $[\![ \, M \in X; \, X \leq \text{LListD-Fun } r \, (X \text{ Un } \text{LListD}(r)) \, ]\!] \implies M \in \text{LListD}(r)$ 
apply (unfold LListD-Fun-def)
apply (erule LListD.coinduct)
apply (erule subsetD [THEN CollectD], assumption)
done

```

lemma *LListD-Fun-NIL-I*: $(NIL, NIL) \in LListD-Fun\ r\ s$
by (*unfold LListD-Fun-def NIL-def, fast*)

lemma *LListD-Fun-CONS-I*:
 $[[\ x \in A; \ (M, N):s \] \implies (CONS\ x\ M, CONS\ x\ N) \in LListD-Fun\ (diag\ A)\ s]$
apply (*unfold LListD-Fun-def CONS-def, blast*)
done

Utilise the "strong" part, i.e. $gfp(f)$

lemma *LListD-Fun-LListD-I*:
 $M \in LListD(r) \implies M \in LListD-Fun\ r\ (X\ Un\ LListD(r))$
apply (*unfold LListD.defs LListD-Fun-def*)
apply (*rule gfp-fun-UnI2*)
apply (*rule monoI, blast*)
apply *assumption*
done

This converse inclusion helps to strengthen *LList-equalityI*

lemma *diag-subset-LListD*: $diag(llist(A)) \leq LListD(diag\ A)$
apply (*rule subsetI*)
apply (*erule LListD-coinduct*)
apply (*rule subsetI*)
apply (*erule diagE*)
apply (*erule ssubst*)
apply (*erule llist.cases*)
apply (*simp-all add: diagI LListD-Fun-NIL-I LListD-Fun-CONS-I*)
done

lemma *LListD-eq-diag*: $LListD(diag\ A) = diag(llist(A))$
apply (*rule equalityI LListD-subset-diag diag-subset-LListD*)
done

lemma *LListD-Fun-diag-I*: $M \in llist(A) \implies (M, M) \in LListD-Fun\ (diag\ A)\ (X\ Un\ diag(llist(A)))$
apply (*rule LListD-eq-diag [THEN subst]*)
apply (*rule LListD-Fun-LListD-I*)
apply (*simp add: LListD-eq-diag diagI*)
done

11.3.2 To show two LLists are equal, exhibit a bisimulation! [also admits true equality] Replace A by some particular set, like $\{x. True\}$???

lemma *LList-equalityI*:
 $[[\ (M, N) \in r; \ r \leq LListD-Fun\ (diag\ A)\ (r\ Un\ diag(llist(A))) \] \implies M = N]$
apply (*rule LListD-subset-diag [THEN subsetD, THEN diagE]*)
apply (*erule LListD-coinduct*)
apply (*simp add: LListD-eq-diag, safe*)

done

11.4 Finality of $l\text{list}(A)$: Uniqueness of functions defined by corecursion

We must remove *Pair-eq* because it may turn an instance of reflexivity $(h1\ b, h2\ b) = (h1\ ?x17, h2\ ?x17)$ into a conjunction! (or strengthen the Solver?)

declare *Pair-eq* [*simp del*]

abstract proof using a bisimulation

lemma *LList-corec-unique*:

$[[\text{!!}x. h1(x) = (\text{case } f\ x \text{ of } \text{None} \Rightarrow \text{NIL} \mid \text{Some}(z,w) \Rightarrow \text{CONS } z\ (h1\ w));$
 $\text{!!}x. h2(x) = (\text{case } f\ x \text{ of } \text{None} \Rightarrow \text{NIL} \mid \text{Some}(z,w) \Rightarrow \text{CONS } z\ (h2\ w)) \]]$
 $\Rightarrow h1=h2$

apply (*rule ext*)

next step avoids an unknown (and flexflex pair) in simplification

apply (*rule-tac* $A = \text{UNIV}$ **and** $r = \text{range}(\%u. (h1\ u, h2\ u))$
in *LList-equalityI*)

apply (*rule rangeI, safe*)

apply (*simp add: LListD-Fun-NIL-I UNIV-I [THEN LListD-Fun-CONS-I]*)

done

lemma *equals-LList-corec*:

$[[\text{!!}x. h(x) = (\text{case } f\ x \text{ of } \text{None} \Rightarrow \text{NIL} \mid \text{Some}(z,w) \Rightarrow \text{CONS } z\ (h\ w)) \]]$
 $\Rightarrow h = (\%x. \text{LList-corec } x\ f)$

by (*simp add: LList-corec-unique LList-corec*)

11.4.1 Obsolete proof of *LList-corec-unique*: complete induction, not coinduction

lemma *ntrunc-one-CONS* [*simp*]: $\text{ntrunc } (\text{Suc } 0) (\text{CONS } M\ N) = \{\}$

by (*simp add: CONS-def ntrunc-one-In1*)

lemma *ntrunc-CONS* [*simp*]:

$\text{ntrunc } (\text{Suc}(\text{Suc}(k))) (\text{CONS } M\ N) = \text{CONS } (\text{ntrunc } k\ M) (\text{ntrunc } k\ N)$

by (*simp add: CONS-def*)

lemma

assumes *prem1*:

$\text{!!}x. h1\ x = (\text{case } f\ x \text{ of } \text{None} \Rightarrow \text{NIL} \mid \text{Some}(z,w) \Rightarrow \text{CONS } z\ (h1\ w))$

and *prem2*:

$\text{!!}x. h2\ x = (\text{case } f\ x \text{ of } \text{None} \Rightarrow \text{NIL} \mid \text{Some}(z,w) \Rightarrow \text{CONS } z\ (h2\ w))$

shows $h1=h2$

apply (*rule ntrunc-equality [THEN ext]*)

apply (*rule-tac* $x = x$ **in** *spec*)

apply (*induct-tac* k *rule: nat-less-induct*)

```

apply (rename-tac n)
apply (rule allI)
apply (subst prem1)
apply (subst prem2, simp)
apply (intro strip)
apply (case-tac n)
apply (rename-tac [2] m)
apply (case-tac [2] m)
apply simp-all
done

```

11.5 Lconst: defined directly by lfp

But it could be defined by corecursion.

```

lemma Lconst-fun-mono: mono(CONS(M))
apply (rule monoI subset-refl CONS-mono)+
apply assumption
done

```

$Lconst(M) = CONS\ M\ (Lconst\ M)$

```

lemmas Lconst = Lconst-fun-mono [THEN Lconst-def [THEN def-lfp-unfold]]

```

A typical use of co-induction to show membership in the gfp. The containing set is simply the singleton $\{Lconst(M)\}$.

```

lemma Lconst-type:  $M \in A \implies Lconst(M): llist(A)$ 
apply (rule singletonI [THEN llist-coinduct], safe)
apply (rule-tac P = %u. u ∈ ?A in Lconst [THEN ssubst])
apply (assumption | rule list-Fun-CONS-I singletonI UnI1)+
done

```

```

lemma Lconst-eq-LList-corec:  $Lconst(M) = LList-corec\ M\ (\%x. Some(x,x))$ 
apply (rule equals-LList-corec [THEN fun-cong], simp)
apply (rule Lconst)
done

```

Thus we could have used gfp in the definition of Lconst

```

lemma gfp-Lconst-eq-LList-corec:  $gfp(\%N. CONS\ M\ N) = LList-corec\ M\ (\%x. Some(x,x))$ 
apply (rule equals-LList-corec [THEN fun-cong], simp)
apply (rule Lconst-fun-mono [THEN gfp-unfold])
done

```

11.6 Isomorphisms

```

lemma LListI:  $x \in llist\ (range\ Leaf) \implies x \in LList$ 
by (unfold LList-def, simp)

```

```

lemma LListD:  $x \in LList \implies x \in llist\ (range\ Leaf)$ 
by (unfold LList-def, simp)

```

11.6.1 Distinctness of constructors

```
lemma LCons-not-LNil [iff]:  $\sim$  LCons  $x$   $xs$  = LNil
apply (unfold LNil-def LCons-def)
apply (subst Abs-LList-inject)
apply (rule llist.intros CONS-not-NIL rangeI LListI Rep-LList [THEN LListD])+
done
```

```
lemmas LNil-not-LCons [iff] = LCons-not-LNil [THEN not-sym, standard]
```

11.6.2 llist constructors

```
lemma Rep-LList-LNil: Rep-LList LNil = NIL
apply (unfold LNil-def)
apply (rule llist.NIL-I [THEN LListI, THEN Abs-LList-inverse])
done
```

```
lemma Rep-LList-LCons: Rep-LList(LCons  $x$   $l$ ) = CONS (Leaf  $x$ ) (Rep-LList  $l$ )
apply (unfold LCons-def)
apply (rule llist.CONST-I [THEN LListI, THEN Abs-LList-inverse]
      rangeI Rep-LList [THEN LListD])+
done
```

11.6.3 Injectiveness of CONS and LCons

```
lemma CONS-CONS-eq2: (CONS  $M$   $N$  = CONS  $M'$   $N'$ ) = ( $M=M'$  &  $N=N'$ )
apply (unfold CONS-def)
apply (fast elim!: Scons-inject)
done
```

```
lemmas CONS-inject = CONS-CONS-eq [THEN iffD1, THEN conjE, standard]
```

For reasoning about abstract llist constructors

```
declare Rep-LList [THEN LListD, intro] LListI [intro]
declare llist.intros [intro]
```

```
lemma LCons-LCons-eq [iff]: (LCons  $x$   $xs$  = LCons  $y$   $ys$ ) = ( $x=y$  &  $xs=ys$ )
apply (unfold LCons-def)
apply (subst Abs-LList-inject)
apply (auto simp add: Rep-LList-inject)
done
```

```
lemma CONS-D2: CONS  $M$   $N$   $\in$  llist( $A$ ) ==>  $M \in A$  &  $N \in$  llist( $A$ )
apply (erule llist.cases)
apply (erule CONS-neq-NIL, fast)
done
```

11.7 Reasoning about llist(A)

A special case of *list-equality* for functions over lazy lists


```

lemma LList-fun-equalityI:
  [|  $M \in \text{llist}(A)$ ;  $g(\text{NIL}) : \text{llist}(A)$ ;
     $f(\text{NIL}) = g(\text{NIL})$ ;
    !! $x\ l$ . [|  $x \in A$ ;  $l \in \text{llist}(A)$  |] ==>
      ( $f(\text{CONS } x\ l), g(\text{CONS } x\ l) \in$ 
         $\text{LListD-Fun } (\text{diag } A) ((\%u. (f(u), g(u))) \text{llist}(A) \text{Un}$ 
           $\text{diag}(\text{llist}(A)))$ 
      |] ==>  $f(M) = g(M)$ 
apply (rule LList-equalityI)
apply (erule imageI)
apply (rule image-subsetI)
apply (erule-tac  $aa=x$  in llist.cases)
apply (erule ssubst, erule ssubst, erule LListD-Fun-diag-I, blast)
done

```

11.8 The functional *Lmap*

```

lemma Lmap-NIL [simp]:  $Lmap\ f\ \text{NIL} = \text{NIL}$ 
by (rule Lmap-def [THEN def-LList-corec, THEN trans], simp)

```

```

lemma Lmap-CONS [simp]:  $Lmap\ f\ (\text{CONS } M\ N) = \text{CONS } (f\ M)\ (Lmap\ f\ N)$ 
by (rule Lmap-def [THEN def-LList-corec, THEN trans], simp)

```

Another type-checking proof by coinduction

```

lemma Lmap-type:
  [|  $M \in \text{llist}(A)$ ; !! $x$ .  $x \in A \implies f(x) : B$  |] ==>  $Lmap\ f\ M \in \text{llist}(B)$ 
apply (erule imageI [THEN llist-coinduct], safe)
apply (erule llist.cases, simp-all)
done

```

This type checking rule synthesises a sufficiently large set for *f*

```

lemma Lmap-type2:  $M \in \text{llist}(A) \implies Lmap\ f\ M \in \text{llist}(f'A)$ 
apply (erule Lmap-type)
apply (erule imageI)
done

```

11.8.1 Two easy results about *Lmap*

```

lemma Lmap-compose:  $M \in \text{llist}(A) \implies Lmap\ (f\ o\ g)\ M = Lmap\ f\ (Lmap\ g\ M)$ 
apply (unfold o-def)
apply (erule imageI)
apply (erule LList-equalityI, safe)
apply (erule llist.cases, simp-all)
apply (rule LListD-Fun-NIL-I imageI UnI1 rangeI [THEN LListD-Fun-CONS-I])
apply assumption
done

```

```

lemma Lmap-ident:  $M \in \text{llist}(A) \implies Lmap\ (\%x. x)\ M = M$ 

```

```

apply (drule imageI)
apply (erule LList-equalityI, safe)
apply (erule llist.cases, simp-all)
apply (rule LListD-Fun-NIL-I imageI UnI1 rangeI [THEN LListD-Fun-CONS-I]) +
apply assumption
done

```

11.9 Lappend – its two arguments cause some complications!

```

lemma Lappend-NIL-NIL [simp]: Lappend NIL NIL = NIL
apply (unfold Lappend-def)
apply (rule LList-corec [THEN trans], simp)
done

```

```

lemma Lappend-NIL-CONS [simp]:
  Lappend NIL (CONS N N') = CONS N (Lappend NIL N')
apply (unfold Lappend-def)
apply (rule LList-corec [THEN trans], simp)
done

```

```

lemma Lappend-CONS [simp]:
  Lappend (CONS M M') N = CONS M (Lappend M' N)
apply (unfold Lappend-def)
apply (rule LList-corec [THEN trans], simp)
done

```

```

declare llist.intros [simp] LListD-Fun-CONS-I [simp]
  range-eqI [simp] image-eqI [simp]

```

```

lemma Lappend-NIL [simp]:  $M \in \text{llist}(A) \implies \text{Lappend NIL } M = M$ 
by (erule LList-fun-equalityI, simp-all)

```

```

lemma Lappend-NIL2:  $M \in \text{llist}(A) \implies \text{Lappend } M \text{ NIL} = M$ 
by (erule LList-fun-equalityI, simp-all)

```

11.9.1 Alternative type-checking proofs for Lappend

weak co-induction: bisimulation and case analysis on both variables

```

lemma Lappend-type:  $[| M \in \text{llist}(A); N \in \text{llist}(A) |] \implies \text{Lappend } M \text{ } N \in \text{llist}(A)$ 
apply (rule-tac  $X = \bigcup u \in \text{llist}(A) . \bigcup v \in \text{llist}(A) . \{\text{Lappend } u \text{ } v\}$  in llist-coinduct)
apply fast
apply safe
apply (erule-tac  $aa = u$  in llist.cases)
apply (erule-tac  $aa = v$  in llist.cases, simp-all)
apply blast
done

```

strong co-induction: bisimulation and case analysis on one variable

```

lemma Lappend-type': [|  $M \in \text{llist}(A)$ ;  $N \in \text{llist}(A)$  |] ==> Lappend  $M$   $N \in \text{llist}(A)$ 
apply (rule-tac  $X = (\%u. \text{Lappend } u \ N) \ \text{llist } (A)$  in llist-coinduct)
apply (erule imageI)
apply (rule image-subsetI)
apply (erule-tac  $aa = x$  in llist.cases)
apply (simp add: list-Fun-llist-I, simp)
done

```

11.10 Lazy lists as the type 'a llist – strongly typed versions of above

11.10.1 *llist-case*: case analysis for 'a llist

```

declare LListI [THEN Abs-LList-inverse, simp]
declare Rep-LList-inverse [simp]
declare Rep-LList [THEN LListD, simp]
declare rangeI [simp] inj-Leaf [simp]

```

```

lemma llist-case-LNil [simp]: llist-case  $c$   $d$   $LNil = c$ 
by (unfold llist-case-def LNil-def, simp)

```

```

lemma llist-case-LCons [simp]:
  llist-case  $c$   $d$  (LCons  $M$   $N$ ) =  $d \ M \ N$ 
apply (unfold llist-case-def LCons-def, simp)
done

```

Elimination is case analysis, not induction.

```

lemma llistE: [|  $l = LNil \Rightarrow P$ ;  $\forall x \ l'. \ l = LCons \ x \ l' \Rightarrow P$  |] ==>  $P$ 
apply (rule Rep-LList [THEN LListD, THEN llist.cases])
apply (simp add: Rep-LList-LNil [symmetric] Rep-LList-inject)
apply blast
apply (erule LListI [THEN Rep-LList-cases], clarify)
apply (simp add: Rep-LList-LCons [symmetric] Rep-LList-inject, blast)
done

```

11.10.2 *llist-corec*: corecursion for 'a llist

Lemma for the proof of *llist-corec*

```

lemma LList-corec-type2:
  LList-corec  $a$ 
    ( $\%z. \text{case } f \ z \text{ of } None \Rightarrow None \mid \text{Some}(v,w) \Rightarrow \text{Some}(\text{Leaf}(v),w)$ )
     $\in \text{llist}(\text{range } \text{Leaf})$ 
apply (rule-tac  $X = \text{range } (\%x. \text{LList-corec } x \ ?g)$  in llist-coinduct)
apply (rule rangeI, safe)
apply (subst LList-corec, force)
done

```

```

lemma llist-corec:

```

```

    llist-corec a f =
      (case f a of None => LNil | Some(z,w) => LCons z (llist-corec w f))
  apply (unfold llist-corec-def LNil-def LCons-def)
  apply (subst LList-corec)
  apply (case-tac f a)
  apply (simp add: LList-corec-type2)
  apply (force simp add: LList-corec-type2)
done

```

definitional version of same

```

lemma def-llist-corec:
  [| !!x. h(x) == llist-corec x f |] ==>
    h(a) = (case f a of None => LNil | Some(z,w) => LCons z (h w))
by (simp add: llist-corec)

```

11.11 Proofs about type 'a llist functions

11.12 Deriving llist-equalityI – llist equality is a bisimulation

```

lemma LListD-Fun-subset-Times-llist:
  r <= (llist A) <*> (llist A)
  ==> LListD-Fun (diag A) r <= (llist A) <*> (llist A)
by (auto simp add: LListD-Fun-def)

```

```

lemma subset-Times-llist:
  prod-fun Rep-LList Rep-LList ‘ r <=
    (llist(range Leaf)) <*> (llist(range Leaf))
by (blast intro: Rep-LList [THEN LListD])

```

```

lemma prod-fun-lemma:
  r <= (llist(range Leaf)) <*> (llist(range Leaf))
  ==> prod-fun (Rep-LList o Abs-LList) (Rep-LList o Abs-LList) ‘ r <= r
apply safe
apply (erule subsetD [THEN SigmaE2], assumption)
apply (simp add: LListI [THEN Abs-LList-inverse])
done

```

```

lemma prod-fun-range-eq-diag:
  prod-fun Rep-LList Rep-LList ‘ range(%x. (x, x)) =
    diag(llist(range Leaf))
apply (rule equalityI, blast)
apply (fast elim: LListI [THEN Abs-LList-inverse, THEN subst])
done

```

Used with *lfilter*

```

lemma llistD-Fun-mono:
  A <= B ==> llistD-Fun A <= llistD-Fun B
apply (unfold llistD-Fun-def prod-fun-def, auto)
apply (rule image-eqI)

```

```

prefer 2 apply (blast intro: rev-subsetD [OF - LListD-Fun-mono], force)
done

```

11.12.1 To show two llists are equal, exhibit a bisimulation! [also admits true equality]

```

lemma llist-equalityI:
  [| (l1,l2) ∈ r; r ≤ llistD-Fun(r Un range(%x.(x,x))) |] ==> l1=l2
apply (unfold llistD-Fun-def)
apply (rule Rep-LList-inject [THEN iffD1])
apply (rule-tac r = prod-fun Rep-LList Rep-LList 'r and A = range (Leaf) in
  LList-equalityI)
apply (erule prod-fun-imageI)
apply (erule image-mono [THEN subset-trans])
apply (rule image-compose [THEN subst])
apply (rule prod-fun-compose [THEN subst])
apply (subst image-Un)
apply (subst prod-fun-range-eq-diag)
apply (rule LListD-Fun-subset-Times-llist [THEN prod-fun-lemma])
apply (rule subset-Times-llist [THEN Un-least])
apply (rule diag-subset-Times)
done

```

11.12.2 Rules to prove the 2nd premise of llist-equalityI

```

lemma llistD-Fun-LNil-I [simp]: (LNil,LNil) ∈ llistD-Fun(r)
apply (unfold llistD-Fun-def LNil-def)
apply (rule LListD-Fun-NIL-I [THEN prod-fun-imageI])
done

```

```

lemma llistD-Fun-LCons-I [simp]:
  (l1,l2):r ==> (LCons x l1, LCons x l2) ∈ llistD-Fun(r)
apply (unfold llistD-Fun-def LCons-def)
apply (rule rangeI [THEN LListD-Fun-CONS-I, THEN prod-fun-imageI])
apply (erule prod-fun-imageI)
done

```

Utilise the "strong" part, i.e. $\text{gfp}(f)$

```

lemma llistD-Fun-range-I: (l,l) ∈ llistD-Fun(r Un range(%x.(x,x)))
apply (unfold llistD-Fun-def)
apply (rule Rep-LList-inverse [THEN subst])
apply (rule prod-fun-imageI)
apply (subst image-Un)
apply (subst prod-fun-range-eq-diag)
apply (rule Rep-LList [THEN LListD, THEN LListD-Fun-diag-I])
done

```

A special case of *list-equality* for functions over lazy lists

```

lemma llist-fun-equalityI:

```

```

    [| f(LNil)=g(LNil);
      !!x l. (f(LCons x l),g(LCons x l))
              ∈ llistD-Fun(range(%u. (f(u),g(u))) Un range(%v. (v,v)))
    |] ==> f(l) = (g(l :: 'a llist) :: 'b llist)
  apply (rule-tac r = range (%u. (f (u),g (u))) in llist-equalityI)
  apply (rule rangeI, clarify)
  apply (rule-tac l = u in llistE)
  apply (simp-all add: llistD-Fun-range-I)
done

```

11.13 The functional *lmap*

lemma *lmap-LNil* [simp]: *lmap f LNil = LNil*
by (rule *lmap-def* [THEN *def-llist-corec*, THEN *trans*], *simp*)

lemma *lmap-LCons* [simp]: *lmap f (LCons M N) = LCons (f M) (lmap f N)*
by (rule *lmap-def* [THEN *def-llist-corec*, THEN *trans*], *simp*)

11.13.1 Two easy results about *lmap*

lemma *lmap-compose* [simp]: *lmap (f o g) l = lmap f (lmap g l)*
by (rule-tac *l = l* in *llist-fun-equalityI*, *simp-all*)

lemma *lmap-ident* [simp]: *lmap (%x. x) l = l*
by (rule-tac *l = l* in *llist-fun-equalityI*, *simp-all*)

11.14 *iterates* – *llist-fun-equalityI* cannot be used!

lemma *iterates*: *iterates f x = LCons x (iterates f (f x))*
by (rule *iterates-def* [THEN *def-llist-corec*, THEN *trans*], *simp*)

lemma *lmap-iterates* [simp]: *lmap f (iterates f x) = iterates f (f x)*
apply (rule-tac *r = range (%u. (lmap f (iterates f u),iterates f (f u)))* in *llist-equalityI*)
apply (rule *rangeI*, *safe*)
apply (rule-tac *x1 = f (u)* in *iterates* [THEN *ssubst*])
apply (rule-tac *x1 = u* in *iterates* [THEN *ssubst*], *simp*)
done

lemma *iterates-lmap*: *iterates f x = LCons x (lmap f (iterates f x))*
apply (*subst lmap-iterates*)
apply (rule *iterates*)
done

11.15 A rather complex proof about *iterates* – cf Andy Pitts

11.15.1 Two lemmas about *natrec n x (%m. g)*, which is essentially $(g^n)(x)$

lemma *fun-power-lmap*: *nat-rec (LCons b l) (%m. lmap(f)) n = LCons (nat-rec b (%m. f) n) (nat-rec l (%m. lmap(f)) n)*

apply (*induct-tac* *n*, *simp-all*)
done

lemma *fun-power-Suc*: *nat-rec* (*g x*) (%*m. g*) *n* = *nat-rec* *x* (%*m. g*) (*Suc n*)
by (*induct-tac* *n*, *simp-all*)

lemmas *Pair-cong* = *refl* [*THEN cong*, *THEN cong*, of **concl**: *Pair*]

The bisimulation consists of $\{(lmap(f) \hat{\ }^n (h(u)), lmap(f) \hat{\ }^n (iterates(f,u)))\}$
for all *u* and all *n::nat*.

lemma *iterates-equality*:

(!!*x. h(x) = LCons x (lmap f (h x))*) ==> *h = iterates(f)*

apply (*rule ext*)

apply (*rule-tac*

*r = $\bigcup u. range$ (%*n. (nat-rec (h u) (%*m y. lmap f y*) *n*,
nat-rec (iterates f u) (%*m y. lmap f y*) *n*))**

in *llist-equalityI*)

apply (*rule UN1-I range-eqI Pair-cong nat-rec-0 [symmetric]*)+

apply *clarify*

apply (*subst iterates, atomize*)

apply (*drule-tac x=u in spec*)

apply (*erule ssubst*)

apply (*subst fun-power-lmap*)

apply (*subst fun-power-lmap*)

apply (*rule llistD-Fun-LCons-I*)

apply (*rule lmap-iterates [THEN subst]*)

apply (*subst fun-power-Suc*)

apply (*subst fun-power-Suc, blast*)

done

11.16 *lappend* – its two arguments cause some complications!

lemma *lappend-LNil-LNil* [*simp*]: *lappend LNil LNil = LNil*

apply (*unfold lappend-def*)

apply (*rule llist-corec [THEN trans], simp*)

done

lemma *lappend-LNil-LCons* [*simp*]:

lappend LNil (LCons l l') = LCons l (lappend LNil l')

apply (*unfold lappend-def*)

apply (*rule llist-corec [THEN trans], simp*)

done

lemma *lappend-LCons* [*simp*]:

lappend (LCons l l') N = LCons l (lappend l' N)

apply (*unfold lappend-def*)

apply (*rule llist-corec [THEN trans], simp*)

done

lemma *lappend-LNil* [*simp*]: *lappend LNil l = l*
by (*rule-tac l = l in llist-fun-equalityI, simp-all*)

lemma *lappend-LNil2* [*simp*]: *lappend l LNil = l*
by (*rule-tac l = l in llist-fun-equalityI, simp-all*)

The infinite first argument blocks the second

lemma *lappend-iterates* [*simp*]: *lappend (iterates f x) N = iterates f x*
apply (*rule-tac r = range (%u. (lappend (iterates f u) N, iterates f u))*)
in *llist-equalityI*)
apply (*rule rangeI*)
apply (*safe*)
apply (*subst (1 2) iterates*)
apply *simp*
done

11.16.1 Two proofs that *lmap* distributes over *lappend*

Long proof requiring case analysis on both both arguments

lemma *lmap-lappend-distrib*:
 $lmap\ f\ (lappend\ l\ n) = lappend\ (lmap\ f\ l)\ (lmap\ f\ n)$
apply (*rule-tac r = $\bigcup n. range\ (\%l. (lmap\ f\ (lappend\ l\ n),$*
 $lappend\ (lmap\ f\ l)\ (lmap\ f\ n)))$)
in *llist-equalityI*)
apply (*rule UN1-I*)
apply (*rule rangeI, safe*)
apply (*rule-tac l = l in llistE*)
apply (*rule-tac l = n in llistE, simp-all*)
apply (*blast intro: llistD-Fun-LCons-I*)
done

Shorter proof of theorem above using *llist-equalityI* as strong coinduction

lemma *lmap-lappend-distrib'*:
 $lmap\ f\ (lappend\ l\ n) = lappend\ (lmap\ f\ l)\ (lmap\ f\ n)$
apply (*rule-tac l = l in llist-fun-equalityI, simp*)
apply *simp*
done

Without strong coinduction, three case analyses might be needed

lemma *lappend-assoc'*: *lappend (lappend l1 l2) l3 = lappend l1 (lappend l2 l3)*
apply (*rule-tac l = l1 in llist-fun-equalityI, simp*)
apply *simp*
done

end

12 The "filter" functional for coinductive lists – defined by a combination of induction and coinduction

```
theory LFilter imports LList begin
```

consts

$$findRel \quad :: ('a \Rightarrow bool) \Rightarrow ('a\ list * 'a\ list) \Rightarrow set$$

inductive *findRel* *p*

intros

$$found: p\ x ==> (LCons\ x\ l, LCons\ x\ l) \in findRel\ p$$
$$seek: \quad [\sim p \ x; \ (l, l') \in findRel \ p \] \implies (LCons \ x \ l, \ l') \in findRel \ p$$

```
declare findRel.intros [intro]
```

constdefs

$$find \quad :: ['a \Rightarrow bool, 'a\ list] \Rightarrow 'a\ list$$
$$find\ p\ l == @l'. (l, l'): findRel\ p \mid (l' = LNil \ \& \ l \sim: Domain(findRel\ p))$$
$$lfilter :: ['a \Rightarrow bool, 'a\ llist] \Rightarrow 'a\ llist$$
$$lfilter\ p\ l == llist-corec\ l\ (\%l.\ case\ find\ p\ l\ of$$

```
LNil => None
```

$$| LCons\ y\ z \Rightarrow Some(y,z))$$

12.1 *findRel*: basic laws

inductive-cases

$$findRel-LConsE \text{ [elim!]}: (LCons \ x \ l, l'') \in findRel \ p$$

lemma *findRel-functional* [rule-format]:

$$(l, l'): \text{findRel } p ==> (l, l''): \text{findRel } p \dashv\dashv l'' = l'$$

```
by (erule findRel.induct, auto)
```

lemma *findRel-imp-LCons* [rule-format]:

$$(l, l'): findRel\ p ==> \exists x\ l''.\ l' = LCons\ x\ l'' \ \&\ p\ x$$
`by (erule findRel.induct, auto)`

lemma *findRel-LNil* [*elim!*]: $(LNil, l): findRel\ p ==> R$

by (*blast elim: findRel.cases*)

12.2 Properties of $\text{Domain } (findRel\ p)$

lemma *LCons-Domain-findRel* [simp]:

$$LCons\ x\ l \in Domain(findRel\ p) = (p\ x \mid l \in Domain(findRel\ p))$$
by *auto*

lemma *Domain-findRel-iff*:

$(l \in \text{Domain } (\text{findRel } p)) = (\exists x l'. (l, \text{LCons } x l') \in \text{findRel } p \ \& \ p \ x)$
by (*blast dest: findRel-imp-LCons*)

lemma *Domain-findRel-mono*:

$[!x. p \ x ==> q \ x] ==> \text{Domain } (\text{findRel } p) \leq \text{Domain } (\text{findRel } q)$
apply *clarify*
apply (*erule findRel.induct, blast+*)
done

12.3 *find*: basic equations

lemma *find-LNil [simp]*: $\text{find } p \ \text{LNil} = \text{LNil}$
by (*unfold find-def, blast*)

lemma *findRel-imp-find [simp]*: $(l, l') \in \text{findRel } p ==> \text{find } p \ l = l'$
apply (*unfold find-def*)
apply (*blast dest: findRel-functional*)
done

lemma *find-LCons-found*: $p \ x ==> \text{find } p \ (\text{LCons } x \ l) = \text{LCons } x \ l$
by (*blast intro: findRel-imp-find*)

lemma *diverge-find-LNil [simp]*: $l \sim: \text{Domain}(\text{findRel } p) ==> \text{find } p \ l = \text{LNil}$
by (*unfold find-def, blast*)

lemma *find-LCons-seek*: $\sim (p \ x) ==> \text{find } p \ (\text{LCons } x \ l) = \text{find } p \ l$
apply (*case-tac LCons x l \in Domain (findRel p)*)
apply *auto*
apply (*blast intro: findRel-imp-find*)
done

lemma *find-LCons [simp]*:
 $\text{find } p \ (\text{LCons } x \ l) = (\text{if } p \ x \text{ then } \text{LCons } x \ l \text{ else } \text{find } p \ l)$
by (*simp add: find-LCons-seek find-LCons-found*)

12.4 *lfilter*: basic equations

lemma *lfilter-LNil [simp]*: $\text{lfilter } p \ \text{LNil} = \text{LNil}$
by (*rule lfilter-def [THEN def-llist-corec, THEN trans], simp*)

lemma *diverge-lfilter-LNil [simp]*:
 $l \sim: \text{Domain}(\text{findRel } p) ==> \text{lfilter } p \ l = \text{LNil}$
by (*rule lfilter-def [THEN def-llist-corec, THEN trans], simp*)

lemma *lfilter-LCons-found*:
 $p \ x ==> \text{lfilter } p \ (\text{LCons } x \ l) = \text{LCons } x \ (\text{lfilter } p \ l)$
by (*rule lfilter-def [THEN def-llist-corec, THEN trans], simp*)

lemma *findRel-imp-lfilter [simp]*:
 $(l, \text{LCons } x \ l') \in \text{findRel } p ==> \text{lfilter } p \ l = \text{LCons } x \ (\text{lfilter } p \ l')$

```

by (rule lfilter-def [THEN def-llist-corec, THEN trans], simp)

lemma lfilter-LCons-seek:  $\sim (p\ x) \implies \text{lfilter } p\ (LCons\ x\ l) = \text{lfilter } p\ l$ 
apply (rule lfilter-def [THEN def-llist-corec, THEN trans], simp)
apply (case-tac  $LCons\ x\ l \in Domain\ (findRel\ p)$  )
  apply (simp add: Domain-findRel-iff, auto)
done

lemma lfilter-LCons [simp]:
  lfilter p (LCons x l) =
    (if p x then LCons x (lfilter p l) else lfilter p l)
by (simp add: lfilter-LCons-found lfilter-LCons-seek)

declare llistD-Fun-LNil-I [intro!] llistD-Fun-LCons-I [intro!]

lemma lfilter-eq-LNil:  $\text{lfilter } p\ l = LNil \implies l \sim: Domain(findRel\ p)$ 
apply (auto iff: Domain-findRel-iff)
done

lemma lfilter-eq-LCons [rule-format]:
  lfilter p l = LCons x l'  $\implies$ 
    ( $\exists l''. l' = \text{lfilter } p\ l'' \ \& \ (l, LCons\ x\ l'') \in findRel\ p$ )
apply (subst lfilter-def [THEN def-llist-corec])
apply (case-tac  $l \in Domain\ (findRel\ p)$  )
  apply (auto iff: Domain-findRel-iff)
done

lemma lfilter-cases:  $\text{lfilter } p\ l = LNil \mid$ 
  ( $\exists y\ l'. \text{lfilter } p\ l = LCons\ y\ (\text{lfilter } p\ l') \ \& \ p\ y$ )
apply (case-tac  $l \in Domain\ (findRel\ p)$  )
apply (auto iff: Domain-findRel-iff)
done

```

12.5 lfilter: simple facts by coinduction

```

lemma lfilter-K-True:  $\text{lfilter } (\%x. True)\ l = l$ 
by (rule-tac  $l = l$  in llist-fun-equalityI, simp-all)

lemma lfilter-idem:  $\text{lfilter } p\ (\text{lfilter } p\ l) = \text{lfilter } p\ l$ 
apply (rule-tac  $l = l$  in llist-fun-equalityI, simp-all)
apply safe

```

Cases: $p\ x$ is true or false

```

apply (rule lfilter-cases [THEN disjE])
  apply (erule ssubst, auto)
done

```

12.6 Numerous lemmas required to prove *lfilter-conj*

lemma *findRel-conj-lemma* [rule-format]:

$(l, l') \in \text{findRel } q$
 $\implies l' = LCons\ x\ l'' \dashrightarrow p\ x \dashrightarrow (l, l') \in \text{findRel } (\%x. p\ x \ \&\ q\ x)$

by (*erule findRel.induct, auto*)

lemmas *findRel-conj* = *findRel-conj-lemma* [*OF - refl*]

lemma *findRel-not-conj-Domain* [rule-format]:

$(l, l') \in \text{findRel } (\%x. p\ x \ \&\ q\ x)$
 $\implies (l, LCons\ x\ l') \in \text{findRel } q \dashrightarrow \sim p\ x \dashrightarrow$
 $l' \in \text{Domain } (\text{findRel } (\%x. p\ x \ \&\ q\ x))$

by (*erule findRel.induct, auto*)

lemma *findRel-conj2* [rule-format]:

$(l, lxx) \in \text{findRel } q$
 $\implies lxx = LCons\ x\ lx \dashrightarrow (lx, lz) \in \text{findRel } (\%x. p\ x \ \&\ q\ x) \dashrightarrow \sim p\ x$
 $\dashrightarrow (l, lz) \in \text{findRel } (\%x. p\ x \ \&\ q\ x)$

by (*erule findRel.induct, auto*)

lemma *findRel-lfilter-Domain-conj* [rule-format]:

$(lx, ly) \in \text{findRel } p$
 $\implies \forall l. lx = \text{lfilter } q\ l \dashrightarrow l \in \text{Domain } (\text{findRel } (\%x. p\ x \ \&\ q\ x))$

apply (*erule findRel.induct*)

apply (*blast dest!: sym [THEN lfilter-eq-LCons] intro: findRel-conj, auto*)

apply (*drule sym [THEN lfilter-eq-LCons], auto*)

apply (*drule spec*)

apply (*drule refl [THEN rev-mp]*)

apply (*blast intro: findRel-conj2*)

done

lemma *findRel-conj-lfilter* [rule-format]:

$(l, l'') \in \text{findRel } (\%x. p\ x \ \&\ q\ x)$
 $\implies l'' = LCons\ y\ l' \dashrightarrow$
 $(\text{lfilter } q\ l, LCons\ y\ (\text{lfilter } q\ l')) \in \text{findRel } p$

by (*erule findRel.induct, auto*)

lemma *lfilter-conj-lemma*:

$(\text{lfilter } p\ (\text{lfilter } q\ l), \text{lfilter } (\%x. p\ x \ \&\ q\ x)\ l)$
 $\in \text{lListD-Fun } (\text{range } (\%u. (\text{lfilter } p\ (\text{lfilter } q\ u),$
 $\text{lfilter } (\%x. p\ x \ \&\ q\ x)\ u)))$

apply (*case-tac l \in Domain (findRel q)*)

apply (*subgoal-tac [2] l \sim: Domain (findRel (%x. p x \& q x))*)

prefer 3 apply (*blast intro: rev-subsetD [OF - Domain-findRel-mono]*)

There are no *qs* in *l*: both lists are *LNil*

apply (*simp-all add: Domain-findRel-iff, clarify*)

```

case q x
apply (case-tac p x)
apply (simp-all add: findRel-conj [THEN findRel-imp-lfilter])

case q x and  $\sim(p\ x)$ 
apply (case-tac  $l' \in \text{Domain } (\text{findRel } (\%x. p\ x \ \&\ q\ x))$ )

subcase: there is no  $p \ \&\ q$  in  $l'$  and therefore none in  $l$ 

apply (subgoal-tac [2]  $l \sim: \text{Domain } (\text{findRel } (\%x. p\ x \ \&\ q\ x))$ )
prefer 3 apply (blast intro: findRel-not-conj-Domain)
apply (subgoal-tac [2]  $l\text{filter } q\ l' \sim: \text{Domain } (\text{findRel } p)$ )
prefer 3 apply (blast intro: findRel-lfilter-Domain-conj)

... and therefore too, no  $p$  in  $l\text{filter } q\ l'$ . Both results are LNil

apply (simp-all add: Domain-findRel-iff, clarify)

subcase: there is a  $p \ \&\ q$  in  $l'$  and therefore also one in  $l$ 

apply (subgoal-tac ( $l, LCons\ xa\ l'a \in \text{findRel } (\%x. p\ x \ \&\ q\ x)$ ))
prefer 2 apply (blast intro: findRel-conj2)
apply (subgoal-tac ( $l\text{filter } q\ l', LCons\ xa\ (l\text{filter } q\ l'a) \in \text{findRel } p$ ))
apply simp
apply (blast intro: findRel-conj-lfilter)
done

lemma lfilter-conj:  $l\text{filter } p\ (l\text{filter } q\ l) = l\text{filter } (\%x. p\ x \ \&\ q\ x)\ l$ 
apply (rule-tac  $l = l$  in llist-fun-equalityI, simp-all)
apply (blast intro: lfilter-conj-lemma rev-subsetD [OF - llistD-Fun-mono])
done

```

12.7 Numerous lemmas required to prove $l\text{filter } p\ (lmap\ f\ l) = lmap\ f\ (l\text{filter } (\%x. p(f\ x))\ l)$

```

lemma findRel-lmap-Domain:
  ( $l, l' \in \text{findRel } (\%x. p\ (f\ x))$ ) ==>  $lmap\ f\ l \in \text{Domain } (\text{findRel } p)$ 
by (erule findRel.induct, auto)

lemma lmap-eq-LCons [rule-format]:  $lmap\ f\ l = LCons\ x\ l' \dashv\vdash$ 
  ( $\exists y\ l''. x = f\ y \ \&\ l' = lmap\ f\ l'' \ \&\ l = LCons\ y\ l''$ )
apply (subst lmap-def [THEN def-llist-corec])
apply (rule-tac  $l = l$  in llistE, auto)
done

```

```

lemma lmap-LCons-findRel-lemma [rule-format]:
  ( $lx, ly \in \text{findRel } p$ )
  ==>  $\forall l. lmap\ f\ l = lx \dashv\vdash ly = LCons\ x\ l' \dashv\vdash$ 
  ( $\exists y\ l''. x = f\ y \ \&\ l' = lmap\ f\ l'' \ \&$ 

```

```

      (l, LCons y l'') ∈ findRel(%x. p(f x)))
apply (erule findRel.induct, simp-all)
apply (blast dest!: lmap-eq-LCons)+
done

lemmas lmap-LCons-findRel = lmap-LCons-findRel-lemma [OF - refl refl]

lemma lfilter-lmap: lfilter p (lmap f l) = lmap f (lfilter (p o f) l)
apply (rule-tac l = l in llist-fun-equalityI, simp-all)
apply safe
apply (case-tac lmap f l ∈ Domain (findRel p))
  apply (simp add: Domain-findRel-iff, clarify)
  apply (frule lmap-LCons-findRel, force)
apply (subgoal-tac l ~: Domain (findRel (%x. p (f x))), simp)
apply (blast intro: findRel-lmap-Domain)
done

end

```