

Fundamental Properties of Lambda-calculus


Tobias Nipkow
Stefan Berghofer

1st October 2005

Contents

1	Basic definitions of Lambda-calculus	4
1.1	Lambda-terms in de Bruijn notation and substitution	4
1.2	Beta-reduction	4
1.3	Congruence rules	5
1.4	Substitution-lemmas	5
1.5	Equivalence proof for optimized substitution	6
1.6	Preservation theorems	6
2	Abstract commutation and confluence notions	7
2.1	Basic definitions	7
2.2	Basic lemmas	7
2.3	Church-Rosser	9
2.4	Newman's lemma	9
3	Parallel reduction and a complete developments	9
3.1	Parallel reduction	9
3.2	Inclusions	10
3.3	Misc properties of par-beta	10
3.4	Confluence (directly)	10
3.5	Complete developments	10
3.6	Confluence (via complete developments)	11
4	Eta-reduction	11
4.1	Definition of eta-reduction and relatives	11
4.2	Properties of eta, subst and free	12
4.3	Confluence of eta	12
4.4	Congruence rules for eta*	12
4.5	Commutation of beta and eta	13
4.6	Implicit definition of eta	13
4.7	Parallel eta-reduction	14
4.8	n-ary eta-expansion	14

4.9	Elimination rules for parallel eta reduction	15
4.10	Eta-postponement theorem	15
5	Application of a term to a list of terms	15
6	Simply-typed lambda terms	17
6.1	Environments	17
6.2	Types and typing rules	18
6.3	Some examples	19
6.4	Lists of types	19
6.5	n-ary function types	19
6.6	Lifting preserves well-typedness	20
6.7	Substitution lemmas	20
6.8	Subject reduction	20
6.9	Alternative induction rule for types	20
7	Lifting an order to lists of elements	21
8	Lifting beta-reduction to lists	22
9	Inductive characterization of terminating lambda terms	23
9.1	Terminating lambda terms	23
9.2	Every term in IT terminates	23
9.3	Every terminating term is in IT	23
10	Strong normalization for simply-typed lambda calculus	24
10.1	Properties of IT	24
10.2	Well-typed substitution preserves termination	24
10.3	Well-typed terms are strongly normalizing	25
11	Weak normalization for simply-typed lambda calculus	25
11.1	Terms in normal form	25
11.2	Properties of NF	26
11.3	Main theorems	26
11.4	Extracting the program	27
11.5	Generating executable code	31



1 Basic definitions of Lambda-calculus

theory *Lambda* **imports** *Main* **begin**

1.1 Lambda-terms in de Bruijn notation and substitution

datatype *dB* =

Var nat
| *App dB dB* (**infixl** \circ 200)
| *Abs dB*

consts

subst :: [*dB*, *dB*, *nat*] => *dB* (λ [-'/-] [300, 0, 0] 300)
lift :: [*dB*, *nat*] => *dB*

primrec

lift (*Var i*) *k* = (if *i* < *k* then *Var i* else *Var* (*i* + 1))
lift (*s* \circ *t*) *k* = *lift s k* \circ *lift t k*
lift (*Abs s*) *k* = *Abs* (*lift s* (*k* + 1))

primrec

subst-Var: (*Var i*)[*s/k*] =
(if *k* < *i* then *Var* (*i* - 1) else if *i* = *k* then *s* else *Var i*)
subst-App: (*t* \circ *u*)[*s/k*] = *t*[*s/k*] \circ *u*[*s/k*]
subst-Abs: (*Abs t*)[*s/k*] = *Abs* (*t*[*lift s 0 / k+1*])

declare *subst-Var* [*simp del*]

Optimized versions of *subst* and *lift*.

consts

substn :: [*dB*, *dB*, *nat*] => *dB*
liftn :: [*nat*, *dB*, *nat*] => *dB*

primrec

liftn n (*Var i*) *k* = (if *i* < *k* then *Var i* else *Var* (*i* + *n*))
liftn n (*s* \circ *t*) *k* = *liftn n s k* \circ *liftn n t k*
liftn n (*Abs s*) *k* = *Abs* (*liftn n s* (*k* + 1))

primrec

substn (*Var i*) *s k* =
(if *k* < *i* then *Var* (*i* - 1) else if *i* = *k* then *liftn k s 0* else *Var i*)
substn (*t* \circ *u*) *s k* = *substn t s k* \circ *substn u s k*
substn (*Abs t*) *s k* = *Abs* (*substn t s* (*k* + 1))

1.2 Beta-reduction

consts

beta :: (*dB* \times *dB*) *set*

syntax

$-beta :: [dB, dB] ==> bool \text{ (infixl } -> 50)$
 $-beta-rtranc1 :: [dB, dB] ==> bool \text{ (infixl } ->> 50)$
syntax *(latex)*
 $-beta :: [dB, dB] ==> bool \text{ (infixl } \rightarrow_\beta 50)$
 $-beta-rtranc1 :: [dB, dB] ==> bool \text{ (infixl } \rightarrow_\beta^* 50)$
translations
 $s \rightarrow_\beta t == (s, t) \in beta$
 $s \rightarrow_\beta^* t == (s, t) \in beta^*$

inductive beta

intros

$beta \text{ [simp, intro!]: } Abs \ s \circ t \rightarrow_\beta s[t/0]$
 $appL \text{ [simp, intro!]: } s \rightarrow_\beta t ==> s \circ u \rightarrow_\beta t \circ u$
 $appR \text{ [simp, intro!]: } s \rightarrow_\beta t ==> u \circ s \rightarrow_\beta u \circ t$
 $abs \text{ [simp, intro!]: } s \rightarrow_\beta t ==> Abs \ s \rightarrow_\beta Abs \ t$

inductive-cases beta-cases [elim!]:

$Var \ i \rightarrow_\beta t$
 $Abs \ r \rightarrow_\beta s$
 $s \circ t \rightarrow_\beta u$

declare *if-not-P* [simp] *not-less-eq* [simp]
 — don't add *r-into-rtranc1*[intro!]

1.3 Congruence rules

lemma *rtranc1-beta-Abs* [intro!]:

$s \rightarrow_\beta^* s' ==> Abs \ s \rightarrow_\beta^* Abs \ s'$
 $\langle proof \rangle$

lemma *rtranc1-beta-AppL*:

$s \rightarrow_\beta^* s' ==> s \circ t \rightarrow_\beta^* s' \circ t$
 $\langle proof \rangle$

lemma *rtranc1-beta-AppR*:

$t \rightarrow_\beta^* t' ==> s \circ t \rightarrow_\beta^* s \circ t'$
 $\langle proof \rangle$

lemma *rtranc1-beta-App* [intro]:

$[[s \rightarrow_\beta^* s'; t \rightarrow_\beta^* t']] ==> s \circ t \rightarrow_\beta^* s' \circ t'$
 $\langle proof \rangle$

1.4 Substitution-lemmas

lemma *subst-eq* [simp]: $(Var \ k)[u/k] = u$

$\langle proof \rangle$

lemma *subst-gt* [simp]: $i < j ==> (Var \ j)[u/i] = Var \ (j - 1)$

$\langle proof \rangle$

lemma *subst-lt* [*simp*]: $j < i \implies (\text{Var } j)[u/i] = \text{Var } j$
 $\langle \text{proof} \rangle$

lemma *lift-lift* [*rule-format*]:
 $\forall i k. i < k + 1 \dashv\vdash \text{lift } (\text{lift } t \ i) \ (\text{Suc } k) = \text{lift } (\text{lift } t \ k) \ i$
 $\langle \text{proof} \rangle$

lemma *lift-subst* [*simp*]:
 $\forall i j s. j < i + 1 \dashv\vdash \text{lift } (t[s/j]) \ i = (\text{lift } t \ (i + 1)) \ [\text{lift } s \ i / j]$
 $\langle \text{proof} \rangle$

lemma *lift-subst-lt*:
 $\forall i j s. i < j + 1 \dashv\vdash \text{lift } (t[s/j]) \ i = (\text{lift } t \ i) \ [\text{lift } s \ i / j + 1]$
 $\langle \text{proof} \rangle$

lemma *subst-lift* [*simp*]:
 $\forall k s. (\text{lift } t \ k)[s/k] = t$
 $\langle \text{proof} \rangle$

lemma *subst-subst* [*rule-format*]:
 $\forall i j u v. i < j + 1 \dashv\vdash t[\text{lift } v \ i / \text{Suc } j][u[v/j]/i] = t[u/i][v/j]$
 $\langle \text{proof} \rangle$

1.5 Equivalence proof for optimized substitution

lemma *liftn-0* [*simp*]: $\forall k. \text{liftn } 0 \ t \ k = t$
 $\langle \text{proof} \rangle$

lemma *liftn-lift* [*simp*]:
 $\forall k. \text{liftn } (\text{Suc } n) \ t \ k = \text{lift } (\text{liftn } n \ t \ k) \ k$
 $\langle \text{proof} \rangle$

lemma *substn-subst-n* [*simp*]:
 $\forall n. \text{substn } t \ s \ n = t[\text{liftn } n \ s \ 0 / n]$
 $\langle \text{proof} \rangle$

theorem *substn-subst-0*: $\text{substn } t \ s \ 0 = t[s/0]$
 $\langle \text{proof} \rangle$

1.6 Preservation theorems

Not used in Church-Rosser proof, but in Strong Normalization.

theorem *subst-preserves-beta* [*simp*]:
 $r \rightarrow_\beta s \implies (\bigwedge t \ i. r[t/i] \rightarrow_\beta s[t/i])$
 $\langle \text{proof} \rangle$

theorem *subst-preserves-beta'*: $r \rightarrow_{\beta^*} s \implies r[t/i] \rightarrow_{\beta^*} s[t/i]$
 $\langle \text{proof} \rangle$

theorem *lift-preserves-beta* [*simp*]:
 $r \rightarrow_{\beta} s \implies (\bigwedge i. \text{lift } r \ i \rightarrow_{\beta} \text{lift } s \ i)$
<proof>

theorem *lift-preserves-beta'*: $r \rightarrow_{\beta^*} s \implies \text{lift } r \ i \rightarrow_{\beta^*} \text{lift } s \ i$
<proof>

theorem *subst-preserves-beta2* [*simp*]:
 $\bigwedge r \ s \ i. r \rightarrow_{\beta} s \implies t[r/i] \rightarrow_{\beta^*} t[s/i]$
<proof>

theorem *subst-preserves-beta2'*: $r \rightarrow_{\beta^*} s \implies t[r/i] \rightarrow_{\beta^*} t[s/i]$
<proof>

end

2 Abstract commutation and confluence notions

theory *Commutation* imports *Main* begin

2.1 Basic definitions

constdefs
 $\text{square} :: [('a \times 'a) \text{ set}, ('a \times 'a) \text{ set}, ('a \times 'a) \text{ set}, ('a \times 'a) \text{ set}] \Rightarrow \text{bool}$
 $\text{square } R \ S \ T \ U ==$
 $\forall x \ y. (x, y) \in R \longrightarrow (\forall z. (x, z) \in S \longrightarrow (\exists u. (y, u) \in T \wedge (z, u) \in U))$

$\text{commute} :: [('a \times 'a) \text{ set}, ('a \times 'a) \text{ set}] \Rightarrow \text{bool}$
 $\text{commute } R \ S == \text{square } R \ S \ S \ R$

$\text{diamond} :: ('a \times 'a) \text{ set} \Rightarrow \text{bool}$
 $\text{diamond } R == \text{commute } R \ R$

$\text{Church-Rosser} :: ('a \times 'a) \text{ set} \Rightarrow \text{bool}$
 $\text{Church-Rosser } R ==$
 $\forall x \ y. (x, y) \in (R \cup R^{\wedge -1})^* \longrightarrow (\exists z. (x, z) \in R^{\wedge *} \wedge (y, z) \in R^{\wedge *})$

syntax
 $\text{confluent} :: ('a \times 'a) \text{ set} \Rightarrow \text{bool}$

translations
 $\text{confluent } R == \text{diamond } (R^{\wedge *})$

2.2 Basic lemmas

square

lemma *square-sym*: $\text{square } R \ S \ T \ U \implies \text{square } S \ R \ U \ T$

$\langle \text{proof} \rangle$

lemma *square-subset*:

$\llbracket \text{square } R \ S \ T \ U; T \subseteq T' \rrbracket \implies \text{square } R \ S \ T' \ U$
 $\langle \text{proof} \rangle$

lemma *square-reflcl*:

$\llbracket \text{square } R \ S \ T \ (R^{\hat{=}}); S \subseteq T \rrbracket \implies \text{square } (R^{\hat{=}}) \ S \ T \ (R^{\hat{=}})$
 $\langle \text{proof} \rangle$

lemma *square-rtrancl*:

$\text{square } R \ S \ S \ T \implies \text{square } (R^{\hat{*}}) \ S \ S \ (T^{\hat{*}})$
 $\langle \text{proof} \rangle$

lemma *square-rtrancl-reflcl-commute*:

$\text{square } R \ S \ (S^{\hat{*}}) \ (R^{\hat{=}}) \implies \text{commute } (R^{\hat{*}}) \ (S^{\hat{*}})$
 $\langle \text{proof} \rangle$

commute

lemma *commute-sym*: $\text{commute } R \ S \implies \text{commute } S \ R$

$\langle \text{proof} \rangle$

lemma *commute-rtrancl*: $\text{commute } R \ S \implies \text{commute } (R^{\hat{*}}) \ (S^{\hat{*}})$

$\langle \text{proof} \rangle$

lemma *commute-Un*:

$\llbracket \text{commute } R \ T; \text{commute } S \ T \rrbracket \implies \text{commute } (R \cup S) \ T$
 $\langle \text{proof} \rangle$

diamond, confluence, and union

lemma *diamond-Un*:

$\llbracket \text{diamond } R; \text{diamond } S; \text{commute } R \ S \rrbracket \implies \text{diamond } (R \cup S)$
 $\langle \text{proof} \rangle$

lemma *diamond-confluent*: $\text{diamond } R \implies \text{confluent } R$

$\langle \text{proof} \rangle$

lemma *square-reflcl-confluent*:

$\text{square } R \ R \ (R^{\hat{=}}) \ (R^{\hat{=}}) \implies \text{confluent } R$
 $\langle \text{proof} \rangle$

lemma *confluent-Un*:

$\llbracket \text{confluent } R; \text{confluent } S; \text{commute } (R^{\hat{*}}) \ (S^{\hat{*}}) \rrbracket \implies \text{confluent } (R \cup S)$
 $\langle \text{proof} \rangle$

lemma *diamond-to-confluence*:

$\llbracket \text{diamond } R; T \subseteq R; R \subseteq T^{\hat{*}} \rrbracket \implies \text{confluent } T$
 $\langle \text{proof} \rangle$

2.3 Church-Rosser

lemma *Church-Rosser-confluent*: Church-Rosser $R = \text{confluent } R$
 $\langle \text{proof} \rangle$

2.4 Newman's lemma

Proof by Stefan Berghofer

theorem *newman*:
assumes $wf: wf \ (R^{-1})$
and $lc: \bigwedge a \ b \ c. (a, b) \in R \implies (a, c) \in R \implies$
 $\exists d. (b, d) \in R^* \wedge (c, d) \in R^*$
shows $\bigwedge b \ c. (a, b) \in R^* \implies (a, c) \in R^* \implies$
 $\exists d. (b, d) \in R^* \wedge (c, d) \in R^*$
 $\langle \text{proof} \rangle$

Alternative version. Partly automated by Tobias Nipkow. Takes 2 minutes (2002).

This is the maximal amount of automation possible at the moment.

theorem *newman'*:
assumes $wf: wf \ (R^{-1})$
and $lc: \bigwedge a \ b \ c. (a, b) \in R \implies (a, c) \in R \implies$
 $\exists d. (b, d) \in R^* \wedge (c, d) \in R^*$
shows $\bigwedge b \ c. (a, b) \in R^* \implies (a, c) \in R^* \implies$
 $\exists d. (b, d) \in R^* \wedge (c, d) \in R^*$
 $\langle \text{proof} \rangle$

end

3 Parallel reduction and a complete developments

theory *ParRed* **imports** *Lambda Commutation* **begin**

3.1 Parallel reduction

consts
 $\text{par-beta} :: (dB \times dB) \text{ set}$

syntax
 $\text{par-beta} :: [dB, dB] \Rightarrow \text{bool} \ (\text{infixl} \Rightarrow 50)$

translations
 $s \Rightarrow t == (s, t) \in \text{par-beta}$

inductive *par-beta*
intros
 $\text{var} \ [simp, \text{intro!}]: \text{Var } n \Rightarrow \text{Var } n$
 $\text{abs} \ [simp, \text{intro!}]: s \Rightarrow t \implies \text{Abs } s \Rightarrow \text{Abs } t$

$app [simp, intro!]: [| s => s'; t => t' |] ==> s \circ t => s' \circ t'$
 $beta [simp, intro!]: [| s => s'; t => t' |] ==> (Abs s) \circ t => s'[t'/0]$

inductive-cases *par-beta-cases* [elim!]:

$Var\ n \Rightarrow t$
 $Abs\ s \Rightarrow Abs\ t$
 $(Abs\ s) \circ t \Rightarrow u$
 $s \circ t \Rightarrow u$
 $Abs\ s \Rightarrow t$

3.2 Inclusions

$beta \subseteq par\text{-}beta \subseteq beta^*$

lemma *par-beta-varL* [simp]:

$(Var\ n \Rightarrow t) = (t = Var\ n)$
 $\langle proof \rangle$

lemma *par-beta-refl* [simp]: $t \Rightarrow t$

$\langle proof \rangle$

lemma *beta-subset-par-beta*: $beta \leq par\text{-}beta$

$\langle proof \rangle$

lemma *par-beta-subset-beta*: $par\text{-}beta \leq beta^*$

$\langle proof \rangle$

3.3 Misc properties of par-beta

lemma *par-beta-lift* [rule-format, simp]:

$\forall t' n. t \Rightarrow t' \longrightarrow lift\ t\ n \Rightarrow lift\ t'\ n$
 $\langle proof \rangle$

lemma *par-beta-subst* [rule-format]:

$\forall s s' t' n. s \Rightarrow s' \longrightarrow t \Rightarrow t' \longrightarrow t[s/n] \Rightarrow t'[s'/n]$
 $\langle proof \rangle$

3.4 Confluence (directly)

lemma *diamond-par-beta*: *diamond* *par-beta*

$\langle proof \rangle$

3.5 Complete developments

consts

$cd :: dB \Rightarrow dB$

recdef *cd measure size*

$cd\ (Var\ n) = Var\ n$
 $cd\ (Var\ n \circ t) = Var\ n \circ cd\ t$
 $cd\ ((s1 \circ s2) \circ t) = cd\ (s1 \circ s2) \circ cd\ t$

$cd (Abs\ u \circ t) = (cd\ u)[cd\ t/0]$
 $cd (Abs\ s) = Abs\ (cd\ s)$

lemma *par-beta-cd* [rule-format]:
 $\forall t. s \Rightarrow t \dashv\dashv t \Rightarrow cd\ s$
 <proof>

3.6 Confluence (via complete developments)

lemma *diamond-par-beta2*: *diamond par-beta*
 <proof>

theorem *beta-confluent*: *confluent beta*
 <proof>

end

4 Eta-reduction

theory *Eta* imports *ParRed* begin

4.1 Definition of eta-reduction and relatives

consts

free :: *dB* \Rightarrow *nat* \Rightarrow *bool*

primrec

$free\ (Var\ j)\ i = (j = i)$
 $free\ (s \circ t)\ i = (free\ s\ i \vee free\ t\ i)$
 $free\ (Abs\ s)\ i = free\ s\ (i + 1)$

consts

eta :: (*dB* \times *dB*) *set*

syntax

$-eta :: [dB, dB] \Rightarrow bool \quad (\text{infixl } -e> 50)$
 $-eta\text{-}rtrancl :: [dB, dB] \Rightarrow bool \quad (\text{infixl } -e>> 50)$
 $-eta\text{-}reflcl :: [dB, dB] \Rightarrow bool \quad (\text{infixl } -e>= 50)$

translations

$s -e> t == (s, t) \in eta$
 $s -e>> t == (s, t) \in eta^*$
 $s -e>= t == (s, t) \in eta^=$

inductive *eta*

intros

$eta\ [simp, intro]: \neg free\ s\ 0 \Rightarrow Abs\ (s \circ Var\ 0) -e> s[dummy/0]$
 $appL\ [simp, intro]: s -e> t \Rightarrow s \circ u -e> t \circ u$
 $appR\ [simp, intro]: s -e> t \Rightarrow u \circ s -e> u \circ t$
 $abs\ [simp, intro]: s -e> t \Rightarrow Abs\ s -e> Abs\ t$

inductive-cases *eta-cases* [elim!]:

$Abs\ s -e> z$
 $s \circ t -e> u$
 $Var\ i -e> t$

4.2 Properties of eta, subst and free

lemma *subst-not-free* [rule-format, simp]:

$\forall i\ t\ u. \neg free\ s\ i \longrightarrow s[t/i] = s[u/i]$
 <proof>

lemma *free-lift* [simp]:

$\forall i\ k. free\ (lift\ t\ k)\ i =$
 $(i < k \wedge free\ t\ i \vee k < i \wedge free\ t\ (i - 1))$
 <proof>

lemma *free-subst* [simp]:

$\forall i\ k\ t. free\ (s[t/k])\ i =$
 $(free\ s\ k \wedge free\ t\ i \vee free\ s\ (if\ i < k\ then\ i\ else\ i + 1))$
 <proof>

lemma *free-eta* [rule-format]:

$s -e> t \implies \forall i. free\ t\ i = free\ s\ i$
 <proof>

lemma *not-free-eta*:

$[| s -e> t; \neg free\ s\ i |] \implies \neg free\ t\ i$
 <proof>

lemma *eta-subst* [rule-format, simp]:

$s -e> t \implies \forall u\ i. s[u/i] -e> t[u/i]$
 <proof>

theorem *lift-subst-dummy*: $\bigwedge i\ dummy. \neg free\ s\ i \implies lift\ (s[dummy/i])\ i = s$
 <proof>

4.3 Confluence of eta

lemma *square-eta*: $square\ eta\ eta\ (eta\hat{=})\ (eta\hat{=})$

<proof>

theorem *eta-confluent*: $confluent\ eta$

<proof>

4.4 Congruence rules for eta*

lemma *rtrancl-eta-Abs*: $s -e>> s' \implies Abs\ s -e>> Abs\ s'$

<proof>

lemma *rtrancl-eta-AppL*: $s -e>> s' \implies s \circ t -e>> s' \circ t$
 $\langle proof \rangle$

lemma *rtrancl-eta-AppR*: $t -e>> t' \implies s \circ t -e>> s \circ t'$
 $\langle proof \rangle$

lemma *rtrancl-eta-App*:
 $[| s -e>> s'; t -e>> t' |] \implies s \circ t -e>> s' \circ t'$
 $\langle proof \rangle$

4.5 Commutation of beta and eta

lemma *free-beta* [rule-format]:
 $s -> t \implies \forall i. \text{free } t \ i \longrightarrow \text{free } s \ i$
 $\langle proof \rangle$

lemma *beta-subst* [rule-format, intro]:
 $s -> t \implies \forall u \ i. s[u/i] -> t[u/i]$
 $\langle proof \rangle$

lemma *subst-Var-Suc* [simp]: $\forall i. t[\text{Var } i/i] = t[\text{Var}(i)/i + 1]$
 $\langle proof \rangle$

lemma *eta-lift* [rule-format, simp]:
 $s -e> t \implies \forall i. \text{lift } s \ i -e> \text{lift } t \ i$
 $\langle proof \rangle$

lemma *rtrancl-eta-subst* [rule-format]:
 $\forall s \ t \ i. s -e> t \longrightarrow u[s/i] -e>> u[t/i]$
 $\langle proof \rangle$

lemma *square-beta-eta*: *square beta eta* (η^*) (β^*)
 $\langle proof \rangle$

lemma *confluent-beta-eta*: *confluent* ($\beta \cup \eta$)
 $\langle proof \rangle$

4.6 Implicit definition of eta

Abs ($\text{lift } s \ 0 \circ \text{Var } 0$) $-e> s$

lemma *not-free-iff-lifted* [rule-format]:
 $\forall i. (\neg \text{free } s \ i) = (\exists t. s = \text{lift } t \ i)$
 $\langle proof \rangle$

theorem *explicit-is-implicit*:
 $(\forall s \ u. (\neg \text{free } s \ 0) \longrightarrow R (\text{Abs } (s \circ \text{Var } 0)) (s[u/0])) =$
 $(\forall s. R (\text{Abs } (\text{lift } s \ 0 \circ \text{Var } 0)) s)$
 $\langle proof \rangle$

4.7 Parallel eta-reduction

consts

par-eta :: (*dB* × *dB*) *set*

syntax

-par-eta :: [*dB*, *dB*] => *bool* (**infixl** =*e*> 50)

translations

s =*e*> *t* == (*s*, *t*) ∈ *par-eta*

syntax (*xsymbols*)

-par-eta :: [*dB*, *dB*] => *bool* (**infixl** ⇒_η 50)

inductive *par-eta*

intros

var [*simp*, *intro*]: *Var* *x* ⇒_η *Var* *x*

eta [*simp*, *intro*]: ¬ *free* *s* 0 ⇒ *s* ⇒_η *s'* ⇒ *Abs* (*s* ° *Var* 0) ⇒_η *s'*[*dummy*/0]

app [*simp*, *intro*]: *s* ⇒_η *s'* ⇒ *t* ⇒_η *t'* ⇒ *s* ° *t* ⇒_η *s'* ° *t'*

abs [*simp*, *intro*]: *s* ⇒_η *t* ⇒ *Abs* *s* ⇒_η *Abs* *t*

lemma *free-par-eta* [*simp*]: **assumes** *eta*: *s* ⇒_η *t*

shows ∧*i*. *free* *t* *i* = *free* *s* *i* ⟨*proof*⟩

lemma *par-eta-refl* [*simp*]: *t* ⇒_η *t*

⟨*proof*⟩

lemma *par-eta-lift* [*simp*]:

assumes *eta*: *s* ⇒_η *t*

shows ∧*i*. *lift* *s* *i* ⇒_η *lift* *t* *i* ⟨*proof*⟩

lemma *par-eta-subst* [*simp*]:

assumes *eta*: *s* ⇒_η *t*

shows ∧*u* *u'* *i*. *u* ⇒_η *u'* ⇒ *s*[*u*/*i*] ⇒_η *t*[*u'*/*i*] ⟨*proof*⟩

theorem *eta-subset-par-eta*: *eta* ⊆ *par-eta*

⟨*proof*⟩

theorem *par-eta-subset-eta*: *par-eta* ⊆ *eta**

⟨*proof*⟩

4.8 n-ary eta-expansion

consts *eta-expand* :: *nat* ⇒ *dB* ⇒ *dB*

primrec

eta-expand-0: *eta-expand* 0 *t* = *t*

eta-expand-Suc: *eta-expand* (*Suc* *n*) *t* = *Abs* (*lift* (*eta-expand* *n* *t*) 0 ° *Var* 0)

lemma *eta-expand-Suc'*:

∧*t*. *eta-expand* (*Suc* *n*) *t* = *eta-expand* *n* (*Abs* (*lift* *t* 0 ° *Var* 0))

⟨*proof*⟩

theorem *lift-eta-expand*: $\text{lift } (\text{eta-expand } k \ t) \ i = \text{eta-expand } k \ (\text{lift } t \ i)$
 $\langle \text{proof} \rangle$

theorem *eta-expand-beta*:
assumes $u: u \Rightarrow u'$
shows $\bigwedge t \ t'. t \Rightarrow t' \implies \text{eta-expand } k \ (\text{Abs } t) \circ u \Rightarrow t'[u'/0]$
 $\langle \text{proof} \rangle$

theorem *eta-expand-red*:
assumes $t: t \Rightarrow t'$
shows $\text{eta-expand } k \ t \Rightarrow \text{eta-expand } k \ t'$
 $\langle \text{proof} \rangle$

theorem *eta-expand-eta*: $\bigwedge t \ t'. t \Rightarrow_\eta t' \implies \text{eta-expand } k \ t \Rightarrow_\eta t'$
 $\langle \text{proof} \rangle$

4.9 Elimination rules for parallel eta reduction

theorem *par-eta-elim-app*: **assumes** $\text{eta}: t \Rightarrow_\eta u$
shows $\bigwedge u1' \ u2'. u = u1' \circ u2' \implies$
 $\exists u1 \ u2 \ k. t = \text{eta-expand } k \ (u1 \circ u2) \wedge u1 \Rightarrow_\eta u1' \wedge u2 \Rightarrow_\eta u2' \langle \text{proof} \rangle$

theorem *par-eta-elim-abs*: **assumes** $\text{eta}: t \Rightarrow_\eta t'$
shows $\bigwedge u'. t' = \text{Abs } u' \implies$
 $\exists u \ k. t = \text{eta-expand } k \ (\text{Abs } u) \wedge u \Rightarrow_\eta u' \langle \text{proof} \rangle$

4.10 Eta-postponement theorem

Based on a proof by Masako Takahashi [2].

theorem *par-eta-beta*: $\bigwedge s \ u. s \Rightarrow_\eta t \implies t \Rightarrow u \implies \exists t'. s \Rightarrow t' \wedge t' \Rightarrow_\eta u$
 $\langle \text{proof} \rangle$

theorem *eta-postponement'*: **assumes** $\text{eta}: s -e>> t$
shows $\bigwedge u. t \Rightarrow u \implies \exists t'. s \Rightarrow t' \wedge t' -e>> u$
 $\langle \text{proof} \rangle$

theorem *eta-postponement*:
assumes $st: (s, t) \in (\text{beta} \cup \text{eta})^*$
shows $(s, t) \in \text{eta}^* \ O \ \text{beta}^* \langle \text{proof} \rangle$

end

5 Application of a term to a list of terms

theory *ListApplication* **imports** *Lambda* **begin**

syntax

$\text{-list-application} :: dB \Rightarrow dB \text{ list} \Rightarrow dB \quad (\text{infixl } \circ^\circ \ 150)$

translations

$t \circ^\circ ts == \text{foldl } (op \circ) \ t \ ts$

lemma *apps-eq-tail-conv* [iff]: $(r \circ^\circ ts = s \circ^\circ ts) = (r = s)$
 $\langle \text{proof} \rangle$

lemma *Var-eq-apps-conv* [iff]:
 $\bigwedge s. (Var \ m = s \circ^\circ ss) = (Var \ m = s \wedge ss = [])$
 $\langle \text{proof} \rangle$

lemma *Var-apps-eq-Var-apps-conv* [iff]:
 $\bigwedge ss. (Var \ m \circ^\circ rs = Var \ n \circ^\circ ss) = (m = n \wedge rs = ss)$
 $\langle \text{proof} \rangle$

lemma *App-eq-foldl-conv*:
 $(r \circ s = t \circ^\circ ts) =$
 $(if \ ts = [] \ then \ r \circ s = t$
 $\ \ \ else \ (\exists ss. \ ts = ss \ @ \ [s] \wedge \ r = t \circ^\circ ss))$
 $\langle \text{proof} \rangle$

lemma *Abs-eq-apps-conv* [iff]:
 $(Abs \ r = s \circ^\circ ss) = (Abs \ r = s \wedge ss = [])$
 $\langle \text{proof} \rangle$

lemma *apps-eq-Abs-conv* [iff]: $(s \circ^\circ ss = Abs \ r) = (s = Abs \ r \wedge ss = [])$
 $\langle \text{proof} \rangle$

lemma *Abs-apps-eq-Abs-apps-conv* [iff]:
 $\bigwedge ss. (Abs \ r \circ^\circ rs = Abs \ s \circ^\circ ss) = (r = s \wedge rs = ss)$
 $\langle \text{proof} \rangle$

lemma *Abs-App-neq-Var-apps* [iff]:
 $\forall s \ t. \ Abs \ s \circ \ t \sim = Var \ n \circ^\circ ss$
 $\langle \text{proof} \rangle$

lemma *Var-apps-neq-Abs-apps* [iff]:
 $\bigwedge ts. \ Var \ n \circ^\circ ts \sim = Abs \ r \circ^\circ ss$
 $\langle \text{proof} \rangle$

lemma *ex-head-tail*:
 $\exists ts \ h. \ t = h \circ^\circ ts \wedge ((\exists n. \ h = Var \ n) \vee (\exists u. \ h = Abs \ u))$
 $\langle \text{proof} \rangle$

lemma *size-apps* [simp]:
 $\text{size } (r \circ^\circ rs) = \text{size } r + \text{foldl } (op \ +) \ 0 \ (\text{map size } rs) + \text{length } rs$
 $\langle \text{proof} \rangle$

lemma *lem0*: $[[(0::nat) < k; m \leq n]] \implies m < n + k$
 $\langle proof \rangle$

lemma *lift-map* [*simp*]:
 $\bigwedge t. \text{lift } (t \circ\circ ts) \ i = \text{lift } t \ i \circ\circ \text{map } (\lambda t. \text{lift } t \ i) \ ts$
 $\langle proof \rangle$

lemma *subst-map* [*simp*]:
 $\bigwedge t. \text{subst } (t \circ\circ ts) \ u \ i = \text{subst } t \ u \ i \circ\circ \text{map } (\lambda t. \text{subst } t \ u \ i) \ ts$
 $\langle proof \rangle$

lemma *app-last*: $(t \circ\circ ts) \circ u = t \circ\circ (ts @ [u])$
 $\langle proof \rangle$

A customized induction schema for $\circ\circ$.

lemma *lem* [*rule-format* (*no-asm*)]:
 $[[!!n \ ts. \forall t \in \text{set } ts. P \ t \implies P \ (Var \ n \circ\circ \ ts);$
 $!!u \ ts. [[P \ u; \forall t \in \text{set } ts. P \ t]] \implies P \ (Abs \ u \circ\circ \ ts)$
 $]] \implies \forall t. \text{size } t = n \dashrightarrow P \ t$
 $\langle proof \rangle$

theorem *Apps-dB-induct*:
 $[[!!n \ ts. \forall t \in \text{set } ts. P \ t \implies P \ (Var \ n \circ\circ \ ts);$
 $!!u \ ts. [[P \ u; \forall t \in \text{set } ts. P \ t]] \implies P \ (Abs \ u \circ\circ \ ts)$
 $]] \implies P \ t$
 $\langle proof \rangle$

end

6 Simply-typed lambda terms

theory *Type* **imports** *ListApplication* **begin**

6.1 Environments

constdefs
 $\text{shift} :: (nat \Rightarrow 'a) \Rightarrow nat \Rightarrow 'a \Rightarrow nat \Rightarrow 'a \quad (-<:-> [90, 0, 0] \ 91)$
 $e<i:a> \equiv \lambda j. \text{if } j < i \text{ then } e \ j \text{ else if } j = i \text{ then } a \text{ else } e \ (j - 1)$
syntax (*xsymbols*)
 $\text{shift} :: (nat \Rightarrow 'a) \Rightarrow nat \Rightarrow 'a \Rightarrow nat \Rightarrow 'a \quad (-\langle:-\rangle [90, 0, 0] \ 91)$
syntax (*HTML output*)
 $\text{shift} :: (nat \Rightarrow 'a) \Rightarrow nat \Rightarrow 'a \Rightarrow nat \Rightarrow 'a \quad (-\langle:-\rangle [90, 0, 0] \ 91)$

lemma *shift-eq* [*simp*]: $i = j \implies (e\langle i:T \rangle) \ j = T$
 $\langle proof \rangle$

lemma *shift-gt* [*simp*]: $j < i \implies (e\langle i:T \rangle) \ j = e \ j$

$\langle \text{proof} \rangle$

lemma *shift-lt* [*simp*]: $i < j \implies (e\langle i:T \rangle) j = e(j - 1)$
 $\langle \text{proof} \rangle$

lemma *shift-commute* [*simp*]: $e\langle i:U \rangle\langle 0:T \rangle = e\langle 0:T \rangle\langle \text{Suc } i:U \rangle$
 $\langle \text{proof} \rangle$

6.2 Types and typing rules

datatype *type* =
 Atom nat
 | Fun type type (infixr \Rightarrow 200)

consts
typing :: $((\text{nat} \Rightarrow \text{type}) \times \text{dB} \times \text{type}) \text{ set}$
typings :: $(\text{nat} \Rightarrow \text{type}) \Rightarrow \text{dB list} \Rightarrow \text{type list} \Rightarrow \text{bool}$

syntax
-funs :: $\text{type list} \Rightarrow \text{type} \Rightarrow \text{type}$ (infixr \Rightarrow 200)
-typing :: $(\text{nat} \Rightarrow \text{type}) \Rightarrow \text{dB} \Rightarrow \text{type} \Rightarrow \text{bool}$ ($-|-$: - [50, 50, 50] 50)
-typings :: $(\text{nat} \Rightarrow \text{type}) \Rightarrow \text{dB list} \Rightarrow \text{type list} \Rightarrow \text{bool}$
 ($-||-$: - [50, 50, 50] 50)

syntax (*xsymbols*)
-typing :: $(\text{nat} \Rightarrow \text{type}) \Rightarrow \text{dB} \Rightarrow \text{type} \Rightarrow \text{bool}$ ($- \vdash$: - [50, 50, 50] 50)

syntax (*latex*)
-funs :: $\text{type list} \Rightarrow \text{type} \Rightarrow \text{type}$ (infixr \Rightarrow 200)
-typings :: $(\text{nat} \Rightarrow \text{type}) \Rightarrow \text{dB list} \Rightarrow \text{type list} \Rightarrow \text{bool}$
 ($- \Vdash$: - [50, 50, 50] 50)

translations
 $Ts \Rightarrow T \equiv \text{foldr Fun Ts } T$
 $\text{env} \vdash t : T \equiv (\text{env}, t, T) \in \text{typing}$
 $\text{env} \Vdash ts : Ts \equiv \text{typings env ts Ts}$

inductive *typing*

intros

Var [*intro!*]: $\text{env } x = T \implies \text{env} \vdash \text{Var } x : T$
Abs [*intro!*]: $\text{env}\langle 0:T \rangle \vdash t : U \implies \text{env} \vdash \text{Abs } t : (T \Rightarrow U)$
App [*intro!*]: $\text{env} \vdash s : T \Rightarrow U \implies \text{env} \vdash t : T \implies \text{env} \vdash (s \circ t) : U$

inductive-cases *typing-elim* [*elim!*]:

$e \vdash \text{Var } i : T$
 $e \vdash t \circ u : T$
 $e \vdash \text{Abs } t : T$

primrec

$(e \Vdash [] : Ts) = (Ts = [])$
 $(e \Vdash (t \# ts) : Ts) =$
 (case Ts of

$\square \Rightarrow \text{False}$
 $| T \# Ts \Rightarrow e \vdash t : T \wedge e \Vdash ts : Ts)$

6.3 Some examples

lemma $e \vdash \text{Abs} (\text{Abs} (\text{Abs} (\text{Var } 1 \circ (\text{Var } 2 \circ \text{Var } 1 \circ \text{Var } 0)))) : ?T$
 $\langle \text{proof} \rangle$

lemma $e \vdash \text{Abs} (\text{Abs} (\text{Abs} (\text{Var } 2 \circ \text{Var } 0 \circ (\text{Var } 1 \circ \text{Var } 0)))) : ?T$
 $\langle \text{proof} \rangle$

6.4 Lists of types

lemma *lists-typings*:

$\bigwedge Ts. e \Vdash ts : Ts \Longrightarrow ts \in \text{lists } \{t. \exists T. e \vdash t : T\}$
 $\langle \text{proof} \rangle$

lemma *types-snoc*: $\bigwedge Ts. e \Vdash ts : Ts \Longrightarrow e \vdash t : T \Longrightarrow e \Vdash ts @ [t] : Ts @ [T]$
 $\langle \text{proof} \rangle$

lemma *types-snoc-eq*: $\bigwedge Ts. e \Vdash ts @ [t] : Ts @ [T] =$
 $(e \Vdash ts : Ts \wedge e \vdash t : T)$
 $\langle \text{proof} \rangle$

lemma *rev-exhaust2* [*case-names Nil snoc, extraction-expand*]:

$(xs = [] \Longrightarrow P) \Longrightarrow (\bigwedge ys y. xs = ys @ [y] \Longrightarrow P) \Longrightarrow P$

— Cannot use *rev-exhaust* from the *List* theory, since it is not constructive

$\langle \text{proof} \rangle$

lemma *types-snocE*: $e \Vdash ts @ [t] : Ts \Longrightarrow$
 $(\bigwedge Us U. Ts = Us @ [U] \Longrightarrow e \Vdash ts : Us \Longrightarrow e \vdash t : U \Longrightarrow P) \Longrightarrow P$
 $\langle \text{proof} \rangle$

6.5 n-ary function types

lemma *list-app-typeD*:

$\bigwedge t T. e \vdash t \circ \circ ts : T \Longrightarrow \exists Ts. e \vdash t : Ts \Rightarrow T \wedge e \Vdash ts : Ts$
 $\langle \text{proof} \rangle$

lemma *list-app-typeE*:

$e \vdash t \circ \circ ts : T \Longrightarrow (\bigwedge Ts. e \vdash t : Ts \Rightarrow T \Longrightarrow e \Vdash ts : Ts \Longrightarrow C) \Longrightarrow C$
 $\langle \text{proof} \rangle$

lemma *list-app-typeI*:

$\bigwedge t T Ts. e \vdash t : Ts \Rightarrow T \Longrightarrow e \Vdash ts : Ts \Longrightarrow e \vdash t \circ \circ ts : T$
 $\langle \text{proof} \rangle$

For the specific case where the head of the term is a variable, the following theorems allow to infer the types of the arguments without analyzing the typing derivation. This is crucial for program extraction.

theorem *var-app-type-eq*:

$$\bigwedge T U. e \vdash \text{Var } i \circ \circ ts : T \implies e \vdash \text{Var } i \circ \circ ts : U \implies T = U$$

<proof>

lemma *var-app-types*: $\bigwedge ts Ts U. e \vdash \text{Var } i \circ \circ ts \circ \circ us : T \implies e \Vdash ts : Ts \implies$
 $e \vdash \text{Var } i \circ \circ ts : U \implies \exists Us. U = Us \implies T \wedge e \Vdash us : Us$
<proof>

lemma *var-app-typesE*: $e \vdash \text{Var } i \circ \circ ts : T \implies$
 $(\bigwedge Ts. e \vdash \text{Var } i : Ts \implies T \implies e \Vdash ts : Ts \implies P) \implies P$
<proof>

lemma *abs-typeE*: $e \vdash \text{Abs } t : T \implies (\bigwedge U V. e \langle \theta : U \rangle \vdash t : V \implies P) \implies P$
<proof>

6.6 Lifting preserves well-typedness

lemma *lift-type* [*intro!*]: $e \vdash t : T \implies (\bigwedge i U. e \langle i : U \rangle \vdash \text{lift } t \ i : T)$
<proof>

lemma *lift-types*:
 $\bigwedge Ts. e \Vdash ts : Ts \implies e \langle i : U \rangle \Vdash (\text{map } (\lambda t. \text{lift } t \ i) \ ts) : Ts$
<proof>

6.7 Substitution lemmas

lemma *subst-lemma*:
 $e \vdash t : T \implies (\bigwedge e' i U u. e' \vdash u : U \implies e = e' \langle i : U \rangle \implies e' \vdash t[u/i] : T)$
<proof>

lemma *subst-lemma*:
 $\bigwedge Ts. e \vdash u : T \implies e \langle i : T \rangle \Vdash ts : Ts \implies$
 $e \Vdash (\text{map } (\lambda t. t[u/i]) \ ts) : Ts$
<proof>

6.8 Subject reduction

lemma *subject-reduction*: $e \vdash t : T \implies (\bigwedge t'. t \rightarrow t' \implies e \vdash t' : T)$
<proof>

theorem *subject-reduction'*: $t \rightarrow_{\beta^*} t' \implies e \vdash t : T \implies e \vdash t' : T$
<proof>

6.9 Alternative induction rule for types

lemma *type-induct* [*induct type*]:
 $(\bigwedge T. (\bigwedge T1 T2. T = T1 \implies T2 \implies P \ T1) \implies$
 $(\bigwedge T1 T2. T = T1 \implies T2 \implies P \ T2) \implies P \ T) \implies P \ T$
<proof>

end

7 Lifting an order to lists of elements

theory *ListOrder* **imports** *Accessible-Part* **begin**

Lifting an order to lists of elements, relating exactly one element.

constdefs

$step1 :: ('a \times 'a) \text{ set} \Rightarrow ('a \text{ list} \times 'a \text{ list}) \text{ set}$
 $step1 \ r ==$
 $\{(ys, xs). \exists us \ z \ z' \ vs. xs = us @ z \# vs \wedge (z', z) \in r \wedge ys =$
 $us @ z' \# vs\}$

lemma *step1-converse* [simp]: $step1 \ (r^{-1}) = (step1 \ r)^{-1}$
 $\langle proof \rangle$

lemma *in-step1-converse* [iff]: $(p \in step1 \ (r^{-1})) = (p \in (step1 \ r)^{-1})$
 $\langle proof \rangle$

lemma *not-Nil-step1* [iff]: $([], xs) \notin step1 \ r$
 $\langle proof \rangle$

lemma *not-step1-Nil* [iff]: $(xs, []) \notin step1 \ r$
 $\langle proof \rangle$

lemma *Cons-step1-Cons* [iff]:
 $((y \# ys, x \# xs) \in step1 \ r) =$
 $((y, x) \in r \wedge xs = ys \vee x = y \wedge (ys, xs) \in step1 \ r)$
 $\langle proof \rangle$

lemma *append-step1I*:
 $(ys, xs) \in step1 \ r \wedge vs = us \vee ys = xs \wedge (vs, us) \in step1 \ r$
 $\Rightarrow (ys @ vs, xs @ us) : step1 \ r$
 $\langle proof \rangle$

lemma *Cons-step1E* [rule-format, elim!]:
 $[(ys, x \# xs) \in step1 \ r;$
 $\forall y. ys = y \# xs \longrightarrow (y, x) \in r \longrightarrow R;$
 $\forall zs. ys = x \# zs \longrightarrow (zs, xs) \in step1 \ r \longrightarrow R$
 $] \Rightarrow R$
 $\langle proof \rangle$

lemma *Snoc-step1-SnocD*:
 $(ys @ [y], xs @ [x]) \in step1 \ r$
 $\Rightarrow ((ys, xs) \in step1 \ r \wedge y = x \vee ys = xs \wedge (y, x) \in r)$
 $\langle proof \rangle$

lemma *Cons-acc-step1I* [rule-format, intro!]:
 $x \in \text{acc } r \implies \forall xs. xs \in \text{acc } (\text{step1 } r) \longrightarrow x \# xs \in \text{acc } (\text{step1 } r)$
 <proof>

lemma *lists-accD*: $xs \in \text{lists } (\text{acc } r) \implies xs \in \text{acc } (\text{step1 } r)$
 <proof>

lemma *ex-step1I*:
 $[| x \in \text{set } xs; (y, x) \in r |]$
 $\implies \exists ys. (ys, xs) \in \text{step1 } r \wedge y \in \text{set } ys$
 <proof>

lemma *lists-accI*: $xs \in \text{acc } (\text{step1 } r) \implies xs \in \text{lists } (\text{acc } r)$
 <proof>

end

8 Lifting beta-reduction to lists

theory *ListBeta* **imports** *ListApplication ListOrder* **begin**

Lifting beta-reduction to lists of terms, reducing exactly one element.

syntax

-list-beta :: $dB \Rightarrow dB \Rightarrow \text{bool}$ (infixl \Rightarrow 50)

translations

$rs \Rightarrow ss == (rs, ss) : \text{step1 } \text{beta}$

lemma *head-Var-reduction-aux*:

$v \rightarrow v' \implies \forall rs. v = \text{Var } n \circ\circ rs \longrightarrow (\exists ss. rs \Rightarrow ss \wedge v' = \text{Var } n \circ\circ ss)$
 <proof>

lemma *head-Var-reduction*:

$\text{Var } n \circ\circ rs \rightarrow v \implies (\exists ss. rs \Rightarrow ss \wedge v = \text{Var } n \circ\circ ss)$
 <proof>

lemma *apps-betasE-aux*:

$u \rightarrow u' \implies \forall r rs. u = r \circ\circ rs \longrightarrow$
 $((\exists r'. r \rightarrow r' \wedge u' = r' \circ\circ rs) \vee$
 $(\exists rs'. rs \Rightarrow rs' \wedge u' = r \circ\circ rs') \vee$
 $(\exists s t ts. r = \text{Abs } s \wedge rs = t \# ts \wedge u' = s[t/0] \circ\circ ts))$
 <proof>

lemma *apps-betasE* [elim!]:

$[| r \circ\circ rs \rightarrow s; !!r'. [| r \rightarrow r'; s = r' \circ\circ rs |] \implies R;$
 $!!rs'. [| rs \Rightarrow rs'; s = r \circ\circ rs' |] \implies R;$
 $!!t u us. [| r = \text{Abs } t; rs = u \# us; s = t[u/0] \circ\circ us |] \implies R |]$
 $\implies R$
 <proof>

```

lemma apps-preserves-beta [simp]:
   $r \rightarrow s \implies r \circ\circ ss \rightarrow s \circ\circ ss$ 
  <proof>

lemma apps-preserves-beta2 [simp]:
   $r \rightarrow\rightarrow s \implies r \circ\circ ss \rightarrow\rightarrow s \circ\circ ss$ 
  <proof>

lemma apps-preserves-betas [rule-format, simp]:
   $\forall ss. rs \Rightarrow ss \dashrightarrow r \circ\circ rs \rightarrow r \circ\circ ss$ 
  <proof>

end

```

9 Inductive characterization of terminating lambda terms

theory *InductTermi* **imports** *ListBeta* **begin**

9.1 Terminating lambda terms

```

consts
  IT :: dB set

inductive IT
  intros
    Var [intro]:  $rs : \text{lists } IT \implies \text{Var } n \circ\circ rs : IT$ 
    Lambda [intro]:  $r : IT \implies \text{Abs } r : IT$ 
    Beta [intro]:  $(r[s/0]) \circ\circ ss : IT \implies s : IT \implies (\text{Abs } r \circ s) \circ\circ ss : IT$ 

```

9.2 Every term in IT terminates

```

lemma double-induction-lemma [rule-format]:
   $s : \text{termi beta} \implies \forall t. t : \text{termi beta} \dashrightarrow$ 
   $(\forall r ss. t = r[s/0] \circ\circ ss \dashrightarrow \text{Abs } r \circ s \circ\circ ss : \text{termi beta})$ 
  <proof>

```

```

lemma IT-implies-termi:  $t : IT \implies t : \text{termi beta}$ 
  <proof>

```

9.3 Every terminating term is in IT

declare *Var-apps-neq-Abs-apps* [*THEN not-sym*, *simp*]

```

lemma [simp, THEN not-sym, simp]:  $\text{Var } n \circ\circ ss \neq \text{Abs } r \circ s \circ\circ ts$ 
  <proof>

```

```

lemma [simp]:
  (Abs r  $\circ$  s  $\circ\circ$  ss = Abs r'  $\circ$  s'  $\circ\circ$  ss') = (r = r'  $\wedge$  s = s'  $\wedge$  ss = ss')
  <proof>

inductive-cases [elim!]:
  Var n  $\circ\circ$  ss : IT
  Abs t : IT
  Abs r  $\circ$  s  $\circ\circ$  ts : IT

theorem termi-implies-IT: r : termi beta ==> r : IT
  <proof>

end

```

10 Strong normalization for simply-typed lambda calculus

theory StrongNorm **imports** Type InductTermi **begin**

Formalization by Stefan Berghofer. Partly based on a paper proof by Felix Joachimski and Ralph Matthes [1].

10.1 Properties of IT

```

lemma lift-IT [intro!]: t  $\in$  IT  $\implies$  ( $\bigwedge i$ . lift t i  $\in$  IT)
  <proof>

lemma lifts-IT: ts  $\in$  lists IT  $\implies$  map ( $\lambda t$ . lift t 0) ts  $\in$  lists IT
  <proof>

lemma subst-Var-IT: r  $\in$  IT  $\implies$  ( $\bigwedge i j$ . r[Var i/j]  $\in$  IT)
  <proof>

lemma Var-IT: Var n  $\in$  IT
  <proof>

lemma app-Var-IT: t  $\in$  IT  $\implies$  t  $\circ$  Var i  $\in$  IT
  <proof>

```

10.2 Well-typed substitution preserves termination

```

lemma subst-type-IT:
   $\bigwedge t e T u i$ . t  $\in$  IT  $\implies$  e<i:U>  $\vdash$  t : T  $\implies$ 
    u  $\in$  IT  $\implies$  e  $\vdash$  u : U  $\implies$  t[u/i]  $\in$  IT
  (is PROP ?P U is  $\bigwedge t e T u i$ . -  $\implies$  PROP ?Q t e T u i U)
  <proof>

```


10.3 Well-typed terms are strongly normalizing

lemma *type-implies-IT*: $e \vdash t : T \implies t \in IT$
<proof>

theorem *type-implies-termi*: $e \vdash t : T \implies t \in \text{termi beta}$
<proof>

end

11 Weak normalization for simply-typed lambda calculus

theory *WeakNorm* **imports** *Type* **begin**

Formalization by Stefan Berghofer. Partly based on a paper proof by Felix Joachimski and Ralph Matthes [1].

11.1 Terms in normal form

constdefs

listall :: $('a \Rightarrow \text{bool}) \Rightarrow 'a \text{ list} \Rightarrow \text{bool}$
listall $P \ xs \equiv (\forall i. i < \text{length } xs \longrightarrow P \ (xs \ ! \ i))$

declare *listall-def* [*extraction-expand*]

theorem *listall-nil*: *listall* $P \ []$
<proof>

theorem *listall-nil-eq* [*simp*]: *listall* $P \ [] = \text{True}$
<proof>

theorem *listall-cons*: $P \ x \implies \text{listall } P \ xs \implies \text{listall } P \ (x \ \# \ xs)$
<proof>

theorem *listall-cons-eq* [*simp*]: *listall* $P \ (x \ \# \ xs) = (P \ x \wedge \text{listall } P \ xs)$
<proof>

lemma *listall-conj1*: *listall* $(\lambda x. P \ x \wedge Q \ x) \ xs \implies \text{listall } P \ xs$
<proof>

lemma *listall-conj2*: *listall* $(\lambda x. P \ x \wedge Q \ x) \ xs \implies \text{listall } Q \ xs$
<proof>

lemma *listall-app*: *listall* $P \ (xs \ @ \ ys) = (\text{listall } P \ xs \wedge \text{listall } P \ ys)$
<proof>

lemma *listall-snoc* [*simp*]: *listall* $P \ (xs \ @ \ [x]) = (\text{listall } P \ xs \wedge P \ x)$

$\langle proof \rangle$

lemma *listall-cong* [*cong*, *extraction-expand*]:
 $xs = ys \implies listall\ P\ xs = listall\ P\ ys$
 — Currently needed for strange technical reasons
 $\langle proof \rangle$

consts *NF* :: *dB set*

inductive *NF*

intros

App: $listall\ (\lambda t. t \in NF)\ ts \implies Var\ x\ {}^{\circ\circ} ts \in NF$

Abs: $t \in NF \implies Abs\ t \in NF$

monos *listall-def*

lemma *nat-eq-dec*: $\bigwedge n::nat. m = n \vee m \neq n$
 $\langle proof \rangle$

lemma *nat-le-dec*: $\bigwedge n::nat. m < n \vee \neg (m < n)$
 $\langle proof \rangle$

lemma *App-NF-D*: **assumes** *NF*: $Var\ n\ {}^{\circ\circ} ts \in NF$
 shows $listall\ (\lambda t. t \in NF)\ ts\ \langle proof \rangle$

11.2 Properties of *NF*

lemma *Var-NF*: $Var\ n \in NF$
 $\langle proof \rangle$

lemma *subst-terms-NF*: $listall\ (\lambda t. t \in NF)\ ts \implies$
 $listall\ (\lambda t. \forall i\ j. t[Var\ i/j] \in NF)\ ts \implies$
 $listall\ (\lambda t. t \in NF)\ (map\ (\lambda t. t[Var\ i/j])\ ts)$
 $\langle proof \rangle$

lemma *subst-Var-NF*: $t \in NF \implies (\bigwedge i\ j. t[Var\ i/j] \in NF)$
 $\langle proof \rangle$

lemma *app-Var-NF*: $t \in NF \implies \exists t'. t \circ Var\ i \rightarrow_{\beta}^* t' \wedge t' \in NF$
 $\langle proof \rangle$

lemma *lift-terms-NF*: $listall\ (\lambda t. t \in NF)\ ts \implies$
 $listall\ (\lambda t. \forall i. lift\ t\ i \in NF)\ ts \implies$
 $listall\ (\lambda t. t \in NF)\ (map\ (\lambda t. lift\ t\ i)\ ts)$
 $\langle proof \rangle$

lemma *lift-NF*: $t \in NF \implies (\bigwedge i. lift\ t\ i \in NF)$
 $\langle proof \rangle$

11.3 Main theorems

lemma *subst-type-NF*:

$\bigwedge t e T u i. t \in NF \implies e\langle i:U \rangle \vdash t : T \implies u \in NF \implies e \vdash u : U \implies \exists t'.$
 $t[u/i] \rightarrow_{\beta}^* t' \wedge t' \in NF$
 (is *PROP* ?*P* *U* is $\bigwedge t e T u i. - \implies \text{PROP } ?Q t e T u i U$)
 $\langle \text{proof} \rangle$

consts — A computationally relevant copy of $e \vdash t : T$
 $rtyping :: ((nat \Rightarrow type) \times dB \times type) \text{ set}$

syntax
 $-rtyping :: (nat \Rightarrow type) \Rightarrow dB \Rightarrow type \Rightarrow bool \quad (-|-_R - : - [50, 50, 50] 50)$
syntax (*xsymbols*)
 $-rtyping :: (nat \Rightarrow type) \Rightarrow dB \Rightarrow type \Rightarrow bool \quad (-\vdash_R - : - [50, 50, 50] 50)$
translations
 $e \vdash_R t : T \equiv (e, t, T) \in rtyping$

inductive *rtyping*

intros

$Var: e x = T \implies e \vdash_R Var x : T$
 $Abs: e\langle 0:T \rangle \vdash_R t : U \implies e \vdash_R Abs t : (T \Rightarrow U)$
 $App: e \vdash_R s : T \Rightarrow U \implies e \vdash_R t : T \implies e \vdash_R (s \circ t) : U$

lemma *rtyping-imp-typing*: $e \vdash_R t : T \implies e \vdash t : T$
 $\langle \text{proof} \rangle$

theorem *type-NF*: **assumes** $T: e \vdash_R t : T$
shows $\exists t'. t \rightarrow_{\beta}^* t' \wedge t' \in NF \langle \text{proof} \rangle$

11.4 Extracting the program

declare *NF.induct* [*ind-realizer*]
declare *rtrancL.induct* [*ind-realizer irrelevant*]
declare *rtyping.induct* [*ind-realizer*]
lemmas [*extraction-expand*] = *trans-def conj-assoc listall-cons-eq*

extract *type-NF*

lemma *rtrancLR-rtrancL-eq*: $((a, b) \in \text{rtrancLR } r) = ((a, b) \in \text{rtrancL } (\text{Collect } r))$
 $\langle \text{proof} \rangle$

lemma *NFR-imp-NF*: $(nf, t) \in NFR \implies t \in NF$
 $\langle \text{proof} \rangle$

The program corresponding to the proof of the central lemma, which performs substitution and normalization, is shown in Figure 1. The correctness theorem corresponding to the program *subst-type-NF* is

$\bigwedge x. (x, t) \in NFR \implies$
 $e\langle i:U \rangle \vdash t : T \implies$

```

subst-type-NF ≡
λx xa xb xc xd xe H Ha.
  type-induct-P xc
    (λx H2 H2a xa xb xc xd xe H.
      NFT-rec arbitrary
        (λts xa xaa r xb xc xd xe H.
          case nat-eq-dec xa xe of
            Left ⇒ case ts of [] ⇒ (xd, H)
            | a # list ⇒
              var-app-typesE-P (xb⟨xe:x⟩) xa (a # list)
                (λUs. case Us of [] ⇒ arbitrary
                  | T'' # Ts ⇒
                    let (x, y) =
                      rev-induct-P list (λx H. ([], Var-NF 0))
                      (λx xa H2 xc Ha.
                        types-snocE-P xa x xc
                          (λVs W.
                            let (x, y) = H2 Vs (fst (fst (listall-snoc-P xa) Ha));
                            (xa, ya) = snd (fst (listall-snoc-P xa) Ha) xb W xd xe H
                            in (x @ [xa],
                                NFT.App (map (λt. lift t 0) (x @ [xa])) 0
                                  (λxa. snd (listall-snoc-P (map (λt. lift t 0) x)) (App-NF-D y, lift-NF 0 ya) xa))))
                                Ts (listall-conj2-P-Q list
                                  (λi. (xaa (Suc i), r (Suc i))));
                            (xa, ya) = snd (xaa 0, r 0) xb T'' xd xe H;
                            (xd, yb) = app-Var-NF 0 (lift-NF 0 H);
                            (xa, ya) = H2 T'' (Ts ⇒ xc) xd xb (Ts ⇒ xc) xa 0 yb ya;
                            (x, y) =
                              H2a T'' (Ts ⇒ xc)
                                (foldl dB.App (dB.Var 0) (map (λt. lift t 0) x)) xb xc xa
                                0 y ya
                            in (x, y))
                                | Right ⇒
                                  var-app-typesE-P (xb⟨xe:x⟩) xa ts
                                    (λUs. let (x, y) =
                                      rev-induct-P ts (λx H. ([], λx. Var-NF x))
                                      (λx xa H2 xc Ha.
                                        types-snocE-P xa x xc
                                          (λVs W. let (x, y) = H2 Vs (fst (fst (listall-snoc-P xa) Ha));
                                          (xa, ya) =
                                            snd (fst (listall-snoc-P xa) Ha) xb W xd xe H
                                            in (x @ [xa],
                                                λxb.
                                                  NFT.App (x @ [xa]) xb (snd (listall-snoc-P x) (App-NF-D (y 0), ya))))
                                                  Us (listall-conj2-P-Q ts (λz. (xaa z, r z)))
                                          in case nat-le-dec xe xa of
                                            Left ⇒ (foldl (λu ua. dB.App u ua) (dB.Var (xa - Suc 0)) x,
                                                y (xa - Suc 0))
                                            | Right ⇒ (foldl (λu ua. dB.App u ua) (dB.Var xa) x, y xa)))
                                      (λt x r xa xb xc xd H.
                                        abs-typeE-P xb
                                          (λU V. let (x, y) =
                                            let (x, y) = r (λu. (xa⟨0:U⟩) u) V (lift xc 0) (Suc xd) (lift-NF 0 H)
                                            in (dB.Abs x, NFT.Abs x y)
                                            in (x, y)))
                                          H (λu. xb u) xc xd xe)
                                      x xa xd xe xb H Ha

```

Figure 1: Program extracted from *subst-type-NF*

```

subst-Var-NF ≡
λx xa H.
  NFT-rec arbitrary
    (λts x xa r xb xc.
      case nat-eq-dec x xc of
      Left ⇒ NFT.App (map (λt. t[dB.Var xb/xc]) ts) xb
        (subst-terms-NF ts xb xc (listall-conj1-P-Q ts (λz. (xa z, r z)))
          (listall-conj2-P-Q ts (λz. (xa z, r z))))
      | Right ⇒
        case nat-le-dec xc x of
        Left ⇒ NFT.App (map (λt. t[dB.Var xb/xc]) ts) (x - Suc 0)
          (subst-terms-NF ts xb xc (listall-conj1-P-Q ts (λz. (xa z, r z)))
            (listall-conj2-P-Q ts (λz. (xa z, r z))))
        | Right ⇒
          NFT.App (map (λt. t[dB.Var xb/xc]) ts) x
            (subst-terms-NF ts xb xc (listall-conj1-P-Q ts (λz. (xa z, r z)))
              (listall-conj2-P-Q ts (λz. (xa z, r z))))
    (λt x r xa xb. NFT.Abs (t[dB.Var (Suc xa)/Suc xb]) (r (Suc xa) (Suc xb))) H x xa

app-Var-NF ≡
λx. NFT-rec arbitrary
  (λts xa xaa r.
    (foldl dB.App (dB.Var xa) (ts @ [dB.Var x]),
      NFT.App (ts @ [dB.Var x]) xa
        (snd (listall-app-P ts)
          (listall-conj1-P-Q ts (λz. (xaa z, r z)),
            listall-cons-P (Var-NF x) listall-nil-eq-P))))
  (λt xa r. (t[dB.Var x/0], subst-Var-NF x 0 xa))

lift-NF ≡
λx H. NFT-rec arbitrary
  (λts x xa r xb.
    case nat-le-dec x xb of
    Left ⇒ NFT.App (map (λt. lift t xb) ts) x
      (lift-terms-NF ts xb (listall-conj1-P-Q ts (λz. (xa z, r z)))
        (listall-conj2-P-Q ts (λz. (xa z, r z))))
    | Right ⇒
      NFT.App (map (λt. lift t xb) ts) (Suc x)
        (lift-terms-NF ts xb (listall-conj1-P-Q ts (λz. (xa z, r z)))
          (listall-conj2-P-Q ts (λz. (xa z, r z))))
  (λt x r xa. NFT.Abs (lift t (Suc xa)) (r (Suc xa))) H x

type-NF ≡
λH. rtypingT-rec (λe x T. (dB.Var x, Var-NF x))
  (λe T t U x r. let (x, y) = r in (dB.Abs x, NFT.Abs x y))
  (λe s T U t x xa r ra.
    let (x, y) = r; (xa, ya) = ra;
    (x, y) =
      let (x, y) =
        subst-type-NF (dB.App (dB.Var 0) (lift xa 0)) e 0 (T ⇒ U) U x
          (NFT.App [lift xa 0] 0 (listall-cons-P (lift-NF 0 ya) listall-nil-P)) y
      in (x, y)
    in (x, y))
  H

```

Figure 2: Program extracted from lemmas and main theorem

$$\begin{aligned}
& (\bigwedge xa. (xa, u) \in NFR \implies \\
& \quad e \vdash u : U \implies \\
& \quad t[u/i] \rightarrow_{\beta}^* fst \ (subst\text{-}type\text{-}NF \ t \ e \ i \ U \ T \ u \ x \ xa) \wedge \\
& \quad (snd \ (subst\text{-}type\text{-}NF \ t \ e \ i \ U \ T \ u \ x \ xa), fst \ (subst\text{-}type\text{-}NF \ t \ e \ i \ U \ T \ u \ x \\
& \quad xa)) \in NFR)
\end{aligned}$$

where NFR is the realizability predicate corresponding to the datatype NFT , which is inductively defined by the rules

$$\begin{aligned}
& \forall i < \text{length } ts. (nfs \ i, ts \ ! \ i) \in NFR \implies \\
& (NFT.App \ ts \ x \ nfs, foldl \ dB.App \ (dB.Var \ x) \ ts) \in NFR \\
& (nf, t) \in NFR \implies (NFT.Abs \ t \ nf, dB.Abs \ t) \in NFR
\end{aligned}$$

The programs corresponding to the main theorem *type-NF*, as well as to some lemmas, are shown in Figure 2. The correctness statement for the main function *type-NF* is

$$\bigwedge x. (x, e, t, T) \in rtypingR \implies t \rightarrow_{\beta^*} fst \ (type\text{-}NF \ x) \wedge (snd \ (type\text{-}NF \ x), fst \ (type\text{-}NF \ x)) \in NFR$$

where the realizability predicate *rtypingR* corresponding to the computationally relevant version of the typing judgement is inductively defined by the rules

$$\begin{aligned}
& e \ x = T \implies (rtypingT.Var \ e \ x \ T, e, dB.Var \ x, T) \in rtypingR \\
& (ty, e \langle 0:T \rangle, t, U) \in rtypingR \implies (rtypingT.Abs \ e \ T \ t \ U \ ty, e, dB.Abs \ t, T \Rightarrow U) \in rtypingR \\
& (ty, e, s, T \Rightarrow U) \in rtypingR \implies \\
& (ty', e, t, T) \in rtypingR \implies (rtypingT.App \ e \ s \ T \ U \ t \ ty \ ty', e, dB.App \ s \ t, U) \in rtypingR
\end{aligned}$$

11.5 Generating executable code

consts-code

```

arbitrary :: 'a          ((error arbitrary))
arbitrary :: 'a => 'b ((fn '- => error arbitrary))

```

code-module Norm

contains

```

test = type-NF

```

The following functions convert between Isabelle's built-in **term** datatype and the generated **dB** datatype. This allows to generate example terms using Isabelle's parser and inspect normalized terms using Isabelle's pretty printer.

```

⟨ML⟩

```

We now try out the extracted program *type-NF* on some example terms.

```

⟨ML⟩

```

```

end

```

References

- [1] F. Joachimski and R. Matthes. Short proofs of normalization for the simply-typed λ -calculus, permutative conversions and Gödel's T. *Archive for Mathematical Logic*, 42(1):59–87, 2003.
- [2] M. Takahashi. Parallel reductions in λ -calculus. *Information and Computation*, 118(1):120–127, April 1995.