

Features

- SUPPORTS ALL ispLSI[®] 1000, 2000, 3000 AND 6000 FAMILY MEMBERS
- STAND-ALONE DEVICE PROGRAMMER
- DOWNLOAD DIRECTLY TO AN ISPTM DEVICE ON A SYSTEM BOARD
 - Only 5 Control/Data Pins Needed
- QUICK DEVICE PROGRAMMING
- INEXPENSIVE, SMALL AND COMPACT
 - Eliminates Need For Expensive, Remote Programmer
- EXCELLENT FOR PROTOTYPING NEW DESIGNS
 - Not Intended For Production Programming
- EASY TO USE
- CONNECTS DIRECTLY TO PARALLEL PRINTER PORT OF HOST PC

Description

The isp Engineering Kit Model 100 provides designers a quick and inexpensive means of evaluating and prototyping new designs using Lattice Semiconductor Corporation (LSC) in-system programmable Large Scale Integration (ispLSI) devices. This Kit is designed for engineering purposes only and is not intended for production use. The Kit programs devices from the parallel printer port of a host PC using the Lattice Semiconductor's pLSI/ispLSI Development System (pDS[®]) or pLSI/ispLSI Development System Plus (pDS+TM) design tools. By connecting a system cable (included) from a host PC to isp Engineering Kit, or connecting from the host PC to the target device on the system board, a JEDEC file can be easily downloaded into the ispLSI device(s).

Components

The isp Engineering Kit Model 100 consists of two primary components, each sold separately:

- Universal Programming Module (UPM)
- Socket Adapters

The adapters plug into the UPM base. The adapter provides the appropriate PLCC, PQFP, TQFP, or QFP socket for a particular ispLSI device package.



isp Engineering Kit - Model 100

UPM Description

The Model 100 Universal Programming Module is designed to support all package types available from LSC. It consists of the following components:

- Universal Programming Module Base Unit
- Power Supply Converter (110VAC/9VDC @ 200mA)
 - Included for North America and Asia Only
- 25-Pin Parallel Port Adapter
- 6' Universal Programming Module Download Cable with Modular Phone connectors (RJ45) on both ends
- 6' System Download Cable with a Modular Phone connector on one end and a AMP 1-87499-3 connector on other end

The connection between the host PC and the UPM base unit is shown in figure 1.

Electrical Characteristics

Power Supply

AC Input Voltage: 110 VAC
DC Output Voltage: 9 VDC @ 200mA

UPM Physical Characteristics

Length: 3.75 inches
Width: 2.625 inches
Depth: 1.375 inches

Download Cables


Download Cable with RJ-45 Phone Connectors on Both Ends

Length: 6.0 feet (192.8 cm)
Connectors: RJ-45 with eight positions

System Download Cable with RJ-45 Phone and AMP 1-87499-3 Connectors

Length: 6.0 feet (192.8 cm)
Connectors: RJ-45 with eight positions
AMP single in-line 0.100 " center spacing 8 positions

Figure 1. Universal Programming Module Description



0813A

Product Ordering Information

Product Code	Description
pDS4102-PM	isp Engineering Kit Model 100 for the PC: UPM programming module, (2) 8 wire Download cables, AC/DC Power Supply Converter, 25-Pin Parallel Port Adapter
pDS4102E-PM	ISP Engineering Kit Model 100 for the PC (European Model)
pDS4102-J44	44-pin PLCC socket adapter, (1) ispLSI 1016 Engineering Sample
pDS4102-T44	44-pin TQFP socket adapter, (1) ispLSI 1016 Engineering Sample
pDS4102-J68	68-pin PLCC socket adapter, (1) ispLSI 1024 Engineering Sample
pDS4102-J84	84-pin PLCC socket adapter, (1) ispLSI 1032 Engineering Sample
pDS4102-T100	100-pin TQFP socket adapter, (1) ispLSI 1032 Engineering Sample
pDS4102-Q120	120-pin PQFP socket adapter, (1) ispLSI 1048 Engineering Sample
pDS4102-Q128	128-pin PQFP socket adapter, (1) ispLSI 1048E Engineering Sample
pDS4102-M160	160-pin MQFP socket adapter, (1) ispLSI 3256 Engineering Sample



Copyright © 1996 Lattice Semiconductor Corporation.

E²CMOS, GAL, ispGAL, ispLSI, pLSI, pDS, Silicon Forest, UltraMOS, Lattice Logo, L with Lattice Semiconductor Corp. and L (Stylized) are registered trademarks of Lattice Semiconductor Corporation (LSC). The LSC Logo, Generic Array Logic, In-System Programmability, In-System Programmable, ISP, ispATE, ispCODE, ispDOWNLOAD, ispGDS, ispStarter, ispSTREAM, ispTEST, ispTURBO, Latch-Lock, pDS+, RFT, Total ISP and Twin GLB are trademarks of Lattice Semiconductor Corporation. ISP is a service mark of Lattice Semiconductor Corporation. All brand names or product names mentioned are trademarks or registered trademarks of their respective holders.

Lattice Semiconductor Corporation (LSC) products are made under one or more of the following U.S. and international patents: 4,761,768 US, 4,766,569 US, 4,833,646 US, 4,852,044 US, 4,855,954 US, 4,879,688 US, 4,887,239 US, 4,896,296 US, 5,130,574 US, 5,138,198 US, 5,162,679 US, 5,191,243 US, 5,204,556 US, 5,231,315 US, 5,231,316 US, 5,237,218 US, 5,245,226 US, 5,251,169 US, 5,272,666 US, 5,281,906 US, 5,295,095 US, 5,329,179 US, 5,331,590 US, 5,336,951 US, 5,353,246 US, 5,357,156 US, 5,359,573 US, 5,394,033 US, 5,394,037 US, 5,404,055 US, 5,418,390 US, 5,493,205 US, 0194091 EP, 0196771B1 EP, 0267271 EP, 0196771 UK, 0194091 GB, 0196771 WG, P3686070.0-08 WG. LSC does not represent that products described herein are free from patent infringement or from any third-party right.

The specifications and information herein are subject to change without notice. Lattice Semiconductor Corporation (LSC) reserves the right to discontinue any product or service without notice and assumes no obligation to correct any errors contained herein or to advise any user of this document of any correction if such be made. LSC recommends its customers obtain the latest version of the relevant information to establish, before ordering, that the information being relied upon is current.

LSC warrants performance of its products to current and applicable specifications in accordance with LSC's standard warranty. Testing and other quality control procedures are performed to the extent LSC deems necessary. Specific testing of all parameters of each product is not necessarily performed, unless mandated by government requirements.

LSC assumes no liability for applications assistance, customer's product design, software performance, or infringements of patents or services arising from the use of the products and services described herein.

LSC products are not authorized for use in life-support applications, devices or systems. Inclusion of LSC products in such applications is prohibited.

LATTICE SEMICONDUCTOR CORPORATION

5555 Northeast Moore Court
Hillsboro, Oregon 97124 U.S.A.
Tel.: (503) 681-0118
FAX: (503) 681-3037
<http://www.latticesemi.com>

November 1996
