


ispLSI and pLSI Design Flow

Introduction

Once the system design has been organized into functional components, and the logic functions which need to be incorporated in the selected components defined, the logic design phase begins. The general design flow is shown in figure 1. An ispLSI or pLSI design may be implemented from a number of design environments: including pLSI/ispLSI Development System (pDS) and numerous third-party CAE tools.

Figure 1. General Design Flow



These design environments offer various levels of design implementation from logic entry through programming the device. They support a variety of user interfaces and entry methods including: MS Windows GUI, Verilog-HDL, VHDL, truth tables, state machines and Boolean equations.

Design Entry

The pDS software allows the user to manually partition the logic to control design fit and performance. Using the MS Windows environment, logic functions are placed into Generic Logic Blocks (GLBs) and I/O Cells. This can be done by using the Edit, Cut, Copy, and Paste functions to enter Boolean equations and/or pre-defined functions from the LSC Macro and TTL libraries.

In addition to Boolean design entry, the pDS+ Fitters (in conjunction with third-party CAE tools) allow high-level descriptions of counters, adders, comparators, etc. High-level languages also support state machines, truth tables and case constructs for behavioral design implementations.

For standard CAE schematic designs, the pDS+ Fitters/third-party CAE tools provide support for graphical and hierarchical logic implementations using the Lattice Semiconductor Corporation (LSC) libraries of primitives and macros. The integrated user interfaces also allow easy integration of system or user-created functions into a hierarchical schematic using a top-down or bottom-up design methodology.

Design Verification

Verification using the pDS software is accomplished in two steps after logic has been placed. First, each cell may be individually verified to ensure that the minimized logic will fit into the GLB architecture. After all GLB and I/O cells are incrementally checked, the entire design is then verified to ensure that all nets have proper sources and destinations.

Because the advanced pDS+ tools perform automatic partitioning, design verification is done at a higher-level (pre-partitioned). For example, in the ABEL environment, the Compile (ahdl2pla) function performs the syntax and design rule checks. After the Compile phase, the Optimize (plaopt) function (optionally) minimizes the design.

In the pDS+Viewlogic environment, pre-partitioned design verification is performed by the Design Analyzer which ensures the logic conforms to the LSC design rules. Other CAE tools may perform these functions differently, but each has been tested for completeness and accuracy.

Partitioning

Partitioning using the pDS software is done by the user as part of the design entry process. The advanced pDS+ tools incorporate LSC's automatic partitioner which accepts converted data from designs entered using the third-party CAE tool of choice. LSC specific attributes for design entry are available to guide the partitioner in order to optimize usage of device features and performance.

Place and Route

All LSC design tools offer automatic place and route. This entails placement of GLB and IOC logic and then routing (or interconnecting) the source signals to their destinations. In the ispLSI and pLSI devices, the Global

ispLSI and pLSI Design Flow

Routing Pool (GRP) provides fast interconnects from external inputs and GLB feedbacks to the GLB inputs. The Output Routing Pool (ORP) provides flexible interconnects from GLB outputs to external pins.

Post-Route Simulation

After place and route, a netlist for full timing and function simulation may be passed to the third-party simulator. Many of these simulators offer both textual and graphical input and interfaces. Board and system level simulation models are available from Synopsys Logic Modeling Division.

Documentation

Report files, containing partitioned equations and pin-out information, may be generated for routed or un-routed designs. The pDS software can also generate reports with post-route maximum timing delays. In addition, the design can be exported in a variety of design formats. This supports design interfaces to standard third-party CAE tools.

Device Programming

Programming information is generated on a routed design by the FuseMap Generator for a specific ispLSI and pLSI device. It is an ASCII file written in the JEDEC format.

Two programming methods are used to program the ispLSI and pLSI devices. The first method uses the Device Programming Mode for both types of devices. This method facilitates device programming support from third-party vendors. The second method uses the LSC In-System Programming Mode and applies to the ispLSI family of devices.

Both methods of device programming allow the user to program and read back the fuesmap from the programmed device for verification (if the security cell has not been set).

Figure 2. pDS Design Flow





Figure 2a. Typical pDS+ Design Flow





Copyright © 1996 Lattice Semiconductor Corporation.

E²CMOS, GAL, ispGAL, ispLSI, pLSI, pDS, Silicon Forest, UltraMOS, Lattice Logo, L with Lattice Semiconductor Corp. and L (Stylized) are registered trademarks of Lattice Semiconductor Corporation (LSC). The LSC Logo, Generic Array Logic, In-System Programmability, In-System Programmable, ISP, ispATE, ispCODE, ispDOWNLOAD, ispGDS, ispStarter, ispSTREAM, ispTEST, ispTURBO, Latch-Lock, pDS+, RFT, Total ISP and Twin GLB are trademarks of Lattice Semiconductor Corporation. ISP is a service mark of Lattice Semiconductor Corporation. All brand names or product names mentioned are trademarks or registered trademarks of their respective holders.

Lattice Semiconductor Corporation (LSC) products are made under one or more of the following U.S. and international patents: 4,761,768 US, 4,766,569 US, 4,833,646 US, 4,852,044 US, 4,855,954 US, 4,879,688 US, 4,887,239 US, 4,896,296 US, 5,130,574 US, 5,138,198 US, 5,162,679 US, 5,191,243 US, 5,204,556 US, 5,231,315 US, 5,231,316 US, 5,237,218 US, 5,245,226 US, 5,251,169 US, 5,272,666 US, 5,281,906 US, 5,295,095 US, 5,329,179 US, 5,331,590 US, 5,336,951 US, 5,353,246 US, 5,357,156 US, 5,359,573 US, 5,394,033 US, 5,394,037 US, 5,404,055 US, 5,418,390 US, 5,493,205 US, 0194091 EP, 0196771B1 EP, 0267271 EP, 0196771 UK, 0194091 GB, 0196771 WG, P3686070.0-08 WG. LSC does not represent that products described herein are free from patent infringement or from any third-party right.

The specifications and information herein are subject to change without notice. Lattice Semiconductor Corporation (LSC) reserves the right to discontinue any product or service without notice and assumes no obligation to correct any errors contained herein or to advise any user of this document of any correction if such be made. LSC recommends its customers obtain the latest version of the relevant information to establish, before ordering, that the information being relied upon is current.

LSC warrants performance of its products to current and applicable specifications in accordance with LSC's standard warranty. Testing and other quality control procedures are performed to the extent LSC deems necessary. Specific testing of all parameters of each product is not necessarily performed, unless mandated by government requirements.

LSC assumes no liability for applications assistance, customer's product design, software performance, or infringements of patents or services arising from the use of the products and services described herein.

LSC products are not authorized for use in life-support applications, devices or systems. Inclusion of LSC products in such applications is prohibited.

LATTICE SEMICONDUCTOR CORPORATION

5555 Northeast Moore Court
Hillsboro, Oregon 97124 U.S.A.

Tel.: (503) 681-0118

FAX: (503) 681-3037

<http://www.latticesemi.com>

November 1996
