

Introduction

Lattice Semiconductor's GAL16VP8 and GAL20VP8 devices combine the programmable logic flexibility of the industry standard GAL16V8 and GAL20V8 devices with the high output drive capability of the 74240 series of TTL devices. The GAL16VP8 and GAL20VP8 devices have been designed to implement bus and memory interface logic as a one chip solution, as opposed to the historical two chip solution.

The addition of 64mA output drive capability, and the option to individually configure the outputs either as standard totem pole outputs or open-drain outputs, has taken these 16/20VP8 devices beyond the realm of common glue logic integration. These capabilities allow the devices to drive heavy capacitive loads in applications such as bus and memory address and control signal drivers.

The following bus arbitration design example takes full advantage of the bus driving capability and the open-drain option of the GAL16VP8 to implement the bus arbitration circuit.

Design Example

A bus arbitration circuit is used to determine which board connected to the system bus gets control of the bus for data transfers. One of the most common methods of arbitrating the bus is to assign a priority level to each board and to award bus ownership to the board with the highest priority request. This normally requires a combination of a priority encoder and decoder logic to determine the priority. The GAL16VP8 highlighted in this design example uses wired-OR logic on the bus, implemented with open-drain outputs, to determine the relative priority, eliminating the use of dedicated priority encoder/decoder logic. This scheme is similar to the one used in IBM's Micro Channel bus standard.

Using this scheme, the board with the lowest numeric value ID has the highest priority — 0000 being the highest priority and 1111 being the lowest priority. Priority is resolved between competing boards by making the arbitration outputs (ARB3-ARB0) and bus request signals (BREQ) open-drain with external pull-up resistors.

A typical bus arbitration cycle begins by detection of an active BREQ signal driven by all requesting boards. (If BREQ is inactive, it means that none of the boards on the bus has requested the bus.) The requesting boards drive the ARB3-ARB0 signals according to the predetermined priority that is assigned by the ID3-ID0 inputs. The bit-by-bit resolution of the arbitration begins with a comparison at ARB3. When comparing the ARB3 bit, a logic low on ARB3 will prevail over a logic high on ARB3 since the bus has a wired-OR structure.

The comparison continues with ARB2, which compares ARB3 from the previous stage as well as the prevailing ARB2. The requesting boards that do not match the priority driven on ARB3 will no longer drive ARB2-ARB0. For example, if ARB3=0 on the bus but a board has ID3=1, the board will no longer drive the low order bits (ARB2-ARB0). This process continues until ARB0 is reached. After resolving ARB0, the lowest numerical value (highest priority) will be driven on ARB3-ARB0. A local bus grant signal is generated from the result of the arbitration if the value on ARB3-ARB0 matches that on the ID3-ID0 inputs to a given board. The board winning the bus keeps BREQ active until its bus access is complete.


An example CUPL source file which implements the arbitration logic is shown on the following pages. Figure 1 illustrates a typical bus interface block diagram. As a footnote to the open-drain configuration, use the FUSES statement and the fuse numbers provided in the datasheet to implement open-drain outputs in ABEL.

GAL16VP8/20VP8: Bus Arbitration Circuit

Summary

The unique ability for a logic device to drive 64mA and the option to have open-drain outputs have made the GAL16VP8 and GAL20VP8 ideal for bus and memory interface logic. The GAL16/20VP8 devices allow the design engineer a one chip solution for complex memory or bus applications that require 64mA Iol. The one chip solution reduces power and cost, while increasing speed and reliability.

Figure 1. Typical System Interface



GAL16VP8/20VP8: Bus Arbitration Circuit

Listing 1. Example of a CUPL Source File

```
Name          VP8ARB;
Partno        U00;
Device        G16VP8MA;
Revision      1.0;
Date          09/09/99;
Designer      John Doe;
Company       Lattice Semiconductor Corp.;
Location      Hillsboro, OR;
Assembly      16VP8 bus arbitration circuit;

/*****
/* This bus arbitration circuit is based on the priority */
/* assigned to the board. ID3..0 is configured to the board */
/* priority code. This example uses ID 3..1=0111 for the */
/* priority code. ARB3..0 is driven to the same priority */
/* code. */
*****/

/** Dedicated Inputs definition**/

Pin 1 = ID3; /* priority ID must be driven to .... */
Pin 2 = ID2; /* ... the appropriate priority levels ...*/
Pin 3 = ID1; /* ... by the local board. */
Pin 4 = ID0;

/** Note Pin 5 is Vcc on this package **/

Pin 6 = LARB; /* Local arbitrate signal. Enables local board arbitration */

/** I/O pin definitions **/

Pin 17 = BREQ; /* active low open-drain bus request */
Pin 12 = ARB3; /* open-drain arbitration bits */
```

GAL16VP8/20VP8: Bus Arbitration Circuit

```
Pin 13 = ARB2;
Pin 14 = ARB1;
Pin 16 = ARB0;
/** Note Pin 15 is GND on this package **/

/** Output Equations **/

!BREQ = !ARB3 & ARB2 & ARB1 & ARB0;
BREQ.TEC = 'b'0; /* .TEC=0 specifies the open-drain output..TEC=1 or
                  the default is the totem pole output. */
BREQ.OE = LARB; /* Enables local board arbitration */

!ARB3 = !ARB3 & !BREQ
      # ID3 & BREQ; /* arbitration bit 3 */
ARB3.TEC = 'b'0;
ARB3.OE = LARB; /* Enables local board arbitration */

ARB2 = !ARB3 & ARB2 & !BREQ
      # ID2 & BREQ; /* arbitration bit 2 */
ARB2.TEC = 'b'0;
ARB2.OE = LARB; /* Enables local board arbitration */

ARB1 = !ARB3 & ARB2 & ARB1 & !BREQ
      # ID1 & BREQ; /* arbitration bit 1 */
ARB1.TEC = 'b'0;
ARB1.OE = LARB; /* Enables local board arbitration */

ARB0 = !ARB3 & ARB2 & ARB1 & ARB0 & !BREQ
      # ID0 & BREQ; /* arbitration bit 0 */
ARB0.TEC = 'b'0;
ARB0.OE = LARB; /* Enables local board arbitration */
```



Copyright © 1996 Lattice Semiconductor Corporation.

E²CMOS, GAL, ispGAL, ispLSI, pLSI, pDS, Silicon Forest, UltraMOS, Lattice Logo, L with Lattice Semiconductor Corp. and L (Stylized) are registered trademarks of Lattice Semiconductor Corporation (LSC). The LSC Logo, Generic Array Logic, In-System Programmability, In-System Programmable, ISP, ispATE, ispCODE, ispDOWNLOAD, ispGDS, ispStarter, ispSTREAM, ispTEST, ispTURBO, Latch-Lock, pDS+, RFT, Total ISP and Twin GLB are trademarks of Lattice Semiconductor Corporation. ISP is a service mark of Lattice Semiconductor Corporation. All brand names or product names mentioned are trademarks or registered trademarks of their respective holders.

Lattice Semiconductor Corporation (LSC) products are made under one or more of the following U.S. and international patents: 4,761,768 US, 4,766,569 US, 4,833,646 US, 4,852,044 US, 4,855,954 US, 4,879,688 US, 4,887,239 US, 4,896,296 US, 5,130,574 US, 5,138,198 US, 5,162,679 US, 5,191,243 US, 5,204,556 US, 5,231,315 US, 5,231,316 US, 5,237,218 US, 5,245,226 US, 5,251,169 US, 5,272,666 US, 5,281,906 US, 5,295,095 US, 5,329,179 US, 5,331,590 US, 5,336,951 US, 5,353,246 US, 5,357,156 US, 5,359,573 US, 5,394,033 US, 5,394,037 US, 5,404,055 US, 5,418,390 US, 5,493,205 US, 0194091 EP, 0196771B1 EP, 0267271 EP, 0196771 UK, 0194091 GB, 0196771 WG, P3686070.0-08 WG. LSC does not represent that products described herein are free from patent infringement or from any third-party right.

The specifications and information herein are subject to change without notice. Lattice Semiconductor Corporation (LSC) reserves the right to discontinue any product or service without notice and assumes no obligation to correct any errors contained herein or to advise any user of this document of any correction if such be made. LSC recommends its customers obtain the latest version of the relevant information to establish, before ordering, that the information being relied upon is current.

LSC warrants performance of its products to current and applicable specifications in accordance with LSC's standard warranty. Testing and other quality control procedures are performed to the extent LSC deems necessary. Specific testing of all parameters of each product is not necessarily performed, unless mandated by government requirements.

LSC assumes no liability for applications assistance, customer's product design, software performance, or infringements of patents or services arising from the use of the products and services described herein.

LSC products are not authorized for use in life-support applications, devices or systems. Inclusion of LSC products in such applications is prohibited.

LATTICE SEMICONDUCTOR CORPORATION

5555 Northeast Moore Court
Hillsboro, Oregon 97124 U.S.A.

Tel.: (503) 681-0118

FAX: (503) 681-3037

<http://www.latticesemi.com>

November 1996
