

Introduction


The blistering speed of today's leading-edge microprocessors necessitates the use of new memory and logic technologies. To keep up with the operating frequencies of these new microprocessors while still providing a clean memory interface, ultra-high-performance synchronous DRAMs and PLDs are required. This article discusses the design of a system based on an Intel Pentium microprocessor and Toshiba SDRAMs. The memory interface between the Pentium and the SDRAMs is implemented using Lattice 3.3 volt Generic Array Logic (GAL) programmable logic devices. For the purpose of this design, the Pentium P54C-100/66 processor, operating at a 100 MHz internal frequency and a 66 MHz bus frequency, was used. The bus frequency of the processor is vitally important in the design of the synchronous memory interface, as will be shown later in this article. A 2M x 64 SDRAM bank consisting of eight pieces of 2M x 8 SDRAM is used in the design. The design can be easily modified to support a 2M x 32 SDRAM bank, since the Pentium supports a 32-bit memory interface by connecting the Pentium's A2 address to the appropriate memory address.

Design Implementation

Due to the speed of the system, a phase-locked loop (PLL) circuit is used in the design (see Figure 1). The PLL can reside either on the motherboard or on the SDRAM memory module, if one exists. Note that the current JEDEC SDRAM dual in-line memory module (DIMM) specification recommends that a PLL be placed on the DIMM, between the processor clock and the SDRAM clocks. As for the choice of PLL, a Motorola MC952 is used. This device is used in some SDRAM modules currently available. The memory interface was designed using 3.3 volt Lattice GAL devices.

As mentioned earlier, the design uses a Pentium operating at a 66 MHz external bus, which translates to a 15.15 ns clock cycle time. The high-speed Toshiba SDRAM (part number TC59S1608AFT-10) clock frequency is 100 MHz, which is the equivalent of a 10 ns clock cycle time. The GAL devices need to be 5 ns or faster in order to incorporate two levels of logic into the 10 ns clock cycle. These timing requirements are easily met by the 3.5 ns 3.3 volt GAL16LV8D-3LJ devices from Lattice Semiconductor. This device is a registered GAL with 16 inputs and

Figure 1. Pentium/SDRAM Interface



Interfacing SDRAMs to Pentium Processors with 3.3V GAL Devices

8 outputs, 3.5 ns maximum propagation delay (Tpd), 2.5 ns maximum clock-to-output delay (Tco), and 200 MHz operating frequency (Fmax). Any one of the registered outputs may be bypassed. The memory interface logic was implemented using two GAL16LV8D-3LJ devices. The first GAL is used to generate the RAS# and CAS# signal to the memory bank. The second GAL device is used to generate NA# and BRDY#. The ABEL equations for the two GAL16LV8D devices are shown in Listing 1.


Other signals in the design do not require additional control logic. Each of the eight Pentium byte-enable signals is tied directly to the chip-select signal of one of the SDRAM banks. In this way, each SDRAM will provide the byte corresponding to its location when selected. Pentium addresses A3-A13 are connected to SDRAM addresses A0-A10 directly, and the 64 data lines on the SDRAM bus are directly connected to D0-D63 of the Pentium. Alternatively, the designer may consider isolat-

ing the memory bus by using a very fast bi-directional buffer, such as a 244 device. And, finally, the DQM signal is connected to ground since read data is not being tristated, and write data is not being masked. (The DQM signal, when sampled high, places the outputs in high-Z state in a Read cycle and acts as an out mask in a Write cycle.) Figure 2 shows an example of an interleaved bank read cycle. For the purposes of this article, the CAS latency (the number of clocks from the time the CAS# signal is asserted low until the time that the first byte of data is read) is set to three cycles, which is equivalent to 30 ns. Also, the burst length is set to 4.

Acknowledgement

Lattice Semiconductor would like to thank Michael Jahed, Senior Product Engineer, Toshiba, Inc., for sourcing this applications note.

Figure 2. Interleaved Bank Read



Interfacing SDRAMs to Pentium Processors with 3.3V GAL Devices

Listing 1. ABEL Files for the Design Module

```
module psdram1
title `pentium sdram interface 1
                                u1      device    `P16R8' ;
Pclk, !WR, !Cache, !ADS, !KEN    pin       1, 2, 3, 5, 6 ;
A10, A14                        pin       7, 8 ;
!WE                              pin       19 ;
BS                               pin       12 ;
!RAS                             pin       13 ;
!CAS                             pin       14 ;
Q2, Q3, Q4                      pin       16, 17, 18 ;
MIO                             pin       4

equations

BS = A14 ;
!WE = !ADS & MIO & !Cache & KEN & WR ;
!RAS := !ADS & MIO & !Cache ;
!Q2 := !RAS ;
!Q3 := !Q2 ;
!Q4 := !Q3 ;
!CAS := (!WE & !Q2) # (WE & !Q4) ;

end psdram1

module psdram2
title `pentium sdram interface 2
                                u2      device    `P16R8' ;
                                Pclk, !WE, !CAS    pin       1, 2, 3 ;
                                !BRDY, !NA        pin       12, 13 ;
                                Q4, Q5, Q6, Q7, Q8 pin       14, 15, 16, 17, 18 ;

equations

!NA := (!WE & !Q6) # (WE & !Q9) ;
!BRDY := (WE & !Q6 & !Q7 & !Q8 & !Q9) # (!WE & !CAS & !Q4 & !Q5 & !Q6) ;
!Q4 := !CAS ;
!Q5 := !Q6 ;
!Q6 := !Q5 ;
!Q7 := !Q6 ;
!Q8 := !Q7 ;
!Q9 := !Q8 ;
```



Copyright © 1996 Lattice Semiconductor Corporation.

E²CMOS, GAL, ispGAL, ispLSI, pLSI, pDS, Silicon Forest, UltraMOS, Lattice Logo, L with Lattice Semiconductor Corp. and L (Stylized) are registered trademarks of Lattice Semiconductor Corporation (LSC). The LSC Logo, Generic Array Logic, In-System Programmability, In-System Programmable, ISP, ispATE, ispCODE, ispDOWNLOAD, ispGDS, ispStarter, ispSTREAM, ispTEST, ispTURBO, Latch-Lock, pDS+, RFT, Total ISP and Twin GLB are trademarks of Lattice Semiconductor Corporation. ISP is a service mark of Lattice Semiconductor Corporation. All brand names or product names mentioned are trademarks or registered trademarks of their respective holders.

Lattice Semiconductor Corporation (LSC) products are made under one or more of the following U.S. and international patents: 4,761,768 US, 4,766,569 US, 4,833,646 US, 4,852,044 US, 4,855,954 US, 4,879,688 US, 4,887,239 US, 4,896,296 US, 5,130,574 US, 5,138,198 US, 5,162,679 US, 5,191,243 US, 5,204,556 US, 5,231,315 US, 5,231,316 US, 5,237,218 US, 5,245,226 US, 5,251,169 US, 5,272,666 US, 5,281,906 US, 5,295,095 US, 5,329,179 US, 5,331,590 US, 5,336,951 US, 5,353,246 US, 5,357,156 US, 5,359,573 US, 5,394,033 US, 5,394,037 US, 5,404,055 US, 5,418,390 US, 5,493,205 US, 0194091 EP, 0196771B1 EP, 0267271 EP, 0196771 UK, 0194091 GB, 0196771 WG, P3686070.0-08 WG. LSC does not represent that products described herein are free from patent infringement or from any third-party right.

The specifications and information herein are subject to change without notice. Lattice Semiconductor Corporation (LSC) reserves the right to discontinue any product or service without notice and assumes no obligation to correct any errors contained herein or to advise any user of this document of any correction if such be made. LSC recommends its customers obtain the latest version of the relevant information to establish, before ordering, that the information being relied upon is current.

LSC warrants performance of its products to current and applicable specifications in accordance with LSC's standard warranty. Testing and other quality control procedures are performed to the extent LSC deems necessary. Specific testing of all parameters of each product is not necessarily performed, unless mandated by government requirements.

LSC assumes no liability for applications assistance, customer's product design, software performance, or infringements of patents or services arising from the use of the products and services described herein.

LSC products are not authorized for use in life-support applications, devices or systems. Inclusion of LSC products in such applications is prohibited.

LATTICE SEMICONDUCTOR CORPORATION

5555 Northeast Moore Court
Hillsboro, Oregon 97124 U.S.A.

Tel.: (503) 681-0118

FAX: (503) 681-3037

<http://www.latticesemi.com>

November 1996
