



A. Product Status

The scope of this document encompasses the PCI 9054RDK-LITE Reference Design Kit

Product	Revision	Description	Production
PCI 9054RDK-LITE	Version 1.0	PCI Bus Master prototyping design kit	June 1999

1. The PCI 9054RDK-LITE board with a blank serial EEPROM or no EEPROM will prevent the PC from booting

Problem:

The PCI 9054RDK-LITE board is designed with a programmed EEPROM for PC BIOS to access during the boot up

Solution/workaround:

To boot the PCI 9054RDK-LITE with either no serial EEPROM or a blank one, the board needs to be modified in order to pull the local READY# input to the PCI 9054 low. With READY# pulled low, the board can then be booted with either a programmed EEPROM or a blank one. In both cases, the EEDI/EEDO signal must have a pull-up resistor. To boot with no EEPROM, this pull-up resistor must be changed to a pull-down resistor, in addition to pulling READY# low.

To modify the PCI 9054RDK-LITE for READY# signal pull-down:

1. Lift the READY# output pin (pin 84) on the Altera CPLD from the board.
2. Tie the PCI 9054 READY# pin low through a 10K pull-down to ground.

This signal is available at the following locations:

PCI 9054 pin 185, the solder pad to CPLD pin 84, test header LAH[12], POM connector pin 75, and either side of R71.

Note that a spare 10K resistor is available at RN4[4:5]. Since pin 6 of RN4 is already grounded, pin 5 can be soldered to pin 6 to ground one leg of the resistor. A wire can then be soldered to connect R71 with RN4-4.

To change the EEDI/EEDO resistor from a pull-up to a pull-down:

Remove the 10K resistor R74, and install a 1K resistor at R19.

Copyright © 2000 by PLX Technology, Inc. All rights reserved. PLX is a trademark of PLX Technology, Inc. which may be registered in some jurisdictions. All other product names that appear in this material are for identification purposes only and are acknowledged to be trademarks or registered trademarks of their respective companies. Information supplied by PLX is believed to be accurate and reliable, but PLX Technology, Inc. assumes no responsibility for any errors that may appear in this material. PLX Technology reserves the right, without notice, to make changes in product design or specification.