

Fast, versatile desktop printing for business professionals and small workgroups.



IBM Infoprint 12 Printer

Highlights

Lightweight, low-cost desktop laser printer with small footprint

Direct or network attachment

EuroReady*, e-business ready

Up to 12 pages per minute, 1200x1200 dpi print quality

Up to 20,000 page monthly print volume¹

Variable media sizes—A4, legal, letter, envelope

USB and parallel interfaces

PCL6, PCL5e datastreams

Optional PostScript 3 and Fast Ethernet 10/100 Base TX

Fast warm-up and first page out time

1 year warranty

The IBM® Infoprint® 12 is designed for business professionals who want superior performance, quality and reliability for desktop or small workgroup printing. With its ability to switch automatically among print languages and interfaces and to produce up to 1200-dpi print quality, the Infoprint 12 excels at printing reports, spreadsheets, proposals and much more.

Robust, lightweight printer

With an output speed of up to 12 pages per minute and a 66 MHz RISC processor, the Infoprint 12 meets the challenge of printing a wide variety of simple and complex business documents. The printer's input and output capacities accommodate lengthy documents and various media

including labels and transparencies. A straight paper path helps optimize printing speed and reliability. Yet, the Infoprint 12 weighs only 25 pounds (11.4 kilograms).

Optimum versatility

The versatile Infoprint 12 can be attached directly or networked, which allows growing companies to extend printer capabilities with minimal additional capital outlay. Because connectivity options are important in dynamic business environments, the printer includes USB and parallel interfaces, as well as optional Fast Ethernet.

The Infoprint 12 supports the most popular datastreams—PCL6, PCL5e and PostScript 3—in a convenient, small footprint.



The Infoprint 12's flexible attachment capability and excellent reliability enable high-quality printing at the point of need.

Worldwide service and support

In addition to the standard one-year warranty, IBM supports the Infoprint 12 with technical support by telephone and an exchange service program. Call (800) 358-6661 or contact your local IBM Printing Systems representative for details.

Maximize performance with IBM supplies and paper

Get the most out of your Infoprint 12 with genuine IBM supplies and paper, which are designed to provide exceptional print quality and reliability. For more information, contact IBM at 888-IBM PRINT or your local dealer.



© International Business Machines Corporation 2000

IBM Printing Systems
Dept. HT7/001H
P.O. Box 1900
Boulder, CO 80301-9191

Printed in the United States of America
8-00
All Rights Reserved

References in this publication to IBM products or services do not imply that IBM intends to make them available outside the United States.

IBM hardware products are manufactured from new parts, or new and used parts. Regardless, our warranty terms apply.

Visit the Printing Systems home page at ibm.com/printers



G563-0138-00

IBM Infoprint 12 at a glance

Print Speed	Up to 12 pages per minute (ppm) monochrome															
First Page Out Time	As fast as 14 seconds from Ready State															
Usage¹	Up to 20,000 simplex pages monthly															
Resolution	600 x 600 dpi at rated speed (up to 12 ppm), 300 dpi and 1200 x 1200 dpi print quality															
Memory	4MB standard/68MB maximum															
Processor	66MHz, 32 bit RISC ARM 7 processor															
Paper Handling	<i>Standard input capacity:</i> —Primary tray: up to 250 sheets —Auxiliary tray: up to 100 sheets <i>Optional input capacity:</i> —Optional tray: up to 550 sheets/40 envelopes <i>Standard output capacity:</i> —Main bin; up to 250 sheets —Rear exit tray: up to 100 sheets															
Media Sizes	Letter (8.5"x11"); Legal (8.5"x14"); Folio (8.5"x13"); Executive (7.25"x10.5"); Statement (5.5"x8.5"); Postcard (3"x5.8"); A4 (210 x 297 mm); A5 (148 x 210 mm); B5-ISO (176x250 mm); B5-JIS (182x257 mm); Envelopes: Commercial #10, Monarch, C5 and DL Custom forms sizes from 3"x5.8" (76.2x127 mm) to 8.5"x14" (215.9x355.6 mm)															
Media Types/Weights	Copier/xerographic papers: 16 to 28 lbs. (60 to 105 gsm); Cardstock: 16 to 43 lbs. (60 to 163 gsm); Envelopes: 16 to 28 lbs. (60 to 105 gsm)															
Server Platform Support	S/390® (G5, G6 Parallel Enterprise Servers® and Multiprise® 3000); AS/400e™ servers; RS/6000® servers/workstations; Netfinity®; NUMA-Q®; IntelliStation®; Network Stations; ThinkPad®, Aptiva®, NetVista®, PC Servers and IBM compatibles															
Printer Attachments	Bi-directional parallel (IEEE 1284 Type B), USB, 1 Network Interface Card (NIC) slot <i>Optional NIC:</i> —Fast Ethernet 10/100BaseTX (RJ-45)															
Printer Drivers	Microsoft® Windows® 2000, 95/98 and NT® 4.0; Mac OS 8.1+; Linux® (RedHat)															
Network Environment	Microsoft Windows 2000, 95/98, Millennium and NT 4.0; Macintosh® OS 8.1 and higher; Linux® (RedHat®); AppleTalk®; USB for Windows 2000, Windows 98, Millennium and Macintosh OS 8.6 and higher; LAN (IEEE 802.3); IPX/SPX Novell Netware 3.1x, 4x, 5x; TCP/IP Windows 2000, 95/98, Millennium and NT 4.0															
Physical Characteristics	<table><thead><tr><th></th><th>Depth</th><th>Height</th><th>Width</th><th>Weight</th></tr></thead><tbody><tr><td><i>Base model:</i></td><td>16.1"/407mm</td><td>9.9"/249mm</td><td>14.2"/360mm</td><td>25lb./11.4kg</td></tr><tr><td><i>Fully configured:</i></td><td>16.1"/407mm</td><td>15.6"/396mm</td><td>14.2"/360mm</td><td>37lb./17kg</td></tr></tbody></table>		Depth	Height	Width	Weight	<i>Base model:</i>	16.1"/407mm	9.9"/249mm	14.2"/360mm	25lb./11.4kg	<i>Fully configured:</i>	16.1"/407mm	15.6"/396mm	14.2"/360mm	37lb./17kg
	Depth	Height	Width	Weight												
<i>Base model:</i>	16.1"/407mm	9.9"/249mm	14.2"/360mm	25lb./11.4kg												
<i>Fully configured:</i>	16.1"/407mm	15.6"/396mm	14.2"/360mm	37lb./17kg												
Power Requirements	Low voltage: 100 - 127V, 50/60 Hz High voltage: 220 - 240V, 50/60 Hz															
Environmental Conditions	—Relative Humidity: 20% to 80% RH —Acoustics: 470 dBA (operating), 350 dBA (idle) —Operating Temperature: 50° to 90° F (10° to 30° C)															
Supplies	Toner Cartridge (P/N 01P6897): Yield up to 6,000 pages at 5% coverage															
Warranty	1 year (exchange)															

¹IBM does not recommend reaching this monthly maximum on a consistent basis.

* For more information on the implications of the euro, visit the IBM euro Web site at ibm.com/euro.

The following terms are trademarks of IBM Corporation in the United States and/or other countries: AIX, Aptiva, AS/400, AS/400e, IBM, Infoprint, IntelliStation, Multiprise, MVS, Netfinity, NetVista, NUMA-Q, OS/2, OS/390, OS/400, Parallel Enterprise Server, PowerPC, RS/6000, S/390 and ThinkPad.

Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation.

Adobe, PostScript and PostScript 3 are trademarks or registered trademarks of Adobe Systems Incorporated.

Java is a trademark of Sun Microsystems, Inc.

Linux is a registered trademark of Linus Torvalds.

AppleTalk and Macintosh are registered trademarks of Apple Computer, Inc.

UNIX is a registered trademark in the United States and other countries licensed exclusively through X/Open Company Limited.

ENERGY STAR is a U.S. registered mark. The ENERGY STAR Emblem does not represent EPA endorsement of any product or service.

Other company, product and service names may be trademarks or service marks of others.



Postnet



IBM EuroReady