



IBM Systems Group

As Cool as Ice: Analyzing Your RACF Data Using DFSORT and ICETOOL

RACF-2005, Orlando, Florida
May 2005

Mark Nelson, CISSP
RACF Design and Development
IBM Poughkeepsie
markan@us.ibm.com

Trademarks

- **The following are trademarks or registered trade marks of the International Business Machines Corporation:**
 - ▶ DB2
 - ▶ DFSORT
 - ▶ OS/390
 - ▶ RACF
 - ▶ z/OS

- **CISSP is a registered certification mark of the International Information Systems Security Certification Consortium, Inc.**

- **UNIX is a registered trademark of The Open Group in the United States and other countries.**

Agenda

- **The Shortest Overview of IRRDBU00 and IRRADU00 Ever**
- **Processing IRRDBU00 and IRRADU00 Output using DFSORT**
 - ▶ Introduction to DFSORT
 - ▶ Ordering records
 - ▶ Selecting records
 - ▶ Writing Records to Multiple Files
 - ▶ Using ICETOOL

The Shortest Overview of the RACF Data
Base Unload Utility (IRRDBU00) and RACF
SMF Unload Utility (IRRADU00) That You Will
Ever Hear From Me

The Shortest Overview of IRRxxU00 Ever

- **The RACF Database Unload Utility (IRRADU00) and the RACF SMF Unload Utility (IRRADU00) convert security information from its terse and cryptic format to a “flat file” format**
 - ▶ **Unloaded format is easy to read and import into data-analysis tools such as DB2, Microsoft Excel, SAS, DFSORT, and even ISPF edit or browse**
 - ▶ **The output of these utilities is documented in “RACF Macros and Interface”**
 - ▶ **RACF ships default 30+ sample reports in ‘SYS1.SAMPLIB(IRRICE)’**

An Introduction to DFSORT

An Introduction to DFSORT: A Few Notes

- **All of the DFSORT information contained within this presentation is derived from:**
 - ▶ ***DFSORT: Getting Started (SC26-7527)***
 - ▶ ***DFSORT Application Programming Guide (SC26-7523)***
 - <http://www.ibm.com/servers/storage/support/software/sort/mvs/srtmpub.html> contains these book and may more DFSORT publications
- **This focus of this session is that subset of DFSORT's functionality which is most used when doing basic analysis of RACF information. This is only a small subset of the many functions available with DFSORT and DFSORT's ICETOOL.**
- **These examples may or may not work if you are using a sort product other than DFSORT. Consult your OEM sort product vendor for questions on other sort products.**

An Introduction to DFSORT: The Big Picture

- **IBM's DFSORT is a high-performance product that you can use to sort data, merge data, copy data, select data, reformat data, and create reports.**
- **DFSORT works on information that is contained within data sets.**
- **A record is a collection of related information that is managed as a unit, such as an employee record.**
- **A field is a specific portion of a record that defines a particular category of data , such as an employee's name.**
 - ▶ In DFSORT, each field is identified by a starting position, a length, and a data type (format).
 - ▶ DFSORT supports a large number of data types, such as CH, ZD, PD, BI, FS, UFF, SFF, Y2K, etc.).

An Introduction to DFSORT: Sorting Data

- **As its name implies, sorting is one of the main functions of DFSORT, and is invoked with the SORT statement:**
 - ▶ SORT FIELDS=(startingPosition,length,dataType,sortOrder)
 - sortOrder: 'A' for ascending, 'D' for descending
 - dataType: 'CH' for character (EBCDIC) data

- **For example, to sort the output of the RACF SMF Unload Utility by the type of record:**
 - ▶ SORT FIELDS=(5,8,CH,A)

An Introduction to DFSORT: Sorting Data...

- You can sort on multiple fields by specifying multiple sort fields.
- For example, to sort on the type of record, the date, and the time, code:

```
SORT FIELDS=(5, 8, CH, A, 32, 10, CH, A, 23, 8, CH, A)
```

- **Tip:** If all of the fields have the same data type, you can code the **FORMAT=** keyword, which applies the specified data type to all of the fields in the statement:

```
SORT FORMAT=CH, FIELDS=(5, 8, A, 32, 10, A, 23, 8, A)
```

An Introduction to DFSORT: Selecting Records

- **DFSORT can be used to select records using the INCLUDE and OMIT statements.**
 - ▶ INCLUDE COND=(startingPosition,length,dataType,testType,value)
 - ▶ OMIT COND=(startingPosition,length,dataType,testType,value)
- **You can specify either a constant value (C'YES ') or another field in the record (39,4,CH) for the value.**
- **You can code multiple selection criteria, joined together with the Boolean AND and OR operators**
 - ▶ INCLUDE COND=(startingPosition,length,dataType,testType,value,AND|OR, startingPosition,length,dataType,testType...)
 - ▶ OMIT COND=(startingPosition,length,dataType,testType,value,AND|OR, startingPosition,length,dataType,testType...)
- **You can code only one INCLUDE or OMIT statement per sort operation**

An Introduction to DFSORT: Selecting Records...

- **You must code a SORT, MERGE, or COPY statement with your INCLUDE or OMIT statement**
 - ▶ SORT FIELD=COPY or OPTION COPY can be used instead of SORT FIELDS=(....) if you don't want to or need to sort the input data
- **Example: Select all of the RACF Database Unload records ('0200' in columns 5-8) which define users who have the SPECIAL, OPERATIONS, or AUDITOR attribute ('YES' in columns 44-46, 49-51, or 390-392)**

```
SORT      FIELDS= (10, 8, CH, A)
INCLUDE  COND= (5, 4, CH, EQ, C'0200', AND,
               (44, 3, CH, EQ, C'YES', OR,
                49, 3, CH, EQ, C'YES', OR,
                390, 3, CH, EQ, C'YES'))
```

An Introduction to DFSORT: The Substring Operator

- You can use the DFSORT substring ("SS") comparison test to find a specified character string anywhere in a field

```
INCLUDE COND=(10,44,CH,SS,C'*)
```

- selects any record in which the character '*' appears within columns 10 to 53

- Consider this example:

```
INCLUDE COND=(5,4,CH,EQ,C'0500',AND,  
              266,4,CH,EQ,C'NO',AND,  
              (10,249,SS,EQ,C'*,OR,  
              10,249,SS,EQ,C'%',OR,  
              10,249,SS,EQ,C'&'))
```

- ▶ Which finds all general resource profiles (record type '0500') which are not generic (record offset 266 contains 'NO') but have a generic character in the name (the "SS" operands)

An Introduction to DFSORT: Reformatting Records

- **DFSORT allows extensive reformatting of records using the OUTREC statement and/or the INREC statement**
 - ▶ The OUTREC statement defines the format of the output record
 - ▶ The OUTREC statement indicates:
 - What columns are to be copied to the output data set (startingPosition,length)
 - What other data is to be inserted into the record
 - Constant values
 - System generated data
 - Edited or converted numeric values
 - Results of arithmetic expressions
- **Example: To copy the user ID, programmer name, and owner of the IRRDBU00 User Basic Data record, with a blank between each field, code:**

```
SORT      FIELDS=COPY
INCLUDE  COND=(5,4,CH,EQ,C'0200')
OUTREC  FIELDS=(1,4,10,8,X,78,20,X,30,8)
OPTION  VLSHRT
```

- ▶ We'll talk about what "1,4" means in a moment

An Introduction to DFSORT: Reformatting Records...

- **One very powerful feature of OUTREC is the ability to insert text into a record during the reformatting processing**
 - ▶ Can be very useful in transforming data into more usable forms
- **Example: To copy the user ID, programmer name, and owner of the IRRDBU00 User Basic Data record, with a blank between each field, you would code:**

```
SORT      FIELDS=COPY
INCLUDE  COND=(5,4,CH,EQ,C'0200')
OUTREC  FIELDS=(1,4,C'The owner of ID ',10,8,C' is ',
                30,8,C' and is assigned to ',79,20)
OPTION  VLSHRT
```

An Introduction to DFSORT: Reformatting Records...

```
The owner of ID AUDTR01 is MARKN and is assigned to EXTERNAL AUDITOR 01
The owner of ID AUDTR02 is MARKN and is assigned to EXTERNAL AUDITOR 02
The owner of ID A6 is MARKN and is assigned to #####
The owner of ID BBB4 is MARKN and is assigned to #####
The owner of ID FRED is MARKN and is assigned to FRED THE OPERATOR
```

- **Some other powerful features of OUTREC are the ability to reformat different records in different ways using IFTHEN clauses and the ability to overlay selected bytes of a record using OVERLAY fields**

An Introduction to DFSORT: UTFIL

- **The UTFIL statement allows you to create one or more output data sets from a single pass of your input data**
 - ▶ The output data sets can be complete copies of the input data set or may contain only selected records
 - You can select the records go into each output data set
 - Based on values within the record
 - Based on relative record number
 - “Round robin” assignment
 - Every “nth” record
 - You can reformat the selected records in various ways
 - ▶ Very useful if you want to partition your RACF data base information or SMF
 - ▶ UTFIL can also be used to create reports.

An Introduction to DFSORT: OUTFIL...

- To put all of the IRRADU00 ACCESS records in one data set, all of the JOBINIT records into a second data set, and the remaining records into a third data set, you could code:

```
//SELECT      EXEC PGM=SORT
//SYSOUT      DD SYSOUT=*
//SORTWK01    DD UNIT=SYSALLDA, SPACE=(TRK,(5,5,0))
//SORTIN      DD DISP=SHR,DSN=MARKN.TEST.IRRADU00
//ACCESS      DD DISP=SHR,DSN=MARKN.ACCESS.IRRADU00
//JOBINIT     DD DISP=SHR,DSN=MARKN.JOBINIT.IRRADU00
//OTHERS      DD DISP=SHR,DSN=MARKN.OTHERS.IRRADU00
//SYSIN       DD *
SORT         FIELDS=COPY
OUTFIL       FNAMES=ACCESS,INCLUDE=(5,4,CH,EQ,C'ACCESS')
OUTFIL       FNAMES=JOBINIT,INCLUDE=(5,4,CH,EQ,C'JOBINIT')
OUTFIL       FNAMES=OTHERS,SAVE
/*
```

An Introduction to DFSORT: Symbols

- **DFSORT allows you to define symbols that can be used to replace fields (and constants) in DFSORT and ICETOOL statements with easy-to-read labels**
 - **USBD_OPER could be used as a symbol for 44,1,CH**
- **The RACFICE package on the “Downloads” section of the RACF web site (<http://www.ibm.com/servers/eserver/zseries/zos/racf/>) contains DFSORT symbols for all of the IRRADU00 and IRRDBU00 fields. Using these symbols you can specify:**

```
SORT FIELDS=(USBD_NAME,A)
INCLUDE COND=(GRBD_RECORD_TYPE,EQ,C'0500',AND,
              GRBD_GENERIC,EQ,C'NO  ',AND,
              (GRBD_NAME,SS,EQ,C'* ',OR,
              GRBD_NAME,SS,EQ,C'% ',OR,
              GRBD_NAME,SS,EQ,C'& '))
```

An Introduction to DFSORT: Variable Length Records

- **In z/OS, there are two data set structures:**
 - ▶ *Fixed-length* records, in which all records in the data set have the same length (RECFM=F, or FB) and
 - ▶ *Variable-length* records, in which the records in the data set do not have to have the same size records (RECFM=V,VB, VS, or VBS). Each record must have a length which is less than the maximum record length specified for the data set.
 - Each variable length record is prefixed with a four-byte *record descriptor word* (RDW) that contains the length of the record in the first two bytes.

- **When specifying the starting position, the RDW must be included.**
 - ▶ ... which means that you must add 4 to all of the starting positions documented for the IRRADU00 and IRRDBU00 output in *RACF Macros and Interfaces*. The DFSORT Symbols mentioned previously already have the RDF built into their starting positions.

DFSORT's ICETOOL Utility

An Introduction to ICETOOL: The Big Picture

- **ICETOOL is a multipurpose DFSORT utility that extends and simplifies the use of DFSORT**
- **ICETOOL allows the processing of multiple input and output data sets within the same job step**
- **ICETOOL processing is controlled by thirteen ICETOOL operators.**
- **All of the power of DFSORT, as well as additional functions, are available to you through ICETOOL!**

An Introduction to ICETOOL: ICETOOL Operators

ICETOOL Operator	Description
COPY	Copies a data set to one or more output data sets.
COUNT	Counts the records in a data set or sets a return code based on the count.
DEFAULTS	Prints the DFSORT installation defaults.
DISPLAY	Print field values with titles, headings, sections, etc.
MODE	Sets the ICETOOL error option: STOP, CONTINUE or SCAN. STOP is the default.
OCCURS	Print field values and their counts with titles, headings, etc.
RANGE	Prints the count of values in a specified range.
SELECT	Selects records based on value counts.
SORT	Sorts a data set to one or more output data sets.
SPLICE	Performs various join and match operations.
STATS	Prints minimum, maximum, total, and average values.
UNIQUE	Prints a count of unique values.
VERIFY	Identifies invalid decimal values.

An Introduction to ICETOOL: ICETOOL Operators...

- **All of the sample ICETOOL reports that are shipped in member IRRICE of 'SYS1.SAMPLIB' were written using just these ICETOOL operators:**
 - ▶ **COPY**
 - ▶ **SORT**
 - ▶ **DISPLAY**
 - ▶ **OCCURS**

An Introduction to ICETOOL: SORT

- The **SORT** operator allows you to sort data, select the records which are of interest, reformat the records, etc.

- The syntax is:

```
SORT FROM(indd) USING(cntl) TO(outdd)
```

- ...where

- ▶ **indd** is the input data set DD name
- ▶ **outdd** is the output data set DD name
- ▶ **cntl** is the one to four character prefix for the DD name that contains the DFSORT control statements
 - The DD name is formed by appending “CNTL” to the USING value

An Introduction to ICETOOL: SORT...

- **Let's create a realistic example. To create a report that lists all of the users who have either SPECIAL, OPERATIONS, or AUDITOR, we have to find all of the user basic data records (which have '0200' in columns 5 to 9) and which have a 'Y' in column 44, column 49, or column 390.**
- **The DFSORT INCLUDE statement which does this is:**

```
INCLUDE COND= ( (44,1,CH,EQ,C'Y',OR,  
                49,1,CH,EQ,C'Y',OR,  
                390,1,CH,EQ,C'Y' ) ,AND,  
                5,4,CH,EQ,C'0200' )
```

An Introduction to ICETOOL: DISPLAY

- **The DISPLAY operator allows you to:**
 - ▶ Select the information that is going to be in your report
 - ▶ Specify single line or multi-line column headings
 - ▶ Specify the title elements
- **The syntax is:**

```
DISPLAY FROM(indd) ON(field,<parms>) LIST(listdd) options
```

- **...where**
 - ▶ indd is the DD name of the input data set
 - ▶ field is the starting position, length and data type of the field that is to be in displayed the report
 - ▶ listdd is the DD name of the report data set
 - ▶ ON(field) can be (and usually is) repeated, once for each field in the report, up to 20 times

An Introduction to ICETOOL: DISPLAY...

- **For processing RACF data, the options that are most of interest are:**
 - ▶ TITLE('string'), which puts a title on the report
 - ▶ PAGE, which puts the page number on the report
 - ▶ DATE[(format)], which puts the current date, in various forms, on the report
 - ▶ TIME[(format)], which puts the current time, in various forms, on the report
 - ▶ BLANK, which suppresses leading zeros in numeric fields
 - ▶ ON(starting_position,length,datatype), which identifies a field to be processed
 - ▶ HEADER('string1', 'string2', 'string3'), which specifies a one, two, or three line column heading for each ON field
 - ▶ WIDTH, which sets the line length (width) of the report as 121 to 2048 bytes

- **There are many other DISPLAY operands... see “DFSORT: Getting Started” or “DFSORT Application Programming Guide” for details.**

An Introduction to ICETOOL: DISPLAY...

- **Continuing our example: To create a report which lists all of the users who have either SPECIAL, OPERATIONS, or AUDITOR, along with their name (from columns 79 to 98) and their user ID (from columns 10 to 17), you code this ICETOOL DISPLAY operator:**

```
DISPLAY FROM(TEMP0001) LIST(PRINT) -  
  PAGE -  
  TITLE('User IDs With Extraordinary Global Authorities')-  
  DATE(YMD/) -  
  TIME(12:) -  
  BLANK -  
  ON(10,8,CH)  HEADER('User ID') -  
  ON(79,20,CH) HEADER('User Name') -  
  ON(44,4,CH)  HEADER('Special') -  
  ON(49,4,CH)  HEADER('Operations') -  
  ON(390,4,CH) HEADER('Auditor')
```

An Introduction to ICETOOL: JCL

```
//REPORT      EXEC PGM=ICETOOL
//TOOLMSG     DD SYSOUT=*
//DFSMSG      DD SYSOUT=*
//DBUDATA     DD DISP=(SHR,DELETE),DSN=USER01.IRRDBU00
//TEMP0001    DD DISP=(NEW,DELETE),SPACE=(CYL,(5,1,0)),UNIT=SYSALLDA
//PRINT       DD SYSOUT=*
//TOOLIN      DD *
SORT          FROM(DBUDATA) TO(TEMP0001) USING(RACF)
DISPLAY FROM(TEMP0001) LIST(PRINT) -
PAGE -
TITLE('User IDs With Extraordinary Global Authorities') -
DATE(YMD/) -
TIME(12:) -
BLANK -
ON(10,8,CH)   HEADER('User ID') -
ON(79,20,CH)  HEADER('User Name') -
ON(44,4,CH)   HEADER('Special') -
ON(49,4,CH)   HEADER('Operations') -
ON(390,4,CH)  HEADER('Auditor')

/*
//RACFCNTL   DD *
SORT        FIELDS=(5,8,CH,A)
INCLUDE COND=((44,1,CH,EQ,C'Y',OR,
              49,1,CH,EQ,C'Y',OR,
              390,1,CH,EQ,C'Y'),AND,
              5,4,CH,EQ,C'0200')
/*
```

Sample RACFICE Report: Output

- 1 -

User IDs With Extraordinary Global Authorities

05/01/19

User ID	User Name	Special	Operations	Auditor
-----	-----	-----	-----	-----
AUDTR01	EXTERNAL AUDITOR 01	NO	NO	YES
AUDTR02	EXTERNAL AUDITOR 02	NO	NO	YES
FRED	FRED THE OPERATOR	NO	YES	NO
IBMUSER		YES	YES	YES
MARKN	#####	YES	YES	YES
SYSPRG1	SYSTEMS PROGRAMMER 1	YES	NO	NO

An Introduction to ICETOOL: OCCURS

- The **OCCURS** (or **OCCUR**) operator prints each unique value and its count (how many records it appears in) for the field you specify. You can use various options (title elements, headings, etc.) as for **DISPLAY**.
- The syntax is:

```
OCCURS FROM(indd) ON(field<,parms>)  
ON(VALCNT<,parms> options
```

- **...where**
 - ▶ **indd** is the DD name of the input data set
 - ▶ **field** is the starting position, length and data type of the field to be displayed in the report
 - **VALCNT** is a special keyword for the count field
 - ▶ **ON(field)** can be (and usually is) repeated, once for each field up to 10 times

An Introduction to ICETOOL: OCCURS...

- **Example: Create a report which counts all of the RACF events by hour**
 - ▶ The time is in hh:mm:ss format starting in column 23
- **The ICETOOL OCCURS statement for this is:**

```
OCCURS FROM(IRRADU00) LIST(PRINT) -  
  PAGE -  
  TITLE('RACF Activity by Hour') -  
  DATE(YMD/) -  
  TIME(12:) -  
  BLANK -  
  ON(23,2,CH)                HEADER('Hour') -  
  ON(VALCNT)                 HEADER('RACF Events Logged')
```

Sample RACFICE Report: OCCURS Output

- 1 - RACF Activity by Hour 05/02/06 08:46:51 pm

Hour	RACF Events Logged
00	756
01	160
02	170
03	214
04	220
05	206
06	228
07	244
08	320
09	390
10	398
11	448
12	378
13	704
14	1308
15	762
16	762
17	516
18	260
19	296
20	160

An Introduction to ICETOOL: SPLICE

- The **SPLICE** operator allows you to join together fields from different records that share a common value
- The syntax is:

SPLICE FROM(indd) TO(outdd) ON(onfield) WITH(withfield)

...where

- ▶ indd is the DD name of the input data set
- ▶ onfield is the starting position, length, and data type of the field to be used for matching “key” values.
 - ON(onfield) can be repeated up to 10 times
- ▶ withfield is the starting position, length, and data type of a field which is to be overlaid into the new record
 - ON(withfield) can be repeated up to 50 times.

An Introduction to ICETOOL: SPLICE Example...

- **The steps to follow when you want to SPLICE records from two different record types:**
 1. Identify the fields that you want in the output records
 2. Identify the source of these fields in the input records
 3. Map out a “common record format” that contains all of information from for #1
 4. Reformat each of the record types from #2 into the format defined in #3
 5. SPLICE the records from #4
 6. Write a report using the records created in #5

An Introduction to ICETOOL: SPLICE Example

- **Let's create a report which shows all of the user IDs in the RACF data base that have a UID and for those user IDs show the SPECIAL, OPERATIONS, AUDITOR, and the z/OS UNIX UID that is assigned to the user**
 1. **What fields are we interested in?**
 - **USBD_NAME (columns 10-17)**
 - **USBD_SPECIAL (columns 44-47)**
 - **USBD_OPER (columns 49-52)**
 - **USBD_AUDITOR (columns 390-393)**
 - **USOMVS_NAME (columns 10-17)**
 - **USOMVS_UID (columns 19-28)**
 2. **What records are these fields in?**
 - **The USBD fields are in USER BASIC DATA, record type 0200**
 - **The USOMVS fields are in USER OMVS DATA, record type 0270**

An Introduction to ICETOOL: SPLICE Example...

3. Let's define a common record format for these two records:

Columns	Field	Source/Comments
01-04	Record Length	Created by DFSORT
05-12	User ID	0200 and 0270 record; "Key" field
14-21	Owner	0200 record, blank for 0270 record
23-26	Special	0200 record, blank for 0270 record
28-31	Operations	0200 record, blank for 0270 record
33-36	Auditor	0200 record, blank for 0270 record
38-41	Revoked	0200 record, blank for 0270 record
43-46	Restricted	0200 record, blank for 0270 record
48-57	UID	0270 record, blank for 0200 record

An Introduction to ICETOOL: SPLICE Example ...

4. Reformat the records into the common format (JCL):

```
//SPLICE      EXEC PGM=ICETOOL
//IRRDBU00   DD DISP=SHR,DSN=MARKN.TEST.IRRDBU00
//USERS     DD DISP=(NEW,DELETE,DELETE),SPACE=(CYL,(20,5,0))
//UIDS      DD DISP=(NEW,DELETE,DELETE),SPACE=(CYL,(20,5,0))
//TEMP0001  DD DISP=(NEW,DELETE,DELETE),SPACE=(CYL,(20,5,0))
//CONCAT    DD DISP=(OLD,DELETE,DELETE),DSN=*.USERS,VOL=REF=*.USERS
//          DD DISP=(OLD,DELETE,DELETE),DSN=*.UIDS,VOL=REF=*.UIDS
//DFSMSG    DD SYSOUT=*
//TOOLMSG   DD SYSOUT=*
//PRINT     DD SYSOUT=*
```

An Introduction to ICETOOL: SPLICE Example ...

4. Reformat the records into the common format (JCL):

```
//TOOLIN DD *
  SORT FROM(IRRDBU00) USING(CTL1)
//CTL1CNTL DD *
  OPTION VLSHRT
  SORT FIELDS=(10,8,CH,A)
  OUTFIL FNAMES=USERS,INCLUDE=(5,4,CH,EQ,C'0200'),
    OUTREC=(1,4,10,8,X,30,8,X,44,4,X,49,4,
    X,390,4,X,54,4,X,546,4,11X)
  OUTFIL FNAMES=UIDS,INCLUDE=(5,4,CH,EQ,C'0270'),
    OUTREC=(1,4,10,8,35X,19,10)
/*
```


An Introduction to ICETOOL: SPLICE Example ...

5. **SPLICE** the records - Add the **SPLICE** statement to the **ICETOOL** statements:

```
//TOOLIN DD *  
  SORT FROM(IRRDBU00) USING(CTL1)  
  SPLIC FROM(CONCAT) TO(TEMP001) -  
    ON(5,8,CH) WITH(48,10) WITHALL
```

An Introduction to ICETOOL: SPLICE Example ...

6. Define the report format - Add the DISPLAY statement to the ICETOOL statements

```
//TOOLIN DD *
  SORT FROM(IRRDBU00) USING(CTL1)
  SPLIC FROM(CONCAT) TO(TEMP0001) -
    ON(5,8,CH) WITH(48,10) WITHALL
DISPLAY FROM(TEMP0001) LIST(PRINT) -
  PAGE -
  TITLE('User ID Attributes') -
  DATE(YMD/) -
  TIME(12:) -
  BLANK -
  ON(05,8,CH) HEADER('User ID') -
  ON(14,8,CH) HEADER('Owner') -
  ON(23,4,CH) HEADER('Spec') -
  ON(27,4,CH) HEADER('Oper') -
  ON(33,4,CH) HEADER('Audit') -
  ON(37,4,CH) HEADER('Revoke') -
  ON(43,4,CH) HEADER('Rstd') -
  ON(48,10,CH) HEADER('UID')
```

An Introduction to ICETOOL: SPLICE Example ...

7. ... And Now the Report

User ID	Owner	Spec	Oper	Audit	Revoke	Rstd	UID
-----	-----	----	----	-----	-----	----	-----
A6	MARKN	NO	NO	NO	NO		000000001
BBB4	MARKN	NO	NO	NO	NO		000000002
HCHECKER	MARKN	NO	NO	NO	NO		000000003
IBMUSER	IBMUSER	YES	YES	YES	NO		000000004
LOWAUTH	MARKN	NO	NO	NO	NO		000000005
MARKN	IBMUSER	YES	YES	YES	NO		000000006
NOAUTH	MARKN	NO	NO	NO	NO		000000007
T	MARKN	NO	NO	NO	NO		000000008
TESTPARM	MARKN	NO	NO	NO	NO		000000009
TESTPRM	MARKN	NO	NO	NO	NO		000000010
TP	MARKN	NO	NO	NO	NO		000000011
TPARM	MARKN	NO	NO	NO	NO		000000012

What RACF DB Reports Are in RACFICE?

- **Users who have extraordinary global/group RACF attributes**
- **Discrete data set/general resource profiles which contain generic characters**
- **Users who have more than 20 group connections**
- **Count of user/group/data set/general resource (by class) profiles**
- **User IDs with group privileges above USE**
- **Data set standard and general resources with a UACC of other than NONE**
- **Data set standard and conditional access lists with ID(*) of other than NONE**
- **General resource standard and conditional access lists with ID(*) of other than NONE**
- **Users who have explicit RRSF associations defined**
- **User IDs with an OMVS segment**
- **OS/390 UNIX super users (UID of zero)**
- **OS/390 UNIX UIDs which are used more than once**
- **HLQs with excessive generic profiles**
- **HLQs with excessive fully-qualified generic profiles**
- **User profiles defined in the past 90 days**

What SMF RACFICE Reports are in RACFICE?

- **Events associated with a specific user**
- **User IDs with excessive incorrect passwords**
- **Terminals with excessive incorrect passwords**
- **Accesses allowed due to WARNING mode profiles**
- **Accesses allowed because the user has OPERATIONS**
- **Users who are using Automatic Command Direction**
- **Users who are directing command explicitly**
- **User who log on with LOGON BY**
- **RACLINK audit records**
- **Users who are using password synchronization**
- **Access violations**

An Introduction to DFSORT: New Cool Stuff

- **In December 2004, DFSORT introduced these neat new functions with PTFs UQ95214 (for z/OS DFSORT V1R5) and UQ95213 (for DFSORT R14)**
 - ▶ ICETOOL
 - Multi-line headers for DISPLAY and OCCUR
 - KEEPBASE, VLENMAX, VLENONLY for SPLICE
 - ▶ Reformatting for DFSORT
 - IFTHEN – reformat different records in different ways
 - OVERLAY – just overlay specific columns
 - ▶ New data formats for DFSORT and ICETOOL
 - SFF, UFF, DCn, TCn, Den, Ten
 - ▶ Larger numbers and constants for DFSORT and ICETOOL
 - Up to 31 digits
 - ▶ and more!

- **See “User Guide for DFSORT PTFs UQ95214 and UQ05213” at <http://www.ibm.com/storage/dfsor>**

An Introduction to DFSORT: Sources of Information

■ Sources of Information

- ▶ The DFSORT website at www.ibm.com/storage/dfsor which contains examples, tricks, Q&A, papers, etc.
- ▶ The DFSORT library at www.ibm.com/servers/storage/support/software/sort/mvs/srtmpub.html, which has all of the DFSORT books and papers
- ***DFSORT: Getting Started*** is an excellent tutorial on DFSORT, DFSORT's ICETOOL, and DFSORT Symbols
- For the latest information on the newest functions, such as IFTHEN, OVERLAY, and the new data formats, see www.ibm.com/servers/storage/support/software/sort/mvs/pdug/

Disclaimer

The information contained in this document is distributed on an "as is" basis, without any warranty either express or implied. The customer is responsible for use of this information and/or implementation of any techniques mentioned. IBM has reviewed the information for accuracy, but there is no guarantee that a customer using the information or techniques will obtain the same or similar results in its own operational environment.

In this document, any references made to an IBM licensed program are not intended to state or imply that only IBM's licensed program may be used. Functionally equivalent programs that do not infringe IBM's intellectual property rights may be used instead. Any performance data contained in this document was determined in a controlled environment and therefore, the results which may be obtained in other operating environments may vary significantly. Users of this document should verify the applicable data for their specific environment.

It is possible that this material may contain references to, or information about, IBM products (machines and programs), programming, or services that are not announced in your country. Such references or information must not be construed to mean that IBM intends to announce such IBM Products, programming or services in your country.

IBM retains the title to the copyright in this paper as well as title to the copyright in all underlying works. IBM retains the right to make derivative works and to republish and distribute this paper to whomever it chooses.