

===== TGCS UPS Control Installation and Operation =====

DESCRIPTION

TGCS Control Package for monitoring the status of the SP700 UPS

SUPPORTED OPERATING SYSTEMS

- Microsoft(R) Windows(R) 7 (32-bit)
- Microsoft(R) Windows(R) 7 (64-bit)

TGCS UPS Controls

Front panel Switch settings

1. Both Switches in the Off position (Up)

Standalone Mode: in this mode the UPS ignores presence or absence of an active RS232 connection and always switches to battery if AC power is lost. This mode allows the UPS to operate in DC Mode without an RS232 connection to the POS Terminal, similar to what would be the case with an off-the-shelf UPS in today's market.

2. Both Switches in the On position (Down)

Normal Mode: prevents the UPS from switching to battery if the POS terminal is powered off. This mode is intended to extend the life of the battery in stores where primary AC power is periodically removed, usually at the end of the day. This mode requires that a cable be attached between the UPS and the POS terminal for proper UPS operation.

How to install and Run the Program

1. Extract the compressed file contained in the release package
2. Execute Setdefault.exe file
3. Reboot the system, the function will work on COM A by default without any additional configuration setups
4. A shortcut will be created on the Windows desktop called UPS_Config.exe
5. Execute the UPS_config.exe shortcut on the Desktop to alter program settings

How to modify the UPS Monitoring Settings

1. Click the drop down menu on the COM Port Number setting and select COM port (A or B), depending on the port where the Signal cable is connected between the POS and UPS.
2. See Configuration section below

Note: The UPS will remain in control even if the UPS Configuration Tool application is closed, as this is a Windows service that will remain in place.

Configuring the UPS Monitoring

1. Disable Pop Notification

By default this box is checked. When this box is not checked (enabled), it allows notification pop-up on the Windows desktop. UPS events are logged in a new Windows system event log entitled **TGCS UPS Log** regardless if this box is checked or not.

Events that will be logged are:

1. When AC power is first removed

Event ID 0: An AC power failure was detected, the system is currently running on UPS power

2. Subsequent notifications as long as AC power is removed

Event ID 0: The system is currently running on UPS power

3. Notice when the UPS battery is low

Event ID 0: TGCSUPS Battery Low

4. Notice when AC power is restored

Event ID 0: TGCSUPS AC Normal

2. Seconds between power failure and first event and notification

Set this to desired time between the power loss event and the first notification.

3. Seconds between subsequent power failure and first event and notification

Set this to desired time between the power loss event and the subsequent notifications.

4. Click "Apply" button

How to disable UPS Monitoring

1. Click the drop down menu on the COM Port Number setting and select "none"
2. Click "Apply" button