

Documentation for DirectoryObject.addProperty()

Add/update the value of the specified property.

Synopsis

directoryObject.addProperty(name, value)

Arguments

name - String representing the name of the property to be created/modified.

value - The value to add the property to.

Description

This method changes the value of the specified property, or adds the specified property if it does not already exist. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. For multi-valued objects, `addProperty()` will add the values to specified property in the directory object and NOT replace them. The value's type (syntax) of object must be compatible with the syntax of the specified property. This method is available for the following data types:

- `void addProperty(String name, Collection value);`
- `void addProperty(String name, Date value);`
- `void addProperty(String name, Map value);`
- `void addProperty(String name, boolean value);`
- `void addProperty(String name, byte value);`
- `void addProperty(String name, String value);`
- `void addProperty(String name, number value);`

Usage

```
directoryObject.addProperty("eruid", "jdoe");
```

The `getProperty` method returns a Java™ array of objects that is actually stored in a JavaScript™ `JSONArray` object. Unlike a standard JavaScript array, `JSONArray` objects are used to access members of a Java array. Since Java arrays cannot be resized, the size of a `JSONArray` object can not be changed. Also, `JSONArray` objects are typed. Setting a `JSONArray` element to the wrong type will throw a JavaScript error.

In Tivoli Identity Manager, a `JSONArray` object cannot be passed directly back into a `addProperty` method. The `JSONArray` array may be converted into a standard JavaScript array as follows:

```
jsAliases = new Array();  
myPerson = person.get();  
aliases = myPerson.getProperty("eraliases");  
for (i=0; i < aliases.length; i++) {  
    jsAliases[i] = aliases[i];  
}  
jsAliases[aliases.length] = "myNewAlias";
```

```
myPerson.addProperty("eraliases", jsAliases);  
person.set(myPerson);
```