

Select accounts to exclude from reconciliations:

To select accounts to exclude from reconciliations, do the following:

1. Create an LDIF file specifying the accounts to exclude from reconciliation and the services on which these accounts exist.
2. Import the LDIF file to the LDAP Directory Server.

Excluding accounts from reconciliation:

During reconciliations, all accounts are returned from the managed resource, unless otherwise specified by a query. Accounts are automatically adopted if the account is owned by a recognized user in the system or if an alias exists for any account.

However, the IBM Tivoli Identity Manager Server can be configured to prevent automatic adoption of specified accounts. This feature can be used to prevent system accounts, such as **root**, **lp**, **sys**, and **etc** in UNIX resources, from automatically being adopted. This prevents users from accidentally or maliciously adopting and modifying sensitive accounts.

Although these accounts are not automatically adopted, these accounts can still be manually adopted by an administrative user.

The accounts to exclude from reconciliations are specified in an LDIF file. The following is an example of entries in an LDIF file:

```
dn: ou=excludeAccounts, ou=ITIM, ou=ITIM, dc=com
ou: excludeAccounts
objectClass: top
objectClass: organizationalunit
dn: cn=SolarisProfile, ou=excludeAccounts, ou=ITIM, ou=ITIM, dc=com
erObjectProfileName: SolarisProfile
objectClass: top
objectClass: eridentityexclusion
cn: SolarisProfile
erAccountID: root
erAccountID: admin
```

The *cn* and *erObjectProfileName* is the name of the service profile. Excluded accounts are defined by the *erAccountID* attribute. The example excludes the root and admin accounts from automatically being adopted when a reconciliation is run on a Solaris service.