

VisualAge Pachbase



# The Administrator's Procedures Windows 2000 or NT Server

*Version 3.0*





VisualAge Pachbase



# The Administrator's Procedures Windows 2000 or NT Server

*Version 3.0*

**Note**

Before using this document, read the general information under "Notices" on page v.

According to your licence agreement, you may consult or download the complete up-to-date collection of the VisualAge Pacbase documentation from the VisualAge Pacbase Support Center at:

<http://www.ibm.com/software/ad/vapacbase/productinfo.htm>

Consult the Catalog section in the Documentation home page to make sure you have the most recent edition of this document.

**Third Edition (May 2002)**

This edition applies to the following licensed programs:

- VisualAge Pacbase Version 3.0

Comments on publications (including document reference number) should be sent electronically through the Support Center Web site at: <http://www.ibm.com/software/ad/vapacbase/support.htm> or to the following postal address:

IBM Paris Laboratory  
1, place Jean-Baptiste Clément  
93881 Noisy-le-Grand, France.

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© Copyright International Business Machines Corporation 1983,2002. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

<b>Notices . . . . .</b>	<b>v</b>
--------------------------	----------

<b>Trademarks. . . . .</b>	<b>vii</b>
----------------------------	------------

## **Chapter 1. Overview . . . . . 1**

Presentation of the Manual . . . . .	1
Presentation of the Procedures . . . . .	1
User Identification . . . . .	2
Access Authorization . . . . .	2
Abnormal Ending . . . . .	3
List of Run-Time Errors . . . . .	4
Procedures Error Management . . . . .	4
Definition and Submission of Procedures . . . . .	4
Definition . . . . .	4
Execution Mode . . . . .	5
Server Start-Up . . . . .	6
3270 Emulator start-up . . . . .	6

## **Chapter 2. Administration Database Management. . . . . 7**

ARCH - Backup for Administration. . . . .	7
ARCH - Introduction . . . . .	7
ARCH - Input / Processing / Results . . . . .	7
ARCH - Description of Steps . . . . .	10
ARCH - Execution Script . . . . .	10
PACS - Backup for Administration. . . . .	12
PACS - Introduction . . . . .	12
PACS - Input / Processing / Results . . . . .	13
PACS - Description of Steps . . . . .	13
PACS: Execution Script . . . . .	14
REOR - Reorganization for Administration . . . . .	15
REOR - Introduction . . . . .	15
REOR - Input / Processing / Results . . . . .	16
REOR - Description of Steps. . . . .	20
REOR - Execution Script . . . . .	20
REST - Restoration for Administration . . . . .	23
REST - Introduction . . . . .	23
REST - Input / Processing / Results . . . . .	24
REST - Description of Steps . . . . .	26
REST - Execution Script . . . . .	27

## **Chapter 3. Development Databases Management . . . . . 31**

Backup Procedures . . . . .	31
Introduction . . . . .	31
PACS - Input Common to Managers . . . . .	31
Database Management. . . . .	32
MLIB - Introduction . . . . .	32
MLIB - Input / Processing / Results . . . . .	33
Database Backup . . . . .	34
SAVE - Introduction . . . . .	34
SAVE - Input / Processing / Results . . . . .	35
Sub-Network Backup . . . . .	36
SASN - Introduction . . . . .	36

SASN - User Input . . . . .	36
Partial Sub-Network Extraction. . . . .	36
UXSR - Introduction . . . . .	36
UXSR - User Input . . . . .	38
PACS - Description of Steps . . . . .	39
PACS - Execution Script . . . . .	40
UPDT - Freeze . . . . .	41
UPDT - Introduction . . . . .	41
UPDT - Input. . . . .	42
UPDT - Description of Steps. . . . .	42
UPDT - Execution Script . . . . .	43
SASY - Database System Backup Complement. . . . .	45
SASY - Introduction . . . . .	45
SASY - Description of Steps . . . . .	45
SASY - Execution Script . . . . .	46
REST - Database Restoration. . . . .	47
REST - Introduction . . . . .	47
REST - Input / Processing / Results . . . . .	47
REST - Description of Steps . . . . .	51
REST - Execution Script . . . . .	52
RESY - Database System Restoration Complement	54
RESY - Introduction . . . . .	54
RESY - Input / Processing / Results . . . . .	55
RESY - Description of Steps . . . . .	58
RESY - Execution Script . . . . .	59
ARCH - Journal Archival. . . . .	61
ARCH - Introduction . . . . .	61
ARCH - Input / Processing / Results. . . . .	62
ARCH - Description of Steps . . . . .	65
ARCH - Execution Script . . . . .	65
REOR - Reorganization . . . . .	67
REOR - Introduction . . . . .	67
REOR - Input / Processing / Results. . . . .	69
REOR - Description of Steps. . . . .	73
REOR - Execution Script . . . . .	73

## **Chapter 4. Manager's Utilities . . . . . 77**

PACX - Extractions . . . . .	77
PACX - Introduction . . . . .	77
PACX - Input Common to Extractors . . . . .	77
Extraction of Archived Transactions . . . . .	79
EXPJ - Introduction. . . . .	79
EXPJ - User Input . . . . .	80
Extraction of Libraries. . . . .	80
EXLI - Introduction. . . . .	80
EXLI - User Input . . . . .	80
Extraction for Purge . . . . .	81
EXPU - Introduction . . . . .	81
EXPU - User Input . . . . .	82
Standardization Utility . . . . .	83
RMEN - Introduction . . . . .	83
RMEN - User Input. . . . .	86
RMEN - Recommendations and Restrictions . . . . .	87
Sub-Network and Entities Comparison . . . . .	90

CPSN - Introduction . . . . .	90
CPSN - User Input . . . . .	90
PACX - Description of Steps . . . . .	91
PACX - Execution Script . . . . .	92
Session Management . . . . .	94
Introduction . . . . .	94
ESES - Session Numbers Extraction . . . . .	94
ESES - Introduction. . . . .	94
ESES - User Input . . . . .	95
ESES - Description of Steps . . . . .	95
ESES - Execution Script . . . . .	95
CSES - Compression of Session Numbers . . . . .	96
CSES - Introduction . . . . .	96
CSES - User Input . . . . .	96
CSES - Description of Steps . . . . .	97
CSES - Execution Script . . . . .	98
Database statistics . . . . .	99
STAT - Introduction . . . . .	100
STAT - User input . . . . .	101
STAT - Description of steps. . . . .	101
STAT - Execution JCL . . . . .	101

**Chapter 5. Analysis of Activity and Quality Control. . . . . 103**

Analysis of Activity . . . . .	103
ACTI - Introduction . . . . .	103
ACTI - Query Language. . . . .	110
ACTI - User Input . . . . .	111
ACTI - Description of Steps. . . . .	111
ACTI - Execution Script . . . . .	111
Pacbench Quality Control . . . . .	113
Introduction . . . . .	113
Analysis . . . . .	113
PQCA - Introduction . . . . .	113
PQCA - User Input . . . . .	114
PQCA - Description of Steps . . . . .	114
PQCA - Execution Script. . . . .	115
Extraction of Quality Rules . . . . .	117
PQCE - Introduction . . . . .	117
PQCE - Input / Processing / Results . . . . .	118
PQCE - Description of Steps . . . . .	120
PQCE - Execution Script. . . . .	120

**Chapter 6. Versioning Facilities. . . . . 123**

Standard Bridge (PCM) . . . . .	123
Introduction . . . . .	123
Database Automatic Freeze . . . . .	123
HIPM - Introduction . . . . .	123
HIPM - Input / Processing / Results . . . . .	124
HIPM - Description of Steps . . . . .	124
HIPM - Execution Script. . . . .	125
Generation Simulation . . . . .	126
SIPM - Introduction . . . . .	126
SIPM - Input / Processing / Results. . . . .	127
SIPM - Description of Steps . . . . .	127
SIPM - Execution Script . . . . .	128
Extraction of the Development Database Data . . . . .	129
EXPM - Introduction . . . . .	129
EXPM - Input / Processing / Results . . . . .	130
EXPM - Description of Steps . . . . .	131

EXPM - Execution Script . . . . .	131
Comparison with Extracted Files . . . . .	132
CPPM - Introduction . . . . .	132
CPPM - Input / Processing / Results . . . . .	133
CPPM - User File . . . . .	133
CPPM - Description of Steps . . . . .	135
CPPM - Execution Script . . . . .	135
Integrity Control of Events/Elements . . . . .	136
CHPM - Introduction. . . . .	136
CHPM - Input / Processing / Results . . . . .	137
CHPM - Description of Steps . . . . .	137
CHPM - Execution Script . . . . .	137
Pac/Transfer . . . . .	139
Introduction . . . . .	139
Processes Chronology . . . . .	140
TRUP - Update of Transfer Parameters . . . . .	140
TRUP - Introduction . . . . .	140
TRUP - User Input . . . . .	144
TRUP - Description of Steps . . . . .	146
TRUP - Execution Script. . . . .	146
Print of Transfer Parameters . . . . .	148
TRED - Introduction . . . . .	148
TRED - User Input . . . . .	148
TRED - Description of Steps . . . . .	149
TRED - Execution Script. . . . .	149
TRJC - Compression of Archived Journal . . . . .	151
TRJC - Introduction . . . . .	151
TRJC - User Input . . . . .	152
TRJC - Description of Steps. . . . .	153
TRJC - Execution Script . . . . .	153
TRPF - Creation of the Transfer File . . . . .	155
TRPF - Introduction . . . . .	155
TRPF - User Input. . . . .	155
TRPF - Description of Steps . . . . .	157
TRPF - Execution Script . . . . .	157
Preparing DSMS Environment. . . . .	159
TRDU - Introduction . . . . .	159
TRDU - User Input . . . . .	160
TRDU - Description of Steps . . . . .	162
TRDU - Execution Script . . . . .	162
DSMS Update Before Database Update. . . . .	164
TRRP - Generation of Transfer Transactions . . . . .	164
TRRP - Introduction . . . . .	164
TRRP - User Input. . . . .	167
TRRP - Description of Steps . . . . .	168
TRRP - Execution Script . . . . .	168
Update of the Development Database . . . . .	170
Reinitialization of DSMS Environment . . . . .	170
ASCII Sort . . . . .	171
PEAS - User Parameters, ASCII Sort . . . . .	171
PEAS - Introduction . . . . .	171
PEAS - Description of Steps . . . . .	171
PEAS - Execution Script . . . . .	171
PGAS - Generation-Request Sort, ASCII Format . . . . .	171
PGAS - Introduction . . . . .	171
PGAS - Description of Steps . . . . .	172
PGAS - Execution Script. . . . .	172
PPAS - Environment Sort, ASCII Format . . . . .	172
PPAS - Introduction . . . . .	172
PPAS - Description of Steps . . . . .	172
PPAS - Execution Script . . . . .	173

---

## Notices

References in this publication to IBM products, programs, or services do not imply that IBM intends to make these available in all countries in which IBM operates. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Subject to IBM's valid intellectual property or other legally protectable rights, any functionally equivalent product, program, or service may be used instead of the IBM product, program, or service. The evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, are the responsibility of the user.

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the IBM Director of Licensing, IBM Corporation, North Castle Drive, Armonk NY 10504-1785, U.S.A.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact IBM Paris Laboratory, SMC Department, 1 place J.B.Clément, 93881 Noisy-Le-Grand Cedex. Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

IBM may change this publication, the product described herein, or both.





---

## Trademarks

IBM is a trademark of International Business Machines Corporation, Inc. AIX, AS/400, CICS, CICS/MVS, CICS/VSE, COBOL/2, DB2, IMS, MQSeries, OS/2, PACBASE, RACF, RS/6000, SQL/DS, TeamConnection, and VisualAge are trademarks of International Business Machines Corporation, Inc. in the United States and/or other countries.

Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States and/or other countries.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States and/or other countries.

UNIX is a registered trademark in the United States and/or other countries licensed exclusively through X/Open Company Limited.

All other company, product, and service names may be trademarks of their respective owners.



---

# Chapter 1. Overview

---

## Presentation of the Manual

This manual contains the descriptions of all the batch procedures used by a VisualAge Pacbase Database Administrator.

These procedures are related mainly to the following operations fields:

- Management of the administration Database,
- Administration of the development Databases,
- Manager's utilities,
- Analysis of activity and quality control,
- Management of versions.

---

## Presentation of the Procedures

Batch processes are grouped into procedures. The objective of the following chapters is to present each of the procedures that are likely to be used, and to specify their execution conditions.

The following elements are included for each procedure:

- a general introduction including:
  - the Execution Conditions,
  - operations to be performed in case of Abnormal Executions.
- the description of the User Input, Processes and Results obtained, possibly including use recommendations.
- the Description of Steps.

To use a procedure on a given Database, the user must have the corresponding authorization.

Each user has:

- a general level of authorizations to the batch procedures,
- a specific authorization level per Database

User authorizations are defined in the Administration Database.

---

## User Identification

Batch procedures which access the Databases require a user identification ('\*' -type) line at the beginning of user input to identify the user as well as the Library and session in which he/she wishes to work.

Some information entered on this line is the same as that entered on the Sign-on screen. It is thus possible to check if the user's commands are compatible with his/her authorizations.

Before running any batch procedure, the user must make sure he/she has the adequate authorization level.

Position	Length	Value	Meaning
2	1	*	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
19	3	bbb	Library code
22	4	nnnn	Session number
26	1	T	Test session
		H	Frozen session
27	1		With the UPDT procedure in case of multiple deletion:
		N	Print all transactions, including generated transactions (default option)
		O	Print transactions entered by the user and erroneous generated transactions
		E	Print erroneous transactions only
			The 2 following fields must be valued for all extraction procedures generating update transactions which will modify a Library/session under DSMS control (you can also value them on the UPDT '*' line,
40	3		Product code (3 character-code),
43	6		Change number (6 character-code, non-significant zeros must be entered),
			These two codes will appear in the Journal after the execution of UPDT
49	1		Transfer of Entity Lock:
		blank	Replacement of the user code which locks the entity with the '*' line
		1	New entities created from the extracted entities are not locked after the execution of UPDT
		2	The user code which locks the entity is kept
50	1		Transfer of the password on the extraction procedures, on the '*' line of output transactions
		blank	The password is not transferred in the output file,
		1	The password is transferred, (Note : for EXTR, the '*' line is transferred in the output file only if you have entered a 'C' in Column 1)

---

## Access Authorization

An '\*' line with a user code and password is required by all procedures.

The Administrator manages the user access authorisations on batch procedures via the Administrator workbench.

---

## Abnormal Ending

Abends may occur during the execution of a batch program. Input-output errors on the system files or on the Database cause a forced abnormal end with a return code '12', described by a message on the .Log file of the procedure.

When an abend occurs, you must find the error message. This message is displayed in the following manner:

```
PROGR : pppppp INPUT-OUTPUT ERROR : FILE ff OP : oo STATUS : ss END OF  
RUN DUE TO PROVOKED ABEND
```

In most cases, examining the status and type of operation enables you to find the cause of the abnormal execution.

The summary table below lists the most common values for the status and type of operation.

Code	Operation
W	WRITE
RW	REWRITE
RU	READ UPDATE
OP	OPEN
CL	CLOSE
D	DELETE
R	READ
P	START
RN	READ NEXT

Status	Message
21	Sequence error
22	Duplicate key
23	No record found
24	Boundary violation
30	System error
34	Boundary violation (sequential)
92	Logic error (For example, the opening of an already opened file)
93	File still open on line
95	Invalid or Incomplete file

When this message is absent, and the type of ABEND generated directly reports a problem in the VisualAge Pacbase system programs, contact the VisualAge Pacbase support at IBM. KEEP ALL LISTINGS that may be necessary to analyze the problem.

If an error is detected at the end of a procedure, the procedure is stopped with a return code other than zero. This return code can be retrieved via the "Return" variable right after the command which submits the procedure.

This prevents the execution of the next procedures if various procedures are executed in sequence.

## List of Run-Tile Errors

This list is a reminder of the most common errors and their meaning.

Number	Meaning
-----	-----
004	Invalid file name
005	Invalid device specification
007	No more disk space
009	Directory full or does not exist
013	File not found
026	Block I-O error
027	Device not available
028	Disk space exhausted
033	Physical I-O error
105	Memory allocation error
116	Cannot allocate memory
135	File not found
150	Program abandoned on user request
157	Not enough program memory: object file too big to load
170	System program not found
173	Called program file not found
188	File name too long
198	Not enough program memory: object file too large to load
207	Machine does not exist on the network
208	Network communication error
209	Network communication error
221 !	
222 !>	Error during a SORT
223 !	

## Procedures Error Management

If an error is detected at the end of a procedure, the procedure is stopped with a return code other than zero. This return code can be retrieved via the "Return" variable right after the command which submits the procedure.

This prevents the execution of the next procedures if various procedures are executed in sequence.

---

## Definition and Submission of Procedures

### Definition

A procedure is a Windows Scripting script (.wsf), which includes Visual Basic Script scripts (.vbs).

Each procedure can be executed only via a launch Script (.wsf) which contains the following information:

- a <resource id> field constituted of input data, (or the definition of an input file),
- the user code,
- the Database external name (directory under \DATA).

You must enter all this information before launching the procedure.

Other elements can also be specified to assign files or parameterize procedures. (e.g. whether the message must be displayed or written in a file).

Temporary files, execution reports and output files are found under directories created dynamically.

- Temporary files are located under:  
    \DATA\[Base\_name]\TMP\[user\_code]\[proc\_name]-[number]
- Output files, execution reports are located under:  
    \DATA\[Base\_name]\USERS\[user\_code]\ [proc\_name]-[number]  
    This number is an application execution number ; by default it is the process number of the procedure.

## Execution Mode

There are various execution modes.

You can execute the launch script (BVPproc.wsf) or the supervisor (PRBVP.vbs):

- via a command line,
- by double-clicking on them,
- via the 'Start' menu. Access the shortcut: [[dbase\_name] Database Utilities] in the [VisualAge Pacbase Server] group of [dbase\_name] and enter [Script\_name].

NB: The PRBVP.vbs supervisor is an independent VBScript procedure which starts the execution of the launch scripts. It requires 2 arguments: [dbase\_name] [script\_name] ; [dbase\_name] is located under directory \DATA.

To be executed, each procedure requires the definition of various elements:

1. either in the launch script: This launch script, BVPxxxx.wsf, is in Windows Scripting.
    - User code,
    - Database external name (directory under \DATA),
    - The input data is described in the <resource id> field of the script and retrieved in the BVP\_Resource environment variable (in this case, the data volume is limited to 141 lines), or can also be contained in a file named in the BVP\_Input environment variable (in this case, the data volume is not limited).
    - You can assign files, other than the input file, 'in substitution' by defining an environment variable with:
      - . "StepName\_FileName" for a substituted assignment in a particular step,
      - . or "ProcName\_FileName" for a substituted assignment in the whole procedure.For example, you define the variable WshEnv("PTU907\_PAC7IN") = Fil\_In with pathname to indicate a substituted assignment in the PTU907 step of the PPAS procedure.
    - Information or error messages are:
      - . either displayed on the screen (MsgTyp = 1),
      - . or edited in a file (MsgTyp =2). This is the default value.You parameterize this in the BVP\_Msg environment variable.
- Warning: VA Pac does not manage errors and missing elements in the launch script.

2. or in the part which is common to all procedures. This common part, named 'INIT.vbs', is a VBScript inclusion, in each procedure.

- Retrieval of the arguments: [base] and [user]
- Constitution of the MB file (input data) which contains the user code, password, sometimes a command and analysis elements.

If the [user] user code is not found in the launch script, it is searched for in the input file.

If the elements required for the execution of the procedure are absent, an error occurs.

Note:

The input file of the retrieval procedures can be defined in the launch script of the procedure via an environment variable: WshEnv("NStep\_NFile") = "old 2.5 full file name" which enables the substitution in the procedure. The 'USER' parameter is required for the retrieval procedures, except if the procedure accepts a user input file different from the file of the 2.5 version.

A PC file (Database backup) is defined for each environment variable: WshEnv("BVP\_SaveName").

Via this variable, the parameter for the definition of assignments (PAC7PC, PAC7PD, PAC7PY) is created. The result PC file is then correctly specified, and the data specific to each option cannot be overwritten.

If this environment variable is not indicated in the script, the default value is : [Dir\_SAVE & "\PC].

---

## Server Start-Up

The on-line server must be installed in NT Service mode.

Workstations and terminals can then connect to VisualAge Pacbase.

Via the shortcut 'Start [Base\_name] Database Service' located under the programs group [VisualAge Pacbase Server] in the 'Start Menu', you can start the server on the [Base\_name] Database.

Via the shortcut 'Stop[Base\_name] Database Service' located under the programs group [VisualAge Pacbase Server] in the 'Start Menu', you can stop the server on the [Base\_name] Database.

---

## 3270 Emulator start-up

If you are working under Windows in character mode, you can access the VisualAge Pacbase server via a 3270 emulator installed on your PC.

The emulator must be configured accordingly, i.e., you must indicate the server port number and the address of the terminal on which the emulator is installed.



---

## Chapter 2. Administration Database Management

---

### ARCH - Backup for Administration

#### ARCH - Introduction

This procedure saves the Journal file as a sequential file, and re-initializes it both logically and physically.

Archived transactions do not override those transactions that were previously archived, but are added to them.

The archived-transaction file may be purged. Purged transactions may then be saved in another file (PQ).

Previously archived transactions can be purged, if requested. (However, non-archived journal transactions cannot be purged.)

#### EXECUTION CONDITIONS

On-line access must be closed.

#### ABNORMAL EXECUTIONS

If an abend occurs before the step that creates the Journal file, the procedure can be restarted as it is once the problem has been solved.

Otherwise, the procedure must be restarted after a modification of the user input in order to specify a re-initialization request without a backup of the Journal file, since it has already been backed up.

#### ARCH - Input / Processing / Results

Batch procedure access authorization option: one '\*' line with user code and password.

This procedure includes specific optional input to:

- Deactivate previously archived transactions that are considered obsolete.
- Signal the absence of previously archived transactions in input.
- Signal the unavailability of the Data file (AR) in input.
- Request only the re-initialization of the transaction file.

The structure of this input is as follows:

Position	Length	Value	Meaning
2	1	'S'	Line code
3	4	nnnn	Session number
7	8	ccymmdd	OR date up to which the user requests deactivation
15	1	'T'	Absence of previously archived transactions

Position	Length	Value	Meaning
16	1	'D'	Data file unavailable
17	1	'J'	Re-initialization without backup, the transactions already archived are NOT retrieved in output.

The session number and the date are exclusive. They are ignored if the absence of input transactions is signalled (refer to Section Recommendations).

The unavailability of the Data file is to be indicated only when this file has been physically deleted. (See Section Recommendations below.)

A request to re-initialize without archiving is necessary when the Journal file is physically deleted.

#### WARNING

In this case, the transactions which were already archived are not copied on to the transaction output file. (If this input file is automatically catalogued by the operating system, the transactions already archived may be lost unless the file is uncatalogued).

In an error occurs on one of the options, a message is printed and the archive is generated using the default options.

#### RECOMMENDATIONS

If there is no user input, this procedure can only be executed if the Database is in a consistent state, and if the archived transaction file is correctly formatted.

When the Database needs to be restored after an abend or a system failure, some information in the Specifications Dictionary is sometimes lost, thus preventing the execution of the backup and restoration procedures.

In this case, AND IN THIS CASE ONLY, columns 15 to 17 of the user input are to be used as follows:

- If the Data file (AR) is lost or has been flagged as 'inconsistent', a 'D' in column 16 means that the backup procedure will not take the Data file (AR) into account. However, the restoration procedure must be executed afterward, since under these conditions, the backup procedure leaves the database in an inconsistent state.
- If the Journal file (AJ) is lost or destroyed, a 'J' must be entered in column 17. As a result, the backup procedure formats an empty Journal file. The restoration procedure may then be executed (not compulsory). In this case, the content of the journal file (AJ) is lost.
- If the transactions Back-up file is lost or destroyed, an 'I' must be entered in column 15. As a result, the ARCH procedure reformats a new sequential backup file of (archived) transactions.

If one of these columns is accidentally set, and if the ARCH procedure is executed while the Database is in a consistent state, the consequences are:

- 'I' in col. 15: Previously archived transactions are lost. All transactions can be recovered by concatenating (-1) and (0) to obtain (+1).

- 'D' in col. 16: The ARCH procedure must be re-executed BEFORE any update. If an update is subsequently performed, the Database will be lost, and will have to be restored completely.
- 'J' in col. 17: The contents of the Journal file are definitely lost. The output Journal file, (+1 version in the case of generation data files), is created empty.

#### PRINTED OUTPUT

This procedure prints a report stating the number of archived transactions and, if applicable, the number of records that have been 'purged'.

#### RESULTS

Once this procedure is executed, a sequential file containing all archived transactions is obtained.

The Journal file which displays transactions on-line is re-initialized.

It is also possible to store on another file all transactions that have been purged.

#### NOTE

This procedure does not increment the session number.

## **ARCH - Description of Steps**

### ARCHIVAL OF JOURNAL FILE: PTU300

This step:

- writes obsolete transactions to be purged on to a special file, if the purge is requested in user input.
- positions a flag in the Data file indicating the journal archive.
- updates the file of archived transactions.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7JP	Save dir. : PJ	Input	Previously archived transactions
PAC7AJ	Journal dir. : AJ	Input	Journal to reinitialize from administration database
PAC7MB	User input	Input	User transaction
PAC7BM	Tmp dir. : WBM	Output	User transaction
PAC7AR	Base dir. : AR	Input/Output	Development Database data
PAC7PJ	Save dir. : PJ.new	Output	Archived update transactions
PAC7PQ	null	Output	Deactivated transactions (length=170) : modify file name to save deactivated transactions

Code	Physical name	Type	Label
PAC7EU	User dir. : ARCHEU300	Report	Output report
PAC7DD	User dir. : ARCHDD300	Report	Batch procedures authorization option

Return code:

- 0: No error detected on the files.
- 4: Error in journal record (Date or session number not numeric).
- 8: No access authorization for batch procedure OR invalid database (in this case, restart the procedure with 'D' in column 16 of the user input ).
- 12: Input-output error on a file.

#### RE-INITIALIZATION OF THE JOURNAL FILE: PTU320

This step executes two types of operations:

- Creates the first record in the Journal file,
- Re-initializes the data file flag with the Journal file's address.

Code	Physical name	Type	Label
PAC7BM	Tmp dir. : WBM	Input	User transaction
PAC7AR	Base dir. : AR	Input/Output	Administration Database data
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AJ	Journal dir. : AJ	Output	Journal file to re-initialize
PAC7EU	User dir. : ARCHEU320	Report	Review of re-initialization

Return codes:

- 0: No error detected
- 8: the Database is invalid

If the ARCH and SAVE procedures are grouped into one job, the PTU320 return code can be tested in order to condition the execution of the SAVE procedure.

## ARCH - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - ARCHIVAL OF THE JOURNAL -
REM *
REM * -----
REM * INPUT      : COMMAND FOR DEACTIVATION OF ARCHIVED
REM *             TRANSACTION
REM * COL 2       : 'S'
REM * COL 3 TO 6 : SESSION NUMBER
REM * COL 7 TO 14 : DATE (CCYYMMDD)
REM * COL 15      : ' ' PRESENCE OF ARCHIVED TRANSACTION FILE
REM *             : 'I' ABSENCE OF ARCHIVED TRANSACTION FILE
REM * COL 16      : ' ' PRESENCE OF DATA FILE (AR)
REM *             : 'D' ABSENCE OF DATA FILE (AR)
REM * COL 17      : ' ' ARCHIVAL AND REINITIALIZATION

```

```

REM *           : 'J' REINITIALIZATION WITHOUT ARCHIVAL
REM *
REM * IN THE ABSENCE OF INPUT (OR ERROR ON A COMMAND PARAM.)
REM * NO DEACTIVATION WILL TAKE PLACE, HOWEVER ARCHIVAL AND
REM * REINITIALIZATION WILL BE EXECUTED NORMALLY.
REM *
REM * TRANSACTIONS WHOSE SESSION (DATE) IS PRIOR OR EQUAL TO
REM * THE SESSION (DATE) INDICATED ARE NOT KEPT. THEY ARE
REM * RECOVERED IN THE FILE OF DEACTIVATED TRANSACTION.
REM *
REM * -----
<job id=ARCH>

<script language="VBScript">
MyProc = "ARCH"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1029" ))
'-----
Call StateList (base, statusL)

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTU300"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7JP") = Rep_SAVE & "\PJ"
WshEnv("PAC7PJ") = Rep_SAVE & "\PJ.new"
WshEnv("PAC7PQ") = "NUL"
Call BvpEnv("PTU300","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU300","PAC7EU",Rep_USR & "\ARCHEU300.txt")
Call BvpEnv("PTU300","PAC7DD",Rep_USR & "\ARCHDD300.txt")
Call RunCmdLog ("BVPTU300")

    If Return = 8 Then
Call Msg_Log (Array("1032"))
End If
    If Return = 12 Then
Call Msg_Log (Array("1026"))
End If
Call Err_Cod(Return , 0 , "PTU300")

Call Msg_Log (Array("1022" , "PTU320"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
Call BvpEnv("PTU320","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU320","PAC7EU",Rep_USR & "\ARCHEU320.txt")
Call RunCmdLog ("BVPTU320")

Call Err_Cod(Return , 0 , "PTU320")

```

```

Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(Rep_SAVE & "\PJ")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## PACS - Backup for Administration

### PACS - Introduction

The purpose of this procedure is to save the main files of the administration Database as a 'PE' sequential file.

The following files are saved:

- the data file (AR),
- the index file (AN),
- the extension data file (AY).

#### EXECUTION CONDITIONS

On-line access must be prohibited.

#### ABNORMAL EXECUTION

Refer to subchapter 'Abnormal Endings', chapter 'Overview'.

The main reason for an abend is that on-line environment is still open to transactions.

The procedure can therefore be restarted once the on-line environment is closed.

#### ARCHIVAL AND BACKUP LINKING

If the backup procedure is preceded by a Journal archival procedure (ARAD), its execution may be conditioned by the return code of the PTU320 program of the ARAD procedure:

- 0: No error detected
- 8: Invalid database

#### PRINTED REPORT

Once the procedure is executed, the following reports are printed:

- A report containing the number of records saved in each file and the session number,
- Two optional reports:
  - a statistical report with the number of records per library and per line-type,
  - a report listing database limits reached.

## PACS - Input / Processing / Results

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
29	4	'SAVE'	Function code

## PACS - Description of Steps

FORMATTING OF THE SEQUENTIAL IMAGE: PTU520

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7AY	Admin Base - Base dir. : AY	Input	Administration Database extension data
PAC7AN	Admin Base - Base dir. : AN	Input	Administration Database index
PAC7MB	User input	Input	Update transactions
PAC7PC	Base Admin-Save dir. : PC.new	Output	Sequential image of the administration Database
PAC7RP	Tmp dir. : WRP	Output	Sequential image of data (length=153) (should be able to contain all the data)
PAC7NA	Tmp dir. : WNA	Output	Sequential image of indexes (length=59) (should be able to contain all the indexes)
PAC7NB	Tmp dir. : WNB &&PACSNB	Output	Image of non-sorted indexes (length=59)
PAC7RY	Tmp dir. : WRY	Output	Sequential image of long data (length=1,019)
PAC7RQ	Tmp dir. : WPQ	Output	Intermediate storage (1 record, length=153)
PAC7EV	User dir. : PACSEV520	Report	User transactions list
PAC7EU	User dir. : PACSEU520	Report	Status of network before and after
PAC7EW	User dir. : PACSEW520	Report	Backup report
PAC7DD	User dir. : PACSDD520	Report	Abend output report

Return code:

- 8 : Inconsistency of the database or no authorization for batch procedure

Response to return code:

If the return code is greater than 2, the resulting backup is deleted by the next step in the procedure and a restoration must be performed using the last valid backup.

If there is no other backup to restore the database, the user should first examine the problem with the support team of the product, then the inconsistent database should be saved by the same procedure with the backup deletion step inactive. The resulting backup contains only data and can only be used after running the reorganization procedure.

## PACS: Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - BACKUP OF THE DATABASE -
REM *
REM * -----
REM *
<job id=PACS>

<script language="VBScript">
MyProc = "PACS"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1029" ))
'-----
Call StateList (base, statusL)

If c_error = 1 then Wscript.Quit (1) End If

Dim Ret520
Ret520 = 0

Call Msg_Log (Array("1022" , "PTU520"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("SEMLOCK") = Rep_BASE & "\LO"
WshEnv("SEMADMIN") = Rep_ABASE & "\LO"
WshEnv("PAC7PC") = BVP_SvName & ".NEW"
WshEnv("PAC7PD") = BVP_SvName & "I.NEW"
WshEnv("PAC7PY") = BVP_SvName & "Y.NEW"
Call BvpEnv("PTU520","PAC7NA",Rep_TMP & "\WNA.tmp")
Call BvpEnv("PTU520","PAC7NB",Rep_TMP & "\WNB.tmp")
Call BvpEnv("PTU520","PAC7RP",Rep_TMP & "\WRP.tmp")
Call BvpEnv("PTU520","PAC7RQ",Rep_TMP & "\WRQ.tmp")
Call BvpEnv("PTU520","PAC7RY",Rep_TMP & "\WRY.tmp")

```



```

Call BvpEnv("PTU520","PAC7EU",Rep_USR & "\PACSEU520.txt")
Call BvpEnv("PTU520","PAC7DD",Rep_USR & "\PACSD520.txt")
Call BvpEnv("PTU520","PAC7EW",Rep_USR & "\PACSEW520.txt")
Call BvpEnv("PTU520","PAC7EV",Rep_USR & "\PACSEV520.txt")
Call RunCmdLog ("BVPTU520")
Ret520= Return
If Return = 4 then Return = 0 end if

If Ret520 = 2 then
Call Msg_Log (Array("1022" , "PTU530"))
'-----
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7PC") = BVP_SvName & ".NEW"
WshEnv("PAC7PD") = BVP_SvName & "I.NEW"
WshEnv("PAC7PY") = BVP_SvName & "Y.NEW"
Call BvpEnv("PTU530","PAC7NA",Rep_TMP & "\WNA.tmp")
Call BvpEnv("PTU530","PAC7NB",Rep_TMP & "\WNB.tmp")
Call BvpEnv("PTU530","PAC7RP",Rep_TMP & "\WRP.tmp")
Call BvpEnv("PTU530","PAC7RQ",Rep_TMP & "\WRQ.tmp")
Call BvpEnv("PTU530","PAC7RY",Rep_TMP & "\WRY.tmp")
Call RunCmdLog ("BVPTU530")
Call Err_Cod(Return , 0 , "PTU530")
Else
If Return = 8 Then
Call Msg_Log (Array("1051"))
End If
Call Err_Cod(Return , 4 , "PTU520")
End If

If Ret520 <> 4 then
Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(BVP_SvName & "")
Call Turnover(BVP_SvName & "I")
Call Turnover(BVP_SvName & "Y")
End If

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## REOR - Reorganization for Administration

### REOR - Introduction

The Database Reorganization procedure optimizes Database accesses by accounting for each deletion, and sorting the data again according to the most frequent access order.

It uses the administration Database backup file (PE) and rebuilt a sequential image. This resulting image file must then be restored via the REST procedure.

The operating principle of this procedure is to rebuild the different indexes associated with all data using the 'image' of each Data Element. It makes the best of the system performance features since it separates historical (frozen) sessions

from the current session and sorts the data in the order of the most frequent access. This makes it possible to achieve a significant reduction of the number of indexes and data items.

This procedure may be used in two cases:

- When part of the data was deleted because of a malfunction or system failure, and no other procedure can be used (in particular, deletion of the Index file).
- When the administrator wants to purge the entities not used in the database.

This procedure should be executed only on an exceptional basis, because of the special conditions concerning its use.

#### EXECUTION CONDITIONS

The administration Database may remain open during the reorganization since the procedure operates on sequential images of the database.

Updates executed after the back-up file used for reorganization has been built will be retrievable while the reorganized database is being restored.

#### ABNORMAL EXECUTION

Refer to subchapter 'Abnormal Endings', chapter 'Overview'.

As specified in the recommendations below, it is advisable to keep all temporary files after each step.

If one of the steps abends, the procedure can be restarted at the step level, but not at the procedure level.

## **REOR - Input / Processing / Results**

Batch procedure access authorization option: one '\*' line with user code and password.

Specific user input for the procedure (optional), specifying a double printed copy of the index list of the reorganization procedure.

Position	Length	Value	Meaning
2	1	'D'	Report of the list of the duplicate indexes of the REOR procedure
3	1	' '	No report of duplicate indexes
		'1'	Report of duplicate indexes
		'2'	Report of PMS calls which may be incoherent
		'3'	Reports of values '1' and '2'

When the system finds an input error, it generates an error message and the procedure is not executed.

#### ESTIMATED FILE SIZE

The maximum sizes used during this procedure are based on the sizes of the files in the database before reorganization. The report printed by the preceding procedure provides all the relevant data:

- NI = number of index file records.
- ND = number of data file records MINUS number of gaps.
- NC = number of primary records on the data file.
- NH = number of 'frozen' (historical account) records from the data file (NH = ND - NC).

These symbols are also detailed in the presentation of each of the files for this procedure.

### PRINTED OUTPUT

This procedure prints a report listing errors encountered during reorganization, and statistics on the contents of the database.

It also prints reports with the statement 'Internal report' reserving their use to the product support team in case of problem.

### RESULTS

The output of this procedure is a reorganized sequential image of the database (where purges may have been performed). It does not contain gaps. Gaps will be added by the database restoration procedure.

### IMPORTANT RECOMMENDATIONS

The Reorganization procedure presents a number of characteristics which the user should be aware of:

- The step that rebuilds the Index file uses a large amount of CPU time.
- If the database contains a large amount of data, it is recommended to catalog the temporary files, or to use tape files to obtain the checkpoints in case of an abend in one of the steps.
- If files are transferred onto tape it is preferable to check on the initial blocking factors.
- The space allocated to the sortworks should also be calculated with care.

## **REOR - Description of Steps**

### INPUT CHECK: PTU2CL

This step checks user input and sets a return code if errors have been detected.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error labels
PACGGN	Admin Base - Base dir. : AN	Input	Administration database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration database users

Code	Physical name	Type	Label
PAC7PC	Admin Base - Save dir. : PC	Input	Sequential image of the administration Database
PAC7MB	User Input	Input	Input work file
PAC7BM	Tmp dir. : WBM	Output	Formatted records
PAC7PU	Tmp dir. : WPU	Output	Entity purge transactions (length=44)
PAC7EE	User dir. : ROADEE2CL	Report	Validation report
PAC7DD	User dir. : ROADDD2CL	Report	Batch procedure authorization option

Return codes:

- 0: OK
- 4: Error on user inputs
- 8: No authorization for batch procedure

#### DATA RETRIEVAL: PTU200

This step selects 'data' type information in the initial sequential image and then formats the key of each record selected for the subsequent sort.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7BM	Tmp dir. : WBM &&ROADBM	Input	User transactions
PAC7PC	Admin Base - Save dir. : PC	Input	Administration Database sequential image
PAC7PR	Tmp dir. : WPR	Output	Formatted records (length=176 size = ND)
PAC7NX	Tmp dir. : WNX	Output	Long data
PAC7NY	Tmp dir. : WNY	Output	Unformatted data
PAC7AU	Tmp dir. : WAU	Output	PR image (length=153)
PAC7PY	Admin Base - Save dir. : PCY	Output	PY image (length=1,036)
PAC7EE	User dir. : REOREE200	Report	Retrieval statistics output report

#### ASCII SORT: PTU205

Code	Physical name	Type	Label
PAC7PR	Tmp dir. : WPR	Input	Sorted data records
PAC7RP	Tmp dir. : WRP	Output	ASCII sorted data records

The SORT program requires disk space equivalent to twice the size of the file to be sorted.

#### PURGE: PTU210

This step reformats the records.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7PR	Tmp dir. : WRP	Input	Sorted records
PAC7PU	Tmp dir. : WPU	Input	Entity records to be purged
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7QS	Tmp dir. : WQS	Output	Purged records (length=176, size=ND)
PAC7UM	Tmp dir. : WUM	Output	Macro-structure call lines (length=176)
PAC7EE	User dir. : REOREE210	Report	Library and session purge report
PAC7EK	User dir. : REOREK210	Report	Entity-purge report
PAC7EB	User dir. : REOREB210	Report	Technical report

Return codes:

- 0: OK
- 8: Capacity overload

The steps that follow are executed only if the return code for the purge step is zero.

#### INDEX REBUILDING: PTU220

This step rebuilds indexes using the data.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7UR	Tmp dir. : WQS	Input	Purged data
PAC7NX	Tmp dir. : WNX	Input	Long data
PAC7UM	Tmp dir. : WUM	Input	Macro-structure call lines
PAC7PA	Tmp dir. : WPA	Output	Data from frozen sessions (length=153 size=NH)
PAC7PB	Tmp dir. : WPB	Output	Data from the current session (length=153 size=NC)
PAC7PC	Tmp dir. : WPC	Output	First data record (length=153)
PAC7AN	Tmp dir. : WAN	Output	Temporary index file (length=60 size=NI)
PAC7MR	Tmp dir. : WMR	Input/Output	Macro-structure call lines
PAC7EE	User dir. : REOREE220	Report	Report of index building

#### ASCII SORT: PTU225

Code	Physical name	Type	Label
PAC7AN	Tmp dir.: WAN	Input	Sorted index
PAC7NA	Tmp dir.: WNA	Output	ASCII Sorted index

The SORT program requires disk space equivalent to twice the size of the file to be sorted.

EXTENSION DATA PROCESSING: PTU226

Code	Physical name	Type	Label
PAC7NY	Tmp dir. : WNY	Input	Unformatted data
PAC7PA	Tmp dir. : WPA	Input	Data from frozen sessions
PAC7PB	Tmp dir. : WPB	Input	Data from the current session
PAC7PC	Tmp dir. : WPC	Input	First data record
PAC7QA	Tmp dir. : WQA	Output	Data from frozen sessions (length=153)
PAC7QB	Tmp dir. : WQB	Output	Data from the current session (length=153)
PAC7QC	Tmp dir. : WQC	Output	First data record (length=153)
PAC7QY	Tmp dir. : WQY	Output	Long data (length=1018)

MERGE: PTU240

This step rebuilds the final sequential image using the temporary files produced by the previous step.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Tmp dir. : WNA	Input	Sorted index
PAC7AU	Tmp dir. : WAU	Input	PR image
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7PA	Tmp dir. : WQA	Input	Data from frozen sessions
PAC7PB	Tmp dir. : WQB	Input	Data from the current session
PAC7PC	Tmp dir. : WQC	Input	First data record
PAC7QY	Tmp dir. : WQY	Input	Extension data
PAC7CP	Admin Base - Save dir. : PC+	Output	Sequential image of the administration Database
PAC7IE	User dir. : REORIE240	Report	Building the logical database

## REOR - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *           - REORGANIZATION OF THE DATABASE -
REM *
REM * -----
REM *
REM * THE REOR PROCEDURE MAY BE USED IN TWO CASES:
REM * . WHEN PART OF THE DATA WAS DELETED BECAUSE OF A MAL-
REM * FUNCTION OR SYSTEM FAILURE, AND NO OTHER PROCEDURE CAN
REM * BE USED (IN PARTICULAR, DELETION OF THE AN INDEX FILE)
REM * . WHEN THE DATABASE IS TO BE PURGED OF THE FOLLOWING:
REM *   - OBSOLETE LIBRARIES AND/OR SESSIONS;
REM *   - ENTITIES NOT USED IN THE DATABASE;

```

```

REM *
REM * -----
REM *
<job id=REOR>

<script language="VBScript">
MyProc = "REOR"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTU2CL"))
'-----
'Example of Input File extracted from PACX/EXPU :
' Call BvpEnv("PTU2CL","PAC7MB",RepT_USR & "\PACXMR.txt")
' The first line must contain User/Password information
'With RepT_USR is Global User Directory.

WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PTU2CL","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU2CL","PAC7PU",Rep_TMP & "\WPU.tmp")
Call BvpEnv("PTU2CL","PAC7DD",Rep_USR & "\REORDD2CL.txt")
Call BvpEnv("PTU2CL","PAC7EE",Rep_USR & "\REOREE2CL.txt")
WshEnv("PAC7PC") = BVP_SvName & ""
Call RunCmdLog ("BVPTU2CL")
If Return = 4 Then
Call Msg_Log (Array("1057"))
End If
If Return = 8 Then
Call Msg_Log (Array("1028"))
End If
Call Err_Cod(Return , 0 , "PTU2CL")

Call Msg_Log (Array("1022" , "PTU200"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7PC") = BVP_SvName & ""
WshEnv("PAC7PY") = "NULL"
' WshEnv("PAC7PY") = BVP_SvName & "Y"
Call BvpEnv("PTU200","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU200","PAC7PR",Rep_TMP & "\WPR.tmp")
Call BvpEnv("PTU200","PAC7NX",Rep_TMP & "\WNX.tmp")
Call BvpEnv("PTU200","PAC7NY",Rep_TMP & "\WNY.tmp")
Call BvpEnv("PTU200","PAC7AU",Rep_TMP & "\WAU.tmp")
Call BvpEnv("PTU200","PAC7EE",Rep_USR & "\REOREE200.txt")
Call RunCmdLog ("BVPTU200")
If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
Call Err_Cod(Return , 0 , "PTU200")

Call Msg_Log (Array("1022" , "PTU205"))
'-----
Call BvpEnv("PTU205","PAC7PR",Rep_TMP & "\WPR.tmp")
Call BvpEnv("PTU205","PAC7RP",Rep_TMP & "\WRP.tmp")
Call RunCmdLog ("BVPTU205")
Call Err_Cod(Return , 0 , "PTU205")
'OK :
Call DelFile (Rep_TMP & "\WPR.tmp")

```

```

Call Msg_Log (Array("1022" , "PTU210"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
Call BvpEnv("PTU210","PAC7EB",Rep_USR & "\REOREB210.txt")
Call BvpEnv("PTU210","PAC7EE",Rep_USR & "\REOREE210.txt")
Call BvpEnv("PTU210","PAC7EK",Rep_USR & "\REOREK210.txt")
Call BvpEnv("PTU210","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU210","PAC7PR",Rep_TMP & "\WRP.tmp")
Call BvpEnv("PTU210","PAC7PU",Rep_TMP & "\WPU.tmp")
Call BvpEnv("PTU210","PAC7QS",Rep_TMP & "\WQS.tmp")
Call BvpEnv("PTU210","PAC7UM",Rep_TMP & "\WUM.tmp")
Call RunCmdLog ("BVPTU210")
If Return = 8 Then
Call Msg_Log (Array("1056"))
End If
If Return = 12 Then
Call Msg_Log (Array("1026"))
End If
Call Err_Cod(Return , 0 , "PTU210")
'OK :
Call DelFile (Rep_TMP & "\WRP.tmp")
Call DelFile (Rep_TMP & "\WPU.tmp")

Call Msg_Log (Array("1022" , "PTU220"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTU220","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU220","PAC7AN",Rep_TMP & "\WAN.tmp")
Call BvpEnv("PTU220","PAC7MR",Rep_TMP & "\WMR.tmp")
Call BvpEnv("PTU220","PAC7NX",Rep_TMP & "\WNX.tmp")
Call BvpEnv("PTU220","PAC7PA",Rep_TMP & "\WPA.tmp")
Call BvpEnv("PTU220","PAC7PB",Rep_TMP & "\WPB.tmp")
Call BvpEnv("PTU220","PAC7PC",Rep_TMP & "\WPC.tmp")
Call BvpEnv("PTU220","PAC7UM",Rep_TMP & "\WUM.tmp")
Call BvpEnv("PTU220","PAC7UR",Rep_TMP & "\WQS.tmp")
Call BvpEnv("PTU220","PAC7EE",Rep_USR & "\REOREE220.txt")
Call RunCmdLog ("BVPTU220")
Call Err_Cod(Return , 0 , "PTU220")

Call Msg_Log (Array("1024"))
'-----
Call DelFile (Rep_TMP & "\WUM.tmp")
Call DelFile (Rep_TMP & "\WQS.tmp")

Call Msg_Log (Array("1022" , "PTU225"))
'-----
Call BvpEnv("PTU225","PAC7AN",Rep_TMP & "\WAN.tmp")
Call BvpEnv("PTU225","PAC7NA",Rep_TMP & "\WNA.tmp")
Call RunCmdLog ("BVPTU225")
Call Err_Cod(Return , 0 , "PTU225")

Call Msg_Log (Array("1024"))
'-----
Call DelFile (Rep_TMP & "\WAN.tmp")

Call Msg_Log (Array("1022" , "PTU226"))
'-----
Call BvpEnv("PTU226","PAC7PA",Rep_TMP & "\WPA.tmp")
Call BvpEnv("PTU226","PAC7PB",Rep_TMP & "\WPB.tmp")
Call BvpEnv("PTU226","PAC7PC",Rep_TMP & "\WPC.tmp")
Call BvpEnv("PTU226","PAC7QA",Rep_TMP & "\WQA.tmp")
Call BvpEnv("PTU226","PAC7QB",Rep_TMP & "\WQB.tmp")
Call BvpEnv("PTU226","PAC7QC",Rep_TMP & "\WQC.tmp")

```



```

Call BvpEnv("PTU226","PAC7QY",Rep_TMP & "\\WQY.tmp")
Call BvpEnv("PTU226","PAC7NY",Rep_TMP & "\\WNY.tmp")
Call RunCmdLog ("BVPTU226")
Call Err_Cod(Return , 0 , "PTU226")

Call Msg_Log (Array("1024"))
'-----
Call DelFile (Rep_TMP & "\\WPA.tmp")
Call DelFile (Rep_TMP & "\\WPB.tmp")
Call DelFile (Rep_TMP & "\\WPC.tmp")

Call Msg_Log (Array("1022" , "PTU240"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\\AE"
Call BvpEnv("PTU240","PAC7AN",Rep_TMP & "\\WNA.tmp")
Call BvpEnv("PTU240","PAC7AU",Rep_TMP & "\\WAU.tmp")
Call BvpEnv("PTU240","PAC7BM",Rep_TMP & "\\WBM.tmp")
Call BvpEnv("PTU240","PAC7PA",Rep_TMP & "\\WQA.tmp")
Call BvpEnv("PTU240","PAC7PB",Rep_TMP & "\\WQB.tmp")
Call BvpEnv("PTU240","PAC7PC",Rep_TMP & "\\WQC.tmp")
Call BvpEnv("PTU240","PAC7QY",Rep_TMP & "\\WQY.tmp")
WshEnv("PAC7CP") = BVP_SvName & ".new"
WshEnv("PAC7PD") = BVP_SvName & "I.new"
WshEnv("PAC7PY") = BVP_SvName & "Y.new"
Call BvpEnv("PTU240","PAC7IE",Rep_USR & "\\REORIE240.txt")
Call RunCmdLog ("BVPTU240")
Call Err_Cod(Return , 0 , "PTU240")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

If Return = 0 then
Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(BVP_SvName & "")
Call Turnover(BVP_SvName & "I")
Call Turnover(BVP_SvName & "Y")
End if

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## REST - Restoration for Administration

### REST - Introduction

The purpose of this procedure is to rebuild the administration Database with the use of the sequential image resulting from the execution of the backup procedure (PACS SAVE option).

It is also used to retrieve archived transactions via the resulting sequential image and to modify the number of 'gaps' of the Database.

#### EXECUTION CONDITIONS

The administration Database must be closed to on-line use.

The procedure re-initializes the transactions Journal physically and logically. It is therefore required to execute first the ARCH procedure to backup the Journal.

#### ABNORMAL EXECUTION

Refer to subchapter 'Abnormal Endings' in chapter 'Overview'.

Whatever the reason of the abnormal ending, the procedure can be restarted once the problem solved.

## **REST - Input / Processing / Results**

A '\*' line with user code and password.

The structure of the specific input is described in the chart below.

Position	Length	Value	Meaning
2	1	'Y'	Line code
3	5	nnnnn	Number of gaps as absolute value
8	2	pp	OR number of gaps as % (1)
10	2		Language code (FR, EN, ...)
12	1	'0'	No inhibition of the Journal
		'1'	Journal inhibition (no journalization of updated transactions)
		' '	Retrieval of the last value
14	3	'REC'	If archived transactions retrieved

**NOTES:** Where there is no input, the Database characteristics remain unchanged.

Any field left blank will be filled in with the current options.

If the Journal is inhibited ( parameter set to '1'), update transactions are not backed-up in the Journal file. In this case, it is impossible to restore the Database using the recovery of archived transactions ('REC' parameter on user input). It is therefore highly recommended to set this parameter to '0' (which is the default value) so as to avoid restoration problems.

In case of error, invalid parameters are ignored, and the system ensures restoration using the parameter values stored in the sequential image of the Database.

#### PRINTED REPORT

This procedure prints a report listing the requested options, associated errors, the number of records restored in the Database for each file, the number of gaps, and the options stored in the new Database.

#### RESULTS

Once the procedure has been executed, the Database is ready to be used in batch or on-line mode.

**NOTE:** Once this procedure is executed, the current session number is that of the sequential image, or of the most recent transaction if the retrieval of archived transactions has been run.

## REST - Description of Steps

### USER INPUT RECOGNITION: PTU010

Code	Physical name	Type	Label
CARTE	User input	Input	User parameters
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7PC	Save dir. : PC	Input	Sequential image of the Administration Database
PAC7MB	Tmp dir. : WMB	Output	Parameter
PAC7DD	User dir. : RESTDD010	Report	Batch procedure authorization option

Return code:

- 8: No authorization for batch procedure

### VALIDATION OF JOURNAL CONTENTS: PTU380

This step is executed if the Journal file exists.

Code	Physical name	Type	Label
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PAC7AJ	Journal dir. : AJ	Input	Journal file
PAC7EU	User dir. : RESTEU380	Report	(only if the Journal was not archived)

Return code:

- 0: The Journal file was archived
- 8 : The Journal file was not archived (none of the RSAD steps was executed).

### RESTORATION OF THE DATABASE: PTU400

This step is executed only if the Journal file has been archived.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error labels
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7PC	Admin Base - Save dir. : PC	Input	Sequential image of the administration Database

Code	Physical name	Type	Label
PAC7AR	Admin Base - Base dir. : AR	Output	Administration Database data
PAC7AY	Admin Base - Base dir. : AY	Output	Administration Database extension data
PAC7AN	Admin Base - Base dir. : AN	Output	Administration Database index
PAC7AJ	Journal dir. : AJ	Output	Administration Database Journal
PAC7PS	Tmp dir. : WPS	Output	Work file (2 records, length=144)
PAC7EU	User dir. : RESTEU400	Report	Restoration report
PAC7DD	User dir. : RESTDD400	Report	Batch procedure authorization option

#### DATABASE AVAILABILITY - TRANSACTIONS RETRIEVAL: PTU420

This step is executed if the Journal file has been archived. It updates the first record of the Data file.

Warning: this step is REQUIRED to obtain a consistent database.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7AR	Admin Base - Base dir. : AR	Input/Output	Administration Database data
PAC7JO	Save dir. : PJ	Input	Journal to apply
PAC7PS	Tmp dir. : WPS	Input	Work file
PAC7OJ	Tmp dir. : WOJ	Output	Update transactions (length=170)
PAC7EU	User dir. : RESTEU420	Report	Retrieval report

Return codes:

- 0: There are transactions to retrieve
- 4: No transaction to retrieve  
OR erroneous user input.

In case of abnormal ending, the database cannot be updated.

#### UPDATE OF THE ADMINISTRATION DATABASE: PACA15

Code	Physical name	Type	Label
PAC7AR	Admin Base - Base dir. : AR	Output	Administration Database data
PAC7AN	Admin Base - Base dir. : AN	Output	Administration Database index
PAC7AY	Admin Base - Base dir. : AY	Output	Administration Database extension
PAC7AJ	Journal dir. : AJ	Output	Administration Database Journal
PAC7AE	System - Skel. dir. : AE	Input	Error messages

Code	Physical name	Type	Label
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin. Base - Base dir. : AR	Input	Administration Database data
PACGGY	Admin. Base - Base dir. : AY	Input	Administration Database Extension
PACGGR	Admin. Base - Base dir. : GU	Input	Administration Database users
PAC7DC	Base dir. : DC	Input	DSMS file of the development Database
PAC7ME	null	Input	Working file
PAC7MV	Tmp dir. : WOJ	Input	Update transactions
PAC7RB	null	Output	UPDT erroneous transactions (length=80)
PAC7RY	null	Output	UPDP erroneous transactions (length=310)
PAC7IE	User dir. : RESTIEA15	Report	Update report (length=132)
PAC7IF	User dir. : RESTIFA15	Report	Erroneous transactions list (length=132)

The list of a user's transactions is preceded by a banner specifying the user's code.

Return codes :

- 0: OK, no error
- 2: warning
- 4: critical error

## REST - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - RELOADING RESTORATION OF THE DATABASE -
REM *
REM * -----
REM *
REM * INPUT
REM * COL 2      : 'Y'
REM * COL 3-7    : NUMBER OF GAPS IN ABSOLUTE VALUE
REM * COL 8-9    : NUMBER OF GAPS IN PERCENTAGE ( / BASE )
REM * COL 10-11  : INITIAL LANGUAGE CODE (FR, EN, ..)
REM * COL 12     : '1' INHIBITION OF TRANSACTION LOG
REM * COL 14-16  : 'REC' FOR RECOVERY OF ARCHIVED TRANSACTIONS
REM * COL 17-20  : 4 CHARACTERS TO BE DISPLAYED
REM *           : ON ALL SCREEN OF THE PRODUCT
REM * COL 21-24  : 'NNNN' MAXIMUM NUMBER OF SEARCH ACCESSES
REM *           : TO THE DATABASE(LISTS)-(DEFAULT VALUE:300)
REM * COL 25     : 'U' (DEFAULT VALUE) : IMPLICIT UPDATE
REM *           : 'N' EXPLICIT UPDATE
REM * COL 26-29  : CCKECPPOINT FREQUENCY
REM * COL 36-47  : PF-KEYS SIGNIFICATIONS
REM * COL 79     : BACKUP FILES DISPATCH
REM *           : 'N' (DEFAULT VALUE) : NO DISPATCH (1 FILE)
REM *           : 'D' : DISPATCH (3 FILES)

```

```

REM *
REM * IN THE ABSENCE OF INPUT, THE RELOAD DOES NOT MODIFY THE
REM * NUMBER OF EXISTING GAPS, AND OTHER DATA IS UNCHANGED.
REM *
REM * IF THE JOURNAL FILE OF TRANSACTIONS ON DISK (AJ) IS NOT
REM * REINITIALIZED, THE RESTORE CHAIN IS NOT EXECUTED.
REM * IT IS THEREFORE NECESSARY TO EXECUTE THE ARCH PROCEDURE
REM * FIRST.
REM * -----
<job id=REST>

<script language="VBScript">
Dim MyProc
MyProc = "REST"
</script>
<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1029" ))
'-----
Call StateList (base, statusL)

If c_error = 1 then Wscript.Quit (1) End If

Dim Ret420
Ret420 = 0

Call Msg_Log (Array("1022" , "PTU010"))
'-----
WshEnv("CARTE") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTU010","PAC7DD",Rep_USR & "\RESTD010.txt")
Call BvpEnv("PTU010","PAC7MB",Rep_TMP & "\WMB.tmp")
WshEnv("PAC7PC") = BVP_SvName & ""
WshEnv("PAC7PD") = BVP_SvName & "I"
WshEnv("PAC7PY") = BVP_SvName & "Y"
Call RunCmdLog ("BVPTU010")
WshVolEnv("RC") = Return

If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
Call Err_Cod(Return , 0 , "PTU010")

If FSO.FileExists(Rep_JOURNAL & "\AJ") Then
Call Msg_Log (Array("1022" , "PTU380"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
Call BvpEnv("PTU380","PAC7EU",Rep_USR & "\RETEU380.txt")
Call BvpEnv("PTU380","PAC7MB",Rep_TMP & "\WMB.tmp")
Call RunCmdLog ("BVPTU380")
WshVolEnv("RC") = Return
If Return = 8 Then
Call Msg_Log (Array("1058"))
End If
Call Err_Cod(Return , 0 , "PTU380")
End If

Call Msg_Log (Array("1022" , "PTU400"))
'-----

```

```

WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
Call BvpEnv("PTU400","PAC7DD",Rep_USR & "\RESTDD400.txt")
Call BvpEnv("PTU400","PAC7EU",Rep_USR & "\RESTEU400.txt")
Call BvpEnv("PTU400","PAC7MB",Rep_TMP & "\WMB.tmp")
WshEnv("PAC7PC") = BVP_SvName & ""
WshEnv("PAC7PD") = BVP_SvName & "I"
Call BvpEnv("PTU400","PAC7PS",Rep_TMP & "\WPS.tmp")
WshEnv("PAC7PY") = BVP_SvName & "Y"
Call RunCmdLog ("BVPTU400")
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PTU400")

If FSO.FileExists( Rep_SAVE & "\PJ" ) Then
Call Msg_Log (Array("1022" , "PTU420"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7J0") = Rep_SAVE & "\PJ"
Call BvpEnv("PTU420","PAC7MB",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTU420","PAC7OJ",Rep_TMP & "\WOJ.tmp")
Call BvpEnv("PTU420","PAC7PS",Rep_TMP & "\WPS.tmp")
Call BvpEnv("PTU420","PAC7EU",Rep_USR & "\RESTEU420.txt")
Call RunCmdLog ("BVPTU420")
Ret420 = Return

If Return = 4 Then
'No transaction to be retrieved : Normal End
'-----
Call Msg_Log (Array("1059"))
Call Msg_Log (Array("1024"))
Return = 0
WshVolEnv("RC") = Return

Else
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PTU420")
End If

If Ret420 = 0 then
'Update
Call Msg_Log (Array("1022" , "PACA15"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PACGGY") = Rep_ABASE & "\AY"
WshEnv("PAC7DC") = Rep_BASE & "\DC"
Call BvpEnv("PACA15","PAC7IE",Rep_USR & "\RESTIEA15.txt")
Call BvpEnv("PACA15","PAC7IF",Rep_USR & "\RESTIFA15.txt")
WshEnv("SEMLOCK") = Rep_BASE & "\LO"
WshEnv("SEMADMIN") = Rep_ABASE & "\LO"
WshEnv("PAC7ME") = "NUL"
Call BvpEnv("PACA15","PAC7MV",Rep_TMP & "\WOJ.tmp")
WshEnv("PAC7RB") = "NUL"
WshEnv("PAC7RY") = "NUL"
Call RunCmdLog ("BVPACA15")
WshVolEnv("RC") = Return
If Return = 2 Then

```

```
Call Msg_Log (Array("1061"))
End If
If Return = 4 Then
Call Msg_Log (Array("1060"))
End If
Call Err_Cod(Return , 4 , "PACA15")
End If

End If 'If Rep_SAVE & "\PJ"

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
WshVolEnv("RC") = Return
Wscript.Quit (Return)

</script>
</job>
```



---

## Chapter 3. Development Databases Management

---

### Backup Procedures

#### Introduction

This procedure is used to perform different types of operations on the development Database data according to the input code entered on the '\*' line.

#### PACS - Input Common to Managers

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
22	4	nnnn	Session number (UXSR-reserved) blank = current session
26	1		Session type (UXSR-reserved)
		'T'	If selection of frozen session
		' '	If selection of current session
29	4	cccc	Procedure function code (1)
33	1		Library extraction code (reserved to SASN)
		'A'	Extraction of a lower-level library and of its higher-level library
		'D'	Extraction of a library and of its dependent libraries
34	1		Library extraction option (reserved to SASN)
		'I'	Extraction of inter-library also (only if col 33 = 'D')
49	1		Locks extraction option (UXSR-reserved)
		' '	Locks extraction with user code = user code of '*' line
		'1'	No locks extraction
		'2'	Locks extraction with user code = source user code
67	1		(UXSR-reserved)
		'T'	If col 26 = ' ' selection of all the frozen sessions
		' '	IF col 26 = ' ' selection of the current session only

(1) The different values of function codes are:

- MLIB: library management
- SAVE: development Database backup

- SASN: sub-networks backup
- UXSR: sub-networks extraction

There is one launch script (BVPxxxx.wsf) for each of these values. An environment variable, named WshEnv("BVP\_SaveName"), is defined for each script.

## Database Management

### MLIB - Introduction:

The Database Management procedure has a two-fold purpose:

- Initialize the database in the form of a sequential file (or 2 files if the Dispatch option is used), called 'PC', which is then used as input to the Restoration (REST) procedure.
- Create or delete libraries in an existing database.

### EXECUTION CONDITIONS

The database must be closed to on-line access and use, unless the current execution is a simulation. The procedure must be followed by the REST procedure so that the new library structure is taken into account.

### ABNORMAL EXECUTIONS

Once the problem has been solved, the procedure can be restarted as it is.

### MLIB - Input / Processing / Results:

There are two types of user input lines:

- Heading line (required) before all other input lines used to specify that a new VisualAge Pacbase Database is to be initialized or that an existing Database is to be modified.
- As many (optional) lines as there are Libraries to create, modify ou delete.

The structure of the header is the following:

Position	Length	Value	Meaning
2	1	'G'	Line code
3	1	' '	Modification of existing Database
		'I'	Initialization of new Database
4	1	' '	Actual update
		'S'	Simulation

Update simulation is used to obtain the state of the Database as it would be if the requested modifications had actually been carried out.

It allows you to assess the impact of a change in the structure of the Database before actual execution. For large Databases, actual execution may use considerable machine time.

The structure of the 'Library' lines is as follows:

Position	Length	Value	Meaning
1	1	'C'	Creation
		'M'	Modification
		'A'	Deletion
2	1	'*'	Line code
3	3	bbb	Code of the Library to update
6	3	ccc	Code of the upper level Library
9	1	' '	Non initialized Library
		'V'	Virtual Library (only for the creation)

#### NOTE

Asterisks ("\*") are not authorized in Library codes.

#### UPDATE RULES

Updates are executed line by line. No previous transaction sort is executed. The resulting Database must remain consistent during the update.

#### DELETION TRANSACTIONS

A Library with dependent Libraries cannot be deleted. To delete an entire sub-network, begin by deleting the Libraries at the lowest hierarchical level and work upward to the highest level.

The upper Library code must not be entered on Library deletion lines. Only the code of the Library to be deleted may be specified.

The deletion of a Library causes this Library's entire contents to be deleted. Its contents are replaced by empty records, or 'gaps' (see the REST restoration procedure).

#### CREATION TRANSACTIONS

When a Library is created, it can only be linked to an already existing Library or to a Library that was previously created in the update job stream.

Therefore, always create the 'parent' Library before its 'child' Libraries. Both can be created by the same run of the procedure.

Once created, a Library has either a 'virtual' or 'not initialized' status.

- Virtual Libraries are created for future development projects. They are visible to the Administrator only. They cannot receive development specifications. You change their status to Not initialized in the Administrator workbench.
- Not initialized Libraries are visible to all users, but are not ready to receive development specifications. You change their status to Initialized in the Administrator workbench.

Caution: a VisualAge Pacbase Database cannot contain more than 300 Libraries.

## MODIFICATION TRANSACTIONS

Generally, transactions modify existing links between two Libraries. Usually a new Library is inserted between two existing Libraries.

When a new upper Library is assigned to a Library, the new Library must be empty and linked directly or indirectly to the former upper Library.

Structural errors are automatically detected.

It is not possible to cancel and recreate a Library during the same MLIB procedure.

When an error is detected on a line, a message is generated, and the update is interrupted because the resulting Database would otherwise be inconsistent. The line containing the error must be corrected and the job restarted, as the initial Database will not have been modified.

## PRINTED REPORTS

In all cases, a report on the initial state of the Database and an update report are printed.

If no errors have been detected, a report on the Database after the update is printed.

## RESULTS

If no errors are detected and if the update is 'real' (not simulated), the result is a sequential image of the updated Database (PC), which serves as input for Database reloading.

The execution report of a Database initialization does not include the Database name since it is later assigned via user input for the Restoration procedure.

## WARNING

This procedure does not allow for the recovery of disk space when Libraries are deleted. Records are physically present in the Database as 'gaps'. It is the Reorganization (REOR) procedure that deletes these gaps so that disk space can be recovered.

## NOTE

This procedure increments the session number.

## **Database Backup**

### **SAVE - Introduction:**

The Database Backup procedure (SAVE) saves the Database main files as sequential files: 'PC', 'PD' and 'PY'.

The backup is performed on the following files:

- Data file (AR),
- Index file (AN),
- Extension data file (AY).

An option allows for a backup of data files, indexes and extension data in three sequential files: ('AR' saved as 'PC', 'AN' saved as 'PD' and AY as 'PY'). Otherwise, all three files are saved as one 'PC' file.

This option (Dispatch or No dispatch) is implemented in the database restoration procedure. For further details, see the REST procedure user input description.

#### EXECUTION CONDITIONS

On-line access must be closed.

#### ABNORMAL EXECUTION

Refer to chapter 'Overview', subchapter 'Abnormal Endings'.

The main cause of an abend is that the database remained open to on-line use while the procedure was being executed.

The procedure can be restarted as it is once the problem has been solved.

#### EXECUTION OF ARCHIVING AND SAVE PROCEDURES

If the save procedure is preceded by a Journal archival (ARCH procedure), its execution may be conditioned by the return code of the PTU320 program of the ARCH procedure.

- 0: No error detected
- 8: Invalid database

#### SIMPLIFIED BACKUP

Files may also be backed up via standard system utilities. In this case, run the SASY procedure to check the consistency of data and indexes (see Subchapter 'System Backup Complement').

#### PRINTED REPORTS

The procedure prints:

- a report containing the number of records saved in each file and the session number),
- optional reports:
  - A statistical report with the number of records per library and per line type,
  - A report which indicates the limitations reached in the Database.

#### **SAVE - Input / Processing / Results:**

#### OUTPUT

Depending on the 'Dispatch' option taken during restoration, the output of the backup procedure is the following:

- Either a single sequential file (PC), of variable length, containing the mirror of the three saved files,
- Or three sequential files (PC, PD and PY) of variable length.

If the database is no longer consistent after an abend during the last update, the backup procedure will not be executed.

If the database is inconsistent, the procedure sends back a return code.

#### NOTE

This procedure increments the current session number.

### **Sub-Network Backup**

#### **SASN - Introduction:**

The Sub-Network Backup procedure (SASN) extracts one or more sub-networks from a database. The result is a consistent set of libraries which will make up a new database (formatted as a backup file to be used as input to the Restoration procedure).

Each extracted sub-network is identified by its lowest-level library; the utility automatically extracts all higher-level libraries pertaining to the sub-network.

#### NOTE

The MLIB procedure can produce a result similar to that produced by SASN. However, it keeps data 'gaps' in the backup and, unlike the SASN procedure, does not allow physical space to be gained.

#### EXECUTION CONDITIONS

The database must be closed to on-line use.

#### ABNORMAL EXECUTIONS

If an abend occurs, the procedure can be restarted as it is once the problem has been solved.

#### **SASN - User Input:**

The user must code one line per library to be extracted.

Position	Length	Value	Meaning
1	2	' '	
3	3	bbb	Code of lowest-level library of sub-network to be extracted. (All the upper-libraries of 'bbb' will be automatically extracted.)

### **Partial Sub-Network Extraction**

#### **UXSR - Introduction:**

The Partial Sub-Network Extraction procedure (UXSR) creates a VisualAge Pacbase sub-network from an existing database, by:

- Creating Libraries (MLIB equivalent)
- Merging Libraries
- Renaming Libraries

It is also possible to select:

- A frozen session (nT):  
This frozen session will become the current session in the new Database.  
No other frozen session will be selected.  
The image of this Database will be identical to the view which existed in the nT frozen session, but this time it will be in n+1 current session.
- The current session or all sessions (current included):  
Via an option, you can select all the sessions ('T' in position 67 of the \* line), or only the current session (' ' in position 67 of the \* line).

Examples:

- Creation of Libraries:  
C\*CEN\_\_AAA (1)  
C\*APPCENBBB (2)  
(1) Creation of the CEN Library. AAA must not exist in the source Database.  
(2) Creation of the APP Library in the CEN Library. BBB must not exist in the source Database.
- Merging of Libraries in the same Library:  
C\*CEN\_\_CEN (1)  
C\*APPCENAPP (2)  
C\*APPCENBQQ (2)  
(1) Creation of the CEN Library with the contents of CEN.  
(2) Creation of the APP Library under the CEN Library with the contents of APP and BQQ.  
The definition of the APP Library in the new Database will be identical to that of APP in the source Database since APP comes first, before BQQ.
- Renaming of Library:  
C\*CEN\_\_AAA (1)  
(1) Creation of the CEN Library with the contents of APP.

### CAUTION

No consistency checks are carried out; make sure you have entered valid user input lines.

It is not possible to copy an existing Library network and create new Libraries whose contents are identical to that of Libraries in the source network.

### EXECUTION CONDITIONS

On-line access must be closed.

This procedure processes data only. It must therefore be followed by the REOR, then REST procedures, in order for the new Database to be taken into account.

### **UXSR - User Input:**

There are two types of specific user input:

- Heading line (required) at the top of the input file that specifies if a simulation of the database is desired or not.

- As many lines (optional) as there are libraries to be created, modified or canceled.

The structure of the header is the following:

Position	Length	Value	Meaning
2	1	'G'	Line code
4	1	' '	Actual update
		'S'	Simulation

The simulation allows to obtain the state of the network after modifications, without actually carrying out these modifications. You can then assess the impact of a modification in the network structure before carrying it out (it might prove to be costly in terms of machine time if the Database is very large).

You must enter as many (optional) lines as Libraries to be extracted for update.

Position	Length	Value	Meaning
1	1	'C'	Creation
2	1	'*'	Line code
3	3	bbb	Code of Library to be created
6	3	ccc	Code of higher Library if any
9	3	ddd	Code of source Library required even when creating a new Library ; in this case enter any code not existing in the source Database.

#### NOTE

Do not use the character '\*' in Library codes (incompatibility with the WorkStation).

## **PACS - Description of Steps**

### FORMATTING SEQUENTIAL IMAGES: PTU520

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AY	Base dir. : AY	Input	Development Database extension data
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7MB	User input	Input	Update transactions
PAC7PC	Save dir. : PC.new	Output	Database sequential image (length=1,023)



Code	Physical name	Type	Label
PAC7PD	Save dir. : PD.new	Output	If Dispatch option of backup: sequential image 2 of the database (length=1,023)
PAC7PY	Save dir. : PY.new	Output	If Dispatch option of backup: sequential image 3 of the database (length=1,023)
PAC7RP	Tmp dir. : WRP	Output	Sequential image of data (length=153) (should be able to contain all data)
PAC7NA	Tmp dir. : WNA	Output	Sequential image of index (length=59) (should be able to contain all data)
PAC7NB	Tmp dir. : WNB	Output	Image of unsorted index (length=59)
PAC7RY	Tmp dir. : WRY	Output	Sequential image of long data (length=1,019)
PAC7RQ	Tmp dir. : WPQ	Output	Temporary storage (1 record, length=153)
PAC7EV	User dir. : PACSEV520	Report	User transactions list
PAC7EU	User dir. : PACSEU520	Report	State of library before and after
PAC7EW	User dir. : PACSEW520	Report	Backup report
PAC7DD	User dir. : PACSDD520	Report	Abnormal endings report

Return codes:

- 2: MLIB or SASN and no error. Execution of PTU530.
- 4: MLIB and database simulation
- 8: Inconsistency of the database or no authorization for batch procedure

#### FORMATTING SEQUENTIAL IMAGES: PTU530

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7RP	Tmp dir. : WRP	Input	Data sequential image
PAC7NA	Tmp dir. : WNA	Input	Index sequential image
PAC7NB	Tmp dir. : WNB	Input	unsorted index image
PAC7RY	Tmp dir. : WRY	Input	extension data sequential image
PAC7RQ	Tmp dir. : WRQ	Input	Intermediary storage
PAC7PC	Save dir. : PC.new	Output	Development Database sequential image
PAC7PD	Save dir. : PD.new	Output	If backup Dispatch option: sequential image 2 of the network
PAC7PY	Save dir. : PY.new	Output	If backup Dispatch option: sequential image 3 of the network

Response to return code:

If the program sends a return code greater than '2', the backup is deleted by the next step in the procedure and a restoration must be performed using the last valid backup.

If there is no other backup, the user should first contact the product support to analyze the problem, then, the inconsistent database should be saved by the same procedure with the backup deletion step inactive. The resulting backup contains only data, and can only be used after running the REOR procedure.

## PACS - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - BACKUP OF THE DATABASE -
REM *
REM * -----
REM *
<job id=PACS>

<script language="VBScript">
MyProc = "PACS"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1029" ))
'-----
Call StateList (base, statusL)

If c_error = 1 then Wscript.Quit (1) End If

Dim Ret520
Ret520 = 0

Call Msg_Log (Array("1022" , "PTU520"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("SEMLOCK") = Rep_BASE & "\LO"
WshEnv("SEMADMIN") = Rep_ABASE & "\LO"
WshEnv("PAC7PC") = BVP_SvName & ".NEW"
WshEnv("PAC7PD") = BVP_SvName & "I.NEW"
WshEnv("PAC7PY") = BVP_SvName & "Y.NEW"
Call BvpEnv("PTU520","PAC7NA",Rep_TMP & "\WNA.tmp")
Call BvpEnv("PTU520","PAC7NB",Rep_TMP & "\WNB.tmp")
Call BvpEnv("PTU520","PAC7RP",Rep_TMP & "\WRP.tmp")
Call BvpEnv("PTU520","PAC7RQ",Rep_TMP & "\WRQ.tmp")
Call BvpEnv("PTU520","PAC7RY",Rep_TMP & "\WRY.tmp")
Call BvpEnv("PTU520","PAC7EU",Rep_USR & "\PACSEU520.txt")
Call BvpEnv("PTU520","PAC7DD",Rep_USR & "\PACSDD520.txt")
Call BvpEnv("PTU520","PAC7EW",Rep_USR & "\PACSEW520.txt")
Call BvpEnv("PTU520","PAC7EV",Rep_USR & "\PACSEV520.txt")
Call RunCmdLog ("BVPTU520")
Ret520= Return
If Return = 4 then Return = 0 end if

If Ret520 = 2 then

```

```

Call Msg_Log (Array("1022" , "PTU530"))
'-----
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7PC") = BVP_SvName & ".NEW"
WshEnv("PAC7PD") = BVP_SvName & "I.NEW"
WshEnv("PAC7PY") = BVP_SvName & "Y.NEW"
Call BvpEnv("PTU530","PAC7NA",Rep_TMP & "\WNA.tmp")
Call BvpEnv("PTU530","PAC7NB",Rep_TMP & "\WNB.tmp")
Call BvpEnv("PTU530","PAC7RP",Rep_TMP & "\WRP.tmp")
Call BvpEnv("PTU530","PAC7RQ",Rep_TMP & "\WRQ.tmp")
Call BvpEnv("PTU530","PAC7RY",Rep_TMP & "\WRY.tmp")
Call RunCmdLog ("BVPTU530")
Call Err_Cod(Return , 0 , "PTU530")
Else
If Return = 8 Then
Call Msg_Log (Array("1051"))
End If
Call Err_Cod(Return , 4 , "PTU520")
End If

If Ret520 <> 4 then
Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(BVP_SvName & "")
Call Turnover(BVP_SvName & "I")
Call Turnover(BVP_SvName & "Y")
End If

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## UPDT - Freeze

### UPDT - Introduction

The Database Update procedure (UPDT) is used to freeze the database and executes also a Batch update of the database.

The principle of sessions makes it possible to manage various versions of the same application. The administrator then freezes the Database, creating a snapshot of the current session.

The procedure allows access to all libraries which make up the database, according to the different user authorizations.

The update can be executed in on-line mode.

For further information about UPDT, refer to 'the Developer's Procedures' manual.

### UPDT - Input

A '\*' line for user identification contains the user code, password and the corresponding library conversion.

The \*-type line may contain conversion options: 'N' entered in column 67 inhibits any lowercase/upercase conversion.

No other update should precede the 'X1HIST' line.

Position	Length	Value	Meaning
2	6	'X1HIST'	Line code for a session freeze
8	50		Session Name
58	4		Session number
65	1		Session status
		' '	Frozen and updateable session
		'N'	Frozen and non-updateable session
		'D'	Deleted session
66	15		Session Short Name

## UPDT - Description of Steps

### TRANSACTIONS FORMATTING: PACA05

Code	Physical name	Type	Label
PAC7AR	Base dir.: AR	Input	Development Database Data file
PAC7AN	Base dir.: AN	Input	Development Database Index file
PAC7AY	Base dir.: AY	Input	Development Database extension data
PAC7AE	System - Skel. dir.: AE	Input	Error messages
PACGGN	Admin. Base - Base dir.: AN	Input	Administration Database Index file
PACGGR	Admin. Base - Base dir.: AR	Input	Administration Database Data file
PACGGU	Admin. Base - Base dir.: GU	Input	Administration Database Users
PAC7MB	User input	Input	Update transactions
PAC7ME	Tmp dir.: WME	Output	Work file (length=372)
PAC7MV	Tmp dir. : WMV	Output	Formatted transactions (length=170, must be able to contain all input transactions plus the elementary delete transactions generated by the multiple delete transactions)
PAC7MW	Tmp dir. : WMW	Output	Work file

### UPDATE OF THE DEVELOPMENT DATABASE: PACA15

Code	Physical name	Type	Label
PAC7AR	Base dir.: AR	Output	Development Database Data file
PAC7AN	Base dir.: AN	Output	Development Database index
PAC7AY	Base dir.: AY	Output	Development Database extension
PAC7AJ	Journal dir.: AJ	Output	Development Database journal
PAC7AE	System - Skel. dir.: AE	Input	Error messages

Code	Physical name	Type	Label
PACGGN	Admin. Base - Base dir.: AN	Input	Administration Database Index file
PACGGR	Admin. Base - Base dir.: AR	Input	Administration Database Data file
PACGGY	Admin. Base - Base dir.: AY	Input	Administration Database Extension
PACGGU	Admin. Base - Base dir.: GU	Input	Administration Database users
PAC7DC	Base dir.: DC	Input	DSMS file of Development Database Elements
PAC7ME	Tmp dir.: WME	Input	Working file
PAC7MV	Tmp dir.: WMV	Input	Update transactions
PAC7RB	User dir. : ....RBA15	Output	UPDT erroneous transactions (length=80)
PAC7RY	User dir. : ....RYA15	Output	UPDP erroneous transactions (length=310)
PAC7IE		Report	Update report (length=132)
PAC7IF		Report	List of erroneous transactions (length=132)

The list of user transactions is preceded by a banner with the user code.

Return codes:

- 0: OK, no error
- 2: Warning
- 4: Critical error

## UPDT - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - BATCH UPDATE -
REM *
REM * -----
REM *
REM * REFER TO THE BATCH FORMS AND TO THE DESCRIPTION OF THE
REM * INPUT CORRESPONDING TO EACH ENTITY.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM *   COL 2 : '*'
REM *   COL 3 : USERIDXX
REM *   COL 11 : PASSWORD
REM *   COL 28 : LANGUAGE CODE, USEFUL WHEN TRANSACTION ARE
REM *           NOT IN THE SAME LANGUAGE AS THE DATABASE.
REM *   COL 67 : 'N' NOT 'UPPERCASE/LOWERCASE CONVERSION'
REM * - COMMAND LINE
REM *   THE LIST OF ALL AVAILABLE VALUES FOR THE ENTITY
REM *   TO BE UPDATED IS FOUND IN REFERENCE MANUAL.
REM *
REM * -----
REM *

```

```

<job id=UPDT>

<script language="VBScript">
Dim MyProc
MyProc = "UPDT"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PACA05"))
'-----
WshEnv("PAC7MB") = Fic_Input

'Example of Input File extracted from PACX :
' Call BvpEnv("PACA05", "PAC7xx", RepT_USR & "\PACxxx.txt")
'With RepT_USR is Global User Directory.

WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PACA05", "PAC7MV", Rep_TMP & "\WMV.tmp")
Call BvpEnv("PACA05", "PAC7ME", Rep_TMP & "\WME.tmp")
Call BvpEnv("PACA05", "PAC7MW", Rep_TMP & "\WMW.tmp")
Call RunCmdLog ("BVPACA05")

Call Err_Cod(Return , 0 , "PACA05")

Call Msg_Log (Array("1022" , "PACA15"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PACGGY") = Rep_ABASE & "\AY"
WshEnv("PAC7DC") = Rep_BASE & "\DC"
WshEnv("SEMLOCK") = Rep_BASE & "\LO"
WshEnv("SEMADMIN") = Rep_ABASE & "\LO"
Call BvpEnv("PACA15", "PAC7IE", Rep_USR & "\UPDTIEA15.txt")
Call BvpEnv("PACA15", "PAC7IF", Rep_USR & "\UPDTIFA15.txt")
Call BvpEnv("PACA15", "PAC7ME", Rep_TMP & "\WME.tmp")
Call BvpEnv("PACA15", "PAC7MV", Rep_TMP & "\WMV.tmp")
Call BvpEnv("PACA15", "PAC7RB", Rep_USR & "\UPDTRBA15.txt")
Call BvpEnv("PACA15", "PAC7RY", Rep_USR & "\UPDTRYA15.txt")
Call RunCmdLog ("BVPACA15")
If Return = 2 Then
Call Msg_Log (Array("1061"))
End If
If Return = 4 Then
Call Msg_Log (Array("1060"))
End If
Call Err_Cod(Return , 4 , "PACA15")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

```

```

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## SASY - Database System Backup Complement

### SASY - Introduction

This Database Backup procedure saves the Database using any utility of the Operating System, while at the same time creating a checkpoint, through the incrementation of the session number.

The following files are to saved:

- Data file (AR),
- Index file (AN).

#### EXECUTION CONDITIONS

The Data (AR) and Index (AN) files must have been saved.

The transaction Journal file (AJ) must have been archived via the ARCH procedure.

The database must be closed to on-line use in order to maintain its consistency during the backup.

#### ABNORMAL EXECUTION

The main cause of an abend is that the database remained open to on-line use while the procedure was being executed.

The procedure can be restarted as it is once the problem has been solved.

#### USER INPUT

No user input is necessary when requesting the execution of the SASY procedure.

#### RESULT

This procedure increments the current session number.

If the database is in an inconsistent state due to an abend in the last update, the SASY procedure is not executed and the backup executed by the on-site Operating System utility is not valid.

### SASY - Description of Steps

#### SESSION NUMBER INCREMENTATION: PTU502

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Input/Output	Development Database data
PAC7AE	System - Skel dir. : AE	Input	Error messages

Code	Physical name	Type	Label
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7MB	User input	User transactions	User transactions
PAC7GZ	User dir. : SASYGZ502	Report	Report
PAC7DD	User dir. : SASYDD502	Report	Batch procedure authorization option
PAC7DS	User dir. : SASYDS502	Report	Database validity report

## SASY - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *     - COMPLEMENT OF 'SYSTEM' BACKUP OF THE DATABASE-
REM *
REM * -----
REM *
REM * THE DATABASE SYSTEM BACKUP COMPLEMENT PROCEDURE
REM * (SASY) ALLOWS YOU TO SAVE THE DATABASE USING ANY
REM * UTILITY OF THE OPERATING SYSTEM, WHILE AT THE
REM * SAME TIME CREATING A CHECKPOINT, THROUGH THE
REM * INCREMENTATION OF THE SESSION NUMBER.
REM * THE FOLLOWING FILES ARE TO BE BACKED UP:
REM *   . DATA FILE (AR),
REM *   . INDEX FILE (AN).
REM *
REM * -----
REM *
<job id=SASY>

<script language="VBScript">
Dim MyProc
MyProc = "SASY"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTU502"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTU502","PAC7DD",Rep_USR & "\SASYDD502.txt")
Call BvpEnv("PTU502","PAC7DS",Rep_USR & "\SASYDS502.txt")
Call BvpEnv("PTU502","PAC7GZ",Rep_USR & "\SASYGZ502.txt")
Return = WshShell.Run("BVPTU502.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTU502")

```



```

Call Msg_Log (Array("1023"))
'-----
Call DeleteFldr (Rep_TMP)
Wscript.Quit (Return)

</script>
</job>

```

---

## REST - Database Restoration

### REST - Introduction

The Database Restoration procedure (REST) re-creates a database that can be manipulated on-line, using the sequential image produced by the Backup, the Database Management (PACS), the Reorganization (REOR) and Storage Optimization of Multi-volume Data (STOP) procedures.

It also allows the retrieval of archived transactions after this sequential image has been produced.

#### EXECUTION CONDITIONS

The database must be closed to on-line processing.

recommended

The REST procedure physically and logically reinitializes the Journal file, which must have been saved previously by the ARCH procedure.

#### ABNORMAL EXECUTIONS

Refer to chapter 'Overview', subchapter 'Abnormal Endings'.

If an abend occurs, the procedure can be restarted as it is once the problem has been solved.

### REST - Input / Processing / Results

Batch procedure access authorization: one '\*' line with user code and password.

The structure of the specific input is described in the chart below.

Position	Length	Value	Meaning
2	1	Y	Line code
3	5	nnnnn	Number of gaps
8	2	pp	Number of gaps as a percentage
10	2		Language code (EN, FR, ...)
12	1	0	No inhibition of journal
		1	Inhibition of journal (no
			journalization of update transactions)
		' '	Retrieval of previous value
14	3	REC	If archived transactions recovered

Position	Length	Value	Meaning
17	4	XXXX	4-character Database code chosen by the Database Manager (displayed in the top-right corner of VA Pac screens) Database code is required
21	4	nnnn	Maximum number of accesses for on-line searches in the Database (default value: 300)
25	1	U	Implicit update (default option)
		N	Explicit update
36	12		PFkeys assigned functions (2).
79	1		Dispatch option of Backup:
		'D'	Dispatch: sequential backup of the database in two separate files.
		'N'	No Dispatch: standard backup of the database in one PC file.
		' '	Retrieval of previous value

(2): PFKeys assignment:

12-position table, with each position referring to a standard function.

To modify the PFkey assigned to a function, the value of the new PFkey coded in base 36 is entered in the corresponding position in the table.

For example, to assign function 1 to PFKey 17, enter code 'H' in position 1 of the table.

No validation procedure is executed by the system. The PFkey assignment may be viewed on the corresponding sub-menu.

#### NOTE

Where there is no input, the Database characteristics remain unchanged.

Any field left blank will retrieve the current options.

- The limit of on-line accesses to the Journal depends on the number specified as input to the restoration procedure.

If you do not want the update transactions of the database to be saved in the Journal file, you can turn the 'journalization' off by setting this parameter to '1'.

In this case, it is not possible to restore the database using the recovery of archived transactions ('REC' entered on the input parameter line). It is therefore highly recommended to set this parameter to 0 (which is the default option), in order to avoid restoration problems.

In case of error, invalid parameters are ignored, and the system ensures restoration using the parameter values stored in the sequential image of the database.

#### SIMPLIFIED RESTORATION

If the backup was performed via a system utility followed by the SASY procedure, restoration via a utility must be followed by the RESY procedure, which ensures the consistency between files.

#### PRINTED REPORT

This procedure prints a report listing the requested options, associated errors, the number of records restored in the database for each file and the options stored in the new database.

#### RESULTS

Once the procedure has been executed, the database is ready to be used in batch or on-line mode.

#### NOTE

Once this procedure is executed, the current session number is the same as the session number of the sequential image, or of the most recent transaction, if you've requested archived transaction retrieval.

## **REST - Description of Steps**

### USER INPUT RECOGNITION: PTU010

Code	Physical name	Type	Label
CARTE	User input	Input	User parameters
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7PC	Save dir. : PC	Input	Sequential image of the development Database
PAC7PD	Save dir. : PD	Input	If backup option Dispatch: sequential image 2 of the database
PAC7PY	Save dir. : PY	Input	If Dispatch option of the backup: sequential image 3 of the database
PAC7MB	Tmp dir. : WMB	Output	Parameter
PAC7DD	User dir. : RESTDD010	Report	Batch procedures authorization option

Return code:

- 8: no authorization for batch procedure

### VALIDATION OF JOURNAL CONTENTS: PTU380

This step is executed only if the Journal file exists.

Code	Physical name	Type	Label
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7AE	System - Skel dir. : AE	Input	Error messages file

Code	Physical name	Type	Label
PAC7AJ	Journal dir. : AJ	Input	Journal file
PAC7EU		Report	(only if the journal was not saved)

Return codes:

0: The Journal file was archived.

8: The Journal file was not archived (no REST step is executed).

#### RESTORATION OF THE DATABASE: PTU400

This step is executed only if the Journal file has been archived.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7MB	Tmp dir. : WMB	Input	User transaction
PAC7PC	Save dir. : PC	Input	Sequential image of the development Database
PAC7PD	Save dir. : PD	Input	If backup option Dispatch: sequential image 2 of the database
PAC7PY	Save dir. : PY	Input	If Dispatch option in save procedure: sequential image 3 of the database
PAC7AR	Base dir. : AR	Output	Development Database data
PAC7AN	Base dir. : AN	Output	Development Database index
PAC7AY	Base dir. : AY	Output	Development Database extension data
PAC7AJ	Rép. journal : AJ	Output	Development Database Journal
PAC7PS	Tmp dir. : WPS	Output	Work file (2 records, length=144)
PAC7EU	User dir. : RESTEU400	Report	Backup report
PAC7DD	User dir. : RESTDD400	Report	Batch procedures authorization option

#### DATABASE AVAILABILITY - TRANSACTION RETRIEVAL: PTU420

This step is executed if the Journal file has been archived. It updates the first record of the Data file.

This step is REQUIRED to obtain a consistent database.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7AR	Base dir. : AR	Input/Output	Development Database data
PAC7JO	Save dir. : PJ	Input	Journal to apply
PAC7PS	Tmp dir. : WPS	Input	Work file
PAC7OJ	Tmp dir. : WOJ	Output	Update transactions (length=170)

Code	Physical name	Type	Label
PAC7EU		Report	Retrieval report

Return codes:

- 0: Transactions to retrieve
- 4: No transactions to retrieve or error on user input.

In case of abend, the update cannot be performed.

#### UPDATE OF THE ADMINISTRATION DATABASE: PACA15

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Output	Development Database data
PAC7AN	Base dir. : AN	Output	Development Database index
PAC7AY	Base dir. : AY	Output	Development Database extension
PAC7AJ	Journal dir. : AJ	Output	Development Database Journal
PAC7AE	System - Skel. dir.: AE	Input	Error messages
PACGGN	Admin. Base - Base dir.: AN	Input	Administration Database index
PACGGR	Admin. Base - Base dir.: AR	Input	Administration Database data
PACGGY	Admin. Base - Base dir.: AY	Input	Administration Database extension
PACGGU	Admin. Base - Base dir.: GU	Input	Administration Database users
PAC7DC	Base dir.: DC	Input	DSMS elements file of the development Database
PAC7ME	null	Input	Working file
PAC7MV	Tmp dir.: WOJ	Input	Update transactions
PAC7RB	nul	Output	UPDT erroneous transactions (length=80)
PAC7RY	nul	Output	UPDP erroneous transactions (length=310)
PAC7IE		Report	Update report (length=132)
PAC7IF		Report	List of erroneous transactions (length=132)

The list of transactions belonging to a user is preceded by a banner specifying the user code.

Return codes:

- 0: OK, no error
- 2: Warning
- 4: Critical error

## REST - Execution Script

```
REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - RELOADING RESTORATION OF THE DATABASE -
REM *
REM * -----
REM *
REM * INPUT
REM * COL  2      : 'Y'
REM * COL  3-7    : NUMBER OF GAPS IN ABSOLUTE VALUE
REM * COL  8-9    : NUMBER OF GAPS IN PERCENTAGE ( / BASE )
REM * COL 10-11   : INITIAL LANGUAGE CODE (FR, EN, ..)
REM * COL 12      : '1' INHIBITION OF TRANSACTION LOG
REM * COL 14-16   : 'REC' FOR RECOVERY OF ARCHIVED TRANSACTIONS
REM * COL 17-20   : 4 CHARACTERS TO BE DISPLAYED
REM *              ON ALL SCREEN OF THE PRODUCT
REM * COL 21-24   : 'NNNN' MAXIMUM NUMBER OF SEARCH ACCESSES
REM *              TO THE DATABASE(LISTS)-(DEFAULT VALUE:300)
REM * COL 25      : 'U' (DEFAULT VALUE) : IMPLICIT UPDATE
REM *              : 'N' EXPLICIT UPDATE
REM * COL 26-29   : CKECKPOINT FREQUENCY
REM * COL 36-47   : PF-KEYS SIGNIFICATIONS
REM * COL 79      : BACKUP FILES DISPATCH
REM *              : 'N' (DEFAULT VALUE) : NO DISPATCH (1 FILE)
REM *              : 'D' : DISPATCH (3 FILES)
REM *
REM * IN THE ABSENCE OF INPUT, THE RELOAD DOES NOT MODIFY THE
REM * NUMBER OF EXISTING GAPS, AND OTHER DATA IS UNCHANGED.
REM *
REM * IF THE JOURNAL FILE OF TRANSACTIONS ON DISK (AJ) IS NOT
REM * REINITIALIZED, THE RESTORE CHAIN IS NOT EXECUTED.
REM * IT IS THEREFORE NECESSARY TO EXECUTE THE ARCH PROCEDURE
REM * FIRST.
REM * -----
<job id=REST>

<script language="VBScript">
Dim MyProc
MyProc = "REST"
</script>
<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1029" ))
'-----
Call Statelist (base, statusL)

If c_error = 1 then Wscript.Quit (1) End If

Dim Ret420
Ret420 = 0

Call Msg_Log (Array("1022" , "PTU010"))
'-----
WshEnv("CARTE") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTU010","PAC7DD",Rep_USR & "\RESTDD010.txt")
Call BvpEnv("PTU010","PAC7MB",Rep_TMP & "\WMB.tmp")
```

```

WshEnv("PAC7PC") = BVP_SvName & ""
WshEnv("PAC7PD") = BVP_SvName & "I"
WshEnv("PAC7PY") = BVP_SvName & "Y"
Call RunCmdLog ("BVPTU010")
WshVolEnv("RC") = Return

If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
Call Err_Cod(Return , 0 , "PTU010")

If FSO.FileExists(Rep_JOURNAL & "\AJ") Then
Call Msg_Log (Array("1022" , "PTU380"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
Call BvpEnv("PTU380","PAC7EU",Rep_USR & "\RETEU380.txt")
Call BvpEnv("PTU380","PAC7MB",Rep_TMP & "\WMB.tmp")
Call RunCmdLog ("BVPTU380")
WshVolEnv("RC") = Return
If Return = 8 Then
Call Msg_Log (Array("1058"))
End If
Call Err_Cod(Return , 0 , "PTU380")
End If

Call Msg_Log (Array("1022" , "PTU400"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
Call BvpEnv("PTU400","PAC7DD",Rep_USR & "\RESTDD400.txt")
Call BvpEnv("PTU400","PAC7EU",Rep_USR & "\RETEU400.txt")
Call BvpEnv("PTU400","PAC7MB",Rep_TMP & "\WMB.tmp")
WshEnv("PAC7PC") = BVP_SvName & ""
WshEnv("PAC7PD") = BVP_SvName & "I"
Call BvpEnv("PTU400","PAC7PS",Rep_TMP & "\WPS.tmp")
WshEnv("PAC7PY") = BVP_SvName & "Y"
Call RunCmdLog ("BVPTU400")
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PTU400")

If FSO.FileExists( Rep_SAVE & "\PJ" ) Then
Call Msg_Log (Array("1022" , "PTU420"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7JO") = Rep_SAVE & "\PJ"
Call BvpEnv("PTU420","PAC7MB",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTU420","PAC7OJ",Rep_TMP & "\WOJ.tmp")
Call BvpEnv("PTU420","PAC7PS",Rep_TMP & "\WPS.tmp")
Call BvpEnv("PTU420","PAC7EU",Rep_USR & "\RETEU420.txt")
Call RunCmdLog ("BVPTU420")
Ret420 = Return

If Return = 4 Then
'No transaction to be retrieved : Normal End
'-----
Call Msg_Log (Array("1059"))
Call Msg_Log (Array("1024"))
Return = 0
WshVolEnv("RC") = Return

Else
WshVolEnv("RC") = Return

```

```

Call Err_Cod(Return , 0 , "PTU420")
End If

If Ret420 = 0 then
'Update
Call Msg_Log (Array("1022" , "PACA15"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PACGGY") = Rep_ABASE & "\AY"
WshEnv("PAC7DC") = Rep_BASE & "\DC"
Call BvpEnv("PACA15","PAC7IE",Rep_USR & "\RESTIEA15.txt")
Call BvpEnv("PACA15","PAC7IF",Rep_USR & "\RESTIFA15.txt")
WshEnv("SEMLOCK") = Rep_BASE & "\LO"
WshEnv("SEMADMIN") = Rep_ABASE & "\LO"
WshEnv("PAC7ME") = "NUL"
Call BvpEnv("PACA15","PAC7MV",Rep_TMP & "\WOJ.tmp")
WshEnv("PAC7RB") = "NUL"
WshEnv("PAC7RY") = "NUL"
Call RunCmdLog ("BVPACA15")
WshVolEnv("RC") = Return
If Return = 2 Then
Call Msg_Log (Array("1061"))
End If
If Return = 4 Then
Call Msg_Log (Array("1060"))
End If
Call Err_Cod(Return , 4 , "PACA15")
End If

End If 'If Rep_SAVE & "\PJ"

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
WshVolEnv("RC") = Return
Wscript.Quit (Return)

</script>
</job>

```

---

## RESY - Database System Restoration Complement

### RESY - Introduction

This procedure restores a Database that can be handled in on-line mode, from a System backup obtained through a utility followed by the SASY procedure.

It is executed after a System restoration utility to complete the restoration of the Data (AR), Index (AN), and Extension (AY) files, and reinitializes the Journal (AJ) file.

Through the RESY procedure, the archived transactions can be recovered if 'REC' is entered on the input parameter line.



If the Journal file is not reinitialized, it must be archived prior to the System utility restoration and RESY procedures.

#### EXECUTION CONDITIONS

This procedure can be executed only after restoration of the AN AR and AY files by the on-site system utility.

On-line access must be closed.

#### ABNORMAL EXECUTIONS

If an abend occurs, the procedure can be restarted as it is once the problem has been solved.

#### PRINTED REPORT

The RESY procedure prints a report listing the requested options and related errors, the number of records reloaded in the database per file and the options memorized in the new database.

#### RESULTS

Once the RESY procedure has been executed, the database can be used in both batch or on-line modes.

**NOTE:** After the procedure execution, the current session number is the session number of the restored image, or of the most recent transaction if the retrieval of archived transactions has been requested.

## **RESY - Input / Processing / Results**

A '\*' line with user code and password.

The input has the following structure:

Position	Length	Value	Meaning
2	1	'Y'	Line code
10	1		Language code (FR, EN...)
12		'0'	No journal inhibition
		'1'	Inhibition of journal (update transactions are not journalized)
		' '	Retrieval of the last value
14	3	REC	if archived transactions are recovered
17	4	XXXX	4-character Database code chosen by the Database Manager (displayed in the top-right corner of all screens)
21	4	'nnnn'	Maximum number of accesses for on-line searches in the Database (default value: 300)
25	1	U	Implicit update (default option)
		N	Explicit update

Position	Length	Value	Meaning
26	4	'nnnn'	Checkpoint frequency rate (IMS, UNISYS, GCOS7, and GCOS8 only) if REC in col. 13 (default: nnnn=0000)
36	12		PFkeys assigned functions (1)
79	1		Dispatch option of backup:
		'D'	Dispatch Sequential backup of the database on two separate files.
		'N'	No Dispatch Standard backup on a single PC file.
		' '	Same as previous execution.

PFKeys assignment:

12-position table: each position corresponds to a standard function. To modify the PFkey assigned to a function, the value of the new PFkey coded in base 36 is entered in the corresponding position in the table.

For example, to assign function 1 to PFkey 17, code 'H' in position 1 of the table.

No validation procedure is executed by the system. The PFkey assignment may be viewed on the corresponding sub-menu.

#### NOTE

Any field left blank defaults to the current option selection.

If you do not want the update transactions of the database to be saved on the Journal file, you can turn "journalization" off by setting this parameter to '1'. In this case, it is not possible to restore the database using the recovery of the archived transactions (REC parameter in the user input).

It is thus highly recommended that you set this parameter to '0' or leave it blank (default option), in order to avoid restoration problems.

In case of error, invalid parameters are ignored, and the system ensures restoration using the parameter values stored in the sequential image of the database.

## **RESY - Description of Steps**

### USER INPUT RECOGNITION: PTU004

Code	Physical name	Type	Label
CARTE	User input	Input	Parameter
PAC7MB	Tmp dir. : WMB	Output	Parameter
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7DD	User dir. : RESYDD004	Input	Batch procedures authorization option

Return code:

- 8: no batch procedure authorization

#### VALIDATION OF JOURNAL CONTENTS: PTU380

This step is executed only if the Journal file exists.

Code	Physical name	Type	Label
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PAC7AJ	Journal dir. : AJ	Input	Journal file
PAC7EU		Report	(only if the journal was not saved)

Return codes:

0: The Journal file was archived.

8: The Journal file was not archived (no REST step is executed).

#### DATABASE POSITIONING: PTU402

This step is executed only if the Journal file has been archived.

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Output	Data file
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7PS	Tmp dir. : WPS	Output	Work file (2 records, length=144)
PAC7PS	User dir. : RESYGZ402	Report	Backup report

#### DATABASE AVAILABILITY - TRANSACTION RETRIEVAL: PTU420

This step is executed if the Journal file has been archived. It updates the first record of the Data file.

This step is REQUIRED to obtain a consistent database.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7MB	Tmp dir. : WMB	Input	User transactions
PAC7AR	Base dir. : AR	Input/Output	Development Database data
PAC7JO	Save dir. : PJ	Input	Journal to apply
PAC7PS	Tmp dir. : WPS	Input	Work file
PAC7OJ	Tmp dir. : WOJ	Output	Update transactions (length=170)
PAC7EU		Report	Retrieval report

Return codes:

- 0: Transactions to retrieve
- 4: No transactions to retrieve or error on user input.

In case of abend, the update cannot be performed.

#### UPDATE OF THE ADMINISTRATION DATABASE: PACA15

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Output	Development Database data
PAC7AN	Base dir. : AN	Output	Development Database index
PAC7AY	Base dir. : AY	Output	Development Database extension
PAC7AJ	Journal dir. : AJ	Output	Development Database Journal
PAC7AE	System - Skel. dir.: AE	Input	Error messages
PACGGN	Admin. Base - Base dir.: AN	Input	Administration Database index
PACGGR	Admin. Base - Base dir.: AR	Input	Administration Database data
PACGGY	Admin. Base - Base dir.: AY	Input	Administration Database extension
PACGGU	Admin. Base - Base dir.: GU	Input	Administration Database users
PAC7DC	Base dir.: DC	Input	DSMS elements file of the development Database
PAC7ME	null	Input	Working file
PAC7MV	Tmp dir.: WOJ	Input	Update transactions
PAC7RB	nul	Output	UPDT erroneous transactions (length=80)
PAC7RY	nul	Output	UPDP erroneous transactions (length=310)
PAC7IE		Report	Update report (length=132)
PAC7IF		Report	List of erroneous transactions (length=132)

The list of transactions belonging to a user is preceded by a banner specifying the user code.

Return codes:

- 0: OK, no error
- 2: Warning
- 4: Critical error

## RESY - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - 'SYSTEM' RELOADING RESTORATION COMPLEMENT -
REM *
REM * -----
REM *
REM *
REM * INPUT
REM * COL 2      : 'Y'
REM * COL 10-11  : INITIAL LANGUAGE CODE (FR, EN, ..)
REM * COL 12     : '1' INHIBITION OF TRANSACTION LOG
REM * COL 14-16  : 'REC' FOR RECOVERY OF ARCHIVED TRANSACTIONS
REM * COL 17-20  : 4 CHARACTERS TO BE DISPLAYED ON ALL
REM *              SCREEN OF THE PRODUCT
REM * COL 21-24  : 'NNNN' MAXIMUM NUMBER OF SEARCH ACCESSES
REM *              TO THE DATABASE(LISTS)-(DEFAULT VALUE:300)
REM * COL 25     : 'U' (DEFAULT VALUE) : IMPLICIT UPDATE
REM *              : 'N' EXPLICIT UPDATE
REM * COL 26-29  : CKECKPOINT FREQUENCY
REM * COL 36-47  : PF-KEYS SIGNIFICATIONS
REM * COL 79     : BACKUP FILES DISPATCH
REM *              : 'N' (DEFAULT VALUE) : NO DISPATCH (1 FILE)
REM *              : 'D' : DISPATCH (2 FILES)
REM *
REM * IF THE JOURNAL FILE OF TRANSACTIONS ON DISK (AJ) IS NOT
REM * REINITIALIZED, THE RESTORE CHAIN IS NOT EXECUTED.
REM * IT IS THEREFORE NECESSARY TO EXECUTE THE ARCH
REM * PROCEDURE FIRST.
REM *
REM * -----
REM *
<job id=RESY>

<script language="VBScript">
Dim MyProc
MyProc = "RESY"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then
  WshVolEnv("RC") = 1
  Wscript.Quit (1)
End If

Call Msg_Log (Array("1022" , "PTU004"))
'-----
WshEnv("CARTE") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"

```

```

WshEnv("PACGGR") = Rep_ABASE & "\\AR"
WshEnv("PACGGU") = Rep_ABASE & "\\GU"
Call BvpEnv("PTU004","PAC7DD",Rep_USR & "\\RESYDD004.txt")
Call BvpEnv("PTU004","PAC7MB",Rep_TMP & "\\WMB.tmp")
Return = WshShell.Run("BVPTU004.exe" , 1, TRUE)
WshVolEnv("RC") = Return
If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
Call Err_Cod(Return , 0 , "PTU004")

If FSO.FileExists(Rep_JOURNAL & "\\AJ") Then
Call Msg_Log (Array("1022" , "PTU380"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\\AJ"
Call BvpEnv("PTU380","PAC7EU",Rep_USR & "\\RESYEU380.txt")
Call BvpEnv("PTU380","PAC7MB",Rep_TMP & "\\WMB.tmp")
Return = WshShell.Run("BVPTU380.EXE" , 1, TRUE)
WshVolEnv("RC") = Return
If Return = 8 Then
Call Msg_Log (Array("1058"))
End If
Call Err_Cod(Return , 0 , "PTU380")

Call Msg_Log (Array("1022" , "PTU402"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\\AE"
WshEnv("PAC7AR") = Rep_BASE & "\\AR"
WshEnv("PACGGN") = Rep_ABASE & "\\AN"
WshEnv("PACGGR") = Rep_ABASE & "\\AR"
WshEnv("PACGGU") = Rep_ABASE & "\\GU"
Call BvpEnv("PTU402","PAC7GZ",Rep_USR & "\\RESYGZ402.txt")
Call BvpEnv("PTU402","PAC7MB",Rep_TMP & "\\WMB.tmp")
Call BvpEnv("PTU402","PAC7PS",Rep_TMP & "\\WPS.tmp")
Return = WshShell.Run("BVPTU402.exe" , 1, TRUE)
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PTU402")

If FSO.FileExists( Rep_SAVE & "\\PJ" ) Then
Call Msg_Log (Array("1022" , "PTU420"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\\AE"
WshEnv("PAC7AR") = Rep_BASE & "\\AR"
WshEnv("PAC7J0") = Rep_SAVE & "\\PJ"
Call BvpEnv("PTU420","PAC7MB",Rep_TMP & "\\WMB.tmp")
Call BvpEnv("PTU420","PAC7OJ",Rep_TMP & "\\WOJ.tmp")
Call BvpEnv("PTU420","PAC7PS",Rep_TMP & "\\WPS.tmp")
Call BvpEnv("PTU420","PAC7EU",Rep_USR & "\\RESYEU420.txt")
Return = WshShell.Run("BVPTU420.EXE" , 1, TRUE)
Ret420 = Return

If Return = 4 Then
'No transaction to be retrieved : Normal End
'-----
Call Msg_Log (Array("1059"))
Call Msg_Log (Array("1024"))
Return = 0
WshVolEnv("RC") = Return

Else
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PTU420")
End If

If Ret420 = 0 then

```

```

'Update
Call Msg_Log (Array("1022" , "PACA15"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PACGGY") = Rep_ABASE & "\AY"
WshEnv("PAC7DC") = Rep_BASE & "\DC"
Call BvpEnv("PACA15","PAC7IE",Rep_USR & "\RESYIEA15.txt")
Call BvpEnv("PACA15","PAC7IF",Rep_USR & "\RESYIFA15.txt")
WshEnv("SEMLOCK") = Rep_BASE & "\LO"
WshEnv("SEMADMIN") = Rep_ABASE & "\LO"
WshEnv("PAC7ME") = "NUL"
Call BvpEnv("PACA15","PAC7MV",Rep_TMP & "\WOJ.tmp")
WshEnv("PAC7RB") = "NUL"
WshEnv("PAC7RY") = "NUL"
Return = WshShell.Run("BVPACA15.exe" , 1, TRUE)
WshVolEnv("RC") = Return
If Return = 2 Then
Call Msg_Log (Array("1061"))
End If
If Return = 4 Then
Call Msg_Log (Array("1060"))
End If
Call Err_Cod(Return , 4 , "PACA15")
End If

End If 'If Rep_SAVE & "\PJ"

End If
'/ ? existing AJ

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr ( Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
WshVolEnv("RC") = Return
Wscript.Quit (Return)

</script>
</job>

```

---

## ARCH - Journal Archival

### ARCH - Introduction

This procedure saves the Journal file as a sequential file, and re-initializes it both logically and physically.

Archived transactions do not override those transactions that were previously archived, but are added to them.

The archived-transaction file may be purged. Purged transactions may then be saved in another file (PQ).

Previously archived transactions can be purged, if requested. (However, non-archived journal transactions cannot be purged.)

## EXECUTION CONDITIONS

On-line access must be closed.

## ABNORMAL EXECUTIONS

If an abend occurs before the step that creates the Journal file, the procedure can be restarted as it is once the problem has been solved.

Otherwise, the procedure must be restarted after a modification of the user input in order to specify a re-initialization request without a backup of the Journal file, since it has already been backed up.

## **ARCH - Input / Processing / Results**

Batch procedure access authorization option: one '\*' line with user code and password.

This procedure includes specific optional input to:

- Deactivate previously archived transactions that are considered obsolete.
- Signal the absence of previously archived transactions in input.
- Signal the unavailability of the Data file (AR) in input.
- Request only the re-initialization of the transaction file.

The structure of this input is as follows:

Position	Length	Value	Meaning
2	1	'S'	Line code
3	4	nnnn	Session number
7	8	ccymmdd	OR date up to which the user requests deactivation
15	1	'T'	Absence of previously archived transactions
16	1	'D'	Data file unavailable
17	1	'J'	Re-initialization without backup, the transactions already archived are NOT retrieved in output.

The session number and the date are exclusive. They are ignored if the absence of input transactions is signalled (refer to Section Recommendations).

The unavailability of the Data file is to be indicated only when this file has been physically deleted. (See Section Recommendations below.)

A request to re-initialize without archiving is necessary when the Journal file is physically deleted.

## WARNING

In this case, the transactions which were already archived are not copied on to the transaction output file. (If this input file is automatically catalogued by the operating system, the transactions already archived may be lost unless the file is uncatalogued).



In an error occurs on one of the options, a message is printed and the archive is generated using the default options.

### RECOMMENDATIONS

If there is no user input, this procedure can only be executed if the Database is in a consistent state, and if the archived transaction file is correctly formatted.

When the Database needs to be restored after an abend or a system failure, some information in the Specifications Dictionary is sometimes lost, thus preventing the execution of the backup and restoration procedures.

In this case, AND IN THIS CASE ONLY, columns 15 to 17 of the user input are to be used as follows:

- If the Data file (AR) is lost or has been flagged as 'inconsistent', a 'D' in column 16 means that the backup procedure will not take the Data file (AR) into account. However, the restoration procedure must be executed afterward, since under these conditions, the backup procedure leaves the database in an inconsistent state.
- If the Journal file (AJ) is lost or destroyed, a 'J' must be entered in column 17. As a result, the backup procedure formats an empty Journal file. The restoration procedure may then be executed (not compulsory). In this case, the content of the journal file (AJ) is lost.
- If the transactions Back-up file is lost or destroyed, an 'T' must be entered in column 15. As a result, the ARCH procedure reformats a new sequential backup file of (archived) transactions.

If one of these columns is accidentally set, and if the ARCH procedure is executed while the Database is in a consistent state, the consequences are:

- 'T' in col. 15: Previously archived transactions are lost. All transactions can be recovered by concatenating (-1) and (0) to obtain (+1).
- 'D' in col. 16: The ARCH procedure must be re-executed BEFORE any update. If an update is subsequently performed, the Database will be lost, and will have to be restored completely.
- 'J' in col. 17: The contents of the Journal file are definitely lost. The output Journal file, (+1 version in the case of generation data files), is created empty.

### PRINTED OUTPUT

This procedure prints a report stating the number of archived transactions and, if applicable, the number of records that have been 'purged'.

### RESULTS

Once this procedure is executed, a sequential file containing all archived transactions is obtained.

The Journal file which displays transactions on-line is re-initialized.

It is also possible to store on another file all transactions that have been purged.

### NOTE

This procedure does not increment the session number.

## ARCH - Description of Steps

### PARTICULAR CASE OF THE FIRST DATABASE ARCHIVING

In order for the first database archival to run correctly, the PJ file, containing archived transactions used as input of the procedure, is created as an empty file, and stored in the ÈSAVE directory during installation.

### ARCHIVED-TRANSACTION PURGE

When a purge of archives is requested in the transactions files, two situations are possible:

1. The user does not wish to keep the purged archives in the PJ file: the file with PAC7PQ as internal name must be assigned to 'NUL'.

This is done as a default in the procedure command file.

2. The user wishes to keep purged archives in the PJ file: the file with PAC7PQ as internal name must be assigned.

For instance:

```
WshEnv("PAC7PQ") = Rep_SAVE & "\PQ"
```

### ARCHIVAL OF JOURNAL FILE: PTU300

This step:

- writes obsolete transactions to be purged on to a special file, if the purge is requested in user input.
- positions a flag in the Data file indicating the journal archive.
- updates the file of archived transactions.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7JP	Save dir. : PJ	Input	Previously archived transactions
PAC7AJ	Journal dir. : AJ	Input	Development Database journal to re-initialize
PAC7MB	User input	Input	User transactions
PAC7BM	Tmp dir. : WBM	Output	User transactions
PAC7AR	Base dir. : AR	Input/Output	Development Database data
PAC7PJ	Save dir. : PJ.new	Output	Archived update transactions
PAC7PQ	nul	Output	Deactivated transactions (length=170): modify the file name in order to keep the transactions
PAC7EU	User dir. : ARCHEU300	Report	Output report
PAC7DD	User dir. : ARCHDD300	Report	Batch procedures authorization option

Return codes:

- 0: No error detected on the files,
- 4: Error in journal record (Date or session number not numeric)
- 8: No access authorization for batch procedure, OR: invalid database; in this case, restart the procedure with 'D' in column 16 of the user input .
- 12: Input-output error on a file.

#### RE-INITIALIZATION OF THE JOURNAL FILE: PTU320

This step executes the following:

- Creates the first record in the Journal file,
- Re-initializes the Data file flag with the Journal file's address.

Code	Physical name	Type	Label
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7AR	Base dir. : AR	Input/Output	Data file
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PAC7AJ	Journal dir. : AJ	Output	Journal file to re-initialize
PAC7EU	User dir. : ARCHEU320	Report	Re-initialization report

Return codes:

- 0: No error detected,
- 8: The database is invalid.

If the archival and backup procedures are grouped into one job, the PTU320 return code can be tested in order to condition the execution of the backup programs.

## ARCH - Execution Script

```
REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - ARCHIVAL OF THE JOURNAL -
REM *
REM * -----
REM *
REM * INPUT      : COMMAND FOR DEACTIVATION OF ARCHIVED
REM *              TRANSACTION
REM * COL 2      : 'S'
REM * COL 3 TO 6 : SESSION NUMBER
REM * COL 7 TO 14 : DATE (CCYYMMDD)
REM * COL 15     : ' ' PRESENCE OF ARCHIVED TRANSACTION FILE
REM *              : 'I' ABSENCE OF ARCHIVED TRANSACTION FILE
REM * COL 16     : ' ' PRESENCE OF DATA FILE (AR)
REM *              : 'D' ABSENCE OF DATA FILE (AR)
REM * COL 17     : ' ' ARCHIVAL AND REINITIALIZATION
REM *              : 'J' REINITIALIZATION WITHOUT ARCHIVAL
REM *
REM * IN THE ABSENCE OF INPUT (OR ERROR ON A COMMAND PARAM.)
REM * NO DEACTIVATION WILL TAKE PLACE, HOWEVER ARCHIVAL AND
REM * REINITIALIZATION WILL BE EXECUTED NORMALLY.
REM *
REM * TRANSACTIONS WHOSE SESSION (DATE) IS PRIOR OR EQUAL TO
REM * THE SESSION (DATE) INDICATED ARE NOT KEPT. THEY ARE
```

```

REM * RECOVERED IN THE FILE OF DEACTIVATED TRANSACTION.
REM *
REM * -----
<job id=ARCH>

<script language="VBScript">
MyProc = "ARCH"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1029" ))
'-----
Call Statelist (base, statusL)

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTU300"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7JP") = Rep_SAVE & "\PJ"
WshEnv("PAC7PJ") = Rep_SAVE & "\PJ.new"
WshEnv("PAC7PQ") = "NUL"
Call BvpEnv("PTU300","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU300","PAC7EU",Rep_USR & "\ARCHEU300.txt")
Call BvpEnv("PTU300","PAC7DD",Rep_USR & "\ARCHDD300.txt")
Call RunCmdLog ("BVPTU300")

If Return = 8 Then
Call Msg_Log (Array("1032"))
End If
If Return = 12 Then
Call Msg_Log (Array("1026"))
End If
Call Err_Cod(Return , 0 , "PTU300")

Call Msg_Log (Array("1022" , "PTU320"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AJ") = Rep_JOURNAL & "\AJ"
Call BvpEnv("PTU320","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU320","PAC7EU",Rep_USR & "\ARCHEU320.txt")
Call RunCmdLog ("BVPTU320")

Call Err_Cod(Return , 0 , "PTU320")

Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(Rep_SAVE & "\PJ")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

```

```
Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>
```

---

## REOR - Reorganization

### REOR - Introduction

The Database Reorganization procedure optimizes Database accesses by accounting for each deletion, and sorting the data again according to the most frequent access order.

It uses one or two backup files of the development Database (if the Dispatch option is used), to rebuild one (or 2) sequential image(s). This resulting image file must then be restored via the REST procedure described above.

The operating principle of this procedure is to rebuild the different indexes associated with all data using the 'image' of each Data Element. It makes the best of the system performance features since it separates historical (frozen) sessions from the current session and sorts the data in the order of the most frequent access. This makes it possible to achieve a significant reduction of the number of indexes and data items.

The REOR procedure may be used in two cases:

- When part of the data was deleted because of a malfunction or system failure, and no other procedure can be used (in particular, deletion of the AN Index file),
- When the database is to be purged of the following:
  - Obsolete libraries and/or sessions;
  - Entities not used in the database;

When a library is deleted, this procedure produces the same results as the Database Management (MLIB) procedure, except that it additionally deletes 'gaps'.

This procedure should be executed only on an exceptional basis, because of the special conditions concerning its use and its lengthy execution time.

Deletions taken into account by the reorganization may have been made logically by the Database update, or generated by one or several utilities. For example:

- Deletion of unused Production sessions (PEI Function)
- Deletion of entities not associated to a specific use, determined by the unused-entity extraction utility, EXPU (see the PACX procedure in 'the Developer's Procedures' manual).

### EXECUTION CONDITIONS

If the database is available, it may remain open during reorganization since the procedure operates on sequential images of the database.

Updates executed after the back-up file used for reorganization has been built will be retrievable while the reorganized database is being restored.

Batch procedure access authorization option: Global authorization level 4 is required.

### ABNORMAL EXECUTIONS

Refer to chapter 'Overview', subchapter 'Abnormal Endings'.

As specified in paragraph 'Important recommendations' below, the Reorganization procedure can be very long. It is therefore advisable to keep all temporary files after each step.

If one of the steps abends, the procedure can be restarted at the step level, but not at the procedure level.

## **REOR - Input / Processing / Results**

A '\*' line with user code and password.

Specific user input for the procedure (optional), specifying

- libraries to be purged,
- sessions to be purged or to be kept,
- users to be purged.
- entities to be purged.
- a report of the duplicate indexes of the REOR procedure.

Position	Length	Value	Meaning
2	1	'B'	Library purge
3		bbb	Library code(s)
			up to 23 library codes per line

Maximum number of libraries to be purged: 300.

Position	Length	Value	Meaning
2	1	'V'	Purge frozen sessions
		'S'	Save frozen sessions
			'V' and 'S' lines are not compatible
3		ssss	Session number(s): up to 17 session numbers per line, entered without any separator.

Maximum number of sessions indicated on the request: 999.

Maximum number of frozen sessions in a database: 7,500.

Position	Length	Value	Meaning
2	1	'U'	Purge users
3		uuuuuuuu	User code(s) up to 9 user codes per line

Position	Length	Value	Meaning
2	1	'E'	Physical purge of entities (transactions provided by EXPU)
3			Entity Type:
	1		.Type
	2		.UE call type (if Type "\$")
6	30		Code of the entity to be purged (may be a joker code)
36	3		Library code
			5 groups of type/code entity/lib. possible per 'E'-type line

A line per entity.

A Maximum number of 2,500 occurrences of an entity type is processed by the execution of the REOR procedure. The 'List of 'purged' entities' signals when this limit is reached. In case of a generic request, the entity code must be completed with \*'s to make up for six characters. If the code contains six '\*', all of the entity's occurrences will be deleted.

Position	Length	Value	Meaning
2	1	'D'	List of duplicate indexes of the REOR procedure
3	1	' '	no report of duplicate indexes
		'1'	Report of duplicate indexes
		'2'	Report of PMS calls which might be incoherent
		'3'	Reports of values '1' and '2'

When the system finds an input error, it generates an error message and the procedure is not executed.

#### ESTIMATING FILE SIZE

The maximum sizes used during this procedure are based on the sizes of the files in the database before reorganization. The report printed by the preceding SAVE procedure provides all the relevant data:

- NI = number of index file records,
- ND = number of data file records MINUS number of gaps,
- NC = number of primary records on the data file,
- NH = number of 'frozen' (historical account) records from the data file (NH = ND - NC)

These symbols are also detailed in the presentation of each of the files for this procedure.

#### PRINTED REPORT

This procedure prints a report listing errors found during reorganization, and statistics on the contents of the database.

## RESULTS

The output of this procedure is a reorganized sequential image of the database (where purges may have been performed). It does not contain gaps. Gaps can be added by the REST procedure.

## NOTE

This procedure does not increment the current session number of the database.

## IMPORTANT RECOMMENDATIONS

The Reorganization procedure presents a number of characteristics which the user should be aware of:

- The step that rebuilds the Index file uses a large amount of CPU time.
- If the database contains a large amount of data, it is recommended to catalog the temporary files, or to use tape files to obtain the checkpoints in case of an abend in one of the steps.
- If files are transferred onto tape it is preferable to check on the initial blocking factors.
- The space allocated to the sortworks should also be calculated with care.

## **REOR - Description of Steps**

### VALIDATION OF USER INPUT: PTU2CL

This step validates user input and sets a return code when an error is detected.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7PC	Save dir. : PC	Input	Sequential image of the development Database
PAC7MB	User Input	Input	Input work file
PAC7BM	Tmp dir. : WBM	Output	Formatted records
PAC7PU	Tmp dir. : WPU	Output	Entity records to be purged (length=44)
PAC7EE	User dir. : REOREE2CL	Report	Control report
PAC7DD	User dir. : REORDD2CL	Report	Batch procedures authorization option

.Return code(s):

- 0: OK
- 4: Error on user input
- 8: No authorization for Batch procedure.



### RETRIEVAL OF DATA: PTU200

This step selects 'data' type information in the initial sequential file of the database (in case the Dispatch option is used, it leads to the recognition of one input file, which contains the data, i.e. PC(0)). It then formats the key of each record selected for the subsequent sort.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7PC	Save dir. : PC	Input	Sequential image of the development Database
PAC7PY	Save dir. : PCY	Input	Sequential image of the extension data of the development Database
PAC7PR	Tmp dir. : WPR	Output	Formatted records (length=176 size=ND)
PAC7NX	Tmp dir. : WNX	Output	Long data
PAC7NY	Tmp dir. : WNY	Output	Unformatted data
PAC7AU	Tmp dir. : WAU	Output	PR image (length=153)
PAC7EE	User dir. : REOREE200	Report	Report on statistics retrieval

### ASCII SORT: PTU205

Code	Physical name	Type	Label
PAC7PR	Tmp dir. : WPR	Input	Sorted data records
PAC7RP	Tmp dir. : WRP	Output	ASCII sorted data records

The SORT program requires disk space equivalent to twice the size of the file to be sorted.

### PURGE: PTU210

This step purges all libraries and sessions entered in the user input. When there is no input, it reformats records.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7PR	Tmp dir. : WRP	Input	Sorted records
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7PU	Tmp dir. : WPU	Input	Entity records to be purged
PAC7QS	Tmp dir. : WQS	Output	Purged records (length=176, size=ND)
PAC7UM	Tmp dir. : WUM	Output	Macro-structure call lines (length=176)
PAC7EE	User dir. : REOREE210	Report	Library and session purge report
PAC7EK	User dir. : REOREK210	Report	Entity-purge report
PAC7EB	User dir. : REOREB210	Report	Technical report

Return codes:

- 0: OK
- 8: Overload of capacity

The following steps are executed only if the return code is 0.

#### INDEX REBUILDING: PTU220

This step executes two types of procedures:

- Reconstruction of the indexes using the data

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PAC7BM	Tmp dir. : WBM	Input	User transactions
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7UR	Tmp dir. : WQS	Input	Purged data
PAC7NX	Tmp dir. : WNX	Input	Long data
PAC7UM	Tmp dir. : WUM	Input	Macro-structure call lines
PAC7PA	Tmp dir. : WPA	Output	Data from frozen sessions (length=153 size=NH)
PAC7PB	Tmp dir. : WPB	Output	Data from current session (length=153 size=NC)
PAC7PC	Tmp dir. : WPC	Output	First data records (length=153)
PAC7AN	Tmp dir. : WAN	Output	Intermediate index file (length=60 size=NI)
PAC7MR	Tmp dir. : WMR	Input/Output	Macro-structure call lines
PAC7EE	User dir. : REOREE220	Report	Index-building report

#### ASCII SORT: PTU225

Code	Physical name	Type	Label
PAC7AN	Tmp dir.: WAN	Input	Sorted index
PAC7NA	Tmp dir.: WNA	Output	ASCII Sorted index

The SORT program requires disk space equivalent to twice the size of the file to be sorted.

#### EXTENSION DATA PROCESSING: PTU226

Code	Physical name	Type	Label
PAC7NY	Tmp dir. : WNY	Input	Unformatted data
PAC7PA	Tmp dir. : WPA	Input	Data from frozen sessions
PAC7PB	Tmp dir. : WPB	Input	Data from current session
PAC7PC	Tmp dir. : WPC	Input	First data records

Code	Physical name	Type	Label
PAC7QA	Tmp dir. : WQA	Output	Data from frozen sessions (length=153)
PAC7QB	Tmp dir. : WQB	Output	Data from current session (length=153)
PAC7QC	Tmp dir. : WQC	Output	First data records (length=153)
PAC7QY	Tmp dir. : WQY	Output	Long data (length=1,018)

#### MERGE: PTU240

This step reconstructs the final sequential image using the temporary files produced by the previous step.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Tmp dir. : WNA	Input	Sorted index
PAC7AU	Tmp dir. : WAU	Input	PR image
PAC7BM	Tmp dir. : WBM	Input	User transactions
PAC7PA	Tmp dir. : WQA	Input	Data from frozen sessions
PAC7PB	Tmp dir. : WQB	Input	Data from current session
PAC7PC	Tmp dir. : WQC	Input	First data records
PAC7QY	Tmp dir. : WQY	Input	Extension data
PAC7CP	Save dir. : PC.new	Output	Sequential image of the development Database
PAC7PD	Save dir. : PD.new	Output	Sequential image of the development Database
PAC7PY	Save dir. : PY.new	Output	Sequential image of the development Database
PAC7IE	User dir. : REORIE240	Report	Building of Logical database

## REOR - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *           - REORGANIZATION OF THE DATABASE -
REM *
REM * -----
REM *
REM * THE REOR PROCEDURE MAY BE USED IN TWO CASES:
REM * . WHEN PART OF THE DATA WAS DELETED BECAUSE OF A MAL-
REM * FUNCTION OR SYSTEM FAILURE, AND NO OTHER PROCEDURE CAN
REM * BE USED (IN PARTICULAR, DELETION OF THE AN INDEX FILE)
REM * . WHEN THE DATABASE IS TO BE PURGED OF THE FOLLOWING:
REM * - OBSOLETE LIBRARIES AND/OR SESSIONS;
REM * - ENTITIES NOT USED IN THE DATABASE;
REM *
REM * -----
REM *
<job id=REOR>

<script language="VBScript">

```

```

MyProc = "REOR"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTU2CL"))
'-----
'Example of Input File extracted from PACX/EXPU :
' Call BvpEnv("PTU2CL","PAC7MB",RepT_USR & "\PACXMR.txt")
' The first line must contain User/Password information
'With RepT_USR is Global User Directory.

WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7MB") = Fic Input
Call BvpEnv("PTU2CL","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU2CL","PAC7PU",Rep_TMP & "\WPU.tmp")
Call BvpEnv("PTU2CL","PAC7DD",Rep_USR & "\REORDD2CL.txt")
Call BvpEnv("PTU2CL","PAC7EE",Rep_USR & "\REOREE2CL.txt")
WshEnv("PAC7PC") = BVP_SvName & ""
Call RunCmdLog ("BVPTU2CL")
If Return = 4 Then
Call Msg_Log (Array("1057"))
End If
If Return = 8 Then
Call Msg_Log (Array("1028"))
End If
Call Err_Cod(Return , 0 , "PTU2CL")

Call Msg_Log (Array("1022" , "PTU200"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7PC") = BVP_SvName & ""
WshEnv("PAC7PY") = "NUL"
' WshEnv("PAC7PY") = BVP_SvName & "Y"
Call BvpEnv("PTU200","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU200","PAC7PR",Rep_TMP & "\WPR.tmp")
Call BvpEnv("PTU200","PAC7NX",Rep_TMP & "\WNX.tmp")
Call BvpEnv("PTU200","PAC7NY",Rep_TMP & "\WNY.tmp")
Call BvpEnv("PTU200","PAC7AU",Rep_TMP & "\WAU.tmp")
Call BvpEnv("PTU200","PAC7EE",Rep_USR & "\REOREE200.txt")
Call RunCmdLog ("BVPTU200")
If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
Call Err_Cod(Return , 0 , "PTU200")

Call Msg_Log (Array("1022" , "PTU205"))
'-----
Call BvpEnv("PTU205","PAC7PR",Rep_TMP & "\WPR.tmp")
Call BvpEnv("PTU205","PAC7RP",Rep_TMP & "\WRP.tmp")
Call RunCmdLog ("BVPTU205")
Call Err_Cod(Return , 0 , "PTU205")
'OK :
Call DelFile (Rep_TMP & "\WPR.tmp")

Call Msg_Log (Array("1022" , "PTU210"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
Call BvpEnv("PTU210","PAC7EB",Rep_USR & "\REOREB210.txt")
Call BvpEnv("PTU210","PAC7EE",Rep_USR & "\REOREE210.txt")

```

```

Call BvpEnv("PTU210","PAC7EK",Rep_USR & "\\REOREK210.txt")
Call BvpEnv("PTU210","PAC7BM",Rep_TMP & "\\WBM.tmp")
Call BvpEnv("PTU210","PAC7PR",Rep_TMP & "\\WRP.tmp")
Call BvpEnv("PTU210","PAC7PU",Rep_TMP & "\\WPU.tmp")
Call BvpEnv("PTU210","PAC7QS",Rep_TMP & "\\WQS.tmp")
Call BvpEnv("PTU210","PAC7UM",Rep_TMP & "\\WUM.tmp")
Call RunCmdLog ("BVPTU210")
If Return = 8 Then
Call Msg_Log (Array("1056"))
End If
If Return = 12 Then
Call Msg_Log (Array("1026"))
End If
Call Err_Cod(Return , 0 , "PTU210")
'OK :
Call DelFile (Rep_TMP & "\\WRP.tmp")
Call DelFile (Rep_TMP & "\\WPU.tmp")

Call Msg_Log (Array("1022" , "PTU220"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\\AE"
WshEnv("PACGGN") = Rep_ABASE & "\\AN"
WshEnv("PACGGR") = Rep_ABASE & "\\AR"
WshEnv("PACGGU") = Rep_ABASE & "\\GU"
Call BvpEnv("PTU220","PAC7BM",Rep_TMP & "\\WBM.tmp")
Call BvpEnv("PTU220","PAC7AN",Rep_TMP & "\\WAN.tmp")
Call BvpEnv("PTU220","PAC7MR",Rep_TMP & "\\WMR.tmp")
Call BvpEnv("PTU220","PAC7NX",Rep_TMP & "\\WNX.tmp")
Call BvpEnv("PTU220","PAC7PA",Rep_TMP & "\\WPA.tmp")
Call BvpEnv("PTU220","PAC7PB",Rep_TMP & "\\WPB.tmp")
Call BvpEnv("PTU220","PAC7PC",Rep_TMP & "\\WPC.tmp")
Call BvpEnv("PTU220","PAC7UM",Rep_TMP & "\\WUM.tmp")
Call BvpEnv("PTU220","PAC7UR",Rep_TMP & "\\WQS.tmp")
Call BvpEnv("PTU220","PAC7EE",Rep_USR & "\\REOREE220.txt")
Call RunCmdLog ("BVPTU220")
Call Err_Cod(Return , 0 , "PTU220")

Call Msg_Log (Array("1024"))
'-----
Call DelFile (Rep_TMP & "\\WUM.tmp")
Call DelFile (Rep_TMP & "\\WQS.tmp")

Call Msg_Log (Array("1022" , "PTU225"))
'-----
Call BvpEnv("PTU225","PAC7AN",Rep_TMP & "\\WAN.tmp")
Call BvpEnv("PTU225","PAC7NA",Rep_TMP & "\\WNA.tmp")
Call RunCmdLog ("BVPTU225")
Call Err_Cod(Return , 0 , "PTU225")

Call Msg_Log (Array("1024"))
'-----
Call DelFile (Rep_TMP & "\\WAN.tmp")

Call Msg_Log (Array("1022" , "PTU226"))
'-----
Call BvpEnv("PTU226","PAC7PA",Rep_TMP & "\\WPA.tmp")
Call BvpEnv("PTU226","PAC7PB",Rep_TMP & "\\WPB.tmp")
Call BvpEnv("PTU226","PAC7PC",Rep_TMP & "\\WPC.tmp")
Call BvpEnv("PTU226","PAC7QA",Rep_TMP & "\\WQA.tmp")
Call BvpEnv("PTU226","PAC7QB",Rep_TMP & "\\WQB.tmp")
Call BvpEnv("PTU226","PAC7QC",Rep_TMP & "\\WQC.tmp")
Call BvpEnv("PTU226","PAC7QY",Rep_TMP & "\\WQY.tmp")
Call BvpEnv("PTU226","PAC7NY",Rep_TMP & "\\WNY.tmp")
Call RunCmdLog ("BVPTU226")
Call Err_Cod(Return , 0 , "PTU226")

Call Msg_Log (Array("1024"))

```

```

'-----
Call DelFile (Rep_TMP & "\WPA.tmp")
Call DelFile (Rep_TMP & "\WPB.tmp")
Call DelFile (Rep_TMP & "\WPC.tmp")

Call Msg_Log (Array("1022" , "PTU240"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
Call BvpEnv("PTU240","PAC7AN",Rep_TMP & "\WNA.tmp")
Call BvpEnv("PTU240","PAC7AU",Rep_TMP & "\WAU.tmp")
Call BvpEnv("PTU240","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTU240","PAC7PA",Rep_TMP & "\WQA.tmp")
Call BvpEnv("PTU240","PAC7PB",Rep_TMP & "\WQB.tmp")
Call BvpEnv("PTU240","PAC7PC",Rep_TMP & "\WQC.tmp")
Call BvpEnv("PTU240","PAC7QY",Rep_TMP & "\WQY.tmp")
WshEnv("PAC7CP") = BVP_SvName & ".new"
WshEnv("PAC7PD") = BVP_SvName & "I.new"
WshEnv("PAC7PY") = BVP_SvName & "Y.new"
Call BvpEnv("PTU240","PAC7IE",Rep_USR & "\REORIE240.txt")
Call RunCmdLog ("BVPTU240")
Call Err_Cod(Return , 0 , "PTU240")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

If Return = 0 then
Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(BVP_SvName & "")
Call Turnover(BVP_SvName & "I")
Call Turnover(BVP_SvName & "Y")
End if

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## Chapter 4. Manager's Utilities

---

### PACX - Extractions

#### PACX - Introduction

The extraction procedure allows to perform various types of data extractions from the VA Pac Database via a PAF extractor (selection criteria).

See Chapter UPDP: Update from PAF extractions. This data is extracted in the form of transactions that can be used in input of the following procedures:

- UPDT
- UPDP
- CPSN (If the optional LCU Partitioned Database Manager utility is available.)

#### EXECUTION CONDITIONS

None since the Database is not directly updated by this procedure.

#### PACX - Input Common to Extractors

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
19	3	bbb	Extraction library code, or target Library code if RMEN with upload
22	4	nnnn	Session number (blank=current ses.)
26	1	T	Session status if Test session
29	4	cccc	Extractor code (1)
33	1	'1'	Formatting for UPDT
		'2'	CPSN : formatting for UPDT with explicit transaction codes
		' '	No formatting for UPDT
34	1	'1'	Formatting for UPDP (PAF)
		'2'	CPSN : formatting for UPDP with explicit transaction codes
		' '	No formatting for UPDP (PAF)
35	1	'1'	Formatting for CPSN
		' '	No formatting for CPSN
40	3	ppp	DSMS Product Code
43	6	nnnnnn	DSMS Change number (DSMS Function only)
49	1		Lock processing
		' '	Lock extraction: user code = '*'-line user code

Position	Length	Value	Meaning
		'1'	No lock extraction
		'2'	Lock extraction: user code = original user code
		'N'	For RMEN only : no extraction of locked entities by an other user
50	1	' '	No transfer of password
		'1'	Password transfer
69	3	bbb	Library code for the '*'-line of the output file(s) (For EXTR,EXLI, and EXUE only)
76	5	nnnnT	Session number for the '*'-line of the output file(s) (For EXTR,EXLI, and EXUE only)

(1) Possible values for the extractor code include:

- EXTR: Extraction of entities
- EXTA: Extraction of entities (extracted transactions are sorted, according to the input identification lines order. So if each request is preceded by a '\*' line, extracted transactions will be sorted in the order of the requests). The formatting is forced to UPDT.
- EXUE: Extraction of user entities

The following values are reserved for the Administrator:

- EXLI: Extraction of libraries or library sub-networks
- EXPJ: Extraction of Journal (formatting for CPSN is not possible)
- EXPU: Extraction for purge (formatting for CPSN is not possible)
- RMEN: Extraction of entities for upload/replacement/ recoding (formatting for CPSN is not possible). RMEN is subject to a separate purchase agreement.
- CPSN: comparison of sub-networks.

#### IMPORTANT

- One extractor type only for each run: If the procedure detects more than one type of extractors, it will take only the first one into account.
- Formatting for CPSN: This procedure is part of the ' LCU Partitioned Database Manager' optional utility. Its use is therefore subject to a separate purchase agreement.
- Maximum number of input '\*' lines : 1 for RMEN and EXPJ, 400 for EXSN, 1000 for EXTR, EXTA, EXUE et EXPU.

#### RESULTS

The PACX procedure produces:

- A report containing the list of executed programs and the number of generated transactions.
- A list of requests with possible associated errors.
- One or several execution reports depending on the type of extractor.



## Extraction of Archived Transactions

### EXPJ - Introduction:

The EXPJ procedure has a two-fold action:

- It converts the Journal file into update transactions with possible selection from a range of dates, sessions, libraries, etc.
- It prints out a listing of the contents of the archived Journal file, using the same criteria.

Its main purpose is to retrieve transactions associated with one database in order to update another database.

It is executed on the archived Journal file (PJ).

### EXECUTION CONDITIONS

Password transfer option ('\*-line col. 50 = 1):

. database access authorization level 4 is required.

### EXPJ - User Input:

User entry specific to this procedure and specifying the extraction characteristics.

Position	Length	Value	Meaning
2	1	'J'	Line code
3	1	'S'	Selection on session number
		'D'	Selection on date
4	1	' '	Chronological sort
		'N'	No chronological sort
5	1	' '	Sort by user
		'N'	No sort by user
6	1	' '	Sort by Library
		'N'	No sort by library
7	1	' '	Sort by session
		'N'	No sort by session
8	8	uuuuuuuu	User code for batch update
16	8	pppppppp	User password
24	4	dddd	Session number: beginning (if 'S')
28	4	ffff	Session number: end (if 'S')
32	8	CCYYMMDD	Date of beginning of select.(if 'D')
40	8	CCYYMMDD	Date of end of selection (if 'D')
48	1		Version of selected transactions
		' '	Selection of all sessions
		'Z'	Selection of current session
		'T'	Selection of frozen session
49	3	'bbb'	Code of selected library

Position	Length	Value	Meaning
52	5	'ssssT'	Selection of T-type session (test version of frozen session:'ssssT')
57	3	ppp	DSMS Product Code
60	6	nnnnnn	DSMS Change number (Selection by change number-DSMS)
66	6	HHMMSS	Starting time
72	6	HHMMSS	Ending time
80	1	'*'	If selection on user, indicates continuation line

Second user entry if selection on user code :

Position	Length	Value	Meaning
2	1	'J'	Line code
3	1	'*'	Indicates a following line
4	8	uuuuuuuu	User code

#### REPORTS

- The list of selection options used,
- The list of selected transactions, if requested.

#### RESULTS

In the case of a request for conversion of the Journal entries into transactions, the result of the EXPJ procedure is a sequential file containing all selected transactions.

### **Extraction of Libraries**

#### **EXLI - Introduction:**

The EXLI procedure extracts a complete library from the database and transforms it in transactions which are used in the update or comparison procedures.

The file obtained, according to its formatting, can be used as input to the UPDT, UPDP or CPSN procedures.

#### EXECUTION CONDITIONS

If DESIGN entities have been downloaded and have then been locked, they must be uploaded before the extraction to ensure data consistency.

#### **EXLI - User Input:**

No specific line, but as many '\*'-lines as there are libraries to be extracted in the sub-network.

#### PRINTED REPORT

The extractor prints:

- A list of extracted libraries with the number of records for each library,

- The details of records extracted for each library.

## **Extraction for Purge**

### **EXPU - Introduction:**

The EXPU utility purges: unused entities from a database, frozen sessions which have been logically cancelled, cancelled libraries, GP lines belonging to the users who no longer exist.

Several types of purges are possible:

- 'Logical' purge of entities which have become obsolete;
- 'Logical' purge of unused entities in a particular context;
- 'Physical' purge of entities which have never been used.

### TERMINOLOGY

- Final entities  
These are entities which are not used by other entities.
- Free-type cross-reference  
Reference whose existence does not prevent deletion of the Definition screen of the Entity on which it is dependent.

### PRINCIPLES

Logical purge: the EXPU procedure shows the list of entities which have not been used since an indicated frozen session and in a given context.

For these entities, the procedure generates logical deletion transactions of definition and description lines. These transactions can be used as input to the UPDT procedure.

For free-type entities, no deletion transaction is generated: only a message is printed in the report.

- Physical purge: the EXPU procedure gives the list of entities which have never been cross-referenced since they have been created in a given context. For these entities, physical purge transactions are generated. They can be used as input to the REOR procedure.

Limits of physical purge: if a data structure has already been purged, there is no physical purge possible for its segments.

- Purge of frozen sessions: the extraction for purge procedure indicates to the user the sessions which have been logically cancelled.  
For these sessions, physical-purge transactions are generated. They can be used as input to the reorganization procedure.
- Purge of libraries: the extraction for purge procedure indicates to the user the libraries which have been cancelled.  
For these libraries, physical-purge transactions are generated. They can be used as input to the reorganization procedure.
- Purge of GP lines: the extraction for purge procedure specifies to the user, the users who no longer exist in the administration database, despite the GP lines which still exist in the database.

For these users, physical-purge transactions are generated. They can be used as input to the reorganization procedure.

## EXECUTION CONDITIONS

None.

### **EXPU - User Input:**

One line with the extraction characteristics:

Position	Length	Value	Meaning
2	2	'P '	Line code
3	1		Purge of frozen sessions
		'S'	yes
		' '	no purge
4	1		Purge of libraries
		'B'	yes
		' '	No purge
5	1		Purge of GP lines for users who no longer exist
		'U'	yes
		' '	No purge
6	1		Purge of entities
		'P'	Physical (via the REOR procedure)
		'L'	Logical (via the UPDT/UPDP update)
		' '	No purge
7	1	t	Entity type
8	1	m	Print option for the last entity update: user code and date
9	1	s	Print option for the last session in which the entity is used
10	4	ssss	Session number (L type only) from which the entities should not be used in order to be logically purged
14	6	pppppp	Program code where the search stops if the programs are processed Information required if the entity type is 'P' or if it is blank

## COMMENTS

Each entity type may be processed separately. If there is no entity type entered, all the entities are processed except the final entities.

## COMMAND EXAMPLES

\*user\_\_\_\_passwordLIB

P\_\_\_\_PE1

Command for physical purge transactions for the data elements in the BIB library sub-network and printing of the last update (user and date).

\*user\_\_\_\_passwordLIB

P\_\_LP112222PROGR

Command for logical deletion transactions for the programs in the BIB library sub-network whose codes are less than or equal to PROGR, and no longer used since the 2222 session with the printing of the last update (user and date) and the last session of use.

\*user\_\_\_\_passwordLIB

PSBUP\_\_\_\_\_PROGR

Command for the physical purge transactions for all entities in the BIB library sub-network (except the final entities), for logically cancelled frozen sessions, for deleted libraries and GP lines of users who no longer exist.

### PRINTED REPORTS

This procedure prints out:

- the list of entities to be purged logically,
- the list of entities to be purged physically,
- the list of entities copied in the sub-network,
- the list of frozen sessions to be purged physically.
- the list of libraries to be purged physically.
- the list of users whom GP lines are to be purged physically.

### RESULT

The result of this procedure is:

- In the case of a logical purge, a sequential file containing entity deletion transactions to be used as input in the batch updating UPDT or UPDP procedures. These transactions are sorted as follows:
  - by decreasing hierarchical library level,
  - by library,
  - by record type: descriptions, definition screens.
- In the case of a physical purge, purge of frozen sessions, purge of libraries or GP lines, a sequential file of purge transactions to be used as input in the REOR procedure.

Each transaction contains an entity to be purged. For each entity, the following information is included:

- the type of entity,
- the entity code,
- the library code (see section 'Input Recommendations' in subchapter 'Database Reorganization').

## **Standardization Utility**

### **RMEN - Introduction:**

The RMEN procedure is an optional utility. It is subject to a separate purchase agreement.

Through this procedure you can:

- Rename an entity
- Replace an entity with another
- Move an entity to a higher-level library
- Rename and move up an entity simultaneously.

This procedure may be applied to the Dictionary and WorkStation entities.

Its output is a file containing update transactions, which will be used as input to the batch update procedure (UPDT or UPDP).

#### EXECUTION CONDITIONS

None, since the Database is not directly updated.

#### **RMEN - User Input:**

Several command lines per entity to be processed:

First line - concerned entity :

Position	Length	Value	Meaning
2	2	'W2'	Line code
4	2		Processing option:
		'MV'	Entity move (UP)
		'RN'	Entity rename
		'MR'	Upward move and rename
		'RP'	Entity replace
6	1	' '	Line type
7	3	ttt	Entity type or local code of a WorkStation entity: D, E, I, O, P, R, S, T, \$nn, Ynn,M Q, B, V, or DST, DEL ...
10	30	eeee..	Code of entity to be extracted

Second line - environment :

Position	Length	Value	Meaning
2	2	'W2'	Line code
4	2		Processing option - same as line 1
6	1	'E'	Line type
7	3	sss	Source library code (for MOVE)
10	3		For extraction of WorkStation entities: methodology code
		'//A'	SSADM
		'//M'	MERISE
		'//D'	YSM
		'//O'	OMT
		'//F'	IFW

Position	Length	Value	Meaning
13	3	'ALL'	for 'MV' and 'MR': Selects all occurrences of a UE or all Segments or Reports of a Data Structure (implicit option for 'RN' and 'RP')
16	6	rrrrrr	Parent Data Element code

Third line - new codes:

Position	Length	Value	Meaning
2	2	'W2'	Line code
4	2		Processing option - same as line 1
6	1	'N'	Line type
7	30	nnnn...	New entity code
37	8	gggggggg	For programs and screens, new generated code
45	6	cccccc	For programs, new sequencing code
51	8	eeeeeeee	For screens, new map code

Fourth line - selection for REPLACE:

Position	Length	Value	Meaning
2	2	'W2'	Line code
4	2	'RP'	'REPLACE'
6	1	'S'	Line type
7	3		REPLACE: Selection of the types of the entities to be modified
			'DEL': Data Element
			'DBD': Database Block
			'DST': Data Structure
			'SEG': Segment
			'RPT': Report
			'TXT': Text
			'VOL': PDM volume
			'PGM': Program
			'SCR': Screen
			'PIA': P.I.A.
			'MET': Methodology
			'CME': Client Meta-Entity
			'CRL': Client Relationship
			'\$tt': Client User Entity : (tt = type code)
			'\$**': All Client User Entities
			'Ytt': Extension User Entity : (tt = type code)

Position	Length	Value	Meaning
			'Y**': All Extension User Entities
10	30		REPLACE: Codes of entities to be modified (* may be used if you want to specify only the beginning of a code)

Lines for REPLACE (continuation lines for selection):

Position	Length	Value	Meaning
2	2	'W2'	Line code
4	2	'RP'	'REPLACE'
6	1	'*'	Line type
7	3		Selection of types of entities to be modified
10	30		Codes of entities to be modified

Last line (required):

Position	Length	Value	Meaning
2	2	'W2'	Line code
4	2		Processing option - same as line 1
6	1	'/'	Line type

#### REQUEST-SEQUENCING REQUIREMENTS

The sequencing of RMEN requests should follow a logical order.

Examples:

- A parent Data Element must be moved to the higher-level library before its child Data Element(s).
- When a Segment is called by another Segment, the called Segment must be moved to the higher-level library before the Segment that is calling it.
- When a macro-structure is called by a batch Program or on-line Screen, it must be moved into the higher-level library before this Program or Screen.

#### REQUEST-INPUT REQUIREMENTS

All input is required except:

- The source library code in case of entity renaming (RN) or replacing (RP),
- The new entity code in case of upward move (MV),
- The code of the parent data element (except when a child data element is to be associated with it).

The 'RP' processing type is incompatible with the other processing types.

#### EXECUTION CONDITIONS

The source library must belong to the sub-network of the target library.



When an upward move is requested for an entity which already exists in the target library, a warning message appears in the report, but the transaction is still generated.

#### PRINTED REPORT

This procedure prints out the following:

- The list of entities processed by RMEN.
- The number of lines extracted for each request.

#### RESULT

The output is a sequential file which contains update transactions:

- Creation or modification transactions sorted by:
  - Ascending library hierarchical level,
  - Library,
  - Record type (uses, definition, or description).
- Deletion transactions sorted by:
  - Descending library hierarchical level,
  - Library,
  - Record type (uses, description, definition).

#### NOTE

The replacement of entities (RP) does not ensure data consistency.

Example: if you replace a Data Element with another one in a Segment, RMEN does not modify the program lines where this Data Element is used by this Segment, except if you have requested the replacement in programs.

New occurrence codes longer than the initial ones may sometimes cause update transactions to be truncated. However, they will still belong to the flow of update transactions, but will also appear in the validation report with a warning message.

**WARNING:** If not correctly managed, the RMEN procedure may have undesired effects on the Database. Caution is highly recommended when requesting its execution.

#### **RMEN - Recommendations and Restrictions:**

Processing in a frozen session is possible. The number of the session is indicated on the '\*' line.

When an error is detected on the '\*' line, the request flow is not processed.

Only one '\*' line is authorized.

#### ALL ENTITY TYPES

The MOVE+RENAME (MR) command first moves and then renames. The consequence is that all the entities bearing the same code within the sub-network of libraries equal to or lower than the target library are renamed by the RMEN procedure.

If this result is not satisfactory, it is advised to first run a RMEN/RENAME followed by a UPDT, then a RMEN/MOVE followed by another UPDT execution.

If the entity uses other entities, these used entities must exist in a library whose level is greater than or equal to that of the target library.

When an occurrence is renamed, if it is called on Assigned Text (-AT) lines,

- it is changed on I-type lines,
- it is not changed on J-type lines.

### DATA STRUCTURES

Renaming a Data Structure causes the renaming of all its Segments.

**WARNING:** an upward move of a Data Structure involves the upward move of all of its Segments contained in the source library in cases where the 'global upward move' field contains 'ALL'. If this field is blank, the Segments remain in the source library.

The existence of the Data Structure in an upper-level library is checked.

### SEGMENTS

These entities can only be moved upward. Their Data Structure must exist in a library whose level is higher than or equal to that of the target library.

The existence of a Segment in a library whose level is higher than or equal to that of the target library is checked, as is that of called Segments, Data Elements, and MERISE Objects and Relationships.

### REPORTS

It is not possible to change a single report code or to replace a single report. It is however possible to perform an upward move of a single report.

However, you can rename, move upward or replace all the reports with the same prefixes (two first characters), you just need to enter '\*' in the third character place:

W2RN R xx\*

or W2MV R xx\*

or W2MR R xx\*

or W2RP R xx\*

An existence validation is performed in a library upper or equal to the target library for the called data elements only.

### DATA ELEMENTS

The indication of a parent Data Element code affects only the Data Element Definition in the source library. By default, a child Data Element remains attached to its parent. However, it is possible to suppress this link by entering the code '&&&&&&' in the parent Data Element field.

A child Data Element can be turned into a parent Data Element or may be assigned another parent by specifying a parent Data Element code. This parent Data Element must be defined in a library whose level is greater than or equal to the target library.

A parent Data Element contained in a request must not have been previously processed as a source Element.

The format of the Data Element being moved remains the same, whatever the modification in relation to a parent Data Element.

If the target Data Element is used as an undefined Data Element, the format of its uses (on Segment or Report '-CE' screens) must correspond to the format specified in the Definition.

The renaming of a key Data Element of a Data Structure (indicated as an argument on the Call of Data Structures '-CD' screen) is not allowed.

### PROGRAMS

Their processing goes through a check on libraries whose level is higher than or equal to that of the target library of the:

- called Macro-Structures,
- called Data Structures,
- Segments or Data Elements called in WORKING-STORAGE.

### SCREENS

Screens are processed individually. RMEN does not process the whole Dialogue. The Dialogue must therefore exist in a library whose level is higher than or equal to that of the target library.

### META-ENTITIES

A Meta-entity can be processed only if there is no other meta-entity bearing the same call code in the sub-network of the target library.

**WARNING:** when the global upward move field contains 'ALL', an upward move of a Meta Entity involves the upward move of all of its User Entities contained in the source library. If this field is blank, the User Entities remain in the source library.

The existence of all Data Elements and User Relations called in the Definition lines is checked in a library whose level is higher than or equal to the target library.

### USER ENTITIES

The existence of the Meta-entity in a library higher or equal to that of the target library is checked, as is that of occurrences linked to the User Entities or details lines.

### MERISE ENTITIES

For MERISE Objects and Properties called in description lines, an existence check is performed in the library whose level is higher than or equal to that of the target library.

#### DATABASE BLOCKS

The existence of MERISE objects or called segments is checked.

#### VOLUMES

The existence of Reports called in the Volume Definition screen is checked.

#### THE WORKSTATION ENTITIES

Calls of the '//A', '//M', '//D', '//O' and '//F' type are used to extract all the WorkStation entities. The local entity type must be entered (in the entity type field) as well as the code of entity before processing, the library code and the code of the entity after processing.

The WorkStation methodology (MERISE, IFW, OMT, YSM...) is entered in a special field at position 10 in the command line corresponding to the environment (line type : 'E').

**WARNING:** one procedure execution can process occurrences related to only one Methodology.

### **Sub-Network and Entities Comparison**

#### **CPSN - Introduction:**

The Sub-Network Comparison procedure (CPSN) compares the images of two sub-networks extracted by the PACX procedure (EXLI extractor, formatting for CPSN), which may or may not belong to the same network, or the images of entities extracted by the PACX procedure (EXTR or EXUE extractor, formatting for CPSN), in order to obtain the batch update transactions which will align the 'slave' sub-network or entities with the 'master' sub-network or entities.

- 'Master' sub-network = reference sub-network,
- 'Slave' sub-network = sub-network to align with the Master entity.
- 'Master' entity = reference entity,
- 'Slave' entity = entity to align with the reference entity

#### EXECUTION CONDITION

None.

#### ABNORMAL EXECUTIONS

If an abend occurs, the procedure can be restarted as it is once the problem has been solved.

#### **CPSN - User Input:**

No specific line.

#### NOTE

The sub-networks or entities to be compared must have been extracted via the PACX procedure (EXLI, EXTR or EXUE extractor; formatting for CPSN).

They must contain the same number of libraries (checked by the system) and have the same structure.

## PACX - Description of Steps

### EXTRACTION: PACX

This step extracts transactions according to user input.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Base dir. : AN	Input	Development Database Index file
PAC7AR	Base dir. : AR	Input	Development Database Data file
PAC7AY	Base dir. : AY	Input	Development Database Extension Data
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database Index file
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database Data file
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database Users
PAC7PJ	Save dir.: PJ	Input	Archived transactions
PAC7MB	User input	Input	User input
PAC7MA	nul	Input	CPSN Master file
PAC7ES	nul	Input	CPSN Slave file
PAC7BM	Tmp dir.: WBM	Input/Output	User input
PAC7MM	Tmp dir.: WMM	Input/Output	EXPU Work file
PAC7MJ	Tmp dir.: WMJ	Input/Output	EXPJ Work file
PAC7TE	Tmp dir.: WTE	Input/Output	RMEN Work file
PAC7RE	Tmp dir.: WRE	Input/Output	RMEN Work file
PAC7RM	Tmp dir.: WRM	Input/Output	RMEN Work file
PAC7WD	Tmp dir.: WWD	Input/Output	Extracted transactions
SYSEXT	Tmp dir.: WSY	Input/Output	Indexed Work File
PAC7MV	User dir.: PACXMV	Output	Extracted transactions for UPDT
PAC7MR	User dir.: PACXMR	Output	Extracted transactions for REOR (EXPU)
PAC7MX	User dir.: PACMX	Output	Non extracted entities (PACX)
PAC7GY	User dir.: PACXGY	Output	Extracted transactions for UPDP
PAC7TD	User dir.: PACXTD	Output	Extracted transactions for CPSN
PAC7UE	User dir.: PACXUE	Output	Extracted transactions for EXUE
PAC7IA	User dir.: PACXIA	Report	General printout of the program stream
PAC7DD	User dir.: PACXDD	Report	Errors on input transactions
PAC7ED	User dir.: PACXED	Report	Extractions report

Code	Physical name	Type	Label
PAC7EE	User dir.: PACXEE	Report	Extractions report
PAC7EG	User dir.: PACXEG	Report	Extractions report
PAC7EM	User dir.: PACXEM	Report	Extractions report
PAC7EP	User dir.: PACXEP	Report	Extractions report
PAC7EQ	User dir.: PACXEQ	Report	Extractions report
PAC7EU	User dir.: PACXEU	Report	Extractions report
PAC7EZ	User dir.: PACXEZ	Report	Extractions report

Return codes:

- 0: No error
- 4: Error on user input (detailed in PAC7EE) or on the extractions for EXTR/EXUE (detailed in PAC7EZ)
- 8: Error on '\*' line (detailed in PAC7DD) or in EXLI (Database not available)

## PACX - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *           - EXTR:EXTRACTIONS FROM DATABASE -
REM *           - EXUE:EXTRACTIONS COMPARATOR   -
REM * -----
REM *
REM * THE PACX PROCEDURE ALLOWS TO PERFORM VARIOUS TYPES
REM * OF DATA EXTRACTIONS FROM THE DEVELOPMENT DATABASE
REM * VIA PAF EXTRACTOR.
REM *
REM * POSSIBLE VALUES FOR THE EXTRACTOR CODE INCLUDE:
REM * - EXTR: EXTRACTION OF ENTITIES
REM * - EXTA: EXTRACTION OF ENTITIES (EXTRACTED TRANSACTIONS
REM *       ARE SORTED, ACCORDING TO THE INPUT
REM *       IDENTIFICATION LINES ORDER.
REM *       EACH REQUEST IS THUS PRECEDED BY A '*' LINE,
REM *       EXTRACTED TRANSACTIONS WILL BE SORTED IN THE
REM *       REQUEST ORDER).
REM * - EXUE: EXTRACTION OF USER ENTITIES
REM * FOLLOWING VALUES ARE RESERVED FOR THE ADMINISTRATOR:
REM * - EXLI:EXTRACTION OF LIBRARIES OR LIBRARY SUB-NETWORKS
REM * - EXPJ:EXTRACTION OF JOURNAL (FORMATTING FOR CPSN IS
REM *       NOT POSSIBLE)
REM * - EXPU:EXTRACTION OF ENTITIES TO BE PURGED
REM *       (FORMATTING FOR CPSN IS NOT POSSIBLE)
REM * - RMEN:EXTRACTION OF ENTITIES FOR UPLOAD/REPLACEMENT/
REM *       RECODING (FORMATTING FOR CPSN IS NOT POSSIBLE).
REM *       RMEN IS SUBJECT TO A SEPARATE PURCHASE AGREEMENT
REM * - CPSN:COMPARISON OF SUB-NETWORKS.
REM *
REM * -----
REM *
<job id=PACX>

<script language="VBScript">
MyProc = "PACX"
</script>

<script language="VBScript" src="INIT.vbs"/>

```

```

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PACX"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7PJ") = Rep_SAVE & "\PJ"
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PACX","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PACX","PAC7WD",Rep_TMP & "\WWD.tmp")
Call BvpEnv("PACX","PAC7MM",Rep_TMP & "\WMM.tmp")
Call BvpEnv("PACX","PAC7MJ",Rep_TMP & "\WMJ.tmp")
Call BvpEnv("PACX","PAC7TE",Rep_TMP & "\WTE.tmp")
Call BvpEnv("PACX","PAC7RE",Rep_TMP & "\WRE.tmp")
Call BvpEnv("PACX","PAC7RM",Rep_TMP & "\WRM.tmp")
WshEnv("PAC7MA") = "NUL"
WshEnv("PAC7ES") = "NUL"

'Example of Output File reuse in next procedure :
' Call BvpEnv("PACX","PAC7xx",RepT_USR & "\PACXxx.txt")
'With RepT_USR is Global User Directory.

'One for each procedure : Rep_USR & "\PACXxx.txt"
'One for all the procedure : RepT_USR & "\PACXxx.txt"

'Call BvpEnv("PACX","PAC7UE",Rep_USR & "\PACXUE.txt")
Call BvpEnv("PACX","PAC7UE",RepT_USR & "\PACXUE.txt")

'Call BvpEnv("PACX","PAC7GY",Rep_USR & "\PACXGY.txt")
Call BvpEnv("PACX","PAC7GY",RepT_USR & "\PACXGY.txt")

'Call BvpEnv("PACX","PAC7TD",Rep_USR & "\PACXTD.txt")
Call BvpEnv("PACX","PAC7TD",RepT_USR & "\PACXTD.txt")

'Call BvpEnv("PACX","PAC7MV",Rep_USR & "\PACXMV.txt")
Call BvpEnv("PACX","PAC7MV",RepT_USR & "\PACXMV.txt")

'Call BvpEnv("PACX","PAC7MR",Rep_USR & "\PACXMR.txt")
Call BvpEnv("PACX","PAC7MR",RepT_USR & "\PACXMR.txt")

'Call BvpEnv("PACX","PAC7MX",Rep_USR & "\PACXMX.txt")
Call BvpEnv("PACX","PAC7MX",RepT_USR & "\PACXMX.txt")

Call BvpEnv("PACX","PAC7IA",Rep_USR & "\PACXIA.txt")
Call BvpEnv("PACX","PAC7DD",Rep_USR & "\PACXDD.txt")
Call BvpEnv("PACX","PAC7ED",Rep_USR & "\PACXED.txt")
Call BvpEnv("PACX","PAC7EE",Rep_USR & "\PACXEE.txt")
Call BvpEnv("PACX","PAC7EG",Rep_USR & "\PACXEG.txt")
Call BvpEnv("PACX","PAC7EM",Rep_USR & "\PACXEM.txt")
Call BvpEnv("PACX","PAC7EP",Rep_USR & "\PACXEP.txt")
Call BvpEnv("PACX","PAC7EQ",Rep_USR & "\PACXEQ.txt")
Call BvpEnv("PACX","PAC7EU",Rep_USR & "\PACXEU.txt")
Call BvpEnv("PACX","PAC7EZ",Rep_USR & "\PACXEZ.txt")

Call BvpEnv("PACX","SYSEXT",Rep_TMP & "\WSY.tmp")
Call RunCmdLog ("BVPACX")
Call Err_Cod(Return , 4 , "PACX")

Call Msg_Log (Array("1024"))
'-----

```

```

Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## Session Management

### Introduction

The VA Pac session number cannot be greater than 9999. When the session number is close to 9999, the utility program re-assigns all the session numbers by incrementing the numbers of frozen sessions by 1 (starting from session 0001 or from a session chosen by the Administrator).

The utility consists in two procedures: the ESES preparation procedure and CSES compression procedure.

#### NOTE

The session freeze is performed by the UPDT procedure. It increments the current session number.

This reassignment is carried out on sequential images of the files that include the session number, i.e. the backup files of the Database (PC), of the Journal (PJ), of the DSMS Journal (BJ), of the DSMS Database (BB), and of the Pactables Database (TC).

This utility includes two procedures: ESES and CSES.

## ESES - Session Numbers Extraction

### **ESES - Introduction**

The Extraction of Session Numbers procedure (ESES) creates a correspondence-table file linking older frozen sessions and new frozen sessions.

#### PRELIMINARY OPERATIONS

Backup of the VA Pac files:

- Archival of the Journal (ARCH)
- Backup of the VA Pac Database (PACS with SAVE option)

If Pactables is installed:

- Table backup (SVTA)

If DSMS is installed, perform a backup of the DSMS environment, by:

- Archiving the DSMS Journal (DARC)
- Backing up the DSMS Database (DSAV)

#### EXECUTION CONDITIONS

None.



## ESES - User Input

A '\*' line with User code and Password is required.

One line (optional) per session number to force :

Position	Length	Value	Meaning
2	1	'S'	Line Code
3	4	nnnn	Original session number
7	4	nnnn	New session number

## ESES - Description of Steps

CREATION OF THE SESSION MATCHING FILE: PTUESS

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AN	Base dir. : AN	Input	Development Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7MB	User input	Input	Input transactions
PAC7MV	User dir. : MVESES	Output	Session-number correspondence table
PAC7EU	User dir. : ESESEUCSS	Report	Extraction report
PAC7DD	User dir. : ESESDDCSS	Report	Batch procedure authorization option

Return codes:

- 8: No authorization for this procedure.

## ESES - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - SESSION NUMBERS CORRESPONDENCE TABLE -
REM *
REM * -----
REM *
REM * THE EXTRACTION OF SESSION NUMBERS PROCEDURE
REM * (ESES) CREATES A CORRESPONDENCE-TABLE FILE LINKING
REM * OLDER FROZEN SESSIONS AND NEW FROZEN SESSIONS.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM * - COMMAND LINE :
REM * COL 2  : 'S'    LINE CODE
REM * COL 3  : (4 N) ORIGINAL SESSION NUMBER
REM * COL 7  : (4 N) NEW SESSION NUMBER
REM * -----
REM *
<job id=ESES>

<script language="VBScript">

```

```

MyProc = "ESES"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUESS"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PTUESS","PAC7MV",RepT_USR & "\Mveses.txt")
Call BvpEnv("PTUESS","PAC7DD",Rep_USR & "\ESESDEESS.txt")
Call BvpEnv("PTUESS","PAC7EU",Rep_USR & "\ESESEUESS.txt")
Return = WshShell.Run("BVPTUESS.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUESS")

Call Msg_Log (Array("1023"))
'-----
Call DeleteFldr (Rep_TMP)
Wscript.Quit (Return)

</script>
</job>

```

## CSES - Compression of Session Numbers

### CSES - Introduction

The Compression of Session Numbers procedure (CSES) compresses the session numbers of the development Database logical backups, the Pactables Database if this module is installed on the site, and the DSMS Database if this module is installed on the site. It uses the correspondence table created by the ESES procedure.

The resulting files must be restored.

### EXECUTION CONDITIONS

None.

Yet, all the backups to be processed must be valid.

### CSES - User Input

A \* line with User Code and Password.

The user input is used to indicate the list of files to be retrieved (PC, PJ, BB, BJ, and TC), in order to execute the retrieval after one or several runs.

The line is built as follows:

Position	Length	Value	Meaning
2	1	'S'	Line code

Position	Length	Value	Meaning
3	21		Code of the files to retrieve (PC PJ BB BJ TC) separated with a blank
33	4		If the DSMS database has to be retrieved: development Database logical code

### CSES - Description of Steps

#### COMPRESSION OF SESSION NUMBERS: PTUCSS

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7MV	nul	Input	Session numbers correspondence table
PAC7MB	User input	Input	Parameter line
PAC7PC	Save dir. : PC	Input	Development Database backup
PAC7PD	Save dir. : PCI	Input	If Dispatch option of the backup: Backup 2 of the development Database
PAC7PY	Save dir. : PCY	Input	If Dispatch option of the backup: Backup 3 of the development Database
PAC7CP	Save dir. : PC.new	Output	If Dispatch option of the backup:
PAC7DP	Save dir. : PCI.new	Output	If Dispatch option of the backup: Backup 2 of the development Database
PAC7YP	Save dir. : PCY.new	Output	If Dispatch option of the backup: Backup 3 of the development Database
PAC7PJ	Save dir. : PJ	Input	Backup of the development Database Journal
PAC7JP	Save dir. : PJ.new	Output	Backup of the development Database Journal
PACDBB	Base dir. DSMS : BB	Input	DSMS Database backup (if DSMS is installed)
PACDJB	Base dir. DSMS : BB.new	Output	DSMS Database backup (if DSMS is installed)
PACDDJ	Base dir. DSMS : BJ	Input	Retrieval of DSMS archived Journal (if DSMS is installed)
PAC7JD	Base dir. DSMS : BJ.new	Output	Retrieval of DSMS archived Journal (if DSMS is installed)
PACDTC	Save dir. : TC	Input	Retrieval of Pactables backup (if Pactables is installed)
PACDCT	Save dir. : TC.new	Output	Retrieval of Pactables backup (if Pactables is installed)
PAC7EU	User dir. : CSESEUCSS	Report	Execution output

Code	Physical name	Type	Label
PAC7DD	User dir. : CSESDDCSS	Report	Batch procedure authorization option

## CSES - Execution Script

```

REM * -----
REM *          VISUALAGE PACBASE
REM *
REM * -----
REM *          - COMPRESSION OF SESSION NUMBERS -
REM *
REM * -----
REM *
REM * THE COMPRESSION OF SESSION NUMBERS PROCEDURE (CSES)
REM * COMPRESSES THE SESSION NUMBERS OF THE DEVELOPMENT
REM * DATABASE LOGICAL BACKUPS, THE PACTABLES DATABASE IF
REM * THIS MODULE IS INSTALLED ON THE SITE, AND THE DSMS DATA
REM * BASE IF THIS MODULE IS INSTALLED ON THE SITE. IT USES
REM * THE CORRESPONDENCE TABLE CREATED BY THE ESES PROCEDURE.
REM * THE RESULTING FILES MUST BE RESTORED.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM * - COMMAND LINE :
REM * COL 2  : 'S'          LINE CODE
REM * COL 3  : (21 CAR.)  CODE OF THE FILES TO RETRIEVE (PC
REM *          PJ BB BJ TC) SEPARATED WITH A BLANK
REM * COL 33 : (4 CAR.)  IF THE DSMS DATABASE HAS TO BE
REM *          RETRIEVED : DEVELOPMENT DATABASE LOGICAL CODE
REM * -----
REM *
<job id=CSES>

<script language="VBScript">
MyProc = "CSES"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUCSS"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7MB") = Fic_Input
If FSO.FileExists(RepT_USR & "\Mveses.txt") Then
WshEnv("PAC7MV") = RepT_USR & "\Mveses.txt"
Else
Call Msg_Log (Array("1001" , RepT_USR & "\Mveses.txt"))
c_error = 1
WshVolEnv("RC") = 32
WshEnv("PAC7MV") = "NUL"
End If
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7PC") = Rep_SAVE & "\PC"
WshEnv("PAC7CP") = Rep_SAVE & "\PC.NEW"
WshEnv("PAC7PD") = Rep_SAVE & "\PCI"
WshEnv("PAC7DP") = Rep_SAVE & "\PCI.NEW"
WshEnv("PAC7PY") = Rep_SAVE & "\PCY"
WshEnv("PAC7YP") = Rep_SAVE & "\PCY.NEW"

```

```

WshEnv("PAC7PJ") = Rep_SAVE & "\PJ"
WshEnv("PAC7JP") = Rep_SAVE & "\PJ.NEW"
WshEnv("PACDBB") = Rep_SAVE & "\BB"
WshEnv("PACDJB") = Rep_SAVE & "\BB.NEW"
WshEnv("PACDDJ") = Rep_SAVE & "\BJ"
WshEnv("PACDJD") = Rep_SAVE & "\BJ.NEW"
WshEnv("PAC7TC") = Rep_SAVE & "\TC"
WshEnv("PAC7CT") = Rep_SAVE & "\TC.NEW"
Call BvpEnv("PTUCSS","PAC7DD",Rep_USR & "\CSESDDCSS.txt")
Call BvpEnv("PTUCSS","PAC7EU",Rep_USR & "\CSESEUCSS.txt")
Return = WshShell.Run("BVPTUCSS.exe" , 1, TRUE)
If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
Call Err_Cod(Return , 0 , "PTUCSS")

If Return = 0 and c_error = 0 then
Call Msg_Log (Array("1022" , "BACKUP"))
'-----
Call Turnover(Rep_SAVE & "\PC")
Call Turnover(Rep_SAVE & "\PJ")
Call Turnover(Rep_SAVE & "\BB")
Call Turnover(Rep_SAVE & "\BJ")
Call Turnover(Rep_SAVE & "\TC")
End If

Call Msg_Log (Array("1023"))
'-----
Call DeleteFldr (Rep_TMP)
Wscript.Quit (Return)

</script>
</job>

```

---

## Database statistics

### STAT - Introduction

This procedure creates, from the files ouptput by the save procedure, a sequential file which can be used to calculate statistics.

#### Execution Condition

None.

#### Output Result

This procedure outputs a sequential file whose records are 100 character-long and whose contents are:

- a global record:

Pos.	Len.	Format/Value	Meaning
9	10	'GLOBAL '	Constant
19	3	9(3)	Number of libraries
22	8	9(8)	Index: number of records
30	8	9(8)	Index number of deleted records
38	8	9(8)	Data: number of records (gaps + data)
46	8	9(8)	Data: number of deleted records

Pos.	Len.	Format/Value	Meaning
54	8	9(8)	Data: number of 'gap' records
62	8	9(8)	Data: number of 'data' records
70	8	9(8)	Data: number of records in frozen sessions
78	8	9(8)	Data: number of records in current sessions
86	8	9(8)	Container: number of records

- One or more records per library which has lower-level libraries:

Pos.	Len.	Format/Value	Meaning
1	3	X(3)	Library code
9	6	'LIBINF'	Constant (BIBINF for a French database)
16	2	X(2)	First record: ' ' Next records: 01, 02, 03, etc ...
19	81		Table containing 27 items (3-character long) which represent lower-level libraries

- One or more records per library which has higher-level libraries:

Pos.	Len.	Format/Value	Meaning
1	3	X(3)	Library code
9	6	'LIBSUP'	Constant (BIBSUP for a French database)
16	2	X(2)	First record: ' ' Next records: 01, 02, 03, etc ...
19	81		Table containing 27 items (3-character long) which represent higher-level libraries

- One record per library/session/line type:

Pos.	Len.	Format/Value	Meaning
1	3	X(3)	Library code
9	10	X(10)	Line type
19	8	9(8)	Number of data items
27	8	9(8)	Number of deleted data items

The line type corresponds to the PAF table code. The following codes have been added:

- \$ttDSC/YttDSC: User Entity description, tt being the call type (each description type is not detailed),
- xxxLOCKS: locks and timestamps, xxx being the entity type: TXT, DEL,... (xxxBLOCAGE for a French Database),
- xxxKWD: keywords, xxx being the entity type: TXT, DEL, ... (xxxMCL pour base non française),
- LONGV3: Long data attached to comments (-GC), generation elements (-GG), generation options (-GO) and error messages lines (-GE),
- LONG4: Long data attached to the layout lines of Reports,
- LONGY3: Long data attached to the User Entity Definition,
- LONGY4: Long data attached to the User Entity Descriptions.

## STAT - User input

A '\*' line with the user code and password.

## STAT - Description of steps

Formatting of the sequential file: PTUSTA

Code	Physical Name	Type	Name
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7PC	Save dir. : PC.new	Input	Sequential image of the Development Database
PAC7PD	Save dir. : PD.new	Input	If Dipatch option in the save procedure: Sequential image 2 of the network
PAC7PY	Save dir. : PY.new	Input	If Dipatch option in the save procedure: Sequential image 3 of the network
PAC7MB	User input	Input	User transactions
PAC7ST	Tmp dir. : WST	Output	Output file (length= 100)
PAC7DD	User dir. : STATDD	Report	Execution report

## STAT - Execution JCL

```
REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      GENERATE DATABASE STATISTICS
REM *
REM * -----
REM *
<job id=STAT>

<script language="VBScript">
Dim MyProc
MyProc = "STAT"
</script>
<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUSTA"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
Call BvpEnv("PTUSTA","PAC7DD",Rep_USR & "\STATDD.txt")
Call BvpEnv("PTUSTA","PAC7ST",Rep_TMP & "\WST.tmp")
```

```
WshEnv("PAC7PC") = Rep_SAVE & "\\PC"
WshEnv("PAC7PD") = Rep_SAVE & "\\PCI"
WshEnv("PAC7PY") = Rep_SAVE & "\\PCY"
Call RunCmdLog ("BVPTUSTA")
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PTUSTA")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
WshVolEnv("RC") = Return
Wscript.Quit (Return)

</script>
</job>
```



---

## Chapter 5. Analysis of Activity and Quality Control

---

### Analysis of Activity

#### ACTI - Introduction

The ACTI procedure is an optional utility, and its use depends on the corresponding purchase agreement.

The Specifications Dictionary manages all the data related to the various applications being developed or maintained at the site.

The Journal file contains all the database update transactions. As such, it reflects user activity.

With the Journal Statistics Utility (ACTI), this activity can be monitored and presented in the form of charts.

The Journal Statistics Utility allows the Database Manager to query the Journal backup file based on various parameters:

- library code,
- user code,
- entity type,
- entity code,
- line code,
- transaction type,
- date of update,
- time of update,
- session number of update,
- transaction code,
- change number.

These criteria are used to specify the REQUEST AREA.

Results are obtained in the form of three types of charts, i.e., statistical reports, curve-type graphs, or lists of transactions.

This output will be printed according to the selected PAGE LAYOUT. Statistics and graphs are sorted and calculated according to the user request.

- Output Report Type,
- page layout criteria,
- Request Area,
- Data sequencing mode,
- Activity calculation mode.

#### EXECUTION CONDITIONS

None.

## ACTI - Query Language

### REQUEST CODING

A Journal Statistics Request consists of five different types of lines, identified by the following KEYWORDS:

- Output : Output Report Type,
- Page : Page Layout (page breaks),
- Area : Request Area,
- Line : Statistical Report Lines,
- Column : Statistical Report Columns,
- Abscissa : Curve-type graph Abscissas,
- Ordinate : Curve-type graph Ordinates.

The meaning of the keywords, the parameters which define them, as well as their compatibility are explained in paragraph 'Keywords definitions and values'.

The Output line is required; the Page and Area lines are optional. The Line, Column, Abscissa, and Ordinate lines are either required or prohibited, depending on the requested output report type.

Only the first three characters of a keyword are used to identify a line type.

On the printed report, each request line is explicitly stated on the first page and an explicit error message is generated in case of a rejected line.

Request lines must be entered in the following order:

Output Page Area Line Column Abscissa Ordinate

Any error in this sequence will be considered as the beginning of another request.

The user may enter up to 10 requests at the same time.

The purpose of the ':' character is to mark the end of the keyword.

The rest of the line contains the parameters of each characteristic.

### PARAMETERS

Parameters are used to define page layouts, lines and abscissas. These are called 'Presentation Criteria'.

Parameters followed by '=' and a value are called 'Selection Criteria'.

Parameters which define calculations are called 'Calculations'.

The coding, meaning and compatibility of the parameters are described in paragraph 'Parameters: definition and comments'.

### SEPARATORS

The data entered on request lines are separated and grouped together using the following characters:

- ':' = end of keyword,

- '=' = link between a parameter and its value,
- '(' )' = set of parameters for calculations,
- ',' = parameter or calculation separator,
- '/' = calculation combination,
- '\*' = generic selection,
- 'Blank' = end of line (subsequent data is entered for documentary purposes).

#### KEYWORDS: MEANING AND FILLING MODES

OUT(put) : Output report type

This type of line is required at the beginning of each request.

The parameters used to define the output report type are:

- STA for statistics
- GRA for graph
- LIS for list

PAG(es) : Page layout

This type of line is used to indicate at which level a page skip is to be inserted.

The Page layout line is optional.

Headings are printed for each level, as well as totals for the statistical reports.

The page layout is defined by a series of parameters (three maximum separated by the ',' character) identifying data from the Journal, and called 'presentation criteria'.

Example: A page skip may be requested for each user and for each library.

ARE(a) : Request area

This type of line is used to define the transactions to be taken into account.

The REQUEST AREA line is optional.

The Request Area is defined by parameters (separated by the ',' character) followed by the '=' character and the selected value.

Example: The request applies to only some users and for a given period of time.

LIN(es) : Data sorting mode

or

ABS(cissa)

This type of line is used to define either the lines of a statistical report or the X-axis of a curve-type graph.

It is required for both statistical reports and curve-type graphs. However, it is not permitted for transaction lists.

There may be several lines of this type for statistical report.

The Data Sorting Mode may be defined by Presentation Criteria, as well as Selection Criteria. Parameters and values are separated by the ',' character.

Example: Data is sorted by entity type for a statistical report, or by week for for a curve-type graph.

COL(umns) : Activity calculation mode

or

ORD(inate)

This type of line defines the columns of a statistical report or the ordinates of a curve-type graph (maximum of seven columns or curves).

It is required for both statistical reports and curve-type graphs. However, it is not permitted for transaction lists.

Each column or curve is determined by a calculation, followed by bracketed Selection Criteria. Columns or curves, parameters and values, are all separated by the ',' character.

A printing character (&Cn\*dofHAR='X') must be specified for each curve.

A statistical report column may be defined by the relationship between two calculations; these calculations are separated by the '/' character.

Example: A first column or a first curve may be a calculation of the transactions entered on-line, while a second one may show the ratio between the input transactions and the real transactions.

#### PARAMETERS: DEFINITION AND COMMENTS

&LIB : Library code

This parameter is used as a Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

A generic selection may be requested by simply replacing every appropriate character by the '\*' character.

&USER : User code

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

A generic selection may be requested by simply replacing every appropriate character by the '\*' character.

&ENTG : Entity type

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

&ENTD : Line code / Entity type

This parameter is used as a Presentation and Selection Criterion to define the Data Sorting Mode.

Values are selected according to the entity type entered in the preceding parameter.

&LICO : Line code

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and Activity Calculation Mode.

Values are selected according to the batch line codes.

&ENT : Entity code

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

A generic selection may be requested by simply replacing every appropriate character by the '\*' character.

Values are selected according to the entity type and code.

&INPT : Input type

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

The value 'B' corresponds to batch input mode; any other value corresponds to on-line input mode.

&D1 : Starting date

This parameter is used as a Selection Criterion to define the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

This parameter has to be followed by a date (MMDDCCYY). If this parameter is missing, the starting date coincides with the beginning of the Journal.

&D2 : End date

This parameter is used as a Selection Criterion to define the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

This parameter has to be followed by a MMDDCCYY date format.

If this parameter is missing, the end date coincides with the end of the Journal.

&S1 : Starting session

This parameter is used as a Selection Criterion to define the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

This parameter has to be followed by a five-character field: a four-character session field and one-character session status field.

If this parameter is missing, the starting session coincides with the beginning of the Journal.

&S2 : Final session

This parameter is used as a Selection Criterion to define the Request Area, the Data Sorting Mode, and the Activity Calculation mode.

This parameter has to be followed by a five-character session field: a four-character session number and a one-character session status. If this parameter is missing, the final session coincides with the end of the Journal.

&DAY : Day-by-day presentation

Used as a Presentation Criterion to define the page layout and the data sorting mode.

To define an X-axis, this parameter must be followed by the '=' character and the number of characters corresponding to the curve step (its default value is one character).

&WEEK : Week-by-week presentation

Used as a presentation criterion to define the page layout and the data sorting mode.

To define an X-axis, this parameter must be followed by the '=' character and the number of characters corresponding to the curve step (its default value is one character).

&MON : Month-by-month presentation

Used as a presentation criterion to define the page layout and the data sorting mode.

To define an X-axis, this parameter must be followed by the '=' character and the number of characters corresponding to the curve step (its default value is one character).

&YEAR : Year-by-year presentation

Used as a presentation criterion to define the page layout and the data sorting mode.

To define an X-axis, this parameter must be followed by the '=' character and the number of characters corresponding to the curve step (its default value is one character).

&SESS : Presentation by session

Used as a presentation criterion to define the page layout and the data sorting mode.

The user cannot use it to select sessions (the '=' character is therefore unnecessary).

&CHAR : Printing curve character

May only be used to define the activity calculation mode relative to the curve-type graphs.

It must follow (within parentheses) the calculation defining a curve.

&INTR : Number of input transactions

May only be used to define the activity calculation mode. Each Journal transaction is an input transaction.

&RETR : Number of real transactions

May only be used to define the activity calculation mode.

A Journal transaction is effective, provided it is not modified by another transaction and it is not itself a deletion transaction. This concept is linked to the presentation criteria, i.e. a transaction which is modified once a day is effective every day with a day-by-day presentation; it is effective only once with another presentation.

&H1 : Starting hour

This parameter is used as a Selection Criterion to define the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

This parameter has to be followed by a HHMMSS hour format.

If this parameter is missing, the starting hour coincides with the beginning of the Journal.

&H2 : End hour

This parameter is used as a Selection Criterion to define the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

This parameter has to be followed by a HHMMSS hour format.

If this parameter is missing, the end hour coincides with the beginning of the Journal.

&MIN : Minute-by-minute presentation

Used as a presentation criterion to define the page layout and the data sorting mode.

To define an X-axis, this parameter must be followed by a '=' character and the number of characters corresponding to the curve step (its default value is one character)

&HOUR : Hour-by-hour presentation

Used as a presentation criterion to define the page layout and the data sorting mode.

To define an X-axis, this parameter must be followed by a '=' character and the number of characters corresponding to the curve step (its default value is one character)

&MCOd : Transaction code

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

&DSMS : Change number

This parameter is used as a Presentation and Selection Criterion to define the Page Layout, the Request Area, the Data Sorting Mode, and the Activity Calculation Mode.

Parameter	AREa	PAGes	OUTput	OUTput
			STA	GRA
			LIN COL	ABS ORD
&LIB	YES	YES	YES	YES
&USER	YES	YES	YES	YES
&ENTG	YES	YES	YES	YES
&ENTD		YES	YES	
&LICO	YES	YES	YES	YES
&ENT	YES	YES	YES	YES
&INPT	YES	YES	YES	YES
&D1=				
MMDDCCYY	YES		YES	YES
&D2=				
MMDDCCYY	YES		YES	YES
&S1=9999Z	YES		YES	YES
&S2=9999Z	YES		YES	YES
&MIN	YES	YES	YES	=
&HOUR	YES	YES	YES	=
&DAY	YES	YES	YES	=
&WEEK	YES	YES	YES	=
&MON	YES	YES	YES	=
&YEAR	YES	YES	YES	=
&SESS		YES	YES	
&MCOd		YES	YES	YES
&DSMS		YES	YES	YES
&CHAR				CALCULATION



Parameter	AREa	PAGes	OUTput	OUTput
&INTR				CALCULATION
&RETR				CALCULATION

'=' : the parameter must be followed by the separator character '=' and the curve step;

CALCULATION : only used in the Activity Calculation Mode.

## ACTI - User Input

A '\*' line with user code and password.

Specific input needed for this procedure is described in the optional utilities Reference Manual, in the chapter dedicated to this procedure.

## ACTI - Description of Steps

EXTRACTION: PTU630

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Base dir. : AR	Output	Development Database data
PAC7AN	Base dir. : AN	Output	Development Database index
PAC7PJ	Save dir. : PJ	Input	Archived update transactions
PAC7MB	User input	Input	Update transactions
PAC7ST	Tmp dir. : WST	Output	Selected reports transactions (length=247)
PAC7DD	User dir. : ACTIDD630	Report	Batch procedure authorization option

Return codes:

- 0: OK
- 8: No authorization on batch procedures.
- 12: System error.

PRINTING OF RESULTS: PTU640

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7ST	Tmp dir. : WST	Input	Transactions for selected reports
PAC7IV	User dir. : ACTIIV640	Report	Selected reports

## ACTI - Execution Script

```
REM * -----
REM *     VISUALAGE PACBASE
REM *
```

```

REM * -----
REM *           - ACTIVITY ANALYSIS -
REM *
REM * -----
REM *
REM * THE JOURNAL FILE CONTAINS ALL THE DATABASE UPDATE
REM * TRANSACTIONS. AS SUCH, IT REFLECTS USER ACTIVITY.WITH
REM * THE JOURNAL STATISTICS UTILITY (ACTI), THIS ACTIVITY
REM * CAN BE MONITORED AND PRESENTED IN THE FORM OF CHARTS.
REM * THE JOURNAL STATISTICS UTILITY ALLOWS THE DATABASE
REM * MANAGER TO QUERY THE JOURNAL BACKUP FILE BASED ON
REM * VARIOUS PARAMETERS:
REM *   - LIBRARY CODE
REM *   - USER CODE
REM *   - ENTITY TYPE
REM *   - ENTITY CODE
REM *   - LINE CODE
REM *   - TRANSACTION TYPE (C,M,D)
REM *   - DATE OF UPDATE
REM *   - SESSION NUMBER OF UPDATE
REM * -----
REM *
<job id=ACTI>

<script language="VBScript">
MyProc = "ACTI"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTU630"))
'-----
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7PJ") = Rep_SAVE & "\PJ"
Call BvpEnv("PTU630","PAC7ST",Rep_TMP & "\WST.tmp")
Call BvpEnv("PTU630","PAC7DD",Rep_USR & "\ACTIDD630.txt")
Return = WshShell.Run("BVPTU630.exe" , 1, TRUE)
If Return = 8 Then
Call Msg_Log (Array("1027"))
End If
If Return = 12 Then
Call Msg_Log (Array("1026"))
End If
Call Err_Cod(Return , 0 , "PTU630")

Call Msg_Log (Array("1022" , "PTU640"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
Call BvpEnv("PTU640","PAC7ST",Rep_TMP & "\WST.tmp")
Call BvpEnv("PTU640","PAC7IV",Rep_USR & "\ACTIIV640.txt")
Return = WshShell.Run("BVPTU640.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTU640")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

```

```
Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>
```

---

## Pacbench Quality Control

### Introduction

The Pacbench Quality Control (PQC) facility is optional, and its use depends on the corresponding purchase agreement.

The Pacbench Quality Control facility is divided into two components:

- The Analysis component, to evaluate the quality of applications in use. This is based either on standard rules or on rules customized by the user.
- The Quality rule extraction component, customized by the user.

Two purchase options are therefore available:

- A basic option providing standard rules for quality control;
- A quality rule CUSTOMIZATION option.

The components supplied on the installation tape are:

- For both purchase options:
  - A Batch Quality Analysis procedure (PQCA);
  - A set of 'compiled' standard quality rules, in the form of a sequential file (see the Environment & Installation manual).
- For the CUSTOMIZATION option:
  - A batch procedure for the extraction and 'compilation' of the customized rules (PQCE);
  - A data element dictionary and the user entity needed for the customization of the rules, in the form of Batch transactions that the user enters in his/her own dictionary via a Batch update (UPDT). (See the Environment & Installation manual.)

### Analysis

#### PQCA - Introduction

The PQCA procedure carries out an analysis of the quality of the applications, according to either standard rules or user-defined rules.

#### CHARACTERISTICS

The procedure invokes a unique program (BVPACQ), which is used as a base for links to the various programs used by the procedure.

All the programs called during the procedure are therefore considered to be sub-programs of PACQ, with which they communicate via a Communication Area and special return codes.

It is functionally identical to the GPRT procedure.

The procedure is split up into 'sub-chains', identified by a 1-position code:

- D for Dictionary
- E for OLSD Screens (OSD)
- G PACBENCH/CS Screens (OSC)
- P for Batch Language Programs (BSD)

After two general programs (BVPACA10 and BVPACA20), common to all the chains, have been executed, the sub-chains are activated, according to the generation-print requests, in the following order:

- Screens
- Programs
- Dictionary

Each sub-chain performs an extraction (followed by a printing for GCP or GCO commands).

Once these sub-chains have been activated for the extraction of the entities to be analyzed, the PTUQ20 program performs the analysis according to the rules that it has been assigned and to the analysis parameters.

Results are printed by the BVPTUQ24, PBVTUQ25 and BVPTUQ30 programs.

The processing of the generated flow in the case of generation requests is identical to that of the GPRT procedure.

#### EXECUTION CONDITIONS

None. Files can remain open to on-line use.

#### **PQCA - User Input**

See the 'PQC' Reference manual.

#### **PQCA - Description of Steps**

##### QUALITY ANALYSIS: PACQ

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AY	Base dir. : AY	Input	Development Database extension data
PAC7AJ	Journal dir. : AJ	Input	Development Database Journal file
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7LB	Base dir. : LB	Input	Generation follow-up
PACQMF	User dir. : MPQCE	Input	Quality rules
PAC7SC	System - Skel dir. : SC	Input	Batch generation language skeleton
PAC7SG	System - Skel dir. : SG	Input	OLSD generation skeleton
PAC7SN	System - Skel dir. : SN	Input	Client/server meta-entity skeleton

Code	Physical name	Type	Label
PAC7SS	System - Skel dir. : SS	Input	Map skeleton
PAC7ME	User input	Input	Entity input to be analyzed
PACQMC	User dir. : PQCR	Input	Selection parameter input
PAC7IA	User dir. : PQCAIA	Report	PACQ execution output
PAC7ID	User dir. : PQCAID	Report	Documentation
PACQIB	User dir. : PQCAIB	Report	Selection parameter check
PACQIE	User dir. : PQCAIE	Report	Results by entity type
PACQIF	User dir. : PQCAIF	Report	Results by entity
PACQIG	User dir. : PQCAIG	Report	List of identifiers exceeding the identifier limits
PAC7GB	User dir. : PQCAGB	Output	DBD generated Cobol
PAC7GE	User dir. : PQCAGE	Output	OLSD generated Cobol
PAC7GG	User dir. : PQCAGG	Output	Pacbench C/S generated Cobol
PAC7GP	User dir. : PQCAGP	Output	Batch language generated Cobol
PAC7GV	User dir. : PQCAGV	Output	PDM generated Cobol
			Other files mentioned in the procedure are temporary files used in the programs flows.

After the execution, the generated streams are concatenated in the PQCAGB file.

### PQCA - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *     - PACBENCH QUALITY CONTROL -
REM *
REM * -----
REM * THE PQCA PROCEDURE CARRIES OUT AN ANALYSIS OF THE
REM * QUALITY OF THE APPLICATIONS, ACCORDING TO EITHER
REM * STANDARD RULES OR USER-DEFINED RULES.
REM *
REM * -----
REM *
<job id=PQCA>

<script language="VBScript">
Dim MyProc
MyProc = "PQCA"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Dim CodLang
If base = "ADMIN" Then
Call Msg_Log (Array("1028",base))
Wscript.Quit (0)
Else

```

```

CodLang = WshShell.RegRead (Rep_BVP & "_SYS\" _
& "\GENLANG")
End If
Call Msg_Log (Array("1022" , "PACQ"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7LB") = Rep_BASE & "\LB"

Call BvpEnv("PACQ", "PACQMC", RepT_USR & "\PQCR")
Call BvpEnv("PACQ", "PACQMF", RepT_USR & "\MPQCE.txt")

Call BvpEnv("PACQ", "PAC7EE", Rep_TMP & "\WEE.tmp")
Call BvpEnv("PACQ", "PAC7EG", Rep_TMP & "\WEG.tmp")
Call BvpEnv("PACQ", "PAC7EP", Rep_TMP & "\WEP.tmp")
Call BvpEnv("PACQ", "PAC7EV", Rep_TMP & "\WEV.tmp")
Call BvpEnv("PACQ", "PAC7GB", Rep_USR & "\PQCAGB.txt")
Call BvpEnv("PACQ", "PAC7GE", Rep_USR & "\PQCAGE.txt")
Call BvpEnv("PACQ", "PAC7GG", Rep_USR & "\PQCAGG.txt")
Call BvpEnv("PACQ", "PAC7GP", Rep_USR & "\PQCAGP.txt")
Call BvpEnv("PACQ", "PAC7GV", Rep_USR & "\PQCAGV.txt")
Call BvpEnv("PACQ", "PAC7IA", Rep_USR & "\PQCAIA.txt")
Call BvpEnv("PACQ", "PAC7IB", Rep_USR & "\PQCAIB.txt")
Call BvpEnv("PACQ", "PAC7ID", Rep_USR & "\PQCAID.txt")
Call BvpEnv("PACQ", "PAC7IE", Rep_USR & "\PQCAIE.txt")
Call BvpEnv("PACQ", "PAC7IF", Rep_USR & "\PQCAIF.txt")
Call BvpEnv("PACQ", "PAC7IG", Rep_USR & "\PQCAIG.txt")
Call BvpEnv("PACQ", "PAC7JG", Rep_TMP & "\WJG.tmp")
Call BvpEnv("PACQ", "PAC7KD", Rep_TMP & "\WKD.tmp")
Call BvpEnv("PACQ", "PAC7KE", Rep_TMP & "\WKE.tmp")
Call BvpEnv("PACQ", "PAC7KF", Rep_TMP & "\WKF.tmp")
Call BvpEnv("PACQ", "PAC7KG", Rep_TMP & "\WKG.tmp")
Call BvpEnv("PACQ", "PAC7KP", Rep_TMP & "\WKP.tmp")
Call BvpEnv("PACQ", "PAC7KS", Rep_TMP & "\WKS.tmp")
Call BvpEnv("PACQ", "PAC7KU", Rep_TMP & "\WKU.tmp")
Call BvpEnv("PACQ", "PAC7KV", Rep_TMP & "\WKV.tmp")

WshEnv("PAC7ME") = Fic_Input

Call BvpEnv("PACQ", "PAC7MG", Rep_TMP & "\WMG.tmp")
Call BvpEnv("PACQ", "PAC7MV", Rep_TMP & "\WMV.tmp")
Call BvpEnv("PACQ", "PAC7MJ", Rep_TMP & "\WMJ.tmp")
Call BvpEnv("PACQ", "PAC7MK", Rep_TMP & "\WMK.tmp")
Call BvpEnv("PACQ", "PAC7MM", Rep_TMP & "\WMM.tmp")
Call BvpEnv("PACQ", "PAC7MN", Rep_TMP & "\WMN.tmp")
Call BvpEnv("PACQ", "PAC7MO", Rep_TMP & "\WMO.tmp")
Call BvpEnv("PACQ", "PAC7MZ", Rep_TMP & "\WMZ.tmp")
WshEnv("PAC7SC") = Rep_SKEL & "\SC" & CodLang
WshEnv("PAC7SG") = Rep_SKEL & "\SG" & CodLang
WshEnv("PAC7SN") = Rep_SKEL & "\SN" & CodLang
WshEnv("PAC7SS") = Rep_SKEL & "\SS" & CodLang
Call BvpEnv("PACQ", "PAC7W1", Rep_TMP & "\WW1.tmp")
Call BvpEnv("PACQ", "PAC7W2", Rep_TMP & "\WW2.tmp")
Call BvpEnv("PACQ", "PAC7W3", Rep_TMP & "\WW3.tmp")
Call BvpEnv("PACQ", "PAC7W4", Rep_TMP & "\WW4.tmp")

Call RunCmdLog ("BVPACQ")

If Return < 10 then
Call Msg_Log (Array("1062"))
End if

```

```

If Return = 10 then
Call Msg_Log (Array("1063"))
End if
If Return > 10 then
Call Msg_Log (Array("1064"))
End if
Call Err_Cod(Return , 10 , "PACQ")

If Return < 10 or Return = 10 Then
'Information : Normal End
'-----
Return = 0
WshVolEnv("RC") = Return

If Not FSO.FileExists(WshEnv("PAC7GB")) Then
Set LogPqc = FSO.CreateTextFile(WshEnv("PAC7GB") , TRUE)
LogPqc.Close
End if
GB = WshEnv("PAC7GB")

'Write For Appending on PQCAGB.txt
'COPY GB + G. ==> GB
Call CopMFile(GB , WshEnv("PAC7GE") ,GB )
Call DelFile (WshEnv("PAC7GE"))
Call CopMFile(GB , WshEnv("PAC7GG") ,GB )
Call DelFile (WshEnv("PAC7GG"))
Call CopMFile(GB , WshEnv("PAC7GP") ,GB )
Call DelFile (WshEnv("PAC7GP"))
Call CopMFile(GB , WshEnv("PAC7GV") ,GB )
Call DelFile (WshEnv("PAC7GV"))

Else
WshVolEnv("RC") = Return
Call Err_Cod(Return , 0 , "PACQ")
End If

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Extraction of Quality Rules

### PQCE - Introduction

The PQCE procedure performs the extraction of quality rules created by the user in his/her database via the user entity supplied with the Customization option of the Pacbench Quality Control Facility.

It extracts the user entity occurrences that make up the customized quality rule dictionary, checks the information, and builds a file with the 'compiled' quality rules required by the Analysis of application quality (PQCA).

For further details, see the Pacbench Quality Control Reference Manual.

## EXECUTION CONDITIONS

None. The files can remain available for on-line use.

### **PQCE - Input / Processing / Results**

The user input of the PQCE procedure is similar to that of the EXUE extractor (PACX procedure).

One '\*' line per library to be consulted for extraction:

Position	Length	Value	Meaning
2	1	*	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	User password
19	3	bbb	Library code
22	4	nnnn	Session number (Blank=current session)
26	1	T	Session status if Test session
28	1	L	Language code (F=French, A=English)
29	4	EXUE	Extractor code

For further details, see the chapter 'Manager's Utilities' (PACX: Extractions) in this manual.

One command line:

Pos.	Len.	Value	Meaning
2	4	W1EX	Line code
6	1	Y	UE extraction identifier
7	1	U C	Library selection code: Selected library Selected library + higher level lib.
8	2	5Q	Type code of user entity dedicated to Quality Control

## RESULT

The output of the PQCE procedure is a file containing the 'compiled' customized quality rules, which can be processed by the PQCA procedure.

### PRINTED REPORT

This procedure prints:

- An occurrence-extraction report.
- A check report on the validity and usage of quality indicators.
- Descriptive reports on quality rules:
  - List of quality factors and criteria,
  - Description of each quality indicator,
  - Quality Control Dictionary.



## PQCE - Description of Steps

### EXTRACTION: PACX

This step extracts transactions according to user input.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Base dir. : AN	Input	Development Database Index file
PAC7AR	Base dir. : AR	Input	Development Database Data file
PAC7AY	Base dir. : AY	Input	Development Database Extension Data
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database Index file
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database Data file
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database Users
PAC7PJ	nul	Input	Archived transactions
PAC7MB	User input	Input	User input
PAC7BM	Tmp dir.: WBM	Input/Output	User input
PAC7MM	Tmp dir.: WMM	Input/Output	EXPU work file
PAC7MJ	Tmp dir.: WMJ	Input/Output	EXPJ work file
PAC7TE	Tmp dir.: WTE	Input/Output	RMEN work file
PAC7RE	Tmp dir.: WRE	Input/Output	RMEN work file
PAC7RM	Tmp dir.: WRM	Input/Output	RMEN work file
PAC7WD	Tmp dir.: WWD	Input/Output	Extracted transactions
SYSEXT	Tmp dir.: WWSY et WSY.idx	Input/Output	Work file
PAC7MV	User dir.: PQCEMV	Output	Extracted transactions for UPDT
PAC7MR	User dir.: PQCEMR	Output	Extracted transactions for REOR (EXPU)
PAC7GY	User dir.: PQCEGY	Output	Extracted transactions for UPDP
PAC7TD	User dir.: PQCETD	Output	Extracted transactions for CPSN
PAC7UE	User dir.: PQCEUE	Output	Extracted transactions for EXUE
PAC7IA	User dir.: PQCEIA	Report	General printing of program chains
PAC7DD	User dir.: PQCEDD	Report	Printing of abends on input transactions
PAC7EE	User dir.: PQCEEE	Report	Extraction reports
PAC7EP	User dir.: PQCEEP	Report	Extraction reports
PAC7EQ	User dir.: PQCEEQ	Report	Extraction reports
PAC7EZ	User dir.: PQCEEZ	Report	Extraction reports

### COMPILATION OF QUALITY RULES: PTUQ10

This step creates the customized quality rule file that will be used by the PQCA analysis procedure.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PACGGY	Admin Base - Base dir. : AY	Input	Administration Database Extension
PAC7AR	Base dir. : AR	Input	Development Database data
PACQMI	User dir. : MPQCE	Output	'Compiled' quality rules (length=80)
PAC7MB	User input	Input	User input
PACQMC	Tmp dir. : WUE	Input	User input instances
PACQML	Tmp dir. : WML	Output	Preparation for printing
PACQIC	User dir. : PQCEICQ10	Report	Rule-validity report
PAC7DD	User dir. : PQCEDDQ10	Report	Batch procedure authorization option

#### PRINTING OF QUALITY RULES: PTUQ15

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACQML	Tmp dir. : WML	Input	Preparation for printing
PACQII	User dir. : PQCEIIQ15	Report	List of quality factors and criteria and description by indicator
PACQIJ	User dir. : PQCEIJQ15	Report	Dictionary of quality rules

#### PQCE - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      - PACBENCH QUALITY CONTROL EXTRACTION -
REM *
REM * -----
REM *
REM * FORMAT OF TRANSACTIONS AT INPUT :
REM * .. A USER AND LIBRARY LINE
REM * .. A COMMAND LINE PER ENTITY TO BE EXTRACTED
REM *   COL 2-6 : 'WIEX$'
REM *   COL 7   : SELECTION CODE OF THE LIBRARY
REM *           'U'(LIBRARY ONLY)
REM *           'C'(LIBRARY AND HIGHER LEVEL LIBRAIRIES)
REM *   COL 8-9 : TYPE CODE OF THE USER ENTITY (2 CHAR.)
REM *
REM * -----
REM *
<job id=PQCE>

<script language="VBScript">
Dim MyProc
MyProc = "PQCE"

```

```

</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PACX"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PACX","PAC7IA",Rep_USR & "\PQCEIA.txt")
Call BvpEnv("PACX","PAC7DD",Rep_USR & "\PQCEDD.txt")
Call BvpEnv("PACX","PAC7EE",Rep_USR & "\PQCEEE.txt")
Call BvpEnv("PACX","PAC7EZ",Rep_USR & "\PQCEEZ.txt")
Call BvpEnv("PACX","PAC7EP",Rep_USR & "\PQCEEP.txt")
Call BvpEnv("PACX","PAC7EQ",Rep_USR & "\PQCEEQ.txt")
WshEnv("PAC7GY") = "NUL"
Call BvpEnv("PACX","PAC7BM",Rep_TMP & "\WBM.tmp")
WshEnv("PAC7MB") = Fic_Input
WshEnv("PAC7MJ") = "NUL"
Call BvpEnv("PACX","PAC7MM",Rep_TMP & "\WMM.tmp")
WshEnv("PAC7MR") = "NUL"
WshEnv("PAC7MX") = "NUL"
WshEnv("PAC7MV") = "NUL"
WshEnv("PAC7PJ") = "NUL"
WshEnv("PAC7RE") = "NUL"
WshEnv("PAC7RM") = "NUL"
Call BvpEnv("PACX","SYSEXT",Rep_TMP & "\WSY.tmp")
WshEnv("PAC7TD") = "NUL"
WshEnv("PAC7TE") = "NUL"
Call BvpEnv("PACX","PAC7UE",Rep_TMP & "\WUE.tmp")
Call BvpEnv("PACX","PAC7WD",Rep_TMP & "\WWD.tmp")
Return = WshShell.Run("BVPACX.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PACX")

Call Msg_Log (Array("1022" , "PTUQ10"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGY") = Rep_ABASE & "\AY"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUQ10","PAC7DD",Rep_USR & "\PQCEDDQ10.txt")
Call BvpEnv("PTUQ10","PACQIC",Rep_USR & "\PQCEICQ10.txt")
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PTUQ10","PACQMI",Rep_USR & "\MPQCE.txt")
Call BvpEnv("PTUQ10","PACQMC",Rep_TMP & "\WUE.tmp")
Call BvpEnv("PTUQ10","PACQML",Rep_TMP & "\WML.tmp")
Return = WshShell.Run("BVPTUQ10.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUQ10")

Call Msg_Log (Array("1022" , "PTUQ15"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
Call BvpEnv("PTUQ15","PACQII",Rep_USR & "\PQCEIIQ15.txt")
Call BvpEnv("PTUQ15","PACQIJ",Rep_USR & "\PQCEIJQ15.txt")
Call BvpEnv("PTUQ15","PACQML",Rep_TMP & "\WML.tmp")
Return = WshShell.Run("BVPTUQ15.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUQ15")

```

```
Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>
```

---

## Chapter 6. Versioning Facilities

---

### Standard Bridge (PCM)

#### Introduction

The STANDARD BRIDGE is an optional module and its use depends upon the corresponding purchase agreement. The purpose of the module is twofold:

##### 1. PRODUCTION TURNOVER MANAGEMENT

This function is used to:

- Manage the generation environments, by specifying the 'production environments' which are used to manage the database freeze.
- Follow up entities generated from a database and put into production.
- Give the user information related to these entities such as their library code, the session number of the last generation, and of the last database freeze.
- Automatically freeze the database when generating into a production environment.
- Provide project follow-up to development teams in relation to generated entities.

##### 2. RECOGNITION OF A CONFIGURATION MANAGEMENT UTILITY

With the use of two complementary procedures, the module ensures the consistency between the production turnover data which is stored in the development Database, and the programs generated by a configuration management utility. But the user needs to ship a file that is to be extracted from the product so as to compare it with another file extracted from the development Database.

#### Database Automatic Freeze

##### **HIPM - Introduction**

The purpose of the HIPM procedure is to generate transactions related to the production turnover of entities and if necessary, the transactions related to the freezing of the development Database.

##### EXECUTION CONDITIONS

None

##### ABNORMAL EXECUTION

The procedure can be restarted once the problem has been solved.

##### **HIPM - Input / Processing / Results**

A '\*' line with user code and password.

User input specific to the optional procedure which is used for database freeze request.

The structure of the line is as follows:

Position	Length	Value	Meaning
2	2		Line code
		'X1'	if the entities have been put into production
		'X4'	If no entity has been put into production
4	4	'HIST'	Freeze request
8	50		Freeze comments
58	4	ssss	Forcing of session number to be frozen: this number must be included between the current session number +1 and the current session +100

If this line is not entered, it is automatically generated when entities are put into production.

This line may be entered in order to:

- Give a specific freeze comment,
- Force the session number to be frozen.

#### PRINTED REPORTS

This procedure prints:

- a report,
- a list of the entities used in production, and if the database has been frozen.

#### RESULTS

The result of the procedure execution is a sequential file containing the production environment transactions and the optional freeze transactions.

This file must be put in input of the UPDP procedure in order to update the development Database.

### **HIPM - Description of Steps**

#### GENERATION OF PRODUCTION TURNOVER TRANSACTIONS: PCM300

This step is used to explore the development database and generate production turnover and database freeze transactions.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AY	Base dir. : AY	Input	Development Database random data
PAC7MB	User input	Input	Users data .

Code	Physical name	Type	Label
PAC7TR	Tmp dir. : WTR	Output	Work file
PAC7SR	Tmp dir. : WSR	Output	Work file
PAC7IG	User dir. : HIPMIG300	Report	Production turnover output report
PAC7GY	Journal dir. : MY	Output	Production turnover transactions
PAC7DD	User dir. : HIPMDD300	Report	Batch procedures authorization option

## HIPM - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM * AUTOMATIC SESSION FREEZE
REM * -----
REM *
REM * INPUT      : USER IDENTIFICATION
REM * COL 2      : '*'
REM * COL 3      : USER CODE
REM * COL 11     : PASSWORD
REM * -----
<job id=HIPM>

<script language="VBScript">
Dim MyProc
MyProc = "HIPM"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PCM300"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7GY") = Rep_JOURNAL & "\MY"
Call BvpEnv("PCM300","PAC7DD",Rep_USR & "\HIPMDD300.txt")
Call BvpEnv("PCM300","PAC7IG",Rep_USR & "\HIPMIG300.txt")
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PCM300","PAC7TR",Rep_TMP & "\WTR.tmp")
Call BvpEnv("PCM300","PAC7SR",Rep_TMP & "\WSR.tmp")
Return = WshShell.Run("BVPCM300.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM300")

Call Msg_Log (Array("1022" , "PCM039"))
'-----
WshEnv("PAC7WY") = Rep_JOURNAL & "\WY"
WshEnv("PAC7MY") = Rep_JOURNAL & "\MY"
Return = WshShell.Run("BVPCM039.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM039")

```

```

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Generation Simulation

### SIPM - Introduction

The SIPM procedure is used to simulate the production turnover of entities which is usually performed by GPRT.

There are two possibilities:

- Production turnover of entities:

The information related to the entities and the environment is entered by the user.

- Transfer from one environment to another one:

The information related to the entity is provided by the source environment.

### EXECUTION CONDITIONS

None.

SIPM execution conditions are the same as GPRT's.

### ABNORMAL EXECUTION

Whatever the reason for an abnormal ending, the procedure can be restarted as it is, once the problem has been solved.

### SIPM - Input / Processing / Results

A '\*' line with user code and password including information related to the procedure

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
19	3	bbb	Library code
22	4	ssss	session number (blank if current session)
26	1		Session status (' ' or 'T')
59	8	ssaammjj	Generation date , if the session is not the current session (input field for a frozen session of blank or T type, no input field for a current session)



An environment identification line 'EG' (required):

Position	Length	Value	Meaning
2	2	'EG'	Line code
4	3	ttt	Type of entities processed
7	30		Target environment
37	10		Target application

Source environment line 'ES'(if transfer):

Position	Length	Value	Meaning
2	2	'ES'	Line code
7	30		Source environment
37	10		Source application

Entity identification line 'EU' for each entity generation to be simulated

Position	Length	Value	Meaning
2	2	'EU'	Line code
4	6	cccccc	Entity code
10	8	eeeeeeee	External name of the entity in target environment (if different from the database code)
18	8	nnnnnnnn	External name of the entity in source environment (if transfer with RENAME)

## REPORT OUTPUT

This procedure prints a report

## RESULTS

Once the procedure has been executed, a sequential file is produced. This file contains the production turnover transactions.

It must be used as input to the UPDP procedure in order to update the development Database.

## **SIPM - Description of Steps**

Work file initialization : PCMINI

Code	Physical name	Type	Label
PAC7QJ	base dir. : WY	Output	Work file

## GENERATION OF SIMULATION TRANSACTIONS: PCM320

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index

Code	Physical name	Type	Label
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AY	Base dir. : AY	Input	Administration Database random data
PAC7MB	User input	Input	User transactions
PAC7MT	Tmp dir. : WMT	Output	File to be used by a transfer utility
PAC7IE	User dir. : SIPMIE320	Report	Simulation output report
PAC7GY	Base dir. : WY	Output	Transactions for UPDP (simulation output)
PAC7DD	User dir. : SIPMDD320	Report	Batch procedures authorization option

## SIPM - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM * SIMULATION
REM * -----
REM *
REM * INPUT      : USER IDENTIFICATION
REM * COL 2      : '*'
REM * COL 3      : USER CODE
REM * COL 11     : PASSWORD
REM * COL 19     : LIBRARY
REM * COL 22     : SESSION
REM * COL 25     : SESSION STATE
REM * -----
<job id=SIPM>

<script language="VBScript">
Dim MyProc
MyProc = "SIPM"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

If Not FSO.FileExists(Rep_JOURNAL & "\WY") Then
Call Msg_Log (Array("1022" , "PCMINI"))
'-----
WshEnv("PAC7QJ") = Rep_JOURNAL & "\WY"
Return = WshShell.Run("BVPCMINI.exe", 1, TRUE)
Call Err_Cod(Return , 0 , "PCMINI")
End if

Call Msg_Log (Array("1022" , "PCM320"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"

```

```

WshEnv("PACGGR") = Rep_ABASE & "\\AR"
WshEnv("PACGGU") = Rep_ABASE & "\\GU"
WshEnv("PAC7GY") = Rep_JOURNAL & "\\WY"
Call BvpEnv("PCM320","PAC7DD",Rep_USR & "\\SIPMDD320.txt")
Call BvpEnv("PCM320","PAC7IE",Rep_USR & "\\SIPMIE320.txt")
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PCM320","PAC7MT",Rep_TMP & "\\WMT.tmp")
Return = WshShell.Run("BVPCM320.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM320")

Call Msg_Log (Array("1022" , "PCM039"))
'-----
WshEnv("PAC7WY") = Rep_JOURNAL & "\\WY"
WshEnv("PAC7MY") = Rep_JOURNAL & "\\MY"
Return = WshShell.Run("BVPCM039.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM039")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Extraction of the Development Database Data

### EXPM - Introduction

The EXPM procedure extracts, from the development Database, the entities whose generation status is to be compared to the configuration management utility.

The extracted file will be compared to the file extracted from the utility.

The extraction can be limited to sessions, databases, environments and applications.

### EXECUTION CONDITIONS

None.

### ABNORMAL EXECUTION

The procedure can be restarted as it is once the problem has been solved.

### EXPM - Input / Processing / Results

A '\*' line with user code and password.

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
19	3	bbb	Library code

Position	Length	Value	Meaning
		***	if extraction from all Libraries
22	4	ssss	Number of session in use (blank in current session)
		****	if extraction from all sessions
26	1	*	Status of the session ( ' ' or 'T') if extraction from all sessions

One or more 'S' line(s) to select the environments /application

The line is structure is as follows:

Position	Length	Value	Meaning
2	1	'S'	Line code
3	30		Selected environment
33	10		Selected application

#### PRINTED REPORT

This procedure prints a report.

#### RESULTS

Once the procedure has been executed, a sequential file extracted from the development Database is produced, it must be used as input to the CPPM procedure.

### **EXPM - Description of Steps**

#### EXTRACTION OF THE DEVELOPMENT DATABASE: PCM200

This step explores the development Database and extracts the elements in accordance with the extraction request.

Code	Physical name	Type	Label
PAC7MB	User input	Input	User transactions
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AY	Base dir. : AY	Input	Development Database random data
PAC7MV	User dir. : EXPMMV	Input	User data file
PAC7ET	User dir. : EXPMET200	Report	Extraction output report
PAC7MS	Tmp dir. : WMS	Output	Extracted elements file
PAC7DD	User dir. : EXPMDD200	Report	Batch procedures authorization option

## DELETION OF DUPLICATE EXTRACTED ELEMENTS: PCM202

This step is used to suppress the elements that would be assigned by error to several extracted applications.

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7ME	Tmp dir. : WMS	Input	Input extracted elements file
PAC7MS	Tmp dir. : WMS2	Output	Output extracted elements file
PAC7EQ	User dir. : EXPMEQ202	Report	List of elements extracted twice

## EXTRACTED ELEMENTS SORTING FILE: PCM205

This step sorts the extracted elements file in accordance with the criterion required for the comparison with the file provided by the configuration management utility.

Code	Physical name	Type	Label
PAC7ME	Tmp dir. : WMS2	Input	Input extracted elements file
PAC7MS	User dir. : MSEXP	Output	Output extracted elements file

## Sequential GY: PCM039

Code	Physical name	Type	Label
PAC7WY	Journal dir.: WY	Input	Indexed GY records
PAC7MY	Journal dir.: MY	Output	GY records

## **EXPM - Execution Script**

```
REM * -----  
REM *     VISUALAGE PACBASE  
REM *  
REM * -----  
REM * EXTRACTION  
REM * -----  
REM *  
REM * INPUT      : USER IDENTIFICATION  
REM * COL 2      : '*'  
REM * COL 3      : USER CODE  
REM * COL 11     : PASSWORD  
REM * COL 19     : LIBRARY  
REM * COL 22     : SESSION  
REM * COL 26     : SESSION STATE  
REM * -----  
<job id=EXPM>  
  
<script language="VBScript">  
Dim MyProc  
MyProc = "EXPM"  
</script>  
  
<script language="VBScript" src="INIT.vbs"/>  
  
<script language="VBScript">
```

```

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PCM200"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PCM200","PAC7DD",Rep_USR & "\EXPMDD200.txt")
Call BvpEnv("PCM200","PAC7ET",Rep_USR & "\EXPMET200.txt")
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PCM200","PAC7MS",Rep_TMP & "\WMS.tmp")
Call BvpEnv("PCM200","PAC7MV",Rep_USR & "\EXPMMV.txt")
Return = WshShell.Run("BVPCM200.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM200")

Call Msg_Log (Array("1022" , "PCM202"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
Call BvpEnv("PCM202","PAC7ME",Rep_TMP & "\WMS.tmp")
Call BvpEnv("PCM202","PAC7MS",Rep_TMP & "\WMS2.tmp")
Call BvpEnv("PCM202","PAC7EQ",Rep_USR & "\EXPMEQ202.txt")
Return = WshShell.Run("BVPCM202.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM202")

Call Msg_Log (Array("1022" , "PCM205"))
'-----
Call BvpEnv("PCM205","PAC7MS",RepT_USR & "\MSEXPM.txt")
Call BvpEnv("PCM205","PAC7ME",Rep_TMP & "\WMS2.tmp")
Return = WshShell.Run("BVPCM205.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM205")

Call Msg_Log (Array("1022" , "PCM039"))
'-----
WshEnv("PAC7WY") = Rep_JOURNAL & "\WY"
WshEnv("PAC7MY") = Rep_JOURNAL & "\MY"
Return = WshShell.Run("BVPCM039.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM039")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Comparison with Extracted Files

### CPPM - Introduction

The CPPM procedure is used to compare a file extracted from the development Database via the EXPM procedure, with a similar file extracted by the user from the configuration management utility.

The purpose is to generate a transactions file to update the development Database via the UPDP procedure.

The transactions are due to set the development Database to the level of the configuration management utility, in relation to the production entities.

#### EXECUTION CONDITIONS

The EXPM procedure must be executed at first so as to obtain a file extracted from the development Database.

Moreover, a file extracted from the configuration management utility must have been defined, with the same status as the file's extracted from the development Database

#### ABNORMAL EXECUTION

Whatever the reason for an abnormal ending, the procedure can be restarted as it is, once the problem has been solved.

### **CPPM - Input / Processing / Results**

A '\*' line with user code and password.

#### PRINTED REPORT

This procedure prints:

- A report,
- A list of entities which will be modified in the development Database after executing the UPDP procedure.

#### RESULTS

Once the procedure executed, a sequential file is produced. It contains the development Database update transactions to be used as input to the UPDP procedure.

### **CPPM - User File**

To be able to align the development Database with the Configuration management utility used on-site, it is necessary to create a file which contains the data extracted from the utility so as to compare it with the file extracted from the development Database via the EXPM procedure.

The length of the file should be 900 with the following structure:

Position	Length	Value	Meaning
1	35		Parameter 1
36	35		Parameter 2
71	35		Parameter 3
106	35		Parameter 4
141	35		Parameter 5
176	35		Parameter 6
211	35		Parameter 7
246	35		Parameter 8

Position	Length	Value	Meaning
281	35		Parameter 9
316	35		Parameter 10
351	35		Parameter 11
386	35		Parameter 12
421	35		Parameter 13
456	35		Parameter 14
491	35		Parameter 15
526	30		Environment code
556	10		Application code
566	1		Entity type
567	6		Entity
573	8		External code of entity
585	3		Library code
588	4		Session number
592	1		Session status
593	2		Call code (when it is a user entity)
595	10		Generation data (CCYYMMDD)
605	8		Generation time
613	8		User code
621	35		Group field
796	51		Optional fields which display information on the last action performed on the object:
796	20		Action label
816	10		Action date
826	8		Action hour
834	8		User code
842	5		Object version
847	54		VA Pac internal fields

The information of 'parameter 1' up to 'parameter 15' corresponds to the parameters defined in the environment screen. The sorting order is taken into account.

The 'Entity type' and the next information correspond to the values defined in the generated program, in the PACBASE-CONSTANTS (or CONTANTES-PACBASE).

### **CPPM - Description of Steps**

Initialization of the Work file: PCMINI

Code	Physical name	Type	Label
PAC7QJ	Journal dir. : WY	Output	Work file



## COMPARISON PROCESSING: PCM210

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AY	Base dir. : AY	Output	Development Database extension data
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7MB	User input	Input	User transactions
PAC7MP	User dir. : MSEXPM	Input	File extracted from the development Database
PAC7MU	Tmp dir. : WMU	Input	File extracted from configuration management utility
PAC7EQ	User dir. : CPPMEQ210	Report	Output report of check
PAC7ME	Tmp dir. : WME	Output	File used to print comparison errors
PAC7MS	Tmp dir. : WMS	Output	File used to print update transactions
PAC7DD	User dir. : CPPMDD210	Report	Batch procedures authorization option

## PRINT OF UPDATE TRANSACTIONS: PCM220

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7EQ	User dir. : CPPMEQ220	Report	Comparison output report
PAC7MS	Tmp dir. : WMS2	Input	File used to print the results of comparison
PAC7GY	Journal dir. : WY	Input	RRDS file containing transactions for UPDP

## CPPM - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM * COMPARIZON
REM * -----
REM *
REM * INPUT      : USER IDENTIFICATION
REM * COL 2      : '*'
REM * COL 3      : USER CODE
REM * COL 11     : PASSWORD
REM * -----
<job id=CPPM>

<script language="VBScript">
Dim MyProc

```

```

MyProc = "CPPM"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

    If Not FSO.FileExists(Rep_JOURNAL & "\WY") Then
    Call Msg_Log (Array("1022" , "PCMINI"))
    '-----
    WshEnv("PAC7QJ") = Rep_JOURNAL & "\WY"
    Return = WshShell.Run("BVPCMINI.exe", 1, TRUE)
    Call Err_Cod(Return , 0 , "PCMINI")
    End if

Call Msg_Log (Array("1022" , "PCM210"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PCM210","PAC7DD",Rep_USR & "\CPPMDD210.txt")
Call BvpEnv("PCM210","PAC7EQ",Rep_USR & "\CPPMEQ210.txt")
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PCM210","PAC7MP",RepT_USR & "\MSEXPM.txt")
Call BvpEnv("PCM210","PAC7MS",Rep_TMP & "\WMS.tmp")
Call BvpEnv("PCM210","PAC7MU",Rep_TMP & "\WMU.tmp")
Call BvpEnv("PCM210","PAC7ME",Rep_TMP & "\WME.tmp")
Return = WshShell.Run("BVPCM210.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM210")

Call Msg_Log (Array("1022" , "PCM220"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7GY") = Rep_JOURNAL & "\WY"
Call BvpEnv("PCM220","PAC7MS",Rep_TMP & "\WMS2.tmp")
Call BvpEnv("PCM220","PAC7EQ",Rep_USR & "\CPPMEQ220.txt")
Return = WshShell.Run("BVPCM220.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM220")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Integrity Control of Events/Elements

### CHPM - Introduction

The CHPM procedure is used to check the consistency of the environments and elements present in the VA Pac Database. The procedure produces a report

printout for erroneous events and elements. The purpose of this check is to highlight the inconsistencies in the development Database.

EXECUTION CONDITION

None.

ABNORMAL EXECUTION

The procedure can be restarted as it is, once the problem has been solved.

**CHPM - Input / Processing / Results**

Batch procedures access authorization option: A '\*' line with user code and password.

PRINTED REPORT

This procedure prints a report listing the consistency errors detected in the development Database, and related to the environments and elements.

**CHPM - Description of Steps**

ENVIRONMENTS/ELEMENTS CONSISTENCY CHECK: PCM400

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AY	Base dir. : AY	Input	Development Database random data
PAC7MB	User input	Input	User transactions
PAC7MS	Tmp dir. : WMS	Output	File used to print a a check report
PAC7MV	Tmp dir. : WMV	Output	Working file
PAC7DD	User dir. : CHPMDD400	Report	Batch procedures authorization option

CONSISTENCY CHECK REPORT PRINTOUT: PCM410

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7EQ	User dir. : CHPMEQ410	Report	Output validation report
PAC7MS	Tmp dir. : WMS	Input	File used for the report printout
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data

**CHPM - Execution Script**

```

REM * -----
REM *     VISUALAGE PACBASE
REM *

```

```

REM * -----
REM * VALIDATION OF THE DEVELOPMENT DATABASE
REM * -----
REM *
REM * INPUT      : USER IDENTIFICATION
REM * COL 2      : '*'
REM * COL 3      : USER CODE
REM * COL 11     : PASSWORD
REM * -----
<job id=CHPM>

<script language="VBScript">
Dim MyProc
MyProc = "CHPM"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PCM400"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PCM400","PAC7DD",Rep_USR & "\CHPMDD400.txt")
WshEnv("PAC7MB") = Fic Input
Call BvpEnv("PCM400","PAC7MV",Rep_TMP & "\WMV.tmp")
Call BvpEnv("PCM400","PAC7MS",Rep_TMP & "\WMS.tmp")
Return = WshShell.Run("BVPCM400.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM400")

Call Msg_Log (Array("1022" , "PCM410"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
Call BvpEnv("PCM410","PAC7MS",Rep_TMP & "\WMS.tmp")
Call BvpEnv("PCM410","PAC7EQ",Rep_USR & "\CHPMEQ410.txt")
Return = WshShell.Run("BVPCM410.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PCM410")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

---

## Pac/Transfer

### Introduction

The purpose of the Pac/Transfer facility is to provide an easy versioning of the developments made in a VisualAge Pacbase Database; it automates transfers of update transactions between two sessions or more.

Pac/Transfer scans the VA Pac archived Journal file and reads a dedicated Parameter file.

One or more source environments are defined in this parameter file. Each can correspond with one or more target environments.

Pac/Transfer selects, from the archived Journal file, transactions that match the criteria defined via these parameters.

Pac/Transfer then generates update transactions for the target environment(s) defined in the parameter file.

These transactions are used by the VA Pac batch update procedure (UPDT). If the VA Pac Database is under DSMS control, such updates are automatically included in this control.

### FUNCTIONALITIES

Pac/Transfer is used to transfer updates made in a source session to one or several target sessions.

Once a development is completed in a test session, it is possible to transfer this session's contents onto another validation-dedicated session, and, if necessary, onto another session dedicated to production-turnover.

In the transfer file, the selected transactions from the source session are duplicated as many times as there are target sessions.

There are no constraints regarding the chronological order of sessions. It is possible to transfer the transactions entered in a given source session into a later target session (target-session number greater than that of the source session), just as it is possible to transfer it onto a previous target session (target-session number smaller than that of the source session).

The transfer parameters for all development Databases managed by the administrator is stored in administration Database. The list of these databases is itself defined in the administration Database.

Thus, the development Database notion is now important to parameterize Pac/Transfer.

You need to have defined a logical database code for each development Database.

The logical database code used is the one entered when you restore the development database with the REST procedure execution.

In batch Pac/Transfer processing procedures, it is not necessary to indicate the logical code of the development Database. The code indicated in the data file of

the database processed will be systematically taken into account. This code will be used as a link between the development database and the transfer sets stored in the administration Database throughout the processing, as indicated above.

## Processes Chronology

### 1. Updating the transfer parameters (TRUP)

Process to be executed if there are new Transaction Sets to be defined, or if parameters of existing Sets are to be modified.

### 2. Compressing the archived journal

Optional process (depending on the site).

### 3. Creating the transfer file

### 4. Preparing the DSMS environment

Process to be executed only if the Database is under DSMS control.

### 5. Generating the transfer transactions

### 6. Updating the development Database

### 7. Reinitializing the DSMS environment

Process to be executed only if the Database is under DSMS control.

## TRUP - Update of Transfer Parameters

### TRUP - Introduction

PacTransfer processing is based on user-defined parameters stored in the UV parameters file. These parameters monitor all PacTransfer procedures.

These parameters must be created -- via a TRUP execution -- prior to any PacTransfer operation. Any change to one of these parameters must be followed by a new TRUP execution.

Several sets of transfer parameters, called Transaction Sets, may be defined. The parameter file can therefore store several Transaction Sets.

By defining several Transaction Sets, you obtain flexible transfer operations, fully adaptable to your own requirements.

Transfer parameters -- described below -- define one Transaction Set. It is not possible to set parameters common to all Sets.

### TRANSFER PARAMETERS

- Transfer set header line

It is required at the beginning of the transactions relating to transfer set.

It identifies the transfer set to which the parameters entered on the continuation lines are related.

- Session number

It is required to specify one source session and at least one target session.

If you specify several target sessions, transactions entered in the source session will be transferred to each specified target session.

**NOTE:** For each transfer request line, you must specify an order number so as to ensure the adequate chronology of transfers. This is particularly important when several source sessions have the same target session.

- Library

By default, ALL Libraries in the VisualAge Pacbase Database are taken into account for the requested source session, and the transfer target are the same Libraries.

You may restrict the scope of a transfer by selecting one particular source Library, which then becomes the default target Library. This means that you have the wider option of selecting one or more target Libraries.

**NOTE:** If the source Library is to be part of the selected target Libraries, specify its code explicitly.

If you specify several target Libraries, transactions relating to the selected source Library will be transferred to each of the target Libraries.

**Example:** When a transfer is defined from one source session to TWO target sessions, and from one source Library to THREE target Libraries, the volume of transferred transactions will be SIX times larger than the volume of selected transactions.

- User

As a default, transactions entered by ANY Database user are transferred under a unique user code.

You may restrict the scope of the transfer by selecting one particular source user-code, which will be considered as the default target user-code. You may therefore also select a target user-code different from the selected source user-code.

- DSMS change number

This type of selection refers to VisualAge Pacbase Databases under DSMS control only.

By default, transactions associated to ANY Change are transferred under the same Change number.

You may restrict the scope of the transfer by selecting one particular source Change-number, which will be considered as the default target Change-number. You may also select a target Change-number different from the source Change-number.

It is also possible to transfer all transactions under a single target user-code.

**NOTE:** This option overrides any target user selection such as described in Paragraph 1.3.

### EXECUTION CONDITION

Since this procedure updates the network, the GR, GN, GJ and GY files must be closed to on-line mode (except on hardware which supports batch/on-line concurrency).

### PRINTED REPORT

Printout of the parameter-file contents.

### TRUP - User Input

User identification line (required)

Position	Length	Value	Meaning
2	1	'*	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password

Transfer set header line (required)

This line must precede the update transactions of a transfer set. It identifies the transfer set to which the following transactions are related.

Position	Length	Value	Meaning
1	1		Action code
		'C'	Creation
		'M'	Modification
		'D'	Deletion
		' '	Creation or modification depending on the database status
		'X'	Equal to ' ', without any uppercase conversion of the label
2	2	'GA'	Line type
4	10		Transfer set code (required) different from 9999999999 and *****
14	36		Transfer set label (required in creation mode)

Session selection line

Within a Transaction Set, there must be at least one selection line of this type.

Position	Length	Value	Meaning
1	1		Action code
		'C'	Creation
		'M'	Modification
		'A'	Deletion
		' '	Creation or modification depending on the database state
		'X'	Equal to ' ', with no uppercase conversion of the label
2	2	'GS'	Line type
4	4		Source session (required)
13	2		Line number (two lines only are authorized)



Position	Length	Value	Meaning
		'00'	First line for the 9 first target sessions (default value)
		'01'	Continuation line for the 9 following target sessions, if required (the target session number is limited to 18: the input in position 1 to 7 on the first line must be repeated on continuation line).
15	3		Sequence number of reports (required and numeric)
18	36		List of target sessions: The sessions are entered without 'T' and are not followed by blanks (one session is required at least)

#### Selection line of Libraries

Position	Length	Value	Meaning
1	1		Action code:
		'C'	Creation
		'M'	Modification
		'D'	Deletion
		' '	Creation or modification depending on the database state
		'X'	equal to ' ', with no uppercase conversion of the label
2	2	'GB'	Line type
4	3		Source Library (required)
13	60		Library codes (20 max.) Default: source Library. Library codes are not separated by blanks.

#### Selection line of user codes

Position	Length	Value	Meaning
1	1		Action code
		'C'	Creation
		'M'	Modification
		'D'	Deletion
		' '	Creation or modification depending the database state
		'X'	Equal to ' ', without any uppercase conversion of the label
2	2	'GU'	Line type
4	8		Source user code (required)
13	8		Target user code Default: source user code

### Selection line of DSMS changes

Position	Length	Value	Meaning
1	1		Action code:
		'C'	Creation
		'M'	Modification
		'D'	Deletion
		' '	Creation or modification depending the database state
		'X'	Equal to ' ', without any uppercase conversion of the label
2	2	'GC'	Line type
4	3		Source product code (required) it must be left-justified
7	6		Source Change number (required)
13	3		Target product code must be left-justified
16	6		Target Change number Default: Source product/Change
22	8		Target user code Default: Source user

### Request line for multiple deletions

Multiple deletions may be requested at many levels:

- at the level of each type of selection
- for a given Transaction Set,
- at the level of the whole Set.

Position	Length	Value	Meaning
1	1	'B'	Multiple deletion request
2	2	'GA'	Deletion of whole Set
		'GS'	Deletion of set lines: 'GS' 'GB' 'GC' and 'GU'
		'GB'	Deletion of 'GB' Set line
		'GU'	Deletion of 'GU' Set line
		'GC'	Deletion of 'GC' Set line
4	10		Only if value 'GA' in columns 2 and 3.
		IIIIIIII	Set code
		'*****'	Deletion of the whole Sets in a development Database

### TRUP - Description of Steps

#### UPDATE OF THE ADMINISTRATION DATABASE: PTUG20

This step updates the administration Database in order to store selection parameters.

Code	Physical name	Type	Label
PAC7AR	Base dir. : AR	Input	Development database data file
PAC7AN	Base dir. : AN	Input	Development database index file
PAC7AY	nul	Output	Development Database extension data
PACGGU	Admin Base - Base dir. : GU	Input	Users file
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PACGGR	Admin Base - Base dir. : AR	Input/Output	Administration Database data file
PACGGN	Admin Base - Base dir. : AN	Input/Output	Administration Database index file
PACGGY	Admin Base - Base dir. : AY	Input/Output	Administration Database extension data file
PACGGJ	Journal dir. : AJ	Input/Output	Administration Database Journal file
PAC7MC	User input	Input	Parameters update transactions file
PAC7ME	Tmp dir. : WME	Input/Output	Work file
PAC7MY	Tmp dir. : WMY	Input/Output	Work file
PAC7TB	Tmp dir. : WTB	Input/Output	Work file
PAC7BM	Tmp dir. : WBM	Output	Parameters print request file
PAC7ET	User dir. : TRUPETG20	Report	Input validation
PAC7IE	User dir. : TRUPIEG20	Report	Administration Database update report
PAC7IF	User dir. : TRUPIFG20	Report	Administration Database update errors
PAC7DD	User dir. : TRUPDDG20	Report	Output report: check of line '*' in relation to the development Database
PAC7DE	User dir. : TRUPDEG20	Report	Output report: check of line '*' in relation to the administration Database

#### EXTRACTION OF THE ADMINISTRATION DATABASE: PTUG30

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Admin Base - Base dir. : AN	Input	Administration Database index
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7AY	null	Input	Administration Database extension data

Code	Physical name	Type	Label
PAC7MB	Tmp dir. : WMB	Input	Extraction request file
PAC7GL	Tmp dir. : WGL	Output	Target sessions list
PAC7UY	User dir. : UY	Output	Limited parameters file
PAC7DD	User dir. : TRUPDDG30	Report	'*' line validation report
PAC7TK	Tmp dir. : WTK	Input/Output	Work file

#### PRINTING OF SELECTION PARAMETERS: PTUG31

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages file
PAC7UY	User dir. : UY	Input	Limited parameters file
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data file
PAC7ET	User dir. : TRUPETG31	Report	Printing of the selection parameters list

#### PRINTING OF THE TARGET SESSIONS FILE: PTUG32

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7GL	Tmp dir. : WGL	Input	Target session
PAC7ET	User dir. : TRUPETG32	Report	Printing of the target session list

### TRUP - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      PAC/TRANSFER:
REM *      UPDATE OF THE TRANSFER PARAMETERS
REM * -----
REM *
REM * PAC/TRANSFER'S PROCESSING IS BASED ON THE USER-DEFINED
REM * PARAMETERS STORED IN THE ADMINISTRATION DATABASE.
REM * THESE PARAMETERS CONTROL THE VARIOUS PROCESSES OF THE
REM * FACILITY'S PROCEDURES.
REM *
REM * -----
REM *
<job id=TRUP>

<script language="VBScript">
Dim MyProc
MyProc = "TRUP"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

```

```
If c_error = 1 then Wscript.Quit (1) End If
```

```
Call Msg_Log (Array("1022" , "PTUG20"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = "NUL"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGJ") = Rep_AJOURNAL & "\AJ"
WshEnv("PACGGY") = Rep_ABASE & "\AY"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG20","PAC7BM",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTUG20","PAC7DD",Rep_USR & "\TRUPDDG20.txt")
Call BvpEnv("PTUG20","PAC7DE",Rep_USR & "\TRUPDEG20.txt")
Call BvpEnv("PTUG20","PAC7ET",Rep_USR & "\TRUPETG20.txt")
Call BvpEnv("PTUG20","PAC7IE",Rep_USR & "\TRUPIEG20.txt")
Call BvpEnv("PTUG20","PAC7IF",Rep_USR & "\TRUPIFG20.txt")
WshEnv("PAC7MC") = Fic Input
Call BvpEnv("PTUG20","PAC7ME",Rep_TMP & "\WME.tmp")
Call BvpEnv("PTUG20","PAC7MY",Rep_TMP & "\WMY")
Call BvpEnv("PTUG20","PAC7TB",Rep_TMP & "\WTB.tmp")
Return = WshShell.Run("BVPTUG20.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG20")
```

```
Call Msg_Log (Array("1022" , "PTUG30"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_ABASE & "\AN"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
WshEnv("PAC7AY") = "NUL"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG30","PAC7DD",Rep_USR & "\TRUPDDG30.txt")
Call BvpEnv("PTUG30","PAC7GL",Rep_TMP & "\WGL.tmp")
Call BvpEnv("PTUG30","PAC7MB",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTUG30","PAC7TK",Rep_TMP & "\WTK.tmp")
Call BvpEnv("PTUG30","PAC7UY",Rep_TMP & "\WUY.tmp")
Return = WshShell.Run("BVPTUG30.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG30")
```

```
Call Msg_Log (Array("1022" , "PTUG31"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
Call BvpEnv("PTUG31","PAC7UY",Rep_TMP & "\WUY.tmp")
Call BvpEnv("PTUG31","PAC7ET",Rep_USR & "\TRUPETG31.txt")
Return = WshShell.Run("BVPTUG31.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG31")
```

```
Call Msg_Log (Array("1022" , "PTUG32"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
Call BvpEnv("PTUG32","PAC7GL",Rep_TMP & "\WGL.tmp")
Call BvpEnv("PTUG32","PAC7ET",Rep_USR & "\TRUPETG32.txt")
Return = WshShell.Run("BVPTUG32.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG32")
```

```
Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)
```

```

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Print of Transfer Parameters

### TRED - Introduction

This procedure is used to print all the parameters for each development Database and transfer set.

It is possible to print all the parameters, or to print those of only one development Database.

### TRED - User Input

User identification line (required).

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
29	4		Selection of the development Database to be printed
		bbbb	Selection of a Database
		'****'	Selection of all Databases

### TRED - Description of Steps

CHECKING OF THE PROCESS REQUEST: PTUG28

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGR	Admin Base - Base dir. : AR	Input	Administration database data
PACGGN	Admin Base - Base dir. : AN	Input	Administration database index
PACGGU	Admin Base - Base dir. : GU	Input	Administration database users
PAC7AR	Admin Base - Base dir. : AR	Input	Administration database data
PAC7MB	User input	Input	Parameters print request
PAC7BM	Tmp dir. : WMB	Output	Parameters print request
PAC7DD	User dir. : TREDDDG28	Report	Output report: user code validity check
PAC7ET	User dir. : TREDETG28	Report	Output report: print request check

EXTRACTION OF THE ADMINISTRATION DATABASE: PTUG30

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Admin Base - Base dir. : AN	Input	Administration Database index
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7AY	null	Input	Administration Databasea extension data
PAC7MB	Tmp dir. : WMB	Input	Printing request file
PAC7GL	Tmp dir. : WGL	Output	Target sessions file
PAC7UY	Tmp dir. : WUY	Output	Limited parameters file
PAC7TK	Tmp dir. : WTK	Input/Output	Working file
PAC7DD	User dir. : TREDDDG30	Report	'*' line validation report

PRINTING OF SELECTION PARAMETERS: PTUG31

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7UY	Tmp dir. : WUY	Input	Limited parameters
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7ET	User dir. : TREDETG31	Report	List of selection parameters

PRINTING OF TARGET SESSIONS LIST: PTUG32

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7GL	Tmp dir. : WGL	Input	Target sessions
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7ET	User dir. : TREDETG32	Report	List of target sessions

**TRED - Execution Script**

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *     PAC/TRANSFER -

```

```

REM *          EDITING THE DATABASE PARAMETERS
REM * -----
REM *
REM * FOR ALL THE DATABASE OR ONE DATABASE
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM * -----
REM *
<job id=TRED>

<script language="VBScript">
Dim MyProc
MyProc = "TRED"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUG28"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG28","PAC7BM",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTUG28","PAC7DD",Rep_USR & "\TREDDDG28.txt")
Call BvpEnv("PTUG28","PAC7ET",Rep_USR & "\TREDETG28.txt")
WshEnv("PAC7MB") = Fic_Input
Return = WshShell.Run("BVPTUG28.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG28")

Call Msg_Log (Array("1022" , "PTUG30"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_ABASE & "\AN"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
WshEnv("PAC7AY") = "NUL"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG30","PAC7DD",Rep_USR & "\TREDDDG30.txt")
Call BvpEnv("PTUG30","PAC7GL",Rep_TMP & "\WGL.tmp")
Call BvpEnv("PTUG30","PAC7MB",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTUG30","PAC7TK",Rep_TMP & "\WTK.tmp")
Call BvpEnv("PTUG30","PAC7UY",Rep_TMP & "\WUY.tmp")
Return = WshShell.Run("BVPTUG30.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG30")

Call Msg_Log (Array("1022" , "PTUG31"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
Call BvpEnv("PTUG31","PAC7UY",Rep_TMP & "\WUY.tmp")
Call BvpEnv("PTUG31","PAC7ET",Rep_USR & "\TREDETG31.txt")
Return = WshShell.Run("BVPTUG31.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG31")

Call Msg_Log (Array("1022" , "PTUG32"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"

```



```

WshEnv("PAC7AR") = Rep_ABASE & "\AR"
Call BvpEnv("PTUG32","PAC7GL",Rep_TMP & "\WGL.tmp")
Call BvpEnv("PTUG32","PAC7ET",Rep_USR & "\TREDETG32.txt")
Return = WshShell.Run("BVPTUG32.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG32")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## TRJC - Compression of Archived Journal

### TRJC - Introduction

From the VisualAge Pacbase archived Journal, the TRJC procedure produces a compressed Journal containing only useful transactions, by eliminating the intermediary transactions which are known to be useless for the transfer.

User input may include an interval of dates and/or session numbers in order to limit transfer processing to the archived Journal's transactions belonging to that interval only.

If there is no optional user input, the compression is carried out on the complete archived Journal.

You also have the possibility to erase user codes and/or Change numbers from the archived Journal. As a result, a higher rate of compression is obtained.

In this case, transfer criteria based on user codes and Changes can no longer be used.

Journal compressing is not required; it depends on the site's requirements (Journal volume, frequency of transfer operations, etc).

### EXECUTION CONDITIONS

None.

### RESULT

A smaller archived Journal including 'useful' transactions only.

### PRINTED REPORT

Statistical data on the TRJC execution.

### TRJC - User Input

User identification line (required)

Position	Length	Value	Meaning
2	1	'*'	Line code

Position	Length	Value	Meaning
3	8	uuuuuuuu	User code
11	8	pppppppp	Password

#### Options

Position	Length	Value	Meaning
1	1		Deletion of user codes
		'0'	Yes
		'1'	No
2	1		Deletion of Change numbers
		'0'	Yes
		'1'	No
3	4		Start session number
7	4		End session number
11	8		Start date in the form CCYYMMDD
19	8		End date in the form CCYYMMDD

### TRJC - Description of Steps

#### COMPRESSION (FIRST PHASE): PTUG04

Code	Physical Name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	LError messages
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AN	Base dir. : AN	Input	Development Database index
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7MB	User input	Input	User input
PAC7BM	Tmp dir. : WMB	Output	User input
PAC7DD	User dir. : TRJCDDG04	Report	Batch procedures' execution report

#### COMPRESSION (FIRST PHASE): PTUG05

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7PJ	Save dir. : PJ	Input	Sequential image of the development Database
PAC7AN	Base dir. : AN	Input	Development Database index
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index

Code	Physical name	Type	Label
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7MB	User input	Input	User Input
PAC7GP	Tmp dir. : WGP	Output	Temporary journal
PAC7ET	User dir. : TRJCETG05	Report	Input validation
PAC7DD	User dir. : TRJCDDG05	Report	Batch procedures error status

#### COMPRESSION (SECOND PHASE): PTUG06

Code	Physical name	Type	Label
PAC7GP	Tmp dir. : WGP	Input	Temporary Journal
PAC7PK	Tmp dir. : WPK	Output	Compressed sequential journal

#### CLASSIFICATION OF DELETIONS/CREATIONS: PTUG07

Code	Physical name	Type	Label
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7PK	Tmp dir. : WPK	Input	Temporary journal
PAC7PL	Save dir. : JT	Output	Compressed sequential journal

### TRJC - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *     PAC/TRANSFER -
REM *     COMPRESSION OF ARCHIVED JOURNAL
REM * -----
REM *
REM *
REM * FROM THE DATABASE ARCHIVED JOURNAL, THE TRJC
REM * PROCEDURE PRODUCES A COMPRESSED JOURNAL
REM * CONTAINING ONLY USEFUL TRANSACTIONS,
REM * BY ELIMINATING THE INTERMEDIARY TRANSACTIONS
REM * WHICH ARE KNOWN TO BE USELESS FOR THE TRANSFER.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM * - COMMAND LINE :
REM * COL 1  : DELETION OF USER CODES:
REM *         '0'  YES
REM *         '1'  NO
REM * COL 2  : DELETION OF CHANGE NUMBERS:
REM *         '0'  YES
REM *         '1'  NO
REM * COL 3  : (4 CAR.) START SESSION NUMBER
REM * COL 7  : (4 CAR.) END SESSION NUMBER
REM *
REM * COL 11 : (8 CAR.) START DATE IN THE FORM CCYYMMDD
REM * COL 19 : (8 CAR.) END DATE IN THE FORM CCYYMMDD
REM * -----

```

```

REM *
<job id=TRJC>

<script language="VBScript">
Dim MyProc
MyProc = "TRJC"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUG04"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PTUG04","PAC7DD",Rep_USR & "\TRJCDDG04.txt")
Call BvpEnv("PTUG04","PAC7BM",Rep_TMP & "\WMB.tmp")
Return = WshShell.Run("BVPTUG04.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG04")

Call Msg_Log (Array("1022" , "PTUG05"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG05","PAC7DD",Rep_USR & "\TRJCDDG05.txt")
Call BvpEnv("PTUG05","PAC7ET",Rep_USR & "\TRJCETG05.txt")
Call BvpEnv("PTUG05","PAC7GP",Rep_TMP & "\WGP.tmp")
Call BvpEnv("PTUG05","PAC7MB",Rep_TMP & "\WMB.tmp")
WshEnv("PAC7PJ") = Rep_SAVE & "\PJ"
Return = WshShell.Run("BVPTUG05.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG05")

Call Msg_Log (Array("1022" , "PTUG06"))
'-----
Call BvpEnv("PTUG06","PAC7GP",Rep_TMP & "\WGP.tmp")
Call BvpEnv("PTUG06","PAC7PK",Rep_TMP & "\WPK.tmp")
Return = WshShell.Run("BVPTUG06.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG06")

Call Msg_Log (Array("1022" , "PTUG07"))
'-----
WshEnv("PAC7AN") = Rep_BASE & "\AN"
Call BvpEnv("PTUG07","PAC7PK",Rep_TMP & "\WPK.tmp")
WshEnv("PAC7PL") = Rep_SAVE & "\JT"
Return = WshShell.Run("BVPTUG07.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG07")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

```

```
</script>  
</job>
```

## TRPF - Creation of the Transfer File

### TRPF - Introduction

From the archived Journal --whether compressed or not, depending on the site's choice and according to the contents of the Parameter file-- the TRPF procedure produces a Transfer file, which has the following characteristics:

- The only transactions processed are those meeting the source selection parameters (sessions, Libraries, users, Changes),
- The values of the selected parameters are replaced by those of the target parameters specified in the Parameter file,
- The selected transactions of the archived journal are duplicated as many times as there are target session numbers and target Library codes.

The file may contain the transactions for one, several or all of the Sets.

### EXECUTION CONDITIONS

None.

### RESULT

The TRPF procedure produces a Transfer file, which will be used by the TRRP procedure.

### TRPF - User Input

User identification line (required)

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password

Transaction Set for processing selection line (required)

Position	Length	Value	Meaning
2	2	'LT'	
4	10	llllllllll	Code of Transaction Set to process
		*****	Selection of all Sets

### NOTE

The selection of all Sets necessarily implies that only one LT-type line be entered (with the value '\*\*\*\*\*' in Positions 4 to 13).

**TRPF - Description of Steps**  
PROCESSING REQUEST CHECK: PTUG27

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7MB	User input	Input	Parameters extraction request
PAC7BM	Tmp dir. : WBM	Output	Parameters extraction request
PAC7DD	User dir. : TRPFDDG27	Report	Output report: user code validity check
PAC7ET	User dir. : TRPFETG27	Report	Output report: extraction request check

EXTRACTION OF THE ADMINISTRATION DATABASE: PTUG30

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Admin Base - Base dir. : AN	Input	Administration Database index
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7AY	null	Input	Administration Database extension data
PAC7MB	Tmp dir. : WBM	Input	EXtraction request
PAC7GL	Tmp dir. : WGL	Output	List of target sessions
PAC7UY	Tmp dir. : UY	Output	Limited parameters for TRRP processing
PAC7DD	User dir. : TRPFDDG30	Report	'*' line validation report
PAC7TK	Tmp dir. : WTK	Output	Work file

### Indexation of UY file: PTUG39

Code	Physical name	Type	Label
PAC7UY	Tmp dir. : WUY	Input	Limited parameters for TRRP processes
PAC7YU	User dir. : WYU	Output	Limited parameters

### CREATION OF TRANSFERS FILE: PTUG50

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7JT	Save dir. : PJ	Input	Sequential or compressed Journal
PAC7MB	Tmp dir. : WBM	Input	User input
PAC7UY	User dir. : WYU	Input	Limited parameters
PAC7TJ	Save dir. : TJ	Output	Transfers file
PAC7DD	User dir. : TRPFDDG50	Report	User line validation report
PAC7ER	User dir. : TRPFERG50	Report	List of user input
PAC7ET	User dir. : TRPFETG50	Report	Statistics on transfers

### TRPF - Execution Script

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *     PAC/TRANSFER -
REM *     CREATING THE TRANSFER FILE
REM * -----
REM *
REM * FROM THE ARCHIVED JOURNAL THE TRPF PROCEDURE PRODUCES
REM * A TRANSFER FILE.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM * - COMMAND LINE :
REM * COL 2  : 'LT'
REM * COL 4  : (5 CAR.) TRANSACTION SET FOR PROCESSING CODE.
REM *           IF SELECTION OF ALL SETS '*****'
REM *
REM * -----
REM *
<job id=TRPF>

<script language="VBScript">
Dim MyProc
MyProc = "TRPF"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

```

```

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUG27"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG27","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTUG27","PAC7DD",Rep_USR & "\TRPFDDG27.txt")
Call BvpEnv("PTUG27","PAC7ET",Rep_USR & "\TRPFETG27.txt")
WshEnv("PAC7MB") = Fic_Input
Return = WshShell.Run("BVPTUG27.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG27")

Call Msg_Log (Array("1022" , "PTUG30"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_ABASE & "\AN"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
WshEnv("PAC7AY") = "NUL"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG30","PAC7DD",Rep_USR & "\TRPFDDG30.txt")
Call BvpEnv("PTUG30","PAC7GL",Rep_TMP & "\WGL.tmp")
Call BvpEnv("PTUG30","PAC7MB",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTUG30","PAC7TK",Rep_TMP & "\WTK.tmp")
Call BvpEnv("PTUG30","PAC7UY",Rep_TMP & "\WUY.tmp")
Return = WshShell.Run("BVPTUG30.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG30")

If MyUser = "" then
Rep_RI = Rep1_USR
Else
Rep_RI = Rep1_USR & "\" & MyUser
End If

Call Msg_Log (Array("1022" , "PTUG39"))
'-----
Call BvpEnv("PTUG39","PAC7UY",Rep_TMP & "\WUY.tmp")
WshEnv("PAC7YU") = Rep_RI & "\UY"
Return = WshShell.Run("BVPTUG39.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG39")

Call Msg_Log (Array("1022" , "PTUG50"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG50","PAC7DD",Rep_USR & "\TRPFDDG50.txt")
Call BvpEnv("PTUG50","PAC7ER",Rep_USR & "\TRPFER50.txt")
Call BvpEnv("PTUG50","PAC7ET",Rep_USR & "\TRPFETG50.txt")
WshEnv("PAC7JT") = Rep_SAVE & "\PJ"
Call BvpEnv("PTUG50","PAC7MB",Rep_TMP & "\WBM.tmp")
WshEnv("PAC7TJ") = Rep_SAVE & "\TJ"
WshEnv("PAC7UY") = Rep_RI & "\UY"
Return = WshShell.Run("BVPTUG50.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG50")

Call Msg_Log (Array("1024"))
'-----

```



```

Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Preparing DSMS Environment

### TRDU - Introduction

The DSMS-Environment Preparation procedure (TRDU) must be used when the VisualAge Pacbase Database is under DSMS control, and when source criteria include a selected Change number.

TRDU can operate for either one or all of the Sets defined in the Parameters file.

The VisualAge Pacbase authorizations notified for the target Change(s) must include the authorizations of the source Change(s). Otherwise, transfers in VA Pac will be rejected.

Compliance to this requirement is ensured by the TRDU procedure which temporarily aligns the target Change(s) with the source Changes regarding their VisualAge Pacbase authorizations.

### NOTE

When source criteria do not include a selected Change number, TRDU cannot be applied because of the bulk of Changes involved. In this case, manual checks and alignments will be necessary.

TRDU takes into account the following additional parameters:

- If the Parameters file specifies the transfer of transactions from one source Library to one or more target Libraries, the target Change must authorize the transactions of the target Library(ies).
- If the Parameters file specifies the transfer of transactions from one source user to a target user, the target Change number must authorize the transactions under this target user code.

The TRDU procedure produces two files:

- A DSMS update-transaction file to allow target Change(s) to accept updates made on the source Change(s).  
Also, all VA Pac authorizations attached to source Changes are withdrawn. This means that during the transfer operation, no update made in VA Pac in relation to those Changes will be authorized.  
This update must be executed BEFORE the transfer operation.
- A DSMS update transactions file to set the authorizations of the source and target Changes to their initial state.  
This update must be executed AFTER the transfers are introduced in the VA Pac Database.

### EXECUTION CONDITIONS

None.

## RESULTS

Two DSMS batch update-transaction files, one of which should be applied before the transfers, the other after all transfers.

### **TRDU - User Input**

User identification line (required)

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password

Transaction set selection line (required)

Position	Length	Value	Meaning
2	2	'LT'	
4	10	llllllllll	Selected Transaction Set code
		*****	Selection of all Sets

One and only one LT-type line is required.

### **TRDU - Description of Steps**

CHECK ON PROCESSING REQUEST: PTUG26

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database data
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database index
PAC7GU	Admin Base - Base dir. : GU	Input	Administration Database index
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7MB	User input	Input	Parameters extraction request
PAC7BM	Tmp dir. : WBM	Output	Parameters extraction request
PAC7ET	User dir. : TRDUETG26	Report	Output report: check on user code validity
PAC7DD	User dir. : TRDUDDG26	Report	Output report: check on print request

### EXTRACTION OF THE ADMINISTRATION DATABASE: PTUG30

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages

Code	Physical name	Type	Label
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AN	Admin Base - Base dir. : AN	Input	Administration Database index
PAC7AR	Admin Base - Base dir. : AR	Input	Administration Database data
PAC7AY	nul	Input	Administration Database extension data
PAC7MB	Tmp dir. : WBM	Input	Extraction request
PAC7GL	Tmp dir. : WGL	Output	Target sessions
PAC7UY	Tmp dir. : WUY	Output	Limited parameters
PAC7DD	User dir. : TRDUDDG30	Report	Report output: '*' line validation
PAC7TK	Tmp dir. : WTK	Input/Output	Work file

#### Indexation of UY file: PTUG39

Code	Physical name	Type	Label
PAC7UY	Tmp dir. : WUY	Input	Limited parameters for TRRP processes
PAC7YU	User dir. : WYU	Output	Limited parameters

#### SELECTION OF SETS: PTUG42

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7UY	User dir. : UY	Input	Limited parameters
PAC7MB	Tmp dir. : WBM	Input	User input
PAC7BM	Tmp dir. : WBM2	Output	Sets file
PAC7DD	User dir. : TRDUDDG42	Report	Report output: check on users
PAC7ET	User dir. : TRDUETG42	Report	Report output: check on extraction

## DSMS PREPARATION BEFORE TRANSFER: PTUG44

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7UY	User dir. : UY	Input	Limited parameters
PACDDC	Base dir. : DC	Input	Elements of the product (DSMS)
PAC7MB	Tmp dir. : WBM2	Input	Batch transactions
PAC7CI	Tmp dir. : WCI	Output	Source/target initial state creation transactions
PAC7SI	Tmp dir. : WSI	Output	Source/target initial state deletion transactions
PAC7GC	Tmp dir. : WGC	Output	Target-change authorization preparation file
PAC7ET	User dir. : TRDUETG44	Report	Report

## GENERATION OF TARGET CHANGE TRANSACTIONS: PTUG46

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7GC	Tmp dir. : WGC	Input	Preparation file for target-change authorizations
PAC7CC	Tmp dir. : WCC	Output	Target creation transactions before transfer
PAC7SC	Tmp dir. : WSC	Output	Target deletion transactions after transfer
PAC7ET	User dir. : TRDUETG46	Report	Report output

## TRDU - Execution Script

```

REM * -----
REM *      VISUALAGE PACBASE
REM *
REM * -----
REM *      PAC/TRANSFER -
REM *      PREPARING THE DSMS ENVIRONMENT
REM * -----
REM *
REM * THE DSMS-ENVIRONMENT PREPARATION PROCEDURE
REM * (TRDU) MUST BE USED WHEN THE DEVELOPMENT DATABASE
REM * IS UNDER DSMS CONTROL, AND WHEN SOURCE CRITERIA INCLUDE
REM * A SELECTED CHANGE NUMBER.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM * - COMMAND LINE :
REM * COL 2  : 'LT'
REM * COL 4  : (5 CAR.) SELECTED TRANSACTION SET CODE.
REM *          IF SELECTION OF ALL SETS '*****'
REM *
REM * -----
REM *
<job id=TRDU>

```

```

<script language="VBScript">
Dim MyProc
MyProc = "TRDU"
</script>

<script language="VBScript" src="INIT.vbs"/>

<script language="VBScript">

If c_error = 1 then Wscript.Quit (1) End If

Call Msg_Log (Array("1022" , "PTUG26"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG26","PAC7BM",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTUG26","PAC7DD",Rep_USR & "\TRDUDDG26.txt")
Call BvpEnv("PTUG26","PAC7ET",Rep_USR & "\TRDUETG26.txt")
WshEnv("PAC7MB") = Fic_Input
Return = WshShell.Run("BVPTUG26.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG26")

Call Msg_Log (Array("1022" , "PTUG30"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_ABASE & "\AN"
WshEnv("PAC7AR") = Rep_ABASE & "\AR"
WshEnv("PAC7AY") = "NUL"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG30","PAC7DD",Rep_USR & "\TRDUDDG30.txt")
Call BvpEnv("PTUG30","PAC7GL",Rep_TMP & "\WGL.tmp")
Call BvpEnv("PTUG30","PAC7MB",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTUG30","PAC7TK",Rep_TMP & "\WTK.tmp")
Call BvpEnv("PTUG30","PAC7UY",Rep_TMP & "\WUY.tmp")
Return = WshShell.Run("BVPTUG30.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG30")

Call Msg_Log (Array("1022" , "PTUG39"))
'-----
Call BvpEnv("PTUG39","PAC7UY",Rep_TMP & "\WUY.tmp")
Call BvpEnv("PTUG39","PAC7YU",RepT_USR & "\WYU.txt")
Return = WshShell.Run("BVPTUG39.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG39")

Call Msg_Log (Array("1022" , "PTUG42"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG42","PAC7DD",Rep_USR & "\TRDUDDG42.txt")
Call BvpEnv("PTUG42","PAC7ET",Rep_USR & "\TRDUETG42.txt")
Call BvpEnv("PTUG42","PAC7BM",Rep_TMP & "\WBM2.tmp")
Call BvpEnv("PTUG42","PAC7MB",Rep_TMP & "\WBM.tmp")
Call BvpEnv("PTUG42","PAC7YU",RepT_USR & "\WYU.txt")
Return = WshShell.Run("BVPTUG42.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG42")

```

```

Call Msg_Log (Array("1022" , "PTUG44"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACDDC") = Rep_BASE & "\DC"
Call BvpEnv("PTUG44","PAC7MB",Rep_TMP & "\WBM2.tmp")
Call BvpEnv("PTUG44","PAC7CI",Rep_TMP & "\WCI.tmp")
Call BvpEnv("PTUG44","PAC7GC",Rep_TMP & "\WGC.tmp")
Call BvpEnv("PTUG44","PAC7SI",Rep_TMP & "\WSI.tmp")
Call BvpEnv("PTUG44","PAC7YU",Rep_USR & "\WYU.txt")
Call BvpEnv("PTUG44","PAC7ET",Rep_USR & "\TRDUETG44.txt")
Return = WshShell.Run("BVPTUG44.EXE" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG44")

Call Msg_Log (Array("1022" , "PTUG46"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
Call BvpEnv("PTUG46","PAC7ET",Rep_USR & "\TRDUETG46.txt")
Call BvpEnv("PTUG46","PAC7CC",Rep_TMP & "\WCC.tmp")
Call BvpEnv("PTUG46","PAC7GC",Rep_TMP & "\WGC.tmp")
Call BvpEnv("PTUG46","PAC7SC",Rep_TMP & "\WSC.tmp")
Return = WshShell.Run("BVPTUG46.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG46")

Call Msg_Log (Array("1022" , "COPY"))
'-----
'COPY SI + CC ==> TRDUAV
Call CopMfil (Rep_TMP & "\WCC.tmp" ,Rep_TMP & "\WSI.tmp" , Rep_USR & "\TRDUav.txt")
'COPY SC + CI ==> TRDUAP
Call CopMfil (Rep_TMP & "\WSC.tmp" ,Rep_TMP & "\WCI.tmp" , Rep_USR & "\TRDUap.txt")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## DSMS Update Before Database Update

This update is performed using, as input of the DUPT procedure, the first file produced by the DSMS authorization update process.

## TRRP - Generation of Transfer Transactions

### TRRP - Introduction

Once the transfer file has been built, the TRTP procedure generates transfer transactions. These have the same format as batch update transactions applicable in the development Database by the UPDT procedure.

The transaction generation may be performed on the whole of the Transfer file or on selected parts, based on the following criteria:

1. Transaction Set (required),

## 2. Target Session.

Values for both criteria are indicated on the user identification line '\*'. Sort options are also available and must be entered in a J-type line.

Each combination of criteria corresponds to a TRRP execution mode.

### STANDARD EXECUTION (BY TRANSACTION SET)

- Transaction Set code different from '\*\*\*\*\*'
- Absence of target session

TRRP considers transactions that belong to the selected Transaction Set only. Since you have not selected a target session, transactions are generated for all target sessions found in the Parameters file regarding this Set.

However, you must run as many TRRP executions as there are target sessions:

A specific attribute -- SESSION PROCESSED -- is automatically positioned in the Parameter file once all transactions have been generated for a given session.

As a result, if this attribute is positioned for a given session (see also the other execution modes, described in Paragraphs 2 and 3), transactions for that session will not be generated and TRRP will automatically proceed with the next target session, as listed in the Parameter file.

This execution mode brings an automatic control over your transfer operations since it avoids duplicating transactions which could otherwise happen when prior TRRP executions have been run.

The TRRP standard execution mode is therefore recommended for sites where PacTransfer operations involve large volumes of transactions.

A Warning message will tell you when all sessions have been dealt with.

Generated transactions must then be used by the VisualAge Pacbase batch update procedure (UPDT).

You may prefer to concatenate all TRRP subsequent outputs and run the UPDT procedure only once.

### EXECUTION BY SESSION

- Transaction Set code different from '\*\*\*\*\*'
- Target session: 'nnnnT' or '\*\*\*\*\*'

TRRP considers transactions that belong to the selected Transaction Set only.

- If you have selected a target session, transactions are generated for this session only.
- If you have selected all sessions ('\*\*\*\*\*'), transactions are systematically generated for all target sessions, all in one TRRP execution.

A specific attribute -- SESSION PROCESSED -- is automatically positioned in the Parameters file once all transactions have been generated for a given session.

Generated transactions must then be used by the VA Pac batch update procedure (UPDT).

## EXECUTION MODE FOR ALL SETS AND ALL TARGET SESSIONS

- Transaction Set code: '\*\*\*\*\*'
- Target session number: '\*\*\*\*\*'

Transactions are systematically generated for all Sets and for all their respective target sessions.

**NOTE:** A specific attribute -- SESSION PROCESSED -- is automatically positioned in the Parameters file once all transactions have been generated for a given session.

Generated transactions must then be used by the VA Pac batch update procedure (UPDT).

## EXECUTION CONDITIONS

The Transfer file must exist (created by the TRPF procedure). Authorization level 4 is required to run a TRRP execution.

## RESULT

Transfer transactions formatted for the VA Pac UPDT batch update procedure.

### **TRRP - User Input**

User identification line (required)

Position	Length	Value	Meaning
2	1	'*'	Line code
3	8	uuuuuuuu	User code
11	8	pppppppp	Password
22	5		Selection of target session(s):
		blank	. All target sessions (default), one session processed per TRRP execution. This value cannot be used when all Transaction sets are selected
		nnnnT	. Target session number (required)
		'*****'	. All target sessions processed in one TRRP execution
33	10		Selection of Transaction Set(s):
		llllllllll	Transaction Set code
		*****	All Transaction Sets
43	1		Formatting for UPDT
		'1'	Formatting
		' '	No formatting
44	1		Formatting for UPDP
		'1'	Formatting
		' '	No formatting



Sort Options line

Position	Length	Value	Meaning
2	1	'J'	Line code
4	1	' '	Chronological list
		'N'	No chronological list
5	1	' '	List by user
		'N'	No list by user
6	1	' '	List by library
		'N'	No list by library

## TRRP - Description of Steps

PREPARATION OF EXTRACTION: PTUG60

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database users
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7JT	Base dir. : TJ	Input	Sequential or compressed Journal
PAC7MB	User input	Input	User input
PAC7UY	User dir.: WYU	Input	Limited parameters
PAC7BM	Tmp dir. : WMB	Output	Extraction request for PACX
PAC7PJ	Tmp dir. : WPJ	Output	Temporary file
PAC7ET	User dir. : TRRPETG60	Report	Statistics on transfer
PAC7DD	User dir. : TRRPDDG60	Report	Check on user

Return codes:

- 0: No error
- 8: Critical error (detailed in PAC7DD)

EXTRACTION: PACX

This step extracts the transactions according to user inputs

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AN	Base dir. : AN	Input	Development Database index
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7AY	Base dir. : AY	Input	Development Database extension data
PACGGN	Admin Base - Base dir. : AN	Input	Administration Database index
PACGGR	Admin Base - Base dir. : AR	Input	Administration Database data

Code	Physical name	Type	Label
PACGGU	Admin Base - Base dir. : GU	Input	Administration Database user file
PAC7PJ	Save dir. : PJ	Input	Transactions selected by the Journal
PAC7MB	Tmp dir. : WMB	Input	User input
PAC7BM	Tmp dir. : WBM	Input/Output	User input
SYSEXT	Tmp dir. : WXT	Input/Output	Work file
PAC7MJ	Tmp dir. : WMJ	Input/Output	Journal transactions (EXPJ)
PAC7WD	Tmp dir. : WWD	Input/Output	Extracted transactions
PAC7MV	Tmp dir. : WMV	Output	Extracted transactions for UPDT
PAC7GY	Tmp dir. : WGY	Output	Extracted transactions for UPDP
PAC7IA	User dir. : TRRPIAPAC	Report	General program-stream printout
PAC7DD	User dir. : TRRPDDPAC	Report	Printing of errors list on input transactions
PAC7EE	User dir. : TRRPEEPAC	Report	Extractions report
PAC7EP	User dir. : TRRPEPPAC	Report	Extractions report
PAC7EQ	User dir. : TRRPEQPAC	Report	Extractions report
PAC7EZ	User dir. : TRRPEZPAC	Report	Extractions report

Return codes:

- 0: No error
- 8: Critical error (detailed in PAC7DD)

#### POSITIONING THE 'PROCESSING SESSION' ATTRIBUTE: PTUG61

Code	Physical name	Type	Label
PAC7AE	System - Skel dir. : AE	Input	Error messages
PAC7AR	Base dir. : AR	Input	Development Database data
PAC7MB	User input	Input	User input
PAC7UY	User dir. : WYU	Input/Output	Limited parameters
PAC7ET	User dir. : TRRPETG61	Report	Transfer statistics

### **TRRP - Execution Script**

```

REM * -----
REM *     VISUALAGE PACBASE
REM *
REM * -----
REM *     PAC/TRANSFER -
REM *     GENERATING THE TRANSFER TRANSACTIONS
REM * -----
REM *
REM * ONCE THE TRANSFER FILE HAS BEEN BUILT, THE TRRP
REM * PROCEDURE GENERATES TRANSFER TRANSACTIONS. THESE HAVE
REM * THE SAME FORMAT AS BATCH UPDATE TRANSACTIONS
REM * APPLICABLE BY THE UPDT PROCEDURE.
REM *
REM * INPUT :
REM * - USER IDENTIFICATION LINE (REQUIRED)
REM *   COL 2 : '*'

```

```

REM *      COL 3 : USERIDXX
REM *      COL 11 : PASSWORD
REM *      COL 22 : (5 CAR.) SELECTION OF TARGET SESSION(S)
REM *      COL 40 : (5 CAR.) SELECTION OF TRANSACTION SET(S)
REM * - COMMAND LINE :
REM * COL 2 : 'J' LINE CODE
REM * COL 4 : ' ' CHRONOLOGICAL LIST
REM *      'N' NO CHRONOLOGICAL LIST
REM * COL 5 : ' ' LIST BY USER
REM *      'N' NO LIST BY USER
REM * COL 6 : ' ' LIST BY LIBRARY
REM *      'N' NO LIST BY LIBRARY
REM * -----
REM *
<job id=TRRP>

```

```

<script language="VBScript">
Dim MyProc
MyProc = "TRRP"
</script>

```

```

<script language="VBScript" src="INIT.vbs"/>

```

```

<script language="VBScript">

```

```

If c_error = 1 then Wscript.Quit (1) End If

```

```

If MyUser = "" then
Rep_RI = Rep1_USR
Else
Rep_RI = Rep1_USR & "\" & MyUser
End If

```

```

Call Msg_Log (Array("1022" , "PTUG60"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PTUG60","PAC7BM",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PTUG60","PAC7DD",Rep_USR & "\TRRPDDG60.txt")
Call BvpEnv("PTUG60","PAC7ET",Rep_USR & "\TRRPETG60.txt")
WshEnv("PAC7JT") = Rep_BASE & "\TJ"
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PTUG60","PAC7PJ",Rep_TMP & "\WPJ.tmp")
Call BvpEnv("PTUG60","PAC7UY",Rep_USR & "\WYU.txt")
Return = WshShell.Run("BVPTUG60.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG60")

```

```

Call Msg_Log (Array("1022" , "PACX"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AN") = Rep_BASE & "\AN"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
WshEnv("PAC7AY") = Rep_BASE & "\AY"
WshEnv("PACGGN") = Rep_ABASE & "\AN"
WshEnv("PACGGR") = Rep_ABASE & "\AR"
WshEnv("PACGGU") = Rep_ABASE & "\GU"
Call BvpEnv("PACX","PAC7DD",Rep_USR & "\TRRPDDPAC.txt")
Call BvpEnv("PACX","PAC7EE",Rep_USR & "\TRRPEEPAC.txt")
Call BvpEnv("PACX","PAC7EP",Rep_USR & "\TRRPEPPAC.txt")
Call BvpEnv("PACX","PAC7EQ",Rep_USR & "\TRRPEQPAC.txt")
Call BvpEnv("PACX","PAC7EZ",Rep_USR & "\TRRPEZPAC.txt")
Call BvpEnv("PACX","PAC7IA",Rep_USR & "\TRRPIAPAC.txt")
Call BvpEnv("PACX","PAC7MV",Rep_TMP & "\WMV.tmp")

```

```

Call BvpEnv("PACX","PAC7BM",Rep_TMP & "\WBM.tmp")
WshEnv("PAC7GY") = "NUL"
Call BvpEnv("PACX","PAC7MB",Rep_TMP & "\WMB.tmp")
Call BvpEnv("PACX","PAC7MJ",Rep_TMP & "\WMJ.tmp")
WshEnv("PAC7MM") = "NUL"
WshEnv("PAC7MR") = "NUL"
Call BvpEnv("PACX","PAC7PJ",Rep_TMP & "\WPJ.tmp")
WshEnv("PAC7RE") = "NUL"
WshEnv("PAC7RM") = "NUL"
WshEnv("PAC7TD") = "NUL"
WshEnv("PAC7TE") = "NUL"
WshEnv("PAC7UE") = "NUL"
Call BvpEnv("PACX","PAC7WD",Rep_TMP & "\WWD.tmp")
Call BvpEnv("PACX","SYSEXT",Rep_TMP & "\WSY.tmp")
Return = WshShell.Run("BVPACX.exe" , 1, TRUE)
Call Err_Cod(Return , 4 , "PACX")

Call Msg_Log (Array("1022" , "PTUG61"))
'-----
WshEnv("PAC7AE") = Rep_SKEL & "\AE"
WshEnv("PAC7AR") = Rep_BASE & "\AR"
Call BvpEnv("PTUG61","PAC7ET",Rep_USR & "\TRRPETG61.txt")
WshEnv("PAC7MB") = Fic_Input
Call BvpEnv("PTUG61","PAC7UY",RepT_USR & "\WYU.txt")
Return = WshShell.Run("BVPTUG61.exe" , 1, TRUE)
Call Err_Cod(Return , 0 , "PTUG61")

Call Msg_Log (Array("1024"))
'-----
Call DeleteFldr (Rep_TMP)

Call Msg_Log (Array("1023"))
'-----
Wscript.Quit (Return)

</script>
</job>

```

## Update of the Development Database

The VisualAge Pacbase Database is updated via the UPDT procedure, taking the Transfer file -- created by the TRRP procedure -- as input.

In the case of a 'standard processing' of the generation of transfer transactions (see previous subchapter), the following procedures may be executed several times:

- . TRRP (Generation of transfer transactions),
- . UPDT (Update of the VA Pac Database).

## Reinitialization of DSMS Environment

This procedure resets update authorizations on the selected source and target Changes as they were before the transfer operation.

This initial state is obtained by running the DSMS update procedure (DUPT), using as input transactions the contents of the file resulting from the DSMS Environment Preparation procedure (TRDU).

---

## ASCII Sort

### PEAS - User Parameters, ASCII Sort

#### PEAS - Introduction

The PEAS sorts the user parameter backup file (PE) as an ASCII sequence. It thus makes it possible to use this backup on ASCII platforms.

This procedure does not require any execution condition nor user input.

#### PEAS - Description of Steps

ASCII SORT ON PE FILE: PTU903

.Input backup file:

-Original user parameters  
PAC7IN

.Output backup file:

-User parameters sorted in ASCII sequence  
PAC7OU

#### PEAS - Execution Script

```
REM * -----  
REM *      VISUALAGE PACBASE  
REM *  
REM * -----  
<job id=PEAS>  
  
<script language="VBScript">  
Dim MyProc  
MyProc = "PEAS"  
</script>  
  
<script language="VBScript" src="INIT.vbs"/>  
  
<script language="VBScript">  
  
If c_error = 1 then Wscript.Quit (1) End If  
  
Call Msg_Log (Array("1022" , "PTU903"))  
'-----  
Call BvpEnv("PTU903","PAC7IN",Rep_USR & "\WIN.txt")  
  
Call BvpEnv("PTU903","PAC7OU",Rep_USR & "\WOU.txt")  
  
Return = WshShell.Run("BVptu903.exe" , 1, TRUE)  
Call Err_Cod(Return , 0 , "ptu903")  
  
Call Msg_Log (Array("1023"))  
'-----  
Wscript.Quit (Return)  
  
</script>  
</job>
```

### PGAS - Generation-Request Sort, ASCII Format

#### PGAS - Introduction

The PGAS procedure sorts the generation-request backup file (PG) as an ASCII sequence. It thus makes it possible to use this backup on ASCII platforms.

This procedure does not require any execution condition nor user input.

## PGAS - Description of Steps

ASCII SORT ON PG FILE: PTU906

.Input backup file:

-Original generation requests  
PAC7IN

.Output backup file:

-Generation requests sorted as an ASCII sequence  
PAC70U

## PGAS - Execution Script

```
REM * -----  
REM *      VISUALAGE PACBASE  
REM *  
REM * -----  
<job id=PGAS>  
  
<script language="VBScript">  
Dim MyProc  
MyProc = "PGAS"  
</script>  
  
<script language="VBScript" src="INIT.vbs"/>  
  
<script language="VBScript">  
  
If c_error = 1 then Wscript.Quit (1) End If  
  
Call Msg_Log (Array("1022" , "PTU906"))  
'-----  
Call BvpEnv("PTU906","PAC7IN",Rep_USR & "\WIN.txt")  
  
Call BvpEnv("PTU906","PAC70U",Rep_USR & "\WOU.txt")  
  
Return = WshShell.Run("BVptu906.exe" , 1, TRUE)  
Call Err_Cod(Return , 0 , "ptu906")  
  
Call Msg_Log (Array("1023"))  
'-----  
Wscript.Quit (Return)  
  
</script>  
</job>
```

## PPAS - Environment Sort, ASCII Format

### PPAS - Introduction

The PPAS procedure sorts the environment backup file (PP) as an ASCII sequence. It is then possible to use this backup on ASCII platforms.

This procedure does not require any execution condition nor user input.

### PPAS - Description of Steps

ASCII SORT ON PP FILE: PTU907

.Input backup file:

-Original environments  
PAC7IN

.Output backup file:  
-Environments sorted as an ASCII sequence  
PAC70U

## PPAS - Execution Script

```
REM * -----  
REM *      VISUALAGE PACBASE  
REM *  
REM * -----  
<job id=PPAS>  
  
<script language="VBScript">  
Dim MyProc  
MyProc = "PPAS"  
</script>  
  
<script language="VBScript" src="INIT.vbs"/>  
  
<script language="VBScript">  
  
If c_error = 1 then Wscript.Quit (1) End If  
  
Call Msg_Log (Array("1022" , "PTU907"))  
'-----  
Call BvpEnv("PTU907","PAC7IN",Rep_USR & "\WIN.txt")  
  
Call BvpEnv("PTU907","PAC70U",Rep_USR & "\WOU.txt")  
  
Return = WshShell.Run("BVptu907.exe" , 1, TRUE)  
Call Err_Cod(Return , 0 , "ptu907")  
  
Call Msg_Log (Array("1023"))  
'-----  
Wscript.Quit (Return)  
  
</script>  
</job>
```









Part Number: DELNT002303A - 5950

Printed in U.S.A.

(1P) P/N: DELNT002303A - 5950

