



## VIVOTEK NETWORK DEVELOPMENT PLATFORM

**AvSynchronizer**

**Version 5.4.0.16**

**2017/01/20**

© 2017 VIVOTEK Inc. All Right Reserved

*VIVOTEK may make changes to specifications and product descriptions at any time, without notice.*

*The following is trademarks of VIVOTEK Inc., and may be used to identify VIVOTEK products only: VIVOTEK. Other product and company names contained herein may be trademarks of their respective owners.*

*No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from VIVOTEK Inc.*

## TABLE OF CONTENTS

---

TABLE OF CONTENTS .....	1
1. OVERVIEW.....	7
1.1 Introduction .....	7
1.2 Getting Started with AvSynchronizer module .....	7
1.3 File Structure .....	7
2. PROGRAMMER'S GUIDE .....	8
2.1 Using AvSynchronizer Module .....	8
2.1.1 Play audio/video from DataBroker .....	8
2.1.2 Play audio/video from raw data .....	8
2.1.3 Decode audio/video and get the raw data .....	8
2.1.4 Convert audio/video to AVI file .....	8
2.1.5 Convert live audio/video to AVI file .....	9
3. SAMPLE CODE .....	10
3.1 PlayRawFile .....	11
3.2 PlayWithDataBroker.....	14
3.3 GetRawDataFromDevice .....	16
3.4 DisplayAndGetRawDataWithLiveChannel.....	18
3.5 DisplayAndGetRawDataWithPlaybackChannel.....	20
3.6 ConvertAVI .....	21
3.7 GetSnapshotAndSaveAsJPG .....	23
3.8 GetDifferentRawFormatAtOnce.....	24
3.9 CustomDrawWithDisplayCallback.....	26
3.10 DigitalZoom .....	27
3.11 Display32Channels .....	28
3.12 Fisheye .....	29
4. API REFERENCE .....	31
4.1 Enumeration.....	32
4.1.1 EANTITEARING .....	33
4.1.2 EAUDIOFOCUSTYPE.....	34
4.1.3 EAVISTATUSCODE .....	35
4.1.4 EAVSYNCFISHEYEMOUNTTYPE .....	36

4.1.5	EAVSYNCSYNVIDEOMODE.....	37
4.1.6	EAVSYBCINITFLAG .....	38
4.1.7	ECHFLAG.....	41
4.1.8	ECHANNELSTATUS .....	44
4.1.9	EDIGITALZOOMFLAG.....	46
4.1.10	EDISPLAYCAP .....	48
4.1.11	EDISPLAYCALLBACK_INTERVAL.....	52
4.1.12	EAVSYNCHRONIZERDISPLAYMODE.....	53
4.1.13	EDISPLAYINFOFLAG .....	55
4.1.14	EFRAMETYPE .....	57
4.1.15	EGRAPHALIGN.....	58
4.1.16	EMEDIATYPE (TMediaType).....	61
4.1.17	EMOTIONALERTCOLOR .....	62
4.1.18	EPBCHFLAG .....	63
4.1.19	EPIXELFORMAT .....	66
4.1.20	ESETOPTION .....	69
4.1.21	ESNAPSHOTFLAG .....	78
4.1.22	ESTARTAVICHFLAG.....	80
4.1.23	ESTARTCHANNELFLAG .....	81
4.1.24	EUPCHOPTION .....	82
4.1.25	EFISHEYEPRESENTMODE.....	85
4.1.26	EFISHEYEPTZRCONTROLFLAGS.....	87
4.1.27	EFISHEYEUPDATEROTATEOPTFLAGS .....	89
4.1.28	EFISHEYEUPDATEVIEWERFLAGS .....	90
4.1.29	EFISHEYEVIEWERANGLEFLAGS .....	91
4.1.30	TsdrAudioCodec.....	92
4.1.31	TsdrVideoCodec .....	93
4.1.32	EMediaCodecType .....	94
4.2	Callback Function .....	95
4.2.1	LPDECODEFRAMECALLBACK.....	96
4.2.2	LPDECODEFRAMECALLBACK_EX.....	97

4.2.3	LPDISPLAYCALLBACK .....	98
4.2.4	LPOUTPUTVIDEOFRAMEBEFOREDISPLAY .....	99
4.2.5	LPENDOFSTREAMING.....	100
4.2.6	LPINPUTFRAMEREQUESTCALLBACK .....	101
4.2.7	LPSTATUSCALLBACK.....	102
4.3	Data Structure .....	104
4.3.1	TAVSYNCQUEUESTATUS .....	105
4.3.2	TAFRAMEINFO .....	106
4.3.3	TAVIAINFO.....	108
4.3.4	TAVICHOPTION .....	109
4.3.5	TCURRENTDISPLAYINFO.....	110
4.3.6	TAVICHOPTION2 .....	111
4.3.7	TAVIVINFO.....	113
4.3.8	TAVSYNCCALLBACKMOTIONINFO.....	114
4.3.9	TBORDERSIZE .....	115
4.3.10	TCHANNELOPTION .....	116
4.3.11	TFISHEYECONTROLPARAMS.....	119
4.3.12	TFISHEYECURRENTDISPLAY.....	120
4.3.13	TFISHEYEPRESENTPARAMS.....	121
4.3.14	TFISHEYEPTZRCONTROL_COMMANDS.....	123
4.3.15	TFISHEYEROTATEOPTIONS.....	126
4.3.16	TFISHEYESNAPSHOT.....	127
4.3.17	TFISHEYEVIEWER.....	128
4.3.18	TDECCHOPTION .....	130
4.3.19	TDIGITALZOOMPARAM.....	131
4.3.20	TDISPLAYINFO .....	134
4.3.21	TFRAMEINFO.....	136
4.3.22	TFRAMEINFOEX.....	137
4.3.23	TONEDISPBLOCK .....	139
4.3.24	TPBCHOPTION.....	140
4.3.25	TSNAPSHOT.....	145

4.3.26	TUPDATECHANNELOPTION.....	146
4.3.27	TVIDEOINFO .....	148
4.3.28	TUPDATEPBCHANNELOPTION .....	149
4.3.29	TVFRAMEINFO .....	152
4.3.30	TVIDEOOPTION .....	154
4.3.31	TAUDIOOPTION.....	156
4.3.32	TMediaDataPacketInfo .....	157
4.4	API Definition .....	158
4.4.1	AvSynchronizer_ChooseAudioCompressor .....	159
4.4.2	AvSynchronizer_ChooseChannelAudioCompressor .....	161
4.4.3	AvSynchronizer_ChooseVideoCompressor.....	163
4.4.4	AvSynchronizer_ChooseChannelVideoCompressor .....	165
4.4.5	AvSynchronizer_CreateAVIChannel.....	168
4.4.6	AvSynchronizer_CreateChannel .....	170
4.4.7	AvSynchronizer_CreateDecoderChannel.....	172
4.4.8	AvSynchronizer_CreateLiveAVIChannel .....	174
4.4.9	AvSynchronizer_CreatePlaybackChannel .....	176
4.4.10	AvSynchronizer_DecomposeAudio.....	178
4.4.11	AvSynchronizer_DecomposeVideo.....	180
4.4.12	AvSynchronizer_DecomposeVideoDecodeOnly .....	182
4.4.13	AvSynchronizer_DeleteAVIChannel.....	184
4.4.14	AvSynchronizer_DeleteChannel .....	186
4.4.15	AvSynchronizer_DeleteDecoderChannel.....	188
4.4.16	AvSynchronizer_FreePicture.....	189
4.4.17	AvSynchronizer_GetCurrentDisplay .....	190
4.4.18	AvSynchronizer_GetAudioCompressorParam .....	192
4.4.19	AvSynchronizer_GetChannelAudioCompressorParam .....	194
4.4.20	AvSynchronizer_GetChannelVideoCompressorParam .....	196
4.4.21	AvSynchronizer_GetCapabilities.....	198
4.4.22	AvSynchronizer_GetRemainingQueueElementCount .....	200
4.4.23	AvSynchronizer_GetCurrentSnapShot.....	201

4.4.24	AvSynchronizer_GetDecodedVideoFrame .....	203
4.4.25	AvSynchronizer_GetFlags .....	205
4.4.26	AvSynchronizer_GetVersionInfo .....	206
4.4.27	AvSynchronizer_GetVideoCompressorParam .....	208
4.4.28	AvSynchronizer_GetZoomedSnapShot .....	210
4.4.29	AvSynchronizer_GetZoomedDisplay .....	212
4.4.30	AvSynchronizer_Initial .....	214
4.4.31	AvSynchronizer_InitialEx .....	217
4.4.32	AvSynchronizer_InputAVIMedia .....	220
4.4.33	AvSynchronizer_InputDecodedAVIMedia .....	222
4.4.34	AvSynchronizer_InputEncodedMediaFrame .....	224
4.4.35	AvSynchronizer_InputPlaybackMediaFrame .....	226
4.4.36	AvSynchronizer_InputToBeDecodedMediaFrame .....	228
4.4.37	AvSynchronizer_Release .....	229
4.4.38	AvSynchronizer_SetAudioCompressorParam .....	230
4.4.39	AvSynchronizer_SetBufferTime .....	232
4.4.40	AvSynchronizer_SetChannelAudioCompressorParam .....	233
4.4.41	AvSynchronizer_SetChannelOption .....	235
4.4.42	AvSynchronizer_SetChannelVideoCompressorParam .....	237
4.4.43	AvSynchronizer_SetDisplayMode .....	239
4.4.44	AvSynchronizer_SetFlags .....	240
4.4.45	AvSynchronizer_SetQueueEmptyNotify .....	242
4.4.46	AvSynchronizer_SetVideoCompressorParam .....	244
4.4.47	AvSynchronizer_StartAVIChannel .....	246
4.4.48	AvSynchronizer_StartChannel .....	248
4.4.49	AvSynchronizer_StopAVIChannel .....	250
4.4.50	AvSynchronizer_StopChannel .....	252
4.4.51	AvSynchronizer_UpdateChannelSettings .....	253
4.4.52	AvSynchronizer_UpdatePlaybackChannelSettings .....	255
4.5	Fisheye API Definition .....	256
4.5.1	AvSynchronizer_FisheyeCheckSupport .....	257

4.5.2	AvSynchronizer_FisheyeDisableRenderer .....	258
4.5.3	AvSynchronizer_FisheyeEnableRenderer .....	259
4.5.4	AvSynchronizer_FisheyeGetCurrentViewerDisplay .....	260
4.5.5	AvSynchronizer_FisheyeGetCurrentViewerSnapshot.....	262
4.5.6	AvSynchronizer_FisheyeGetViewerPresentParameters .....	264
4.5.7	AvSynchronizer_FisheyeRegisterViewer.....	266
4.5.8	AvSynchronizer_FisheyeRemoveViewer.....	267
4.5.9	AvSynchronizer_FisheyeSetViewerPresentParameters.....	268
4.5.10	AvSynchronizer_FisheyeUpdateRotateOptions.....	269
4.5.11	AvSynchronizer_FisheyeUpdateViewer .....	270

# 1. Overview

---

## 1.1 Introduction

---

This document describes the properties and methods supported by the VIVOTEK AvSynchronizer module.

## 1.2 Getting Started with AvSynchronizer module

---

The main purpose of AvSynchronizer module is to display the audio and video from DataBroker or MediaDataBase module synchronously.

## 1.3 File Structure

---

**Table 1-1 File Structure**

File	Description
doc\VNDP_AvSynchronizer_API.pdf	This manual document
lib\d_AvSynchronizer.lib	The dynamic linking library
lib\AvSynchronizer.dll	The dynamic runtime library
lib\AviConverter.dll	The dynamic runtime library for AVI conversion
lib\ffmpeg.dll	Required file
inc\AvSynchronizer.h	Header file
inc\SrvTypeDef.h	Common definition file
inc\datapacketdef.h	Data packet definition file
inc\AvSynchronizer_Fisheye.h	Header file



## 2. Programmer's Guide

---

### 2.1 Using AvSynchronizer Module

---

You can play audio/video from the network through the DataBroker or the audio/video from the MediaDataBase with AvSynchronizer module. And it is also possible to decode audio and video data directly by decoder channel. To convert media into AVI files, this module also provides an AVI channel to handle it.

The Linux platform is newly supported, but only decoder channel is ported. Those functions that are not available in Linux would be marked with underline in the following document.

#### 2.1.1 Play audio/video from DataBroker

---

After initializing the AvSynchronizer module, you might create a channel to play the audio/video from DataBroker. Use [AvSynchronizer CreateChannel](#) to create the channel. Call [AvSynchronizer StartChannel](#) to tell the Avsynchronizer to start play the audio/video, then input audio/video through [AvSynchronizer InputEncodedMediaFrame](#).

This channel is only available in Windows 32 / Windows CE platform now.

#### 2.1.2 Play audio/video from raw data

---

After initializing the AvSynchronizer module, you might create a playback channel to play the audio/video from MediaDatabase. Use [AvSynchronizer CreatePlaybackChannel](#) to create the channel. Call [AvSynchronizer StartChannel](#) to tell the Avsynchronizer start to play the audio/video and input audio/video through [AvSynchronizer InputPlaybackMediaFrame](#).

This channel is only available in Windows 32 platform now.

#### 2.1.3 Decode audio/video and get the raw data

---

After initializing the AvSynchronizer module, you could create a decoder channel to decode audio/video either from MediaDatabase or from on-line. Use [AvSynchronizer CreateDecoderChannel](#) to create the channel. Then input audio/video through [AvSynchronizer InputToBeDecodedMediaFrame](#). The decoded data would be called back through [LPDECODEFRAMECALLBACK](#). It is possible to decode audio and video in synchronous mode, the two functions [AvSynchronizer DecodeAudio](#) and [AvSynchronizer DecodeVideo](#) are now provided to satisfy the request.

#### 2.1.4 Convert audio/video to AVI file

---

After initializing the AvSynchronizer module, you could create an AVI channel to convert audio/video from MediaDatabase into AVI file. Use [AvSynchronizer CreateAVIChannel](#) to create the channel. Start the channel by

calling [AvSynchronizer\\_StartAVIChannel](#) before input packet. Then input audio/video through [AvSynchronizer\\_InputAVIMedia](#). Use [AvSynchronizer\\_ChooseVideoCompressor](#) or [AvSynchronizer\\_ChooseAudioCompressor](#) to set the compressor for video and audio.

This channel is only available in Windows 32 platform now.

### 2.1.5 Convert live audio/video to AVI file

---

After initializing the AvSynchronizer module, you could create a live AVI channel to convert live audio/video from MediaDatabase into AVI file. Here the live means the data comes from a live connection to video servers. For this kind of data, use the decoder callback for live channel to avoid the same frames be decoded twice (use the decoder channel or non-live AVI channel). It is ok to use the non- AVI channel to create AVI, but the performance would be worse. It is recommended to application to change a file when the video size is changed during AVI generation. Users could do this by closing the AVI file and reopen again when it receive the size change callback from this module. Using [AvSynchronizer\\_CreateLiveAVIChannel](#) to create the channel. Start the channel by calling [AvSynchronizer\\_StartAVIChannel](#) before input packet. Set a decoder callback [LPDECODEFRAMECALLBACK\\_EX](#) when for the live channel. Then input audio/video through [AvSynchronizer\\_InputDecodedAVIMedia](#) whenever the decoded frames are notified. Use [AvSynchronizer\\_ChooseChannelVideoCompressor](#) or [AvSynchronizer\\_ChooseChannelAudioCompressor](#) to set the compressor for video and audio.

This channel is only available in Windows 32 platform now.

### 3. Sample Code

---

VIVOTEK CONFIDENTIAL  
2017.01.20

## 3.1 PlayRawFile

### Description

Read a binary file that is saved from the AvCallback of DataBroker. Parse this file and input the parsed data to the playback channel of AvSynchronizer. This sample also demonstrates the usage of Pause / Resume / Next frame / change display speed.

### Sample Code

#### Step 1. Prepare the callback functions

You have to prepare two callback functions for AvSynchronizer. One for display callback and another is status callback.

```
//DisplayCallback is to draw the caption of graph if needed.
SCODE __stdcall AvSynchronizerDisplayCallBack(DWORD dwContext, TDISPLAYINFO*
ptDisplayInfo)
{
//Draw the caption
}

//StatusCallback is to inform AP the status of AvSynchronizer.
SCODE __stdcall AvSynchronizerStatusCallBack(DWORD dwContext, DWORD dwStatusCode, DWORD
dwParam1, DWORD dwParam2)
{
//handles the status such as decode error, frame size changes, ...etc.
}
```

#### Step 2. Initialize AvSynchronizer

```
scRet = AvSynchronizer_InitialEx(&hAvSync, AvSyncStatusCallback, AvSyncDisplayCallback,
hWnd, AUDIOOUT_FOCUS_NORMAL, 0, AVSYNCHRONIZER_VERSION, 0, RGB(0, 0, 0));
```

#### Step 3. Create Playback channel

```
TPBCHOPTION tPBCHOption;
memset(&tPBCHOption, 0, sizeof(tPBCHOption));
tPBCHOption.dwFlags = PBCH_STATUSCB | PBCH_DISPLAYCB | PBCH_STATUSCONTEXT |
PBCH_DISPLAYCONTEXT | PBCH_ALLBORDER | PBCH_BITMAP;
tPBCHOption.pfStatus = AvShynchronizerStatusCallback;
```

```

tPBCHOption.pfDisplay = AvSynchronizerDisplayCallack;
tPBCHOption.dwStatusContext = dwStatusContext;
tPBCHOption.dwDisplayContext = dwDisplayContext;
tPBCHOption.dwTopBorderSize = 20;
tPBCHOption.dwLeftBorderSize = 0;
tPBCHOption.dwBottomBorderSize = 0;
tPBCHOption.dwRightBorderSize = 0;
tPBCHOption.hBMP = hBitmapHandle;
tPBCHOption.hDisplay = hDisplayWindow;
scRet = AvSynchronizer_CreatePlaybackChannel(hAvSync, &hPlaybackChannel, tPBCHOption);

```

#### Step 4. Start Playback channel

```

scRet = AvSynchronizer_StartChannel(hPlaybackChannel, dwStartFlag);

```

#### Step 5. Input TMediaDataPacketInfo to playback channel

```

while (bEndOfFileIsFalse)
{
    scRet = AvSynchronizer_InputPlaybackMediaFrame(hPlaybackChannel, ptMediaDataPacket);
}

```

#### Step 6. Wait until all frames are displayed and then stop channel

```

TAVSYNCQUEUESTATUS tQueueStatus;
do{
    Sleep(16);
    memset(&tQueueStatus, 0, sizeof(tQueueStatus));
    // Get remaining audio and video elements in queue
    scRet = AvSynchronizer_GetRemainingQueueElementCount(m_hPlaybackChannel,
        &tAvSyncQueueStatus);
}while ((tQueueStatus.dwAudioQueueElements != tQueueStatus.dwAudioQueueSize) ||
    (tQueueStatus.dwVideoQueueElements != tQueueStatus.dwVideoQueueSize - 1));
scRet = AvSynchronizer_StopChannel(hPlaybackChannel);

```

#### Step 7. Delete channel and release AvSynchronizer

```

scRet = AvSynchronizer_DeleteChannel(hAvSync, &hPlaybackChannel);
scRet = AvSynchronizer_Release(&hAvSync);

```

## Tips

---

1. Remember to set media type of playback channel
2. Before calling NextFrame, please pause the channel
3. Playback channel will block the input thread if the internal queue is full. User can disable this function by calling:

[AvSynchronizer SetChannelOption](#)(hPlaybackChannel, SETCH\_NOT\_BLOCK\_WHEN\_QUEUE\_FULL, FALSE, 0);

## 3.2 PlayWithDataBroker

### Description

This sample demonstrates the usage of live channel when connect to camera by using DataBroker.

### Sample Code

#### Step 1. Initialize AvSynchronizer

```
scRet = AvSynchronizer_InitialEx(&hAvSync, AvSyncStatusCallback, AvSyncDisplayCallback,
hWnd, AUDIOOUT_FOCUS_NORMAL, 0, AVSYNCHRONIZER_VERSION, 0, RGB(0, 0, 0));
```

#### Step 2. Create LiveChannel channel

```
TCHANOPTION tCHOption;
memset(&tCHOption, 0, sizeof(tCHOption));
tCHOption.dwFlags = CH_STATUSCB | CH_DISPLAYCB | CH_STATUSCONTEXT | CH_DISPLAYCONTEXT
| CH_ALLBORDER | CH_BITMAP;
tCHOption.pfStatus = AvSynchronizerStatusCallback;
tCHOption.pfDisplay = AvSynchronizerDisplayCallback;
tCHOption.dwStatusContext = dwStatusContext;
tCHOption.dwDisplayContext = dwDisplayContext;
tCHOption.dwTopBorderSize = 20;
tCHOption.dwLeftBorderSize = 0;
tCHOption.dwBottomBorderSize = 0;
tCHOption.dwRightBorderSize = 0;
tCHOption.hBMP = hBMP;
tCHOption.hDisplay = hDisplay;
scRet = AvSynchronizer_CreateChannel(hAvSync, &hLiveChannel, tCHOption);
```

#### Step 3. Start live channel

```
scRet = AvSynchronizer_StartChannel(hLiveChannel, DRAW_CONNECTING);
```

#### Step 4. Set media type

Update the media type of live channel when DataBroker callback eOnConnectionInfo.

#### Step 5. Input media frame in DataBroker AVCallback

```
DataBrokerAVCallback(DWORD dwContext, TMediaDataPacketInfo *ptPacket)
```

```
{  
    scRet = AvSynchronizer_InputEncodedMediaFrame(hLiveChannel, ptPacket);  
    if (scRet == AVSYNCHRONIZER_E_QUEUE_FULL)  
        return DATABROKER_S_FRAME_NOT_HANDLED;  
    ...  
}
```

### Step 6. Stop channel

```
scRet = AvSynchronizer_StopChannel(hLiveChannel);
```

### Step 7. Delete channel and release AvSynchronizer

```
scRet = AvSynchronizer_DeleteChannel(hAvSync, &hLiveChannel);  
scRet = AvSynchronizer_Release(&hAvSync);
```

### Tips

---

1. Remember to set media type of playback channel



### 3.3 GetRawDataFromDevice

---

#### Description

---

This sample demonstrates how to use decoder channel to get raw data, RGB or YUV, when connected to camera by DataBroker.

#### Sample Code

---

##### Step 1. Prepare decode callback

```
SCODE __stdcall AvSynchronizerFrameDecodeCallback(DWORD dwContext, TMediaType
tFrameType, TFRAMEINFO *tFrameInfo)
{
    if (tFrameType == AVSYNCHRONIZER_MEDIATYPE_VIDEO_ONLY)
    {
        //do some operations on tFrameInfo->tVideoFrame.pbyPicture
    }
    else if (tFrameType == AVSYNCHRONIZER_MEDIATYPE_AUDIO_ONLY)
    {
        //do some operations on tFrameInfo->tAudioFrame.pbySound
    }
}
```

##### Step 2. Initialize AvSynchronizer

```
scRet = AvSynchronizer_InitialEx(&hAvSync, NULL, NULL, NULL, 0, 0,
AVSYNCHRONIZER_VERSION, DECODER_CHANNEL_ONLY, 0);
```

##### Step 3. Create decoder channel

```
TDECCHOPTION tDecCHOption;
memset(&tDecCHOption, 0, sizeof(tDecCHOption));
tDecCHOption.pfDecodeFrame = AvSynchronizerFrameDecodeCallback;
tDecCHOption.dwAvDecodeContext = dwDecodeFrameContext;
//please refer to EPIXELFORMAT
tDecCHOption.dwRawDataFormat = ePixelFormat;
scRet = AvSynchronizer_CreateDecoderChannel(hAvSync, &hDecodeChannel, &tDecCHOption);
```

**Step 4. Option. Set output video format. After creating the decoder channel, user can change the output data here.**

```
scRet = AvSynchronizer_SetChannelOption(hDecodeChannel, SETCH_DECODE_DATA_FORMAT,  
ePixelFormat, 0);
```

**Step 5. Input media frame to decoder channel and the decoded raw data will callback to AvSynchronizerFrameDecodeCallback**

```
scRet = AvSynchronizer_InputToBeDecodedMediaFrame(hDecodeChannel, pMediaDataPacket);
```

**Step 6. Delete channel and release AvSynchronizer**

```
scRet = AvSynchronizer_DeleteDecoderChannel(hAvSync, &hDecodeChannel);  
scRet = AvSynchronizer_Release(&hAvSync);
```

## Tips

---

### 3.4 DisplayAndGetRawDataWithLiveChannel

#### Description

Live channel of AvSynchronizer can support display and get raw data of a single frame. This sample shows how to do that.

#### Sample Code

##### Step 1. Prepare decode, display and status callback

```
SCODE __stdcall AvSynchronizerFrameDecodeCallbackEx(DWORD dwContext, TMediaType
tFrameType, TFRAMEINFOEX *tFrameInfoEx)
{
    if (tFrameType == AVSYNCHRONIZER_MEDIATYPE_VIDEO_ONLY)
    {
        //do some operations on tFrameInfo->tVideoFrame.pbyPicture
    }
    else if (tFrameType == AVSYNCHRONIZER_MEDIATYPE_AUDIO_ONLY)
    {
        //do some operations on tFrameInfo->tAudioFrame.pbySound
    }
}
```

##### Step 2. The usage of live channel please refer to PlayWithDataBroker

##### Step 3. Set raw data format and related options

```
//set the output format
scRet = AvSynchronizer_SetChannelOption(hLiveChannel, SETCH_DECODE_DATA_FORMAT,
ePixelFormat, 0);
//enable output raw data
AvSynchronizer_SetChannelOption(m_hLiveChannel, SETCH_OUTPUT_VIDEO_FRAME, (DWORD)TRUE,
0);
//set decode callback
AvSynchronizer_SetChannelOption(m_hLiveChannel, SETCH_DECODE_CBEX
dwDecodeFrameContext, (DWORD)AvSynchronizerFrameDecodeCallbackEx);
```

## Tips

---

1. The decode callback of live channel is DecodeCallbacEx rather than DecodeCallback. The only difference between them is the interface. DecodeCallbackEx uses [TFRAMEINFOEX](#) while DecodeCallback uses [TFRAMEINFO](#).
2. User can get more than one formats for a single video frame.
3. If the data member, bContinueDecode, of [TFRAMEINFOEX](#) is TRUE, AvSynchronizer will callback the DecodeCallbackEx again with the format, dwNextFormat.

### 3.5 DisplayAndGetRawDataWithPlaybackChannel

---

#### Description

---

Playback channel of AvSynchronizer can support display and get raw data of a single frame. This sample is similar to [DisplayAndGetRawDataWithLiveChannel](#) but create playback channel.

#### Sample Code

---

Please reference the source code.

#### Tips

---

## 3.6 ConvertAVI

### Description

Use playback channel to display a saved data and convert the data to an AVI file.

### Sample Code

#### Step 1. The way to use playback client, please refer to PlayRawFile

#### Step 2. Create AVI channel

```
// Avi convertor need to use COM object
CoInitialize (NULL);
TAVICHOPTION tAviCHOption;
tAviCHOption.pfStatus = pfAviStatusCallback;
tAviCHOption.pfCaption = pfAviCaptionCallback;
tAviCHOption.dwStatusContext = dwAviStatusContext;
tAviCHOption.dwCaptionContext = dwAviCaptionContext;
// Create AVI channel
scRet = AvSynchronizer_CreateAVIChannel(hAvSync, &hAviChannel, &tAviCHOption);
```

#### Step 3. Start AVI channel

```
TAVICHOPTION2 tAviCHOption2;
memset(&tAviCHOption2, 0, sizeof(tAviCHOption2));
// Use the first frame's width and height
tAviCHOption2.dwFlag = FIXED_VINFO_AT_FIRST_FRAME;
tAviCHOption2.bVideoEnable = TRUE;
tAviCHOption2.tAviVInfo.dwBitCount = DEFAULT_AVIBITCOUNT;
strcpy(tAviCHOption2.szFileName, "Playbak.avi");
tAviCHOption2.tBorder.dwHeader = 20;
tAviCHOption2.tBorder.dwFooter = 0;
tAviCHOption2.tBorder.dwLeft = 0;
tAviCHOption2.tBorder.dwRight = 0;
// Start AVI channel
scRet = AvSynchronizer_StartAVIChannel(hAviChannel, &tAviCHOption2);
```

#### Step 4. Input media frame to Playback channel and Avi channel

```
scRet = AvSynchronizer_InputPlaybackMediaFrame(hPlaybackChannel, pMediaPacket);
```

```
scRet = AvSynchronizer_InputAVIMedia(hAviChannel, pMediaPacket);
```

**Step 5. Wait until all packets are input and stop Playback and Avi channel.**

```
//wait all packets are displayed as previous sample shows  
scRet = AvSynchronizer_StopChannel(hPlaybackChannel);  
scRet = AvSynchronizer_StopAVIChannel(hAviChannel);  
//release COM  
CoUninitialize();
```

**Step 6. Delete channels and release AvSynchronizer**

```
scRet = AvSynchronizer_DeleteChannel(hAvSync, &hPlaybackChannel);  
scRet = AvSynchronizer_DeleteAVIChannel(hAvSync, &hAviChannel);  
scRet = AvSynchronizer_Release(&hAvSync);
```

**Tips**

---

## 3.7 GetSnapShotAndSaveAsJPG

---

### Description

---

This sample uses DataBroker to connect camera, get a snapshot and save the picture as a JPEG file.

### Sample Code

---

**Step 1. Initialize AvSynchronizer and use live channel to display A/V as sample PlayWithDataBroker.**

**Step 2. Get snapshot and save the picture as Jpeg**

```
TSNAPSHOT tSnapshot;  
memset(&tSnapshot, 0, sizeof(tSnapshot));  
scRet = AvSynchronizer_GetCurrentSnapShot(m_hLiveChannel, &tSnapshot, ((PF_JPEG << 16)  
| SPECIFY_FMT) | ORIGINAL_SIZE);  
//do some operations on the jpeg data pointed by tSnapshot.pDataStart  
scRet = AvSynchronizer_FreePicture(&tSnapshot);
```

### Tips

---

1. Remember to free the buffer pointer in [TSNAPSHOT](#).



## 3.8 GetDifferentRawFormatAtOnce

---

### Description

---

This sample is similar to [DisplayAndGetRawDataWithLiveChannel](#), but it retrieves more than one data format, RGB and YUV, from a single picture.

### Sample Code

---

#### Step 1. Prepare the decode callback function

```
SCODE __stdcall AvSynchronizerFrameDecodeCallbackEx(DWORD dwContext, TMediaType
tFrameType, TFRAMEINFOEX *tFrameInfoEx)
{
    if (tFrameType == AVSYNCHRONIZER_MEDIATYPE_VIDEO_ONLY)
    {
        //do some operations on tFrameInfo->tVideoFrame.pbyPicture
        if (tFrameInfoEx->dwCBCount == 1)
        {
            if (dwNextDecodeFormat != 0)
            {
                //set the format that user wants
                tFrameInfoEx->dwNextFormat = eNextPixelFormat;
                tFrameInfoEx->bContinueDecode = TRUE;
            }
        }
    }
    else if (tFrameType == AVSYNCHRONIZER_MEDIATYPE_AUDIO_ONLY)
    {
        //do some operations on tFrameInfo->tAudioFrame.pbySound
    }
}
```

#### Step 2. The usage of live channel and DataBroker, please refer to

#### DisplayAndGetRawDataWithLiveChannel

### Tips

---

1. When user wants AvSynchronizer to return more video format, please set bContinueDecode to TRUE and dwNextFormat to a video format.

VIVOTEK CONFIDENTIAL  
2017.01.20

## 3.9 CustomDrawWithDisplayCallback

---

### Description

---

This sample is similar to [PlayWithDataBroker](#). There are only two differences. The first is the way to initialize AvSynchronizer and the other is the implementation of display callback.

### Sample Code

---

#### Step 1. Prepare the display callback function

The display callback function is similar to [PlayWithDataBroker](#). But in this case, AvSynchronizer will callback a whole DeviceContext(DC) to application. Application can draw what they want to draw.

#### Step 2. Initialize AvSynchronizer and the following steps are the same as PlayWithDataBroker

```
scRet = AvSynchronizer_InitialEx(&hAvSync, AvSyncStatusCallback, AvSyncDisplayCallback,
hWnd, AUDIOOUT_FOCUS_NORMAL, 0, AVSYNCHRONIZER_VERSION, CAPTION_ON_GRAPH, RGB(0, 0, 0));
```

### Tips

---

1. When turning on the flag, CAPTION\_ON\_GRAPH, it consumes more CPU power. This flag makes AvSynchronizer callback larger DC and increases the callback frequency.

## 3.10 DigitalZoom

### Description

This sample uses live channel to show live streaming. It also demonstrates the way to use digital zoom.

### Sample Code

**Step 1.** The usage of live channel is the same as [PlayWithDataBroker](#)

### Step 2. Set digital zoom

```
TDIGITALZOOMPARAM tDZParam;
memset(&tDZParam, 0, sizeof(tDZParam));
DWORD dwCanvasBorderSize = 4;
DWORD dwZoomAreaBorderSize = 4;
tDZParam.bCanvasWin = TRUE;
//the window handle that will show the whole picture
tDZParam.unCanvas.hTarget = hCanvasWnd;
tDZParam.rectCanvasBorder.top = dwCanvasBorderSize;
tDZParam.rectCanvasBorder.left = dwCanvasBorderSize;
tDZParam.rectCanvasBorder.bottom = dwCanvasBorderSize;
tDZParam.rectCanvasBorder.right = dwCanvasBorderSize;
tDZParam.bZoomWin = TRUE;
//the window handle that AvSynchronizer will draw digital zoom on it
tDZParam.unZoom.hZoomArea = hZoomasWnd;
tDZParam.rectZoomBorder.top = dwZoomAreaBorderSize;
tDZParam.rectZoomBorder.left = dwZoomAreaBorderSize;
tDZParam.rectZoomBorder.bottom = dwZoomAreaBorderSize;
tDZParam.rectZoomBorder.right = dwZoomAreaBorderSize;
tDZParam.bZoomEnabled = TRUE;
tDZParam.bDisplayed = TRUE;
DWORD dwDZFlags = DZ_CANVAS | DZ_CANVAS_DISPLAY | DZ_ZOOM_AREA | DZ_ENABLE_ZOOM |
DZ_CANVAS_BORDER | DZ_ZOOM_AREA_BORDER;
scRet = AvSynchronizer_SetChannelOption(m_hLiveChannel, SETCH_DIGITAL_ZOOM,
(DWORD) (&tDZParam), dwDZFlags);
```

### 3.11 Display32Channels

---

#### Description

---

This sample uses playback channel to show the streaming from a file.

#### Sample Code

---

**Step 1. The usage of live channel is the same as [PlayRawFile](#). But it initializes 4 AvSynchronizers and each one contains 8 live channels**

#### Tips

---

1. In previous version, application should initialize AvSynchronizer many times for better performance. Now application does not need to do this operation.

## 3.12 Fisheye

### Description

This sample demonstrates the usage of live channel when connected to fisheye camera by DataBroker.

### Sample Code

#### Step 1. Initialize AvSynchronizer

```
scRet = AvSynchronizer_InitialEx(&hAvSync, AvSyncStatusCallback, AvSyncDisplayCallback,
hWnd, AUDIOOUT_FOCUS_NORMAL, 0, AVSYNCHRONIZER_VERSION, 0, RGB(0, 0, 0));
```

#### Step 2. Create LiveChannel channel

```
TCHANNELOPTION tCHOption;
memset(&tCHOption, 0, sizeof(tCHOption));
tCHOption.dwFlags = CH_STATUSCB | CH_DISPLAYCB | CH_STATUSCONTEXT | CH_DISPLAYCONTEXT
| CH_ALLBORDER | CH_BITMAP;
tCHOption.pfStatus = AvSynchronizerStatusCallback;
tCHOption.pfDisplay = AvSynchronizerDisplayCallback;
tCHOption.dwStatusContext = dwStatusContext;
tCHOption.dwDisplayContext = dwDisplayContext;
tCHOption.dwTopBorderSize = 20;
tCHOption.dwLeftBorderSize = 0;
tCHOption.dwBottomBorderSize = 0;
tCHOption.dwRightBorderSize = 0;
tCHOption.hBMP = hBMP;
tCHOption.hDisplay = hDisplay;
scRet = AvSynchronizer_CreateChannel(hAvSync, &hLiveChannel, tCHOption);
```

#### Step 3. Enable fisheye channel

```
BOOL bSupportFisheye;
scRet = AvSynchronizer_FisheyeCheckSupport(&bSupportFisheye);
if (bSupportFisheye)
scRet = AvSynchronizer_FisheyeEnableRenderer(hLiveChannel);
```

#### Step 4. Start live channel

```
scRet = AvSynchronizer_StartChannel(hLiveChannel, DRAW_CONNECTING);
```

**Step 5. Set media type**

Update the media type of live channel when DataBroker callback eOnConnectionInfo.

**Step 6. Input media frame in DataBroker AVCallback**

```
DataBrokerAVCallback(DWORD dwContext, TMediaDataPacketInfo *ptPacket)
{
    scRet = AvSynchronizer_InputEncodedMediaFrame(hLiveChannel, ptPacket);
    if (scRet == AVSYNCHRONIZER_E_QUEUE_FULL)
        return DATABROKER_S_FRAME_NOT_HANDLED;
    ...
}
```

**Step 7. Fisheye controls**

```
//Users can call the following functions to control the UI behavior. For more information,
// please reference the API description.
// AvSynchronizer_FisheyeGetCurrentViewerDisplay,
// AvSynchronizer_FisheyeGetCurrentViewerSnapShot
// AvSynchronizer_FisheyeGetViewerPresentParameters
// AvSynchronizer_FisheyeRegisterViewer
// AvSynchronizer_FisheyeRemoveViewer
// AvSynchronizer_FisheyeSetViewerPresentParameters
// AvSynchronizer_FisheyeUpdateRotateOptions
// AvSynchronizer_FisheyeUpdateViewer
```

**Step 8. Stop channel**

```
scRet =AvSynchronizer_StopChannel(hLiveChannel);
```

**Step 9. Delete channel and release AvSynchronizer**

```
scRet = AvSynchronizer_DeleteChannel(hAvSync, &hLiveChannel);
scRet = AvSynchronizer_Release(&hAvSync);
```

**Tips**

1. Remeber to enable fisheye render before calling [AvSynchronizer\\_StartChannel](#).

## 4. API Reference

---

This chapter contains the API function calls for the AvSynchronizer.

VIVOTEK CONFIDENTIAL  
2017.01.20



## 4.1 Enumeration

---

The enumeration used is depicted here.

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.1.1 EANTITEARING

---

This enumeration indicates if AvSynchronizer should turn on anti-tearing or not when drawing pictures.

```
typedef enum {  
  
    ANTI_TEARING_DISABLED        = 1,  
    ANTI_TEARING_ALWAYS         = 2,  
    ANTI_TEARING_AUTO           = 3,  
  
} EANTITEARING;
```

#### Values

---

##### **ANTI\_TEARING\_DISABLED**

Disable the anti-tearing(don't wait for vertical blank).

##### **ANTI\_TEARING\_ALWAYS**

Always wait for vertical blank.

##### **ANTI\_TEARING\_AUTO**

If the height of destination window is bigger than 240, it will wait for vertical blank.

#### Remarks

---

This enumeration is only available for Windows 32 platform.

#### Requirements

---

AvSynchronizer.h

### 4.1.2 EAUDIOFOCUSTYPE

---

This enumeration indicates the focus type of the DirectSound.

```
typedef enum {  
  
        AUDIOOUT_FOCUS_NORMAL        = 1,  
        AUDIOOUT_FOCUS_STICKY       = 2,  
        AUDIOOUT_FOCUS_GLOBAL       = 3,  
  
} EAUDIOFOCUSTYPE;
```

#### Values

---

##### **AUDIOOUT\_FOCUS\_NORMAL**

The buffer is muted if user switches focus to another application.

##### **AUDIOOUT\_FOCUS\_STICKY**

If the user switches to another application not using DirectSound, the buffer is still audible. However, if the user switches to another DirectSound application, the buffer is muted.

##### **AUDIOOUT\_FOCUS\_GLOBAL**

The application can continue to play its buffers if the user switches focus to another application, even if the new application uses DirectSound.

#### Remarks

---

This enumeration is only available for Windows 32 platform.

#### Requirements

---

AvSynchronizer.h

### 4.1.3 EAVISTATUSCODE

---

This enumeration indicates status code for AVI conversion channel.

```
typedef enum {  
  
                                AVI_WRITE_FRAME_TIME           = WM_USER + 100,  
  
} EAVISTATUSCODE;
```

#### Values

---

##### **AVI\_WRITE\_FRAME\_TIME**

Notify application the time value for the current processing media. This could let application shows the processing progress correctly.

#### Remarks

---

This enumeration is only available for Windows 32 platform.

#### Requirements

---

AvSynchronizer.h

#### 4.1.4 EAVSYNCFISHEYEMOUNTTYPE

---

This enumeration indicates the installation type of fisheye camera.

```
typedef enum EAvSyncFisheyeMountType {  
  
    AVSVYNCRHONIZER_FISHEYE_WALL      = 1,  
    AVSVYNCRHONIZER_FISHEYE_CEILING   = 2,  
    AVSVYNCRHONIZER_FISHEYE_FLOOR     = 3,  
  
} EAVSYNCFISHEYEMOUNTTYPE;
```

##### Values

---

###### **AVSVYNCRHONIZER\_FISHEYE\_WALL**

The camera is mounted on the wall.

###### **AVSVYNCRHONIZER\_FISHEYE\_CEILING**

The camera is mounted on the ceiling.

###### **AVSVYNCRHONIZER\_FISHEYE\_FLOOR**

The camera is mounted on the floor.

##### Remarks

---

##### Requirements

---

AvSynchronizer.h

### 4.1.5 EAVSYNCVIDEOMODE

---

This enumeration indicates the display mode.

```
typedef enum {  
  
    AVSYNCHRONIZER_VIDEO_DDRAW    = 1,  
    AVSYNCHRONIZER_VIDEO_GDI      = 2,  
  
} EAVSYNCVIDEOMODE;
```

#### Values

---

##### **AVSYNCHRONIZER\_VIDEO\_DDRAW**

The current display mode is DDraw.

##### **AVSYNCHRONIZER\_VIDEO\_GDI**

The current display mode is GDI.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

#### 4.1.6 EAVSYBCINITFLAG

This enumeration indicates the initial mode. Used by [AvSynchronizer\\_Initial](#) or [AvSynchronizer\\_InitialEx](#).

```
typedef enum {
    DECODER_CHANNEL_ONLY           = 0x00000001,
    USE_GDI_ONLY                   = 0x00000002,
    USE_DIRECTDRAW_ONLY           = 0x00000004,
    CAPTION_ON_GRAPH              = 0x00000008,
    BETTER_GDI_STRETCH            = 0x00000010,
    ONE_PASS_DDRAW                = 0x00000020,
    INDIVIDUAL_SURFACE            = 0x00000040,
    ORG_SIZE_MODE                 = 0x00000080,
    FORCE_GDI                      = 0x00000100,
    CHANGE_TIME_PRECISION         = 0x00000200,
    FORCE_NON_YUV                  = 0x00000400,
    MEGA_PIXEL                    = 0x00000800,
    DECODER_NO_ACCELERATE         = 0x00001000,
    HARDWARE_ACCELERATION_FALLBACK = 0x00002000,
    AV_DONT_SYNC                  = 0x80000000,
} EAVSYBCINITFLAG;
```

#### Values

##### DECODER\_CHANNEL\_ONLY

If this flag is set, then the [AvSynchronizer\\_Initial](#) function won't fail when the video initialize failed. And it will not check for the nullity of window handle passed.

##### USE\_GDI\_ONLY

If this flag is set, then the [AvSynchronizer\\_Initial](#) function will be forced to use GDI as display engine. GDI is slower but more compatible in different platform. This flag cannot be used with USE\_DIRECTDRAW\_ONLY flag.

##### USE\_DIRECTDRAW\_ONLY

If this flag is set, then the [AvSynchronizer\\_Initial](#) function will be forced to use DirectDraw as display engine. If the running environment can't support DirectDraw, the initial would be failed. This flag cannot be used with USE\_GDI\_ONLY flag.

#### **CAPTION\_ON\_GRAPH**

If this flag is set, the [LPDISPLAYCALLBACK](#) will be called every frame. It will cause a worse performance.

#### **BETTER\_GDI\_STRETCH**

If this flag is set, it will get more quality when using GDI with stretching but slower. If DirectDraw is used, this flag is ignored.

#### **ONE\_PASS\_DDRAW**

When in DirectDraw mode, some video card would have problem for the original two passes drawing mode (draw the YUV/BMP to a window size offscreen surface, and then show the surface to primary surface). Set this mode could solve this problem. But one pass mode would suffer the video shivering when other window covers the video partly. This flag will be of no effect when in GDI mode.

#### **INDIVIDUAL\_SURFACE**

When in DirectDraw, decode the video directly to the YUV surface. In such case, the overall performance will be improved by about 20%.

#### **ORG\_SIZE\_MODE**

If AP needs to use original picture size mode to draw the video and caption/borders, it needs to specify this flag when initialize AVSynchronizer. And this flag could not be changed during runtime. Set this flag will need more memory so the default setting is off.

#### **FORCE\_GDI**

Force the module to use GDI to draw the video. This allows the caller to switch between DirectDraw and GDI without release current AVSynchronizer object.

#### **CHANGE\_TIME\_PRECISION**

Change the time precision of OS, with this flag, the sleeping time of the thread in current application would be 1 fourth the original unit. This would get a faster system response time. But in such mode, the CPU would be consumed more than the normal case.

#### **FORCE\_NON\_YUV**



For some cards, the YUV operation will cause green screen. Set this flag will avoid the problem, but the system performance will worse than YUV mode.

### **MEGA\_PIXEL**

AvSynchronizer will allocate the internal buffer as 1280 x 1024 when initialization if this flag is set.

### **AV\_DON'T\_SYNC**

If this flag is set, then the mechanism of synchronization will be disabled.

### Remarks

---

If DECODER\_CHANNEL\_ONLY is set and the initialization of video was failed, then you can only create the decoder channel.

USE\_DIRECTDRAW\_ONLY, ONE\_PASS\_DDRAW, INDIVIDUAL\_SURFACE is only available on Windows 32 platform.

### Requirements

---

AvSynchronizer.h

### 4.1.7 ECHFLAG

This enumeration indicates which field of the structure [TCHANNELOPTION](#) is valid.

```
typedef enum {
    CH_STATUSCB                = 0x00000001,
    CH_DISPLAYCB               = 0x00000002,
    CH_ALLCALLBACK             = 0x00000003,
    CH_STATUSCONTEXT           = 0x00000004,
    CH_DISPLAYCONTEXT           = 0x00000008,
    CH_ALLCONTEXT              = 0x0000000c,
    CH_VOLUME                  = 0x00000010,
    CH_LFBORDER                = 0x00000020,
    CH_RTBOARDER               = 0x00000040,
    CH_TPBORDER                = 0x00000080,
    CH_BTBOARDER               = 0x00000100,
    CH_ALLBOARDER              = 0x000001e0,
    CH_BITMAP                  = 0x00000200,
    CH_MOTION                  = 0x00000400,
    CH_MOTIONRECT              = 0x00000800,
    CH_MOTIONRECTALERT         = 0x00001000,
    CH_VIDEOOUT                = 0x00002000,
    CH_AUDIOOUT                = 0x00004000,
    CH_ALL                     = 0xFFFFFFFF
} ECHFLAG;
```

#### Values

##### **CH\_STATUSCB**

pfStatus is valid.

##### **CH\_DISPLAYCB**

pfDisplay is valid.

**CH\_ALLCALLBACK**

All callback is valid. pfStatus and pfDisplay.

**CH\_STATUSCONTEXT**

dwStatusContext is valid.

**CH\_DISPLAYCONTEXT**

dwDisplayContext is valid.

**CH\_ALLCONTEXT**

All the context is valid. dwStatusContext and dwDisplayContext.

**CH\_VOLUME**

dwVolume is valid.

**CH\_LFBORDER**

dwLeftBorderSize is valid.

**CH\_RTBOARDER**

dwRightBorderSize is valid.

**CH\_TPBOARDER**

dwTopBorderSize is valid.

**CH\_BTBOARDER**

dwBottomBorderSize is valid.

**CH\_ALLBOARDER**

All the Border is valid. dwLeftBorderSize, dwRightBorderSize, dwRightBorderSize and dwBottomBorderSize.

**CH\_BITMAP**

hBMP and bSaveBmp are valid.

**CH\_MOTION**

bMotionAlert is valid.

**CH\_MOTIONRECT**

dwMotionRect is valid.

#### **CH\_MOTIONRECTALERT**

dwMotionRectAlert is valid.

#### **CH\_VIDEOOUT**

bVideoOut is valid.

#### **CH\_AUDIOOUT**

bAudioOut is valid.

#### **CH\_ALL**

All fields are valid.

#### **Remarks**

---

CH\_BITMAP option is only available for Windows 32 platform.

#### **Requirements**

---

AvSynchronizer.h

### 4.1.8 ECHANNELSTATUS

This enumeration lists the status code that appears when [LPSTATUSCALLBACK](#) get called.

```
typedef enum {
    AVSYNCHRONIZER_STATUSCODE_DECODE_ERROR           = 1,
    AVSYNCHRONIZER_STATUSCODE_MEMALLOC_ERROR         = 2,
    AVSYNCHRONIZER_STATUSCODE_FRAME_SIZE_CHG         = 3,
    AVSYNCHRONIZER_STATUSCODE_AUDIO_START             = 4,
    AVSYNCHRONIZER_STATUSCODE_AUDIO_STOP             = 5,
    AVSYNCHRONIZER_STATUSCODE_MOTION                 = 6,
    AVSYNCHRONIZER_NEW_IMAGE                          = 7,
    AVSYNCHRONIZER_FIRST_IMAGE                       = 8,
    AVSYNCHRONIZER_STATUSCODE_VIDEO_MODE             = 9,
    AVSYNCHRONIZER_STATUSCODE_FISHEYE_MOUNT_TYPE     = 10,
    AVSYNCHRONIZER_STATUSCODE_FISHEYE_FOV_TYPE       = 11,
    AVSYNCHRONIZER_STATUSCODE_FISHEYE_STATUS         = 12,
    AVSYNCHRONIZER_STATUSCODE_HARDWARE_ACCELERATION  = 13,
} ECHANNELSTATUS;
```

#### Values

##### **AVSYNCHRONIZER\_STATUSCODE\_DECODE\_ERROR**

Decode error. dwParam1 indicate the frame type ( AUDIO\_FRAME or VIDEO\_FRAME).

##### **AVSYNCHRONIZER\_STATUSCODE\_MEMALLOC\_ERROR**

Memory allocation error happens during decoding.

##### **AVSYNCHRONIZER\_STATUSCODE\_FRAME\_SIZE\_CHG**

The decoded video size is changed. When the first frame is decoded it will issue a call to notify application. dwParam1 is width and dwParam2 is height of the new video size. Note: Please do not resize the window in the called back function. This would cause a deadlock. Use PostMessage() or timer to resize the window instead if needed.

##### **AVSYNCHRONIZER\_STATUSCODE\_AUDIO\_START**

Called when audio only media type starts to play audio. This could let application start to render on screen.

#### **AVSYNCHRONIZER\_STATUSCODE\_AUDIO\_STOP**

Called when audio only media type stop to play audio. These two codes let application could start and stop a timer to show multimedia effect when playing audio (like those in Media Player).

#### **AVSYNCHRONIZER\_STATUSCODE\_MOTION**

Motion is triggered. The dwParam1 is a DWORD array of 3 percentages, and dwParam2 is a DWORD array of 3 alert flags.

#### **AVSYNCHRONIZER\_NEW\_IMAGE**

Notify application that a new image is to be shown. The dwParam1 is a Boolean that records if the video contains signal or not.

#### **AVSYNCHRONIZER\_FIRST\_IMAGE**

Called back when a new I frame comes. It will be called only if the SETCH\_RESUME\_PLAYING is set for a live channel.

#### **AVSYNCHRONIZER\_STATUSCODE\_VIDEO\_MODE**

The status of current video out mode. param1 indicates the display mode. Please refer to [EAVSYNCVIDEOMODE](#).

#### **AVSYNCHRONIZER\_STATUSCODE\_FISHEYE\_MOUNT\_TYPE**

The status of mount type of fish eye camera, param1 = [EAVSYNCFISHEYEMOUNTTYPE](#).

Remarks

---

Requirements

---

AvSynchronizer.h

### 4.1.9 EDIGITALZOOMFLAG

This enumeration specified the valid members in structure of [TDIGITALZOOMPARAM](#) structure parameters used when calling [AvSynchronizer\\_SetChannelOption](#).

```
typedef enum {  
  
    DZ_CANVAS                        = 0x00000001,  
    DZ_CANVAS_BORDER                = 0x00000002,  
    DZ_ZOOM_AREA                    = 0x00000004,  
    DZ_ZOOM_AREA_BORDER             = 0x00000008,  
    DZ_ENABLE_ZOOM                  = 0x00000010,  
    DZ_CANVAS_DISPLAY               = 0x00000020,  
  
} EDIGITALZOOMFLAG;
```

#### Values

##### **DZ\_CANVAS**

The bCanvasWin and unCanvas members are valid.

##### **DZ\_CANVAS\_BORDER**

The rectCanvasBorder member is valid.

##### **DZ\_ZOOM\_AREA**

The bZoomWin and unZoom members are valid.

##### **DZ\_ZOOM\_AREA\_BORDER**

The rectZoomBorder member is valid.

##### **DZ\_ENABLE\_ZOOM**

The bZoomEnabled member is valid.

##### **DZ\_CANVAS\_DISPLAY**

The bDisplayed member is valid.

#### Remarks

## Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20



#### 4.1.10 EDISPLAYCAP

This enumeration lists the video capability for the display card. It is used in [AvSynchronizer\\_GetCapabilities](#).

```
typedef enum {

    AVSYNCHRONIZER_VIDEOSF_OFFSCREEN_YUY2          = 1,
    AVSYNCHRONIZER_VIDEOSF_OFFSCREEN_UYVY          = (1<<1),
    AVSYNCHRONIZER_VIDEOSF_OFFSCREEN_RGB16          = (1<<2),
    AVSYNCHRONIZER_VIDEOSF_OFFSCREEN_RGB24          = (1<<3),
    AVSYNCHRONIZER_VIDEOSF_OFFSCREEN_RGB32          = (1<<4),
    AVSYNCHRONIZER_VIDEOSF_OVERLAY_YUY2            = (1<<5),
    AVSYNCHRONIZER_VIDEOSF_OVERLAY_UYVY            = (1<<6),
    AVSYNCHRONIZER_VIDEOSF_OVERLAY_R5G6B5          = (1<<7),
    AVSYNCHRONIZER_VIDEOSF_OVERLAY_RGB24            = (1<<8),
    AVSYNCHRONIZER_VIDEOSF_OVERLAY_RGB32            = (1<<9),
    AVSYNCHRONIZER_VIDEOCAB_BLTFOURCC              = (1<<10),
    AVSYNCHRONIZER_VIDEOCAB_OVERLAYFOURCC           = (1<<11),
    AVSYNCHRONIZER_VIDEOCAB_CKEY_DESTBLT            = (1<<12),
    AVSYNCHRONIZER_VIDEOCAB_CKEY_DESTOVERLAY        = (1<<13),
    AVSYNCHRONIZER_VIDEOCAB_CKEY_SRCBLT             = (1<<14),
    AVSYNCHRONIZER_VIDEOCAB_CKEY_SRCOVERLAY         = (1<<15),
    AVSYNCHRONIZER_VIDEOCAB_EMULATIONONLY           = (1<<16),
    AVSYNCHRONIZER_VIDEOCAB_NO_HWSTRETCH             = (1<<17),
    AVSYNCHRONIZER_VIDEOCAB_NO_OVERLAYHWSTRETCH      = (1<<18),
    AVSYNCHRONIZER_VIDEOCAP_NO_BLT_SYSMEM           = (1<<19),
    AVSYNCHRONIZER_VIDEOCAP_NO_AGP                   = (1<<20),
    AVSYNCHRONIZER_VIDEOSF_OVERLAY_R5G5B5           = (1<<21),
    AVSYNCHRONIZER_VIDEOCAB_BLTSTRETCHY             = (1<<22),
    AVSYNCHRONIZER_VIDEOCAB_BLTSTRETCHX             = (1<<23),
    AVSYNCHRONIZER_VIDEOCAB_BLTSHRINKY              = (1<<24),
    AVSYNCHRONIZER_VIDEOCAB_BLTSHRINKX              = (1<<25),
    AVSYNCHRONIZER_VIDEOCAB_OVERLAYSTRETCHY         = (1<<26),
```

AVSYNCHRONIZER_VIDEOCAB_OVERLAYSTRETCHX	= (1<<27),
AVSYNCHRONIZER_VIDEOCAB_OVERLAYSHRINKY	= (1<<28),
AVSYNCHRONIZER_VIDEOCAB_OVERLAYSHRINKX	= (1<<29),
} EDISPLAYCAP;	

## Values

### AVSYNCHRONIZER\_VIDEOSF\_OFFSCREEN\_YUY2

Indicates that could create YUY2 off-screen surface.

### AVSYNCHRONIZER\_VIDEOSF\_OFFSCREEN\_UYVY

Indicates that could create UYVY off-screen surface.

### AVSYNCHRONIZER\_VIDEOSF\_OFFSCREEN\_RGB16

Indicates that could create 16 bits RGB off-screen surface.

### AVSYNCHRONIZER\_VIDEOSF\_OFFSCREEN\_RGB24

Indicates that could create 24 bits RGB off-screen surface.

### AVSYNCHRONIZER\_VIDEOSF\_OFFSCREEN\_RGB32

Indicates that could create 32 bits RGB off-screen surface.

### AVSYNCHRONIZER\_VIDEOSF\_OVERLAY\_YUY2

Indicates that could create YUY2 overlay surface.

### AVSYNCHRONIZER\_VIDEOSF\_OVERLAY\_UYVY

Indicates that could create UYVY overlay surface.

### AVSYNCHRONIZER\_VIDEOSF\_OVERLAY\_R5G6B5

Indicates that could create 16 bits RGB (565) overlay surface.

### AVSYNCHRONIZER\_VIDEOSF\_OVERLAY\_R5G5B5

Indicates that could create 15 bits RGB (555) overlay surface.

### AVSYNCHRONIZER\_VIDEOSF\_OVERLAY\_RGB24

Indicates that could create 24 bits RGB overlay surface.

**AVSYNCHRONIZER\_VIDEOSF\_OVERLAY\_RGB32**

Indicates that could create 32 bits RGB overlay surface.

**AVSYNCHRONIZER\_VIDEOCAB\_BLTFOURCC**

Indicates that display hardware is capable of color-space conversions during blit operations.

**AVSYNCHRONIZER\_VIDEOCAB\_OVERLAYFOURCC**

Indicates that overlay hardware is capable of color-space conversions during overlay operations.

**AVSYNCHRONIZER\_VIDEOCAB\_CKEY\_DESTBLT**

Supports transparent blitting with a color key that identifies the replaceable bits of the destination surface for RGB colors.

**AVSYNCHRONIZER\_VIDEOCAB\_CKEY\_DESTOVERLAY**

Supports overlaying with color keying of the replaceable bits of the destination surface being overlaid for RGB colors.

**AVSYNCHRONIZER\_VIDEOCAB\_CKEY\_SRCBLT**

Supports transparent blitting using the color key for the source with this surface for RGB colors.

**AVSYNCHRONIZER\_VIDEOCAB\_CKEY\_SRCOVERLAY**

Supports overlaying using the color key for the source with this overlay surface for RGB colors.

**AVSYNCHRONIZER\_VIDEOCAB\_EMULATIONONLY**

Indicates that there is no hardware support.

**AVSYNCHRONIZER\_VIDEOCAB\_NO\_HWSTRETCH**

Indicates that display hardware is not capable of stretching during blit operations.

**AVSYNCHRONIZER\_VIDEOCAB\_NO\_OVERLAYHWSTRETCH**

Indicates that overlay hardware is not capable of stretching.

**AVSYNCHRONIZER\_VIDEOCAB\_NO\_BLT\_SYSTEM**

Indicates that display hardware is not capable of blitting to or from system memory.

**AVSYNCHRONIZER\_VIDEOCAB\_NO\_AGP**

Indicates that the display driver doesn't supports surfaces in non-local video memory.

**AVSYNCHRONIZER\_VIDEOCAB\_BLTSTRETCHY**

Supports arbitrary stretching of a surface along the y-axis (vertically).

**AVSYNCHRONIZER\_VIDEOCAB\_BLTSTRETCHX**

Supports arbitrary stretching of a surface along the x-axis (horizontally).

**AVSYNCHRONIZER\_VIDEOCAB\_BLTSHRINKY**

Supports arbitrary shrinking of a surface along the y-axis (vertically).

**AVSYNCHRONIZER\_VIDEOCAB\_BLTSHRINKX**

Supports arbitrary shrinking of a surface along the x-axis (horizontally).

**AVSYNCHRONIZER\_VIDEOCAB\_OVERLAYSTRETCHY**

Supports arbitrary stretching of a surface along the y-axis (vertically).

**AVSYNCHRONIZER\_VIDEOCAB\_OVERLAYSTRETCHX**

Supports arbitrary stretching of a surface along the x-axis (horizontally).

**AVSYNCHRONIZER\_VIDEOCAB\_OVERLAYSHRINKY**

Supports arbitrary shrinking of a surface along the y-axis (vertically).

**AVSYNCHRONIZER\_VIDEOCAB\_OVERLAYSHRINKX**

Supports arbitrary shrinking of a surface along the x-axis (horizontally).

**Remarks**

---

**Requirements**

---

AvSynchronizer.h

### 4.1.11 EDISPLAYCALLBACK\_INTERVAL

---

This enumeration indicates display callback interval.

```
typedef enum {  
  
    eDisplayCB_LocalTime      = 0x1,  
    eDisplayCB_CameraTime    = 0x1 << 1,  
    eDisplayCB_RecordingTime  = 0x1 << 2,  
    eDisplayCB_StreamingTime  = 0x1 << 3,  
    eDisplayCB_EveryFrame     = 0x1 << 31,  
    eDisplayCB_Default        = eDisplayCB_LocalTime | eDisplayCB_CameraTime  
  
} EDISPLAYCALLBACK_INTERVAL;
```

#### Values

---

##### **eDisplayCB\_LocalTime**

Application gets the display callback when the second of local time changes.

##### **eDisplayCB\_CameraTime**

Application gets the display callback when the second of camera time changes.

##### **eDisplayCB\_RecordingTime**

Application gets the display callback when the second of recording time changes.

##### **eDisplayCB\_Default**

Application gets the display callback when the second of local time or camera changes.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

#### 4.1.12 EAVSYNCHRONIZERDISPLAYMODE

---

This enumeration specified the decode and display mode. Some of the option are only for SVC-T streaming only.

```
typedef enum {  
  
    eDisplayMode_Normal            = 0,  
    eDisplayMode_I_Frame_Only     = 1,  
    eDisplayMode_Frameskip1       = 2,  
    eDisplayMode_Frameskip2       = 3,  
    eDisplayMode_Frameskip3       = 4,  
    eDisplayMode_Frameskip4       = 5,  
    eDisplayMode_Frameskip5       = 6,  
    eDisplayMode_Frameskip6       = 7,  
    eDisplayMode_Frameskip7       = 8,  
  
} EAVSYNCHRONIZERDISPLAYMODE;
```

#### Values

---

##### **eDisplayMode\_Normal**

decode and display all the frames.

##### **eDisplayMode\_I\_Frame\_Only**

decode and display only I-frames.

##### **eDisplayMode\_Frameskip1**

Skip 1 frame for every 8 incoming frames. Only for SVC-T streaming.

##### **eDisplayMode\_Frameskip2**

Skip 2 frame for every 8 incoming frames. Only for SVC-T streaming.

##### **eDisplayMode\_Frameskip3**

Skip 3 frame for every 8 incoming frames. Only for SVC-T streaming.

##### **eDisplayMode\_Frameskip4**

Skip 4 frame for every 8 incoming frames. Only for SVC-T streaming.

**eDisplayMode\_Frameskip5**

Skip 5 frame for every 8 incoming frames. Only for SVC-T streaming.

**eDisplayMode\_Frameskip6**

Skip 6 frame for every 8 incoming frames. Only for SVC-T streaming.

**eDisplayMode\_Frameskip7**

Skip 7 frame for every 8 incoming frames. Only for SVC-T streaming.

[Remarks](#)

---

[Requirements](#)

---

AvSynchronizer.h

### 4.1.13 EDISPLAYINFOFLAG

This enumeration indicates the type of this callback. Used by [LPDISPLAYCALLBACK](#)

```
typedef enum {
    DIF_PIC_SIZE                = 1,
    DIF_CONNECTING              = 2,
    DIF_SHOW_BLANK              = 4,
    DIF_SHOW_AUDIOONLY         = 8,
    DIF_IGNORE_BORDER           = 16,
    DIF_RESUMING                = 32,
    DIF_TELLME_RECT             = 64,
    DIF_DUMMY                   = 128
} EDISPLAYINFOFLAG;
```

#### Values

##### **DIF\_PIC\_SIZE**

If this flag is set, the caption you draw will be scaled when the picture scaled.

##### **DIF\_CONNECTING**

If this flag is set, then you can show the texts or graphics that you want to show during the time connecting to server.

##### **DIF\_SHOW\_BLANK**

If AP does not specify the bitmap to be displayed before media data is input, it could ask AVSynchronizer to call back when the window needs to be redrawn.

##### **DIF\_SHOW\_AUDIOONLY**

Called back each second when the channel is playing with audio only data. In such case, AP could display anything it likes to be shown to let users know that it's now audio only mode. When return from the callback, if the AP needs only the border part, it could return AVSYNCHRONIZER\_S\_NO\_CONTENT, AVSynchronizer will skip the area not belong to border.

##### **DIF\_IGNORE\_BORDER**



For audio only media type channel, the callback needs AP to fill data in the window, but the border is ignored. This flag just let AP knows that it should not draw the border in current time.

### **DIF\_RESUMING**

For RTSP channel, callback to let application shows resuming message. It will continue to call until I frame reaches.

### **DIF\_TELLME\_RECT**

The callee must tell the callback about the rect and color valid for caption.

### Remarks

---

### Requirements

---

AvSynchronizer.h

#### 4.1.14 EFRAMETYPE

---

This enumeration indicates the type of frame (audio / video).

```
typedef enum {  
  
    AUDIO_FRAME                = 1,  
  
    VIDEO_FRAME                = 2,  
  
} EFRAMETYPE;
```

---

##### Values

###### **AUDIO\_FRAME**

An Audio frame.

###### **VIDEO\_FARME**

A Video frame.

---

##### Remarks

---

##### Requirements

AvSynchronizer.h

### 4.1.15 EGRAPHALIGN

This enumeration specified if the alignment for horizontal and vertical direction when displaying video if users don't want the video to be stretched. It's used when calling [AvSynchronizer\\_SetChannelOption](#).

```
typedef enum {
    ALIGN_HORI_CENTER          = 0,
    ALIGN_HORI_LEFT            = 1,
    ALIGN_HORI_RIGHT           = 2,
    ALIGN_VERT_CENTER          = 0,
    ALIGN_VERT_TOP             = 4,
    ALIGN_VERT_BOTTOM          = 8,
} EGRAPHALIGN;
```

#### Values

##### **ALIGN\_HORI\_CENTER**

Align the video to center in horizontal direction. If the video width is smaller than the width of the display area, Users will see the left and right black (or any color set when calling [AvSynchronizer\\_InitialEx](#)) area. If the video width is larger, then only the center part (horizontally) of the video will be shown.

##### **ALIGN\_HORI\_LEFT**

Align the video to left in horizontal direction. No matter video is larger or smaller, the left side of the video is align with the left side of the display area.

##### **ALIGN\_HORI\_RIGHT**

Align the video to right in horizontal direction. No matter video is larger or smaller, the right side of the video is align with the right side of the display area.

##### **ALIGN\_VERT\_CENTER**

Align the video to center in vertical direction. If the video height is smaller than the height of the display area, Users will see the top and bottom black (or any color set when calling [AvSynchronizer\\_InitialEx](#)) area. If the video height is larger, then only the center part (vertically) of the video will be shown.

##### **ALIGN\_VERT\_TOP**

Align the video to top in vertical direction. No matter video is larger or smaller, the top side of the video is align with the top side of the display area.

### **ALIGN\_VERT\_BOTTOM**

Align the video to bottom in vertical direction. No matter video is larger or smaller, the bottom side of the video is align with the bottom side of the display area.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.1.16 EMEDIATYPE (TMediaType)

---

This enumeration indicates the Media type of the channel. Used by [AvSynchronizer\\_UpdateChannelSettings](#) and [AvSynchronizer\\_UpdatePlaybackChannelSettings](#).

```
typedef enum {  
  
    AVSYNCHRONIZER_MEDIATYPE_VIDEO_ONLY        = 0x0001,  
    AVSYNCHRONIZER_MEDIATYPE_AUDIO_ONLY        = 0x0002,  
    AVSYNCHRONIZER_MEDIATYPE_AUDIO_VIDEO      = 0x0003,  
  
} EMEDIATYPE, TMediaType;
```

#### Values

---

##### **AVSYNCHRONIZER\_MEDIATYPE\_AUDIO\_ONLY**

The channel is audio only.

##### **AVSYNCHRONIZER\_MEDIATYPE\_VIDEO\_ONLY**

The channel is video only.

##### **AVSYNCHRONIZER\_MEDIATYPE\_AUDIO\_VIDEO**

The channel has both audio and video.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

### 4.1.17 EMOTIONALERTCOLOR

---

This enumeration indicates the color of the Motion detection rectangle.

```
typedef enum {  
  
    RECT_RED                = 0,  
    RECT_GREEN              = 1,  
    RECT_BLUE               = 2,  
    RECT_GRAY               = 3  
  
} EMOTIONALERTCOLOR;
```

#### Values

---

##### **RECT\_RED**

Indicate to draw red rectangle.

##### **RECT\_GREEN**

Indicate to draw green rectangle.

##### **RECT\_BLUE**

Indicate to draw blue rectangle.

##### **RECT\_GRAY**

Indicate to draw gray rectangle.

#### Remarks

---

Besides these color, it is possible to use RGB() macro to define your own color, the color field must be set the MSB to 1 and set the low 3 bytes to hold the RGB value.

#### Requirements

---

AvSynchronizer.h

## 4.1.18 EPBCHFLAG

This enumeration indicates which field of the structure [TPBCHOPTION](#) is valid.

```
typedef enum {
    PBCH_STATUSCB                = 0x00000001,
    PBCH_DISPLAYCB               = 0x00000002,
    PBCH_ALLCALLBACK             = 0x10000003,
    PBCH_STATUSCONTEXT           = 0x00000004,
    PBCH_DISPLAYCONTEXT           = 0x00000008,
    PBCH_ALLCONTEXT              = 0x2000000c,
    PBCH_VOLUME                  = 0x00000010,
    PBCH_LFBORDER                = 0x00000020,
    PBCH_RTBOARDER              = 0x00000040,
    PBCH_TPBORDER                = 0x00000080,
    PBCH_BTBOARDER              = 0x00000100,
    PBCH_ALLBOARDER              = 0x000001e0,
    PBCH_BITMAP                  = 0x00000200,
    PBCH_MOTION                  = 0x00000400,
    PBCH_MOTIONRECT              = 0x00000800,
    PBCH_MOTIONRECTALERT         = 0x00001000,
    PBCH_VIDEOOUT                = 0x00002000,
    PBCH_AUDIOOUT                = 0x00004000,
    PBCH_NEXTFRAME               = 0x08000000,
    PBCH_INPUTCB                 = 0x10000000,
    PBCH_INPUTCONTEXT            = 0x20000000,
    PBCH_BLOCKING                = 0x40000000,
    PBCH_ALL                     = 0xFFFFFFFF
} EPBCHFLAG;
```

### Values

#### PBCH\_STATUSCB



pfStatus field is valid.

#### **PBCH\_DISPLAYCB**

pfDisplay field is valid.

#### **PBCH\_ALLCALLBACK**

All the callback is valid. pfStaus, pfDisplay and pfFrameRequest.

#### **PBCH\_STATUSCONTEXT**

dwStatusContext is valid.

#### **PBCH\_DISPLAYCONTEXT**

dwDisplayContext is valid.

#### **PBCH\_ALLCONTEXT**

All the context is valid. dwStatusContext, dwDisplayContext and dwFrameRequestContext.

#### **PBCH\_VOLUME**

dwVolume is valid,

#### **PBCH\_LFBORDER**

dwLeftBorderSize is valid.

#### **PBCH\_RTBOARDER**

dwRightBorderSize is valid.

#### **PBCH\_TPBORDER**

dwTopBorderSize is valid.

#### **PBCH\_BTBOARDER**

dwBottomBorderSize is valid.

#### **PBCH\_ALLBORDER**

All the Border is valid. dwLeftBorderSize, dwRightBorderSize, dwRightBorderSize and dwBottomBorderSize.

#### **PBCH\_BITMAP**

hBMP and bSaveBmp are valid.

**PBCH\_MOTION**

bMotionAlert is valid.

**PBCH\_MOTIONRECT**

dwMotionRect is valid.

**PBCH\_MOTIONRECTALERT**

dwMotionRectAlert is valid.

**PBCH\_VIDEOOUT**

bVideoOut is valid.

**PBCH\_AUDIOOUT**

bAudioOut is valid.

**PBCH\_NEXTFRAME**

If this flag is set and in the pause mode, it will display frame by frame or it will return error.

**PBCH\_INPUTCB**

pfFrameRequest is valid.

**PBCH\_INPUTCONTEXT**

dwFrameRequestContext is valid.

**PBCH\_BLOCKING**

bNonBlocking is valid.

**PBCH\_ALL**

All fields are valid.

[Remarks](#)

---

[Requirements](#)

---

AvSynchronizer.h

### 4.1.19 EPIXELFORMAT

This enumeration indicates the output format. Used by [AvSynchronizer\\_CreateDecoderChannel](#).

```
typedef enum {
    PF_YUY2 = 1,
    PF_RGB16565 = 2,
    PF_RGB24 = 3,
    PF_RGB32 = 4,
    PF_BMP16565 = 5,
    PF_BMP24 = 6,
    PF_BMP32 = 7,
    PF_JPEG = 8,
    PF_RGB16555 = 9,
    PF_BMP16555 = 10,
    PF_YUV = 11,
    PF_IYUV = 11,
    PF_BGR16565 = 12,
    PF_BGR24 = 13,
    PF_BGR32 = 14,
    PF_BGR16555 = 15,
    PF_YV12 = 16,
    PF_UYVY = 17
} EPIXELFORMAT;
```

#### Values

##### **PF\_YUY2**

Output YUY2 format.

##### **PF\_RGB16565**

Output RGB16 format. This is raw data. The RGB mask for the data is R(5), G(6), B(5)

##### **PF\_RGB24**

Output RGB24 format. This is raw data.

**PF\_RGB32**

Output RGB32 format. This is raw data.

**PF\_BMP16565**

Output 16 bit Bitmap file with header. The RGB mask for the data is R(5), G(6), B(5)

**PF\_BMP24**

Output 24Bit Bitmap with file header.

**PF\_BMP32**

Output 32Bit Bitmap with file header.

**PF\_JPEG**

The JPEG frame data. The module will need to encode the decoded data into JPEG if the original video type is not JPEG, so the performance of this type would be worse than other format.

**PF\_RGB16565**

Output RGB16 format. This is raw data. The RGB mask for the data is R(5), G(5), B(5).

**PF\_BMP16565**

Output 16 bit Bitmap file with header. The RGB mask for the data is R(5), G(5), B(5).

**PF\_YUV**

Output YUV (4:2:0) format. The Y data is from  $0 \sim W*H - 1$ , U is from  $W*H \sim W*H * 1.25$ , and V is from  $W*H * 1.25 \sim W*H*1.5$ . Where W, H is the width and height of the frame.

**PF\_BGR16565**

Output BGR16565 format.

**PF\_BGR24**

Output BGR24 format.

**PF\_BGR32**

Output BGR32 format.

**PF\_BGR16555**

Output BGR16555 format.

**PF\_YV12**

Output YV12 format.

**PF\_UYVY**

Output UYVY format.

**Remarks**

---

PF\_ BGR16565, PF\_ BGR24, PF\_ BGR32, and PF\_ BGR16555 are only available for Linux platform currently.

**Requirements**

---

AvSynchronizer.h

#### 4.1.20 ESETCHOPTION

This enumeration specified the parameters used when calling [AvSynchronizer\\_SetChannelOption](#).

```
typedef enum {
    SETCH_DEBLOCKING                = 0x00000001,
    SETCH_BLANK_BORDER_CB           = 0x00000002,
    SETCH_GRAPH_STRETCH             = 0x00000003,
    SETCH_GRAPH_ALIGN               = 0x00000004,
    SETCH_NOTIFY_MOTION             = 0x00000005,
    SETCH_RESERVED_HEADER          = 0x00000006,
    SETCH_LEFT_BORDER               = 0x00000007,
    SETCH_RIGHT_BORDER              = 0x00000008,
    SETCH_TOP_BORDER                = 0x00000009,
    SETCH_BOTTOM_BORDER             = 0x0000000A,
    SETCH_DIGITAL_ZOOM              = 0x0000000B,
    SETCH_REDRAW_DIGITAL_ZOOM       = 0x0000000C,
    SETCH_MEDIA_TYPE                = 0x0000000D,
    SETCH_OUTPUT_VIDEO_FRAME        = 0x0000000E,
    SETCH_OUTPUT_AUDIO_FRAME        = 0x0000000F,
    SETCH_DECODE_DATA_FORMAT        = 0x00000010,
    SETCH_DECODE_JPEG_QUALITY       = 0x00000011,
    SETCH_DECODE_CB                 = 0x00000012,
    SETCH_DECODE_VIDEO_BUFFER       = 0x00000013,
    SETCH_DECODE_AUDIO_BUFFER       = 0x00000014,
    SETCH_RESUME_PLAYING            = 0x00000015,
    SETCH_DECODE_CBEX               = 0x00000016,
    SETCH_DISPLAY_PERIOD            = 0x00000017,
    SETCH_AVI_CAPTION_CB_CONFORM    = 0x00000018,
    SETCH_BITMAP_FILE               = 0x00000019,
    SETCH_BITMAP_HANDLE             = 0x0000001A,
    SETCH_CLEAR_QUEUE               = 0x0000001B,
```

```

    SETCH_BACKWARD_I_MODE           = 0x0000001C,
    SETCH_FASTER_CAPTION_ONGRAPH    = 0x0000001D,
    SETCH_ROTATE_IMAGE              = 0x0000001E,
    SETCH_EMPTY_QUEUE              = 0x0000001F,
    SETCH_DISPLAY_REDRAW            = 0x00000020,
    SETCH_FRAME_BUFF_STRIDE         = 0x00000021,
    SETCH_GETAV_TIME                = 0x00000022,
    SETCH_DEINTERLACE              = 0x00000023,
    SETCH_VIDEO_FRAME_BEFORE_DISPLAY = 0x00000024,
    SETCH_AV_NOT_SYNC               = 0x00000025,
    SETCH_AVI_MAX_FILE_SIZE         = 0x00000026,
    SETCH_AVI_FILE_TIME_INTERVAL    = 0x00000027,
    SETCH_PREROLL                   = 0x00000028,
    SETCH_NOT_FORCE_SHOW_FRAME      = 0x00000029,
    SETCH_NOT_BLOCK_WHEN_QUEUE_FULL = 0x0000002A,
    SETCH_ANTI_TEARING              = 0x0000002C,
    SETCH_DISPLAYCALLBACK_INTERVAL  = 0x0000002D,
    SETCH_USE_CUDA                  = 0x0000002E,
    SETCH_USE_FFMPEG                = 0x0000002F,
    SETCH_THREAD_COUNT              = 0x00000030,
    SETCH_IVA_RULES                 = 0x00000031,
    SETCH_DRAW_METADATA             = 0x00000032,
    SETCH_DRAW_RULE_NAME            = 0x00000033,
    SETCH_HARDWARE_ACCELERATION_H264 = SETCH_USE_CUDA,
    SETCH_HARDWARE_ACCELERATION_MP4V = 0x00000034,
    SETCH_HARDWARE_ACCELERATION_HEVC = 0x00000035,
    SETCH_DRAW_METADATA_NAME        = 0x00000036,
    SETCH_BACKWARD_OPTION           = 0x00000037,
    SETCH_SNAPSHOT_CALLBACK         = 0x00000038,

```

```

} ESETCHOPTION;

```

## Values

---

### SETCH\_DEBLOCKING

Enable or disable the de-blocking capability of the decoder. Enabled de-blocking would gain better quality but will suffer a much worse performance. When setting with this option, the param1 is the Boolean value for enabling (TRUE) or disabling (FALSE).

The default value is FALSE.

### SETCH\_BLANK\_BORDER\_CB

Enable or disable the blank border callback. The param1 is Boolean value: TRUE to enable border callback, FALSE to disable the callback. This is for some applications that need to display their own pattern rather than bitmap before channel display video.

The default is FALSE.

### SETCH\_GRAPH\_STRETCH

Should the channel stretch video when displaying? The param1 is TRUE to stretch, FALSE not. The default value is TRUE. If it is set to FALSE, SETCH\_GRAPH\_ALIGN could be used to specify the alignment in both horizontal and vertical direction.

### SETCH\_GRAPH\_ALIGN

Specify the alignment for horizontal and vertical direction. The param1 is the alignment for horizontal direction, and param2 is the alignment setting for vertical direction. The value range could be found in [EGRAPHALIGN](#). The default alignment is both center in the tow direction.

### SETCH\_NOTIFY\_MOTION

Specify if AVSynchronizer should notify AP that motion is triggered. The param1 is the Boolean value: TRUE to enable the notification, FALSE to disable the notification.

Default value is FALSE.

### SETCH\_RESERVED\_HEADER

Set the reserved header for decoder channel. This value is only used for notifying decoded video frame. The param1 is the wanted reserved size in bytes.

### SETCH\_LEFT\_BORDER

Set the left border for playback channel or normal channel. The param1 is the wanted left border size in pixel.



**SETCH\_RIGHT\_BORDER**

Set the right border for playback channel or normal channel. The param1 is the wanted left border size in pixel.

**SETCH\_TOP\_BORDER**

Set the top border for playback channel or normal channel. The param1 is the wanted left border size in pixel.

**SETCH\_BOTTOM\_BORDER**

Set the bottom border for playback channel or normal channel. The param1 is the wanted left border size in pixel.

**SETCH\_DIGITAL\_ZOOM**

Set the digital zoom parameters for normal or playback channel. The param1 is a pointer for the [TDIGITALZOOMPARAM](#) structure and param2 is the flag to specify the valid members in the structure. Note: digital zoom is now valid for GDI mode only.

**SETCH\_REDRAW\_DIGITAL\_ZOOM**

Force to redraw the digital editing window. The video for this channel is not redrawn.

The parameters are not used.

**SETCH\_MEDIA\_TYPE**

Update the media type of a channel dynamically. It is very important to change to correct type. For example, if the new type is changed to A/V but no audio is input, the video will be blocked there. The param1 is the new media type for the channel. It's only available for normal and playback channel.

**SETCH\_OUTPUT\_VIDEO\_FRAME**

For decoder channel, it tells the decoder to decode the video only, but not output or callback the decoded video frame data. This is useful for fast forward because in such case, only some frames need to be shown but due to the nature of MPEG4, all frames must be encoded. For normal or playback channel, this is to set the output of video frame during displaying. Application could request to get the decoded video frame in any available format no matter GDI or DirectDraw are used. The output mode is disabled default for normal and playback channel. The param1 is a Boolean to specify if users want to output the frame.

**SETCH\_OUTPUT\_AUDIO\_FRAME**

For decoder channel, it tells the decoder whether to decode audio data, if it is set to false, the audio input data will be skipped. For normal or playback channel, this is to set the output of audio frame during playing. The output mode is disabled default for normal and playback channel. The param1 is a Boolean to specify if users want to output the frame.

### **SETCH\_DECODE\_DATA\_FORMAT**

For decoder channel, it tells the decoder what video format to output, this value could be changed at runtime. The param1 is the new format. For normal and playback channel, this is to specify what format to output during playing. If the option is not set, no media will be called back.

### **SETCH\_DECODE\_JPEG\_QUALITY**

Update the jpeg encode quality factor, the value range is 1-125. The param1 is the new quality value. This option is applied to normal, playback, and decoder channel.

### **SETCH\_DECODE\_CB**

Setup the decoder callback for normal and playback channel. If the callback is empty, no callback will be made during playing. The param1 is the context for the callback, and param2 is the function pointer for the callback.

### **SETCH\_DECODE\_VIDEO\_BUFFER**

Set up the video decoding buffer for normal and playback channel. The buffer is used when callback is made. If no buffer is specified, internal buffer will be used.

The param1 is the size of the buffer and param2 is the starting address of the buffer.

Note, if the given buffer is too small, no callback will be made. The buffer needed for each video format is different, but a 704x576x4 + proper reserved header (1024 for example) buffer size could fit most case. Note, if the graph is translate to Jpeg, the buffer size above might sometimes not enough due to complex graph content. But that's quite extreme case.

### **SETCH\_DECODE\_AUDIO\_BUFFER**

Set up the audio decoding buffer for normal and playback channel. The buffer is used when callback is made. If no buffer is specified, internal buffer will be used.

The param1 is the size of the buffer and param2 is the starting address of the buffer.

Note, if the given buffer is too small, no callback will be made. The buffer needed for each audio depends on the audio codec the channel is using, currently the maximum possible size for one frame is 2048 bytes, some more space for packet header is needed (for example 1024 bytes).

### SETCH\_RESUME\_PLAYING

Tell a channel to wait for vide I frame again. This is usually used in RTSP channel. When this option is set, the channel will wait for I frame and before that frame comes, all decoding and displaying stop. The param1 is the flag to be set. Set True to enable resuming and False to stop resuming state. It only applies to live channel

### SETCH\_DECODE\_CBEX

Set up an extension version of decoded data callback. This callback could replace the normal version. It gives application more information about the format of the decoding data. And If application likes, it could let the module decode for more than one output type. To accomplish this, the application could return a resuming flag and the new wanted type. For example, if the application sets the decoded type to BMP24, and it also needs YUV. When callback function is invoked, it could return resuming flag on and set next decoding type to YUV. After YUV is called, return with resuming flag False to decode next frame. The param1 is the context for the callback, and param2 is the address of the callback. When this and the normal callback are both set, this one is taken. This option applies to live, playback, and decoder channel.

### SETCH\_DISPLAY\_PERIOD

Set up the display period for live and playback channel. The period is counted by frame number. For example, if the period is set to 5, the channel will show 1 frame per 5 decoded frames. This could somehow decrease the system loading. The param1 is the period number to be set, 0 or 1 means to show every frame decoded. The param2 is a flag to indicate if the live/playback channels' decode data callbacks are affected by this number. If it is set to be True, the callback will also be called back per period number. If the param2 is false, the callback will be called for every frame.

### SETCH\_AVI\_CAPTION\_CB\_CONFORM

To set if the DrawTime member of [TDISPLAYINFO](#) structure in AVI channel's [LPDISPLAYCALLBACK](#) contains a time\_t value or a "struct tm" pointer. In version before 4.3.0.0, the data member contains a time\_t value. And this is not the same as other channels. To maintain backward compatibility, if this option is not set, the member is still a time\_t value. But if this option is set, the value will contain a pointer to "struct tm". The time\_t value is moved to a new member of dwTimet. The param1 contains Boolean value. True means the DrawTime is a pointer to "struct tm". False means DrawTime is a time\_t value. Only applies to AVI channel.

### SETCH\_BITMAP\_FILE

Set the bitmap to be shown in a channel when off line. The bitmap is assigned by a file name. This module will load the bitmap from the file and maintain it automatically.

Multiple channels will share the same bitmap if the content of the file is the same. This option and the next one are exclusive. And the update channel setting will control the display of this bitmap. The param1 contains the file name (For Windows CE, the file name is in Unicode. For other platform, the name is in char). Only applies to live and playback channel.

#### **SETCH\_BITMAP\_HANDLE**

Update a channel's display bitmap handle. This option and the above one are exclusive. The module will keep the bitmap and maintain it automatically. This means, after the call, application is safe to free the bitmap. The param1 contains the handle to the bitmap (HBITMAP). Only applies to live and playback channel.

#### **SETCH\_CLEAR\_QUEUE**

Set the way to handle if the video queue is full. The param1 is the flag to indicate the way to handle. If param1 is 0, the setting is doing nothing. If param1 is 1, the queue will be cleared only when I frame reaches and queue is full. If param1 is 2, the queue will be cleared when it is full and the I frame flag will be reset. The channel will accept packet only when next I frame reaches. Only applies to normal channel.

#### **SETCH\_BACKWARD\_I\_MODE**

In this mode, the channel will show each I frame for one second. If the format is non-JPEG, the frame will show in reserved sequence. If param1 is true, the backward mode will turn on.

#### **SETCH\_FASTER\_CAPTION\_ONGRAPH**

For some cards, get direct draw dc and painting on graph would be slowing. Setting this flag, the module will use a faster way to handle caption on graph, but the AP must also prepare to handle this type of callback. The drawing area is maximum 640x480 in such mode, and AP must also specify the drawing area before return. To be transparent, mask color must be given.

#### **SETCH\_ROTATE\_IMAGE**

Setting the rotated degree to be 90, 180, or 270 degree in clockwise. This option only works for Windows CE, other platform does not support. param1 is the degree could be.

#### **SETCH\_EMPTY\_QUEUE**

Clear the queue currently playing (both audio and video), this is workable for AP that support switch to time point

#### **SETCH\_DISPLAY\_REDRAW**

Redraw the current channel.

**SETCH\_FRAME\_BUFF\_STRIDE**

Set the stride of the buffer used for retrieving the decoded video frame, dwParam1 is width stride in pixel unit, not in bytes, only works for decoder channel. Set value to 0 would make the scan line continuous in memory.

**SETCH\_GETAV\_TIME**

Get the current time (only second) of the audio and video. The time is the last video and audio frame been played. param1 is the address to hold video time, return 0 if audio only and param2 is the address to hold audio time, return 0 if video only.

**SETCH\_DEINTERLACE**

Enable deinterlace, param1 is true for enable and false for disable.

**SETCH\_VIDEO\_FRAME\_BEFORE\_DISPLAY**

Callback the decoded frame before display. AP can do some operations on this frame.

param1 is the context of this callback function and param2 is the callback function pointer, [LPOUTPUTVIDEOFRAMEBEFOREDISPLAY](#).

**SETCH\_AV\_NOT\_SYNC**

If param1 is TRUE, A/V will not sync and go on their best speed

**SETCH\_AVI\_MAX\_FILE\_SIZE**

Set max avi file size, this is for avi channel. This setting should be called before [AvSynchronizer StartAVIChannel](#). param1 is the max file size of avi file. If the file size reaches the max value, AvSynchronizer will generate another avi file whose name is to append a number(from 1, 2, 3,...) to current avi file name.

**SETCH\_AVI\_FILE\_TIME\_INTERVAL**

Set max avi file length, only for avi channel. This setting should be called before [AvSynchronizer StartAVIChannel](#). param1 is the time interval of avi file and its unit is minute. If the time length reaches the max value, AvSynchronizer will generate another avi file whose name is to append a number(from 1, 2, 3,...) to current avi file name.

param2 is TRUE means using time length to divide the avi file. And param2 is FALSE to disable this function

**SETCH\_NOT\_FORCE\_SHOW\_FRAME**

Playback channel will force the current video to show if the queue is full. param1 = TRUE to disable this behavior.

### **SETCH\_NOT\_BLOCK\_WHEN\_QUEUE\_FULL**

In Playback channel, if AP inputs packets to AvSynchronizer and the internal queue fulls, Playback channel will block the calling thread until internal queue has free space.

User can turn off this mechanism by setting param1 to TRUE or turn on it again by setting param1 = FALSE. This mechanism turn on by default.

### **SETCH\_ANTI\_TEARING**

Set the anti\_tearing policy, please refer to [EANTITEARING](#). The default value is ANTI\_TEARING\_DISABLED.

### **SETCH\_DISPLAYCALLBACK\_INTERVAL**

Set display callback timing. dwParam1 is [EDISPLAYCALLBACK\\_INTERVAL](#)

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

### 4.1.21 ESNAPSHOTFLAG

This enumeration specified if capturing image in original video size. Used by [AvSynchronizer\\_GetCurrentSnapShot](#).

```
typedef enum {
    VISIBLE_SIZE                = 0x0,
    ORIGINAL_SIZE               = 0x01,
    SOURCE_IMAGE                = 0x02,
    SPECIFY_FMT                 = 0x04
    GIVEN_BUFFER                = 0x08
} ESNAPSHOTFLAG;
```

#### Values

##### **VISIBLE\_SIZE**

Capture the image in the visible size.

##### **ORIGINAL\_SIZE**

Capture the image in the original video size.

##### **SOURCE\_IMAGE**

Get the current source encoded image data. This is helpful when the source is JPEG and users want to get JPEG graph.

##### **SPECIFY\_FMT**

Get the data according to specified, the high word of the flag is the format of the request 'fmt'. The available format is listed as [EPIXELFORMAT](#).

##### **GIVEN\_BUFFER**

The buffer pDataStart of [TSNAPSHOT](#) is given by caller, in such case the dwdataSize must specify the buffer size. When return, dwdataSize will be modified to the real size of the buffer if caller needs to reuse the buffer, the buffer size value must be saved before calling this function.

#### Remarks

## Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20



### 4.1.22 ESTARTAVICHFLAG

This enumeration specified the flags in [TAVICHOPTION2](#).

```
typedef enum {  
  
    FIXED_VINFO_AT_FIRST_FRAME          = (1<<2),  
    FIXED_AINFO_AT_FIRST_FRAME          = (1<<3),  
    KEEP_ORIGINAL_VIDEO_TRACK           = (1<<4),  
    KEEP_ORIGINAL_AUDIO_TRACK           = (1<<5),  
  
} ESTARTAVICHFLAG;
```

#### Values

##### **FIXED\_VINFO\_AT\_FIRST\_FRAME**

This flag means that the video size of the output AVI file would be determined by the first of the video frame. All the subsequence frames would be stretched to match this size. If this flag is not set, users need to give the wanted video size when start the channel.

##### **FIXED\_AINFO\_AT\_FIRST\_FRAME**

This flag means that the audio sample frequency of the output AVI file would be determined by the first of the audio frame. All the subsequence frames would be transform to this frequency. If this flag is not set, users need to give the wanted audio sampling frequency when start the channel.

#### Remarks

This enumeration is only available for Windows 32 platform.

#### Requirements

AvSynchronizer.h

### 4.1.23 ESTARTCHANNELFLAG

---

This enumeration indicates if needed to show something during the time connecting to server. Used by [AvSynchronizer\\_StartChannel](#)

```
typedef enum {  
  
    DRAW_CONNECTING                = 0x00000001,  
    USE_REVERSE_CACHE              = 0x00000002,  
  
} ESTARTCHANNELFLAG;
```

#### Values

---

##### **DRAW\_CONNECTING**

Set this flag to notify that you want to draw something during the time connecting to the server.

#### Remarks

---

During the time connecting to the server, if DRAW\_CONNECTING is set, then the [LPDISPLAYCALLBACK](#) will be called. You can show some texts or graphics by using the DC.

#### Requirements

---

AvSynchronizer.h

#### 4.1.24 EUPCHOPTION

This enumeration indicates which field of the structure [TUPDATECHANNELOPTION](#) or [TUPDATEPBCHANNELOPTION](#) is valid.

```
typedef enum {
    UPCH_VIDEOOUT          = 0x00000001,
    UPCH_AUDIOOUT          = 0x00000002,
    UPCH_MOTIONALERT       = 0x00000004,
    UPCH_MOTIONRECT        = 0x00000008,
    UPCH_MOTIONRECTALERT   = 0x00000010,
    UPCH_VOLUME            = 0x00000020,
    UPCH_MEDIATYPE         = 0x00000040,
    UPCH_TIMEITV_CHG       = 0x00000080,
    UPCH_SETSPEED          = 0x00000100,
    UPCH_PAUSE             = 0x00000200,
    UPCH_SHOW_BMP          = 0x00000400,
    UPCH_WIN_HANDLE        = 0x00000800,
    UPCH_RESTORE_WINPROC   = 0x00001000,
    UPCH_IGNORE_BORDER     = 0x00002000,
    UPCH_ALL               = 0xFFFFFFFF
} EUPCHOPTION;
```

#### Values

##### UPCH\_VIDEOOUT

bVideoOut is valid.

##### UPCH\_AUDIOOUT

bAudioOut is valid.

##### UPCH\_MOTIONALERT

bMotionAlert is valid.

##### UPCH\_MOTIONRECT

dwMotionRect is valid.

#### **UPCH\_MOTIONRECTALERT**

dwMotionRectAlert is valid.

#### **UPCH\_VOLUME**

dwVolume is valid.

#### **UPCH\_MEDIATYPE**

tMediaType is valid. This flag is only for [TUPDATEPBCHANNELOPTION](#) structure.

#### **UPCH\_TIMEITV\_CHG**

Set this flag to indicate AvSynchronizer object that time interval change.

#### **UPCH\_SETSPEED**

dwFast and dwSlow is valid.

#### **UPCH\_PAUSE**

bPasue is valid.

#### **UPCH\_SHOW\_BITMAP**

Set this flag to show the specified Bitmap on the channel.

#### **UPCH\_WIN\_HANDLE**

Change the display window handle of a channel.

#### **UPCH\_RESTORE\_WINPROC**

Restore the window message handling proc. Must update this before set the channel a new display window handle.

#### **UPCH\_IGNORE\_BORDER**

Do not show the border when update graph. The video frame will fill the whole window when this is set.

#### **UPCH\_ALL**

All fields are valid.

#### [Remarks](#)

---

## Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.1.25 EFISHEYEPRESENTMODE

This enumeration specified the present mode of fisheye.

```
typedef enum {
    FEPRESENTMODE_SINGLE_SOURCE_STRETCH          = 0,
    FEPRESENTMODE_SINGLE_SOURCE_CONSTRAINPROP    = 1,
    FEPRESENTMODE_SINGLE_PERSPECT_VIEW           = 2,
    FEPRESENTMODE_SINGLE_PANORAMA_VIEW           = 3,
    FEPRESENTMODE_DOUBLE_SOURCE_PERSPECT         = 4,
    FEPRESENTMODE_DOUBLE                         = 5,
    FEPRESENTMODE_TRIPLE                         = 6,
    FEPRESENTMODE_QUAD_WITH_SOURCE_CONSTRAINPROP = 7,
    FEPRESENTMODE_QUAD_PERSPECT_VIEW             = 8,
    FEPRESENTMODE_QUAD_PERSPECT_VIEW_INTERFERED  = 9,
    FEPRESENTMODE_QUAD_WITH_PANORAMA_VIEW        = 10,
    FEPRESENTMODE_NINE                           = 11
} EFISHEYEPRESENTMODE;
```

#### Values

##### **FEPRESENTMODE\_SINGLE\_SOURCE\_STRETCH**

Single view of stretched original source

##### **FEPRESENTMODE\_SINGLE\_SOURCE\_CONSTRAINPROP**

Single view of original source with unchanged aspect ratio.

##### **FEPRESENTMODE\_SINGLE\_PERSPECT\_VIEW**

Single view of perspective projection(calibrated).

##### **FEPRESENTMODE\_SINGLE\_PANORAMA\_VIEW**

Single panorama view.

##### **FEPRESENTMODE\_DOUBLE\_SOURCE\_PERSPECT**

Two perspective projection.

**FEPRESENTMODE\_DOUBLE**

Two panorama views, one for upper half and the other for lower one. This is only for 360 mode.

**FEPRESENTMODE\_TRIPLE**

Three calibrated sources, one is panorama and others are perspective.

**FEPRESENTMODE\_QUAD\_WITH\_SOURCE\_CONSTRAINPROP**

Quadruple views, one original source with unchanged aspect ratio and the others are perspective projection.

**FEPRESENTMODE\_QUAD\_PERSPECT\_VIEW**

Four perspective projection.

**FEPRESENTMODE\_QUAD\_PERSPECT\_VIEW\_INTERFERED**

Four perspective projection, each one stands for 90 degree. When user move one view with certain angle, others will be changed as the same degree. This is only for 360 mode.

**FEPRESENTMODE\_QUAD\_WITH\_PANORAMA\_VIEW**

One panorama and three perspective projection.

**FEPRESENTMODE\_NINE**

Nine views, the center one is original and the remainings are perspective projection.

**Remarks**

---

**Requirements**

---

AvSynchronizer\_Fisheye.h

### 4.1.26 EFISHEYEPTZRCONTROLFLAGS

This enumeration specified the control mode PTZ and rotate.

```
typedef enum {  
  
    FEPTZRCONTROL_PTR                = 1,  
    FEPTZRCONTROL_Z                  = 2,  
    FEPTZRCONTROL_RESET              = 4,  
    FEPTZRCONTROL_CLICK              = 8,  
    FEPTZRCONTROL_ANCHOR             = 16,  
    FEPTZRCONTROL_AUTOSPEED          = 32,  
  
} EFISHEYEPTZRCONTROLFLAGS;
```

#### Values

##### **FEPTZRCONTROL\_PTR**

Pan, tilt and rotate control.

##### **FEPTZRCONTROL\_Z**

Zoom control.

##### **FEPTZRCONTROL\_RESET**

Reset control.

##### **FEPTZRCONTROL\_CLICK**

Click-on-image mode control.

##### **FEPTZRCONTROL\_ANCHOR**

Set focus to a specific view.

##### **FEPTZRCONTROL\_AUTOSPEED**

Speed of auto panoramic view

#### Remarks



## Requirements

---

AvSynchronizer\_Fisheye.h

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.1.27 EFISHEYEUPDATEROTATEOPTFLAGS

---

This enumeration indicates which fields of the structure of [TFISHEYEROTATEOPTIONS](#) is valid.

```
typedef enum {  
  
    FEUPDATEROTATE_POINTS           = 1,  
    FEUPDATEROTATE_TARGET          = 2,  
    FEUPDATEROTATE_SPEED            = 4,  
  
} EFISHEYEUPDATEROTATEOPTFLAGS;
```

##### Values

---

###### **FEUPDATEROTATE\_POINTS**

Update rotation points.

###### **FEUPDATEROTATE\_TARGET**

Update target window.

###### **FEUPDATEROTATE\_SPEED**

Update rotation speed.

##### Remarks

---

##### Requirements

---

AvSynchronizer\_Fisheye.h

#### 4.1.28 EFISHEYEUPDATEVIEWERFLAGS

---

This enumeration indicates which fields of the structure [TFISHEYEVIEWER](#) is valid.

```
typedef enum {  
  
    FEUPDATEVIEWER_PRESENTMODE           = 1,  
    FEUPDATEVIEWER_VIEWERANGLE          = 2,  
    FEUPDATEVIEWER_CONTROLCOMMANDS      = 4,  
    FEUPDATEVIEWER_SHOWFOCUSREGION      = 8  
  
} EFISHEYEUPDATEVIEWERFLAGS;
```

##### Values

---

###### **FEUPDATEVIEWER\_RESENTMODE**

Present mode.

###### **FEUPDATEVIEWER\_VIEWANGLE**

Viewer angle.

###### **FEUPDATEVIEWER\_CONTROLCOMMANDS**

Control commands.

###### **FEUPDATEVIEWER\_SHOWFOCUSREGION**

Show focus region.

##### Remarks

---

##### Requirements

---

AvSynchronizer\_Fisheye.h

#### 4.1.29 EFISHEYEWIEWERANGLEFLAGS

---

This enumeration specified the viewing mode of fisheye. The viewing mode depends on the mount type of the camera. If the camera is wall mount, the viewing angle should be 180. If the camera is ceiling/floor mount, user should choose 360.

```
typedef enum {  
  
    FEVIEWERANGLE_180            = 0,  
    FEVIEWERANGLE_360            = 1,  
    FEVIEWERANGLE_360I           = 2  
  
} EFISHEYEWIEWERANGLEFLAGS;
```

---

##### Values

###### **FEVIEWERANGLE\_180**

180 degree viewer angle.

###### **FEVIEWERANGLE\_360**

360 degree viewer angle.

###### **FEVIEWERANGLE\_360I**

360 degree viewer angle for floor mount.

---

##### Remarks

---

##### Requirements

AvSynchronizer\_Fisheye.h

### 4.1.30 TsdrAudioCodec

This enumeration indicates the audio codec types.

```
typedef enum {
    eACodecNone           = 0x0000,
    eACodecG7221          = 0x0100,
    eACodecG729A          = 0x0200,
    eACodecAAC             = 0x0400,
    eACodecGAMR            = 0x0800
} TsdrAudioCodec;
```

#### Values

##### **eACodecNone**

no audio codec

##### **eACodecG7221**

G.722.1

##### **eACodecG729A**

G.729A

##### **eACodecAAC**

AAC (stereo)

##### **eACodecGAMR**

GAMR, used in RTSP IP camera and server

#### Remarks

#### Requirements

SrvTypeDef.h

### 4.1.31 TsdrVideoCodec

---

This enumeration indicates the video codec types.

```
typedef enum {  
  
    eVCodecNone           = 0x00000000,  
    eVCodecMJPEG          = 0x00000001,  
    eVCodecH263           = 0x00000002,  
    eVCodecMPEG4           = 0x00000004,  
  
} TsdrVideoCodec;
```

#### Values

---

##### **eVCodecNone**

no video codec

##### **eVCodecMJPEG**

Motion JPEG

##### **eVCodecH263**

H.263

##### **eVCodecMPEG4**

MPEG-4

#### Remarks

---

#### Requirements

---

SrvTypeDef.h

#### 4.1.32 EMediaCodecType

---

This enumeration indicates the media codec type. Please refer to Data Packet Parser document for detail definition

VIVOTEK CONFIDENTIAL  
2017.01.20

## 4.2 Callback Function

---

The Callback function is depicted here.

VIVOTEK CONFIDENTIAL  
2017.01.20



## 4.2.1 LPDECODEFRAMECALLBACK

---

This callback function is used to notify the application the decoded audio or video frame.

The timestamp for the original frame is reserved in the structure. This callback is used in decoder, normal and playback channel.

### Syntax

---

```
typedef SCODE ( __stdcall * LPDECODEFRAMECALLBACK)  
  
                DWORD          dwContext,  
                TFrameType     tFrameType,,  
                TFRAMEINFO      *ptFrameInfo,  
  
);
```

### Parameters

---

#### **dwContext**

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

#### **tFrameType**

[in] indicate this frame is audio or video.

#### **ptFrameInfo**

[in] according to the audio frame or video frame pointer to the different structure.

### Return Values

---

Returns S\_OK if success, or an error value otherwise.

### Remarks

---

The buffer will be used for further decoding, so when called back, application needs to copy the frame to its own buffer for future use.

### Requirements

---

AvSynchronizer.h

## 4.2.2 LPDECODEFRAMECALLBACK\_EX

This extended callback function is used to notify the application the decoded audio or video frame. The timestamp for the original frame is reserved in the structure. This callback is used in decoder, normal and playback channel. It is to be used to replace [LPDECODEFRAMECALLBACK](#).

### Syntax

```
typedef SCODE (__stdcall * LPDECODEFRAMECALLBACK_EX)

                                DWORD          dwContext,
                                TFrameType      tFrameType,,
                                TFRAMEINFOEX    *ptFrameInfoEx,

);
```

### Parameters

#### **dwContext**

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

#### **tFrameType**

[in] indicate this frame is audio or video.

#### **ptFrameInfoEx**

[in] according to the audio frame or video frame pointer to the different structure.

### Return Values

Returns S\_OK if success, or an error value otherwise.

### Remarks

The buffer will be used for further decoding, so when called back, application needs to copy the frame to its own buffer for future use.

### Requirements

AvSynchronizer.h

### 4.2.3 LPDISPLAYCALLBACK

This callback function is used to notify the application before displaying.

#### Syntax

```
typedef SCODE (__stdcall * LPDISPLAYCALLBACK)  
  
                                DWORD          dwContext,  
                                TDISPLAYINFO *ptDisplayInfos,  
  
);
```

#### Parameters

##### **dwContext**

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

##### **ptDisplayInfos**

[in] address of the structure contains some information. See Remarks.

#### Return Values

Returns S\_OK if success, or an error value otherwise.

#### Remarks

Because the callback is called from internal thread, it is not proper to call to many UI functions in this callback. To many UI calls might cause un-predicted result.

#### Requirements

AvSynchronizer.h

## 4.2.4 LPOUTPUTVIDEOFRAMEBEFOREDISPLAY

This callback function is used to callback the decoded frame before display.

### Syntax

```
typedef SCODE (__stdcall *  
LPOUTPUTVIDEOFRAMEBEFOREDISPLAY)          DWORD          dwContext,  
                                              TVIDEOINFO        *ptVideoInfo,  
);
```

### Parameters

#### **dwContext**

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

#### **ptVideoInfo**

[in] address of [TVIDEOINFO](#)

### Return Values

Returns S\_OK if success, or an error value otherwise.

### Remarks

Because the callback is called from internal thread, it is not proper to call to many UI functions in this callback. To many UI calls might cause un-predicted result.

### Requirements

AvSynchronizer.h

## 4.2.5 LPENDOFSTREAMING

---

This callback function is used to notify the application when the internal queue of AvSynchronizer is empty.

### Syntax

---

```
typedef SCODE (__stdcall * LPENDOFSTREAMING)  
  
void *pvContext,  
  
);
```

### Parameters

---

#### dwContext

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

### Return Values

---

Returns S\_OK if success, or an error value otherwise.

### Remarks

---

Because the callback is called from internal thread, it is not proper to call to many UI functions in this callback. To many UI calls might cause un-predicted result.

### Requirements

---

AvSynchronizer.h

## 4.2.6 LPINPUTFRAMEREQUESTCALLBACK

Reserved. This callback function is not implemented yet.

### Syntax

```
typedef SCODE (__stdcall * LPINPUTFRAMEREQUESTCALLBACK)
                                     DWORD          dwContext,
                                     HANDLE          hChannel
);
```

### Parameters

#### dwContext

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

#### hChannel

[in] the Handle of the channel.

### Return Values

Return NO\_MORE\_DATA if the channel has no more data to be played, return S\_OK otherwise.

### Remarks

This function is used for nonblocking mode.

The application should call the [AvSynchronizer InputPlaybackMediaFrame](#) to push the packet into internal queue.

### Requirements

AvSynchronizer.h

### 4.2.7 LPSTATUSCALLBACK

---

This callback function is used to notify the application the status of the AvSynchronizer.

#### Syntax

---

```
typedef SCODE (__stdcall * LPSTATUSCALLBACK)

                                DWORD          dwContext,
                                DWORD          dwStatusCode,
                                DWORD          dwParam1,
                                DWORD          dwParam2

);
```

#### Parameters

---

##### **dwContext**

[in] Specify the application-defined value that is passed, along with the returned handle, to this function.

##### **dwStatusCode**

[in] This is the status code that indicates why the callback function is being called. This parameter can be one of the values listed in [ECHANNELSTATUS](#).

##### **dwParam1**

[in] additional status information.

##### **dwParam2**

[in] additional status information.

#### Return Values

---

Returns S\_OK if success, or an error value otherwise.

#### Remarks

---

Because the callback is called from internal thread, it is not proper to call to many UI functions in this callback. To many UI calls might cause un-predicted result.

## Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20



### 4.3 Data Structure

---

The data structure is depicted here.

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.1 TAVSYNCQUEUESTATUS

---

This structure is used when calling [AvSynchronizer\\_GetRemainingQueueElementCount](#).

```
typedef struct {  
  
        DWORD          dwAudioQueueElements;  
  
        DWORD          dwVideoQueueElements;  
  
        DWORD          dwAudioQueueSize;  
  
        DWORD          dwVideoQueueSize;  
  
} TAVSYNCQUEUESTATUS;
```

#### Members

---

##### **dwAudioQueueElements**

The remaining queue elements in audio buffer queue.

##### **dwVideoQueueElements**

The remaining queue elements in video buffer queue.

##### **dwAudioQueueSize**

The size of audio buffer queue.

##### **dwVideoQueueSize**

The size of video buffer queue.

#### Remarks

---

There are two kinds of queues in AvSynchronizer. One is buffer queue and the other is data queue. Buffer queue is the free queue that can be used when user input media frame. If dwAudioQueueElements/dwVideoQueueElements is zero, AP will get queue full message when inputting media frame.

This structure is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer.h

### 4.3.2 TAFRAMEINFO

This structure is used by [LPDECODEFRAMECALLBACK](#) function.

```
typedef struct {
    DWORD dwTime;
    DWORD dwSize;
    BYTE *pbySound;
    DWORD dwTimeStampSec;
    DWORD dwTimeStampMiliSec;
    TMediaDataPacketInfo tPacketInfo;
} TAFRAMEINFO, *PTAFRAMEINFO;
```

#### Members

##### **dwTime**

Specify total time of the frame in millisecond. This time is the length of time that needs to play this piece of sound data. Currently, for eACodecG7221 the value is 20ms, and for eACodecG729A the value is 10ms

##### **dwSize**

Specify the size of the frame in bytes.

##### **pbySound**

A pointer that store the data of the frame.

##### **dwTimeStampSec**

Second of the time stamp for this audio piece.

##### **dwTimeStampMiliSec**

Millisecond of the time stamp for this audio piece. With dwTimeStampSec

##### **tPacketInfo**

The packet info copied from encoded audio frame. Only those fields related to audio are valid.

#### Remarks

## Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.3 TAVIAINFO

---

This structure is used in [TAVICHOPTION2](#)

```
typedef struct {  
  
        DWORD          dwChannels;  
  
        DWORD          dwSamplesPerSec;  
  
        DWORD          dwBitsPerSample;  
  
} TAVIAINFO;
```

#### Members

---

##### **dwChannels**

Specify the number of audio channel in bit stream. Except AAC, all other audio data should specify 1 now. Assign 2 for AAC.

##### **dwSamplesPerSec**

Specify the sample per second for the audio bit stream. Currently only 8000 and 16000 are supported.

##### **dwBitsPerSample**

Specify the bits per sample. Currently, please assign it to 16.

#### Remarks

---

This structure is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer.h

### 4.3.4 TAVICHOPTION

This structure is used by [AvSynchronizer\\_CreateAVIChannel](#) function. It specifies the callback functions for the channel.

```
typedef struct {
    LPSTATUSCALLBACK    pfStatus;
    LPDISPLAYCALLBACK    pfCaption;
    DWORD                dwStatusContext;
    DWORD                dwCaptionContext;
    DWORD                dwBitCount;
} TAVICHOPTION;
```

#### Members

##### **pfStatus**

This is the callback to notify current status of the conversion. Usually, it will be used to update the progress indicator.

##### **pfCaption**

Use to let application draw the caption and border. If application does not need that, set this to NULL.

##### **dwStatusContext**

This is the context associated with the status callback.

##### **dwCaptionContext**

This is the context associated with the caption callback.

##### **dwBitCount**

Reserved. It's not used in current version.

#### Remarks

This structure is only available for Windows 32 platform currently.

#### Requirements

AvSynchronizer.h

### 4.3.5 TCURRENTDISPLAYINFO

---

This structure is used by [AvSynchronizer\\_GetCurrentDisplay](#) function.

```
typedef struct {  
  
        DWORD          dwDisplayWidth;  
  
        DWORD          dwDisplayHeight;  
  
        DWORD          dwTimet;  
  
        DWORD          dwFlag;  
  
} TCURRENTDISPLAYINFO,  
*PTCURRENTDISPLAYINFO;
```

---

#### Members

##### **dwDisplayWidth**

Indicate the display width.

##### **dwDisplayHeight**

Indicate the display height.

##### **dwTimet**

This is the time\_t value for the DrawTime.

##### **dwFlag**

The flag tells if the channel is resuming or audio only.

---

#### Remarks

---

#### Requirements

AvSynchronizer.h

### 4.3.6 TAVICHOPTION2

This structure is used for [AvSynchronizer\\_StartAVIChannel](#) function.

```
typedef struct {
    TAVIVINFO          tAviVInfo;
    TAVIAINFO          tAviAInfo;
    DWORD              dwFrameRate;
    BOOL               bAudioEnable;
    BOOL               bVideoEnable;
    char               szFileName[MAX_PATH];
    TBORDERSIZE        tBorder;
    DWORD              dwFlag;
} TAVICHOPTION2;
```

#### Members

##### **tAviVInfo**

Specify the settings for video stream in AVI file.

##### **tAviAInfo**

Specify the settings for audio stream in AVI file.

##### **dwFrameRate**

Specify the frame rate for video. This is the wanted frame rate, the channel will adjust the frame rate from the input video stream to conform to the wanted frame rate.

##### **bAudioEnable**

Specify whether the channel should generate the audio stream in AVI file.

##### **bVideoEnable**

Specify whether the channel should generate the video stream in AVI file.

##### **szFileName**

Specify the name of the AVI file. The content of the file will be destroyed when generating AVI file.



**tBorder**

Specify the border settings for this channel. If no border is needed, specify 0 for all the member.

**dwFlag**

Specify the extra setting for this channel. The possible values are defined in [ESTARTAVICHFLAG](#).

**Remarks**

---

This structure is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

### 4.3.7 TAVIVINFO

---

This structure is used in [TAVICHOPTION2](#).

```
typedef struct {  
  
        DWORD          dwWidth;  
  
        DWORD          dwHeight;  
  
        DWORD          dwBitCount;  
  
} TAVIVINFO;
```

---

#### Members

##### **dwWidth**

Specify the width of the video in AVI file. This member could be 0 if the FIXED\_VINFO\_AT\_FIRST\_FRAME flag is set in TAVICHOPTION2 structure.

##### **dwHeight**

Specify the height of the video in AVI file. This member could be 0 if the FIXED\_VINFO\_AT\_FIRST\_FRAME flag is set in [TAVICHOPTION2](#) structure.

##### **dwBitCount**

Specify the bitcount of the output file. This value should be always set to 24 now.

---

#### Remarks

---

#### Requirements

AvSynchronizer.h

### 4.3.8 TAVSYNCCALLBACKMOTIONINFO

---

This structure is used in status callback. When callback AVSYNCHRONIZER\_STATUSCODE\_MOTION, the first parameter is the array pointed to this structure.

```
typedef struct {  
  
                                WORD           wPercentage;  
  
                                BOOL           bAlert;  
  
} TAVSYNCCALLBACKMOTIONINFO;
```

---

#### Members

##### **wPercentage**

Percentage of the window.

##### **bAlert**

Is this motion window triggered or not.

---

#### Remarks

---

#### Requirements

AvSynchronizer.h

### 4.3.9 TBORDERSIZE

---

This structure specifies the border setting for the video in an AVI channel.

```
typedef struct {  
  
        DWORD          dwHeader;  
  
        DWORD          dwFooter;  
  
        DWORD          dwLeft;  
  
        DWORD          dwRight;  
  
} TBORDERSIZE;
```

---

#### Members

##### **dwHeader**

The height of the header

##### **dwFooter**

The height for footer

##### **dwLeft**

Specify the width of the left border.

##### **dwRight**

Specify the width of right border.

---

#### Remarks

This structure is only available for Windows 32 / Windows CE platform currently.

---

#### Requirements

AvSynchronizer.h

### 4.3.10 TCHANNELOPTION

This structure collects the settings of the channel. When creating channel, fill this structure to setup the channel.

```
typedef struct {
    DWORD dwFlags;
    LPSTATUSCALLBACK pfStatus;
    LPDISPLAYCALLBACK pfDisplay;
    DWORD dwStatusContext;
    DWORD dwDisplayContext;
    DWORD dwVolume;
    DWORD dwLeftBorderSize;
    DWORD dwRightBorderSize;
    DWORD dwTopBorderSize;
    DWORD dwBottomBorderSize;
    HBITMAP hBMP;
    HWND hVideoOut;
    HWND hDisplay;
    BOOL bSaveBmp;
    BOOL bVideoOut;
    BOOL bAudioOut;
    BOOL bMotionAlert;
    DWORD dwMotionRectAler
    DWORD dwMotionRect;
    BOOL bOrgSizeCallback;
    DWORD dwOrgSizeLeftBorder;
    DWORD dwOrgSizeTopBorder;
    DWORD dwOrgSizeRightBorder;
    DWORD dwOrgSizeBottomBorder;
} TCHANNELOPTION, *PTCHANNELOPTION;
```

#### Members

##### dwFlags

Indicate which field of this structure is valid. It can be one or the combination of the values of [ECHFLAG](#).

**pfStatus**

Specify the pointer to the Status callback function. To be used to notify the application the status of AvSynchronizer.

**pfDisplay**

Specify the pointer to the display callback function. To be used to notify the application to display something.

**dwStatusContext**

Specify the application-defined value that is passed, along with the returned handle, to status callback functions.

**dwDisplayContext**

Specify the application-defined value that is passed, along with the returned handle, to display callback functions.

**dwVolume**

Specify the audio volume. The valid value is 0 ~ 5000. 5000 is the loudest.

**dwLeftBorderSize**

Specify the size of the left border.

**dwRightBorderSize**

Specify the size of the right border.

**dwTopBorderSize**

Specify the size of the top border.

**dwBottomBorderSize**

Specify the size of the bottom border.

**hBMP**

A handle of a bitmap.

**hVideoOut**

Window handle used for the application. Set to the calling application's top-level window handle (not a handle for any child windows created by the top-level window).

**hDisplay**

The handle of the window which the video of this channel will show on it.

**bSaveBmp**

Indicate that if the AvSynchronizer module needs to keep the bitmap. Application could be safely delete the bitmap right after create the channel if this flag is specified.

**bVideoOut**

Indicate if show the video of this channel.

**bAudioOut**

Indicate if this channel audible.

**bMotionAlert**

Indicate if drawing the rectangle of the motion detection window.

**dwMotionRectAlert**

Specify the color of the rectangle of the motion detection window when motion alert happened. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration. If you want to use the color that are not list in the [EMOTIONALERTCOLOR](#), then you can set the MSB to be 1 and the rest of the DWORD is the RGB value.

**dwMotionRect**

Specify the color of the rectangle of the motion detection window. The value is one of the values listed in [EMOTIONALERTCOLOR](#) enumeration. If you don't want to show the rectangle of the motion detection window when motion alert didn't happen, set 0xFFFFFFFF as it's value. If you want to use the color that are not list in the [EMOTIONALERTCOLOR](#), then you can set the MSB to be 1 and the rest of the DWORD is the RGB value.

[Remarks](#)[Requirements](#)

AvSynchronizer.h

### 4.3.11 TFISHEYECONTROLPARAMS

---

This structure contains the position and zoom information of the viewer.

```
typedef struct {
    LONG          ThetaX;
    LONG          ThetaY;
    LONG          ThetaZ;
    LONG          ZoomFactor;
    LONG          ThetaScroll;
} TFISHEYECONTROLPARAMS;
```

#### Members

---

##### **ThetaX**

Rotate angle around the x-axis (Tilt).

##### **ThetaY**

Rotate angle around the y-axis (Pan). This is only valid in 180 degree perspective projection.

##### **ThetaZ**

Rotate angle around the z-axis (Rotate). This is only valid in 360 degree perspective pojection.

##### **ZoomFactor**

Zoom factor along the x-axis and y-axis.

##### **ThetaScroll**

Scroll angle. This is only valid in 360 degree panorama projection.

#### Remarks

---

#### Requirements

---

AvSynchronizer\_Fisheye.h



### 4.3.12 TFISHEYECURRENTDISPLAY

---

This structure is used by [AvSynchronizer\\_FisheyeGetCurrentViewerDisplay](#) function.

```
typedef struct {  
  
    TCURRENTDISPLAYINFO    tCurrentDisplay;  
    HWND                  hViewerWindow;  
  
} TFISHEYECURRENTDISPLAY;
```

---

#### Members

##### **tCurrentDisplay**

See [TCURRENTDISPLAYINFO](#).

##### **hViewerWindow**

The window handle of the viewer which is specified in [TFISHEYEVIEWER::hViewerWindow](#).

---

#### Remarks

---

#### Requirements

AvSynchronizer\_Fisheye.h

### 4.3.13 TFISHEYEPRESENTPARAMS

This structure is used by [AvSynchronizer FisheyeGetViewerPresentParameters](#) or [AvSynchronizer FisheyeSetViewerPresentParameters](#).

```
typedef struct {
    HWND                hViewerWindow;
    BOOL                bResetCtrlParams;
    EFISHEYEPRESENTMODE PresentMode;
    EFISHEYEVIEWERANGLEFLAGS ViewerAngle;
    TFISHEYECONTROLPARAMS *pCtrlParams;
    DWORD               CtrlParamsCount;
    DWORD               FocusQuadrant;
} TFISHEYEPRESENTPARAMS;
```

#### Members

##### **hViewerWindow**

Viewer window.

##### **bResetCtrlParams**

Reset the control parameters in focus quadrant or not.

##### **PresentMode**

Viewer present mod. See [EFISHEYEPRESENTMODE](#).

##### **dwViewerAngle**

Viewer angle. See [EFISHEYEVIEWERANGLEFLAGS](#).

##### **pCtrlParams**

The control commands array. See [TFISHEYEPTZRCONTROL\\_COMMANDS](#).

##### **CtrlParamsCount**

The number of control parameters of pCtrlParams.

##### **FocusQuadrant**

The focus quadrant.

Remarks

---

Requirements

---

AvSynchronizer\_Fisheye.h

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.3.14 TFISHEYPTZRCONTROL\_COMMANDS

This structure is specifies the PTZR commands.

```
typedef struct {
    DWORD dwCtrlFlags;
    BOOL bClick;
    LONG autoSpeed;
    POINTS AnchorPoint;
    struct {
        POINTS BeginPoint;
        POINTS EndPoint;
    } PTRParams;
    struct {
        POINTS FocusPoint;
        SHORT DeltaSteps;
    } ZParams;
    struct {
        POINTS FocusPoint;
        BOOL bResetP;
        BOOL bResetT;
        BOOL bResetZ;
        BOOL bResetR;
    } ResetParams
} TFISHEYPTZRCONTROL_COMMANDS;
```

##### Members

##### **dwCtrlFlags**

Indicate which field of this structure is valid. It can be one or the combination of the values of [EFISHEYPTZRCONTROLFLAGS](#).

##### **bClick**

Enable Click-on-image control or not. When this flag is TRUE, the EndPoint in PTRParams is omitted.

##### **autoSpeed**

Automatic panoramic view speed in degree per unit time. 1 means changing 1 degree per 200 milliseconds.

**AnchorPoint**

Specify the focus quadrant.

**PTRParams::BeginPoint**

When user controls panning, tilting or rotating, this data member indicates the start point. It is often set when pressing the left button of mouse in the client area of viewer window.

**PTRParams::EndPoint**

When user controls panning, tilting or rotating, this data member indicates the end point. It is often set when the cursor moves.

**ZParams::FocusPoint**

When user controls zooming, this data member indicates the focusing point, This is set to the cursor's position in the client area of the viewer window.

**ZParams::DeltaSteps**

Steps of zoom-in or zoom-out operation.

**ResetParams::FocusPoint**

The cursor's position in the client area of viewer's window.

**ResetParams::bResetP**

Reset parameter of pan or not.

**ResetParams::bResetT**

Reset parameter of tilt or not.

**ResetParams::bResetZ**

Reset parameter of zoom or not.

**ResetParams::bResetR**

Reset parameter of rotate or not.

[Remarks](#)

---

## Requirements

---

AvSynchronizer\_Fisheye.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.15 TFISHEYEROTATEOPTIONS

This structure is used by [AvSynchronizer\\_FisheyeUpdateRotateOptions](#) function.

```
typedef struct {
    DWORD dwUpdateFlags;
    TFISHEYECONTROLPARAMS *pPresetPoints;
    DWORD PresetPointsCount;
    HWND hRotateTargetWindow;
    DWORD RotateSpeed;
} TFISHEYEROTATEOPTIONS;
```

#### Members

##### **dwUpdateFlags**

Indicate which field of this structure is valid. It can be one or the combination of the values of [EFISHEYEUPDATEROTATEOPTFLAGS](#).

##### **pPresetPoints**

A pointer to an array of [TFISHEYECONTROLPARAMS](#) structures.

##### **PresetPointsCount**

The number of preset points in the array.

##### **hRotateTargetWindow**

The window user wants to rotate.

##### **RotateSpeed**

Update interval when rotation in seconds. The range is 0 ~ 6. 0 means stop rotate. If user inputs 1, means the rotate interval will be 6 / 1 = 6 seconds. If user inputs 5, means the rotate interval will be 6 / 5 = 1.2 seconds.

#### Remarks

#### Requirements

AvSynchronizer\_Fisheye.h

4.3.16 TFISHEYESNAPSHOT

This structure is used by [AvSynchronizer\\_FisheyeGetCurrentViewerSnapshot](#) function.

```
typedef struct {  
  
    TSNAPSHOT          tSnapshot;  
    HWND              hViewerWindow;  
  
} TFISHEYESNAPSHOT;
```

Members

**tSnapshot**

See [TSNAPSHOT](#).

**hViewerWindow**

The window handle of the viewer which is specified in [TFISHEYEVIEWER](#)::hViewerWindow.

Remarks

Requirements

AvSynchronizer\_Fisheye.h



### 4.3.17 TFISHEYEVIEWER

This structure is used by [AvSynchronizer FisheyeRegisterViewer](#), [AvSynchronizer FisheyeUpdateViewer](#) or [AvSynchronizer FisheyeRemoveViewer](#) for containing the information about viewers.

```
typedef struct {
    DWORD dwUpdateFlags;
    HWND hViewerWindow;
    EFISHEYEPRESENTMODE dwPresentMode;
    EFISHEYEVIEWERANGLEFLAGS dwViewerAngle;
    TFISHEYEPTZRCONTROL_COMMANDS tCtrlCommands;
    DWORD FocusRgnColor;
} TFISHEYEVIEWER;
```

#### Members

##### **dwUpdateFlags**

Indicate which field of this structure is valid. It can be one or the combination of the values of [EFISHEYEUPDATEVIEWERFLAGS](#).

##### **hViewerWindow**

Viewer's window.

##### **dwPresentMode**

Viewer present mode. See [EFISHEYEPRESENTMODE](#).

##### **dwViewerAngle**

Viewer angle. See [EFISHEYEVIEWERANGLEFLAGS](#).

##### **tCtrlCommands**

The control commands. See [TFISHEYEPTZRCONTROL\\_COMMANDS](#).

##### **FocusRgnColor**

Focus region color. Users can use RGB() macro to define the color.

#### Remarks

## Requirements

---

AvSynchronizer\_Fisheye.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.18 TDECCHOPTION

This structure is used by [AvSynchronizer\\_CreateDecoderChannel](#) function.

```
typedef struct {
    LPDECODEFRAMECALLBACK    pfDecodeFrame;
    DWORD                      dwAvDecodeContext;
    DWORD                      dwRawDataFormat;
    DWORD                      dwJpegQualityFactor;
} TDECCHOPTION, * PTDECCHOPTION;
```

#### Members

##### **pfDecodeFrame**

Specify the pointer to the audio/video output callback function.

##### **dwAvDecodeContext**

Specify the application-defined value that is passed, along with the returned handle, to audio/video output callback functions.

##### **dwRawDataFormat**

Indicate the format of the output data. The value is define in [EPIXELFORMAT](#).

##### **dwJpegQualityFactor**

The encoding quality for JPEG output frame. The range is 1-125, the smaller the better quality, but would have worse performance because it requires more time to generate the JPEG frame.

#### Remarks

#### Requirements

AvSynchronizer.h

### 4.3.19 TDIGITALZOOMPARAM

This structure is used in [AvSynchronizer\\_SetChannelOption](#) for the option SETCH\_DIGITAL\_ZOOM.

```
typedef struct {
    BOOL                bCanvasWin;
    union
    {
        HWND            hTarget;
        RECT             rectTarget;
    } unCanvas;
    RECT                rectCanvasBorder;
    BOOL                bZoomWin;
    union
    {
        HWND            hZoomArea;
        RECT             rectZoomArea;
    } unZoom;
    RECT                rectZoomBorder;
    BOOL                bZoomEnabled;
    BOOL                bDisplayed;
} TDIGITALZOOMPARAM;
```

#### Members

##### **bCanvasWin**

Determine which element in unCanvas is correct. If the value is True hTarget is valid, else rectTarget is valid.

##### **hTarget**

The canvas window that will hold the full image, users could set the zoom area in this canvas so that the video for the channel will be zoomed image for the selected part. The drawing will be stuck to the window, so the image will be moved when window moved.

##### **rectTarget**

This is the rectangle to draw the full image. The coordinate should be related to the upper-left corner of screen. The application should be take in charge of the moving of the drawing area when window move. Or the image might be drawn outside the application window.

**rectCanvasBorder**

This is the border size for the canvas. The image will be drawn inside the window or rectangle with left, top, right and bottom offset recorded in this structure. The default is 0.

**bZoomWin**

Determine which element in unZoom is correct. If the value is True hZoomArea is valid, else rectZoomArea is valid.

**hZoomArea**

The child window of canvas window that shows the selected zoomed area. With this window, users could change the position or resize the zoom area.

**rectZoomArea**

This is the rectangle for zoomed area. The coordinate is related to upper-left corner of screen. The rectangle must be within the rectTarget or the rectangle of hTarget or the zooming will not be taken effect.

**rectZoomBorder**

This is the border size for the zoom area. The zoom area will be actually subtracted with left, top, right and bottom offset recorded in this structure. The default is 0.

**bZoomEnabled**

Is the digital zoom turned on for this channel? If the value is false, any previous setup value will be kept, but the channel will be shown with full image. This value provides a quick way to turn off digital zoom.

**bDisplayed**

Should the module try to paint the image in canvas area? Because painting will consume some CPU power, it is recommended to design a UI that will normally hide the canvas and zoom area window. Whenever the windows are shown, turn this value on, and turn it off right after the windows hide

[Remarks](#)

---

[Requirements](#)

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.20 TDISPLAYINFO

This structure is used by [LPDISPLAYCALLBACK](#) function.

```
typedef struct {
    HDC                hDC;
    POINT              ptOrigin;
    DWORD              dwWidth;
    DWORD              dwHeight;
    DWORD              DrawTime;
    DWORD              dwCallTimes;
    DWORD              dwFlag;
    DWORD              dwTimet;
    BOOL               bDrawOneMem;
    DWORD              dwActiveBlock;
    TONEDISPBLOCK      atBlocks[MAX_DISP_BLOCK];
} TDISPLAYINFO, * PDISPLAYINFO;
```

#### Members

##### **hDC**

The hDC to draw with.

##### **ptOrigin**

The Original point of the draw able area.

##### **dwWidth**

Specify the width of the draw able area.

##### **dwHeight**

Specify the height of the draw able area.

##### **DrawTime**

The address of the struct tm. Contains the time of the frame. If for AVI channel, and the SETCH\_AVI\_CAPTION\_CB\_CONFORM is not set, this value is the time\_t value. Caller could use gmtime to convert it to the struct tm pointer

**dwCallTimes**

Specify how many times this callback was called. This is only valid for connecting mode.

**dwFlag**

Specify the mode this callback is. See [EDISPLAYINFOFLAG](#).

**dwTimet**

This is the time\_t value for the DrawTime.

**bDrawOneMem**

If this variable is true, the following

**dwActiveBlock**

Callee must fill this variable to tell the caller how many blocks are correct.

[Remarks](#)

---

[Requirements](#)

---

AvSynchronizer.h



### 4.3.21 TFRAMEINFO

---

This structure is used by [LPDECODEFRAMECALLBACK](#) function.

```
typedef struct {  
  
    union {  
        TVFRAMEINFO    tVideoFrame;  
        TAFRAMEINFO    tAudioFrame;  
    }  
  
} TFRAMEINFO;
```

---

#### Members

##### **tVideoFrame**

See [TVFRAMEINFO](#).

##### **tAudioFrame**

See [TAFRAMEINFO](#).

---

#### Remarks

---

#### Requirements

AvSynchronizer.h

### 4.3.2 TFRAMEINFOEX

This structure is used by [LPDECODEFRAMECALLBACK\\_EX](#) function. For audio data, all other member except tF is effective when this callback is called.

```
typedef struct {
    TFRAMEINFO      tF,
    DWORD            dwCBCount;
    DWORD            dwVideoFormat;
    DWORD            dwNextFormat;
    BOOL             bContinueDecode;
    BYTE             abyReserved[64];
} TFRAMEINFOEX;
```

#### Members

##### tF

This is the [TFRAMEINFO](#) structure for the video or audio frame.

##### dwCBCount

This is the count for the call times of a single frame. It starts from 1. It's only usable for video frame.

##### dwVideoFormat

The video format of current called back data. It's only usable for video frame.

##### dwNextFormat

This is usable when application needs more decoded data format for the same frame. And it is only used if the bContinueDecode is set to be true. It's only usable for video frame.

##### bContinueDecode

The value is set to false when called back. If the application needs more data format of the same frame, set this parameter to true and set the next wanted format in dwNextFormat to ask the module to send out other format. It's only usable for video frame.

##### abyReserved

These bytes are reserved for future used.

Remarks

---

Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.23 TONEDISPBLOCK

---

This structure is used by [LPDECODEFRAMECALLBACK](#) function.

```
typedef struct {  
  
        SIZE          szSrc;  
  
        POINT         ptDest;  
  
        COLORREF      clrMask;  
  
} TONEDISPBLOCK;
```

---

#### Members

##### **szSrc**

This indicates the height and width of a rectangle.

##### **ptDest**

The destination point (x, y) to paint the text and its size is the same as szSrc.

##### **clrMask**

The mask of color that should be treated as transparent.

---

#### Remarks

---

#### Requirements

AvSynchronizer.h

### 4.3.24 TPBCHOPTION

This structure collects the settings of the playback channel. When creating playback channel, fill this structure to setup the channel.

```
typedef struct {
    DWORD dwFlags;
    LPSTATUSCALLBACK pfStatus;
    LPDISPLAYCALLBACK pfDisplay;
    DWORD dwStatusContext;
    DWORD dwDisplayContext;
    DWORD dwVolume;
    DWORD dwLeftBorderSize;
    DWORD dwRightBorderSize;
    DWORD dwTopBorderSize;
    DWORD dwBottomBorderSize;
    HBITMAP hBMP;
    HWND hVideoOut;
    HWND hDisplay;
    BOOL bSaveBmp;
    BOOL bVideoOut;
    BOOL bAudioOut;
    BOOL bMotionAlert;
    DWORD dwMotionRectAlert;
    DWORD dwMotionRect;
    BOOL bOrgSizeCallback;
    DWORD dwOrgSizeLeftBorder;
    DWORD dwOrgSizeTopBorder;
    DWORD dwOrgSizeRightBorder;
    DWORD dwOrgSizeBottomBorder;
    LPINPUTFRAMEREQUESTCALLBACK pfFrameRequest;
    BOOL bNonBlocking;
    DWORD dwFrameRequestContext;
} TPBCHOPTION, *PTPBCHOPTION;
```

## Members

---

### **dwFlags**

Indicate which field of this structure is valid. It can be one or the combination of the values of [EPBCHFLAG](#).

### **pfStatus**

Specify the pointer to the Status callback function. To be used to notify the application the status of AvSynchronizer.

### **pfDisplay**

Specify the pointer to the display callback function. To be used to notify the application to display something.

### **dwStatusContext**

Specify the application-defined value that is passed, along with the returned handle, to status callback functions.

### **dwDisplayContext**

Specify the application-defined value that is passed, along with the returned handle, to display callback functions.

### **dwVolume**

Specify the audio volume. The valid value is 0 ~ 5000.

### **dwLeftBorderSize**

Specify the size of the left border.

### **dwRightBorderSize**

Specify the size of the right border.

### **dwTopBorderSize**

Specify the size of the top border.

### **dwBottomBorderSize**

Specify the size of the bottom border.

### **hBMP**

A handle of a bitmap.

**hVideoOut**

Window handle used for the application. Set to the calling application's top-level window handle (not a handle for any child windows created by the top-level window).

**hDisplay**

Window handle of the window which the video of this channel will show on it.

**bSaveBmp**

This value is ignored now, all bitmap will be parsed and saved internally.

**bVideoOut**

Indicate if show the video of this channel.

**bAudioOut**

Indicate if this channel audible.

**bMotionAlert**

Indicate if drawing the rectangle of the motion detection window.

**dwMotionRectAlert**

Specify the color of the rectangle of the motion detection window when motion alert happened. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration. If you want to use the color that are not list in the [EMOTIONALERTCOLOR](#), then you can set the MSB to be 1 and the rest of the DWORD is the RGB value.

**dwMotionRect**

Specify the color of the rectangle of the motion detection window. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration. If you don't want to show the rectangle of the motion detection window when motion alert didn't happen, set 0xFFFFFFFF as it's value. If you want to use the color that are not list in the [EMOTIONALERTCOLOR](#), then you can set the MSB to be 1 and the rest of the DWORD is the RGB value.

**bOrgSizeCallback**

If this is TRUE, this module will use the real size of the video plus the border size you specified below to draw the video and caption. The generated graph will be scaled onto the display window. If False, only the video will be scaled, and the border will be the same as you specified when shown. Note: To set up this value, the ORG\_SIZE\_MODE must be turned on when initializing AVSynchronizer.

**dwOrgSizeLeftBorder**

Specify the size of the left border. This is valid only when bOrgSizeCallback is TRUE.

**dwOrgSizeTopBorder**

Specify the size of the top border. This is valid only when bOrgSizeCallback is TRUE.

**dwOrgSizeRightBorder**

Specify the size of the right border. This is valid only when bOrgSizeCallback is TRUE.

**dwOrgSizeBottomBorder**

Specify the size of the bottom border. This is valid only when bOrgSizeCallback is TRUE.

**pfFrameRequest**

Reserved. This is not implemented yet.

**bNonBlocking**

Reserved. This is not implemented yet.

**dwFrameRequestContext**

Reserved. This is not implemented yet.

**Remarks**

---

**Requirements**

---

AvSynchronizer.h



VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.25 TSNAPSHOT

---

This structure is used by [AvSynchronizer\\_GetCurrentSnapShot](#) function.

```
typedef struct {  
  
        DWORD          dwdataSize;  
  
        DWORD          dwWidth;  
  
        DWORD          dwHeight;  
  
        BYTE           *pDataStart;  
  
} TSNAPSHOT, * PTSNAPSHOT;
```

---

#### Members

##### **dwdataSize**

Indicate the size of the snapshot in BYTE.

##### **dwWidth**

Indicate the width of the snapshot in pixel.

##### **dwHeight**

Indicate the Height of the snapshot in pixel

##### **pDataStart**

A pointer to the buffer the snapshot store in.

---

#### Remarks

---

#### Requirements

AvSynchronizer.h

### 4.3.26 TUPDATECHANNELOPTION

This structure collects the settings, which can change at run time of the channel. When you want to update the channel settings, fill this structure to setup the channel.

```
typedef struct {
    DWORD dwFlags;
    BOOL bVideoOut;
    BOOL bAudioOut;
    BOOL bMotionAlert;
    DWORD dwMotionRectAlert;
    BOOL bIgnoreBorder;
    DWORD dwMotionRect;
    DWORD dwVolume;
    TMediaType tMediaType;
    HWND hWnd;
} TUPDATECHANNELOPTION,
*PTUPDATECHANNELOPTION;
```

#### Members

##### **dwFlags**

Indicate which field of this structure is valid. It can be one or the combination of the values of [EUPCHOPTION](#).

##### **bVideoOut**

Indicate if show the video of this channel.

##### **bAudioOut**

Indicate if this channel audible.

##### **bMotionAlert**

Indicate if drawing the rectangle of the motion detection window.

##### **dwMotionRectAlert**

Specify the color of the rectangle of the motion detection window when motion alert happened. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration.

If you want to use the color that are not list in the [EMOTIONALERTCOLOR](#), then you can set the MSB to be 1 and the rest of the DWORD is the RGB value.

### **blgnoreBorder**

Should the channel ignore the border setting when displaying video. TRUE means to ignore, FALSE means not.

### **dwMotionRect**

Specify the color of the rectangle of the motion detection window. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration. If you don't want to show the rectangle of the motion detection window when motion alert didn't happen, set -1 as its value. If you want to use the color that are not list in the [EMOTIONALERTCOLOR](#), then you can set the MSB to be 1 and the rest of the DWORD is the RGB value.

### **dwVolume**

Specify the audio volume. The valid value is 0 ~ 5000.

### **tMediaType**

Specify the media type of this channel. The value is one in [EMEDIATYPE \(TMediaType\)](#) enumeration.

### **hWnd**

The new window this channel attach to. Before setting new window, the UPCH\_RESTORE\_WINPROC must be called.

### [Remarks](#)

---

### [Requirements](#)

---

AvSynchronizer.h

### 4.3.27 TVIDEOINFO

This structure is used to hold the video frame information from [LPOUTPUTVIDEOFRAMEBEFOREDISPLAY](#).

```
typedef struct {  
  
        DWORD          dwStride;  
  
        DWORD          dwMaxHeight;  
  
        DWORD          dwWidth;  
  
        DWORD          dwHeight;  
  
        BYTE           *pbyBuf;  
  
} TVIDEOINFO;
```

#### Members

##### **dwStride**

The stride of video buffer.

##### **dwMaxHeight**

The maximum height of video buffer

##### **dwWidth**

Width of video

##### **dwHeight**

Height of video

##### **pbyBuf**

pointer to video buffer

#### Remarks

#### Requirements

AvSynchronizer.h

### 4.3.28 TUPDATEPBCHANNELOPTION

This structure collects the settings of playback channel, which can change at run time of the playback channel. When you want to update playback channel settings, fill this structure to setup the playback channel.

```
typedef struct {
    DWORD dwFlags;
    BOOL bVideoOut;
    BOOL bAudioOut;
    BOOL bMotionAlert;
    BOOL bIgnoreBorder;
    DWORD dwMotionRectAlert;
    DWORD dwMotionRect;
    DWORD dwVolume;
    TMediaType tMediaType;
    HWND hWnd;
    DWORD dwFast;
    DWORD dwSlow;
    BOOL bPause;
} TUPDATEPBCHANNELOPTION,
*PTUPDATEPBCHANNELOPTION;
```

#### Members

##### **dwFlags**

Indicate which field of this structure is valid. It can be one or the combination of the values of [EUPCHOPTION](#).

##### **bVideoOut**

Indicate if show the video of this channel.

##### **bAudioOut**

Indicate if this channel audible.

##### **bMotionAlert**

Indicate if drawing the rectangle of the motion detection window.

**blgnoreBorder**

Should the channel ignore the border setting when displaying video. TRUE means to ignore, FALSE means not.

**dwMotionRectAlert**

Specify the color of the rectangle of the motion detection window when motion alert happened. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration.

**dwMotionRect**

Specify the color of the rectangle of the motion detection window. The value is one of the values in [EMOTIONALERTCOLOR](#) enumeration. If you don't want to show the rectangle of the motion detection window when motion alert didn't happen, set 0xFFFFFFFF as it's value.

**dwVolume**

Specify the audio volume. The valid value is 0 ~ 5000.

**tMediaType**

Specify the media type of this playback channel. The value is one in the [EMEDIATYPE \(TMediaType\)](#) enumeration.

**dwFast**

Specify the multiple of speed for playing. This can't be zero if the dwSlow is not zero.

**dwSlow**

Specify the divisor of speed for playing. If this value is set to be 0 it will be play in full speed (as fast as possible).

**bPause**

Indicate if pause the channel. TRUE for pause. Set it FALSE to resume the channel.

**hWnd**

The new window this channel attach to. Before setting new window, the UPCH\_RESTORE\_WINPROC must be called.

[Remarks](#)

---

## Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20



### 4.3.29 TVFRAMEINFO

This structure is used by [LPDECODEFRAMECALLBACK](#) function.

```
typedef struct {
    DWORD dwWidth;
    DWORD dwHeight;
    DWORD dwSize;
    BYTE *pbyPicture;
    BYTE *pbyHeader;
    DWORD dwReserved;
    TMediaDataPacketInfo tPacketInfo;
} TVFRAMEINFO, * PTVFRAMEINFO;
```

#### Members

##### **dwWidth**

Specify the width of the frame.

##### **dwHeight**

Specify the height of the frame.

##### **dwSize**

Specify the size of the frame.

##### **pbyPicture**

a pointer that store the data of the frame.

##### **pbyHeader**

This pointer is the starting address of the real buffer allocated. It's useful when users need to use the output data to generate another packet. In such case, the dwReserved is the reserved space between pbyHeader and pbyPicture. Users need to use [AvSynchronizer\\_SetChannelOption](#) to specify the reserved space they need. If not, this pointer is the same as pbyPicture is.

##### **dwReserved**

This is the difference in bytes between pbyHeader and pbyPicture.

**tPacketInfo**

The packet that contains this decoded video frame. In this structure: pbyBuff, dwOffset, dwBitstreamSize, dwAudioSamplingFreq, byAudioChannelNum, and bAudioDI are not valid, other fields are the same as the input packet of [AvSynchronizer InputToBeDecodedMediaFrame](#).

**Remarks**

---

**Requirements**

---

AvSynchronizer.h

### 4.3.30 TVIDEOOPTION

This structure is used to hold the video codec information for AVI channel.

```
typedef struct {
    DWORD dwfccType;
    DWORD dwHandler;
    LONG lKey;
    LONG lDataRate;
    LONG lQuality;
    LPBITMAPINFO lpbiOut;
} TVIDEOOPTION;
```

#### Members

##### **dwfccType**

Type of compressor used. Currently only ICTYPE\_VIDEO (VIDC) is supported.

You could check the value for each codec by calling [AvSynchronizer\\_ChooseVideoCompressor](#).

##### **dwHandler**

It's four-character code of the compressor. Specify NULL to indicate the data is not to be recompressed. Specify "DIB" to indicate the data is an uncompressed, full frame.

You can use this member to specify which compressor is selected by default when the dialog box is displayed

##### **lKey**

Key-frame rate. Specify an integer to indicate the frequency that key frames are to occur in the compressed sequence or zero to not use key frames.

##### **lDataRate**

Data rate, in kilobytes per second.

##### **lQuality**

Specify a quality setting of 1 to 10,000.

##### **lpbiOut**

Pointer to a BITMAPINFO structure containing the image output format.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.31 TAUDIOOPTION

---

This structure is an alias for WAVEFORMATEX structure in Win32 SDK. Please refer to the definition in related document.

#### Remarks

---

This structure is only available for Windows 32 / Windows CE platform currently.

#### Requirement

---

Mmreg.h

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.3.32 TMediaDataPacketInfo

---

This structure is used by [AvSynchronizer InputEncodedMediaFrame](#) and [AvSynchronizer InputPlaybackMediaFrame](#) function. Please refer to VNDP\_Data\_Packet\_Parser.doc for the definition of this data structure.

---

#### Remarks

---

---

#### Requirement

---

datapacketdef.h

## 4.4 API Definition

---

The API definition is depicted here.

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.1 AvSynchronizer\_ChooseAudioCompressor

Call this function to show up the audio compressor selection window for AVSynchronizer handle. This window belongs to windows API, so the user interface and the language is determined by the operation system. The settings and the per-channel settings will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_ChooseChannelAudioCompressor](#), the channel will take the settings in AVShychronizer handle.

##### Syntax

```
SCODE AvSynchronizer_ChooseAudioCompressor (
    HANDLE                hAVSync,
    HWND                  hWnd,
    const char             *pszTitle,
    TAVIAINFO              *pAudioInfo
);
```

##### Parameters

###### **hAVSync,**

[in] The handle created by [AvSynchronizer\\_Initial](#) or [AvSynchronizer\\_InitialEx](#).

###### **hWnd**

[in] The handle of the window that would be assigned as the parent of the video compressor choosing window.

###### **pszTitle**

[in] The title of the choosing window.

###### **pAudioInfo**

[in/out] The initial setting for the choosing dialog. It also contains the selected codec when return.

##### Return Values

###### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.



**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

**Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

#### 4.4.2 AvSynchronizer\_ChooseChannelAudioCompressor

Call this function to show up the audio compressor selection window for channel. This window belongs to windows API, so the user interface and the language is determined by the operation system. The settings are related to the specified channel. So application could set different settings for different channels. The settings and the settings in Avsynchronizer will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_ChooseAudioCompressor](#), the channel will take the settings in itself.

##### Syntax

```
SCODE AvSynchronizer_ChooseChannelAudioCompressor (
    HANDLE          hAVIChannel,
    HWND            hWnd,
    const char       *pszTitle,
    TAVIAINFO        *pAudioInfo
);
```

##### Parameters

###### hAVIChannel

[in] the AVI channel created by calling [AvSynchronizer\\_CreateAVIChannel](#) or [AvSynchronizer\\_CreateLiveAVIChannel](#).

###### hWnd

[in] the handle of the window that would be assigned as the parent of the video compressor choosing window.

###### pszTitle

[in] the title of the choosing window.

###### pAudioInfo

[in/out] the initial setting for the choosing dialog. It also contains the selected codec when return.

##### Return Values

**AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

#### **AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

#### **AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

#### **Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

#### **Requirements**

---

AvSynchronizer.h

#### **See Also**

---

### 4.4.3 AvSynchronizer\_ChooseVideoCompressor

Call this function to show up the video compressor selection window for AVSynchronizer handle. This window belongs to Windows API. So the user interface and the language are determined by the operation system. The settings and the per-channel settings will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_ChooseChannelVideoCompressor](#), the channel will take the settings in AVShychronizer handle.

#### Syntax

```
SCODE AvSynchronizer_ChooseVideoCompressor (
    HANDLE          hAvSync,
    HWND            hWnd,
    const char      *pszTitle,
    TAVIVINFO       *pVideoInfo
);
```

#### Parameters

##### **hAvSync**

[in] the handle created by [AvSynchronizer\\_Initial](#) or [AvSynchronizer\\_InitialEx](#).

##### **hWnd**

[in] the handle of the window that would be assigned as the parent of the video compressor choosing window.

##### **pszTitle**

[in] the title of the choosing window.

##### **pVideoInfo**

[in/out] the initial setting for the choosing dialog. It also contains the selected codec when return.

#### Return Values

##### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

**Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

#### 4.4.4 AvSynchronizer\_ChooseChannelVideoCompressor

Call this function to show up the video compressor selection window for channel. This window belongs to Windows API. So the user interface and the language are determined by the operation system. The settings are related to the specified channel. So application could set different settings for different channels. The settings and the settings in Avsynchronizer will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_ChooseVideoCompressor](#), the channel will take the settings in itself.

##### Syntax

```
SCODE AvSynchronizer_ChooseChannelVideoCompressor (
    HANDLE          hAVIChannel,
    HWND            hWnd,
    const char      *pszTitle,
    TAVIVINFO       *pVideoInfo
);
```

##### Parameters

###### **hAVIChannel**

[in] the AVI channel created by calling [AvSynchronizer\\_CreateAVIChannel](#).

###### **hWnd**

[in] the handle of the window that would be assigned as the parent of the video compressor choosing window.

###### **pszTitle**

[in] the title of the choosing window.

###### **pVideoInfo**

[in/out] the initial setting for the choosing dialog. It also contains the selected codec when return.

##### Return Values

###### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

**Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

VIVOTEK CONFIDENTIAL  
2017.01.20



#### 4.4.5 AvSynchronizer\_CreateAVIChannel

Create a channel that could be used to convert audio/video stream into AVI file. It's optional to compress the audio and video frames by the compressors installed on system that runs the conversion program. Please refer to [AvSynchronizer\\_ChoseVideoCompressor](#), [AvSynchronizer\\_ChoseAudioCompressor](#), [AvSynchronizer\\_SetVideoCompressorParam](#), [AvSynchronizer\\_SetAudioCompressorParam](#). When using this channel, please input only the data in the same time interval if they are audio/video. Once the interval end or the conversion stopped, please delete the channel by calling [AvSynchronizer\\_DeleteAVIChannel](#). Create a new channel for new time interval. When generating AVI file, users must call [AvSynchronizer\\_InputAVIMedia](#) to input un-decoded audio or video packets.

##### Syntax

```

SCODE AvSynchronizer_CreateAVIChannel (
                                HANDLE          hAvSync,
                                HWND            *phAVIChannel,,
                                TAVICHOPTION    *ptAviChOption,
);

```

##### Parameters

###### hAvSync

[in] the value of the handle returned by [AvSynchronizer\\_Initial](#).

###### phAVIChannel

[out] the pointer to receive the handle of this channel.

###### ptAviChOption

[in] the channel option.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

**AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

**AVICONVERTER\_E\_OUT\_OF\_MEMORY**

Memory allocation error happens when creating channel.

**Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

#### 4.4.6 AvSynchronizer\_CreateChannel

Create a channel to display video or play sound.

##### Syntax

```
SCODE AvSynchronizer_CreateChannel (
    HANDLE hAvSync,
    HWND *phChannel,
    TCHANNELOPTION tChannelOptions,
);
```

##### Parameters

###### hAvSync

[in] the handle of the AvSynchronizer, which created by [AvSynchronizer\\_Initial](#).

###### \*phChannel

[out] the pointer to receive the handle of this channel.

###### tChannelOptions

[in] a structure contains the settings of the channel. See [TCHANNELOPTION](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Create the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to create the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

There are one or more arguments invalid.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY

There is not enough memory.

**AVSYNCHRONIZER\_E\_CHANNEL\_EXCEEDED**

You can't create more than 16 channels.

**AVSYNCHRONIZER\_E\_DECODER\_CHANNEL\_ONLY**

You can only create decoder channel only.

**Remarks**

---

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

[AvSynchronizer DeleteChannel](#), [AvSynchronizer CreatePlaybackChannel](#), [TCHANNELOPTION](#).

### 4.4.7 AvSynchronizer\_CreateDecoderChannel

Create a decoder channel. A decoder channel could decode audio and video at the same time.

#### Syntax

```
SCODE AvSynchronizer_CreateDecoderChannel (  
  
                                HANDLE                hAvSync,  
                                HWND                  *phDecChannel,  
                                TDECCHOPTION          *ptDecChannelOption  
);
```

#### Parameters

##### **hAvSync**

[in] the handle of the AvSynchronizer, which created by [AvSynchronizer\\_Initial](#).

##### **\*phDecChannel**

[out] the pointer to receive the handle of this channel.

##### **ptDecChannelOptions**

[in] a structure contains the settings of the channel. See [TDECCHOPTION](#).

#### Return Values

##### **AVSYNCHRONIZER\_S\_OK**

Create the channel successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Fail to create the channel.

##### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL

#### Remarks

## Requirements

---

AvSynchronizer.h

## See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.8 AvSynchronizer\_CreateLiveAVIChannel

Create a channel that could be used to convert live audio/video stream into AVI file.

It's optional to compress the audio and video frames by the compressors installed on system that runs the conversion program. Please refer to [AvSynchronizer\\_ChoseVideoCompressor](#), [AvSynchronizer\\_ChoseAudioCompressor](#), [AvSynchronizer\\_SetVideoCompressorParam](#), [AvSynchronizer\\_SetAudioCompressorParam](#). When using this channel, please input only the data in the same time interval if they are audio/video.

Once the interval end or the conversion stopped, please delete the channel by calling [AvSynchronizer\\_DeleteAVIChannel](#). Create a new channel for new time interval. This channel is different from the AVI channel because it accept only decoded data. When generating AVI file, users must call [AvSynchronizer\\_InputDecodedAVIMedia](#) to input audio or video frames.

##### Syntax

```
SCODE AvSynchronizer_CreateLiveAVIChannel (
    HANDLE hAvSync,
    HWND *phAVIChannel,
    TAVICHOPTION *ptAviChOption
);
```

##### Parameters

###### hAvSync

[in] the value of the handle returned by [AvSynchronizer\\_Initial](#).

###### phAVIChannel

[out] the pointer to receive the handle of this channel.

###### ptAviChOption

[in] the channel option.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

**AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

**AVICONVERTER\_E\_OUT\_OF\_MEMORY**

Memory allocation error happens when creating channel.

**Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---



#### 4.4.9 AvSynchronizer\_CreatePlaybackChannel

Create a channel to display video or play sound from the database.

##### Syntax

```
SCODE AvSynchronizer_CreatePlaybackChannel (
    HANDLE hAvSync,
    HWND *phPlaybackChannel,,
    TPBCHOPTION tPbChOption
);
```

##### Parameters

###### hAvSync

[in] the handle of the AvSynchronizer, which created by [AvSynchronizer\\_Initial](#).

###### \*phPlaybackChannel

[out] the pointer to receive the handle of this channel.

###### tPbChOption

[in] a structure contains the settings of the channel. See [TPBCHOPTION](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Create the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to create the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

There are one or more arguments invalid.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY

There is not enough memory.

**AVSYNCHRONIZER\_E\_CHANNEL\_EXCEEDED**

You can't create more than 16 channels.

**AVSYNCHRONIZER\_E\_DECODER\_CHANNEL\_ONLY**

You can only create decoder channel only.

### Remarks

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

### Requirements

---

AvSynchronizer.h

### See Also

---

[AvSynchronizer CreateChannel](#), [AvSynchronizer DeleteChannel](#), [TPBCHOPTION](#)

#### 4.4.10 AvSynchronizer\_DecomposeAudio

Decode audio in synchronous mode. The buffer should be given by caller, and if the buffer size is not enough, error will be returned without decode the audio.

##### Syntax

```

SCOPE AvSynchronizer_DecomposeAudio (
    HANDLE hDecChannel,
    TMediaDataPacketInfo *pMediaDataPacket,
    TAFRAMEINFO *pfAudioFrameInfo,
    DWORD *pdwSize,
);

```

##### Parameters

###### hDecChannel

[in] the decoder handle created by [AvSynchronizer\\_CreateDecoderChannel](#).

###### pMediaDataPacket

[in] the pointer of the media packet that hold the to be decoded audio data.

###### pfAudioFrameInfo

[in/out] the pointer of the structure [TAFRAMEINFO](#) that holds the decoded audio frame. The pbySound must points to the buffer to hold the decoded audio. And the dwSize of this structure hold the size of the buffer. The minimum size of the buffer is (Size of a decoded frame) \* (number of frame in a packet). The former depends on the codec type and the maximum value now is 2048. And the later is recorded in member dwFrameNumber of pMediaDataPacket.

###### pdwSize

[out] It holds the total size of the decoded audio.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_DATA**

The checksum of the packet is not correct.

**AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY**

There is not enough memory.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_BUFFER\_SIZE\_NOTENOUGH**

The given buffer size is not enough to hold the decoded data.

**AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

**AVSYNCHRONIZER\_E\_DECODE\_ERROR**

The audio is decoded error.

**Remarks**

---

Note, if you turn off the output of audio by setting `SETCH_OUTPUT_AUDIO_FRAME` to be false, the call to this function will return `AVSYNCHRONIZER_S_OK`, but no data will be decoded, and no data will be returned. This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

#### 4.4.11 AvSynchronizer\_DecodeVideo

Decode video in synchronous mode. The buffer should be given by caller, and if the buffer size is not enough, error will be returned without decode the video.

##### Syntax

```

SCOPE AvSynchronizer_DecodeVideo (

                                HANDLE                hDecChannel,

                                TMediaDataPacketInfo    *pMediaDataPacket,

                                TVFRAMEINFO            *pfVideoFrameInfo,

                                DWORD                *pdwSize,

);

```

##### Parameters

###### **hDecChannel**

[in] the decoder handle created by [AvSynchronizer\\_CreateDecoderChannel](#).

###### **pMediaDataPacket**

[in] the pointer of the media packet that hold the to be decoded video data.

###### **pfVideoFrameInfo**

[in/out] the pointer of the structure [TVFRAMEINFO](#) that holds the decoded video frame. The pbyHeader must points to the buffer to hold the decoded audio. And the dwSize of this structure hold the size of the buffer. The minimum size of the buffer is (Width of the video) \* (Height of the video) \* (Bytes per pixel) for most video format. For Jpeg, it would relate to the compressing factor. Usually set the buffer size to 704x576x4 would fit most case. The buffer size must also add with the reserved buffer size set by SETCH\_RESERVED\_HEADER option with [AvSynchronizer\\_SetChannelOption](#).

###### **pdwSize**

[out] It holds the total size of the decoded video.

##### Return Values

###### **AVSYNCHRONIZER\_S\_OK**

Decode the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_DATA**

The checksum of the packet is not correct.

**AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY**

There is not enough memory.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_BUFFER\_SIZE\_NOTENOUGH**

The given buffer size is not enough to hold the decoded data.

**AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

**AVSYNCHRONIZER\_E\_DECODE\_ERROR**

The audio is decoded error.

**Remarks**

---

Note, if you turn off the output of video by setting `SETCH_OUTPUT_VIDEO_FRAME` to be false, the call to this function will return `AVSYNCHRONIZER_S_OK`, but no data will be returned. The video is still decoded if the stream type is H263 or MPEG4. For Jpeg, the video decoding process is also skipped.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

#### 4.4.12 AvSynchronizer\_DecomposeVideoDecodeOnly

This function is almost the same as [AvSynchronizer\\_DecomposeVideo](#), but this function only decodes and returns information and size of the frame. It does not retrieve the decoded frame content. Use [AvSynchronizer\\_GetDecodedVideoFrame](#) to get frame content.

##### Syntax

```
SCODE AvSynchronizer_DecomposeVideoDecodeOnly (
    HANDLE hDecChannel,
    TMediaDataPacketInfo *pMediaPacket,
    TVFRAMEINFO *pfVideoFrameInfo,
    DWORD *pdwSize
);
```

##### Parameters

###### hDecChannel

[in] the decoder handle created by [AvSynchronizer\\_CreateDecoderChannel](#).

###### pMediaDataPacket

[in] the pointer of the media packet that hold the to be decoded video data.

###### pfVideoFrameInfo

[in/out] the pointer of the structure [TVFRAMEINFO](#) that holds the decoded video frame. The pbyHeader must points to the buffer to hold the decoded audio. And the dwSize of this structure hold the size of the buffer. The minimum size of the buffer is (Width of the video) \* (Height of the video) \* (Bytes per pixel) for most video format.

For Jpeg, it would relate to the compressing factor. Usually set the buffer size to 704x576x4 would fit most case. The buffer size must also add with the reserved buffer size set by SETCH\_RESERVED\_HEADER option with [AvSynchronizer\\_SetChannelOption](#).

###### pdwSize

[out] It holds the total size of the decoded video.

##### Return Values

AVSYNCHRONIZER\_S\_OK

Decode the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

**AVSYNCHRONIZER\_E\_DECODE\_ERROR**

The audio is decoded error.

[Remarks](#)

---

This function can reduce the overhead when users want to decode the frame but do not retrieve the frame.

[Requirements](#)

---

AvSynchronizer.h

[See Also](#)

---



#### 4.4.13 AvSynchronizer\_DeleteAVIChannel

Delete the AVI channel whenever conversion is done. This function release all the resource associated with the channel.

##### Syntax

```
SCODE AvSynchronizer_DeleteAVIChannel (
                                     HANDLE      hAvSync,
                                     HANDLE      *phAVIChannel,
);
```

##### Parameters

###### hAvSync

[in] the handle created by [AvSynchronizer\\_Initial](#) or [AvSynchronizer\\_InitialEx](#).

###### phAVIChannel

[in/out] the pointer of the handle to be deleted and the content of the pointer would be cleared to NULL.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_S\_ALREADY\_DELETE

The channel has been removed.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

### Requirements

---

AvSynchronizer.h, AviConverter.dll

### See Also

---

#### 4.4.14 AvSynchronizer\_DeleteChannel

Delete the channel created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

##### Syntax

```
SCODE AvSynchronizer_DeleteChannel (  
  
                                HANDLE          hAvSync,  
                                HANDLE          *pChannel,  
  
);
```

##### Parameters

###### hAvSync

[in] the handle created by [AvSynchronizer\\_Initial](#) or [AvSynchronizer\\_InitialEx](#).

###### phChannel

[in] the address of the handle of channel created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to delete the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_CHANNEL\_NOT\_FOUND

The channel you specified does not exist.

##### Remarks

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h, AviConverter.dll

See Also

---

[AvSynchronizer\\_CreateChannel](#), [AvSynchronizer\\_CreatePlaybackChannel](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.15 AvSynchronizer\_DeleteDecoderChannel

---

Delete the decode channel.

##### Syntax

---

```
SCODE AvSynchronizer_DeleteDecoderChannel (  
  
                                HANDLE          hAvSync,  
                                HANDLE          *pDecChannel,  
  
);
```

##### Parameters

---

###### **hAvSync**

[in] the handle of the AvSynchronizer, which created by [AvSynchronizer\\_Initial](#).

###### **phDecChannel**

[in] the address of the handle created by [AvSynchronizer\\_CreateDecoderChannel](#).

##### Return Values

---

###### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

###### **AVSYNCHRONIZER\_E\_FAIL**

Fail delete the channel.

###### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

##### Remarks

---

##### Requirements

---

AvSynchronizer.h

##### See Also

---

#### 4.4.16 AvSynchronizer\_FreePicture

---

Call this function to free the snapshot created by [AvSynchronizer\\_GetCurrentSnapShot](#).

##### Syntax

---

```
SCODE AvSynchronizer_FreePicture (  
                                     PTSNAPSHOT      tSnapShot  
);
```

##### Parameters

---

###### ptSnapShot

[in] the address of the [TSNAPSHOT](#) structure.

##### Return Values

---

###### AVSYNCHRONIZER\_S\_OK

Free snapshot successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to free snapshot.

##### Remarks

---

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

---

AvSynchronizer.h

##### See Also

---

### 4.4.17 AvSynchronizer\_GetCurrentDisplay

---

Call this function to get a snapshot of current display area.

#### Syntax

---

```
SCODE AvSynchronizer_GetCurrentDisplay (
    HANDLE hChannel,
    HDC hDC,
    TCURRENTDISPLAYINFO *ptDspInfo
);
```

#### Parameters

---

##### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

##### hDC

[int/out] The DC to draw the current display area.

##### ptDspInfo

[in/out] The structure to store current display information. See [TCURRENTDISPLAYINFO](#).

#### Return Values

---

##### AVSYNCHRONIZER\_S\_OK

Get snapshot successfully.

##### AVSYNCHRONIZER\_E\_FAIL

Fail to get current display.

##### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

#### Remarks

---

This function is only available for Windows 32 / Windows CE platform currently.

#### Requirements

---

AvSynchronizer.h

[See Also](#)

---

VIVOTEK CONFIDENTIAL  
2017.01.20



#### 4.4.18 AvSynchronizer\_GetAudioCompressorParam

Retrieve the current audio compressor setting in the AVSynchronizer handle.

##### Syntax

```
SCODE AvSynchronizer_GetAudioCompressorParam (  
  
                                     HANDLE          hAVSync,  
                                     TAUDIOOPTION    *ptOption,  
  
);
```

##### Parameters

###### **hAVSync**

[in] the value of the handle returned by [AvSynchronizer Initial](#).

###### **ptAudioOption**

[out] the setting for the audio compressor.

##### Return Values

###### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

###### **AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

###### **AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.19 AvSynchronizer\_GetChannelAudioCompressorParam

Retrieve the current audio compressor setting in the channel.

##### Syntax

```
SCODE AvSynchronizer_GetChannelAudioCompressorParam (
    HANDLE hAVIChannel,,
    TAUDIOOPTION *ptOption,
);
```

##### Parameters

**hAVIChannel,**

[in] the AVI channel created by calling [AvSynchronizer CreateAVIChannel](#) or [AvSynchronizer CreateLiveAVIChannel](#).

**ptAudioOption**

[out] the setting for the audio compressor.

##### Return Values

**AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

[See Also](#)

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.20 AvSynchronizer\_GetChannelVideoCompressorParam

Retrieve the current video compressor setting in the channel.

##### Syntax

```
SCODE AvSynchronizer_GetChannelVideoCompressorParam (
    HANDLE hAVIChannel,,
    TVIDEOOPTION *ptOption,
);
```

##### Parameters

###### hAVIChannel

[in] the AVI channel created by calling [AvSynchronizer CreateAVIChannel](#) or [AvSynchronizer CreateLiveAVIChannel](#).

###### pVideoInfo

[out] the setting for the video compressor.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

[See Also](#)

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.21 AvSynchronizer\_GetCapabilities

Get the capability of the video card.

##### Syntax

```
SCODE AvSynchronizer_GetCapabilities (
                                HANDLE          hAvSync,
                                DWORD           *pdwCapabilities,
                                DWORD           dwScreen
);
```

##### Parameters

###### hAvSync

[in] the handle of the AvSynchronizer, which created by [AvSynchronizer\\_Init](#).

###### pdwCapabilities

[out] the address of the DWORD to receive the value of capabilities. The capabilities are defined in [EDISPLAYCAP](#).

###### dwReserverd

[in] This is the reserved field that should be 0 now.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

Fail delete the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

[See Also](#)

---

VIVOTEK CONFIDENTIAL  
2017.01.20



#### 4.4.22 AvSynchronizer\_GetRemainingQueueElementCount

---

Call this function to get the queue status of AvSynchronizer.

##### Syntax

---

```
SCODE AvSynchronizer_GetRemainingQueueElementCount (
    HANDLE hChannel,
    TAVSYNCQUEUESTATUS *ptQueueStatus,
);
```

##### Parameters

---

###### hChannel

[in] The handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

###### ptQueueStatus

[out] The structure holds the status of queue.

##### Return Values

---

###### AVSYNCHRONIZER\_S\_OK

Retrieve queue status successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

---

##### Requirements

---

AvSynchronizer.h

##### See Also

---

[AvSynchronizer\\_Initial](#), [AvSynchronizer\\_InitialEx](#).

#### 4.4.23 AvSynchronizer\_GetCurrentSnapShot

Call this function to get a snapshot.

##### Syntax

```
SCODE AvSynchronizer_GetCurrentSnapShot (
    HANDLE hChannel,
    PTSNAPSHOT ptSnapShot,
    DWORD dwFlag
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

###### ptSnapShot

[out] the address of the [TSNAPSHOT](#) structure.

###### dwFlag

[in] indicate if get the original video size image. See [ESNAPSHOTFLAG](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Get snapshot successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to get snapshot.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

When you don't need the snapshot, you must call [AvSynchronizer\\_FreePicture](#) to free the snapshot.

This function is only available for Windows 32 / Windows CE platform currently.

## Requirements

---

AvSynchronizer.h

## See Also

---

[AvSynchronizer](#), [FreePicture](#), [TSNAPSHOT](#), [ESNAPSHOTFLAG](#).

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.24 AvSynchronizer\_GetDecodedVideoFrame

Get the previous decoded frame as the specified output format.

##### Syntax

```
SCODE AvSynchronizer_GetDecodedVideoFrame (
    HANDLE hDecChannel,
    TMediaDataPacketInfo *pPacket,
    TVFRAMEINFO *pfVideoFrameInfo,
    DWORD dwRawDataFormat,
    DWORD dwReservedHeaderLen,
    DWORD *pdwSize
);
```

##### Parameters

###### **hDecChannel**

[in] the decoder handle created by [AvSynchronizer\\_CreateDecoderChannel](#).

###### **pMediaDataPacket**

[out] the pointer of the media packet that hold the video frame information to be output.

###### **pfVideoFrameInfo**

[in/out] the pointer of the structure [TVFRAMEINFO](#) that holds the decoded video frame. The pbyHeader must points to the buffer to hold the decoded audio. And the dwSize of this structure hold the size of the buffer. The minimum size of the buffer is (Width of the video) \* (Height of the video) \* (Bytes per pixel) for most video format.

For Jpeg, it would relate to the compressing factor. Usually set the buffer size to 704x576x4 would fit most case. The buffer size must also add with the reserved buffer size set by SETCH\_RESERVED\_HEADER option with [AvSynchronizer\\_SetChannelOption](#).

###### **dwRawDataFormat**

[in]the video format of the output.

###### **dwReservedHeaderLen**

[in]the reserved header length.

**pdwSize**

[out] It holds the total size of the decoded video.

**Return Values**

---

**AVSYNCHRONIZER\_S\_OK**

Decode the channel successfully.

**AVSYNCHRONIZER\_E\_INVALID\_DATA**

The checksum of the packet is not correct.

**AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY**

There is not enough memory

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

**AVSYNCHRONIZER\_E\_BUFFER\_SIZE\_NOTENOUGH**

The given buffer size is not enough to hold the decoded data.

**AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

**AVSYNCHRONIZER\_E\_DECODE\_ERROR**

The audio is decoded error.

**Remarks**

---

Use this function to get the previous frame in various formats repeatedly.

[AvSynchronizer DecodeVideo](#) can only get a given frame with specified format once.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

[AvSynchronizer DecodeVideoDecodeOnly](#), [AvSynchronizer DecodeVideo](#)

#### 4.4.25 AvSynchronizer\_GetFlags

---

Call this function to retrieve the flags for AVSynchronizer.

##### Syntax

---

```
SCODE AvSynchronizer_GetFlags (  
  
                                HANDLE          hAvSync,  
                                DWORD          *pdwFlags,  
  
);
```

##### Parameters

---

###### **hAvSync**

[in] the AvSynchronizer object, returned by [AvSynchronizer\\_Initial](#).

###### **pdwFlags**

[out] the buffer to hold the returned flags.

##### Return Values

---

###### **AVSYNCHRONIZER\_S\_OK**

Retrieve flags successfully.

###### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

##### Remarks

---

##### Requirements

---

AvSynchronizer.h

##### See Also

---

[AvSynchronizer\\_Initial](#), [AvSynchronizer\\_InitialEx](#).

#### 4.4.26 AvSynchronizer\_GetVersionInfo

---

Get the version info about the AvSynchronizer module.

##### Syntax

---

```
SCODE AvSynchronizer_GetVersionInfo (  
  
                                BYTE          *pbyMajor,  
                                BYTE          *pbyMinor,  
                                BYTE          *pbyBuild,  
                                BYTE          *pbyRevision  
);
```

##### Parameters

---

###### **pbyMajor**

[out] the address of a BYTE to receive the Major number of the version.

###### **pbyMinor**

[out] the address of a BYTE to receive the Minor number of the version.

###### **pbyBuildr**

[out] the address of a BYTE to receive the Build number of the version.

###### **pbyRevision**

[out] the address of a BYTE to receive the Revision number of the version.

##### Return Values

---

###### **AVSYNCHRONIZER\_S\_OK**

Get version info successfully.

###### **AVSYNCHRONIZER\_E\_FAIL**

Fail to get version info.

##### Remarks

---

##### Requirements

---

AvSynchronizer.h

[See Also](#)

---

VIVOTEK CONFIDENTIAL  
2017.01.20



#### 4.4.27 AvSynchronizer\_GetVideoCompressorParam

Retrieve the current video compressor setting in the AVSynchronizer handle.

##### Syntax

```
SCODE AvSynchronizer_GetVideoCompressorParam (
    HANDLE hAVIChannel,
    TVIDEOOPTION *ptVideoOption
);
```

##### Parameters

###### **hAvSync**

[in] the AvSynchronizer object, returned by [AvSynchronizer\\_Initial](#).

###### **pVideoInfo**

[out] the setting for the video compressor.

##### Return Values

###### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

###### **AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

###### **AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.28 AvSynchronizer\_GetZoomedSnapShot

Call this function to get a snapshot under digital zoom. The output picture is the zoomed area only.

##### Syntax

```
SCODE AvSynchronizer_GetZoomedSnapShot (
    HANDLE hChannel,
    PTSNAPSHOT ptSnapShot,
    DWORD dwFlag
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

###### ptSnapShot

[out] the address of the [TSNAPSHOT](#) structure.

###### dwFlag

[in] indicate if get the original video size image. See [ESNAPSHOTFLAG](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Get snapshot successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to get snapshot.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

When you don't need the snapshot, you must call [AvSynchronizer\\_FreePicture](#) to free the snapshot.

This function is only available for Windows 32 platform currently.

## Requirements

---

AvSynchronizer.h

## See Also

---

[AvSynchronizer\\_FreePicture](#), [AvSynchronizer\\_GetCurrentSnapShot](#), [TSNAPSHOT](#), [ESNAPSHOTFLAG](#).

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.29 AvSynchronizer\_GetZoomedDisplay

Call this function to get a snapshot of current display area when digital zoom. The output picture is the zoomed area only.

##### Syntax

```
SCODE AvSynchronizer_GetZoomedDisplay (
    HANDLE          hChannel,
    HDC              hDC,
    TCURRENTDISPLAYINFO *ptDspInfo
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

###### HDC

[int/out] The DC to draw the current display area.

###### ptDspInfo

[in/out] The structure to store current display information. See [TCURRENTDISPLAYINFO](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Get snapshot successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to get current display.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

This function is only available for Windows 32 platform currently.

## Requirements

---

AvSynchronizer.h

## See Also

---

[AvSynchronizer\\_FreePicture](#), [AvSynchronizer\\_GetCurrentSnapShot](#), [TSNAPSHOT](#), [ESNAPSHOTFLAG](#).

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.4.30 AvSynchronizer\_Initial

This function initializes the AvSynchronizer Module. You must call either this function or [AvSynchronizer\\_InitialEx](#) before using this module.

#### Syntax

```

SCOPE AvSynchronizer_Initial (
    HANDLE                *phAvSync,
    LPSTATUSCALLBACK    pfStatus,
    LPDISPLAYCALLBACK   pfDisplay,
    HWND                  hWnd,
    DWORD                  dwAudioFocusType,
    long                   lSyncParameter,
    DWORD                  dwVersion,
    DWORD                  dwFlag
);

```

#### Parameters

##### phAvSync

[out] the pointer to receive the handle of this AvSynchronizer object.

##### pfStatus

[in] The pointer to the [LPSTATUSCALLBACK](#). To be used to notify the application the status of AvSynchronizer.

##### pfDisplay

[in] The pointer to the [LPDISPLAYCALLBACK](#). To be used to notify the application to display something.

##### hWnd

[in] Window handle used for the application. Set to the calling application's top-level window handle (not a handle for any child windows created by the top-level window).

##### dwAudioFocusType

[in] indicate the focus type of the DirectSound buffer. Its value is one in [EAUDIOFOCUSTYPE](#) enumeration.

##### lSyncParameter

[in] as long as a parameter to tune the audio and video synchronization.

### **dwVersion**

[in] the version of the AvSynchronizer. Assign the value AVSYNCHRONIZER\_VERSION to this parameter.

### **dwFlag**

[in] See [EAVSYBCINITFLAG](#).

### [Return Values](#)

---

#### **AVSYNCHRONIZER\_S\_OK**

Initializes this module ok.

#### **AVSYNCHRONIZER\_S\_NO\_AUDIO\_PLAY**

Audio initializes failed. Audio input will be ignored.

#### **AVSYNCHRONIZER\_E\_FAIL**

Initial this module fail.

#### **AVSYNCHRONIZER\_E\_INVALID\_VERSION**

You are using an incompatible version.

#### **AVSYNCHRONIZER\_E\_INVALID\_ARG**

There are one or more arguments invalid.

#### **AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY**

There are not enough memory.

#### **AVSYNCHRONIZER\_E\_CREATE\_EVENT\_FAILED**

Create event fail

### [Remarks](#)

---

### [Requirements](#)

---

AvSynchronizer.h

### [See Also](#)

---



[AvSynchronizer\\_Release](#), [AvSynchronizer\\_InitialEx](#), [LPSTATUSCALLBACK](#), [LPDISPLAYCALLBACK](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.4.31 AvSynchronizer\_InitialEx

This function initializes the AvSynchronizer Module. You must call either this function or [AvSynchronizer\\_Initial](#) before using this module.

#### Syntax

```

SCOPE AvSynchronizer_InitialEx (
    HANDLE                *phAvSync,
    LPSTATUSCALLBACK    pfStatus,
    LPDISPLAYCALLBACK   pfDisplay,
    HWND                  hWnd,
    DWORD                  dwAudioFocusType,
    long                   lSyncParameter,
    DWORD                  dwVersion,
    DWORD                  dwFlag
    DWORD                  dwBlankColor
);

```

#### Parameters

##### phAvSync

[out] the pointer to receive the handle of this AvSynchronizer object.

##### pfStatus

[in] The pointer to the [LPSTATUSCALLBACK](#). To be used to notify the application the status of AvSynchronizer.

##### pfDisplay

[in] The pointer to the [LPDISPLAYCALLBACK](#). To be used to notify the application to display something.

##### hWnd

[in] Window handle used for the application. Set to the calling application's top-level window handle (not a handle for any child windows created by the top-level window).

##### dwAudioFocusType

[in] indicate the focus type of the DirectSound buffer. Its value is one in [EAUDIOFOCUSTYPE](#) enumeration.

**ISyncParameter**

[in] as long as a parameter to tune the audio and video synchronization.

**dwVersion**

[in] the version of the AvSynchronizer. Assign the value AVSYNCHRONIZER\_VERSION to this parameter.

**dwFlag**

[in] See [EAVSYBCINITFLAG](#).

**dwBlankColor**

[in] Specified the color to fill when there is no video to display.

**Return Values**

---

**AVSYNCHRONIZER\_S\_OK**

Initializes this module ok.

**AVSYNCHRONIZER\_S\_NO\_AUDIO\_PLAY**

Audio initializes failed. Audio input will be ignored.

**AVSYNCHRONIZER\_E\_FAIL**

Initial this module fail.

**AVSYNCHRONIZER\_E\_INVALID\_VERSION**

You are using an incompatible version.

**AVSYNCHRONIZER\_E\_INVALID\_ARG**

There are one or more arguments invalid.

**AVSYNCHRONIZER\_E\_OUT\_OF\_MEMORY**

There are not enough memory.

**AVSYNCHRONIZER\_E\_CREATE\_EVENT\_FAILED**

Create event fail

**Remarks**

---

## Requirements

---

AvSynchronizer.h

## See Also

---

[AvSynchronizer\\_Release](#), [AvSynchronizer\\_Initial](#), [LPSTATUSCALLBACK](#), [LPDISPLAYCALLBACK](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.32 AvSynchronizer\_InputAVIMedia

Input the media frames into the AVI channel. The channel will decode the frame and insert them into the AVI files. Compression would be taken if specified.

##### Syntax

```
SCODE AvSynchronizer_InputAVIMedia (
    HANDLE hAVIChannel,
    TMediaDataPacketInfo *pPacketInfo
);
```

##### Parameters

###### hAVIChannel

[in] the AVI channel created by calling [AvSynchronizer\\_CreateAVIChannel](#).

###### ptMediaDataPacketInfo

[in] the data packet received from network or retrieved from database.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

###### AVSYNCHRONIZER\_E\_INVALID\_DATA

The checksum of the packet is not correct.

###### AVICONVERTER\_E\_OUT\_OF\_MEMORY

Memory allocation error happens when generating AVI file.

**AVSYNCHRONIZER\_E\_DECODE\_ERROR**

Media frame decoded error.

**Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

**Requirements**

---

AvSynchronizer.h

**See Also**

---

### 4.4.33 AvSynchronizer\_InputDecodedAVIMedia

Input the media frames into the AVI channel. The channel will decode the frame and insert them into the AVI files. Compression would be taken if specified.

#### Syntax

```
SCODE AvSynchronizer_InputDecodedAVIMedia (
    HANDLE                hAVIChannel,
    TMediaType             eFrameType,
    TFRAMEINFO             *ptFrameInfo
);
```

#### Parameters

##### hAVIChannel

[in] the AVI channel created by calling [AvSynchronizer\\_CreateLiveAVIChannel](#).

##### eFrameType

[in] The media type for current frame.

##### ptFrameInfo

[in] The decoded video or audio frame data.

#### Return Values

##### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

##### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

##### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### AVSYNCHRONIZER\_E\_INVALID\_DATA

The checksum of the packet is not correct.

#### **AVICONVERTER\_E\_OUT\_OF\_MEMORY**

Memory allocation error happens when generating AVI file.

#### **AVSYNCHRONIZER\_E\_DECODE\_ERROR**

Media frame decoded error.

#### Remarks

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer.h

#### See Also

---



#### 4.4.34 AvSynchronizer\_InputEncodedMediaFrame

Call this function to input data into the channel.

##### Syntax

```
SCODE AvSynchronizer_InputEncodedMediaFrame (
    HANDLE hChannel,
    TMediaDataPacketInfo *pPacket,
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#).

###### pMediaDataPacket

[in] the address of the structure of data packet generated from DataBroker module.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Input data to the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to input data to the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_INVALID\_DATA

The data you input is not the valid data from VIVOTEK.

###### AVSYNCHRONIZER\_E\_FRAME\_DROPPED

There is one frame dropped.

###### AVSYNCHRONIZER\_E\_MEDIA\_TYPE\_NEEDED

You need to setup the media type before the input the data packet.

## Remarks

---

This function is only available for Windows 32 / Windows CE platform currently.

## Requirements

---

AvSynchronizer.h, datapacketdef.h

## See Also

---

[AvSynchronizer\\_InputPlaybackMediaFrame](#), [TMediaDataPacketInfo](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.35 AvSynchronizer\_InputPlaybackMediaFrame

Call this function to input data into the playback channel.

##### Syntax

```
SCODE AvSynchronizer_InputPlaybackMediaFrame (
    HANDLE hChannel,
    TMediaDataPacketInfo *pPacket,
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#).

###### pMediaDataPacket

[in] the address of the structure of data packet generated from DataBroker module.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Input data to the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to input data to the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_INVALID\_DATA

The data you input is not the valid data from VIVOTEK.

###### AVSYNCHRONIZER\_E\_FRAME\_DROPPED

There is one frame dropped.

##### Remarks

This function is only available for Windows 32 / Windows CE platform currently.

## Requirements

---

AvSynchronizer.h, datapacketdef.h

## See Also

---

[AvSynchronizer](#), [InputEncodedMediaFrame](#), [TMediaDataPacketInfo](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.4.36 AvSynchronizer\_InputToBeDecodedMediaFrame

---

Input data to the decode channel.

#### Syntax

---

```
SCODE AvSynchronizer_InputToBeDecodedMediaFrame (  
  
                                HANDLE                hDecChannel,  
                                TMediaDataPacketInfo *pPacket,  
  
);
```

#### Parameters

---

##### **hDecChannel**

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateDecoderChannel](#).

##### **pMediaDataPacket**

[in] the address of the structure of data packet generated from DataBroker module.

#### Return Values

---

##### **AVSYNCHRONIZER\_S\_OK**

Input data to the channel successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Fail to input data to the channel.

##### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h, datapacketdef.h

#### See Also

---

### 4.4.37 AvSynchronizer\_Release

---

Call this function to release the AvSynchronizer object.

#### Syntax

---

```
SCODE AvSynchronizer_Release (
                                HANDLE          *phAvSync,
);
```

#### Parameters

---

##### phAvSync

[in] the address of the pointer to the AvSynchronizer object, returned by [AvSynchronizer\\_Initial](#).

#### Return Values

---

##### AVSYNCHRONIZER\_S\_OK

Release the object successfully.

##### AVSYNCHRONIZER\_E\_FAIL

Failed to release the object.

##### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h, datapacketdef.h

#### See Also

---

[AvSynchronizer\\_Initial](#)

#### 4.4.38 AvSynchronizer\_SetAudioCompressorParam

Set the audio compressor parameters for AVSynchronizer handle. This function allows program to set the compressor without invoking the selection dialog. The settings and the per-channel settings will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_SetChannelAudioCompressorParam](#), the channel will take the settings in AVShychronizer handle.

##### Syntax

```
SCODE AvSynchronizer_SetAudioCompressorParam (
    HANDLE hAvSync,
    TAUDIOOPTION *ptOption
);
```

##### Parameters

###### hAvSync

[in] the AvSynchronizer object, returned by [AvSynchronizer Initial](#).

###### ptAudioOption

[in] the setting for the audio compressor. The setting could be kept by application in its own database and retrieved whenever starts.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

### Requirements

---

AvSynchronizer.h

### See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20



### 4.4.39 AvSynchronizer\_SetBufferTime

---

Set the buffer time for the internal queue. AvSynchronizer will buffer some frames in the internal queue for preventing network jitter.

#### Syntax

---

SCODE AvSynchronizer_SetBufferTime (		
	HANDLE	hChannel,
	DWORD	dwBufferTime
);		

#### Parameters

---

##### hChannel

[in] the handle of the channel that is created by [AvSynchronizer\\_CreateChannel](#), or [AvSynchronizer\\_CreatePlaybackChannel](#).

##### dwBufferTime

[in] buffer time in milli-seconds.

#### Return Values

---

##### AVSYNCHRONIZER\_S\_OK

Set buffer time successfully.

##### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

#### Remarks

---

#### Requirements

---

AvSynchronizer.h

#### See Also

---

#### 4.4.40 AvSynchronizer\_SetChannelAudioCompressorParam

Set the audio compressor parameters. This function allows program to set the compressor without invoking the selection dialog. If the channel is used without calling this function, the video would be generated uncompressed in the AVI file. The settings and the settings in Avsynchronizer will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_SetAudioCompressorParam](#), the channel will take the settings in itself.

##### Syntax

```
SCODE AvSynchronizer_SetChannelAudioCompressorParam (
    HANDLE hAVIChannel,
    TAUDIOOPTION *ptOption
);
```

##### Parameters

###### hAVIChannel

[in] the AVI channel created by calling [AvSynchronizer\\_CreateAVIChannel](#) or [AvSynchronizer\\_CreateLiveAVIChannel](#).

###### ptAudioOption

[in] the setting for the audio compressor. The setting could be kept by application in its own database and retrieved whenever starts.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

#### Requirements

---

AvSynchronizer.h

#### See Also

---

#### 4.4.41 AvSynchronizer\_SetChannelOption

Set an option for the channel. This function could be applied to all the three channels but if the target channel does not support the option, AVSYNCHRONIZER\_E\_INVALID\_ARG will be returned.

##### Syntax

```
SCODE AvSynchronizer_SetChannelOption (  
  
                                HANDLE            hChannel,  
  
                                DWORD            dwOption,  
  
                                DWORD            dwParam1,  
  
                                DWORD            dwParam2  
  
);
```

##### Parameters

###### hChannel

[in] the handle of the channel that is created by [AvSynchronizer\\_CreateChannel](#), [AvSynchronizer\\_CreatePlaybackChannel](#), or [AvSynchronizer\\_CreateDecoderChannel](#).

###### dwOption

[in] the value of the option defined in [ESETCHOPTION](#)

###### dwParam1

[in] the value of the first parameter, the meaning of this parameter depends on the value of dwOption.

###### dwParam2

[in] the value of the second parameter, the meaning of this parameter depends on the value of dwOption.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

#### Remarks

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

#### Requirements

---

AvSynchronizer.h

#### See Also

---

#### 4.4.42 AvSynchronizer\_SetChannelVideoCompressorParam

Set the video compressor parameters for this channel. This function allows program to set the compressor without invoking the selection dialog. If the channel is used without calling this function, the video would be generated uncompressed in the AVI file. The settings and the settings in Avsynchronizer will be used according to which one is more recently when channel conversion starts. For example if this one is called after the [AvSynchronizer\\_SetVideoCompressorParam](#), the channel will take the settings in itself.

##### Syntax

```
SCODE AvSynchronizer_SetChannelVideoCompressorParam (
    HANDLE hAVIChannel,
    TVIDEOOPTION *ptOption,
);
```

##### Parameters

###### hAVIChannel

[in] the AVI channel created by calling [AvSynchronizer\\_CreateAVIChannel](#).

###### pVideoInfo

[in] the setting for the video compressor. The setting could be kept by application in its own database and retrieved whenever starts.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

### Requirements

---

AvSynchronizer.h

### See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.43 AvSynchronizer\_SetDisplayMode

---

Set the display mode when playing SVC-T streaming.

##### Syntax

---

```
SCODE AvSynchronizer_SetDisplayMode (  
                                     HANDLE hChannel,,  
                                     EAVSYNCHRONIZERDISPLAYMODE eDisplayMode,  
);
```

##### Parameters

---

###### hChannel

[in] the handle of the channel that is created by [AvSynchronizer\\_CreateChannel](#), [AvSynchronizer\\_CreatePlaybackChannel](#).

###### eDisplayMode

[in] the display mode. See [EAVSYNCHRONIZERDISPLAYMODE](#)

##### Return Values

---

###### AVSYNCHRONIZER\_S\_OK

Set display mode successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

---

##### Requirements

---

AvSynchronizer.h

##### See Also

---



#### 4.4.44 AvSynchronizer\_SetFlags

Call this function to change the flags for AVSynchronizer at runtime.

##### Syntax

```
SCODE AvSynchronizer_SetFlags (  
  
                                HANDLE          hAvSync,  
                                DWORD          dwFlags,  
  
);
```

##### Parameters

###### hAvSync

[in] the AvSynchronizer object, returned by [AvSynchronizer\\_Initial](#).

###### dwFlags

[in] the flags to be set, the possible values for this flag is defined [EAVSYBCINITFLAG](#) except DECODER\_CHANNEL\_ONLY, USE\_DIRECTDRAW\_ONLY and ORG\_SIZE\_MODE. It's possible to change the drawing mode from DirectDraw to GDI at runtime, but not vice versa.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Change flags successfully.

###### AVSYNCHRONIZER\_E\_COULDNT\_SWITCH\_TWOPASS

When changing for one pass to two passes mode, the needs resource could not be acquired. It's safe for AP to continue running if this error is returned. But the flag is not changed.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given parameters are not correct.

##### Remarks

## Requirements

---

AvSynchronizer.h

## See Also

---

[AvSynchronizer Initial](#), [AvSynchronizer InitialEx](#) .

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.45 AvSynchronizer\_SetQueueEmptyNotify

Register a callback function that it will callback to application when the internal queue of AvSynchronizer is empty.

##### Syntax

```
SCODE AvSynchronizer_SetQueueEmptyNotify (
    HANDLE hChannel,
    LPENDOFSTREAMING pfEndOfStreamingCB,
    void *pvContext
);
```

##### Parameters

###### hChannel

[in] the handle of the channel that is created by [AvSynchronizer\\_CreateChannel](#), [AvSynchronizer\\_CreatePlaybackChannel](#), or [AvSynchronizer\\_CreateDecoderChannel](#).

###### pfEndOfStreamingCB

[in] The callback function pointer.

###### pvContext

[in] context of the callback function.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be null.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given parameters are not correct.

##### Remarks

## Requirements

---

AvSynchronizer.h

## See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.46 AvSynchronizer\_SetVideoCompressorParam

Set the video compressor parameters for AVSynchronizer handle. This function allows program to set the compressor without invoking the selection dialog. If the channel is used without calling this function, the video would be generated uncompressed in the AVI file. The settings and the per-channel settings will be used according to which one is more recently when channel conversion starts. For example if this one is called after the AvSynchronizer\_GetChannelVideoCompressorParam, the channel will take the settings in AVShychronizer handle.

##### Syntax

```
SCODE AvSynchronizer_SetVideoCompressorParam (  
                                     HANDLE          hAvSync,  
                                     TVIDEOOPTION    *ptOption,  
);
```

##### Parameters

###### hAvSync

[in] the AvSynchronizer object, returned by [AvSynchronizer Initial](#).

###### ptVideoOption

[in] the setting for the video compressor. The setting could be kept by application in its own database and retrieved whenever starts.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

##### Remarks

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

#### Requirements

---

AvSynchronizer.h

#### See Also

---

#### 4.4.47 AvSynchronizer\_StartAVIChannel

Start the AVI channel. This initializes some parameters such as the output file name and media type, etc....

##### Syntax

```
SCODE AvSynchronizer_StartAVIChannel (
    HANDLE hAVIChannel,
    TAVIOPTION2 *ptAviOption2,
);
```

##### Parameters

###### hAVIChannel

[in] the channel handle created by calling [AvSynchronizer\\_CreateAVIChannel](#).

###### ptAviChOption2

[int] the setting for the channel.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Delete the channel successfully.

###### AVSYNCHRONIZER\_E\_INVALID\_ARG

The given option is not supported by this channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT

The AviConverter.dll is not found in the DLL search path.

###### AVICONVERTER\_E\_INVALID\_FILENAME

The file name member in [TAVIOPTION2](#) structure is empty.

###### AVSYNCHRONIZER\_E\_OPEN\_AVI\_FILE

Unable to open the AVI file, the path may not exist, the user does not have the

permission to open file or the disk is full.

#### **AVSYNCHRONIZER\_E\_CREATE\_AVI\_V\_STREAM**

Unable to create video stream in AVI file, may the system resource is not enough.

#### **AVSYNCHRONIZER\_E\_CREATE\_AVI\_A\_STREAM**

Unable to create audio stream in AVI file, may the system resource is not enough.

#### **Remarks**

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 / Windows CE platform currently.

#### **Requirements**

---

AvSynchronizer.h, AviConverter.dll

#### **See Also**

---



#### 4.4.48 AvSynchronizer\_StartChannel

Call this function to start the channel. You can't see the video before calling this function.

##### Syntax

```
SCODE AvSynchronizer_StartChannel (
    HANDLE hChannel,
    DWORD dwFlag
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

###### dwFlag

[in] See [ESTARTCHANNELFLAG](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Start the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to start the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

##### See Also

[AvSynchronizer\\_CreateChannel](#), [AvSynchronizer\\_CreatePlaybackChannel](#), [AvSynchronizer\\_StopChannel](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.49 AvSynchronizer\_StopAVIChannel

---

Stop the AVI channel and close the AVI file.

##### Syntax

---

```
SCODE AvSynchronizer_StopAVIChannel (  
  
                                HANDLE                hAVIChannel,  
  
);
```

##### Parameters

---

###### **hAVIChannel**

[in] the handle of the channel to be stopped. Please ensure that no more packet is input to the channel after calling this function.

##### Return Values

---

###### **AVSYNCHRONIZER\_S\_OK**

Delete the channel successfully.

###### **AVSYNCHRONIZER\_E\_INVALID\_ARG**

The given option is not supported by this channel.

###### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

###### **AVSYNCHRONIZER\_E\_NOT\_IMPLEMENT**

The AviConverter.dll is not found in the DLL search path.

###### **AVSYNCHRONIZER\_E\_ENCODE\_AVI\_AUDIO**

Encode audio packet failed.

###### **AVSYNCHRONIZER\_E\_WRITE\_AVI\_FILE**

Write media data to AVI file error.

##### Remarks

---

Note: to reduce the overhead for the programs that do not need AVI converter, the actual AVI converter operation code is implemented in AviConverter.dll. So for the programs that need AVI converter functions, please make sure the DLL exists in your working directory.

This function is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer.h

#### See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.4.50 AvSynchronizer\_StopChannel

---

Call this function to stop the channel. Once you call this to stop a channel, you must call [AvSynchronizer\\_StartChannel](#) if you want to restart the channel again.

#### Syntax

---

```
SCODE AvSynchronizer_StopChannel (  
                                     HANDLE          hChannel,  
);
```

#### Parameters

---

##### **hChannel**

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#) or [AvSynchronizer\\_CreatePlaybackChannel](#).

#### Return Values

---

##### **AVSYNCHRONIZER\_S\_OK**

Stop the channel successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Fail to stop the channel.

#### Remarks

---

This function is only available for Windows 32 / Windows CE platform currently.

#### Requirements

---

AvSynchronizer.h

#### See Also

---

[AvSynchronizer\\_CreateChannel](#), [AvSynchronizer\\_CreatePlaybackChannel](#), [AvSynchronizer\\_StartChannel](#)

#### 4.4.51 AvSynchronizer\_UpdateChannelSettings

Call this function to change some settings of the channel.

##### Syntax

```
SCODE AvSynchronizer_UpdateChannelSettings (
    HANDLE hChannel,
    TUPDATECHANNELOPTION tUpdateOptions
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreateChannel](#).

###### tUpdateChannelOptions

[in] a structure contains some settings of the channel. See [TUPDATECHANNELOPTION](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Update the channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to update the channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

###### AVSYNCHRONIZER\_E\_NOT\_APPLICABLE

This action is not acceptable.

##### Remarks

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

See Also

---

[AvSynchronizer\\_UpdatePlaybackChannelSettings, TUPDATECHANNELOPTION](#)

VIVOTEK CONFIDENTIAL  
2017.01.20

#### 4.4.52 AvSynchronizer\_UpdatePlaybackChannelSettings

Call this function to change some settings of the playback channel.

##### Syntax

```
SCODE AvSynchronizer_UpdatePlaybackChannelSettings (
    HANDLE hChannel,
    TUPDATEPBCHANNELOPTION tUpdateOptions
);
```

##### Parameters

###### hChannel

[in] the handle of the channel, which created by [AvSynchronizer\\_CreatePlaybackChannel](#).

###### tUpdatePBChannelOptions

[in] a structure contains the settings of the channel. See [TUPDATEPBCHANNELOPTION](#).

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Update the playback channel successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to update the playback channel.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

This function is only available for Windows 32 / Windows CE platform currently.

##### Requirements

AvSynchronizer.h

##### See Also

[AvSynchronizer\\_UpdateChannelSettings](#), [TUPDATEPBCHANNELOPTION](#)



## 4.5 Fisheye API Definition

---

The API definition for fisheye is depicted here.

VIVOTEK CONFIDENTIAL  
2017.01.20

### 4.5.1 AvSynchronizer\_FisheyeCheckSupport

---

Check whether the current machine supports fisheye renderer.

#### Syntax

---

```
SCODE AvSynchronizer_FisheyeCheckSupport (  
  
                                BOOL                                *pbIsSupportFisheye  
  
);
```

#### Parameters

---

##### **pbIsSupportFisheye**

[out] Does this machine support fisheye renderer or not.

#### Return Values

---

##### **AVSYNCHRONIZER\_S\_OK**

Check procedure is done successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Check fails.

#### Remarks

---

This function is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer\_Fisheye.h

#### See Also

---

## 4.5.2 AvSynchronizer\_FisheyeDisableRenderer

---

Disable fisheye renderer.

### Syntax

---

```
SCODE AvSynchronizer_FisheyeDisableRenderer (  
  
                                HANDLE                hChannel  
  
);
```

### Parameters

---

#### hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

### Return Values

---

#### AVSYNCHRONIZER\_S\_OK

Disable the renderer successfully.

#### AVSYNCHRONIZER\_E\_FAIL

Fail to disable the renderer.

### Remarks

---

User should call this function after calling [AvSynchronizer\\_StopChannel](#).

This function is only available for Windows 32 platform currently.

### Requirements

---

AvSynchronizer\_Fisheye.h

### See Also

---

[AvSynchronizer\\_FisheyeEnableRenderer](#)

### 4.5.3 AvSynchronizer\_FisheyeEnableRenderer

---

Enable fisheye renderer.

#### Syntax

---

```
SCODE AvSynchronizer_FisheyeEnableRenderer (  
  
                                HANDLE                hChannel  
  
);
```

#### Parameters

---

##### **hChannel**

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

#### Return Values

---

##### **AVSYNCHRONIZER\_S\_OK**

Enable the renderer successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Fail to enable the renderer.

##### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

#### Remarks

---

User should call this function before calling [AvSynchronizer\\_StartChannel](#).

This function is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer\_Fisheye.h

#### See Also

---

[AvSynchronizer\\_FisheyeDisableRenderer](#)

#### 4.5.4 AvSynchronizer\_FisheyeGetCurrentViewerDisplay

Call this function to get a display content of current viewer.

##### Syntax

```
SCODE
AvSynchronizer_FisheyeGetCurrentViewerDisplay (    HANDLE          hChannel
                                                    HDC             hDC,
                                                    TFISHEYECURRENTDISPLAY *ptDisplay
);
```

##### Parameters

###### hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

###### hDC

[in] The device context.

###### ptDisplay

[out] The information about the current display.

##### Return Values

###### AVSYNCHRONIZER\_S\_OK

Get current display information successfully.

###### AVSYNCHRONIZER\_E\_FAIL

Fail to Get current display information.

###### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

##### Remarks

This function is only available for Windows 32 platform currently.

## Requirements

---

AvSynchronizer\_Fisheye.h

## See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20

## 4.5.5 AvSynchronizer\_FisheyeGetCurrentViewerSnapshot

Call this function to get a snapshot of the viewer.

### Syntax

```
SCODE AvSynchronizer_FisheyeGetCurrentViewerSnapShot (  
  
                                HANDLE          hChannel  
                                TFISHEYESNAPSHOT *ptSnapshot,  
                                DWORD          dwFlags  
);
```

### Parameters

#### hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

#### ptSnapshot

[in] The pointer to [TFISHEYESNAPSHOT](#).

#### dwFlags

[in] Indicate if get the original video size image. See [ESNAPSHOTFLAG](#).

### Return Values

#### AVSYNCHRONIZER\_S\_OK

Get snapshot successfully.

#### AVSYNCHRONIZER\_E\_FAIL

Fail to get snapshot.

#### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

### Remarks

This function is only available for Windows 32 platform currently.

## Requirements

---

AvSynchronizer\_Fisheye.h

## See Also

---

VIVOTEK CONFIDENTIAL  
2017.01.20



## 4.5.6 AvSynchronizer\_FisheyeGetViewerPresentParameters

---

Get the present parameters of specified viewer.

### Syntax

---

```
SCODE  
AvSynchronizer_FisheyeGetViewerPresentParameters (      HANDLE          hChannel  
                                                         TFISHEYEPRESENTPARAMS *ptParams,  
                                                         DWORD          dwFlags  
);
```

### Parameters

---

#### hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

#### ptParams

[out] A structure contains current settings of the viewer. See [TFISHEYEPRESENTPARAMS](#).

### Return Values

---

#### AVSYNCHRONIZER\_S\_OK

Get the parameters successfully.

#### AVSYNCHRONIZER\_E\_FAIL

Fail to get the parameters.

#### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

### Remarks

---

This function is only available for Windows 32 platform currently.

### Requirements

---

AvSynchronizer\_Fisheye.h

### See Also

---

AvSynchronizer\_FisheyeSetViewerPresentParameters

VIVOTEK CONFIDENTIAL  
2017.01.20

4.5.7 AvSynchronizer\_FisheyeRegisterViewer

Call this function to register a viewer of the channel.

Syntax

```
SCODE AvSynchronizer_FisheyeRegisterViewer (  
  
                                HANDLE          hChannel  
                                TFISHEYEVIEWER *ptFisheyeViewer,  
  
);
```

Parameters

hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

ptFisheyeViewer

[in] A structure contains some settings of the viewer. See [TFISHEYEVIEWER](#).

Return Values

AVSYNCHRONIZER\_S\_OK

Register the viewer successfully.

AVSYNCHRONIZER\_E\_FAIL

Fail to register the viewer.

AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

Remarks

This function is only available for Windows 32 platform currently.

Requirements

AvSynchronizer\_Fisheye.h

See Also

[AvSynchronizer\\_FisheyeRemoveViewer](#)

## 4.5.8 AvSynchronizer\_FisheyeRemoveViewer

Call this function to remove the specific viewer of the channel.

### Syntax

```
SCODE AvSynchronizer_FisheyeRemoveViewer (  
  
                                HANDLE          hChannel  
                                TFISHEYEVIEWER *ptFisheyeViewer,  
  
);
```

### Parameters

#### hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

#### ptFisheyeViewer

[in] A structure contains some settings of the viewer. See [TFISHEYEVIEWER](#).

### Return Values

#### AVSYNCHRONIZER\_S\_OK

Remove ster the viewer successfully.

#### AVSYNCHRONIZER\_E\_FAIL

Fail to remove the viewer.

#### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

### Remarks

This function is only available for Windows 32 platform currently.

### Requirements

AvSynchronizer\_Fisheye.h

### See Also

[AvSynchronizer\\_FisheyeRegisterViewer](#)

## 4.5.9 AvSynchronizer\_FisheyeSetViewerPresentParameters

---

Set the present parameters of specified viewer.

### Syntax

---

```
SCODE AvSynchronizer_FisheyeSetViewerPresentParameters
(
    HANDLE hChannel
    TFISHEYEPRESENTPARAMS *ptParams
);
```

### Parameters

---

#### hChannel

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

#### ptParams

[out] A structure contains user-specified settings of the viewer. See [TFISHEYEPRESENTPARAMS](#).

### Return Values

---

#### AVSYNCHRONIZER\_S\_OK

Set the parameters successfully.

#### AVSYNCHRONIZER\_E\_FAIL

Fail to set the parameters.

#### AVSYNCHRONIZER\_E\_INVALID\_HANDLE

The handle can't be NULL.

### Remarks

---

This function is only available for Windows 32 platform currently.

### Requirements

---

AvSynchronizer\_Fisheye.h

### See Also

---

[AvSynchronizer\\_FisheyeGetViewerPresentParameters](#)

### 4.5.10 AvSynchronizer\_FisheyeUpdateRotateOptions

---

Call this function to update the rotate options to specified viewer of the channel.

#### Syntax

---

```
SCODE AvSynchronizer_FisheyeUpdateRotateOptions(  
  
                                HANDLE                hChannel  
                                TFISHEYEROTATEOPTIONS *ptRotateOptions  
  
);
```

#### Parameters

---

##### **hChannel**

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

##### **ptRotateOptions**

[in] a structure contains some options of when rotating. See [TFISHEYEROTATEOPTIONS](#).

#### Return Values

---

##### **AVSYNCHRONIZER\_S\_OK**

Update the rotation options successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Fail to update the rotation options.

##### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

#### Remarks

---

This function is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer\_Fisheye.h

#### See Also

---

### 4.5.11 AvSynchronizer\_FisheyeUpdateViewer

---

Call this function to update the settings of sepcified viewer of the channel.

#### Syntax

---

```
SCODE AvSynchronizer_FisheyeUpdateViewer (  
  
                                HANDLE          hChannel  
                                TFISHEYEVIEWER    *ptFisheyeViewer  
  
);
```

#### Parameters

---

##### **hChannel**

[in] The handle of the channel created by [AvSynchronizer\\_CreateChannel](#).

##### **ptFisheyeViewer**

[in] a structure contains some settings of the viewer. See [TFISHEYEVIEWER](#).

#### Return Values

---

##### **AVSYNCHRONIZER\_S\_OK**

Update the viewer successfully.

##### **AVSYNCHRONIZER\_E\_FAIL**

Fail to update the viewer.

##### **AVSYNCHRONIZER\_E\_INVALID\_HANDLE**

The handle can't be NULL.

#### Remarks

---

This function is only available for Windows 32 platform currently.

#### Requirements

---

AvSynchronizer\_Fisheye.h

#### See Also

---