

IBM XIV Storage System

Storage Reinvented

The IBM XIV® Storage System is a high-end disk system designed to support key current and future business requirements for a highly available information infrastructure. Built from a grid of standard Intel®/Linux® components, it is connected in an any-to-any topology using Gigabit Ethernet.

The ground-breaking XIV architecture delivers outstanding performance, scalability, availability, and reliability. Based on SATA disks, the XIV system applies a unique parallel architecture, caching algorithms and more, eliminating hotspots and achieving performance levels beyond those of FC disk-based systems.

The XIV system provides a true single-tier solution.

Capacity and Resources

Number of Disks	180
Number of FC Ports	24
Number of iSCSI Ports	6
Raw Capacity	180 TB
Net Capacity	79 TB*
Internal Switching Capacity	168 Gbps
Memory	120 GB
Cache to Disk Bandwidth	240 Gbps
CPUs (Quad-core)	15

*Includes effect of mirroring and spares

Physical Features (per rack)

Disks

- Interface: SATA II
- 7,200 RPM supported
- Capacity: 1 TB

Physical Specifications (single rack)

- Rack dimensions: 191 cm high, 60 cm wide, 109 cm deep
- 1,912 lb/869 kg
- Clearance: front, 120 cm; rear, 100 cm

Power and Cooling (single rack)

- Input voltage: 180 to 264 VAC
 - Minimum – maximum, 180 – 264 VAC, at 60A
 - Nominal, 200 – 240 VAC, at 60A
- Power consumption: Typical, 7.7 kW; Maximum, 8.4 kW
- Heat dissipation: 26K BTU/hour
- Redundant power feed

Operating Environment

- Temperature: 10 – 35°C
- Altitude: 0 – 2,133 m
- Humidity: 25 – 80%, non-condensing



Functional Specifications

Protection Features

- Active-active N+1 redundancy on disks, modules, switches and UPS units
- All system components (disks, modules, UPS units, switches) are hot-swappable
- Data mirroring
- Self healing:
 - 30-minute rebuild time after 1 TB disk failure (minimizing double-failure risk)
 - Rebuild after module failure

Functionality

- Differential snapshots
 - Up to 16,000 snapshots
 - Instant snapshot creation
 - Writable snapshots
 - Near-zero performance overhead
- Synchronous remote copy
- Instant volume copy

Connectivity

- Fibre Channel rates: 1 Gbps, 2 Gbps, 4 Gbps
- iSCSI over Gigabit Ethernet
- SCSI-3 protocol for both FC and iSCSI

For more information

To learn more about the IBM XIV Storage System, contact your IBM representative or IBM Business Partner, or visit:

www.xivstorage.com

© Copyright IBM Corporation 2008

IBM Systems and Technology Group

Route 100

Somers, New York 10589

Produced in the United States

August 2008

All Rights Reserved

IBM, the IBM logo, ibm.com, System Storage, XIV, and the XIV logo are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml

Other company, product and service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.



Recyclable, please recycle.

TSD03055-USEN-01

