

```

::::::::::
Angles.hpp
::::::::::
# include <iostream>
# include <iomanip>
# include <fstream>
// # include <cstdlib>
// # include <cmath>
// # include <vector>
// # include <algorithm>

using namespace std;

-----  

// Purpose:  

// Class Angles Interface Files  

// Discussion:  

//  

// Licensing:  

// This code is distributed under the GNU LGPL license.  

// Modified:  

// 2012.04.27  

// Author:  

// Young Won Lim  

// Parameters:  

//-----  

double compute_angle ( int idx, int nIter );
void draw_angle_tree (int nIter, int nAngle);

class Angles
{
public:
    Angles();
    Angles(double *A, int nIter, int nAngle);

    void setA(double *A);
    void setNIter(int nIter);
    void setNAngle(int nAngle);
    int getNIter();
    int getNAngle();

    void plot_unit_circle_angle ();
    void plot_line_angle ();
    void plot_residual_errors ();
    void calc_statistics ();

private:
    double *A;
    int     nIter;
    int     nAngle;
    int     Leaf;
};


```

```

::::::::::
Angles.cpp
::::::::::
# include <iostream>
# include <iomanip>
# include <cstdlib>
# include <cmath>
# include <fstream>
# include <vector>
# include <algorithm>

using namespace std;

# include "Angles.hpp"
# include "cordic.hpp"

double pi = 3.141592653589793;
double K = 1.646760258121;

//-----
// Purpose:
//
// Class Angles Implementation Files
//
// Discussion:
//
//
// Licensing:
//
// This code is distributed under the GNU LGPL license.
//
// Modified:
//
// 2012.04.27
//
// Author:
//
// Young Won Lim
//
// Parameters:
//
//-----

//-----
// Compute Angles based on the binary tree
// idx - index for leaf nodes of the binary tree
// nIter - no of iteration (corresponds to the level of the tree)
//-----
double compute_angle ( int idx, int nIter )
{
    double angle = 0.0;
    char s[32];
    int i, j;

    // i - bit position starting from lsb
    // j = 2^i
    // (idx & (1 << i)) - i-th bit of idx
    // if each bit is '1', add atan(1/2^i)
    // if each bit is '0', sub atan(1/2^i)
    // s[32] contains the binary representation of idx

    for (i=0; i<nIter; i++) {

        j = 1 << i;
        if (idx & (1 << i)) {

```

```

        angle += atan( 1. / j );
        s[nIter-i-1] = '1';
    } else {
        angle -= atan( 1. / j );
        s[nIter-i-1] = '0';
    }

// cout << "i=" << i << " j=" << j << " 1/j=" << 1./j
//      << " atan(1/j)=" << atan(1./j)*180/3.1416 << endl;

}

s[nIter] = '\0';

// cout << nIter << " " << idx << " " << s
//      << " ---> " << angle*180/3.1416 << endl;

return angle;
}

```

```

//-----
// Draw Angle Tree
//-----
void draw_angle_tree (int nIter, int nAngle)
{
    int level = nIter;
    int i, j, k;
    ofstream myout;
    double *A;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }

// cout << "nIter = " << nIter << endl;
// cout << "nAngle = " << nAngle << endl;

A = (double *) malloc(nAngle * sizeof (double));

myout.open("angle.dat");

for (i=0; i<level; ++i) {
    nIter = i;
    nAngle = 1 << nIter;

    for (j=0; j<nAngle; ++j) {
        A[j] = compute_angle(j, nIter);

        // cout << "A[" << j << "] = " << A[j] << endl;
        myout << A[j]*180/pi << " " << 0.5*i << " 0.0 0.5" << endl;
    }
}

myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "plot 'angle.dat' using 1:2:3:4 ";
myout << "with vectors head filled lt 2" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

```

```

system("gnuplot command.gp");

//-----
// Accumulated Angle Tree
//-----

myout.open("angle.dat");

for (i=0; i<level; ++i) {

    for (k=0; k<=i; k++) {
        nIter = k;
        nAngle = 1 << nIter;

        for (j=0; j<nAngle; ++j) {
            A[j] = compute_angle(j, nIter);

            //cout << "A[" << j << "] = " << A[j] << endl;
            myout << A[j]*180/pi << " " << 0.5*i << " 0.0 0.5" << endl;
        }
    }
}

myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "plot 'angle.dat' using 1:2:3:4 ";
myout << "with vectors head filled lt 2" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

free (A);
return;
}

//-----
// Class Angles' Member Functions
//-----

Angles::Angles() : A(NULL), nIter(3), nAngle(8)
{
    Leaf = 1;

    cout << "A is not initialized " << endl;
    cout << "nIter = " << nIter << endl;
    cout << "nAngle = " << nAngle << endl;
}

Angles::Angles(double *A, int nIter, int nAngle) :
    A(A), nIter(nIter), nAngle(nAngle)
{
    if (nAngle == (1 << nIter)) {
        Leaf = 1;
        cout << "A LeafAngles Object is created" << endl;
    } else {
        Leaf = 0;
        cout << "An AllAngles Object is created" << endl;
    }
}

```

```

cout << "nIter = " << nIter << endl;
cout << "nAngle = " << nAngle << endl;
}

void Angles::setNIter(int nIter)
{
    nIter = nIter;
}

void Angles::setNAngle(int nAngle)
{
    nAngle = nAngle;
}

int Angles::getNIter()
{
    return nIter;
}

int Angles::getNAngle()
{
    return nAngle;
}

//-----
//      Plot angle vectors on the unit circle
//-----
void Angles::plot_unit_circle_angle ()
{
    int i;
    ofstream myout;

    cout << "* plot_unit_circle_angle ... ";
    if (Leaf) cout << "(LeafAngles)" << endl;
    else cout << "(AllAngles)" << endl;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }

    // writing angle data on a unit circle
    myout.open("angle.dat");
    for (i=0; i<nAngle; i++) {
        myout << "0.0 0.0 " << cos(A[i]) << " " << sin(A[i]) << " " << endl;
    }
    myout.close();

    // writing gnuplot commands
    myout.open("command.gp");
    myout << "set size square" << endl;
    myout << "set xrange [-1:+1]" << endl;
    myout << "set yrange [-1:+1]" << endl;
    myout << "set object 1 circle at 0, 0 radius 1" << endl;
    myout << "plot 'angle.dat' using 1:2:3:4 ";
    myout << "with vectors head filled lt 2" << endl;
    myout << "pause mouse keypress" << endl;
    myout.close();

    system("gnuplot command.gp");

    return;
}

```

```
}
```

```
-----  
//      Plot angle vectors on the line  
-----  
void Angles::plot_line_angle ()  
{  
  
    ofstream myout;  
  
    cout << "* plot_line_angle ... ";  
    if (Leaf) cout << "(LeafAngles)" << endl;  
    else cout << "(AllAngles)" << endl;  
  
    if (nIter > 10) {  
        cout << "nIter = " << nIter << " is too large to plot! " << endl;  
        return;  
    }  
  
    // cout << "nIter = " << nIter << endl;  
    // cout << "nAngle = " << nAngle << endl;  
  
    myout.open("angle.dat");  
  
    for (int i=0; i<nAngle; ++i) {  
        // cout << "A[" << i << "] = " << A[i] << endl;  
        myout << A[i] << " 0.0 0.0 0.5" << endl;  
    }  
  
    myout.close();  
  
    // writing gnuplot commands  
    myout.open("command.gp");  
    myout << "set yrange [0:+2]" << endl;  
    myout << "plot 'angle.dat' using 1:2:3:4 ";  
    myout << "with vectors head filled lt 2" << endl;  
    myout << "pause mouse keypress" << endl;  
    myout.close();  
  
    system("gnuplot command.gp");  
  
    return;  
}  
  
-----  
//      plot residual errors  
-----  
void Angles::plot_residual_errors ()  
{  
  
    int i;  
    double x, y, z;  
    ofstream myout;  
  
    cout << "* plot_residual_errors ... ";  
    if (Leaf) cout << "(LeafAngles)" << endl;  
    else cout << "(AllAngles)" << endl;  
  
    if (nIter > 10) {  
        cout << "nIter = " << nIter << " is too large to plot! " << endl;  
        return;  
    }  
  
    // writing residue errors
```

```

myout.open("angle.dat");

for (i=0; i<nAngle; i++) {
    x = 1 / K;
    y = 0.0;
    z = A[i];

    cordic(&x, &y, &z, nIter);

    // cout << "A[" << i << "] = ";
    // cout << fixed << right << setw(10) << setprecision(7) << A[i];
    // cout << " z= ";
    // cout << fixed << right << setw(10) << setprecision(7) << z << endl;

    myout << fixed << right << setw(10) << i;
    myout << fixed << right << setw(12) << setprecision(7) << A[i];
    myout << fixed << right << setw(12) << setprecision(7) << z << endl;
}

myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set autoscale y" << endl;
myout << "plot 'angle.dat' using 1:3 with linespoints " << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

return;
}

-----
// Calculate leaf node angle statistics
-----
void Angles::calc_statistics ()
{
    vector <double> B, D;
    vector <double> ::iterator first, last;
    double mean, std;

    cout << "* calc_statistics... ";
    if (Leaf) cout << "(LeafAngles)" << endl;
    else cout << "(AllAngles)" << endl;

    for (int i=0; i < nAngle; ++i)
        B.push_back(A[i]);

    sort(B.begin(), B.end());

    for (int i=0; i < nAngle; ++i) {
        // cout << "B[" << i << "] = " << setw(12) << setprecision(8) << B[i] << endl;
    }

    for (int i=0; i < B.size()-1; ++i)
        D.push_back(B[i+1]- B[i]);

    mean = 0.0;
    for (int i=0; i < D.size(); ++i)
        mean += D[i];
    mean /= D.size();
}

```

```

std = 0.0;
for (int i=0; i < D.size(); ++i)
    std += ((D[i]-mean) * (D[i]-mean));
std /= D.size();
std = sqrt(std);

cout << "delta mean = " << mean << endl;
cout << "delta std = " << std << endl;

return;
}

*****  

for (i=0; i<20; i+=4) {
    for (j=0; j<4; ++j) {
        r = atan( 1. / (1 << (i+j)) ) / atan( 1. / (1 << i) ) * 100;
        cout << "index = " << i+j << " --> r = " << r << endl;
    }
}

return 0;
}
*****
```

```

:::::::::::  

Angles_tb.cpp  

:::::::::::  

# include <cstdlib>  

# include <cmath>  

# include <iostream>  

# include <iomanip>  

# include <fstream>

using namespace std;

# include "cordic.hpp"
# include "Angles.hpp"

//-----  

// Purpose:  

//  

//      Explore Angles Space using Class Angles  

//  

// Discussion:  

//  

// Licensing:  

//  

//      This code is distributed under the GNU LGPL license.  

//  

// Modified:  

//  

//      2012.04.27  

//  

// Author:  

//  

//      Young Won Lim  

//  

// Parameters:
```

```

// -----
// -----
int main (int argc, char * argv[])
{
    int      nIter = 3;
    int      nAngle = 1 << nIter;
    int      i, j, k;
    int      level, leaves;
    double  *A, *All;

    if (argc > 1 ) {
        nIter = atoi(argv[1]);
        nAngle = 1 << nIter;
    }

    // cout << "nIter = " << nIter << endl;
    // cout << "nAngle = " << nAngle << endl;

    A = (double *) malloc ((1<<nIter) * sizeof (double));
    All = (double *) malloc (2* (1<<nIter) * sizeof (double));

    for (j=0; j<nAngle; ++j) {
        A[j] = compute_angle(j, nIter);
    }

    for (i=0, k=0; i<=nIter; ++i) {
        level = i;
        leaves = 1 << level;

        // cout << "level = " << level << "leaves = " << leaves << endl;

        for (j=0; j<leaves; ++j) {
            All[j+k] = compute_angle(j, level);
            // cout << "All[" << j+k << "] = " << All[j+k] << endl;
        }

        k += leaves;
    }

    Angles LeafAngles(A, nIter, nAngle);
    Angles AllAngles(All, nIter, 2*nAngle-1);

    // -----
    // Plot angle vectors on the unit circle
    // -----
    LeafAngles.plot_unit_circle_angle();
    AllAngles.plot_unit_circle_angle();

    // -----
    // Plot angle on the line axis
    // -----
    LeafAngles.plot_line_angle();
    AllAngles.plot_line_angle();

    // -----
    // Plot residue errors at the leaf node angles
    // -----
    LeafAngles.plot_residual_errors();
}

```

```
AllAngles.plot_residual_errors();

// -----
//   Find Angles Statistics
// -----
LeafAngles.calc_statistics();
AllAngles.calc_statistics();

// -----
//   Plot residue errors at the leaf node angles
// -----
draw_angle_tree (nIter, nAngle);

return 0;
}
```