

```

:cordic_gmp.c
:
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <time.h>

#include "cordic.h"

#include <gmp.h>

/*****/

void cordic ( double *x, double *y, double *z, int n )

/*****/
/*
CORDIC returns the sine and cosine using the CORDIC method.
GMP (GNU Multiple Precision Library) is used

Licensing:

    This code is distributed under the GNU LGPL license.

Modified:

    2013.01.12

Author:

    Based on MATLAB code in a Wikipedia article.

    Modifications by John Burkardt

    Further modified by Young W. Lim

Parameters:

    Input:
        *x: x coord of an init vector
        *y: y coord of an init vector
        *z: angle (-90 <= angle <= +90)
        n: number of iteration
            A value of 10 is low. Good accuracy is achieved
            with 20 or more iterations.

    Output:
        *xo: x coord of a final vector
        *yo: y coord of a final vector
        *zo: angle residue

Local Parameters:

    Local, real ANGLES(60) = arctan ( (1/2)^(0:59) );

    Local, real KPROD(33), KPROD(j) = product ( 0 <= i <= j ) K(i),
    K(i) = 1 / sqrt ( 1 + (1/2)^(2i) ).
*/
{
#define ANGLES_LENGTH 60
#define KPROD_LENGTH 33

const int precision = 512;

mpf_t angle;

```

```
mpf_t angles[ANGLES_LENGTH];
mpf_t kprod[KPROD_LENGTH];

int j;

mpf_t factor;

mpf_t pi;
mpf_t poweroftwo;
mpf_t sigma;
mpf_t sign_factor;
mpf_t theta;

mpf_t xn, yn;
mpf_t xt, yt;
mpf_t tt;

mpf_init2(angle, precision);
for (j=0; j<ANGLES_LENGTH; ++j)
    mpf_init2( angles[j], precision);
for (j=0; j<KPROD_LENGTH; ++j)
    mpf_init2( kprod[j], precision);

mpf_init2(factor, precision);
mpf_init2(pi, precision);
mpf_init2(poweroftwo, precision);
mpf_init2(sigma, precision);
mpf_init2(sign_factor, precision);
mpf_init2(theta, precision);
mpf_init2(xn, precision);
mpf_init2(yn, precision);
mpf_init2(xt, precision);
mpf_init2(yt, precision);
mpf_init2(tt, precision);

mpf_set_d(pi, 3.141592653589793);

mpf_set_str(angles[ 0], "7.8539816339744830962e-01", 10);
mpf_set_str(angles[ 1], "4.6364760900080611621e-01", 10);
mpf_set_str(angles[ 2], "2.4497866312686415417e-01", 10);
mpf_set_str(angles[ 3], "1.2435499454676143503e-01", 10);
mpf_set_str(angles[ 4], "6.2418809995957348474e-02", 10);
mpf_set_str(angles[ 5], "3.1239833430268276254e-02", 10);
mpf_set_str(angles[ 6], "1.5623728620476830803e-02", 10);
mpf_set_str(angles[ 7], "7.8123410601011112965e-03", 10);
mpf_set_str(angles[ 8], "3.9062301319669718276e-03", 10);
mpf_set_str(angles[ 9], "1.9531225164788186851e-03", 10);
mpf_set_str(angles[10], "9.7656218955931943040e-04", 10);
mpf_set_str(angles[11], "4.8828121119489827547e-04", 10);
mpf_set_str(angles[12], "2.4414062014936176402e-04", 10);
mpf_set_str(angles[13], "1.2207031189367020424e-04", 10);
mpf_set_str(angles[14], "6.1035156174208775022e-05", 10);
mpf_set_str(angles[15], "3.0517578115526096862e-05", 10);
mpf_set_str(angles[16], "1.5258789061315762107e-05", 10);
mpf_set_str(angles[17], "7.6293945311019702634e-06", 10);
mpf_set_str(angles[18], "3.8146972656064962829e-06", 10);
mpf_set_str(angles[19], "1.9073486328101870354e-06", 10);
mpf_set_str(angles[20], "9.5367431640596087942e-07", 10);
mpf_set_str(angles[21], "4.7683715820308885993e-07", 10);
mpf_set_str(angles[22], "2.3841857910155798249e-07", 10);
mpf_set_str(angles[23], "1.1920928955078068531e-07", 10);
mpf_set_str(angles[24], "5.9604644775390554414e-08", 10);
mpf_set_str(angles[25], "2.9802322387695303677e-08", 10);
mpf_set_str(angles[26], "1.4901161193847655147e-08", 10);
```

```
mpf_set_str(angles[27], "7.4505805969238279871e-09", 10);
mpf_set_str(angles[28], "3.7252902984619140453e-09", 10);
mpf_set_str(angles[29], "1.8626451492309570291e-09", 10);
mpf_set_str(angles[30], "9.3132257461547851536e-10", 10);
mpf_set_str(angles[31], "4.6566128730773925778e-10", 10);
mpf_set_str(angles[32], "2.3283064365386962890e-10", 10);
mpf_set_str(angles[33], "1.1641532182693481445e-10", 10);
mpf_set_str(angles[34], "5.8207660913467407226e-11", 10);
mpf_set_str(angles[35], "2.9103830456733703613e-11", 10);
mpf_set_str(angles[36], "1.4551915228366851807e-11", 10);
mpf_set_str(angles[37], "7.2759576141834259033e-12", 10);
mpf_set_str(angles[38], "3.6379788070917129517e-12", 10);
mpf_set_str(angles[39], "1.8189894035458564758e-12", 10);
mpf_set_str(angles[40], "9.0949470177292823792e-13", 10);
mpf_set_str(angles[41], "4.5474735088646411896e-13", 10);
mpf_set_str(angles[42], "2.2737367544323205948e-13", 10);
mpf_set_str(angles[43], "1.1368683772161602974e-13", 10);
mpf_set_str(angles[44], "5.6843418860808014870e-14", 10);
mpf_set_str(angles[45], "2.8421709430404007435e-14", 10);
mpf_set_str(angles[46], "1.4210854715202003717e-14", 10);
mpf_set_str(angles[47], "7.1054273576010018587e-15", 10);
mpf_set_str(angles[48], "3.5527136788005009294e-15", 10);
mpf_set_str(angles[49], "1.7763568394002504647e-15", 10);
mpf_set_str(angles[50], "8.8817841970012523234e-16", 10);
mpf_set_str(angles[51], "4.4408920985006261617e-16", 10);
mpf_set_str(angles[52], "2.2204460492503130808e-16", 10);
mpf_set_str(angles[53], "1.1102230246251565404e-16", 10);
mpf_set_str(angles[54], "5.5511151231257827021e-17", 10);
mpf_set_str(angles[55], "2.7755575615628913511e-17", 10);
mpf_set_str(angles[56], "1.3877787807814456755e-17", 10);
mpf_set_str(angles[57], "6.9388939039072283776e-18", 10);
mpf_set_str(angles[58], "3.4694469519536141888e-18", 10);
mpf_set_str(angles[59], "1.7347234759768070944e-18", 10);
```

```
mpf_set_str(kprod[ 0], "0.70710678118654752440", 10);
mpf_set_str(kprod[ 1], "0.63245553203367586640", 10);
mpf_set_str(kprod[ 2], "0.61357199107789634961", 10);
mpf_set_str(kprod[ 3], "0.60883391251775242102", 10);
mpf_set_str(kprod[ 4], "0.60764825625616820093", 10);
mpf_set_str(kprod[ 5], "0.60735177014129595905", 10);
mpf_set_str(kprod[ 6], "0.60727764409352599905", 10);
mpf_set_str(kprod[ 7], "0.60725911229889273006", 10);
mpf_set_str(kprod[ 8], "0.60725447933256232972", 10);
mpf_set_str(kprod[ 9], "0.60725332108987516334", 10);
mpf_set_str(kprod[10], "0.60725303152913433540", 10);
mpf_set_str(kprod[11], "0.60725295913894481363", 10);
mpf_set_str(kprod[12], "0.60725294104139716351", 10);
mpf_set_str(kprod[13], "0.60725293651701023413", 10);
mpf_set_str(kprod[14], "0.60725293538591350073", 10);
mpf_set_str(kprod[15], "0.60725293510313931731", 10);
mpf_set_str(kprod[16], "0.60725293503244577146", 10);
mpf_set_str(kprod[17], "0.60725293501477238499", 10);
mpf_set_str(kprod[18], "0.60725293501035403837", 10);
mpf_set_str(kprod[19], "0.60725293500924945172", 10);
mpf_set_str(kprod[20], "0.60725293500897330506", 10);
mpf_set_str(kprod[21], "0.60725293500890426839", 10);
mpf_set_str(kprod[22], "0.60725293500888700922", 10);
mpf_set_str(kprod[23], "0.60725293500888269443", 10);
mpf_set_str(kprod[24], "0.60725293500888161574", 10);
mpf_set_str(kprod[25], "0.60725293500888134606", 10);
mpf_set_str(kprod[26], "0.60725293500888127864", 10);
mpf_set_str(kprod[27], "0.60725293500888126179", 10);
mpf_set_str(kprod[28], "0.60725293500888125757", 10);
mpf_set_str(kprod[29], "0.60725293500888125652", 10);
mpf_set_str(kprod[30], "0.60725293500888125626", 10);
mpf_set_str(kprod[31], "0.60725293500888125619", 10);
```

```

mpf_set_str(kprod[32], "0.60725293500888125617", 10);

// Initialize loop variables:
mpf_set_d(theta, *z);

mpf_set_d(xn, *x);
mpf_set_d(yn, *y);

mpf_set_d(poweroftwo, 1.0);
mpf_set(angle, angles[0]);

// Iterations
for ( j = 1; j <= n; j++ )
{
  if ( mpf_cmp_d(theta, 0.0) < 0 )
  {
    mpf_set_d(sigma, -1.0);
  }
  else
  {
    mpf_set_d(sigma, 1.0);
  }

  mpf_mul(factor, sigma, poweroftwo);

  mpf_mul(xt, factor, yn);
  mpf_sub(xt, xn, xt);

  mpf_mul(yt, factor, xn);
  mpf_add(yt, yt, yn);

  *x = mpf_get_d(xt);
  *y = mpf_get_d(yt);

  mpf_set(xn, xt);
  mpf_set(yn, yt);

  // Update the remaining angle.
  mpf_mul(tt, sigma, angle);
  mpf_sub(theta, theta, tt);

  mpf_div_ui(poweroftwo, poweroftwo, 2);

  // Update the angle from table, or eventually by just dividing by two.
  if ( ANGLES_LENGTH < j + 1 )
  {
    mpf_div_ui(angle, angle, 2);
  }
  else
  {
    mpf_set(angle, angles[j]);
  }

  *z = mpf_get_d(theta);
}

return;
# undef ANGLES_LENGTH
# undef KPROD_LENGTH
}

```

```

:::

```

```
cordic_tb.c
:::::::::::::
# include <stdlib.h>
# include <stdio.h>
# include <math.h>

# include "cordic.h"

/*****/

int main ( )

/*****/
/*

CORDIC test

Licensing:

    This code is distributed under the GNU LGPL license.

Modified:

    2012.04.17

Author:

    Modifications by John Burkardt

    Further modified by Young W. Lim

Parameters:

*/
{
    double pi = 3.141592653589793;
    double K = 1.646760258121;
    int nIter = 10;

    double x, y, z;

    FILE * fp;
    int i;
    int nsamples = 1000;
    double cosz, sinz;

    //-----
    // printf ("\nGrinding on [K, 0, 0]\n");
    // Circular (X0C, 0L, 0L);
    //-----
    x = 1 / K;
    y = 0.0;
    z = 0.0;
    printf("-----\n");
    printf("xi=%f yi=%f zi=%f\n", x, y, z);

    cordic(&x, &y, &z, nIter);

    printf("xo=%f yo=%f zo=%f\n", x, y, z);

    //-----
    // printf ("\nGrinding on [K, 0, pi/6] -> [0.86602540, 0.50000000, 0]\n");
    // Circular (X0C, 0L, HalfPi / 3L);
```

```

//-----
x = 1 / K;
y = 0.0;
z = pi / 6.0;
printf("-----\n");
printf("xi=%f yi=%f zi=%f\n", x, y, z);

cordic(&x, &y, &z, nIter);

printf("xo=%f yo=%f zo=%f\n", x, y, z);

//-----
// printf ("\nGrinding on [K, 0, pi/4] -> [0.70710678, 0.70710678, 0]\n");
// Circular (X0C, 0L, HalfPi / 2L);
//-----
x = 1 / K;
y = 0.0;
z = pi / 4.0;
printf("-----\n");
printf("xi=%f yi=%f zi=%f\n", x, y, z);

cordic(&x, &y, &z, nIter);

printf("xo=%f yo=%f zo=%f\n", x, y, z);

//-----
// printf ("\nGrinding on [K, 0, pi/3] -> [0.50000000, 0.86602540, 0]\n");
// Circular (X0C, 0L, 2L * (HalfPi / 3L));
//-----
x = 1 / K;
y = 0.0;
z = pi / 3.0;
printf("-----\n");
printf("xi=%f yi=%f zi=%f\n", x, y, z);

cordic(&x, &y, &z, nIter);

printf("xo=%lf yo=%lf zo=%lf\n", x, y, z);

//-----
// x = 1/K, y = 0.0, z = [0, pi/2], step = pi/200
//-----

fp = fopen("test.dat", "w+");
for (i=0; i<nsamples; ++i) {
    x = 1 / K;
    y = 0.0;
    z = (pi / (2*nsamples)) * i;

    cosz = cos(z);
    sinz = sin(z);
    fprintf(fp, "%f", z);
    fprintf(fp, " %f %f ", cosz, sinz);

    cordic(&x, &y, &z, nIter);

    fprintf(fp, " %f %f ", x, y);
    // fprintf(fp, " %f %f \n", (x-cosz)/cosz, (y-sinz)/sinz);
    fprintf(fp, " %f %f \n", (x-cosz)*500, (y-sinz)*500);
}
fclose(fp);

```

```
    return 0;  
}
```