

```

::::::::::
Angles.hpp
::::::::::
# include <iostream>
# include <iomanip>
# include <fstream>
// # include <cstdlib>
// # include <cmath>
# include <vector>
# include <algorithm>

using namespace std;

-----  

// Purpose:  

// Class Angles Interface Files  

// Discussion:  

//  

// Licensing:  

// This code is distributed under the GNU LGPL license.  

// Modified:  

// 2012.05.11  

// Author:  

// Young Won Lim  

// Parameters:  

//-----  

//  

// Compute Angles based on the binary tree  

// idx - index for leaf nodes of the binary tree  

// nIter - no of iteration (corresponds to the level of the tree)  

//-----  

double compute_angle ( int idx, int nIter );  

-----  

// Draw Binary Angle Tree and Cumulative Binary Angle Tree  

//-----  

void draw_angle_tree (int nIter, int nAngle);  

  

class Angles  

{  

public:  

    Angles();  

    Angles(double *A, int nIter, int nAngle);  

  

    void      setA(double *A);  

    void      setNIter(int nIter);  

    void      setNAngle(int nAngle);  

    void      setThreshold(double threshold);  

  

    int       getNIter();  

    int       getNAngle();  

    double    getThreshold();  

  

//-----  

// Plot angle vectors on a unit circle

```

```

//-
void plot_circle_angle ();

//-
//  Plot angle vectors on a linear scal
//-
void plot_line_angle ();

//-
//  Find Angles Statistics --> member data
//-
void calc_statistics ();

//-
//  Delta Distribution Plot and Angle-Delta Plot
//-
void plot_statistics ();

//-
//  plot residual errors
//  Residuals-Angle Plot and Residuals-Index Plot
//-
void plot_residual_errors ();

void calc_uscale_statistics (double, double);
void plot_uscale_statistics ();
void plot_uscale_residual_errors ();
void plot_uscale_residual_errors (double, double);

private:

double *A;
int nIter;
int nAngle;
int Leaf;

double avg_delta;
double std_delta;
double min_delta;
double max_delta;
double min_angle;
double max_angle;

double ssr;      // sum of the squares of the residuals
double mse;      // mean squared error
double rms;      // root mean square error
double max_err; // maximum of squared errors

double threshold;

};

::::::::::::::::::
Angles.cpp
::::::::::::::::::
# include <iostream>
# include <iomanip>
# include <cstdlib>
# include <cmath>
# include <fstream>
# include <vector>
# include <algorithm>

using namespace std;

# include "Angles.hpp"

```

```

# include "cordic.hpp"

double pi = 3.141592653589793;
double K = 1.646760258121;

//-----
// Purpose:
//
//   Class Angles Implementation Files
//
// Discussion:
//
//
// Licensing:
//
//   This code is distributed under the GNU LGPL license.
//
// Modified:
//
//   2012.05.11
//
// Author:
//
//   Young Won Lim
//
// Parameters:
//
//-----

//-----
// Compute Angles based on the binary tree
//   idx - index for leaf nodes of the binary tree
//   nIter - no of iteration (corresponds to the level of the tree)
//-----
double compute_angle ( int idx, int nIter )
{
    double angle = 0.0;
    char    s[32];
    int     i, j;

    // i - bit position starting from lsb
    // j = 2^i
    // (idx & (1 << i)) - i-th bit of idx
    // if each bit is '1', add atan(1/2^i)
    // if each bit is '0', sub atan(1/2^i)
    // s[32] contains the binary representation of idx

    for (i=0; i<nIter; i++) {

        j = 1 << i;
        if (idx & (1 << i)) {
            angle += atan( 1. / j );
            s[nIter-i-1] = '1';
        } else {
            angle -= atan( 1. / j );
            s[nIter-i-1] = '0';
        }

        // cout << "i=" << i << " j=" << j << " 1/j=" << 1./j
        //           << " atan(1/j)=" << atan(1./j)*180/3.1416 << endl;
    }

    s[nIter] = '\0';
}

```

```

// cout << nIter << " " << idx << " " << s
//      << " ---> " << angle*180/3.1416 << endl;
return angle;
}

//-----
// Draw Binary Angle Tree and Cumulative Binary Angle Tree
//-----
void draw_angle_tree (int nIter, int nAngle)
{
    int level = nIter;
    int i, j, k;
    ofstream myout;
    double *A;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }

    // cout << "nIter = " << nIter << endl;
    // cout << "nAngle = " << nAngle << endl;

    A = (double *) malloc(nAngle * sizeof (double));

    //-----
    // Binary Angle Tree
    //-----

    myout.open("angle.dat");

    for (i=0; i<level; ++i) {
        nIter = i;
        nAngle = 1 << nIter;

        for (j=0; j<nAngle; ++j) {
            A[j] = compute_angle(j, nIter);

            // cout << "A[" << j << "] = " << A[j] << endl;
            myout << A[j]*180/pi << " " << i << " 0.0 1.0" << endl;
        }
    }

    myout.close();

    // writing gnuplot commands
    myout.open("command.gp");
    myout << "set terminal emf" << endl;
    myout << "set output 'eg01.bin_ang_tree.emf'" << endl;
    myout << "set title \"Binary Angle Tree\" " << endl;
    myout << "set xlabel \"Angles in degree\" " << endl;
    myout << "set ylabel \"Levels \" " << endl;
    myout << "set format x \"%.\0f\" " << endl;
    myout << "set format y \"%.\0f\" " << endl;
    myout << "plot 'angle.dat' using 1:2:3:4 ";
    myout << "with vectors head filled lt 3" << endl;
    myout << "pause mouse keypress" << endl;
    myout.close();

    system("gnuplot command.gp");
}

```

```

// Cumulative Angle Tree
//-----

myout.open("angle.dat");

for (i=0; i<level; ++i) {

    for (k=0; k<=i; k++) {
        nIter = k;
        nAngle = 1 << nIter;

        for (j=0; j<nAngle; ++j) {
            A[j] = compute_angle(j, nIter);

            //cout << "A[" << j << "] = " << A[j] << endl;
            myout << A[j]*180/pi << " " << i << " 0.0 1.0" << endl;
        }
    }

}

myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set terminal emf" << endl;
myout << "set output 'eg02.cumul_ang_tree.emf'" << endl;
myout << "set title \"Cumulative Binary Angle Tree\" " << endl;
myout << "set xlabel \"Angles in degree\" " << endl;
myout << "set ylabel \"Levels \" " << endl;
myout << "set format x \"%.\0f\" " << endl;
myout << "set format y \"%.\0f\" " << endl;
myout << "plot 'angle.dat' using 1:2:3:4 ";
myout << "with vectors head filled lt 4" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

free (A);
return;
}

//-----
// Class Angles' Member Functions
//-----

Angles::Angles() : A(NULL), nIter(3), nAngle(8)
{
    Leaf = 1;

    cout << "A is not initialized " << endl;
    cout << "nIter = " << nIter << endl;
    cout << "nAngle = " << nAngle << endl;

    avg_delta = std_delta = min_angle = max_angle = 0.0;
    ssr = mse = rms = max_err = 0.0;
}

Angles::Angles(double *A, int nIter, int nAngle) :
    A(A), nIter(nIter), nAngle(nAngle)
{
    if (nAngle == (1 << nIter)) {
        Leaf = 1;
        cout << "A LeafAngles Object is created " ;
}

```

```

} else {
    Leaf = 0;
    cout << "An AllAngles Object is created " ;
}

cout << "(nIter = " << nIter << ", ";
cout << "nAngle = " << nAngle << ")" << endl;

avg_delta = std_delta = min_angle = max_angle = 0.0;
ssr = mse = rms = max_err = 0.0;

threshold = 0.0;

}

void Angles::setNIter(int nIter)
{
    nIter = nIter;
}

void Angles::setNAngle(int nAngle)
{
    nAngle = nAngle;
}

void Angles::setThreshold(double threshold)
{
    threshold = threshold;
}

int Angles::getNIter()
{
    return nIter;
}

int Angles::getNAngle()
{
    return nAngle;
}

double Angles::getThreshold()
{
    return threshold;
}

//-----
//      Plot angle vectors on the unit circle
//-----
void Angles::plot_circle_angle ()
{
    int i;
    ofstream myout;

    cout << "* plot_circle_angle ... " ;
    if (Leaf) cout << "(LeafAngles)" << endl;
    else cout << "(AllAngles)" << endl;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }

    // writing angle data on a unit circle
}

```

```

myout.open("angle.dat");
for (i=0; i<nAngle; i++) {
    myout << "0.0 0.0 " << cos(A[i]) << " " << sin(A[i]) << " " << endl;
}
myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set terminal emf" << endl;
if (Leaf) {
    myout << "set output 'eg03.ang_circle_leaf.emf'" << endl;
    myout << "set title \"Leaf Angles on a unit circle \" " << endl;
} else {
    myout << "set output 'eg03.ang_circle_all.emf'" << endl;
    myout << "set title \"All Angles on a unit circle \" " << endl;
}
myout << "set xlabel \"x\" " << endl;
myout << "set ylabel \"y\" " << endl;
myout << "set size square" << endl;
myout << "set xrange [-1:+1]" << endl;
myout << "set yrange [-1:+1]" << endl;
myout << "set object 1 circle at 0, 0 radius 1" << endl;
myout << "plot 'angle.dat' using 1:2:3:4 ";
myout << "with vectors head filled lt 3" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

return;
}

//-----
//      Plot angle vectors on a linear scale
//-----
void Angles::plot_line_angle ()
{
    ofstream myout;

    cout << "* plot_line_angle ... ";
    if (Leaf) cout << "(LeafAngles)" << endl;
    else cout << "(AllAngles)" << endl;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }

    // cout << "nIter = " << nIter << endl;
    // cout << "nAngle = " << nAngle << endl;

    myout.open("angle.dat");

    for (int i=0; i<nAngle; ++i) {
        // cout << "A[" << i << "] = " << A[i] << endl;
        myout << A[i] << " 0.0 0.0 1.0" << endl;
    }

    myout.close();

    // writing gnuplot commands
    myout.open("command.gp");
    myout << "set terminal emf" << endl;
    if (Leaf) {

```

```

myout << "set title \"Leaf Angles on a linear scale\" " << endl;
myout << "set output 'eg04.ang_line_leaf.emf'" << endl;
} else {
    myout << "set title \"All Angles on a linear scale\" " << endl;
    myout << "set output 'eg04.ang_line_all.emf'" << endl;
}
myout << "set xlabel \"angles in radian\" " << endl;
myout << "set ylabel \"\\" " << endl;
myout << "set yrange [0:+2]" << endl;
myout << "plot 'angle.dat' using 1:2:3:4 ";
myout << "with vectors head filled lt 3" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

return;
}

//-----
// Find Angles Statistics --> member data
//-----
void Angles::calc_statistics ()
{
    vector <double> B, D;
    vector <double> ::iterator first, last;
    double mean, std;
    ofstream myout;

    cout << "* calc_statistics... ";
    if (Leaf) cout << "(LeafAngles)" << " nAngle = " << nAngle << endl;
    else cout << "(AllAngles)" << " nAngle = " << nAngle << endl;

    for (int i=0; i < nAngle; ++i) {
        // cout << "A[" << i << "]=" << setw(12) << setprecision(8) << A[i] << endl;
        // cout << "B[" << i << "]=" << setw(12) << setprecision(8) << B[i] << endl;
    }

    // B : sorted angles array
    for (int i=0; i < nAngle; ++i)
        B.push_back(A[i]);

    sort(B.begin(), B.end());

    // D : difference angle array
    for (int i=0; i < nAngle-1; ++i)
        D.push_back(B[i+1]- B[i]);

    sort(D.begin(), D.end());

    mean = 0.0;
    for (int i=0; i < D.size(); ++i)
        mean += D[i];
    mean /= D.size();

    std = 0.0;
    for (int i=0; i < D.size(); ++i)
        std += ((D[i]-mean) * (D[i]-mean));
    std /= D.size();
    std = sqrt(std);
}

```

```

min_angle = B[0];
max_angle = B[B.size()-1];
min_delta = D[0];
max_delta = D[D.size()-1];
avg_delta = mean;
std_delta = std;

double udelta = (B[B.size()-1] - B[0]) / nAngle; // computed unifrom delta

cout << " min angle      = " << min_angle << endl;
cout << " max angle      = " << max_angle << endl;
cout << " min delta      = " << min_delta << endl;
cout << " max delta      = " << max_delta << endl;
cout << " avg delta      = " << avg_delta << endl;
cout << " std delta      = " << std_delta << endl;
cout << " uniform delta   = " << udelta ;
cout << " = (max-min) / nAngle " << endl;

return;
}

```

```

//-----
// Plot Delta Distribution and Angle-Delta
//-----
void Angles::plot_statistics ()
{
    vector <double> B, D;
    vector <double> ::iterator first, last;
    double mean, std;
    ofstream myout;

    cout << "* calc_statistics... ";
    if (Leaf) cout << "(LeafAngles)" << " nAngle = " << nAngle << endl;
    else cout << "(AllAngles)" << " nAngle = " << nAngle << endl;

    for (int i=0; i < nAngle; ++i) {
        // cout << "A[" << i << "]=" << setw(12) << setprecision(8) << A[i] << endl;
        // cout << "B[" << i << "]=" << setw(12) << setprecision(8) << B[i] << endl;
    }

    // B : sorted angles array
    for (int i=0; i < nAngle; ++i)
        B.push_back(A[i]);

    sort(B.begin(), B.end());

    // D : difference angle array
    for (int i=0; i < nAngle-1; ++i)
        D.push_back(B[i+1]- B[i]);

    sort(D.begin(), D.end());

    double udelta = (B[B.size()-1] - B[0]) / nAngle; // computed unifrom delta

    // write histogram data from delta array
    myout.open("angle.dat");
    double pb ;
    for (int i=0, j, k; i<nAngle-2; i++) {
        j = i; k = 1;
        while ((D[j+1] - D[j])/D[j] < 0.01) {
            k++;

```

```

        j++;
    }
    pb = (double) k / D.size();
    myout << fixed << right << setw(12) << setprecision(7) << D[i] ;
    myout << " " << pb << endl;
    i = j;
}
myout.close();

cout << " + Delta Distribution Plot \n" ;

// writing gnuplot commands
myout.open("command.gp");
myout << "set terminal emf" << endl;
if (Leaf) {
    myout << "set output 'eg05.delta_dist_leaf.emf'" << endl;
    myout << "set title \"Delta Distribution of Leaf Angles\" " << endl;
} else {
    myout << "set output 'eg05.delta_dist_all.emf'" << endl;
    myout << "set title \"Delta Distribution of All Angles\" " << endl;
}
myout << "set xlabel \"Delta (Adjacent Angle Difference)\" " << endl;
myout << "set ylabel \"probability\" " << endl;
myout << "set yrange [0:+1]" << endl;

myout << "set arrow from " << avg_delta << ", 0";
myout << " to " << avg_delta << ", 0.7" << endl;
myout << "set label \"avg_delta\" at " << avg_delta;
myout << ", 0.7 right" << endl;

myout << "set arrow from " << udelta << ", 0";
myout << " to " << udelta << ", 0.5" << endl;
myout << "set label \"uniform delta\" at " << udelta;
myout << ", 0.5 right" << endl;

myout << "plot 'angle.dat' with linespoints" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

cout << " + Angle-Delta Plot \n" ;

// write angle-delta data
myout.open("angle.dat");
for (int i=0; i<B.size()-1; i++) {
    myout << B[i] << " " << B[i+1] - B[i] << endl;
}
myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set terminal emf" << endl;
if (Leaf) {
    myout << "set output 'eg06.angle_delta_leaf.emf'" << endl;
    myout << "set title \"Angle-Delta Plot of Leaf Angles\" " << endl;
} else {
    myout << "set output 'eg06.angle_delta_all.emf'" << endl;
    myout << "set title \"Angle-Delta Plot of All Angles\" " << endl;
}
myout << "set xlabel \"Angles in radian\" " << endl;
myout << "set ylabel \"Delta (Adj Angle Diff) \" " << endl;

myout << "set arrow from " << "-1.0, " << avg_delta;
myout << " to " << "+1.0, " << avg_delta << endl;

```

```

myout << "set label \"avg_delta \" at " << "+0.0, ";
myout << avg_delta << " left" << endl;

myout << "set arrow from " << "-1.0, " << udelta;
myout << " to " << "+1.0, " << udelta << endl;
myout << "set label \"uniform delta \" at " << "+1.0, ";
myout << udelta << " left" << endl;

myout << "set arrow from " << "-0.7853, " << min_delta;
myout << "0 to -0.7853, " << max_delta << endl;
myout << "set label \"-pi/4 \" at " << "-0.7853, " ;
myout << min_delta << " right " << endl;

myout << "set arrow from " << "+0.7853, " << min_delta;
myout << "0 to +0.7853, " << max_delta << endl;
myout << "set label "+pi/4 " at " << "+0.7853, " ;
myout << min_delta << " left " << endl;

myout << "plot 'angle.dat' with linespoints" << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

return;
}

```

```

//-----
// plot residual errors
// Residuals-Angle Plot and Residuals-Index Plot
//-----
void Angles::plot_residual_errors ()
{
    int i;
    double x, y, z;
    ofstream myout;

    cout << "* plot_residual_errors ... ";
    if (Leaf) cout << "(LeafAngles)" << endl;
    else cout << "(AllAngles)" << endl;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }

    // B : sorted angles array
    vector <double> B;
    vector <double> ::iterator first, last;

    for (int i=0; i < nAngle; ++i)
        B.push_back(A[i]);

    sort(B.begin(), B.end());

    // I=0 Use A[i] for Index-Residuals Plot
    // I=1 Use b[i] for Angle-Residuals Plot
    //...
    for (int I=0; I<2; I++) {
    //...

```

```

// writing residue errors
myout.open("angle.dat");

int nBreak =0;

// not member but local variables
double se, ssr, mse, rms, max_err;
se = ssr = mse = rms = max_err = 0.0;

if (I==0) cout << " + Index-Residuals Plot" << endl;
else cout << " + Angle-Residuals Plot" << endl;

for (i=0; i<nAngle; i++) {

    x = 1 / K;
    y = 0.0;
    if (I == 0) z = A[i];
    else z = B[i];

    cordic(&x, &y, &z, nIter, &nBreak, i, threshold);

    se = z * z;
    ssr += se;
    if (se > max_err) max_err = se;

    // cout << "A[" << i << "] = ";
    // cout << fixed << right << setw(10) << setprecision(7) << A[i];
    // cout << " z= ";
    // cout << fixed << right << setw(10) << setprecision(7) << z << endl;

    myout << fixed << right << setw(10) << i;
    myout << fixed << right << setw(12) << setprecision(7);
    if (I==0) myout << A[i];
    else myout << B[i];
    myout << fixed << right << setw(12) << setprecision(7) << z << endl;

}

mse = ssr / nAngle;
rms = sqrt(mse);

max_err = sqrt(max_err);

cout << " No of points = " << nAngle ;
cout << " (nBreak = " << nBreak << " : " ;
cout << 100. * nBreak / nAngle << " % )" << endl;

cout << " SSR: Sum of Squared Residuals      = " ;
cout << fixed << right << setw(12) << setprecision(7) << ssr << endl;
cout << " MSR: Mean Squared Residuals        = " ;
cout << fixed << right << setw(12) << setprecision(7) << mse << endl;
cout << " RMS: Root Mean Squared Residuals   = " ;
cout << fixed << right << setw(12) << setprecision(7) << rms << endl;
cout << " Max Residual Error                 = " ;
cout << fixed << right << setw(12) << setprecision(7) << max_err << endl;

myout.close();

// writing gnuplot commands
myout.open("command.gp");
if (I==0) {
    myout << "set terminal emf" << endl;
    if (Leaf) {
        myout << "set output 'eg07.index_res_leaf.emf'" << endl;
        myout << "set title \"Index-Residual Plot (Leaf) \" " << endl;
    } else {
}

```

```

myout << "set output 'eg07.index_res_all.emf'" << endl;
myout << "set title \"Index-Residual Plot (All) \" " << endl;
}
myout << "set xlabel \"Index\" " << endl;
myout << "set ylabel \"Residuals\" " << endl;
myout << "plot 'angle.dat' using 1:3 with linespoints " << endl;
} else {
myout << "set terminal emf" << endl;
if (Leaf) {
myout << "set output 'eg08.angle_res_leaf.emf'" << endl;
myout << "set title \"Angle-Residual Plot (Leaf) \" " << endl;
} else {
myout << "set output 'eg08.angle_res_all.emf'" << endl;
myout << "set title \"Angle-Residual Plot of (All)\" " << endl;
}
myout << "set xlabel \"Angles\" " << endl;
myout << "set ylabel \"Residuals\" " << endl;
myout << "plot 'angle.dat' using 2:3 with linespoints " << endl;
}
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

//-----
}

//-----

return;

}

//-----
// Calculate statistics on the uniform scale
//-----
// ssr      : sum of the squares of the residuals
// mse      : mean squared error
// rms      : root mean square error
// max_err : maximum of squared errors
//-----
// ssr      : sum of the squares of the residuals
// ang = min_angle + avg_delta * offFactor ;
// ang += (avg_delta / resFactor);
//-----
void Angles::calc_uscale_statistics (double resFactor, double offFactor)
{
    int n;
    double x, y, z;
    ofstream myout;

    cout << "* calc_uscale_statistics ... ";
    if (Leaf) cout << "(LeafAngles Resolution)" << endl;
    else cout << "(AllAngles Resolution)" << endl;

    // sr      : square error of a data point

    double ang = min_angle + avg_delta * offFactor ;
    double se = 0.0 ;
    int nBreak =0;
    n = 0;

    ssr = mse = rms = max_err = 0.0;
}

```

```

while (ang < max_angle) {
    x = 1 / K;
    y = 0.0;
    z = ang;

    cordic(&x, &y, &z, nIter, &nBreak, n, threshold);

    se = (z * z);
    ssr += se;
    if (se > max_err) max_err = se;

    // cout << fixed << right << setw(10) << setprecision(7) << A[i];
    // cout << fixed << right << setw(10) << setprecision(7) << z << endl;

    ang += (avg_delta / resFactor);
    n++;
}

mse = ssr / n;
rms = sqrt(mse);

max_err = sqrt(max_err);

cout << " Angles = (" ;
cout << min_angle << " : " << avg_delta << " : " << max_angle << ")" ;
cout << endl << " --> total " << n << " points" ;
cout << " (nBreak = " << nBreak << " : " ;
cout << 100. * nBreak / n << " % )" << endl;

cout << " SSR: Sum of Squared Residuals      = " ;
cout << fixed << right << setw(12) << setprecision(7) << ssr << endl;
cout << " MSR: Mean Squared Residuals        = " ;
cout << fixed << right << setw(12) << setprecision(7) << mse << endl;
cout << " RMS: Root Mean Squared Residuals   = " ;
cout << fixed << right << setw(12) << setprecision(7) << rms << endl;
cout << " Max Residual Error                 = " ;
cout << fixed << right << setw(12) << setprecision(7) << max_err << endl;

return;
}

//-----
// Plot uniform scale statistics
//-----
// ang = min_angle + avg_delta * offFactor ;
// ang += (avg_delta / resFactor);
//-----
void Angles::plot_uscale_statistics ( )
{
    int i, j;
    double resFactor, offFactor;
    ofstream myout;

    cout << "* plot_uscale_statistics ... ";
    if (Leaf) cout << "(LeafAngles Resolution)" << endl;
    else cout << "(AllAngles Resolution)" << endl;

    if (nIter > 10) {
        cout << "nIter = " << nIter << " is too large to plot! " << endl;
        return;
    }
}

```

```

// ssr : sum of the squares of the residuals
// mse : mean squared error
// rms : root mean square error
// sr : square error of a data point
// max_err : maximum of squared errors

int M=4; // no of resFactor's
int N=4; // no of offFactor's
double SSR[M][N];

for (i=0; i<M; i++) {
    resFactor = i + 1.0;

    for (j=0; j<N; j++) {
        offFactor = (j+1) / N;

        cout << " ===== resFactor= " << i << ", offFactor= " << j ;
        cout << " =====" << endl;

        calc_uscale_statistics(resFactor, offFactor);

        SSR[i][j] = ssr;
    }
}

// writing residue errors
myout.open("angle.dat");

for (i=0; i<M; i++) {
    cout << i+1 << " ";
    myout << i+1 << " ";
    for (j=0; j<N; j++) {
        cout << SSR[i][j] << " ";
        myout << SSR[i][j] << " ";
    }
    cout << endl;
    myout << endl;
}
myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set terminal emf" << endl;
myout << "set autoscale y" << endl;
if (Leaf) {
    myout << "set output 'eg09.resfac_ssR_leaf.emf'" << endl;
    myout << "set title \"resFactor-SSR Plot (Leaf)\"" << endl;
} else {
    myout << "set output 'eg09.resfac_ssR_all.emf'" << endl;
    myout << "set title \"resFactor-SSR Plot (All)\"" << endl;
}
myout << "set xlabel \"resFactor\" " << endl;
myout << "set ylabel \"SSR (Sum of Squared Residuals)\" " << endl;
myout << "plot " ;
for (j=0; j<N; j++) {
    myout << "'angle.dat' using 1:" << j+2 ;
    myout << " title 'offFactor=" << (j+1) << "/" << N << "' ";
    myout << " with linespoints" ;
    if (j<N-1) myout << ", "; else myout << endl;
}

myout << "pause mouse keypress" << endl;
myout.close();

```

```

system("gnuplot command.gp");

// writing residue errors
myout.open("angle.dat");

for (j=0; j<N; j++) {
    cout << j+1 << " ";
    myout << j+1 << " ";
    for (i=0; i<M; i++) {
        cout << SSR[i][j] << " ";
        myout << SSR[i][j] << " ";
    }
    cout << endl;
    myout << endl;
}
myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set terminal emf" << endl;
myout << "set autoscale y" << endl;
myout << "set autoscale y" << endl;
if (Leaf) {
    myout << "set output 'eg10.offfac_ssR_leaf.emf'" << endl;
    myout << "set title \"offFactor-SSR Plot (Leaf) \" " << endl;
} else {
    myout << "set output 'eg10.offfac_ssR_all.emf'" << endl;
    myout << "set title \"offFactor-SSR Plot (All) \" " << endl;
}
myout << "set xlabel \"offFactor\" " << endl;
myout << "set ylabel \"SSR (Sum of Squared Residuals)\" " << endl;
myout << "plot " ;
for (i=0; i<M; i++) {
    myout << "'angle.dat' using 1:" << i+2 ;
    myout << " title 'resFactor=' << (i+1) << " ";
    myout << " with linespoints" ;
    if (i<M-1) myout << ", " ; else myout << endl;
}

myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

return;
}

//-----
// Plot residual errors on the uniform scale
//-----
// ang = min_angle + avg_delta * offFactor ;
// ang += (avg_delta / resFactor);
//-----
void Angles::plot_uscale_residual_errors
(double resFactor, double offFactor )
{

```

```

int n;
double x, y, z;
ofstream myout;

cout << "* plot_uscale_residual_errors ... ";
if (Leaf) cout << "(LeafAngles Resolution)" << endl;
else cout << "(AllAngles Resolution)" << endl;

if (nIter > 10) {
    cout << "nIter = " << nIter << " is too large to plot! " << endl;
    return;
}

double ang = min_angle + avg_delta * offFactor ;
double se = 0.0 ;
int nBreak =0;
n = 0;

// writing residue errors
myout.open("angle.dat");

while (ang < max_angle) {
    x = 1 / K;
    y = 0.0;
    z = ang;

    cordic(&x, &y, &z, nIter, &nBreak, n, threshold);

    se = (z * z);

    // cout << fixed << right << setw(10) << setprecision(7) << A[i];
    // cout << fixed << right << setw(10) << setprecision(7) << z << endl;

    myout << fixed << right << setw(10) << n;
    myout << fixed << right << setw(22) << setprecision(7) << ang;
    myout << fixed << right << setw(22) << setprecision(7) << z;
    myout << fixed << right << setw(22) << setprecision(7) << se << endl;

    ang += (avg_delta / resFactor);
    n++;
}

cout << " Angles = (" ;
cout << min_angle << " : " << avg_delta << " : " << max_angle << ")" ;
cout << endl << " --> total " << n << " points" ;
cout << " (nBreak = " << nBreak << " : " ;
cout << 100. * nBreak / n << " % )" << endl;

myout.close();

// writing gnuplot commands
myout.open("command.gp");
myout << "set autoscale y" << endl;
myout << "set terminal emf" << endl;
if (Leaf) {
    myout << "set output 'eg11.idx_res_us_leaf.emf'" << endl;
    myout << "set title \"Index-Residual Plot (uScale-Leaf)\"" << endl;
} else {
    myout << "set output 'eg11.idx_res_us_all.emf'" << endl;
    myout << "set title \"Index-Residual Plot (uScale-All)\"" << endl;
}
myout << "set xlabel \"Index\" " << endl;
myout << "set ylabel \"Residuals\" " << endl;
myout << "plot 'angle.dat' using 1:3 with linespoints " << endl;

```

```

myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

// writing gnuplot commands
myout.open("command.gp");
myout << "set autoscale y" << endl;
myout << "set terminal emf" << endl;
if (Leaf) {
    myout << "set output 'eg12.ang_res_us_leaf.emf'" << endl;
    myout << "set title \"Angle-Residual Plot (uScale-Leaf)\"" << endl;
} else {
    myout << "set output 'eg12.ang_res_us_all.emf'" << endl;
    myout << "set title \"Angle-Residual Plot (uScale-All)\"" << endl;
}
myout << "set xlabel \"Angle\" " << endl;
myout << "set ylabel \"Residuals\" " << endl;
myout << "plot 'angle.dat' using 2:3 with linespoints " << endl;
myout << "pause mouse keypress" << endl;
myout.close();

system("gnuplot command.gp");

return;

}

void Angles::plot_uscale_residual_errors ()
{
    plot_uscale_residual_errors (1.0, 1.0);
}

*****  

for (i=0; i<20; i+=4) {
    for (j=0; j<4; ++j) {
        r = atan( 1. / (1 << (i+j)) ) / atan( 1. / (1 << i) ) * 100;
        cout << "index = " << i+j << " --> r = " << r << endl;
    }
}

return 0;
}
*****
```

```
:::::::::::  
Angles_tb.cpp  
:::::::::::  
# include <cstdlib>  
# include <cmath>  
# include <iostream>  
# include <iomanip>  
# include <fstream>
```

```

using namespace std;

# include "cordic.hpp"
# include "Angles.hpp"

//-----
// Purpose:
//
//   Explore Angles Space using Class Angles
//
// Discussion:
//
//
// Licensing:
//
//   This code is distributed under the GNU LGPL license.
//
// Modified:
//
//   2012.05.11
//
//
// Author:
//
//   Young Won Lim
//
// Parameters:
//
//-----

```

```

int main (int argc, char * argv[])
{
    // -----
    // nIter   : Number of Iteration = Height of binary angle tree
    // nAngle  : Number of Angles   = Number of Leaf Nodes
    //
    int     nIter = 3;
    int     nAngle = 1 << nIter;

    if (argc > 1 ) {
        nIter = atoi(argv[1]);
        nAngle = 1 << nIter;
    }

    // cout << "nIter = " << nIter << endl;
    // cout << "nAngle = " << nAngle << endl;

    // -----
    // A   : contains the angles of leaf nodes in binary angle tree
    // All : contains the angles of all nodes in binary angle tree
    //
    double *A, *All;
    int      level, leaves;
    int      i, j, k;

    A = (double *) malloc ((1<<nIter) * sizeof (double));
    All = (double *) malloc (2* (1<<nIter) * sizeof (double));

    for (j=0; j<nAngle; ++j) {
        A[j] = compute_angle(j, nIter);
        // cout << "A[" << j << "]=" << setw(12) << setprecision(8) << A[j] << endl;
    }

    for (i=0, k=0; i<=nIter; ++i) {

```

```

level = i;
leaves = 1 << level;

// cout << "level = " << level << "leaves = " << leaves << endl;

for (j=0; j<leaves; ++j) {
    All[j+k] = compute_angle(j, level);
    // cout << "All[" << j+k << "] = " << All[j+k] << endl;
}

k += leaves;
}

-----
// LeafAngles : Angles Class for leaf nodes only
// AllAngles : Angles Class for all nodes (internal nodes included)
-----
Angles LeafAngles(A, nIter, nAngle);
Angles AllAngles(All, nIter, 2*nAngle-1);

-----
// Plot Binary Angle Tree
-----
draw_angle_tree (nIter, nAngle);

-----
// Plot angle vectors on a unit circle
-----
LeafAngles.plot_circle_angle();
AllAngles.plot_circle_angle();

-----
// Plot angle vectors on a linear scale
-----
LeafAngles.plot_line_angle();
AllAngles.plot_line_angle();

LeafAngles.setThreshold(0.0);
AllAngles.setThreshold(0.0);

-----
// Find Angles Statistics --> member data
-----
LeafAngles.calc_statistics();
AllAngles.calc_statistics();

-----
// Plot Delta Distribution & Angle-Delta
-----
LeafAngles.plot_statistics();
AllAngles.plot_statistics();

-----
// plot residual errors
// Residuals-Angle Plot & Residuals-Index Plot
-----
LeafAngles.plot_residual_errors();
AllAngles.plot_residual_errors();

-----
// Calculate Uniform Scale Statistics --> member data
-----
LeafAngles.calc_uscale_statistics(1.0, 1.0);

```

```

AllAngles.calc_uscale_statistics(1.0, 1.0);

// -----
// Plot Uniform Scale Statistics
// -----
LeafAngles.plot_uscale_statistics();
AllAngles.plot_uscale_statistics();

// -----
// Plot residue errors at the leaf node angles
// -----
LeafAngles.plot_uscale_residual_errors(1, 2);
AllAngles.plot_uscale_residual_errors(1, 2);

return 0;
}

::::::::::::::::::
cordic.hpp
::::::::::::::::::
void cordic ( double *x, double *y, double *z, int n, int *, int, double =0.0 );
::::::::::::::::::
cordic.cpp
::::::::::::::::::
#include <cstdlib>
#include <iostream>
#include <iomanip>
#include <cmath>
#include <ctime>

using namespace std;

#include "cordic.hpp"

//*****80
void cordic ( double *x, double *y, double *z, int n,
    int *nBreak, int nBreakInit, double threshold)

//*****80
// CORDIC returns the sine and cosine using the CORDIC method.
//
// Licensing:
//
// This code is distributed under the GNU LGPL license.
//
// Modified:
//
// 2012.04.17
//
// Author:
//
// Based on MATLAB code in a Wikipedia article.
//
// Modifications by John Burkardt
```

```

// Further modified by Young W. Lim
// Parameters:
// Input:
//   *x: x coord of an init vector
//   *y: y coord of an init vector
//   *z: angle (-90 <= angle <= +90)
//   n: number of iteration
//     A value of 10 is low. Good accuracy is achieved
//     with 20 or more iterations.
//
// Output:
//   *xo: x coord of a final vector
//   *yo: y coord of a final vector
//   *zo: angle residue
//
// Local Parameters:
// Local, real ANGLES(60) = arctan ( (1/2)^{0:59} );
// Local, real KPROD(33), KPROD(j) = product ( 0 <= i <= j ) K(i),
// K(i) = 1 / sqrt ( 1 + (1/2)^{2i} ).
//
{
#define ANGLES_LENGTH 60
#define KPROD_LENGTH 33

double angle;
double angles[ANGLES_LENGTH] = {
    7.8539816339744830962E-01,
    4.6364760900080611621E-01,
    2.4497866312686415417E-01,
    1.2435499454676143503E-01,
    6.2418809995957348474E-02,
    3.1239833430268276254E-02,
    1.5623728620476830803E-02,
    7.8123410601011112965E-03,
    3.9062301319669718276E-03,
    1.9531225164788186851E-03,
    9.7656218955931943040E-04,
    4.8828121119489827547E-04,
    2.4414062014936176402E-04,
    1.2207031189367020424E-04,
    6.1035156174208775022E-05,
    3.0517578115526096862E-05,
    1.5258789061315762107E-05,
    7.6293945311019702634E-06,
    3.8146972656064962829E-06,
    1.9073486328101870354E-06,
    9.5367431640596087942E-07,
    4.7683715820308885993E-07,
    2.3841857910155798249E-07,
    1.1920928955078068531E-07,
    5.9604644775390554414E-08,
    2.9802322387695303677E-08,
    1.4901161193847655147E-08,
    7.4505805969238279871E-09,
    3.7252902984619140453E-09,
    1.8626451492309570291E-09,
    9.3132257461547851536E-10,
    4.6566128730773925778E-10,
    2.3283064365386962890E-10,
    1.1641532182693481445E-10,
    5.8207660913467407226E-11,
    2.9103830456733703613E-11,
    1.4551915228366851807E-11,
    7.2759576141834259033E-12,
}

```

```

3.6379788070917129517E-12,
1.8189894035458564758E-12,
9.0949470177292823792E-13,
4.5474735088646411896E-13,
2.2737367544323205948E-13,
1.1368683772161602974E-13,
5.684341880808014870E-14,
2.8421709430404007435E-14,
1.4210854715202003717E-14,
7.1054273576010018587E-15,
3.5527136788005009294E-15,
1.7763568394002504647E-15,
8.8817841970012523234E-16,
4.4408920985006261617E-16,
2.2204460492503130808E-16,
1.1102230246251565404E-16,
5.5511151231257827021E-17,
2.7755575615628913511E-17,
1.3877787807814456755E-17,
6.9388939039072283776E-18,
3.4694469519536141888E-18,
1.7347234759768070944E-18 };

double c2;
double factor;
int j;
double kprod[KPROD_LENGTH] = {
    0.70710678118654752440,
    0.63245553203367586640,
    0.61357199107789634961,
    0.60883391251775242102,
    0.60764825625616820093,
    0.60735177014129595905,
    0.60727764409352599905,
    0.60725911229889273006,
    0.60725447933256232972,
    0.60725332108987516334,
    0.60725303152913433540,
    0.60725295913894481363,
    0.60725294104139716351,
    0.60725293651701023413,
    0.60725293538591350073,
    0.60725293510313931731,
    0.60725293503244577146,
    0.60725293501477238499,
    0.60725293501035403837,
    0.60725293500924945172,
    0.60725293500897330506,
    0.60725293500890426839,
    0.60725293500888700922,
    0.60725293500888269443,
    0.60725293500888161574,
    0.60725293500888134606,
    0.60725293500888127864,
    0.60725293500888126179,
    0.60725293500888125757,
    0.60725293500888125652,
    0.60725293500888125626,
    0.60725293500888125619,
    0.60725293500888125617 };
double pi = 3.141592653589793;
double poweroftwo;
double s2;
double sigma;
double sign_factor;
double theta;

double xn, yn;

//
```

```

// Initialize loop variables:
// theta = *z;

xn = *x;
yn = *y;

poweroftwo = 1.0;
angle = angles[0];

angle = atan( 1. );

//
// Iterations
//

for ( j = 1; j <= n; j++ )
{
    if ( theta < 0.0 )
    {
        sigma = -1.0;
    }
    else
    {
        sigma = 1.0;
    }

    //
    // scaling factor is not yet corrected
    //

    static int cntBreak = 0;
    if (nBreakInit == 0) cntBreak = 0;
    if (abs(*z) < threshold) {
        *nBreak = ++cntBreak;

        // cout << "cntBreak= " << cntBreak;
        // cout << " z= " << *z;
        // cout << " < " << threshold << endl;
        break;
    }

    factor = sigma * poweroftwo;

    *x = xn - factor * yn;
    *y = factor * xn + yn;

    xn = *x;
    yn = *y;
}

//
// Update the remaining angle.
//
theta = theta - sigma * angle;

poweroftwo = poweroftwo / 2.0;

//
// Update the angle from table, or eventually by just dividing by two.
//
if ( ANGLES_LENGTH < j + 1 )
{
    angle = angle / 2.0;
}
else
{
    angle = angles[j];
}

angle = atan( 1. / (1 << j));

*z = theta;

```

```
}

// Adjust length of output vector to be [cos(beta), sin(beta)]
// KPROD is essentially constant after a certain point, so if N is
// large, just take the last available value.
//
// if ( 0 < n )
//{
//    *c = *c * kprod [ i4_min ( n, KPROD_LENGTH ) - 1 ];
//    *s = *s * kprod [ i4_min ( n, KPROD_LENGTH ) - 1 ];
//}
//
// Adjust for possible sign change because angle was originally
// not in quadrant 1 or 4.
//
// *c = sign_factor * *c;
// *s = sign_factor * *s;

return;
# undef ANGLES_LENGTH
# undef KPROD_LENGTH
}
```